INTRA-CLASS MIXUP FOR OUT-OF-DISTRIBUTION DETECTION

ABSTRACT

Deep neural networks have found widespread adoption in solving image recognition and natural language processing tasks. However, they make confident mispredictions when presented with data that does not belong to the training distribution, i.e. out-of-distribution (OoD) samples. Inter-class mixup has been shown to improve model calibration aiding OoD detection. However, we show that both empirical risk minimization and inter-class mixup create large angular spread in latent representation. This reduces the separability of in-distribution data from OoD data. In this paper we propose *intra-class mixup* supplemented with *angular margin* to improve OoD detection. Angular margin is the angle between the decision boundary normal and sample representation. We show that intra-class mixup forces the network to learn representations with low angular spread in the latent space. This improves the separability of OoD from in-distribution examples. Our approach when applied to various existing OoD detection techniques shows an improvement of **4.68%** and **6.38%** in AUROC performance over empirical risk minimization and inter-class mixup, respectively. Further, our approach aided with angular margin improves AUROC performance by **7.36%** and **9.10%** over empirical risk minimization and inter-class mixup, respectively.

1 INTRODUCTION

Deep Learning has been employed by many state of the art machine learning models to effectively solve image recognition Krizhevsky et al. (2012); LeCun et al. (2015) and natural language processing Andor et al. (2016) tasks. Despite their effectiveness, recent research has shown the existence of inputs Goodfellow et al. (2015b); Nguyen et al. (2015) that lead these networks to make confident mispredictions. Two classes of such inputs have emerged in literature. The first class, adversarial examples Bruna et al. (2014); Goodfellow et al. (2015a); Kurakin et al. (2017), are specifically crafted inputs with the intent of fooling deep neural nets. The second class dubbed Out-of-Distribution (OoD) Nguyen et al. (2015) examples are examples that do not belong to the underlying true distribution that the training dataset is drawn from. High confidence of the networks on such OoD examples makes it difficult to identify false classifications and poses a challenge to their deployment in safety critical scenarios Amodei et al. (2016), from medical diagnosis to self driving applications.

To address this problem several methods have been proposed which aim to identify out-of-distribution samples. In the context of deep learning, OoD detection methods can be broadly classified into two categories, generative and discriminative methods. Generative methods use various techniques such as Gaussian Discriminant Analysis Lee et al. (2018b), Generative Adversarial Networks (GANs) Deecke et al. (2018); Lee et al. (2018a); Ren et al. (2019) or more generic generative methods Wang et al. (2017) to model the underlying distribution and separate in-distribution samples from OoD samples. On the other hand, discriminative methods Hendrycks & Gimpel (2017); Hendrycks et al. (2019); Hsu et al. (2020); Liang et al. (2018); Liu et al. (2020) detect OoD samples based on measures such as softmax probability Hendrycks & Gimpel (2017); Hendrycks et al. (2019), energy scores Liu et al. (2020) or other metrics computed from the trained network. Most of these metrics are a proxy for the distance of the sample representation from the decision boundary (l_2 margin in Figure 1a). Further, we show that existing techniques such as empirical risk minimization (ERM) and inter-class mixup Zhang et al. (2018) result in networks learning representations that have large spread. This large spread creates broad overlapping representations for in-distribution and OoD data, making it hard to separate in-distribution data from OoD data. Additionally, the use of metrics that are proxies

for distance from decision boundary have a disadvantage when OoD points have similar margin as in-distribution data. For example, consider point "(b) OoD" in Figure 1a where the OoD data point is far from the class representation and has similar l_2 margin as in-distribution data; this OoD point will have similar OoD metric scores as in-distribution data. Using angular margin would help separate OoD data in such a case. To account for these factors, we propose intra-class mixup supplemented with angular margin (refer to Figure 1a) to improve OoD detection where angular margin is the angle between the normal to the decision boundary and the sample representation.

(a) Visualizing angular margin θ and l_2 margin

(b) Intra-class mixup

(c) Inter-class mixup

(d) ERM

Figure 1: Visualizing improved OoD separability of intra-class mixup trained ResNet18 model. SVHN was the in-distribution dataset and TinyImageNet was used as OoD dataset. For all the representations un-mixed inputs were used.

We show that the proposed intra-class mixup forces the network to learn latent representations with low variance (i.e. small spread), thus improving in-distribution and OoD separability. This is visualized in Figure 1, which plots the angular margin vs. l_2 margin for in-distribution and OoD data for ERM, inter-class mixup and intra-class mixup. Further, we show that intra-class mixup trained, angular margin augmented OoD detector achieves on average **7.36%** and **9.10%** improvement in AUROC performance over ERM and inter-class mixup, respectively.

In summary the contributions of this paper are as follows:

- We propose *intra-class mixup* to improve OoD detection. We show that intra-class mixup learnt latent space representations have lower angular spread when compared to ERM and inter-class mixup, thus, improving separability of OoD examples. We attribute this to the reduced input variance resulting from intra-class mixup.

- We show existing discriminiative OoD detection methods that use proxies for distance from the decision boundary benefit from intra-class mixup when compared to ERM and inter-class mixup.

- We leverage better angular separability to improve OoD detection. We show that supplementing angular margin with existing OoD detection scores improves OoD detection performance on various existing techniques.

2 RELATED WORK

In the context of deep-learning, the approaches to detect OoD examples can be broadly classified into two categories discriminative and generative methods. Under discriminative methods recent works Hendrycks & Gimpel (2017); Hendrycks et al. (2019); Hsu et al. (2020); Liang et al. (2018) have leveraged softmax probability scores to detect anomalous examples. The authors of Hendrycks & Gimpel (2017) presented their results on using softmax scores to detect OoD examples on several machine learning tasks. The idea of utilizing softmax scores was further extended in Hendrycks et al. (2019) by modifying the standard loss function used to train the classifier. The network was trained on an in-distribution dataset as well as an additional auxiliary or outlier dataset. The authors claim that such outlier exposure enables the detector to generalize and detect unseen anomalies. Further, the authors also observed characteristic properties of the auxiliary dataset which help improve detection performance. Another approach that leverages softmax scores are the ODIN Hsu et al. (2020); Liang et al. (2018) techniques, which showed improvement to OoD detection without having to explicitly tune the out-of-distribution dataset which the authors argue is generally hard to define *a priori*. The authors proposed decomposing the confidence score and modifying the input pre-processing method. Other recent work under the discriminative techniques proposed the use of energy score Liu et al. (2020) instead of softmax scores arguing that softmax based approaches suffer from overconfident posterior distributions for out-of-distribution samples. They claim that energy scores are theoretically aligned with the probability density of the inputs and is therefore less likely to result in overconfident predictions.

Generative methods attempt to model the underlying true distribution and hence, identify samples outside the modelled distribution. The authors of Lee et al. (2018b) proposed a technique that modelled a class conditional Gaussian distribution with respect to features of the deep network and used a Mahalanobis distance based confidence score calculated from the Gaussian model to detect OoD examples. In Lee et al. (2018a) the authors proposed the use of Generative Adversarial Networks (GANs) Goodfellow et al. (2014) to generate OoD samples to improve OoD detector training. They proposed two additional loss terms that were added to the original loss function. One of the proposed terms forced the classifier to be less confident on OoD samples while the other helped generate more effective OoD examples. Another work that investigated a generative model based approach for OoD detection was Ren et al. (2019) which proposed a likelihood ratio method which corrected for background statistics and achieved competitive performance on vision and sequence classification tasks. Approaches under both categories have focused on networks trained using Empirical Risk Minimization (ERM) which has been observed to result in undesirable behaviors such as memorization Zhang et al. (2016) and sensitivity outside the training examples Bruna et al. (2014). Inter-class mixup Zhang et al. (2018) has been shown to be effective against such undesirable behaviours Zhang et al. (2018); Thulasidasan et al. (2019) and has been shown to improve calibration and OoD performance Thulasidasan et al. (2019). However, we show that inter-class mixup and ERM trained networks learn representations with large variance (i.e. large spread), impacting their OoD detection performance. To counter this effect, in this paper we propose intra-class mixup aided with angular margin for improving OoD detection.

3 BACKGROUND

In-distribution. The training and testing samples used for a machine learning task are drawn from some underlying distribution, also called the true distribution. The samples from this underlying true distribution are called in-distribution samples and are represented by D_{in} in this work. However, in most practical learning scenarios the true distribution is unknown *a priori* and hence, the training distribution, D_{train}, is used as a proxy for D_{in}.

Out-of-distribution. A sample is said to be Out-of-distribution (OoD) if it does not belong to the underlying true distribution D_{in}, and is denoted by D_{out}. Since we do not have access to the true underlying distribution, for our experiments we use uniform noise, Gaussian noise and samples from other datasets for similar tasks as a proxy for Out-of-distribution samples or D_{out}. This is common practice in literature Hendrycks & Gimpel (2017); Hendrycks et al. (2019); Hsu et al. (2020); Lee et al. (2018b); Liang et al. (2018).

Empirical Risk Minimization (ERM). The objective of learning algorithms, when the true underlying distribution is known, is to learn an optimal mapping $f(.)$ from the input $\boldsymbol{x}$ to an output y, where $(\boldsymbol{x}, y) \sim D_{in}$. This objective is satisfied by learning a function $f(.)$ that minimizes a loss function $\mathcal{L}(f(\boldsymbol{x}), y)$ over the entire distribution. We can compute the expectation of the loss function as shown in Equation 1. This is know as expected risk.

$$R_{expected} \quad = E_{\boldsymbol{x}, y \sim D_{in}}[L(f(\boldsymbol{x}), y)] \tag{1}$$

As in most realistic scenarios, we do not have access to the true data distribution, and hence, it is common to use available empirical data as proposed in Vapnik (1998) to approximate the expected risk. This form of approximation, presented in Equation 2, is know as Empirical Risk Minimization (ERM).

$$R_{empirical} \quad = \frac{1}{N_e} \sum_{i=1}^{N_e} \mathcal{L}(f(\boldsymbol{x}_i), y_i) \tag{2}$$

where $(\boldsymbol{x}_i, y_i) \sim D_{train}$ and N_e is the number of training samples in D_{train}.

4 METHODOLOGY

4.1 ANGULAR MARGIN

In this subsection we define angular margin. Angular margin θ can be described by the following equations:

$$\boldsymbol{n} = \frac{W_c^{\hat{y}}}{|W_c^{\hat{y}}|} \tag{3}$$

$$\theta = arccos\left(\frac{\boldsymbol{a}_{inp}}{|\boldsymbol{a}_{inp}|} \cdot \boldsymbol{n}\right) \tag{4}$$

where $W_c^{\hat{y}}$ is the weight vector of the final (classifier) layer of the deep neural net (DNN) for the predicted class $\hat{y}$, $\boldsymbol{n}$ is the unit vector orthogonal to the decision boundary, $\boldsymbol{a}_{inp}$ is the latent space vector representation for the un-mixed input (i.e. activations of the penultimate layer of the DNN).

4.2 INTRA-CLASS MIXUP

In this subsection we explore the properties of intra-class mixup trained deep neural nets and how they can be leveraged to improve OoD detection performance. Inter-class mixup Zhang et al. (2018) is a technique that helps improve the generalization of a machine learning classifier. Mixup trains a neural net on a convex combinations of examples and their corresponding soft labels. Consider a pair of training input, label tuples $(\boldsymbol{x}_i, y_i)$ and $(\boldsymbol{x}_j, y_j)$. Inter-class mixup obtains a new augmented sample $(\hat{\boldsymbol{x}}, \hat{y})$ for training the classifier described by Equation 5.

$$\begin{aligned} \hat{\boldsymbol{x}} &= \lambda \cdot \boldsymbol{x}_i + (1 - \lambda) \cdot \boldsymbol{x}_j \\ \hat{y} &= \lambda \cdot y_i + (1 - \lambda) \cdot y_j \end{aligned} \tag{5}$$

where, $\lambda \in [0, 1]$ represents the mixing parameter. Such an augmentation scheme forces the model to learn smooth interpolations between the samples of the training dataset. The proposed technique of intra-class mixup imposes an additional constraint on Equation 5 such that $\hat{y} = y_i = y_j$, forcing the training sample to be a convex combination of inputs within the same class. It can be shown that the additional constraint on $\hat{y}$ reduces the class conditional input variance (see Appendix A.1).

$$\sigma_{\hat{X}}^2 = \left[\lambda^2 + (1 - \lambda)^2\right] \sigma_X^2$$

$$\text{Since } \lambda^2 + (1 - \lambda)^2 \leq 1 \tag{6}$$

$$\sigma_{\hat{X}}^2 \leq \sigma_X^2$$

where $\sigma_{\hat{X}}^2$ is the variance of the input after mixup and σ_X^2 is the variance of the input prior to mixup.

Therefore intra-class mixup results in reduction of class conditional variance at the input. We observe that deep neural nets trained on intra-class mixup learn to represent even unmixed images with lower angular spread (i.e. reduction of the class conditional representation variance) compared to ERM or inter-class mixup. The angular spread refers to the standard deviation of the angular margin for a given dataset. This reduced angular spread increases the angular margin between in-distribution and OoD samples improving OoD detection performance.

4.3 Supplementing Angular Margin

In this subsection we describe how angular margin scores can be supplemented with various OoD scores to improve detection performance. The supplemented OoD score J_s is given by

$$J_s = J + Cos\left(\theta\right) \tag{7}$$

where J is the OoD score from a detector of choice, θ is the angular margin of the test sample described in Equation 4. The OoD score J is different for different detection schemes. For MSP (Hendrycks & Gimpel (2017)) J would be the softmax probability of the predicted class while J would be the energy score (Liu et al. (2020)) when using energy score detector, and so on. The following section details various experiments to evaluate the performance of the proposed method.

5 Experiments

We perform experiments which aim to understand and show the role of intra-class mixup in improving OoD detection performance. The experiments' goals are summarized below

- To show intra-class mixup trained networks learn representations that have lower angular spread and improved angular separability (Section 5.1).
- To show intra-class mixup improves OoD detection on methods that use distance proxies (Section 5.2).
- To show that supplemental use of angular margin improves OoD detection performance (Section 5.3).

5.1 Separability

In this section we provide evidence for improved OoD separability resulting from *intra-class mixup*. To show that intra-class mixup improves OoD separability we evaluate the angular margin for in-distribution and OoD examples. The improvement in separability resulting from intra-class mixup can be observed using a separability metric S given by

$$S = \frac{(\theta_o - \theta_i)^2}{\sigma_o^2 + \sigma_i^2} \tag{8}$$

where θ_o and θ_i are the angular margins for OoD data and in-distribution data respectively, σ_o and σ_i are the angular scatter/spread (i.e. standard deviation) of the angular margin. The metric S is the angular version of the Fisher's criterion Fisher et al. (1936).

Table 1 shows the angular separability of empirical risk minimization (ERM), inter-class mixup (Zhang et al. (2018)) and the proposed intra-class mixup. From Table 1 we clearly see improved OoD separability from intra-class mixup. For each in-distribution dataset in Table 1, the numbers show the average angular margin and angular spread computed over 5 differently seeded ResNet18 networks evaluated on the test set of SVHN (Netzer et al. (2011)), CIFAR-10, CIFAR-100 (Krizhevsky et al. (2009)), Places365 (Zhou et al. (2017)), Textures (Cimpoi et al. (2014)), LSUN (Yu et al. (2015)), TinyImageNet (Li et al.), Gaussian Noise and Uniform Noise as OoD datasets.

5.2 Intra-class Mixup for OoD detection

We have seen in the previous subsection that intra-class mixup improves OoD separability. In this subsection we provide evidence for improved OoD detection performance of intra-class mixup trained DNNs. We present the results of applying intra-class mixup on a few unsupervised methods that

In-Dist	Average OoD Angular Margin (in rad) $\theta_o \pm \sigma_o$			Average In-Dist. Angular Margin (in rad) $\theta_i \pm \sigma_i$			Angular Separability $\dfrac{(\theta_o - \theta_i)^2}{\sigma_o^2 + \sigma_i^2}$		
	ERM	Inter	Intra	ERM	Inter	Intra	ERM	Inter	Intra
CIFAR-10	1.4262 ± 0.0587	1.2992 ± 0.0585	1.4534 ± 0.0478	1.2901 ± 0.0779	1.1977 ± 0.0480	1.3065 ± 0.0730	1.9469	1.7991	**2.8342**
CIFAR-100	1.4481 ± 0.0474	1.2991 ± 0.0553	1.4819 ± 0.0426	1.3817 ± 0.0929	1.1942 ± 0.1017	1.4012 ± 0.0839	0.4053	**0.8211**	0.7355
SVHN	1.1810 ± 0.1174	1.2351 ± 0.0937	1.2626 ± 0.0952	0.8815 ± 0.1180	1.0501 ± 0.0596	0.9748 ± 0.1067	3.2375	2.7753	**4.0507**
TinyImageNet	1.1344 ± 0.1008	1.2990 ± 0.0444	1.2322 ± 0.0654	1.0931 ± 0.1623	1.2952 ± 0.0736	1.1955 ± 0.1146	0.0467	0.0020	**0.0774**

Table 1: Separability of intra-class mixup, inter-class mixup and ERM trained models (averaged over 5 different seeds) on various datasets. Intra-class mixup has consistently has better separability.

	Predicted Positive	**Predicted Negative**
Actual Positive	True Positive (TP)	False Negative (FN)
Actual Negative	False Positive (FP)	True Negative (TN)

Table 2: Confusion Matrix of true label against predicted label

use proxies for distance from the decision boundary such as Maximum Softmax Probability (MSP) detection Hendrycks & Gimpel (2017), ODIN Liang et al. (2018) and energy score detection Liu et al. (2020). To evaluate the performance of the detectors we use a variety of metrics which are briefly described in the following section.

Metrics. The performance of binary classification algorithm can be evaluated using Recall or True Positive Rate (TPR), False Positive Rate (FPR), Precision or a variety of other metrics. Recall (TPR), FPR and Precision are defined by equations (9), (10) and (11) respectively.

$$\text{Recall = True Positive Rate (TPR)} \quad = \frac{TP}{TP + FN} \tag{9}$$

$$\text{False Positive Rate (FPR)} \quad = \frac{FP}{FP + TN} \tag{10}$$

$$\text{Precision} \quad = \frac{TP}{TP + FP} \tag{11}$$

where, True Positive (TP), False Positive (FP), True Negative (TN) and False Negative (FN) are defined in Table 2. Metrics commonly used in literature Hendrycks & Gimpel (2017); Hendrycks et al. (2019); Lee et al. (2018b) to evaluate the performance of OoD detectors are:

- **AUROC**: The Receiver Operating Characteristic (ROC), the plot of the True Positive Rate (TPR) against the False Positive Rate (FPR). The area under the ROC is called Area Under the Receiver Operating Characteristic (AUROC). AUROC of 1 denotes an ideal detection scheme, since the ideal detection algorithm results in 0 false positive and false negative samples.
- **AUPRC**: The Precision Recall Characteristic (PRC), the plot of the Precision against the Recall. The area under the PR is called AUPRC and should similarly be 1 for a ideal detection scheme.

Dataset	Accuracy		
	ERM	Inter	Intra
CIFAR-10	92.90 ± 0.27	94.32 ± 0.29	93.90 ± 0.34
CIFAR-100	71.62 ± 0.18	76.51 ± 0.28	72.28 ± 0.48
SVHN	95.69 ± 0.16	96.42 ± 0.04	95.91 ± 0.11
TinyImageNet	32.80 ± 0.17	34.04 ± 0.68	34.63 ± 0.30

Table 3: Baseline accuracies (mean $\pm$ std. averaged over 5 seeds) of ERM, inter-class and intra-class mixup trained models on various datasets.

- **FPR at TPR of 95% (FPR95)**: denotes the FPR when the TPR is 95%. Lower value of FPR at TPR of 95% indicates a better classifier.

To evaluate the effect of intra-class mixup on existing OoD detection techniques, we trained 5 differently seeded models each with ERM, inter-class mixup and intra-class mixup. We trained ResNet18 He et al. (2016) networks on CIFAR-10, CIFAR-100, SVHN and TinyImageNet datasets till convergence (baseline accuracies are presented in Table 3). The training procedure used the SGD optimizer with a momentum of 0.9 and weight decay of 5×10^{-4}. The training used a 90%-10% training-validation split with the initial learning rate set to 10^{-2} and it was scaled down by a factor of 10 at 60% and 80% completion using a learning rate scheduler.

Tech.	In-Dist.	AUROC ↑			AUPR ↑			FPR95 ↓		
		ERM	Inter	Intra	ERM	Inter	Intra	ERM	Inter	Intra
MSP	CF-10	0.823 ± 0.054	0.884 ± 0.042	$\mathbf{0.884 \pm 0.037}$	0.780 ± 0.111	$\mathbf{0.859 \pm 0.084}$	0.819 ± 0.113	0.608 ± 0.111	0.504 ± 0.244	$\mathbf{0.303 \pm 0.096}$
	CF-100	0.664 ± 0.168	$\mathbf{0.773 \pm 0.050}$	0.724 ± 0.020	0.620 ± 0.199	$\mathbf{0.701 \pm 0.162}$	0.651 ± 0.170	0.658 ± 0.130	$\mathbf{0.555 \pm 0.179}$	0.608 ± 0.109
	SVHN	0.923 ± 0.007	0.888 ± 0.062	$\mathbf{0.900 \pm 0.036}$	0.761 ± 0.109	$\mathbf{0.783 \pm 0.106}$	0.719 ± 0.126	0.266 ± 0.044	0.495 ± 0.197	$\mathbf{0.338 \pm 0.095}$
	TIN	0.551 ± 0.110	0.527 ± 0.083	$\mathbf{0.581 \pm 0.120}$	0.527 ± 0.199	0.514 ± 0.190	$\mathbf{0.560 \pm 0.206}$	0.826 ± 0.066	0.825 ± 0.050	$\mathbf{0.809 \pm 0.087}$
	Avg.	0.741 ± 0.177	0.768 ± 0.159	$\mathbf{0.772 \pm 0.146}$	0.672 ± 0.192	$\mathbf{0.714 \pm 0.191}$	0.688 ± 0.184	0.590 ± 0.224	0.595 ± 0.227	$\mathbf{0.515 \pm 0.228}$
ODIN	CF-10	0.897 ± 0.017	0.772 ± 0.160	$\mathbf{0.921 \pm 0.031}$	0.852 ± 0.076	0.783 ± 0.150	$\mathbf{0.878 \pm 0.083}$	0.317 ± 0.086	0.594 ± 0.335	$\mathbf{0.259 \pm 0.116}$
	CF-100	0.731 ± 0.090	0.763 ± 0.128	$\mathbf{0.798 \pm 0.065}$	0.656 ± 0.177	0.742 ± 0.202	$\mathbf{0.721 \pm 0.172}$	0.602 ± 0.156	0.621 ± 0.347	$\mathbf{0.515 \pm 0.216}$
	SVHN	0.836 ± 0.167	0.868 ± 0.080	$\mathbf{0.855 \pm 0.122}$	0.693 ± 0.216	0.806 ± 0.115	$\mathbf{0.709 \pm 0.188}$	0.518 ± 0.210	0.626 ± 0.115	$\mathbf{0.480 \pm 0.160}$
	TIN	0.642 ± 0.134	0.553 ± 0.041	$\mathbf{0.680 \pm 0.145}$	0.614 ± 0.220	0.532 ± 0.181	$\mathbf{0.648 \pm 0.242}$	0.738 ± 0.229	0.793 ± 0.092	$\mathbf{0.680 \pm 0.264}$
	Avg.	0.776 ± 0.152	0.739 ± 0.160	$\mathbf{0.814 \pm 0.135}$	0.704 ± 0.203	0.716 ± 0.198	$\mathbf{0.739 \pm 0.200}$	0.544 ± 0.236	0.658 ± 0.264	$\mathbf{0.484 \pm 0.248}$
Energy Score	CF-10	0.880 ± 0.036	0.783 ± 0.164	$\mathbf{0.903 \pm 0.032}$	0.818 ± 0.096	0.812 ± 0.116	$\mathbf{0.842 \pm 0.087}$	0.322 ± 0.056	0.638 ± 0.344	$\mathbf{0.276 \pm 0.099}$
	CF-100	0.672 ± 0.171	0.721 ± 0.096	$\mathbf{0.748 \pm 0.048}$	0.614 ± 0.202	$\mathbf{0.669 \pm 0.176}$	0.656 ± 0.177	0.637 ± 0.132	0.646 ± 0.261	$\mathbf{0.554 \pm 0.154}$
	SVHN	$\mathbf{0.914 \pm 0.014}$	0.881 ± 0.034	0.881 ± 0.035	0.764 ± 0.104	$\mathbf{0.819 \pm 0.085}$	0.703 ± 0.130	0.360 ± 0.072	0.611 ± 0.123	$\mathbf{0.449 \pm 0.100}$
	TIN	0.553 ± 0.097	0.533 ± 0.044	$\mathbf{0.636 \pm 0.135}$	0.523 ± 0.196	0.521 ± 0.179	$\mathbf{0.597 \pm 0.228}$	0.803 ± 0.084	0.801 ± 0.086	$\mathbf{0.725 \pm 0.180}$
	Avg.	0.753 ± 0.179	0.730 ± 0.163	$\mathbf{0.792 \pm 0.132}$	0.680 ± 0.197	$\mathbf{0.705 \pm 0.189}$	0.700 ± 0.187	0.530 ± 0.218	0.674 ± 0.240	$\mathbf{0.501 \pm 0.214}$

Table 4: Various unsupervised distance proxy based OoD detection techniques on ERM, inter-class mixup and intra-class mixup trained models (averaged over 5 different seeds and OoD datasets) on various datasets (mean $\pm$ std). Expanded version of this table is available in Appendix A.2. CF-10 is CIFAR-10, CF-100 is CIFAR-100, TIN is TinyImageNet.

Table 4 reports AUROC, AUPR and FPR95 results of applying MSP (Maximum Softmax Probability Detector Hendrycks & Gimpel (2017)), ODIN Liang et al. (2018) and Energy Score Liu et al. (2020) on ERM, inter-class mixup and intra-class mixup trained models. The detection performance (AUROC, AUPR and FPR95) for a pair of datasets (In-Dist, OoD), for example (CIFAR-10, SVHN), was obtained by averaging over 5 differently seeded models. These numbers were then averaged over the OoD datasets to obtain each row of Table 4. The averaging was performed over the Gaussian Noise, Uniform Noise, SVHN Netzer et al. (2011), CIFAR-10, CIFAR-100 Krizhevsky et al. (2009), Places365 Zhou et al. (2017), Textures Cimpoi et al. (2014), LSUN Yu et al. (2015) and TinyImageNet Li et al. as OoD datasets, excluding the corresponding in-distribution dataset.

On average we observe an improvement of **4.68%**, **3.26%** and **9.78%** on AUROC, AUPR and FPR95 metrics respectively on unsupervised OoD detection schemes with the use of intra-class mixup over empirical risk minimization. Further, we observe an improvement of **6.38%**, and **21.91%** on AUROC and FPR95 metrics over inter-class mixup and near identical AUPR performance when compared to inter-class mixup.

5.3 SUPPLEMENTING ANGULAR MARGIN

In this subsection we present the performance results when the OoD detection score is supplemented angular margin. We show that the addition of the cosine of the angular margin to OoD detection score improves performance. The supplemented score is obtained by adding the OoD score to the cosine of the angular margin as described in Equation 7.

Technique	In-Dataset	AUROC ↑		AUPR ↑		FPR95 ↓	
		Intra	Intra + $\cos(\theta)$	Intra	Intra + $\cos(\theta)$	Intra	Intra + $\cos(\theta)$
MSP	CIFAR-10	0.884 ± 0.037	$\mathbf{0.915 \pm 0.020}$	0.819 ± 0.113	$\mathbf{0.853 \pm 0.089}$	0.303 ± 0.096	$\mathbf{0.107 \pm 0.030}$
	CIFAR-100	0.724 ± 0.020	$\mathbf{0.747 \pm 0.020}$	0.651 ± 0.170	$\mathbf{0.666 \pm 0.168}$	0.608 ± 0.109	$\mathbf{0.557 \pm 0.127}$
	SVHN	0.900 ± 0.036	$\mathbf{0.939 \pm 0.023}$	0.719 ± 0.126	$\mathbf{0.786 \pm 0.105}$	0.338 ± 0.095	$\mathbf{0.177 \pm 0.063}$
	TinyImageNet	0.581 ± 0.120	$\mathbf{0.583 \pm 0.121}$	$\mathbf{0.560 \pm 0.206}$	0.558 ± 0.205	0.809 ± 0.087	$\mathbf{0.799 \pm 0.090}$
	Average	0.772 ± 0.146	$\mathbf{0.796 \pm 0.157}$	0.714 ± 0.191	$\mathbf{0.716 \pm 0.187}$	0.514 ± 0.228	$\mathbf{0.441 \pm 0.271}$
ODIN	CIFAR-10	0.921 ± 0.031	$\mathbf{0.935 \pm 0.027}$	0.878 ± 0.083	$\mathbf{0.900 \pm 0.072}$	0.259 ± 0.116	$\mathbf{0.229 \pm 0.118}$
	CIFAR-100	0.798 ± 0.065	$\mathbf{0.828 \pm 0.087}$	0.721 ± 0.172	$\mathbf{0.764 \pm 0.184}$	0.515 ± 0.216	$\mathbf{0.462 \pm 0.260}$
	SVHN	0.855 ± 0.122	$\mathbf{0.933 \pm 0.092}$	0.709 ± 0.188	$\mathbf{0.840 \pm 0.184}$	0.480 ± 0.160	$\mathbf{0.221 \pm 0.228}$
	TinyImageNet	$\mathbf{0.680 \pm 0.145}$	0.657 ± 0.150	$\mathbf{0.648 \pm 0.242}$	0.629 ± 0.237	$\mathbf{0.680 \pm 0.264}$	0.712 ± 0.221
	Average	0.814 ± 0.135	$\mathbf{0.838 \pm 0.150}$	0.739 ± 0.200	$\mathbf{0.784 \pm 0.206}$	0.483 ± 0.248	$\mathbf{0.406 \pm 0.293}$
Energy Score	CIFAR-10	0.903 ± 0.032	$\mathbf{0.919 \pm 0.017}$	0.842 ± 0.087	$\mathbf{0.863 \pm 0.071}$	0.276 ± 0.099	$\mathbf{0.238 \pm 0.094}$
	CIFAR-100	0.748 ± 0.048	$\mathbf{0.763 \pm 0.043}$	0.656 ± 0.177	$\mathbf{0.700 \pm 0.173}$	0.553 ± 0.154	$\mathbf{0.532 \pm 0.166}$
	SVHN	0.881 ± 0.035	$\mathbf{0.927 \pm 0.030}$	0.703 ± 0.130	$\mathbf{0.798 \pm 0.102}$	0.449 ± 0.100	$\mathbf{0.279 \pm 0.098}$
	TinyImageNet	$\mathbf{0.635 \pm 0.135}$	0.610 ± 0.125	$\mathbf{0.597 \pm 0.228}$	0.570 ± 0.214	$\mathbf{0.725 \pm 0.180}$	0.745 ± 0.143
	Average	0.792 ± 0.132	$\mathbf{0.805 \pm 0.147}$	0.700 ± 0.187	$\mathbf{0.725 \pm 0.189}$	0.501 ± 0.213	$\mathbf{0.449 \pm 0.242}$

Table 5: Various unsupervised distance proxy OoD detection techniques on compared with and with out angular margin (averaged over 5 different seeds and OoD datasets, expanded version of this table is available in Appendix A.2) on various datasets (mean ± std).

Figure 2: Comparison of average AUROC performance (averaged over in-dist and OoD datasets and 5 seeds) of methods that use distance proxies improved with the use of angular margin and intra-class mixup

Figure 2 and Table 5 compare the OoD detection performance of methods that use distance proxies when used with intra-class mixup aided with angular margin. Table 5 reports mean and standard deviation obtained by averaging 5 different seeds for each in-distribution dataset and averaged over various OoD datasets as used for Table 4. We observe that on average the use of angular margin with intra-class mixup improves OoD detection performance (AUROC) by **7.36%** over empirical risk minimization and **9.10%** over inter-class mixup.

6 CONCLUSION

There have been numerous approaches to tackle the problem of OoD detection. In this paper we explore the use of intra-class mixup to train OoD detectors. We show that intra-class mixup reduces the angular spread of the learnt latent space representation, improving the angular separability of in-distribution and out-of-distribution data. We observe that the use of intra-class mixup on detection techniques that use distance proxies improves AUROC performance by **4.68%** and **6.38%** over empirical risk minimization and inter-class mixup trained models respectively. Further, the use of the cosine of the angular margin to supplement detection scores improves AUROC performance by **7.36%** over empirical risk minimization and **9.10%** over inter-class mixup trained networks. Our findings reveal that intra-class mixup can be an effective tool for training OoD detectors.

7 IMPACT STATEMENT

The research presented in this paper focuses on improving the reliability of deep learning techniques in detecting anomalies, reducing the barriers to the deployment of deep learning in safety critical applications such as medical diagnosis, self driving cars etc. Hence it promises a positive impact on the society. However, one must be aware of the limitations of the specific techniques applied in conjunction with the technique proposed in the paper to ensure reliable and secure deployment in safety critical applications. This paper does not utilize human-derived data and does not utilize any datasets that have been discredited by the creators.

REFERENCES

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. Concrete problems in ai safety, 2016.

Daniel Andor, Chris Alberti, David Weiss, Aliaksei Severyn, Alessandro Presta, Kuzman Ganchev, Slav Petrov, and Michael Collins. Globally normalized transition-based neural networks. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2442–2452, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1231. URL https://www.aclweb.org/anthology/P16-1231.

Joan Bruna, Christian Szegedy, Ilya Sutskever, Ian Goodfellow, Wojciech Zaremba, Rob Fergus, and Dumitru Erhan. Intriguing properties of neural networks. *International Conference on Learning Representation (ICLR), Poster*, 2014.

M. Cimpoi, S. Maji, I. Kokkinos, S. Mohamed, , and A. Vedaldi. Describing textures in the wild. In *Proceedings of the IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2014.

Lucas Deecke, Robert Vandermeulen, Lukas Ruff, Stephan Mandt, and Marius Kloft. Image anomaly detection with generative adversarial networks. In *Joint european conference on machine learning and knowledge discovery in databases*, pp. 3–17. Springer, 2018.

Ronald Aylmer Fisher et al. 138: The use of multiple measurements in taxonomic problems. 1936.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014.

Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *International Conference on Learning Representation (ICLR), Poster*, 2015a.

Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples, 2015b.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. *Proceedings of International Conference on Learning Representations*, 2017.

Dan Hendrycks, Mantas Mazeika, and Thomas Dietterich. Deep anomaly detection with outlier exposure. *Proceedings of the International Conference on Learning Representations*, 2019.

Yen-Chang Hsu, Yilin Shen, Hongxia Jin, and Zsolt Kira. Generalized odin: Detecting out-of-distribution image without learning from out-of-distribution data. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In F. Pereira, C. J. C. Burges, L. Bottou, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 25*, pp. 1097–1105. Curran Associates, Inc., 2012. URL http://papers.nips.cc/paper/4824-imagenet-classification-with-deep-convolutional-neural-networks.pdf.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. *International Conference on Learning Representation (ICLR), Workshop Track*, 2017. URL https://openreview.net/forum?id=S1OufnIlx.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *Nature*, 521(7553):436–444, May 2015. ISSN 1476-4687. doi: 10.1038/nature14539. URL https://doi.org/10.1038/nature14539.

Kimin Lee, Honglak Lee, Kibok Lee, and Jinwoo Shin. Training confidence-calibrated classifiers for detecting out-of-distribution samples. In *International Conference on Learning Representations*, 2018a. URL https://openreview.net/forum?id=ryiAv2xAZ.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 7167–7177. Curran Associates, Inc., 2018b. URL http://papers.nips.cc/paper/7947-a-simple-unified-framework-for-detecting-out-of-distribution-samples-and-adversarial-attacks.pdf.

Fei-Fei Li, Andrej Karpathy, and Justin Johnson. Tiny imagenet visual recognition challenge.

Shiyu Liang, Yixuan Li, and R. Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=H1VGkIxRZ.

Weitang Liu, Xiaoyun Wang, John D. Owens, and Yixuan Li. Energy-based out-of-distribution detection, 2020.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y. Ng. Reading digits in natural images with unsupervised feature learning. In *NIPS Workshop on Deep Learning and Unsupervised Feature Learning 2011*, 2011. URL http://ufldl.stanford.edu/housenumbers/nips2011_housenumbers.pdf.

A. Nguyen, J. Yosinski, and J. Clune. Deep neural networks are easily fooled: High confidence predictions for unrecognizable images. In *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 427–436, 2015. doi: 10.1109/CVPR.2015.7298640.

Jie Ren, Peter J Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark Depristo, Joshua Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In *Advances in Neural Information Processing Systems*, pp. 14707–14718, 2019.

Sunil Thulasidasan, Gopinath Chennupati, Jeff A Bilmes, Tanmoy Bhattacharya, and Sarah Michalak. On mixup training: Improved calibration and predictive uncertainty for deep neural networks. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/36ad8b5f42db492827016448975cc22d-Paper.pdf.

Vladimir N. Vapnik. *Statistical Learning Theory*. Wiley-Interscience, 1998.

William Wang, Angelina Wang, Aviv Tamar, Xi Chen, and Pieter Abbeel. Safer classification by synthesis. *arXiv preprint arXiv:1711.08534*, 2017.

Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. Lsun: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. *arXiv preprint arXiv:1611.03530*, 2016.

Hongyi Zhang, Moustapha Cisse, Yann N. Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=r1Ddp1-Rb.

Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2017.

A APPENDIX

A.1 VARIANCE OF INPUT DUE TO INTRA-CLASS MIXUP

Consider two random variables $X_0, X_1 \sim X$ where X is a class conditional distribution for class $\hat{y}$ with mean μ_X and variance σ_X^2. Then the variance of $\hat{X} = a_0 X_0 + a_1 X_1$ where $a_0 = \lambda$ and $a_1 = 1 - \lambda$ is given by

$$\sigma_{\hat{X}}^2 = Var(\hat{X}) = E\left[\left(\hat{X} - \mu_{\hat{X}}\right)^2\right]$$

$$\sigma_{\hat{X}}^2 = E\left[\left(\sum_{k=0}^1 a_i X_i - \sum_{k=0}^1 a_i \mu_X\right)^2\right]$$

$$\sigma_{\hat{X}}^2 = E\left[\left(\sum_{k=0}^1 a_k (X_k - \mu_X)\right)^2\right]$$

$$\sigma_{\hat{X}}^2 = E\left[\left(\sum_{k=0}^1 a_k (X_k - \mu_X)\right)\left(\sum_{k=0}^1 a_k (X_k - \mu_X)\right)\right]$$

$$\sigma_{\hat{X}}^2 = E\left[\sum_{j=0}^1 \sum_{k=0}^1 a_k a_j (X_k - \mu_X)(X_j - \mu_X)\right]$$

$$\sigma_{\hat{X}}^2 = \sum_{j=0}^1 \sum_{k=0}^1 a_k a_j E\left[(X_k - \mu_X)(X_j - \mu_X)\right]$$

$$\sigma_{\hat{X}}^2 = \sum_{k=0}^1 a_k^2 \sigma_X^2 + 2 a_0 a_1 Cov(X_0, X_1)$$

The $Cov(X_0, X_1) = 0$ because X_0 and X_1 are drawn independently, therefore the equation is reduces to

$$\sigma_{\hat{X}}^2 = \left[\lambda^2 + (1-\lambda)^2\right]\sigma_X^2$$

$$\text{Since } \lambda^2 + (1-\lambda)^2 \leq 1$$

$$\sigma_{\hat{X}}^2 \leq \sigma_X^2$$

A.2 EXPANDED RESULTS FOR VARIOUS DETECTION SCHEMES

		Maximum Softmax Probability Detector								
In-Dataset	OoD Dataset	AUROC			AUPR			FPR95		
		ERM	Inter	Intra	ERM	Inter	Intra	ERM	Inter	Intra
CIFAR-10	Gaussian Noise	0.6991 ± 0.2232	0.9470 ± 0.0471	0.8191 ± 0.0697	0.6451 ± 0.2250	0.9073 ± 0.0816	0.7118 ± 0.0975	0.6103 ± 0.3818	0.1290 ± 0.1128	0.3181 ± 0.0854
	Uniform Noise	0.8722 ± 0.0308	0.9462 ± 0.0383	0.9452 ± 0.0310	0.8005 ± 0.0413	0.9059 ± 0.0621	0.9009 ± 0.0691	0.3513 ± 0.2029	0.1383 ± 0.0960	0.1194 ± 0.0347
	SVHN	0.8111 ± 0.0901	0.8539 ± 0.0386	0.9175 ± 0.0105	0.9005 ± 0.0402	0.9263 ± 0.0167	0.9474 ± 0.0071	0.6102 ± 0.2288	0.6285 ± 0.1962	0.2135 ± 0.0230
	Textures	0.8448 ± 0.0089	0.8471 ± 0.0144	0.8674 ± 0.0064	0.7311 ± 0.0058	0.7677 ± 0.0147	0.7407 ± 0.0084	0.6698 ± 0.1196	0.7438 ± 0.0782	0.4066 ± 0.0330
	LSUN	0.8598 ± 0.0177	0.8888 ± 0.0063	0.8924 ± 0.0048	0.6262 ± 0.0203	0.7074 ± 0.0111	0.6447 ± 0.0069	0.6217 ± 0.1507	0.5010 ± 0.0439	0.3075 ± 0.0090
	TinyImageNet	0.8344 ± 0.0143	0.8484 ± 0.0046	0.8743 ± 0.0014	0.8169 ± 0.0078	0.8456 ± 0.0052	0.8409 ± 0.0023	0.7070 ± 0.1248	0.6929 ± 0.0187	0.3862 ± 0.0141
	Places365	0.8422 ± 0.0155	0.8546 ± 0.0055	0.8758 ± 0.0033	0.9418 ± 0.0040	0.9510 ± 0.0018	0.9497 ± 0.0015	0.6851 ± 0.1368	0.6920 ± 0.0307	0.3745 ± 0.0045
	Average	0.8234 ± 0.0538	0.8837 ± 0.0419	0.8845 ± 0.0370	0.7803 ± 0.1113	0.8587 ± 0.0837	0.8194 ± 0.1126	0.6079 ± 0.1106	0.5037 ± 0.2445	0.3034 ± 0.0963
CIFAR-100	Gaussian Noise	0.2596 ± 0.0665	0.8916 ± 0.0579	0.7189 ± 0.1093	0.3647 ± 0.0181	0.7963 ± 0.0875	0.6211 ± 0.1069	0.8237 ± 0.0798	0.2005 ± 0.0778	0.4668 ± 0.1020
	Uniform Noise	0.7941 ± 0.0627	0.7464 ± 0.2002	0.7159 ± 0.0908	0.6889 ± 0.0805	0.6705 ± 0.1818	0.6048 ± 0.0977	0.3759 ± 0.0618	0.3751 ± 0.2218	0.4384 ± 0.0742
	SVHN	0.7426 ± 0.0273	0.7460 ± 0.0302	0.7501 ± 0.0355	0.8507 ± 0.0173	0.8423 ± 0.0150	0.8560 ± 0.0211	0.6120 ± 0.0456	0.6137 ± 0.0796	0.5912 ± 0.0570
	Textures	0.6948 ± 0.0038	0.7454 ± 0.0030	0.6879 ± 0.0031	0.5075 ± 0.0046	0.5502 ± 0.0047	0.5031 ± 0.0046	0.7322 ± 0.0079	0.6451 ± 0.0133	0.7566 ± 0.0110
	LSUN	0.7020 ± 0.0051	0.7417 ± 0.0037	0.7138 ± 0.0018	0.3591 ± 0.0061	0.4014 ± 0.0076	0.3746 ± 0.0031	0.7094 ± 0.0059	0.7162 ± 0.0130	0.6931 ± 0.0059
	TinyImageNet	0.7382 ± 0.0026	0.7857 ± 0.0023	0.7494 ± 0.0032	0.6900 ± 0.0042	0.7447 ± 0.0022	0.7069 ± 0.0042	0.6518 ± 0.0025	0.6305 ± 0.0133	0.6393 ± 0.0037
	Places365	0.7201 ± 0.0040	0.7560 ± 0.0019	0.7326 ± 0.0029	0.8818 ± 0.0022	0.8989 ± 0.0011	0.8885 ± 0.0018	0.6992 ± 0.0066	0.7035 ± 0.0043	0.6720 ± 0.0035
	Average	0.6645 ± 0.1680	0.7733 ± 0.0503	0.7241 ± 0.0203	0.6204 ± 0.1990	0.7006 ± 0.1619	0.6507 ± 0.1702	0.6577 ± 0.1304	0.5549 ± 0.1786	0.6083 ± 0.1090
SVHN	Gaussian Noise	0.9218 ± 0.0141	0.8198 ± 0.1368	0.8606 ± 0.0710	0.7770 ± 0.0298	0.6935 ± 0.2014	0.6570 ± 0.1413	0.2575 ± 0.0560	0.6185 ± 0.4020	0.4203 ± 0.1965
	Uniform Noise	0.9247 ± 0.0061	0.7706 ± 0.1228	0.8336 ± 0.0760	0.7845 ± 0.0061	0.6385 ± 0.1586	0.6170 ± 0.1391	0.2494 ± 0.0335	0.7598 ± 0.3313	0.4974 ± 0.1963
	CIFAR-100	0.9267 ± 0.0042	0.9340 ± 0.0071	0.9285 ± 0.0031	0.7993 ± 0.0067	0.8672 ± 0.0108	0.8072 ± 0.0085	0.2552 ± 0.0257	0.3282 ± 0.0841	0.2549 ± 0.0112
	Textures	0.9066 ± 0.0059	0.8851 ± 0.0253	0.9019 ± 0.0142	0.6651 ± 0.0154	0.7391 ± 0.0417	0.6643 ± 0.0299	0.2534 ± 0.0260	0.7703 ± 0.1736	0.4037 ± 0.0827
	LSUN	0.9258 ± 0.0051	0.9353 ± 0.0110	0.9176 ± 0.0063	0.5614 ± 0.0133	0.7183 ± 0.0313	0.5419 ± 0.0200	0.2534 ± 0.0260	0.3332 ± 0.1233	0.2964 ± 0.0263
	TinyImageNet	0.9308 ± 0.0037	0.9354 ± 0.0105	0.9339 ± 0.0035	0.8071 ± 0.0066	0.8732 ± 0.0176	0.8160 ± 0.0091	0.2306 ± 0.0221	0.3254 ± 0.1094	0.2300 ± 0.0146
	Places365	0.9281 ± 0.0047	0.9355 ± 0.0133	0.9266 ± 0.0052	0.9324 ± 0.0034	0.9540 ± 0.0087	0.9325 ± 0.0047	0.2436 ± 0.0256	0.3307 ± 0.1388	0.2607 ± 0.0220
	Average	0.9235 ± 0.0074	0.8880 ± 0.0624	0.9003 ± 0.0360	0.7610 ± 0.1088	0.7834 ± 0.1065	0.7194 ± 0.1261	0.2660 ± 0.0442	0.4952 ± 0.1967	0.3377 ± 0.0948
TinyImageNet	Gaussian Noise	0.5506 ± 0.1104	0.4041 ± 0.1878	0.7082 ± 0.1253	0.4911 ± 0.0665	0.4355 ± 0.1123	0.6584 ± 0.1311	0.7374 ± 0.1040	0.7842 ± 0.1274	0.6326 ± 0.1357
	Uniform Noise	0.2977 ± 0.0686	0.3944 ± 0.1244	0.3135 ± 0.1295	0.3726 ± 0.0220	0.4104 ± 0.0488	0.3842 ± 0.0420	0.9064 ± 0.0255	0.7805 ± 0.1021	0.8873 ± 0.0470
	SVHN	0.6747 ± 0.0258	0.6042 ± 0.0915	0.6870 ± 0.0422	0.7956 ± 0.0237	0.7473 ± 0.0607	0.8233 ± 0.0262	0.7187 ± 0.0201	0.7458 ± 0.0843	0.7290 ± 0.0445
	CIFAR-100	0.5774 ± 0.0034	0.5680 ± 0.0098	0.5934 ± 0.0033	0.5491 ± 0.0038	0.5423 ± 0.0095	0.5644 ± 0.0040	0.8718 ± 0.0035	0.8819 ± 0.0034	0.8622 ± 0.0031
	Textures	0.5555 ± 0.0078	0.5435 ± 0.0143	0.5610 ± 0.0109	0.3801 ± 0.0099	0.3756 ± 0.0091	0.3913 ± 0.0093	0.8702 ± 0.0056	0.8786 ± 0.0094	0.8809 ± 0.0058
	LSUN	0.5897 ± 0.0051	0.5727 ± 0.0263	0.5892 ± 0.0047	0.2709 ± 0.0041	0.2615 ± 0.0186	0.2690 ± 0.0044	0.8451 ± 0.0044	0.8639 ± 0.0185	0.8426 ± 0.0057
	Places365	0.6117 ± 0.0045	0.6032 ± 0.0106	0.6137 ± 0.0029	0.8309 ± 0.0014	0.8270 ± 0.0061	0.8316 ± 0.0013	0.8334 ± 0.0042	0.8424 ± 0.0070	0.8271 ± 0.0025
	Average	0.5510 ± 0.1104	0.5272 ± 0.0832	0.5808 ± 0.1199	0.5272 ± 0.1990	0.5142 ± 0.1901	0.5603 ± 0.2059	0.8261 ± 0.0658	0.8253 ± 0.0505	0.8088 ± 0.0871
Average		0.7406 ± 0.1771	0.7680 ± 0.1588	0.7725 ± 0.1461	0.6722 ± 0.1915	0.7142 ± 0.1914	0.6875 ± 0.1843	0.5895 ± 0.2243	0.5948 ± 0.2269	0.5145 ± 0.2285

Table 6: Expanded results for Maximum Softmax Probability Detector

		ODIN								
In-Dataset	OoD Dataset	AUROC			AUPR			FPR95		
		ERM	Inter	Intra	ERM	Inter	Intra	ERM	Inter	Intra
CIFAR-10	Gaussian Noise	0.9059 ± 0.0866	0.9942 ± 0.0109	0.8898 ± 0.0665	0.8378 ± 0.1369	0.9935 ± 0.0121	0.8038 ± 0.1183	0.1691 ± 0.1213	0.0282 ± 0.0544	0.2091 ± 0.1046
	Uniform Noise	0.8624 ± 0.0585	0.9576 ± 0.0370	0.9738 ± 0.0105	0.7709 ± 0.0863	0.9335 ± 0.0620	0.9453 ± 0.0287	0.2807 ± 0.1075	0.1214 ± 0.0857	0.0581 ± 0.0173
	SVHN	0.9127 ± 0.0441	0.4742 ± 0.0900	0.9598 ± 0.0116	0.9490 ± 0.0260	0.7191 ± 0.0595	0.9801 ± 0.0057	0.2489 ± 0.1176	0.9100 ± 0.0368	0.1498 ± 0.0388
	Textures	0.8993 ± 0.0202	0.7156 ± 0.0405	0.8927 ± 0.0128	0.8237 ± 0.0266	0.6403 ± 0.0381	0.8078 ± 0.0188	0.3650 ± 0.0836	0.8312 ± 0.0517	0.3799 ± 0.0437
	LSUN	0.9151 ± 0.0049	0.7959 ± 0.0193	0.9243 ± 0.0051	0.7474 ± 0.0074	0.5633 ± 0.0372	0.7552 ± 0.0123	0.3184 ± 0.0258	0.6734 ± 0.0249	0.2745 ± 0.0233
	TinyImageNet	0.8840 ± 0.0130	0.7257 ± 0.0129	0.9010 ± 0.0068	0.8696 ± 0.0123	0.7264 ± 0.0137	0.8867 ± 0.0074	0.4406 ± 0.0560	0.8021 ± 0.0123	0.3857 ± 0.0302
	Places365	0.8987 ± 0.0081	0.7429 ± 0.0175	0.9086 ± 0.0004	0.9642 ± 0.0028	0.9085 ± 0.0078	0.9672 ± 0.0004	0.3942 ± 0.0390	0.7878 ± 0.0188	0.3533 ± 0.0036
	Average	0.8969 ± 0.0170	0.7723 ± 0.1600	0.9214 ± 0.0308	0.8518 ± 0.0764	0.7835 ± 0.1505	0.8780 ± 0.0832	0.3167 ± 0.0857	0.5935 ± 0.3352	0.2587 ± 0.1162
CIFAR-100	Gaussian Noise	0.5267 ± 0.0759	0.9988 ± 0.0015	0.9365 ± 0.0374	0.4631 ± 0.0373	0.9979 ± 0.0026	0.8727 ± 0.0757	0.5671 ± 0.0788	0.0038 ± 0.0051	0.1305 ± 0.0661
	Uniform Noise	0.8447 ± 0.0539	0.9187 ± 0.1022	0.8070 ± 0.1008	0.7173 ± 0.0776	0.8686 ± 0.1521	0.6811 ± 0.1122	0.2490 ± 0.0735	0.1534 ± 0.1610	0.2741 ± 0.1211
	SVHN	0.7614 ± 0.0249	0.7258 ± 0.0377	0.8147 ± 0.0247	0.8480 ± 0.0182	0.8599 ± 0.0256	0.8859 ± 0.0201	0.5813 ± 0.0369	0.7577 ± 0.0412	0.4685 ± 0.0363
	Textures	0.7347 ± 0.0060	0.6878 ± 0.0074	0.7080 ± 0.0094	0.5533 ± 0.0068	0.5830 ± 0.0066	0.5214 ± 0.0095	0.7023 ± 0.0105	0.8855 ± 0.0086	0.7478 ± 0.0202
	LSUN	0.7323 ± 0.0069	0.6783 ± 0.0065	0.7625 ± 0.0024	0.3957 ± 0.0093	0.3754 ± 0.0095	0.4376 ± 0.0036	0.7386 ± 0.0127	0.8414 ± 0.0045	0.6831 ± 0.0113
	TinyImageNet	0.7635 ± 0.0033	0.6510 ± 0.0059	0.7790 ± 0.0012	0.7197 ± 0.0051	0.6329 ± 0.0062	0.7376 ± 0.0016	0.6707 ± 0.0064	0.8698 ± 0.0032	0.6370 ± 0.0050
	Places365	0.7515 ± 0.0062	0.6780 ± 0.0025	0.7778 ± 0.0028	0.8972 ± 0.0032	0.8735 ± 0.0013	0.9104 ± 0.0015	0.7064 ± 0.0097	0.8328 ± 0.0074	0.6624 ± 0.0059
	Average	0.7307 ± 0.0903	0.7626 ± 0.1275	0.7979 ± 0.0651	0.6563 ± 0.1766	0.7416 ± 0.2015	0.7210 ± 0.1724	0.6022 ± 0.1561	0.6206 ± 0.3472	0.5148 ± 0.2162
SVHN	Gaussian Noise	0.8929 ± 0.0257	0.8318 ± 0.1540	0.8902 ± 0.0627	0.7453 ± 0.0509	0.7685 ± 0.1972	0.7592 ± 0.1302	0.4429 ± 0.1016	0.5501 ± 0.3915	0.4052 ± 0.2158
	Uniform Noise	0.4328 ± 0.0662	0.6939 ± 0.1668	0.5604 ± 0.1762	0.2320 ± 0.0232	0.5804 ± 0.1992	0.3311 ± 0.1563	0.9430 ± 0.0224	0.7344 ± 0.3006	0.7954 ± 0.2306
	CIFAR-100	0.9216 ± 0.0105	0.9217 ± 0.0129	0.9264 ± 0.0098	0.8360 ± 0.0145	0.8877 ± 0.0149	0.8444 ± 0.0178	0.3803 ± 0.0717	0.5923 ± 0.0875	0.3507 ± 0.0491
	Textures	0.8375 ± 0.0083	0.8494 ± 0.0382	0.8539 ± 0.0330	0.6088 ± 0.0133	0.7524 ± 0.0522	0.6394 ± 0.0548	0.7294 ± 0.0526	0.8615 ± 0.0566	0.6461 ± 0.1253
	LSUN	0.9216 ± 0.0122	0.9283 ± 0.0171	0.9081 ± 0.0180	0.6500 ± 0.0331	0.8052 ± 0.0318	0.6110 ± 0.0497	0.3831 ± 0.0715	0.5483 ± 0.1222	0.4339 ± 0.0754
	TinyImageNet	0.9251 ± 0.0091	0.9262 ± 0.0173	0.9276 ± 0.0117	0.8422 ± 0.0142	0.8953 ± 0.0210	0.8451 ± 0.0213	0.3628 ± 0.0570	0.5571 ± 0.1221	0.3414 ± 0.0593
	Places365	0.9201 ± 0.0111	0.9255 ± 0.0212	0.9168 ± 0.0160	0.9386 ± 0.0076	0.9559 ± 0.0121	0.9355 ± 0.0121	0.3843 ± 0.0656	0.5415 ± 0.1555	0.3873 ± 0.0763
	Average	0.8359 ± 0.1671	0.8681 ± 0.0803	0.8548 ± 0.1225	0.6933 ± 0.2162	0.8065 ± 0.1148	0.7094 ± 0.1882	0.5180 ± 0.2105	0.6265 ± 0.1147	0.4800 ± 0.1601
TinyImageNet	Gaussian Noise	0.9353 ± 0.0691	0.5092 ± 0.2553	0.9772 ± 0.0219	0.9130 ± 0.0960	0.5169 ± 0.2044	0.9737 ± 0.0263	0.1958 ± 0.1672	0.6574 ± 0.2351	0.0943 ± 0.0854
	Uniform Noise	0.4737 ± 0.0700	0.4829 ± 0.1432	0.5562 ± 0.1663	0.4421 ± 0.0348	0.4541 ± 0.0796	0.5037 ± 0.0968	0.7836 ± 0.0461	0.6827 ± 0.1446	0.6776 ± 0.1424
	SVHN	0.6754 ± 0.0380	0.5840 ± 0.1369	0.8180 ± 0.0125	0.8018 ± 0.0315	0.7332 ± 0.0748	0.9070 ± 0.0054	0.7237 ± 0.0281	0.7344 ± 0.1257	0.5611 ± 0.0282
	CIFAR-100	0.6016 ± 0.0034	0.5700 ± 0.0141	0.6162 ± 0.0032	0.5805 ± 0.0037	0.5461 ± 0.0124	0.5940 ± 0.0032	0.8754 ± 0.0051	0.8861 ± 0.0128	0.8576 ± 0.0048
	Textures	0.5576 ± 0.0067	0.5436 ± 0.0295	0.5700 ± 0.0098	0.4226 ± 0.0084	0.3808 ± 0.0177	0.4415 ± 0.0132	0.9145 ± 0.0032	0.8840 ± 0.0391	0.9140 ± 0.0050
	LSUN	0.6252 ± 0.0052	0.5714 ± 0.0381	0.6045 ± 0.0052	0.3022 ± 0.0056	0.2641 ± 0.0298	0.2803 ± 0.0051	0.8381 ± 0.0056	0.8672 ± 0.0258	0.8350 ± 0.0061
	Places365	0.6251 ± 0.0033	0.6077 ± 0.0181	0.6216 ± 0.0030	0.8388 ± 0.0020	0.8297 ± 0.0089	0.8344 ± 0.0016	0.8373 ± 0.0046	0.8413 ± 0.0241	0.8232 ± 0.0041
	Average	0.6420 ± 0.1335	0.5527 ± 0.0406	0.6805 ± 0.1454	0.6144 ± 0.2203	0.5321 ± 0.1814	0.6478 ± 0.2419	0.7383 ± 0.2287	0.7933 ± 0.0916	0.6804 ± 0.2641
Average		0.7764 ± 0.1520	0.7389 ± 0.1605	0.8137 ± 0.1347	0.7040 ± 0.2028	0.7159 ± 0.1978	0.7390 ± 0.1996	0.5438 ± 0.2355	0.6585 ± 0.2642	0.4835 ± 0.2479

Table 7: Expanded results for ODIN

		Energy Score								
In-Dataset	OoD Dataset	AUROC			AUPR			FPR95		
		ERM	Inter	Intra	ERM	Inter	Intra	ERM	Inter	Intra
CIFAR-10	Gaussian Noise	0.7997 ± 0.1342	0.9694 ± 0.0422	0.8390 ± 0.0910	0.6885 ± 0.1384	0.9496 ± 0.0658	0.7318 ± 0.1090	0.2975 ± 0.1625	0.0966 ± 0.1382	0.2829 ± 0.1262
	Uniform Noise	0.8719 ± 0.0356	0.9645 ± 0.0197	0.9249 ± 0.0402	0.7576 ± 0.0457	0.9294 ± 0.0330	0.8322 ± 0.0862	0.2446 ± 0.0688	0.1060 ± 0.0700	0.1192 ± 0.0544
	SVHN	0.8880 ± 0.0354	0.4423 ± 0.0759	0.9266 ± 0.0111	0.9268 ± 0.0191	0.7171 ± 0.0385	0.9422 ± 0.0088	0.2773 ± 0.0891	0.9542 ± 0.0316	0.1839 ± 0.0294
	Textures	0.8849 ± 0.0114	0.7291 ± 0.0382	0.8742 ± 0.0099	0.7669 ± 0.0132	0.6743 ± 0.0357	0.7548 ± 0.0152	0.3722 ± 0.0541	0.8883 ± 0.0343	0.4320 ± 0.0437
	LSUN	0.9201 ± 0.0041	0.8262 ± 0.0181	0.9346 ± 0.0052	0.7494 ± 0.0104	0.6769 ± 0.0252	0.7747 ± 0.0169	0.2860 ± 0.0119	0.7493 ± 0.0224	0.2343 ± 0.0136
	TinyImageNet	0.8899 ± 0.0072	0.7721 ± 0.0096	0.9057 ± 0.0044	0.8724 ± 0.0071	0.8021 ± 0.0087	0.8898 ± 0.0049	0.4086 ± 0.0326	0.8286 ± 0.0081	0.3584 ± 0.0197
	Places365	0.9030 ± 0.0059	0.7793 ± 0.0128	0.9156 ± 0.0040	0.9650 ± 0.0021	0.9318 ± 0.0042	0.9693 ± 0.0016	0.3693 ± 0.0225	0.8419 ± 0.0152	0.3225 ± 0.0126
	Average	0.8796 ± 0.0355	0.7833 ± 0.1642	0.9029 ± 0.0319	0.8181 ± 0.0957	0.8116 ± 0.1155	0.8421 ± 0.0870	0.3222 ± 0.0562	0.6379 ± 0.3441	0.2762 ± 0.0987
CIFAR-100	Gaussian Noise	0.2613 ± 0.0566	0.9158 ± 0.0781	0.8128 ± 0.0815	0.3657 ± 0.0169	0.8444 ± 0.1359	0.6856 ± 0.0920	0.8050 ± 0.0531	0.1430 ± 0.1170	0.2883 ± 0.0914
	Uniform Noise	0.7004 ± 0.0573	0.7754 ± 0.2019	0.6778 ± 0.0991	0.5664 ± 0.0464	0.7035 ± 0.1933	0.5565 ± 0.0740	0.3918 ± 0.0625	0.3473 ± 0.2581	0.4136 ± 0.1134
	SVHN	0.7763 ± 0.0206	0.5954 ± 0.0330	0.7686 ± 0.0230	0.8414 ± 0.0158	0.7434 ± 0.0234	0.8269 ± 0.0137	0.5026 ± 0.0291	0.8058 ± 0.0457	0.4757 ± 0.0466
	Textures	0.7045 ± 0.0072	0.6451 ± 0.0029	0.6860 ± 0.0087	0.5062 ± 0.0065	0.4727 ± 0.0065	0.4850 ± 0.0068	0.7266 ± 0.0132	0.8539 ± 0.0122	0.7586 ± 0.0162
	LSUN	0.7195 ± 0.0057	0.6886 ± 0.0082	0.7295 ± 0.0038	0.3714 ± 0.0073	0.3550 ± 0.0104	0.3775 ± 0.0054	0.7125 ± 0.0101	0.8057 ± 0.0094	0.6662 ± 0.0075
	TinyImageNet	0.7855 ± 0.0024	0.7350 ± 0.0047	0.7942 ± 0.0010	0.7478 ± 0.0033	0.6916 ± 0.0071	0.7594 ± 0.0027	0.6305 ± 0.0018	0.7495 ± 0.0058	0.6150 ± 0.0039
	Places365	0.7569 ± 0.0040	0.6909 ± 0.0006	0.7665 ± 0.0041	0.9009 ± 0.0020	0.8720 ± 0.0008	0.9043 ± 0.0025	0.6873 ± 0.0055	0.8165 ± 0.0103	0.6574 ± 0.0082
	Average	0.6721 ± 0.1706	0.7209 ± 0.0961	0.7479 ± 0.0481	0.6143 ± 0.2022	0.6689 ± 0.1758	0.6565 ± 0.1769	0.6366 ± 0.1324	0.6460 ± 0.2609	0.5535 ± 0.1537
SVHN	Gaussian Noise	0.9150 ± 0.0220	0.8192 ± 0.1718	0.8406 ± 0.0894	0.7778 ± 0.0484	0.7466 ± 0.2167	0.6500 ± 0.1680	0.3248 ± 0.0859	0.5670 ± 0.4085	0.4952 ± 0.2378
	Uniform Noise	0.9007 ± 0.0148	0.7946 ± 0.1221	0.8251 ± 0.0875	0.7371 ± 0.0478	0.7089 ± 0.1539	0.6260 ± 0.1636	0.3753 ± 0.0504	0.6984 ± 0.3347	0.5352 ± 0.2273
	CIFAR-100	0.9229 ± 0.0072	0.9218 ± 0.0121	0.9122 ± 0.0101	0.8174 ± 0.0136	0.8807 ± 0.0148	0.7858 ± 0.0208	0.3321 ± 0.0450	0.5889 ± 0.0847	0.3605 ± 0.0459
	Textures	0.8862 ± 0.0080	0.8616 ± 0.0343	0.8639 ± 0.0245	0.6555 ± 0.0267	0.7611 ± 0.0505	0.6281 ± 0.0447	0.5292 ± 0.0311	0.8726 ± 0.0616	0.6217 ± 0.1184
	LSUN	0.9203 ± 0.0100	0.9293 ± 0.0170	0.8928 ± 0.0210	0.5992 ± 0.0367	0.7856 ± 0.0333	0.5053 ± 0.0525	0.3448 ± 0.0522	0.5317 ± 0.1322	0.4416 ± 0.0824
	TinyImageNet	0.9283 ± 0.0067	0.9308 ± 0.0147	0.9197 ± 0.0117	0.8266 ± 0.0155	0.8942 ± 0.0196	0.7994 ± 0.0244	0.2979 ± 0.0351	0.5233 ± 0.1276	0.3210 ± 0.0475
	Places365	0.9243 ± 0.0086	0.9309 ± 0.0196	0.9111 ± 0.0164	0.9363 ± 0.0076	0.9574 ± 0.0134	0.9235 ± 0.0134	0.3179 ± 0.0443	0.4968 ± 0.1675	0.3668 ± 0.0740
	Average	0.9140 ± 0.0140	0.8840 ± 0.0542	0.8808 ± 0.0350	0.7643 ± 0.1044	0.8192 ± 0.0849	0.7026 ± 0.1300	0.3603 ± 0.0724	0.6113 ± 0.1228	0.4489 ± 0.1003
TinyImageNet	Gaussian Noise	0.5227 ± 0.1378	0.4536 ± 0.2639	0.8491 ± 0.1009	0.4717 ± 0.0648	0.4843 ± 0.1818	0.7936 ± 0.1324	0.6961 ± 0.1173	0.6887 ± 0.2240	0.3730 ± 0.1908
	Uniform Noise	0.3399 ± 0.0730	0.4879 ± 0.1808	0.4347 ± 0.1476	0.3868 ± 0.0259	0.4730 ± 0.1057	0.4313 ± 0.0622	0.8750 ± 0.0345	0.6881 ± 0.1671	0.7789 ± 0.1042
	SVHN	0.6734 ± 0.0499	0.5505 ± 0.1357	0.8127 ± 0.0385	0.7781 ± 0.0470	0.7066 ± 0.0674	0.8950 ± 0.0267	0.6508 ± 0.0418	0.7373 ± 0.1069	0.5301 ± 0.0585
	CIFAR-100	0.5778 ± 0.0041	0.5522 ± 0.0167	0.5958 ± 0.0032	0.5500 ± 0.0031	0.5287 ± 0.0136	0.5691 ± 0.0028	0.8775 ± 0.0042	0.8945 ± 0.0112	0.8663 ± 0.0029
	Textures	0.5620 ± 0.0187	0.5396 ± 0.0378	0.5874 ± 0.0114	0.3813 ± 0.0185	0.3839 ± 0.0279	0.4200 ± 0.0131	0.8539 ± 0.0055	0.8886 ± 0.0234	0.8650 ± 0.0120
	LSUN	0.5810 ± 0.0052	0.5489 ± 0.0454	0.5598 ± 0.0069	0.2612 ± 0.0063	0.2487 ± 0.0306	0.2461 ± 0.0048	0.8436 ± 0.0051	0.8699 ± 0.0274	0.8457 ± 0.0085
	Places365	0.6135 ± 0.0038	0.5972 ± 0.0276	0.6087 ± 0.0037	0.8287 ± 0.0019	0.8241 ± 0.0129	0.8265 ± 0.0016	0.8212 ± 0.0038	0.8411 ± 0.0292	0.8189 ± 0.0045
	Average	0.5529 ± 0.0971	0.5328 ± 0.0438	0.6355 ± 0.1350	0.5226 ± 0.1961	0.5213 ± 0.1785	0.5974 ± 0.2277	0.8026 ± 0.0845	0.8012 ± 0.0863	0.7254 ± 0.1804
Average		0.7546 ± 0.1792	0.7303 ± 0.1632	0.7918 ± 0.1318	0.6798 ± 0.1966	0.7053 ± 0.1889	0.6996 ± 0.1872	0.5304 ± 0.2184	0.6741 ± 0.2404	0.5010 ± 0.2135

Table 8: Expanded results for Energy Score

		Maximum Softmax Probability Detector					
		AUROC		AUPR		FPR95	
In-Dataset	OoD Dataset	Intra	Intra + Cos(θ)	Intra	Intra + Cos(θ)	Intra	Intra + Cos(θ)
CIFAR-10	Gaussian Noise	0.8191 ± 0.0697	0.9207 ± 0.0195	0.7116 ± 0.0969	0.8191 ± 0.0463	0.3168 ± 0.0862	0.1070 ± 0.0294
	Uniform Noise	0.9452 ± 0.0310	0.9549 ± 0.0229	0.9007 ± 0.0698	0.9105 ± 0.0599	0.1188 ± 0.0341	0.0894 ± 0.0186
	SVHN	0.9175 ± 0.0105	0.9209 ± 0.0101	0.9474 ± 0.0071	0.9486 ± 0.0068	0.2135 ± 0.0230	0.2023 ± 0.0344
	Textures	0.8674 ± 0.0064	0.9049 ± 0.0098	0.7407 ± 0.0084	0.7806 ± 0.0116	0.4066 ± 0.0330	0.2613 ± 0.0472
	LSUN	0.8924 ± 0.0048	0.9166 ± 0.0033	0.6447 ± 0.0069	0.6952 ± 0.0044	0.3075 ± 0.0090	0.2381 ± 0.0174
	TinyImageNet	0.8743 ± 0.0014	0.8885 ± 0.0034	0.8409 ± 0.0023	0.8597 ± 0.0027	0.3862 ± 0.0141	0.3964 ± 0.0256
	Places365	0.8758 ± 0.0033	0.8989 ± 0.0037	0.9497 ± 0.0015	0.9587 ± 0.0008	0.3745 ± 0.0045	0.3299 ± 0.0246
	Average	0.8845 ± 0.0370	0.9150 ± 0.0197	0.8194 ± 0.1126	0.8532 ± 0.0886	0.3034 ± 0.0963	0.2321 ± 0.1030
CIFAR-100	Gaussian Noise	0.7191 ± 0.1088	0.7714 ± 0.0756	0.6208 ± 0.1057	0.6593 ± 0.0951	0.4667 ± 0.1039	0.3616 ± 0.0481
	Uniform Noise	0.7160 ± 0.0911	0.7453 ± 0.0772	0.6050 ± 0.0981	0.6239 ± 0.0891	0.4393 ± 0.0741	0.3772 ± 0.0528
	SVHN	0.7501 ± 0.0355	0.7659 ± 0.0302	0.8560 ± 0.0211	0.8595 ± 0.0189	0.5912 ± 0.0570	0.5370 ± 0.0398
	Textures	0.6879 ± 0.0031	0.7176 ± 0.0029	0.5031 ± 0.0046	0.5205 ± 0.0048	0.7566 ± 0.0110	0.6385 ± 0.0068
	LSUN	0.7138 ± 0.0018	0.7212 ± 0.0018	0.3746 ± 0.0031	0.3804 ± 0.0038	0.6931 ± 0.0059	0.6876 ± 0.0041
	TinyImageNet	0.7494 ± 0.0032	0.7660 ± 0.0029	0.7069 ± 0.0042	0.7238 ± 0.0041	0.6393 ± 0.0037	0.6166 ± 0.0082
	Places365	0.7326 ± 0.0029	0.7434 ± 0.0035	0.8885 ± 0.0018	0.8938 ± 0.0020	0.6720 ± 0.0035	0.6782 ± 0.0096
	Average	0.7242 ± 0.0203	0.7473 ± 0.0202	0.6507 ± 0.1702	0.6659 ± 0.1679	0.6083 ± 0.1090	0.5566 ± 0.1270
SVHN	Gaussian Noise	0.8602 ± 0.0706	0.9279 ± 0.0285	0.6567 ± 0.1414	0.7550 ± 0.0983	0.4207 ± 0.1935	0.1750 ± 0.0543
	Uniform Noise	0.8330 ± 0.0759	0.8903 ± 0.0401	0.6174 ± 0.1388	0.6862 ± 0.1053	0.4974 ± 0.1963	0.3064 ± 0.0954
	CIFAR-100	0.9285 ± 0.0031	0.9567 ± 0.0015	0.8072 ± 0.0085	0.8648 ± 0.0053	0.2549 ± 0.0112	0.1302 ± 0.0051
	Textures	0.9019 ± 0.0142	0.9319 ± 0.0093	0.6643 ± 0.0299	0.7248 ± 0.0256	0.4037 ± 0.0827	0.2299 ± 0.0444
	LSUN	0.9176 ± 0.0063	0.9521 ± 0.0023	0.5419 ± 0.0200	0.6445 ± 0.0172	0.2964 ± 0.0263	0.1401 ± 0.0070
	TinyImageNet	0.9339 ± 0.0035	0.9589 ± 0.0016	0.8160 ± 0.0091	0.8711 ± 0.0058	0.2300 ± 0.0146	0.1234 ± 0.0051
	Places365	0.9266 ± 0.0052	0.9560 ± 0.0022	0.9325 ± 0.0047	0.9565 ± 0.0025	0.2607 ± 0.0220	0.1323 ± 0.0056
	Average	0.9003 ± 0.0360	0.9391 ± 0.0230	0.7194 ± 0.1261	0.7861 ± 0.1050	0.3377 ± 0.0948	0.1768 ± 0.0632
TinyImageNet	Gaussian Noise	0.7089 ± 0.1240	0.7103 ± 0.1186	0.6584 ± 0.1297	0.6510 ± 0.1217	0.6331 ± 0.1384	0.6200 ± 0.1347
	Uniform Noise	0.3133 ± 0.1290	0.3151 ± 0.1270	0.3841 ± 0.0419	0.3840 ± 0.0409	0.8869 ± 0.0472	0.8792 ± 0.0479
	SVHN	0.6870 ± 0.0422	0.6939 ± 0.0414	0.8233 ± 0.0262	0.8203 ± 0.0269	0.7291 ± 0.0445	0.7066 ± 0.0428
	CIFAR-100	0.5934 ± 0.0033	0.5937 ± 0.0031	0.5644 ± 0.0040	0.5634 ± 0.0037	0.8622 ± 0.0031	0.8629 ± 0.0035
	Textures	0.5610 ± 0.0109	0.5651 ± 0.0106	0.3913 ± 0.0093	0.3898 ± 0.0089	0.8809 ± 0.0058	0.8645 ± 0.0034
	LSUN	0.5892 ± 0.0047	0.5907 ± 0.0052	0.2690 ± 0.0044	0.2671 ± 0.0041	0.8426 ± 0.0057	0.8374 ± 0.0063
	Places365	0.6137 ± 0.0029	0.6152 ± 0.0033	0.8316 ± 0.0013	0.8304 ± 0.0014	0.8271 ± 0.0025	0.8210 ± 0.0022
	Average	0.5809 ± 0.1201	0.5834 ± 0.1206	0.5603 ± 0.2060	0.5580 ± 0.2053	0.8088 ± 0.0869	0.7988 ± 0.0905
Average		0.7725 ± 0.1461	0.7962 ± 0.1566	0.6875 ± 0.1843	0.7158 ± 0.1874	0.5146 ± 0.2285	0.4411 ± 0.2710

Table 9: Expanded results for Maximum Softmax Probability detector comparing Intra-class mixup and Intra-class mixup with angular margin.

		ODIN					
		AUROC		AUPR		FPR95	
In-Dataset	OoD Dataset	Intra	Intra + Cos(θ)	Intra	Intra + Cos(θ)	Intra	Intra + Cos(θ)
CIFAR-10	Gaussian Noise	0.8898 ± 0.0665	0.9435 ± 0.0385	0.8038 ± 0.1183	0.8910 ± 0.0764	0.2091 ± 0.1046	0.1194 ± 0.0705
	Uniform Noise	0.9738 ± 0.0105	0.9842 ± 0.0097	0.9453 ± 0.0287	0.9640 ± 0.0249	0.0581 ± 0.0173	0.0367 ± 0.0196
	SVHN	0.9598 ± 0.0116	0.9572 ± 0.0153	0.9801 ± 0.0057	0.9785 ± 0.0073	0.1498 ± 0.0388	0.1560 ± 0.0524
	Textures	0.8927 ± 0.0128	0.9098 ± 0.0102	0.8078 ± 0.0188	0.8336 ± 0.0145	0.3799 ± 0.0437	0.3296 ± 0.0407
	LSUN	0.9243 ± 0.0051	0.9309 ± 0.0047	0.7552 ± 0.0123	0.7715 ± 0.0121	0.2745 ± 0.0233	0.2541 ± 0.0180
	TinyImageNet	0.9010 ± 0.0068	0.9036 ± 0.0076	0.8867 ± 0.0074	0.8898 ± 0.0079	0.3857 ± 0.0302	0.3750 ± 0.0308
	Places365	0.9086 ± 0.0004	0.9139 ± 0.0019	0.9672 ± 0.0004	0.9691 ± 0.0009	0.3533 ± 0.0036	0.3329 ± 0.0060
	Average	0.9214 ± 0.0308	0.9347 ± 0.0269	0.8780 ± 0.0832	0.8996 ± 0.0719	0.2587 ± 0.1162	0.2291 ± 0.1178
CIFAR-100	Gaussian Noise	0.9365 ± 0.0374	0.9878 ± 0.0087	0.8727 ± 0.0757	0.9738 ± 0.0226	0.1305 ± 0.0661	0.0298 ± 0.0179
	Uniform Noise	0.8070 ± 0.1008	0.9357 ± 0.0335	0.6811 ± 0.1122	0.8518 ± 0.0701	0.2741 ± 0.1211	0.1055 ± 0.0479
	SVHN	0.8147 ± 0.0247	0.8135 ± 0.0188	0.8859 ± 0.0201	0.8781 ± 0.0175	0.4685 ± 0.0363	0.4592 ± 0.0292
	Textures	0.7080 ± 0.0094	0.7679 ± 0.0070	0.5214 ± 0.0095	0.5908 ± 0.0082	0.7478 ± 0.0202	0.6369 ± 0.0209
	LSUN	0.7625 ± 0.0024	0.7478 ± 0.0040	0.4376 ± 0.0036	0.4138 ± 0.0063	0.6831 ± 0.0113	0.6883 ± 0.0078
	TinyImageNet	0.7790 ± 0.0012	0.7804 ± 0.0008	0.7376 ± 0.0016	0.7393 ± 0.0006	0.6370 ± 0.0050	0.6343 ± 0.0076
	Places365	0.7778 ± 0.0028	0.7658 ± 0.0043	0.9104 ± 0.0015	0.9048 ± 0.0022	0.6624 ± 0.0059	0.6788 ± 0.0091
	Average	0.7979 ± 0.0651	0.8284 ± 0.0874	0.7210 ± 0.1724	0.7646 ± 0.1843	0.5148 ± 0.2162	0.4618 ± 0.2598
SVHN	Gaussian Noise	0.8902 ± 0.0627	0.9764 ± 0.0115	0.7592 ± 0.1302	0.9265 ± 0.0353	0.4052 ± 0.2158	0.0897 ± 0.0411
	Uniform Noise	0.5604 ± 0.1762	0.7152 ± 0.0749	0.3311 ± 0.1563	0.4173 ± 0.0785	0.7954 ± 0.2306	0.6907 ± 0.1181
	CIFAR-100	0.9264 ± 0.0098	0.9815 ± 0.0016	0.8444 ± 0.0178	0.9531 ± 0.0037	0.3507 ± 0.0491	0.0784 ± 0.0078
	Textures	0.8539 ± 0.0330	0.9167 ± 0.0139	0.6394 ± 0.0548	0.7835 ± 0.0252	0.6461 ± 0.1253	0.4404 ± 0.0766
	LSUN	0.9081 ± 0.0180	0.9819 ± 0.0015	0.6110 ± 0.0497	0.8683 ± 0.0112	0.4339 ± 0.0754	0.0781 ± 0.0091
	TinyImageNet	0.9276 ± 0.0117	0.9810 ± 0.0018	0.8451 ± 0.0213	0.9523 ± 0.0041	0.3414 ± 0.0593	0.0798 ± 0.0074
	Places365	0.9168 ± 0.0160	0.9794 ± 0.0019	0.9355 ± 0.0121	0.9831 ± 0.0016	0.3873 ± 0.0763	0.0881 ± 0.0089
	Average	0.8548 ± 0.1225	0.9331 ± 0.0916	0.7094 ± 0.1882	0.8406 ± 0.1836	0.4800 ± 0.1601	0.2208 ± 0.2281
TinyImageNet	Gaussian Noise	0.9772 ± 0.0219	0.9462 ± 0.0364	0.9737 ± 0.0263	0.9386 ± 0.0448	0.0943 ± 0.0854	0.2069 ± 0.0996
	Uniform Noise	0.5562 ± 0.1663	0.4426 ± 0.1369	0.5037 ± 0.0968	0.4370 ± 0.0609	0.6776 ± 0.1424	0.7706 ± 0.0794
	SVHN	0.8180 ± 0.0125	0.7840 ± 0.0230	0.9070 ± 0.0054	0.8864 ± 0.0117	0.5611 ± 0.0282	0.6242 ± 0.0485
	CIFAR-100	0.6162 ± 0.0032	0.6059 ± 0.0018	0.5940 ± 0.0032	0.5830 ± 0.0030	0.8576 ± 0.0048	0.8621 ± 0.0035
	Textures	0.5700 ± 0.0098	0.5789 ± 0.0065	0.4415 ± 0.0132	0.4387 ± 0.0094	0.9140 ± 0.0050	0.8929 ± 0.0054
	LSUN	0.6045 ± 0.0052	0.6225 ± 0.0076	0.2803 ± 0.0051	0.2896 ± 0.0050	0.8350 ± 0.0061	0.8032 ± 0.0062
	Places365	0.6216 ± 0.0030	0.6158 ± 0.0050	0.8344 ± 0.0016	0.8302 ± 0.0025	0.8232 ± 0.0041	0.8217 ± 0.0026
	Average	0.6805 ± 0.1454	0.6566 ± 0.1499	0.6478 ± 0.2419	0.6291 ± 0.2370	0.6804 ± 0.2641	0.7116 ± 0.2210
Average		0.8137 ± 0.1347	0.8382 ± 0.1505	0.7390 ± 0.1996	0.7835 ± 0.2061	0.4835 ± 0.2479	0.4058 ± 0.2934

Table 10: Expanded results for ODIN comparing Intra-class mixup and Intra-class mixup with angular margin.

		Energy Score					
		AUROC		AUPR		FPR95	
In-Dataset	OoD Dataset	Intra	Intra + Cos(θ)	Intra	Intra + Cos(θ)	Intra	Intra + Cos(θ)
CIFAR-10	Gaussian Noise	0.8390 ± 0.0910	0.9076 ± 0.0591	0.7318 ± 0.1090	0.8164 ± 0.0887	0.2829 ± 0.1262	0.1654 ± 0.0900
	Uniform Noise	0.9249 ± 0.0402	0.9472 ± 0.0299	0.8322 ± 0.0862	0.8710 ± 0.0696	0.1192 ± 0.0544	0.0864 ± 0.0416
	SVHN	0.9266 ± 0.0111	0.9272 ± 0.0116	0.9422 ± 0.0088	0.9432 ± 0.0096	0.1839 ± 0.0294	0.1812 ± 0.0286
	Textures	0.8742 ± 0.0099	0.8961 ± 0.0083	0.7548 ± 0.0152	0.7807 ± 0.0170	0.4320 ± 0.0437	0.3380 ± 0.0353
	LSUN	0.9346 ± 0.0052	0.9356 ± 0.0054	0.7747 ± 0.0169	0.7740 ± 0.0159	0.2343 ± 0.0136	0.2273 ± 0.0162
	TinyImageNet	0.9057 ± 0.0044	0.9060 ± 0.0039	0.8898 ± 0.0049	0.8898 ± 0.0043	0.3584 ± 0.0197	0.3581 ± 0.0233
	Places365	0.9156 ± 0.0040	0.9166 ± 0.0043	0.9693 ± 0.0016	0.9693 ± 0.0016	0.3225 ± 0.0126	0.3128 ± 0.0176
	Average	0.9029 ± 0.0319	0.9195 ± 0.0168	0.8421 ± 0.0870	0.8635 ± 0.0711	0.2762 ± 0.0987	0.2384 ± 0.0938
CIFAR-100	Gaussian Noise	0.8128 ± 0.0815	0.8435 ± 0.0692	0.6856 ± 0.0920	0.7199 ± 0.0879	0.2883 ± 0.0914	0.2450 ± 0.0788
	Uniform Noise	0.6778 ± 0.0991	0.7311 ± 0.0811	0.5565 ± 0.0740	0.5951 ± 0.0717	0.4136 ± 0.1134	0.3513 ± 0.0946
	SVHN	0.7686 ± 0.0230	0.7724 ± 0.0240	0.8269 ± 0.0137	0.8312 ± 0.0146	0.4757 ± 0.0466	0.4729 ± 0.0481
	Textures	0.6860 ± 0.0087	0.7078 ± 0.0068	0.4850 ± 0.0068	0.5022 ± 0.0061	0.7586 ± 0.0162	0.7043 ± 0.0102
	LSUN	0.7295 ± 0.0038	0.7278 ± 0.0040	0.3775 ± 0.0054	0.3771 ± 0.0054	0.6662 ± 0.0075	0.6719 ± 0.0072
	TinyImageNet	0.7942 ± 0.0010	0.7942 ± 0.0011	0.7594 ± 0.0027	0.7593 ± 0.0028	0.6150 ± 0.0039	0.6171 ± 0.0050
	Places365	0.7665 ± 0.0041	0.7644 ± 0.0041	0.9043 ± 0.0025	0.9037 ± 0.0026	0.6574 ± 0.0082	0.6643 ± 0.0087
	Average	0.7479 ± 0.0481	0.7630 ± 0.0428	0.6565 ± 0.1769	0.6698 ± 0.1735	0.5535 ± 0.1537	0.5324 ± 0.1658
SVHN	Gaussian Noise	0.8406 ± 0.0894	0.9078 ± 0.0500	0.6500 ± 0.1680	0.7647 ± 0.1187	0.4952 ± 0.2378	0.3170 ± 0.1596
	Uniform Noise	0.8251 ± 0.0875	0.8685 ± 0.0614	0.6260 ± 0.1636	0.6893 ± 0.1276	0.5352 ± 0.2273	0.4348 ± 0.1837
	CIFAR-100	0.9122 ± 0.0101	0.9521 ± 0.0039	0.7858 ± 0.0208	0.8773 ± 0.0085	0.3605 ± 0.0459	0.1918 ± 0.0143
	Textures	0.8639 ± 0.0245	0.9126 ± 0.0158	0.6281 ± 0.0447	0.7269 ± 0.0341	0.6217 ± 0.1184	0.3978 ± 0.0896
	LSUN	0.8928 ± 0.0210	0.9423 ± 0.0092	0.5053 ± 0.0525	0.6789 ± 0.0357	0.4416 ± 0.0824	0.2412 ± 0.0371
	TinyImageNet	0.9197 ± 0.0117	0.9563 ± 0.0048	0.7994 ± 0.0244	0.8862 ± 0.0107	0.3210 ± 0.0475	0.1729 ± 0.0183
	Places365	0.9111 ± 0.0164	0.9513 ± 0.0072	0.9235 ± 0.0134	0.9590 ± 0.0058	0.3668 ± 0.0740	0.1980 ± 0.0310
	Average	0.8808 ± 0.0350	0.9273 ± 0.0300	0.7026 ± 0.1300	0.7975 ± 0.1015	0.4489 ± 0.1003	0.2791 ± 0.0976
TinyImageNet	Gaussian Noise	0.8491 ± 0.1009	0.7804 ± 0.1048	0.7936 ± 0.1324	0.7042 ± 0.1267	0.3730 ± 0.1908	0.4802 ± 0.1457
	Uniform Noise	0.4347 ± 0.1476	0.3757 ± 0.1311	0.4313 ± 0.0622	0.4043 ± 0.0469	0.7789 ± 0.1042	0.8095 ± 0.0831
	SVHN	0.8127 ± 0.0385	0.7603 ± 0.0384	0.8950 ± 0.0267	0.8500 ± 0.0286	0.5301 ± 0.0585	0.5699 ± 0.0509
	CIFAR-100	0.5958 ± 0.0032	0.5929 ± 0.0029	0.5691 ± 0.0028	0.5631 ± 0.0032	0.8663 ± 0.0029	0.8642 ± 0.0041
	Textures	0.5874 ± 0.0114	0.5757 ± 0.0106	0.4200 ± 0.0131	0.3936 ± 0.0099	0.8650 ± 0.0120	0.8494 ± 0.0083
	LSUN	0.5598 ± 0.0069	0.5736 ± 0.0066	0.2461 ± 0.0048	0.2525 ± 0.0044	0.8457 ± 0.0085	0.8335 ± 0.0084
	Places365	0.6087 ± 0.0037	0.6105 ± 0.0039	0.8265 ± 0.0016	0.8257 ± 0.0017	0.8189 ± 0.0045	0.8113 ± 0.0040
	Average	0.6355 ± 0.1350	0.6099 ± 0.1250	0.5974 ± 0.2277	0.5705 ± 0.2142	0.7254 ± 0.1804	0.7454 ± 0.1426
Average		0.7918 ± 0.1318	0.8049 ± 0.1471	0.6996 ± 0.1872	0.7253 ± 0.1889	0.5010 ± 0.2135	0.4488 ± 0.2420

Table 11: Expanded results for Energy Score comparing Intra-class mixup and Intra-class mixup with angular margin.