Latent Score-Based Reweighting for Robust Classification on Imbalanced Tabular Data

Abstract

Machine learning models often perform well on tabular data by optimizing average prediction accuracy. However, they may underperform on specific subsets due to inherent biases and spurious correlations in the training data, such as associations with non-causal features like demographic information. These biases lead to critical robustness issues as models may inherit or amplify them, resulting in poor performance where such misleading correlations do not hold. Existing mitigation methods have significant limitations: some require prior group labels, which are often unavailable, while others focus solely on the conditional distribution $P(Y|X)$, upweighting misclassified samples without effectively balancing the overall data distribution $P(X)$. To address these shortcomings, we propose a latent score-based reweighting framework. It leverages score-based models to capture the joint data distribution $P(X, Y)$ without relying on additional prior information. By estimating sample density through the similarity of score vectors with neighboring data points, our method identifies underrepresented regions and upweights samples accordingly. This approach directly tackles inherent data imbalances, enhancing robustness by ensuring a more uniform dataset representation. Experiments on various tabular datasets under distribution shifts demonstrate that our method effectively improves performance on imbalanced data.

1 Introduction

Machine learning applied to tabular data has achieved significant success across various practical domains (Liu et al., 2024). While models trained using empirical risk minimization (ERM) often perform well on average, achieving low test errors overall, they can still exhibit high error rates on specific subsets of data (Vapnik, 1999). This inconsistency highlights a critical robustness issue, primarily stemming from inherent biases in the data. For example, training data may contain spurious correlations where target labels are statistically linked to non-causal features like demographic information. As a result, models trained on such biased data may inherit or even amplify these biases, leading to poor performance on data subsets where these correlations do not apply.

To tackle this issue, researchers have proposed various methods to mitigate biases in the training data. Some approaches utilize additional prior information, such as group labels, to reduce the impact of spurious correlations by resampling or adding regularization terms (Arjovsky et al., 2019; Sagawa* et al., 2020). Unfortunately, in many practical situations, such prior information is incomplete or unavailable, limiting these methods' usefulness. To overcome this, other methods focus on automatically generating proxy information for debiasing (Nam et al., 2020; Liu et al., 2021a; Qiu et al., 2023). A common strategy involves pre-training a classification model on the training data and then upweighting samples that the model classifies incorrectly. Since these misclassifications are often determined by a sample's proximity to the model's decision boundary, we refer to these as boundary-based methods. While these methods can enhance robustness by focusing on underrepresented training samples near the classification boundary, their effectiveness is constrained as they may fail to achieve a globally balanced distribution of training data.

To illustrate the limitations of boundary-based methods, consider a binary classification problem with two features, x_0 and x_1, where the true classification boundary follows a sine curve (see Figure 1a). The training data is heavily concentrated in regions where $x_0 \in \left[\frac{\pi}{4}, \frac{3\pi}{4}\right] \cup \left[\frac{5\pi}{4}, \frac{7\pi}{4}\right]$, resulting in a highly imbalanced dataset, as visualized in Figure 1d. Ideally, reweighting should correct this

(a) Unweighted training data (b) Weighted data by JTT (c) Weighted data by latent score

(d) Unweighted data density (e) Weighted density with JTT (f) Weighted density with latent score
(classifier accuracy at 60.25%) (classifier accuracy at 69.50%) (classifier accuracy at 75.75%)

Figure 1: The comparison of weighted density plots on a synthetic dataset.

bias, yielding a more uniformly distributed dataset. Boundary-based methods like JTT (Liu et al., 2021a) try to achieve this by assigning higher weights to samples with large classification errors (Figure 1b). However, many reweighted samples are still from high-density regions near the decision boundary, rather than the low-density regions where the imbalance is most severe. The resulting distribution (Figure 1e) shows that the boundary-based method does not fully balance the training data. Consequently, the accuracy improvement on the balanced test set is modest, increasing from 60.25% to only 69.50%.

The fundamental limitation of boundary-based methods is their exclusive focus on the pre-trained classification boundary, $P(Y|X)$, neglecting the overall data distribution. This oversight leads to ineffective data balancing. Motivated by this observation, we aim to develop new approaches that not only consider classification errors but also more effectively address inherent data imbalances, ensuring a balanced and uniform distribution across the dataset.

To more effectively address inherent data imbalances, we propose leveraging score-based models, also known as diffusion models (Song & Ermon, 2019; Ho et al., 2020). These models can capture the joint data distribution $P(X, Y)$, providing a powerful tool for modeling the underlying data structure. Our key idea is to use a score-based model to estimate the density of samples in the dataset. By identifying low-density regions—areas where data is underrepresented—we can upweight samples from these regions, ensuring a more balanced and unbiased representation during training. This approach moves beyond boundary-based methods by directly targeting data imbalance, aiming to improve performance across diverse data subsets.

However, directly using density estimates from the score-based model poses challenges due to potential extreme values, leading to "density explosions" for certain samples. These extremes can overemphasize a few extremely high-density points, making it difficult to distinguish between other high- and low-density samples. To overcome this, we propose using a proxy for density based on an important observation. We demonstrate this observation using data from a mixture of two Gaussians, as shown in Figure 2. Regions with higher probability densities are represented by warmer colors in Figure 2a. To achieve a balanced data distribution, these regions are expected to have lower weights, as shown in Figure 2b. In Figure 2c, we illustrate that in high-density regions (e.g., points B and D), the score vectors (pink arrows) of neighboring samples tend to align with the direction toward the high-density sample (e.g., cyan arrows $\overrightarrow{B_iB}$, where $i = 1, 2, ...$). In contrast, samples in low-density regions (e.g., points A and C) do not exhibit this similarity. Essentially, if sample B has higher density than sample A, the similarity between the score vectors and $\overrightarrow{B_iB}$ will generally be greater than that for $\overrightarrow{A_iA}$. This directional similarity serves as a proxy for density. By using this proxy, we avoid instability from extreme values, enabling a more stable and effective data reweighting approach.

(a) Data density visualization (b) Score field & expected weights (c) Score similarity as proxy

Figure 2: The score fields of a mixture of two Gaussian.

Our method offers two key advantages. First, it requires no additional prior information, such as group labels, making it applicable in scenarios where such information is unavailable or incomplete. This flexibility allows broad adoption without relying on external data or assumptions. Second, our approach faithfully represents the joint data distribution $P(X, Y)$. By leveraging score-based models, we overcome the limitations of pre-trained classification boundaries $P(Y|X)$, which often inherit biases from the training process. This ensures that the final classification model remains unbiased and accurately captures the underlying relationships between features and labels, leading to improved performance and robustness.

In summary, our contributions are: (1) We recognize that improving robustness requires modeling the joint data distribution, a gap in current boundary-based methods that do not capture the true data distribution. (2) We introduce a new framework that accurately reflects the joint data distribution, detailed in Section 3. (3) We assess our method on various tabular datasets under distribution shifts, demonstrating through extensive experiments that our approach effectively enhances robustness.

2 RELATED WORKS

Achieving robustness with prior information. Commonly, researchers aim to train robust models towards distribution shift. Some works train models with the help of given or self-generated domain labels (Sagawa* et al., 2020; Arjovsky et al., 2019; Sun & Saenko, 2016; Liu et al., 2021b;c; Tong et al., 2023; Zhang et al., 2024b). Generally they expect the model's performance in the worst domain acceptable. Therefore, they may add regularizer into training loss when treating domain labels as extra supervised information. Predefining the form of prior data distribution is also a common approach (Shen et al., 2020; Duchi & Namkoong, 2021; Shen et al., 2023; Gu et al., 2024). Among them, stable learning is an effective approach which pursues feature independence under certain assumptions. The details are listed in Section A.9.

Achieving robustness without prior information. Apart from introducing the prior information, some other methods turn to use the performance of models to guide the final training process (Liu et al., 2021a; Nam et al., 2020; Levy et al., 2020; Qiu et al., 2023). They typically contain two stages. In the first stage, they identify some biased samples which will make ERM-based models make false predictions. In the second stage, they assign greater weights to these samples to develop a more robust model. However, we notice that few of the following methods model the joint data distribution, which is not fit for seeking overall robustness. The requirement of some prior-based methods is also rather strict and can not generalize to realistic scenarios.

Generative Models for Robustness. Generative models can produce novel and diverse data, enriching training datasets and leading to models with a deeper understanding of semantic content. Consequently, several studies have leveraged generative models to enhance robustness, primarily through data augmentation techniques (Li et al., 2021; Choi et al., 2021; Ilse et al., 2020; Dendorfer et al., 2021; Oberdiek et al., 2022; Zhang et al., 2022; 2024a). These approaches have demonstrated promising performance improvements. In contrast to these methods, we introduce a novel approach that utilizes generative models to estimate the density of the data distribution. By assigning weights to data samples based on this density estimation during training, we enhance the model's robustness.

3 METHOD

We present an unbiased learning framework that operates without prior information or pre-trained classification boundaries. The model is designed to provide robust predictions across a range of biased covariates. To address distributional shifts, we employ score-based methods to faithfully capture the joint distribution. The framework follows three steps: (1) training diffusion models on latent representations to model the data distribution, (2) sampling several timesteps and estimating scores to align the probability density of training data, and (3) reweighting samples based on data density to ensure a balanced distribution. The detailed procedure is provided in Algorithm 1.

3.1 PRELIMINARY

We first introduce the background on score models (Song & Ermon, 2019). Score models can model data distributions by learning score (*i.e.*, the gradients of probability density), and have shown remarkable performance in generative tasks. Song et al. proposed a unified framework based on Itô stochastic differential equations (SDEs). Training a score model typically involves an iterative forward and backward process. In the forward pass, a complex data distribution is gradually transformed into a Gaussian distribution by progressively adding noise, described by the following SDE:

$$\mathrm{d}\mathbf{x} = \mathbf{f}(\mathbf{x}, t)\mathrm{d}t + g(t)\mathrm{d}\mathbf{w}, \tag{1}$$

where $\mathbf{x} \in \mathbb{R}^d$ with $\mathbf{x}_0 \sim p_0$ representing the data distribution, $t \in [0, T]$, $\mathbf{f} : \mathbb{R}^d \times [0, T] \to \mathbb{R}^d$, $g : [0, T] \to \mathbb{R}$, and $\mathbf{w} \in \mathbb{R}^d$ is a standard Wiener process. The backward process reconstructs the original data structure from noisy data. Song et al. also introduced the corresponding "probability flow" ordinary differential equation (ODE):

$$\mathrm{d}\mathbf{x} = \left[\mathbf{f}(\mathbf{x}, t) - \frac{1}{2}g(t)^2 \nabla_\mathbf{x} \log p_t(\mathbf{x}) \right] \mathrm{d}\bar{t}, \tag{2}$$

where $\bar{t}$ represents time flowing backward from T to 0. We use a neural network, $s_\theta(\mathbf{x}_t, t)$, to estimate the score of the transformed data distribution at time t, $\nabla_\mathbf{x} \log p_t(\mathbf{x})$. The training loss for $s_\theta(\mathbf{x}_t, t)$ is defined through denoising score-matching:

$$\mathbb{E}_{t \sim \sigma(t)} \lambda(t) \mathbb{E}_{\mathbf{x}_0 \sim p_0} \mathbb{E}_{\mathbf{x}_t \sim p_{t|0}(\cdot|\mathbf{x}_0)} \left[\|s_\theta(\mathbf{x}_t, t) - \nabla_{\mathbf{x}_t} \log p_{t|0}(\mathbf{x}_t|\mathbf{x}_0)\|_2^2 \right], \tag{3}$$

where $\sigma(t)$ represents the time variable distribution, and $\lambda(t)$ is a positive weighting function that stabilizes the time-dependent loss magnitude (Song et al., 2021). The diffusion process generally employs Gaussian transition kernels, leading to $p_{t|0}(\mathbf{x}_t|\mathbf{x}_0) = \mathcal{N}(\boldsymbol{\mu}_t, \sigma_t^2 \mathbf{I})$.

In summary, score models aim to compute score at each time scale with different noise, and finally reconstruct the clean sample with the guidance of score (Karras et al., 2022; Xu et al., 2022; 2023).

3.2 TRAINING DISTRIBUTION MODELING

To ensure robustness, we first train score models to approximate the probability distribution. To enable training on limited computational resources, we adopt the approach of latent diffusion (Rombach et al., 2022; Zhang et al., 2024c). Specifically, we first train a variational autoencoder (VAE), $\phi_{\mathcal{Z}} = \phi_{Enc} \cdot \phi_{Dec}$, using a β-VAE (Higgins et al., 2017), where the coefficient β balances the reconstruction loss and the KL-divergence loss:

$$\mathcal{L}_{\phi_{\mathcal{Z}}} = \ell_{recon}(\mathbf{x}, \hat{\mathbf{x}}) + \beta \ell_{kl}. \tag{4}$$

We then obtain the latent representations using the trained encoder ϕ_{Enc}. The subsequent diffusion process operates on these latent representations, $\mathbf{z} = \phi_{Enc}(\mathbf{x})$, rather than the raw data. Leveraging the VAE allows us to model the latent joint distribution of meaningful semantics, rather than superficial features in the raw data.

After the VAE model is trained, we use score-based methods to model the underlying distribution $p(\mathbf{z})$ (Song et al., 2021; Zhang et al., 2024c):

$$\mathbf{z}_t = \mathbf{z}_0 + \sigma(t)\boldsymbol{\varepsilon}, \ \boldsymbol{\varepsilon} \sim \mathcal{N}(\mathbf{0}, \mathbf{I}), \qquad \text{(Forward Process)} \tag{5}$$

$$\mathrm{d}\mathbf{z}_t = -2\dot{\sigma}(t)\sigma(t)\nabla_{\mathbf{z}_t} \log p(\mathbf{z}_t) \, \mathrm{d}t + \sqrt{2\dot{\sigma}(t)\sigma(t)} \, \mathrm{d}\boldsymbol{\omega}_t, \qquad \text{(Reverse Process)} \tag{6}$$

where $\mathbf{z}_0 = \mathbf{z}$ is the initial embedding from the encoder, $\mathbf{z}_t$ is the diffused embedding at time t, and $\sigma(t)$ is the noise level. In the reverse process (Eq. 6), $\nabla_{\mathbf{z}_t} \log p(\mathbf{z}_t)$ represents the score function of $\mathbf{z}_t$. Following Zhang et al., we set the noise scale $\sigma(t) = t$, making it linear with respect to time.

Following the approach of EDM (Karras et al., 2022), we train our neural network F_θ to directly predict the output at a given timestep t, rather than a scaled unit variance term $\sigma(t)\varepsilon$. The neural network is preconditioned with a σ-dependent skip connection, defined as:

$$D_\theta(z, \sigma) = c_{skip}(\sigma)z + c_{out}(\sigma)F_\theta(c_{in}(\sigma)z, c_{noise}(\sigma)), \tag{7}$$

where $c_{skip}(\sigma)$ modulates the skip connection between timesteps, $c_{in}(\sigma)$ and $c_{out}(\sigma)$ scale the input and output magnitudes, and $c_{noise}(\sigma)$ maps the noise level σ into a conditioning input for F_θ. The specifics of these scaling factors are detailed in Appendix A.2. The final training loss is:

$$\mathcal{L}(D_\theta, \sigma) = \mathbb{E}_t \lambda(t) \mathbb{E}_{z \sim p(\mathbf{z})} \|D_\theta(z + \sigma(t)\varepsilon, t) - z\|_2^2. \tag{8}$$

Here, $\lambda(t)$ is a positive weighting function to maintain the time-dependent loss at a consistent magnitude. The entire process uses the covariates $\mathbf{x}$ as input. After obtaining the latent representation $\mathbf{z}$, we partition $\mathbf{z}$ by their corresponding label y. For binary classification, two models are trained separately on $\mathbf{z}_{y=0}$ and $\mathbf{z}_{y=1}$ using Eq. 8. This allows us to model the joint training distribution for each class through these score models. We demonstrate the advantages of class-wise data separation and independent score model training in Section 3.3.

3.3 PROBABILITY DENSITY PROXY

At this stage, our goal is to estimate the probability density of each sample using the score models trained in Section 3.2. We first address the limitations of computing exact log-likelihood via the probability flow ordinary differential equation (ODE) proposed in (Song et al., 2021). Based on the insights from Figure 2, we introduce an approach to estimate the **relative** probability density through a similarity measure. The difference of score similarities acts as a proxy, preserving the relative magnitudes of probability densities among samples and offering a controllable numerical range at the model level. This makes it well-suited for computing weights, as described in Section 3.4.

3.3.1 EXACT LOG-LIKELIHOOD COMPUTATION VIA PROBABILITY FLOW ODE

Since our goal is to distinguish data based on high or low probability density, a natural approach is to compute the exact log-likelihood using the trained score model from Section 3.2. Song et al. have proposed an estimation method for this. The forward diffusion process is represented by a stochastic differential equation (SDE) that gradually transforms a complex data distribution into a known prior distribution by injecting noise, as described in Eq. 1. The corresponding "probability flow" ordinary differential equation (ODE) is given in Eq. 2. By replacing the score $\nabla_{\mathbf{x}} \log p_t(\mathbf{x})$ with a neural network $\mathbf{s}_\theta(\mathbf{x}, t)$, the probability flow ODE takes the form:

$$d\mathbf{x} = \underbrace{\left[\mathbf{f}(\mathbf{x}, t) - \frac{1}{2}g(t)^2 \mathbf{s}_\theta(\mathbf{x}, t)\right]}_{=:\tilde{\mathbf{f}}_\theta(\mathbf{x}, t)} d\bar{t}. \tag{9}$$

Using the instantaneous change of variables formula (Chen et al., 2018), the log-likelihood of $p_0(\mathbf{x})$ can be computed as:

$$\log p_0(\mathbf{x}(0)) = \log p_T(\mathbf{x}(T)) + \int_0^T \nabla \cdot \tilde{\mathbf{f}}_\theta(\mathbf{x}(t), t) \, dt, \tag{10}$$

where the random variable $\mathbf{x}(t)$ as a function of t is obtained by solving the ODE in Eq. 9.

However, this estimation method has a limitation: extreme differences in log-likelihood values lead to highly imbalanced sample weights, failing to reflect the **relative magnitudes** of densities among different samples globally. Because the log-likelihood strictly follows the functional form of the original data distribution, it leads to explicit numerical differences. When only a few data points have significantly high probability densities, their log-likelihoods become much higher than those of other samples. Using these likelihoods to compute sample weights causes high-density samples to disproportionately overshadow others, whether those have low or moderately high densities. This

imbalance diminishes distinctions among samples outside the highest-density regions, reducing the ultimate training on the remaining samples to an unweighted process without clear density differentiation. To validate this, we visualize the probability density using log-likelihood on a synthetic dataset in Section 4.6. In summary, although log-likelihood faithfully reflects the original density, it does not meet the requirement for global relative density comparison needed for sample reweighting.

3.3.2 DATA DENSITY ESTIMATION VIA SIMILARITY DIFFERENCE MEASURE

Because the exact log-likelihood is unsuitable for sample reweighting, we adopt an alternative measure for global density modeling. As discussed in Section 1, we estimate the relative probability density by measuring similarities between the scores of noisy points. According to the forward process in Eq. 5, a clean point z_0 transforms into a noisy point z_t by adding noise scaled by $\sigma(t)$. This mirrors the scenario depicted in Figure 2, where point A moves to its noisy neighbor A_i'. The vector $\overrightarrow{AA_i'}$ corresponds to $\sigma(t)\varepsilon$, and its length $|\overrightarrow{AA_i'}|$ represents the magnitude of the added noise $\|\sigma(t)\varepsilon\|_2$. To sample a neighborhood of noisy points around a data point z_i, we select T fixed timesteps $t_0, t_1, \ldots, t_{T-1}$ and add noise as per Eq. 5. Repeating this process K times yields $T \times K$ noisy points. We then estimate the relative probability density using these points, employing the squared error as the similarity metric. For a sample z_i and a preconditioned network F_θ, we compute the aggregated similarity, i.e., the average similarity across several noise scales, as:

$$\text{Sim}(z_i; F_\theta) = \frac{1}{K} \sum_{k=1}^{K} \mathbb{E}_t \left[\lambda(t) \left\| D_\theta(z_i + \sigma(t)\varepsilon, t) - z_i \right\|_2^2 \right]. \tag{11}$$

The key difference between Eq. 8 and Eq. 11 is that $\text{Sim}(z_i; F_\theta)$ samples only from specific fixed and sparse timesteps, accounting for different noise scales. Moreover, we randomly sample these timesteps multiple times and average the results to obtain a robust similarity measure.

Using Eq. 11, we compute the aggregated similarity across all training data points to indicate their densities. However, in addition to shifts in latent covariates x, y-shift also commonly occurs in real-world data. To address this, we model the data distribution for each class separately (see Section 3.2) and use the difference in aggregated similarities as a proxy for the final relative probability density. For example, for a data point z_i with class label y_{z_i}, we compute $\text{SimDiff}(z_i)$ as:

$$\text{SimDiff}(z_i) = \text{Sim}(z_i; F_{y \neq y_{z_i}}) - \text{Sim}(z_i; F_{y = y_{z_i}}). \tag{12}$$

$\text{Sim}(\cdot)$ allows us to differentiate the densities of samples within a specific class, where a larger $\text{Sim}(\cdot)$ indicates a lower density. The $\text{SimDiff}(\cdot)$ measure further accounts for distribution shifts in the label y while preserving the properties of $\text{Sim}(\cdot)$ that reflect $p(z)$. When the number of training samples for a given class y_k is small, $\text{Sim}(\cdot; F_{y=y_k})$ increases because the score model $F_{y=y_k}$ is trained on a narrower and less comprehensive data space. Consequently, $F_{y=y_k}$ finds it more challenging to guide noisy points back to their original locations via score fields, leading to higher estimation errors in $\text{Sim}(\cdot; F_{y=y_k})$. The subtraction operation thus causes samples from the minority class to have a lower $\text{SimDiff}(\cdot)$ compared to those from the majority class. In this way, SimDiff captures both covariate distribution shifts in $p(x)$ ($p(z)$) via $\text{Sim}(\cdot)$ and label distribution shifts in $p(y)$ through the subtraction operation, providing a means to indicate relative probability density.

In summary, a lower $\text{SimDiff}(\cdot)$ indicates a lower probability density. Whether the imbalance arises from covariates x or labels y, $\text{SimDiff}(\cdot)$ consistently and faithfully reflects the relative probability density. The whole computation process requires no prior information or predefined boundaries.

3.4 UNBIASED LEARNING ON DISTRIBUTION-BALANCED DATA

Our ultimate goal is achieving the robustness for all sensitive covariates x. The implicit joint distribution on latent representation z has been modeled in Section 3.2 and Section 3.3 through score models. Therefore, we could conduct sample reweighting guided by Eq. 12 directly to acquire an overall unbiased training distribution. Each z_i is assigned a weight w_i through

$$w_i = \frac{\exp(-\text{SimDiff}(z_i)/\tau)}{\sum_{j=0}^{N-1} \exp(-\text{SimDiff}(z_j)/\tau)}, \tag{13}$$

where N is the number of all training samples and τ denotes a temperature which controls the scale of reweighting. Finally, we train an unbiased classification model ψ as:

$$\mathcal{L}_{\text{classification}} = \mathbb{E}_{(z_i, y_i)}[w_i \ell(\psi(z_i), y_i)], \tag{14}$$

where ℓ stands for cross entropy loss. When testing, we only use ϕ_{Enc} and ψ to make predictions.

4 EXPERIMENT

To evaluate the effectiveness of our method, we conduct extensive experiments in various settings.

4.1 DATASETS

To comprehensively validate our method, we selected six diverse datasets that exhibit various types of distribution shifts, including covariate shifts and concept shifts.

The details of our used datasets are as follows:

- **Adult** (Becker & Kohavi, 1996): The classification goal is to predict whether income exceeds \$50K/yr based on census data.

- **Bank** (Moro et al., 2012): The data is related with direct marketing campaigns of a Portuguese banking institution. The task is to predict if the client will subscribe a term deposit.

- **Default** (Yeh, 2016): This dataset aims at the case of customers' default payments in Taiwan. The task is to predict whether the client will default payment next month.

- **Shoppers** (Sakar & Kastro, 2018): The task is to predict if the user's session ends with the shopping behavior. The distribution shift mainly demonstrates as y-shift: About 84.5% samples were class samples that did not end with shopping, and the rest were positive class samples.

- **Taxi** (Navas, 2018): This dataset collects some information about the pickup and dropoff of taxi rides. The task is to predict whether the total ride duration time exceeds 30 minutes. We choose the data collected in Mexican City.

- **US-Wide ACS PUMS Data** (Ding et al., 2021): This large dataset contains individual records from US Census sources. We choose the task where the outcome is whether an individual's income exceeds 50k. The performance is validated separately on three randomly chosen states.

Specifically, for the Taxi and ACS datasets, we followed the preprocessing guidelines outlined in the `WhyShift` benchmark (Liu et al., 2024).

4.2 EVALUATION METRICS

Our objective is to ensure that the model consistently makes robust predictions across all non-causal covariates, rather than focusing on a single one. For each dataset, we select several deterministic non-causal attributes based on prior knowledge—for example, sex and race in the ACS income dataset. We then record the worst-case prediction results for each feature and compute the mean of the worst-group accuracies across these features. Details of the selected features are provided in Appendix A.5. Additionally, we track the mean accuracy for these features. We aim for our model to enhance the average worst-group performance without significantly compromising mean accuracy.

4.3 IMPLEMENTATION DETAILS

We conducted each experiment three times with different random seeds and report the mean results in Table 1 and Table 2. The corresponding standard deviations are provided in Appendix A.3. Our prediction model consists of two components: a Variational AutoEncoder (VAE) for generating latent representations, and a MultiLayer Perceptron (MLP) for classification. Both our method and the baseline models utilize the same architecture. For training the VAE, we followed the default settings described in TabSyn (Zhang et al., 2024c).

In addition, our method involves training score models. Following the guidance from TabSyn, we use a 4-layer MLP architecture as the backbone for our score models. We also adopt the training paradigm from EDM (Karras et al., 2022), which mitigates the influence of varying noise scales on neural network training. The noise scale is set to increase linearly with time, i.e., $\sigma(t) = t$, where t follows a log-normal distribution, resulting in $\ln(\sigma(t)) \sim \mathcal{N}(P_{\text{mean}}, P_{\text{std}}^2)$. The P_{mean} and P_{std} are set to -1.2 and 1.2, respectively. When computing aggregated similarity in Eq. 11, we choose 0.002 and 80 as the minimum and maximum values of t and select T timesteps with equal intervals between them. Regarding hyperparameter selection, we set T to 10 and τ to 3 for all experiments.

Methods	Adult		Bank		Default		Shoppers		Taxi		Average	
	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst
ERM	71.30	48.18	70.23	40.13	62.98	36.12	77.12	53.91	67.53	59.48	69.83	47.56
CVaR-DRO	71.95	49.02	68.93	38.71	62.43	34.60	76.65	51.26	65.55	54.51	69.10	45.62
χ^2-DRO	71.85	50.09	70.88	40.04	62.03	34.16	76.95	52.40	68.27	62.43	70.00	47.83
KL-DRO	**74.33**	49.17	69.95	39.89	59.03	19.39	79.53	59.74	62.30	47.93	69.03	43.22
EIIL	69.37	38.97	61.85	21.69	**65.05**	28.91	74.82	46.18	**69.52**	58.00	68.12	38.75
JTT	71.46	49.93	68.78	37.77	62.47	35.51	78.10	52.59	67.47	60.01	69.65	47.16
FAM	72.85	49.59	**71.03**	41.09	62.50	37.12	76.60	53.51	67.90	62.24	70.18	48.71
SRDO	71.27	46.44	66.34	32.08	62.38	33.34	76.24	53.11	64.57	58.18	68.16	44.63
Ours	**74.33**	**54.79**	69.50	**41.28**	62.62	**38.78**	**79.68**	**60.73**	67.85	**63.14**	**70.80**	**51.74**

Table 1: The classification results on five datasets which exhibit various kinds of distribution shifts. The **bold** and underline denote the best and the second best results respectively.

4.4 COMPARED BASELINES

As referred in Section 4.2, our goal is to enhance overall robustness, with the accuracy on the worst group serving as our main evaluation metric. Therefore, we compare our method with several robust machine learning techniques, including **ERM** (Vapnik, 1999), **CVaR-DRO** (Levy et al., 2020), χ^2**-DRO** (Levy et al., 2020), **KL-DRO** (Duchi & Namkoong, 2021), **JTT** (Liu et al., 2021a), **EIIL** (Creager et al., 2021), **FAM** (Petzka et al., 2021; Zou et al., 2024) and **SRDO** (Shen et al., 2020). Among these, CVaR-DRO, χ^2-DRO, KL-DRO, JTT, and SRDO employ reweighting processes similar to ours, while EIIL and FAM enhance robustness by adding regularization terms.

4.5 CLASSIFICATION RESULTS

4.5.1 ROBUSTNESS ACROSS VARIOUS DISTRIBUTION SHIFTS

We first demonstrate the effectiveness of our method under various types of distribution shifts in Table 1. Our method consistently achieves the highest worst-case accuracy across all five datasets, with an average improvement of at least 3% in worst-case accuracy over all baseline methods. Additionally, it attains the best mean accuracy on two of the five datasets, highlighting its ability to enhance robustness without a significant reduction in overall prediction accuracy.

In contrast, DRO-based methods like KL-DRO perform inconsistently on our datasets. For instance, while KL-DRO achieves the second-best accuracy on the Shoppers dataset, its performance deteriorates significantly on Default and Taxi. This inconsistency stems from KL-DRO's reliance on expanding the search space without adequately modeling the underlying data distribution.

Another popular invariant learning-based method, EIIL (Creager et al., 2021), achieves high mean accuracy. However, its worst-case accuracy is relatively disappointing compared to other methods. EIIL divides samples into different groups based on generated environment labels, which creates implicit boundaries based on data's inherent characteristics. While this boundary-based approach may improve overall accuracy by exploiting data biases, it undermines the balance and robustness required to handle sensitive non-causal attributes.

Compared to the above methods which rely on either prior information or boundaries, our method could achieve consistent and stable robustness on these datasets. The results demonstrate the benefit of modeling relative probability density as referred in Section 1.

4.5.2 GENERALIZATION CAPABILITY UNDER SELECTION BIAS

We further validate the generalization capability of our method with the ACS Income dataset. The key objective is to assess whether our model can learn a robust predictive function from a single source environment that generalizes well to others. We randomly select three geographically distant states in the U.S. and train classification models separately on data from each state.

The second to ninth columns of Table 2 show the results when the model is tested on data from its source state. We then evaluate each model on data from another state in a round-robin manner, with the results recorded in the tenth to last column. The observations are as follows:

Methods	AZ		MA		MI		Average		AZ → MA		MA → MI		MI → AZ		Average	
	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst
ERM	76.95	64.07	78.18	**74.05**	73.70	62.42	75.83	66.04	73.05	57.82	74.28	67.78	72.38	56.77	73.23	60.79
CVaR-DRO	**77.00**	64.41	77.85	72.85	73.48	61.88	76.11	66.39	74.10	59.42	74.85	68.57	71.75	54.67	73.57	60.88
χ^2-DRO	76.95	64.07	77.55	71.82	73.13	59.03	75.88	64.97	74.53	61.18	74.23	68.53	71.33	53.05	73.36	60.92
KL-DRO	75.68	60.98	78.23	71.22	**76.10**	62.88	76.67	65.03	74.20	57.78	75.35	68.72	74.73	57.20	74.76	61.23
EIIL	74.98	55.22	78.18	68.42	75.60	63.77	76.25	62.47	**75.35**	56.80	**76.92**	65.62	**74.78**	57.32	**75.68**	59.91
JTT	75.70	57.73	77.48	68.48	74.48	60.63	75.88	62.28	73.90	55.17	74.00	66.57	72.65	55.17	73.52	58.97
FAM	75.00	57.82	**78.73**	70.12	74.38	59.45	76.03	62.46	72.93	54.60	74.68	66.35	73.40	54.53	73.67	58.49
SRDO	75.17	60.03	77.85	69.52	73.30	54.63	75.44	61.39	74.00	58.37	74.78	61.77	73.83	60.05	74.39	60.07
Ours	76.28	**66.42**	78.35	73.33	75.53	**67.10**	**76.72**	**68.95**	75.00	62.85	74.75	68.75	74.73	64.10	74.83	**65.23**

Table 2: The performance on ACS Income task. The **bold** and underline denote the best and the second best results respectively.

- For the single-source data experiments (Columns 2 to 10), our method achieves both higher mean accuracy and worst-case accuracy compared to most baselines. This consistency with the results in Table 1 supports the robustness of our approach.

- For the generalization experiment on different-source data (Columns 11 to 19), our method does not achieve the highest mean accuracy. This is due to the change in causal mechanisms across states (Liu et al., 2024), leading to variations in the predictive mechanism. However, our method still achieves strong worst-case accuracy, thanks to our modeled relative probability density. Our training process ensures fair treatment of covariates through score-based similarity, which is more reliable than the distances or boundaries employed by other methods.

4.6 VISUALIZATION OF SCORE-SIMILARITY-BASED WEIGHTS

In this section, we provide the visualization results on a synthetic dataset to directly explain the reweighting process of our methods. In addition, we will explain why we use our aggregated similarity difference measure in Eq. 12 instead of running a sampler based on the probability flow ordinary differential equation that allow for exact likelihood computation proposed by Song et al..

Synthetic Data Generation. Our imbalanced synthetic training data has been illustrated in Figure 1a. The data have two features, x_0 and x_1. The perfect classification boundary is a sine curve. We introduce the bias on training data by sampling more points in regions where $x_0 \in [\frac{\pi}{4}, \frac{3\pi}{4}] \cup [\frac{5\pi}{4}, \frac{7\pi}{4}]$. We expect the reweighting process could make the whole data distribution fairly balanced.

Exact Likelihood Computation by Probability Flow ODE. As referred in Section 3.3, we can compute the exact log-likelihood through a probability flow ODE in Eq. 10. Following Song et al., we apply the Skilling-Hutchinson trace estimator (Skilling, 1989; Hutchinson, 1990) to estimate $\nabla \cdot \tilde{\mathbf{f}}_\theta(\mathbf{x}(t), t)$ and finally achieves the log-likelihood.

Extreme Value Problem Brought by Exact Likelihood. The log-likelihood of $p(\mathbf{x})$ represents the estimated probability density at the feature level, making it useful for guiding the reweighting process. We compute the mean of the estimated probabilities across all features to determine the final sample-level probability density. In Figure 3a, color depth represents the log-likelihood of the predicted probability density. Points with higher density are shaded closer to violet, while those with lower density appear more blue. Interestingly, not all points in high-probability regions are assigned warm colors. In fact, most points are blue, similar to those in low-density regions. Only a few points located at cluster centers exhibit significantly higher log-likelihoods. Reweighting based on these estimates could lead to disproportionate emphasis on a small number of extreme high-density points, potentially obscuring the distinction between other high- and low-probability regions.

Density-Aware Weights Computed from Our Similarity-based Measure. We then visualize the unnormalized score similarity in Figure 3b. Points with lower error, corresponding to higher relative probability density, are shaded in blue and are expected to be downweighted. The visualization clearly distinguishes these points, with two regions of relatively high probability density appearing in blue. In contrast, points with truly low probability are represented by higher aggregated error, shown in purple, and can be easily upweighted. Our similarity measure not only differentiates density clearly but also maintains a consistent and stable numerical range, making it suitable for sample reweighting.

(a) Computed log likelihood of $p(\mathbf{x})$ (b) Score similarity as proxy

Figure 3: Our score similarity is a good proxy for density.

Figure 4: Ablation study on temperature of reweighting scale τ. Our method is insensitive to τ.

	$T = 5$		$T = 10$		$T = 15$		$T = 20$	
	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst
Acc. (%)	$73.27_{\pm 0.84}$	$50.82_{\pm 3.17}$	$74.33_{\pm 0.28}$	$54.79_{\pm 2.01}$	$74.92_{\pm 0.52}$	$56.90_{\pm 1.51}$	$74.91_{\pm 0.52}$	$57.46_{\pm 2.48}$

Table 3: Ablation studies of the number of chosen timesteps T on Adult dataset.

In summary, compared to the exact log-likelihood calculation, our method more effectively captures relative probability densities across the dataset. By computing similarity, any two sample points with significantly different probability densities are clearly distinguished and distinctly colored. In contrast, the exact log-likelihood tends to overemphasize a few high-density points, obscuring the distinction between other high- and low-density samples.

4.7 ABLATION STUDIES

We conduct the sensitivity analysis in this section. As referred in Algorithm 1, our method has three hyperparameters. T denotes the number of selected timesteps for computing aggregation similarity. τ controls the strength of reweighting based on SimDiff($\cdot$). K represents the number of repeated sampling iterations for computing scores. The discussion on K is deferred to Appendix A.4, as it does not functionally impact the score computation.

The ablation study results of T on Adult are shown in Table 3. There are two main observations:

- The mean accuracy shows minimal variation with changes in T.
- The worst-case accuracy improves as T increases. This is because T indirectly represents the number of aggregated noisy points in the sampled neighborhood. A larger T leads to a more accurate computation of aggregated similarity in Eq. 11. We set the default value of T to 10, balancing fast computation with optimal performance.

In Figure 4, we show the classification results by using different τ. Our model performs consistently well with all the values. The worst accuracies under different τ all surpass the baseline methods in Table 1, which proves that our method does not heavily rely on the values of hyperparameters.

5 CONCLUSION

In this paper, we tackle the challenge of improving model robustness, measured across all non-causal covariates rather than focusing on a single attribute. We observe that previous methods are limited by their inability to model the original joint data distribution and apply effective balancing strategies. To overcome these limitations, we propose using score-based models to capture the latent data distribution. Specifically, we estimate scores at several fixed timesteps and use their similarity to model the relative probability density of each sample. A score-based reweighting strategy is then employed to train a robust classification model. Our approach requires no prior information during training and ensures that the reweighting process aligns with the original data distribution. Experiments on seven datasets demonstrate that our method effectively balances the original training data globally and achieves robust performance under distribution shifts.

REFERENCES

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Barry Becker and Ronny Kohavi. Adult. UCI Machine Learning Repository, 1996. DOI: https://doi.org/10.24432/C5XW20.

Ricky TQ Chen, Yulia Rubanova, Jesse Bettencourt, and David K Duvenaud. Neural ordinary differential equations. In *Advances in neural information processing systems*, pp. 6571–6583, 2018.

Sungha Choi, Sanghun Jung, Huiwon Yun, Joanne T. Kim, Seungryong Kim, and Jaegul Choo. Robustnet: Improving domain generalization in urban-scene segmentation via instance selective whitening. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 11580–11590, June 2021.

Elliot Creager, Jörn-Henrik Jacobsen, and Richard Zemel. Environment inference for invariant learning. In *International Conference on Machine Learning*, 2021.

Patrick Dendorfer, Sven Elflein, and Laura Leal-Taixé. Mg-gan: A multi-generator model preventing out-of-distribution samples in pedestrian trajectory prediction. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 13158–13167, October 2021.

Frances Ding, Moritz Hardt, John Miller, and Ludwig Schmidt. Retiring adult: New datasets for fair machine learning. *Advances in neural information processing systems*, 34:6478–6490, 2021.

John C Duchi and Hongseok Namkoong. Learning models with uniform performance via distributionally robust optimization. *The Annals of Statistics*, 49(3):1378–1406, 2021.

Yihong Gu, Cong Fang, Peter Bühlmann, and Jianqing Fan. Causality pursuit from heterogeneous environments via neural adversarial invariance learning. *arXiv preprint arXiv:2405.04715*, 2024.

Irina Higgins, Loic Matthey, Arka Pal, Christopher P Burgess, Xavier Glorot, Matthew M Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. *ICLR (Poster)*, 3, 2017.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Michael F Hutchinson. A stochastic estimator of the trace of the influence matrix for Laplacian smoothing splines. *Communications in Statistics-Simulation and Computation*, 19(2):433–450, 1990.

Maximilian Ilse, Jakub M. Tomczak, Christos Louizos, and Max Welling. Diva: Domain invariant variational autoencoders. In Tal Arbel, Ismail Ben Ayed, Marleen de Bruijne, Maxime Descoteaux, Herve Lombaert, and Christopher Pal (eds.), *Proceedings of the Third Conference on Medical Imaging with Deep Learning*, volume 121 of *Proceedings of Machine Learning Research*, pp. 322–348. PMLR, 06–08 Jul 2020. URL https://proceedings.mlr.press/v121/ilse20a.html.

Zahra Kadkhodaie, Florentin Guth, Eero P Simoncelli, and Stéphane Mallat. Generalization in diffusion models arises from geometry-adaptive harmonic representations. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=ANvmVS2Yr0.

Tero Karras, Miika Aittala, Timo Aila, and Samuli Laine. Elucidating the design space of diffusion-based generative models. *Advances in neural information processing systems*, 35:26565–26577, 2022.

Daniel Levy, Yair Carmon, John C Duchi, and Aaron Sidford. Large-scale methods for distributionally robust optimization. *Advances in Neural Information Processing Systems*, 33:8847–8860, 2020.

Daiqing Li, Junlin Yang, Karsten Kreis, Antonio Torralba, and Sanja Fidler. Semantic segmentation with generative models: Semi-supervised learning and strong out-of-domain generalization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 8300–8311, June 2021.

Evan Z Liu, Behzad Haghgoo, Annie S Chen, Aditi Raghunathan, Pang Wei Koh, Shiori Sagawa, Percy Liang, and Chelsea Finn. Just train twice: Improving group robustness without training group information. In *International Conference on Machine Learning*, pp. 6781–6792. PMLR, 2021a.

Jiashuo Liu, Zheyuan Hu, Peng Cui, Bo Li, and Zheyan Shen. Heterogeneous risk minimization. In *International Conference on Machine Learning*, pp. 6804–6814. PMLR, 2021b.

Jiashuo Liu, Zheyuan Hu, Peng Cui, Bo Li, and Zheyan Shen. Kernelized heterogeneous risk minimization. *arXiv preprint arXiv:2110.12425*, 2021c.

Jiashuo Liu, Tianyu Wang, Peng Cui, and Hongseok Namkoong. On the need for a language describing distribution shifts: Illustrations on tabular datasets. *Advances in Neural Information Processing Systems*, 36, 2024.

S. Moro, P. Rita, and P. Cortez. Bank Marketing. UCI Machine Learning Repository, 2012. DOI: https://doi.org/10.24432/C5K306.

Junhyun Nam, Hyuntak Cha, Sungsoo Ahn, Jaeho Lee, and Jinwoo Shin. Learning from failure: De-biasing classifier from biased classifier. *Advances in Neural Information Processing Systems*, 33:20673–20684, 2020.

Mario Navas. Taxi routes of mexico city, quito and more, 2018. URL https://www.kaggle.com/datasets/mnavas/taxi-routes-for-mexico-city-and-quito.

Philipp Oberdiek, Gernot Fink, and Matthias Rottmann. Uqgan: A unified model for uncertainty quantification of deep classifiers trained via conditional gans. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 21371–21385. Curran Associates, Inc., 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/8648e249887ccb0fe8c067d596e35b40-Paper-Conference.pdf.

Henning Petzka, Michael Kamp, Linara Adilova, Cristian Sminchisescu, and Mario Boley. Relative flatness and generalization. In *Advances in Neural Information Processing Systems*, volume 34. Curran Associates, Inc., 2021.

Shikai Qiu, Andres Potapczynski, Pavel Izmailov, and Andrew Gordon Wilson. Simple and Fast Group Robustness by Automatic Feature Reweighting. *International Conference on Machine Learning (ICML)*, 2023.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 10684–10695, 2022.

Shiori Sagawa*, Pang Wei Koh*, Tatsunori B. Hashimoto, and Percy Liang. Distributionally robust neural networks. In *International Conference on Learning Representations*, 2020.

C. Sakar and Yomi Kastro. Online Shoppers Purchasing Intention Dataset. UCI Machine Learning Repository, 2018. DOI: https://doi.org/10.24432/C5F88Q.

Xinwei Shen, Peter Bühlmann, and Armeen Taeb. Causality-oriented robustness: exploiting general additive interventions. *arXiv preprint arXiv:2307.10299*, 2023.

Zheyan Shen, Peng Cui, Tong Zhang, and Kun Kunag. Stable learning via sample reweighting. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 5692–5699, 2020.

John Skilling. The eigenvalues of mega-dimensional matrices. In *Maximum Entropy and Bayesian Methods*, pp. 455–466. Springer, 1989.

Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. *Advances in Neural Information Processing Systems*, 32, 2019.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=PxTIG12RRHS.

Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In *European conference on computer vision*, pp. 443–450. Springer, 2016.

Yunze Tong, Junkun Yuan, Min Zhang, Didi Zhu, Keli Zhang, Fei Wu, and Kun Kuang. Quantitatively measuring and contrastively exploring heterogeneity for domain generalization. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, KDD '23. ACM, August 2023. doi: 10.1145/3580305.3599481. URL http://doi.org/10.1145/3580305.3599481.

Laurens Van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *Journal of machine learning research*, 9(11), 2008.

Vladimir N Vapnik. An overview of statistical learning theory. *IEEE transactions on neural networks*, 10(5):988–999, 1999.

Yilun Xu, Ziming Liu, Max Tegmark, and Tommi Jaakkola. Poisson flow generative models. *arXiv preprint arXiv:2209.11178*, 2022.

Yilun Xu, Shangyuan Tong, and Tommi S. Jaakkola. Stable target field for reduced variance score estimation in diffusion models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=WmIwYTd0YTF.

I-Cheng Yeh. Default of Credit Card Clients. UCI Machine Learning Repository, 2016. DOI: https://doi.org/10.24432/C55S3H.

Fengda Zhang, Kun Kuang, Long Chen, Yuxuan Liu, Chao Wu, and Jun Xiao. Fairness-aware contrastive learning with partially annotated sensitive attributes. In *The Eleventh International Conference on Learning Representations*, 2022.

Fengda Zhang, Qianpei He, Kun Kuang, Jiashuo Liu, Long Chen, Chao Wu, Jun Xiao, and Hanwang Zhang. Distributionally generative augmentation for fair facial attribute classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 22797–22808, 2024a.

Fengda Zhang, Zitao Shuai, Kun Kuang, Fei Wu, Yueting Zhuang, and Jun Xiao. Unified fair federated learning for digital healthcare. *Patterns*, 5(1), 2024b.

Hengrui Zhang, Jiani Zhang, Balasubramaniam Srinivasan, Zhengyuan Shen, Xiao Qin, Christos Faloutsos, Huzefa Rangwala, and George Karypis. Mixed-type tabular data synthesis with score-based diffusion in latent space. In *The twelfth International Conference on Learning Representations*, 2024c.

Xingxuan Zhang, Peng Cui, Renzhe Xu, Linjun Zhou, Yue He, and Zheyan Shen. Deep stable learning for out-of-distribution generalization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 5372–5382, 2021.

Yingtian Zou, Kenji Kawaguchi, Yingnan Liu, Jiashuo Liu, Mong-Li Lee, and Wynne Hsu. Towards robust out-of-distribution generalization bounds via sharpness. *arXiv preprint arXiv:2403.06392*, 2024.

A APPENDIX

The supplementary materials are structured as follows:

- Appendix A.1 provides the pseudocode of our method.
- Appendix A.2 details the default network preconditioning, following the practice of EDM (Karras et al., 2022).
- Appendix A.3 presents the standard deviations of our experiments.
- Appendix A.4 offers a sensitivity analysis of hyperparameter K.
- Appendix A.5 lists the selected non-causal attributes used for robustness evaluation.
- Appendix A.6 conducts the analysis on sample size's influence on our method.
- Appendix A.7 investigates how our method balances the imbalanced real-world dataset.
- Appendix A.8 provides the visualization results of our score-based weights on real-world dataset.
- Appendix A.9 compares our method with stable learning-based methods.

A.1 THE PSEUDOCODE OF OUR METHOD

Algorithm 1 The pseudocode of our method in binary classification problem.

Input: Training dataset $\mathcal{D} = \{x, y\} = \{x_i, y_i\}_{i=0}^{N-1}$, T fixed noises along with specific timesteps $\{\sigma(t)\}_T$, the temperature of the reweighting scale τ, the repeated sampling times K
Parameters to be optimized: a VAE $\phi_{\mathcal{Z}}(\cdot)$, two score-based models $\{s_j(\cdot, \cdot)\}, j \in \{0, 1\}$, a final classification model $\psi(\cdot)$

    // Stage One: Training Distribution Modeling
    Train a VAE $\phi_{\mathcal{Z}} = \phi_{Enc} \cdot \phi_{Dec}$ with Eq. 4
    Obtain latent representation with trained encoder: $z = \phi_{Enc}(x)$
    Separate z into $z_{y=0}$ and $z_{y=1}$ according to their labels, train score model s_j with z_j separately
    by Eq. 8
    // Stage Two: Probability Density Aligning
    For each latent $z_i \in z$, compute the aggregated similarity with target class model $\text{Sim}(z_i; s_{y=y_{z_i}})$
    and with non-target class model $\text{Sim}(z_i; s_{y \neq y_{z_i}})$ through Eq. 11
    Compute $\text{SimDiff}(z_i)$ through Eq. 12 to indicate z_i's relative probability density
    // Stage Three: Unbiased Learning on Distribution-balanced Data
    Reflect SimDiff into weights w_i through Eq. 13
    Train the final unbiased classification model ψ with Eq. 14
    Return ϕ_{Enc} and ψ for testing

A.2 THE CHOICE OF NETWORK PRECONDITIONING

In our method, we follow the practice from EDM (Karras et al., 2022) to train our neural network. The key lies in using preconditioning techniques to make the output of neural network stable, instead of varying with the scale of variance $\sigma(t)\varepsilon$. We take the default choice of scaling factors from Karras et al.; Zhang et al.. The details are listed in Table 4[1].

Skip scaling $c_{\text{skip}}(\sigma)$	$\sigma_{\text{data}}^2/(\sigma^2 + \sigma_{\text{data}}^2)$
Output scaling $c_{\text{out}}(\sigma)$	$\sigma \cdot \sigma_{\text{data}}/\sqrt{\sigma_{\text{data}}^2 + \sigma^2}$
Input scaling $c_{\text{in}}(\sigma)$	$1/\sqrt{\sigma^2 + \sigma_{\text{data}}^2}$
Noise cond. $c_{\text{noise}}(\sigma)$	$\frac{1}{4}\ln(\sigma)$

Table 4: The choices of various scaling factors for denoiser $D_\theta(\cdot, \cdot)$ in Eq. 7.

---

[1]We set $\sigma_{\text{data}} = 0.5$ in our experiment as TabSyn (Zhang et al., 2024c) did.

A.3 DETAILS OF THE STANDARD DEVIATION OF OUR EXPERIMENTS

We randomly conducted each experiment three times using different seeds and computed the mean classification results, as shown in Tables 1 and 2. The standard deviation across these three runs is provided in Tables 5 and 6, respectively.

Methods	Adult		Bank		Default		Shoppers		Taxi	
	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst
ERM	0.47	1.64	0.35	1.85	0.21	3.93	0.73	2.46	0.14	2.61
CVaR-DRO	0.68	2.63	1.52	3.59	0.33	2.44	0.31	2.01	2.00	5.93
χ^2-DRO	0.73	1.78	0.81	3.56	0.19	2.12	1.72	3.60	0.99	1.08
KL-DRO	0.14	0.90	0.60	1.75	3.25	5.10	1.08	3.98	8.96	23.68
EIIL	2.50	8.15	2.49	6.91	1.06	7.55	7.04	15.02	0.07	4.43
JTT	1.89	3.65	0.67	1.50	0.90	1.58	0.75	3.35	0.42	2.60
FAM	1.65	1.95	3.89	5.25	0.19	2.07	0.09	2.05	0.75	0.63
SRDO	2.43	6.82	2.55	5.44	8.06	10.94	0.35	2.31	2.07	2.50
Ours	0.28	2.01	0.39	1.56	0.12	1.22	1.44	3.39	0.16	2.02

Table 5: The standard deviation of the classification results across three runs on five datasets.

Methods	AZ		MA		MI		AZ $\to$ MA		MA $\to$ MI		MI $\to$ AZ	
	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst
ERM	0.85	1.31	0.46	1.23	0.49	2.66	0.78	1.62	0.32	2.50	0.67	1.82
CVaR-DRO	0.14	3.70	1.27	1.88	0.74	4.97	0.35	2.51	0.14	0.65	0.28	2.55
χ^2-DRO	0.14	4.60	0.92	1.58	1.38	2.06	0.25	1.15	0.18	0.67	0.60	1.76
KL-DRO	1.23	3.00	0.32	2.41	0.07	0.37	1.20	2.91	0.78	1.71	0.25	0.97
EIIL	1.80	6.65	0.67	5.86	0.49	3.19	1.70	5.52	1.59	5.88	1.51	4.95
JTT	1.06	2.49	0.25	2.70	0.53	1.84	0.78	3.14	0.28	2.33	0.35	0.62
FAM	0.57	2.17	0.03	3.33	2.09	6.29	0.53	2.45	0.11	2.44	1.27	5.24
SRDO	2.22	10.23	1.01	2.49	1.22	5.75	1.83	8.57	0.49	4.26	0.35	0.96
Ours	0.11	0.89	0.14	1.48	1.77	1.61	0.07	0.40	0.35	0.30	0.35	0.35

Table 6: The standard deviation of the classification results across three runs on ACS dataset.

A.4 THE ABLATION STUDIES OF REPEATED SAMPLING TIMES

In Section 4.7, we conduct sensitivity analysis on the number of selected timesteps T and the temperature τ, which controls the reweighting scale. These two hyperparameters directly influence score computation. Additionally, we have another hyperparameter, K, which governs the number of repeated sampling iterations. While K does not functionally affect score computation, it impacts the robustness of our computed values. Therefore, we will analyze the effect of K independently in this section to distinguish it from T and τ.

K	Mean (%)	Worst (%)	Running Time (s)
8	73.97 $_{\pm 0.50}$	52.47 $_{\pm 0.71}$	7.35 $_{\pm 0.01}$
16	74.13 $_{\pm 0.67}$	54.18 $_{\pm 1.90}$	14.28 $_{\pm 1.50}$
32	74.33 $_{\pm 0.28}$	54.79 $_{\pm 2.01}$	25.32 $_{\pm 0.01}$
48	75.29 $_{\pm 0.40}$	56.28 $_{\pm 1.46}$	38.48 $_{\pm 2.33}$

Table 7: Ablation studies of the repeated sampling iterations K on Adult dataset.

The experimental results are listed in Table 7. We could find larger K corresponds to a longer computation time and a more stable performance. We choose 32 as the default value for K, which achieves a good trade-off between sampling time and model performance.

A.5 DETAILS OF THE SELECTED NON-CAUSAL ATTRIBUTES FOR MEASURING OVERALL ROBUSTNESS

As referred in Section 4.2, we measure overall robustness by selecting several non-causal attributes and recording their worst-case prediction results. Here we provide the details of selected attributes.

- **Adult** (Becker & Kohavi, 1996): We select marital status, race, and sex as sensitive attributes.
- **Bank** (Moro et al., 2012): We select age, housing status, marital status, and the last contact duration as sensitive attributes.
- **Default** (Yeh, 2016): We select age, sex, and the amount of the given credit as sensitive attributes.
- **Shoppers** (Sakar & Kastro, 2018): We select the traffic type, the visitor type as returning or new visitor, a Boolean feature indicating whether the date of the visit is weekend as sensitive attributes.
- **Taxi** (Navas, 2018): We select the indicator for weekday, the month of picking up, and the direction as sensitive attributes.
- **US-Wide ACS PUMS Data** (Ding et al., 2021): We select race and sex as sensitive attributes.

We demonstrate the Pearson correlation coefficients between the attributes and target vairable in training and test data in Table 8.

Dataset	Attribute	Pearson Coefficient	
		train	test
Adult	marital status	-0.0345	-0.0287
	race	-0.0852	-0.0807
	sex	0.0785	0.0700
	native country	0.3872	0.3915
	work class	-0.2160	-0.2119
Default	age	0.0193	0.0224
	sex	-0.0396	-0.0430
	given credit	-0.0368	-0.0287
	education	-0.1407	-0.1365
	payment	0.3297	0.2814
Shoppers	traffic type	-0.0548	-0.0644
	visitor type	-0.0276	-0.0353
	weekend	0.0277	0.0445
	administrative	0.1422	0.1401
	administrative duration	-0.1042	-0.1030
ACS Income (MA)	race	-0.1030	-0.1486
	sex	0.1435	0.1086
	marital status	0.2925	0.2704
	age	0.2748	0.2560

Dataset	Attribute	Pearson Coefficient	
		train	test
Taxi	weekday	0.0200	-0.0169
	month	-0.0004	-0.0243
	direction	0.0180	0.0754
	distance	0.4501	0.4618
	hour	0.0413	0.1220
Bank	age	-0.0086	-0.0130
	housing status	-0.0690	-0.0607
	marital status	-0.0584	-0.0757
	duration	0.0287	0.0263
	job	0.2807	0.2718
	loan	-0.1395	-0.1368
ACS Income (AZ)	race	-0.1127	-0.1312
	sex	-0.1312	0.1205
	marital status	0.2307	0.2472
	age	0.2658	0.2713
ACS Income (MI)	race	-0.0620	-0.0324
	sex	0.1806	0.2030
	marital status	0.2518	0.2405
	age	0.2469	0.2127

Table 8: The Pearson correlation coefficients between our selected sensitive attributes (with regular font) and the target variable in training and test data. For ease of comparison, we also show some typical attributes (with *italic font*) not selected for evaluation. We set attributes that either (1) exhibit low correlation with the target variable across both training and test datasets, or (2) demonstrate significant variation in correlation with the target variable between the training and test datasets as sensitive (non-causal) attributes. Then we evaluate the model bias concerning these attributes.

We select sensitive attributes for evaluation based on the following criteria:

- Weak linear correlation with the target variable: Selected covariates should not exhibit a strong correlation with the target variable. For instance, in the Adult dataset, the attributes marital status, race, and sex were chosen because their Pearson correlation coefficients with the target variable are relatively smaller compared to attributes like *native country* and *workclass*.
- Divergent correlation statistics across training and test datasets: Selected attributes should show notable differences in correlation coefficients between the training and test datasets. For example, in the Taxi dataset, the selected attributes exhibit varying correlation coefficients in the training and test datasets, suggesting that these attributes are not direct causes of the target variable in this context.

A.6 THE ANALYSIS ON SAMPLE SIZE'S INFLUENCE ON OUR METHOD

Our method use score-based model to model the original data distribution, serving a purpose similar to traditional density estimation methods such as Kernel Density Estimation (KDE). Traditional density estimation methods, such as KDE, often require a large amount of background data. However, thanks to the advantages of diffusion models, our score-based density estimation is not sensitive to sample size, as demonstrated in our subsequent experimental results.

In this section, we examine the impact of training samples' size on our score-based proxy. We create subsets of varying sizes from the original training dataset and use these subsets to train score models. The final classification model is trained on the weights from new score models but tested on the original test data. We denote R as the ratio of the subset size relative to the original dataset. The experimental results are listed in Table 9. It demonstrates that the weights generated from our score-based proxy is insensitive to the sample size. The robustness of our method arises from score model's ability to construct the latent score field. As Kadkhodaie et al. (2024) stated, neural networks can memorize the score field even when the number of training samples is finite. This property ensures that our score-based weights faithfully approximate the original probability density, enabling robust classification model training even with reduced subsets ($R = 0.5$ and $R = 0.8$). However, when $R = 0.2$, the number of training samples becomes insufficient to construct an accurate score field, which makes the estimated weights less accurate. However, even when we used only one-fifth of the data for training, the performance of our model still outperformed the results of the other baselines using the full dataset in Table 1.

In a word, our method could generate more effective weights due to the process of modeling implicit score field, which only requires training a neural network. The process of predicting score for new samples does not require to calculate the interaction with other given training samples like statistical density estimation methods. Therefore, the number of training samples has minimal impact on this process, provided the dataset size remains relatively reasonable.

	$R = 0.2$		$R = 0.5$		$R = 0.8$		$R = 1$, original	
	Mean	Worst	Mean	Worst	Mean	Worst	Mean	Worst
Acc. (%)	73.81 $_{\pm 1.03}$	54.24 $_{\pm 5.48}$	74.23 $_{\pm 0.25}$	54.57 $_{\pm 1.98}$	74.78 $_{\pm 0.62}$	54.64 $_{\pm 1.90}$	74.33 $_{\pm 0.28}$	54.79 $_{\pm 2.01}$

Table 9: Experimental performance under different ratio R on Adult dataset. The number of original training and test samples is 32561 and 16281.

A.7 THE BALANCED SAMPLES AFTER DEPLOYING OUR WEIGHTS

To intuitively demonstrate how our score-based weights balance the original dataset, we divide the samples into groups based on the sensitive attribute and target label, then compute the sum of weights for each group. Without accounting for training challenges caused by group-specific variance, we expect the weights to achieve a balanced distribution. Specifically, the majority group is expected to have a lower weighted sum compared to its unweighted sum. Table 10 presents the results for four groups after applying our score-based weights. For nearly all the listed non-causal attributes, the sum of weights for the majority group decreases, while the sum for the minority group increases. This observation confirms that our weights effectively balance the original distributional shift, offering a clear explanation of how our method operates on real-world datasets.

sensitive attribute x	Default						Shoppers					
	age		given credit		sex		traffic type		visitor type		weekend	
	original	weighted	original	weighted	original	weighted	original	weighted	original	weighted	original	weighted
$x{=}1, y{=}0$	9144	6943.19	9834	7390.46	12902	9766.14	4635	2298.18	8221	3951.20	2120	1025.14
$x{=}0, y{=}1$	3236	5972.06	4180	7690.34	2586	4751.89	1004	3855.73	383	1413.91	1282	4930.48
$x{=}1, y{=}1$	2733	5061.28	1789	3343.00	3383	6281.44	725	2707.13	1346	5148.95	447	1632.38
$x{=}0, y{=}0$	11887	9023.47	11197	8576.20	8129	6200.52	4733	2235.96	1147	582.94	7248	3509

Table 10: The number of samples divided into different groups originally as well as the weighted sum of these samples after deploying our score-based weights. The reweighted samples of different groups are more balanced, which is conducive to subsequent unbiased classification learning.

A.8   THE T-SNE VISUALIZATION COMPARISON WITH OUR SCORE-BASED WEIGHTS

We previously provided an intuition for how our score-based weights help balance datasets using a synthetic example in Figure 1. In this section, we present a straightforward visualization on Default dataset to demonstrate how our method balances the real-world dataset. To be specific, we use t-SNE (Van der Maaten & Hinton, 2008) to reduce the latent representation to two dimensions for visualization. Note that in Table 10, the Default dataset predominantly exhibits label y shift. Therefore, we divide the representations into a majority group ($y = 0$) and a minority group ($y = 1$). In Figure 5a, points from the minority group ($y = 1$) are shaded in dark green, while the majority group ($y = 0$) is colored brown. We could observe that minority samples are often situated in the marginal regions of clusters, indicating that they have low probability densities. Correspondingly, we visualize these samples' score-based weights in Figure 5b. Points with higher weights are represented by warmer colors like purple. We expect that the points from the minority group in Figure 5a to be assigned higher weights in Figure 5b. Comparing these two figures, we can observe that our method significantly increases the weights for samples in the minority group. Almost all the dark green points in the left figure are shaded closer to purple in the right figure, which validates the effectiveness of our score-based weights.

(a) Group-specified latent representation   (b) Latent representation with our weights

Figure 5: The t-SNE visualization of the original latent representations and their corresponding weights in Default dataset.

A.9   THE COMPARISON WITH STABLE LEARNING

In this section, we provide a comprehensive comparison between our method and stable learning. Stable learning aims to decorrelate features to achieve a uniform and balanced data distribution, which is similar to our approach. However, our method offers three significant advantages over stable learning, as detailed below:

- **Ability to handle potential Y-shift problems**: Our method use a similarity difference measure to address implicit Y-shift as discussed in Section 3.3. In contrast, stable learning focuses solely on the decorrelation of covariates without differentiating the information carried by labels y.

- **Balanced Distribution via Original Distribution Modeling vs. Feature Independence**: Our method obtains a balanced distribution by modeling the original distribution while stable learning achieves balance through feature independence. The reweighting process in stable learning relies on feature decorrelation under a linear assumption. However, it is important to note that **a balanced distribution does not equate to feature independence, and feature decorrelation does not necessarily achieve balance, particularly in non-linear cases.**
  Consider an example where feature decorrelation fails at the sample level but our method succeeds. Suppose there are two features x_0 and x_1, with samples distributed such that $0 < x_0 < 1$ and $x_0 < x_1 < x_0 + 1$. Suppose that original data distribution is imbalanced, e.g., samples with $x_0 > 0.5$ all share a same higher density than those with $x_0 < 0.5$. Under this circumstance,

our method can transform the original data distribution $p(x_0, x_1)$ into a uniform data distribution $U(x_0, x_1)$ at the **sample level** easily. This is achievable because the score model captures and recovers the original data distribution $p(x_0, x_1)$.

In contrast, stable learning, which enforces feature decorrelation to achieve independence, cannot produce a uniform balanced distribution at the sample level while maintaining independence between x_0 and x_1. The geometry of the sample space—a parallelogram region—dictates that x_0 and x_1 cannot be independent while maintaining a uniform sample-level distribution, i.e., $U(x_0, x_1) \neq p(x_0) \cap p(x_1)$. Thus, stable learning fails to balance the data distribution at the sample level while simultaneously decorrelating features.

Decorrelating features to achieve feature independence is a good idea, but it is insufficient to ensure a balanced dataset without the essential assumptions. In contrast, our method does not depend on the presence or absence of feature correlations. Instead, it estimates the implicit score field to model the original distribution, enabling a robust balancing operation based on the estimated distribution.

- **Enhanced Experimental Outcomes Relative to Stable Learning**: To facilitate a quantitative comparison between our method and stable learning, we conducted experiments in Tables 1 and 2. Our approach shows a minimum improvement of 5% in the worst group accuracy compared to the SRDO baseline across both tables. **The superiority of our score-based reweighting over stable learning stems from the accuracy of the weights derived from our score model compared to the predicted probabilities generated by stable learning predictors.** Stable learning methods typically train a predictor to estimate probabilities, which involves the generation of synthetic samples. For instance, SRDO (Shen et al., 2020) employs empty vectors to create samples, whereas StableNet (Zhang et al., 2021) uses a Random Fourier Transformation. The quality of these synthetic samples crucially affects the training process of the predictor, thereby making the estimated probabilities potentially unreliable. In contrast, the score in our method represents the gradient of the log-likelihood of the original distribution $p(x)$. This ensures that our reweighting process remains rigorously faithful to the actual data distribution.

In a word, our method does not rely on any assumptions about the original data distribution. It utilizes the score, i.e., the gradient of estimated log-likelihood of original data distribution, to perform sample reweighting, which is flexible and easy to conduct. The additional experiments further confirm the effectiveness of our method.