Towards Job-Transition-Tag Graph for a Better Job Title Representation Learning

Abstract

Works on learning job title representation are mainly based on *Job-Transition Graph*, built from the working history of talents. However, since these records are usually messy, this graph is very sparse, which affects the quality of the learned representation and hinders further analysis. To address this specific issue, we propose to enrich the graph with additional nodes that improve the quality of job title representation. Specifically, we construct *Job-Transition-Tag Graph*, a heterogeneous graph containing two types of nodes, i.e., job titles and tags (i.e., words related to job responsibilities or functions). Along this line, we reformulate job title representation learning as the task of learning node embedding on the *Job-Transition-Tag Graph*. Experiments on two datasets show the interest of our approach.

1 Introduction

The learning of job title representation has received much attention in the recruitment field because the learned representation is beneficial to various tasks, such as job recommendation (Dave et al., 2018; Liu et al., 2019b), job title benchmarking (Zhang et al., 2019), and job mobility prediction (Zhang et al., 2021). However, in practice, learning a good representation is challenging for the following reasons: (i) **Noisy data**: job title data is noisy due to personal subjective reasons (i.e., spelling errors) or objective reasons (i.e., resume parsers are not perfect). (ii) **Messy data**: job titles are messy because people have different ways of thinking, and naming conventions vary by company and industry. For example, there are many alternative job titles for the same position, e.g., "purchasing clerk" and "buyer". Another problem is that due to the ambiguity of certain terms, they can refer to different positions in different contexts, e.g., "registered nurses sandwich rehab" and "sandwich maker". For these reasons, standard semantic-based approaches that aggregate (e.g., mean or sum) word representations to get job title semantic representation may lead to mismatches. Moreover, these methods ignore hidden relationships between job titles, e.g., titles in the same resume may be similar. (Dave et al., 2018; Zhang et al., 2019) learn representations from graphs. They create graphs from career trajectories, where nodes represent job titles, edges represent job transitions. Then they design different loss functions to embed the nodes into a low-dimensional space. However, the generated graphs are usually sparse due to the above reasons, limiting the performance of graph-based methods. Standardizing job titles before generating graphs can alleviate the sparsity issue to a certain extent, but at the cost of losing some information. To tackle these challenges, we propose to enrich graphs with structured contextual information and learn job title representations through network embedding methods. Specifically, inspired by domain-specific Named Entity tags (i.e., *RES*ponsibility and *FUN*ction) proposed in (Liu et al., 2019a), we treat the job title as a combination of responsibilities, functionalities, and other additional information. Words related to *responsibility* and *functionality* are defined as tags. We assume that job titles with the same tag describe similar job functions or responsibilities, so they are more likely to have similar representations. Along this line, we construct *Job-Transition-Tag Graph*, a heterogeneous graph containing two types of nodes, i.e., job titles and tags, which carries more information, thereby alleviating the sparsity problem.

2 Methodology

2.1 Preliminaries

A graph/network is represented as $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, with node set $\mathcal{V}$ and edge set $\mathcal{E}$. Nodes and edges can optionally have a type, so a graph can be homogeneous or heterogeneous. In the recruitment field, the career trajectory of talents can be repre-

sented by graphs. Formally, consider a job seeker set $\mathcal{U}$ and their working history set $\mathcal{H} = \{H^u\}_{u \in \mathcal{U}}$, where the working history of each u is represented as a sequence of n work records ordered by time $H^u = \{J_1, \ldots, J_n\}$. The i-th record J_i is denoted by (j_i, p_i), indicating that u is engaged in a position (titled j_i) during the p_i period. The set of job titles j_i that occurred in $\mathcal{H}$ is denoted as $\mathcal{J}$. Based on $\mathcal{H}$, *Job-Transition Graph* (Figure 1a) can be constructed, which is formally defined as:

Definition 1 (Job-Transition Graph) *is defined as a directed homogeneous graph $\mathcal{G}^{jj} = (\mathcal{J}, \mathcal{E}^{jj})$ generated from $\mathcal{H}$, where $\mathcal{J}$ is a set of job titles, and the edge $e_{xy}^{jj} \in \mathcal{E}^{jj}$ represents the job transition from the former job j_x to the next job j_y.*

2.1.1 Learning from Job-Transition Graph: An Overview

$\mathcal{G}^{jj}$ is often used for job title representation learning tasks. The current procedure is to first build a $\mathcal{G}^{jj}$, and then learn job title representation from it. More specifically, (Dave et al., 2018) first builds $\mathcal{G}^{jj}$ and other two graphs. Then, the Bayesian personalized ranking and margin-based loss functions are used to learn job title representations from graphs. Job2Vec (Zhang et al., 2019) constructs a $\mathcal{G}^{jj}$, where the node denotes job title affiliated with the specific company, and a multi-view representation learning method is proposed. (Zhang et al., 2021) adds company nodes in $\mathcal{G}^{jj}$ to build a heterogeneous graph. Then they use a graph neural network to represent the nodes. As mentioned above, the job title and job transition data are messy. Therefore, $\mathcal{G}^{jj}$ may be sparse (Zhang et al., 2019). To alleviate this issue, a simple method is to standardize job titles. For example, (Dave et al., 2018) normalizes titles by using Carotene (Javed et al., 2015), (Zhang et al., 2019) aggregates titles by filtering out low frequency words, and (Zhang et al., 2021) unifies titles according to IPOD (Liu et al., 2019a). However, the standardization of job titles may lose some specific information. Furthermore, these methods either ignore the semantic information contained in job titles (Dave et al., 2018; Zhang et al., 2021) or separate the semantic information from the graph topology (Zhang et al., 2019).

2.1.2 Job Title Composition

Generally, a job title consists of three parts (Liu et al., 2019a; Zhang et al., 2019): (i) **Responsibility**: describes the role and responsibility of a position from different levels (e.g., director, assistant,

and engineer). (ii) **Functionality**: describes the business function of a position from various dimensions (e.g., sales, national and security). (iii) **Additional Information**: contains personal-specific information. We denote the words related to *responsibility* and *functionality* as tags, and they form a tag set $\mathcal{T}$. These tags are the essence of the job title and provide important information about the position. However, few works directly include this information in the representation learning scheme. In this paper, we consider these tags when generating graphs. These tags can alleviate the graph sparsity problem of $\mathcal{G}^{jj}$ and provide additional information for the learning of job title representations.

2.2 Proposed Graphs

In order to address the sparsity issue of $\mathcal{G}^{jj}$, we consider adding more information when generating graphs, i.e., tags related to job responsibilities or functions, driven by the job title composition. Along this line, we define various types of graphs:

Definition 2 (Enhanced Job-Transition Graph) *is based on $\mathcal{G}^{jj}$ with additional enhanced edges. It is defined as $\mathcal{G}_E^{jj} = (\mathcal{J}, \mathcal{E}^{jj} \cup \mathcal{E}_E^{jj})$, where $\mathcal{E}_E^{jj}$ is a set of enhanced edges. More specifically, if j_x and j_y share a word w, then we add a bi-directional edge between them, i.e., e_{xy}^{jj} and e_{yx}^{jj}.*

As shown in Figure 1b, "purchasing manager" shares the tag "purchasing" with "purchasing clerk", so we add an enhanced edge (i.e., the red dashed line) between them.

Definition 3 (Job-Tag Graph) *is a heterogeneous graph $\mathcal{G}^{jt} = (\mathcal{J} \cup \mathcal{T}, \mathcal{E}^{jt})$, with job titles and tags, two node types. $\mathcal{E}^{jt}$ is a set of bi-directional edges between a job title and a tag, representing the "has/in" relationship.*

An example of the "has/in" relationship is given in Figure 1c (i.e., the green line), where the job title "automotive technician" *has* a tag "automotive", and "automotive" is *in* "automotive technician". In order to aggregate more information, we further combine *Job-Transition Graph* and *Job-Tag Graph* to build *Job-Transition-Tag Graph*:

Definition 4 (Job-Transition-Tag Graph) *is a heterogeneous graph $\mathcal{G}^{jtj} = (\mathcal{J} \cup \mathcal{T}, \mathcal{E}^{jj} \cup \mathcal{E}^{jt})$ with two node types and two edge types.*

Inspired by the achievements of network embedding models in the node representation learning problem (Hamilton et al., 2017), we apply differ-

(a) Job-Transition graph.

(b) Enhanced Job-Transition graph.

(c) Job-Tag graph.

(d) Job-Transition-Tag graph.

Figure 1: Examples of four types of graphs with blue/green circles representing job titles/tags. Black lines represent job transitions, red dotted lines represent additional enhanced edges, and green lines represent "has/in" relationships.

ent network embedding models to learn job title representation from the graphs defined above.

3 Experiments

3.1 Datasets

CareerBuilder12 (CB12): an open dataset from a Kaggle competition. [1] It contains a collection of working experiences represented by sequences of job titles. For the node classification task, we use *AutoCoder* [2] to assign a SOC 2018 to each job title. The labeling details are given in Appendix A.1.

Randstad: a private French resume dataset provided by Randstad company, where each resume is parsed into multiple sections, an example is given in Figure 3 of Appendix. Graphs are built from *EmploymentHistory* section.

	#C	#W	$|\mathcal{J}|$	$|\mathcal{E}^{jj}|$	$|\mathcal{E}^{jj}_E|$	$|\mathcal{E}^{jt}|$
CB12	16	1,682	9,216	20,640	6,475,850	22,108
Randstad	18	2,303	12,864	36,722	6,663,267	22,897

Table 1: Statistics of datasets and corresponding graphs, #C represents the number of categories, and #W represents the vocabulary size for node one-hot encoding.

For both datasets, we use the Top-200 tokens that appear most frequently in job titles and belong to IPOD (Liu et al., 2019a) as tags. The details of tag generation are given in Appendix A.3. We assign the one-hot encoding of the corresponding title for

each title node as the node feature. The vocabulary set is obtained by filtering words with a frequency of 1 from the tokenized job titles. Statistics for datasets and graphs are summarized in Table 1. We can observe that $\mathcal{G}^{jj}$ (i.e., $|\mathcal{V}|$ and $|\mathcal{E}^{jj}|$) are sparse.

3.2 Experimental Settings

We evaluate the proposed job title representation learning scheme through (i) a node classification task (i.e., *job title classification*) and (ii) a link prediction task (i.e., *next-job prediction*). For *job title classification*, we randomly split the data into training/validation/test sets with a ratio of 60%/20%/20%. We keep the same split ratio on positive/negative edges for *next-job prediction*, where negative edges are randomly picked from unconnected node pairs (i.e., the same size as positive edges). The baselines used are listed below:

- **Homogeneous**: *Node2Vec (N2V)* (Grover and Leskovec, 2016), *GCN* (Kipf and Welling, 2016) and *GAT* (Veličković et al., 2017).
- **Heterogeneous**: *Metapath2Vec (M2V)* (Dong et al., 2017), *RGCN* (Schlichtkrull et al., 2018) and *HAN* (Wang et al., 2019b).
- **Semantic-based**: *Word2Vec (W2V)* (Le and Mikolov, 2014) and *BERT* (Devlin et al., 2018).

For detailed parameter settings and baseline descriptions, see Appendix A.5 and A.4.

3.3 Results

3.3.1 Job Title Classification

Table 2 summarizes the best results of all methods on different graphs. We have the following obser-

[1] https://www.kaggle.com/c/job-recommendation
[2] http://www.onetsocautocoder.com/plus/onetmatch

		N2V	GCN	GAT	M2V	RGCN	HAN	W2V	BERT
CB12	$\mathcal{G}^{jj}$	0.206/0.360	0.576/0.688	0.568/0.664	0.154/0.334	0.524/0.637	0.670/0.747		
	$\mathcal{G}^{jj}_E$	0.599/0.714	0.628/0.720	0.692/0.759	0.571/0.688	0.591/0.701	0.698/0.781	0.325/0.454	0.688/0.719
	$\mathcal{G}^{jt}$	-	-	-	0.588/0.692	0.687/0.752	0.703/0.766		
	$\mathcal{G}^{jtj}$	-	-	-	0.588/0.692	0.703/0.766	**0.742/0.797**		
Randstad	$\mathcal{G}^{jj}$	0.201/0.304	0.520/0.616	0.529/0.593	0.166/0.282	0.388/0.536	0.592/0.665		
	$\mathcal{G}^{jj}_E$	0.523/0.623	0.484/0.621	0.607/0.677	0.469/0.585	0.452/0.580	0.607/0.689	0.279/0.391	0.580/0.609
	$\mathcal{G}^{jt}$	-	-	-	0.590/0.665	0.552/0.643	0.572/0.663		
	$\mathcal{G}^{jtj}$	-	-	-	0.590/0.665	0.600/0.678	**0.641/0.708**		

Table 2: Job title classification results (Macro-F1/Micro-F1). The score in bold is the best among all methods applied to all graphs, and the scores underlined are the best in all graphs of each method. For *M2V*, we report the best results obtained by the meta-path *Job-Tag-Job*.

vations: (i) Among all graphs, all models generally have the lowest scores on $\mathcal{G}^{jj}$ because this graph is often sparse and can only provide limited information. (ii) All models perform better on $\mathcal{G}^{jj}_E$ (except Macro-F1 of *GCN*) than $\mathcal{G}^{jj}$, which shows that the enhanced edges provide additional information. (iii) The heterogeneous models perform well on our proposed $\mathcal{G}^{jtj}$, which indicates that the added tag nodes can effectively improve the quality of representation. We did not apply homogeneous methods to $\mathcal{G}^{jtj}$, but results on $\mathcal{G}^{jj}_E$ prove that the information given by tags is useful. (iv) *BERT* has a better performance than *W2V*, but graph neural networks generally outperform semantic-based methods.

3.3.2 Next-Job Prediction

We further evaluate the learning scheme using next-job prediction, which can be viewed as a link prediction task to predict whether a position will be recommended as the next job. The results on *CB12* are shown in Table 3. *BERT* performs best, followed by *HAN* on $\mathcal{G}^{jtj}$. However, when we use the dot product used in *HAN* to obtain edge features for *BERT*, the AUC drops to 0.476, while *W2V* drops to 0.557. We will discuss such results in future work. Overall, the results of link prediction also demonstrate the effectiveness of our method.

	N2V	GAN	M2V	HAN	W2V	BERT
$\mathcal{G}^{jj}$	0.564	0.704	0.548	0.685		
$\mathcal{G}^{jj}_E$	0.692	0.789	0.593	0.792	0.670	**0.840**
$\mathcal{G}^{jt}$	-	-	0.604	0.768		
$\mathcal{G}^{jtj}$	-	-	0.604	0.833		

Table 3: Next-job prediction results (AUC) on *CB12*.

3.3.3 Visualization

For a more intuitive comparison, we visualize the learned representations in Figure 2, and each color corresponds to an occupation category [3]. Overall,

the representations learned by *HAN* on all graphs are clustered into groups. However, when considering tags, representations are easier to be subdivided further in each category. For example, in Figure 2d, the orange occupation can be further divided into three sub-clusters, which proves that adding tag nodes can help capture more detailed information and make the learned representation more informative. This detailed information helps to classify positions further because we only classify job titles into the root category in this work.

(a) HAN ($\mathcal{G}^{jj}$). (b) HAN ($\mathcal{G}^{jj}_E$).

(c) HAN ($\mathcal{G}^{jt}$). (d) HAN ($\mathcal{G}^{jtj}$).

Figure 2: Visualization of representations (CB12).

4 Conclusion

This paper first proposes to enrich *Job-Transition Graph* commonly used in job title representation learning tasks by adding tag nodes and then learn job title representations through network embedding methods. This graph can alleviate the sparsity problem, thereby improving the quality of learned representations, as demonstrated by node classification and link prediction tasks on two datasets. Future research lines will focus on learning from weighted graphs and improving the tag generation.

---

[3] *Healthcare support* (green), *Healthcare practitioners and technical* (blue), *Architecture and engineering* (purple), *Office* *and administrative support* (orange) and *Transportation and material handling* (red).

References

Vachik S Dave, Baichuan Zhang, Mohammad Al Hasan, Khalifeh AlJadda, and Mohammed Korayem. 2018. A combined representation learning approach for better job and skill recommendation. In *Proceedings of the 27th ACM International Conference on Information and Knowledge Management*, pages 1997–2005.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*.

Yuxiao Dong, Nitesh V Chawla, and Ananthram Swami. 2017. metapath2vec: Scalable representation learning for heterogeneous networks. In *Proceedings of the 23rd ACM SIGKDD international conference on knowledge discovery and data mining*, pages 135–144.

Jean-Philippe Fauconnier. 2015. French word embeddings.

Aditya Grover and Jure Leskovec. 2016. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 855–864.

William L Hamilton, Rex Ying, and Jure Leskovec. 2017. Representation learning on graphs: Methods and applications. *arXiv preprint arXiv:1709.05584*.

Faizan Javed, Qinlong Luo, Matt McNair, Ferosh Jacob, Meng Zhao, and Tae Seung Kang. 2015. Carotene: A job title classification system for the online recruitment domain. In *2015 IEEE First International Conference on Big Data Computing Service and Applications*, pages 286–293. IEEE.

Diederik P Kingma and Jimmy Ba. 2014. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.

Thomas N Kipf and Max Welling. 2016. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*.

Quoc Le and Tomas Mikolov. 2014. Distributed representations of sentences and documents. In *International conference on machine learning*, pages 1188–1196. PMLR.

Junhua Liu, Yung Chuen Ng, Kristin L Wood, and Kwan Hui Lim. 2019a. Ipod: An industrial and professional occupations dataset and its applications to occupational data mining and analysis. *arXiv preprint arXiv:1910.10495*.

Mengshu Liu, Jingya Wang, Kareem Abdelfatah, and Mohammed Korayem. 2019b. Tripartite vector representations for better job recommendation. *arXiv preprint arXiv:1907.12379*.

Michael Schlichtkrull, Thomas N Kipf, Peter Bloem, Rianne Van Den Berg, Ivan Titov, and Max Welling. 2018. Modeling relational data with graph convolutional networks. In *European semantic web conference*, pages 593–607. Springer.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. 2017. Graph attention networks. *arXiv preprint arXiv:1710.10903*.

Minjie Wang, Da Zheng, Zihao Ye, Quan Gan, Mufei Li, Xiang Song, Jinjing Zhou, Chao Ma, Lingfan Yu, Yu Gai, Tianjun Xiao, Tong He, George Karypis, Jinyang Li, and Zheng Zhang. 2019a. Deep graph library: A graph-centric, highly-performant package for graph neural networks. *arXiv preprint arXiv:1909.01315*.

Xiao Wang, Houye Ji, Chuan Shi, Bai Wang, Yanfang Ye, Peng Cui, and Philip S Yu. 2019b. Heterogeneous graph attention network. In *The World Wide Web Conference*, pages 2022–2032.

Han Xiao. 2018. bert-as-service. https://github.com/hanxiao/bert-as-service.

Denghui Zhang, Junming Liu, Hengshu Zhu, Yanchi Liu, Lichen Wang, Pengyang Wang, and Hui Xiong. 2019. Job2vec: Job title benchmarking with collective multi-view representation learning. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management*, pages 2763–2771.

Le Zhang, Ding Zhou, Hengshu Zhu, Tong Xu, Rui Zha, Enhong Chen, and Hui Xiong. 2021. Attentive heterogeneous graph embedding for job mobility prediction. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*, pages 2192–2201.

A Appendix

A.1 Job Title Label Assignment

In the original working experience dataset provided by CareerBuilder12, job titles are not pre-labeled. Therefore, for the job title classification task, we use an online third-party API O*Net-SOC AutoCoder [4] to assign a Standard Occupation Classification code (SOC) 2018 to each job title, as well as a match score (i.e., scores above 70 means that the correct code is accurately predicted at least 70% of the time). SOC 2018 is a four-level taxonomy structure, including *MajorGroup* (23), *MinorGroup* (98), *BroadGroup* (459) and *DetailedOccupation* (867). For example, *O*Net-SOC AutoCoder* assigns the code 11-2022 (Sales Managers) for the title "sales director", which belongs to the level of *DetailedOccupation*. 11-2020 (Marketing and Sales Managers) is *BroadGroup* level, 11-2000 (Advertising, Marketing, Promotions, Public Relations, and Sales Managers) is *MinorGroup* level, and 11-0000 (Management Occupations) is *MajorGroup* level. In this work, we categorize job titles into *MajorGroup*. We have annotated a total of 30,000 job titles. The developer guarantees that the code assigned to the title plus description has an accuracy rate of 85%. However, only the job title is provided in our experiments, so the SOC 2018 code may be incorrectly assigned. For this reason, we filtered out job titles with scores below 70. Therefore, 22,590 job titles remain.

A.2 Randstad Data Description

Figure 3 shows an example of parsed resume in *Randstad* dataset. We build graphs from *EmploymentHistory*, which contains a *JobTitle*, and its corresponding occupation labels (i.e., *JobCode*, *JobGroup* and *JobClass*). The hierarchical taxonomy structure used in the Randstad dataset has a three-level hierarchy, where *JobCode*s are leaf classes, and each internal (*JobGroup*)/root class (*JobClass*) is the aggregation of all its descendant classes. There are 25 *JobClass*s, 295 *JobGroup*s and 4,443 *JobCode*s, respectively. In this work, we categorize job titles into *JobClass*.

A.3 Tag Generation

For both datasets, we first tokenize titles into tokens and remove stopwords, numbers, and punctuation. The word frequency distribution of words

---

Figure 3: An example of parsed resume in Randstad.

in two datasets are shown respectively in Figure 4, which are subject to the long-tail distribution, similar to the observation in (Zhang et al., 2019). Most words appear only once, i.e., 53.55% of words only appear one time in *CB12* dataset, and this ratio is 56.55% in *Randstad* dataset. Figure 4 further shows the top ten and last ten frequent words in each dataset. Obviously, high-frequency words like "manager" and "sales" describe the responsibility or functionality of the job title, while low-frequency words are usually noise or person-specific words. Based on the domain-specific NE tags (i.e., *RES*ponsibility, *FUN*ction) proposed in IPOD (Liu et al., 2019a), we then select the Top-200 tokens that appear most frequently and appear in the IPOD NE tag set as tags for each dataset.

(a) CB12.   (b) Randstad.

Figure 4: Word frequency distribution, where the red line represents the average value. *Top-10* words are sorted by frequency, and *Last-10* are randomly selected from the words with a frequency of 2.

A.4 Baseline Description

We explore the following network embedding methods on our proposed graphs to learn job title representation. According to the type of graph, the network embedding methods are naturally divided into *Homogeneous* and *Heterogeneous*. Then, we further categorize each category into *Unsupervised* and *Semi-Supervised* according to whether node

---

[4] http://www.onetsocautocoder.com/plus/onetmatch

labels are provided for learning.

Homogeneous&Unsupervised

- *Node2Vec (N2V)* (Grover and Leskovec, 2016): is an extension of DeepWalk with a biased random walk process for neighborhood exploration.

Homogeneous&Semi-supervised:

- *GCN* (Kipf and Welling, 2016): is a semi-supervised GNN that generalizes the convolutional operation to homogeneous graphs.
- *GAT* (Veličković et al., 2017): uses a self-attention strategy to learn the importance between a node and its neighbors.

Heterogeneous&Unsupervised:

- *Metapath2Vec (M2V)* (Dong et al., 2017): performs meta-path-guided walks and utilizes Skip-Gram to embed heterogeneous graphs.

Heterogeneous & Semi-supervised:

- *RGCN* (Schlichtkrull et al., 2018): is an extension of *GCN* on heterogeneous graphs, introducing relation-specific transformations based on the type of edges.
- *HAN* (Wang et al., 2019b): proposes a hierarchical attention mechanism, i.e., node-level and semantic-level for heterogeneous graphs.

In addition to the comparison between network embedding methods, we will also compare the representation learned through graphs with the representation obtained by semantic-based methods.

Semantic-based:

- *Word2Vec (W2V)* (Le and Mikolov, 2014): the representation of a job title is obtained by averaging word vectors in it. We use word vectors trained on Google News [5] for *CB12*, and a pre-trained French embedding model (Fauconnier, 2015) for *Randstad*.
- *BERT* (Devlin et al., 2018): the job title representations are obtained by using bert-as-service package (Xiao, 2018). BERT-Base-Uncased is used for *CB12*, and BERT-Base-Multilingual-Cased (New) for *Randstad*.

A.5 Parameter Settings

Our implementation is based on the PyTorch version of the DGL package (Wang et al., 2019a). For *job title classification*, we randomly split the

data into training/validation/test sets with a ratio of 60%/20%/20%. We keep the same split ratio on positive/negative edges for *next-job prediction*, where negative edges are randomly picked from unconnected node pairs (i.e., the same size as positive edges). To ensure fairness, we keep the same data split for both methods. Each semi-supervised model was trained on the training set, and the parameters were optimized on the validation set. The final performance was evaluated on the test set. Models are optimized with the Adam (Kingma and Ba, 2014) with a learning rate of 1e-3, and we apply L_2 regularization with value 5e-4. We use an early stop with a patience of 100, i.e., if the validation loss does not decrease in 100 consecutive epochs, we stop training. For models applying the attention mechanism, the dropout rate of attention is set to 0.2. For random-walk-based methods include *N2V* and *M2V*, we set the window size to 5, walk length to 10, walks per node to 50, the number of negative samples to 5. For *M2V*, we test all meta-paths and report the best performance. For a fair comparison, we set the dimension of node embedding to 128 for all the above methods, except for *W2V*. In both *job title classification* and *next-job prediction*, for unsupervised methods, node representations are learned from the entire dataset. The logistic regression classifier is then trained on both the training and validation sets. Edge features are represented by applying binary operators (Grover and Leskovec, 2016) on pairs of nodes. We use dot product for all semi-supervised methods, and for unsupervised methods, we choose the best operator based on the validation set. We repeat each prediction experiment ten times and report the average performance scores (i.e., Macro-F1 and Micro-F1 for job classification and AUC for next-job prediction).

---

[5] https://code.google.com/archive/p/word2vec/