GENERATIVE PSEUDO-INVERSE MEMORY

ABSTRACT

We propose Generative Pseudo-Inverse Memory (GPM), a class of deep generative memory models that are fast to write in and read out. Memory operations are recast as seeking robust solutions of linear systems, which naturally lead to the use of matrix pseudo-inverses. The pseudo-inverses are iteratively approximated, with practical computation complexity of almost $O(1)$. We prove theoretically and verify empirically that our model can retrieve exactly what have been written to the memory under mild conditions. A key capability of GPM is iterative reading, during which the attractor dynamics towards fixed points are enabled, allowing the model to iteratively improve sample quality in denoising and generating. More impressively, GPM can store a large amount of data while maintaining key abilities of accurate retrieving of stored patterns, denoising of corrupted data and generating novel samples. Empirically we demonstrate the efficiency and versatility of GPM on a comprehensive suite of experiments involving binarized MNIST, binarized Omniglot, FashionMNIST, CIFAR10 & CIFAR100 and CelebA.

1 INTRODUCTION

Memory is central for intelligence by facilitating information compression, reconstruction, manipulation, and generation. The processing speed and storage capacity of the working memory are known to correlate with reasoning capacity (Jensen and Munro, 1979; Kyllonen and Christal, 1990). Recent work in machine learning has explored slot-based external memory to augment neural networks (Graves et al., 2016; Le et al., 2019) in which memory reads and writes proceed sequentially through attention mechanism, making training and pattern retrieval difficult for very long sequences. Global self-attention techniques (Ramsauer et al., 2021) create short-cuts in information paths, hence are easier to train, but require large memory and computation for long sequences.

Different from slot-based memories, Kanerva Machines (Wu et al., 2018a;b) are a class of generative memory inspired by Kanerva's sparse distributed memory (Kanerva, 1984). Memory update/retrieval and addressing mechanism are treated as Bayesian inference where posteriors are updated when a new data episode arrives. This iterative and dynamic inference handles noisy inputs better due to the convergence of the attractor dynamics to fixed points (Wu et al., 2018b). However, these models suffer from slow processing speed, which originates from sequential writing mechanism. This slowness prevents the model to adapt with large batch of data, thus makes it difficult to conduct experiments on memory storage capacity. On the other side, one cannot ensure theoretically how well those models can retrieve information. This creates an obstacle for theoretical research on the efficiency of memory models.

In this work we propose a new model called Generative Pseudo-Inverse Memory (GPM) to overcome these challenges. Figure 1 illustrates the writing-reading process of our model. GPM reformulates the Bayesian updates of memory and address as finding least-square solutions to linear systems. Among these solutions, the smallest norm is found through applying Moore-Penrose *pseudo-inverse* of matrices (Ben-Israel and Greville, 2001). This helps us achieve rapid and accurate memory read/write. Importantly, our model is able to not only store and retrieve information perfectly under ideal conditions but also generate new samples based on written data. This coincides with recent inspiring results from functional neuroimaging (Addis et al., 2007; Okuda et al., 2003; Schacter et al., 2012), which showed that memory not only helps us memorize but also supports imagining. We derive an energy function for GPM and show that its updates seek to locate local minima of the energy. This dynamics enables GPM to perform iterative reading to improve sample quality during denoising and generating. Finally GPM can store a large amount of data (up to a dataset) while still

Figure 1: *Writing-reading mechanism of Generative Pseudo-Inverse Memory*. Orange boxes and circle contain trainable parameters of GPM. Green circle consists of variational part for the generative scheme. Red arrows are operations of computing the pseudo-inverses. During writing, the episode $\mathbf{X}$ is encoded as $\mathbf{Z}$. Using $\mathbf{Z}$ and prior memory $\mathbf{M}_0$, we compute the writing weight $\mathbf{W}_0$ and then use $\mathbf{W}_0$ to write $\mathbf{Z}$ into the memory. The result of writing phase is the posterior memory $\mathbf{M}$. In reading, the query $\mathbf{X}_q$ is encoded as $\mathbf{Z}_q$. Note that the encoder in the reading phase needs not be identical to the encoder in writing phase. The reading weight $\mathbf{W}$ is computed based on $\mathbf{Z}_q$ and the posterior $\mathbf{M}$. The memory read-out $\mathbf{Z}_r$ is simply the matrix product between $\mathbf{W}$ and $\mathbf{M}$. Finally, $\mathbf{Z}_r$ goes through the decoder to produce the output $\mathbf{X}_o$ of the reading phase. If iterative reading is included, $\mathbf{X}_o$ will become the next query and be fed back to the encoder for next reading step. In training, we use the same encoder for writing and reading, the query $\mathbf{X}_q$ is identical with $\mathbf{X}$ and reading is non-iterative.

maintaining key capabilities. We validate these theoretical insights through a comprehensive suite of experiments on binarized MNIST (LeCun et al., 2010) , binarized Omniglot (Burda et al., 2016), FashionMNIST (Xiao et al., 2017), CIFAR10 & CIFAR100 (Krizhevsky, 2009) and CelebA (Liu et al., 2015), demonstrating superior results.

2 MODEL

Consider a data episode of length T and let $\mathbf{X}$ denote the episode data matrix of T rows, where the i-th row of $\mathbf{X}$ is the i-th item of the episode. Throughout this paper, we refer to the episode as its associated episode matrix. We aim to compress the episode to a fixed-size memory for later reconstruction and generation processes. We maintain a memory matrix $\mathbf{M}$, which is a deterministic real matrix of size $K \times C$ with trainable initialization $\mathbf{M}_0$. For convention, $\mathbf{M}_0$ may be considered as the common prior memory containing information of the whole dataset while $\mathbf{M}$ is the posterior memory dependent of the episode.

In order to write to and read from the memory, we additionally define the writing weight matrix $\mathbf{W}_0$ and reading weight matrix[1] $\mathbf{W}$, both of size $T \times K$. We treat the reading weight $\mathbf{W}$ as a random variable, hence inducing the generative capability of the model. For simplicity, the prior $p\left(\text{vec}(\mathbf{W})\right)$ of $\mathbf{W}$ is the standard Gaussian $\mathcal{N}\left(\mathbf{0}, \mathbf{I}_{T \times K}\right)$ while the posterior $q\left(\text{vec}(\mathbf{W})\right)$ is $\mathcal{N}\left(\overline{\mathbf{W}}, \sigma_{\mathbf{W}}^2 \mathbf{I}_{T \times K}\right)$, where the mean $\overline{\mathbf{W}}$ is adapted to each episode and $\sigma_{\mathbf{W}}$ is a learnable parameter. Read-out's from the memory are matrix products between the weights and the memory. Specifically, we refer $\mathbf{W}_0 \mathbf{M}$ as the *temporary read-out* (read-out after writing phase) and $\mathbf{W} \mathbf{M}$ as the *read-out* in the reading phase.

Let $e_\theta(.)$ be the (neural) encoder and $d_\theta(.)$ be the decoder parameterized by θ. In the following we drop the explicit subscript θ for clarity. We further let $\mathbf{Z}$ denote the $T \times C$ encoding matrix of the episode $\mathbf{X}$, i.e. $\mathbf{Z} = e(\mathbf{X})$ where $e(.)$ is applied to each row of $\mathbf{X}$. We refer $\mathbf{Z}$ as the *to-be-written data* into the memory.

---

[1] We note that weights here are dynamic and unrelated to neural network parameters.

2.1 OBJECTIVE FUNCTION

To reconstruct or generate the data from the memory, we aim to maximize the conditional likelihood $\mathcal{J} = \mathbb{E}_{p(\mathbf{X})p(\mathbf{M}|\mathbf{X})} \ln p(\mathbf{X}|\mathbf{M})$. It is difficult to maximize $\mathcal{J}$ directly, so we instead maximize the evidence lower bound $\mathcal{L}_T$ of $\ln p(\mathbf{X}|\mathbf{M})$, where

$$\mathcal{L}_T = \mathbb{E}_{q(\mathbf{W})} \ln p(\mathbf{X}|\mathbf{W}, \mathbf{M}) - D_{\mathrm{KL}}(q(\mathbf{W})||p(\mathbf{W})). \tag{1}$$

The first term in $\mathcal{L}_T$ is usually called the negative reconstruction loss, while the second term is the Kullback-Leibler divergence between the prior $p(\mathbf{W})$ and posterior $q(\mathbf{W})$ of the reading weight. Details of derivation will be given in Appendix I.

In our model, we use the encoding matrix $\mathbf{Z}$ as the data to be written to the memory instead of the original episode $\mathbf{X}$. Therefore, we would like $\mathbf{Z}$ to be a "good" representation of $\mathbf{X}$. We quantize this goodness by the usual auto-encoder loss $\mathcal{L}_{\mathrm{AE}} = \mathbb{E}_{\mathbf{X} \sim \mathrm{data}} \ln p\left(d\left(e(\mathbf{X})\right)\right)$. Thus during training we will maximize the objective function:

$$\mathcal{O} = \mathcal{L}_T + \mathcal{L}_{\mathrm{AE}}. \tag{2}$$

2.2 GENERATIVE PSEUDO-INVERSE MEMORY

In our model, the posterior memory, the writing weight and the reading weight are all dynamic and depending on the data episode. Hence it is necessary to understand the motivations and computation methods as introduced in the following.

Memory inference

Previous generative memory models such as Kanerva Machine (Wu et al., 2018a) and Dynamic Kanerva Machine (Wu et al., 2018b) incorporate Bayesian update as writing mechanism for the memory. In general, Bayesian update is the process of updating a probability distribution when new information arrives. Bayesian method encourages the update to keep old information as much as possible, thus in our case we can view it as the process of finding a solution to the minimization problem of the distance between the prior (or the old) and the posterior (or the new) memory.

Let us temporarily abuse notations and let $\mathbf{M}_0, \mathbf{M}$ denote random variables of the prior and posterior memory, respectively, and suppose that both have matrix Gaussian distributions. Given the prior $\mathbf{M}_0$, the to-be-written data $\mathbf{Z}$ and the writing weight $\mathbf{W}_0$, determining the posterior $\mathbf{M}$ by Bayesian update is equivalent to solving the optimization problem:

$$\min_{\mathbf{A},\mathbf{B}} \mathbb{E}\left(\|\mathbf{M} - \mathbf{M}_0\|_F^2\right) \quad \text{s.t.} \quad \mathbf{M} = \mathbf{A}\mathbf{Z} + \mathbf{B} \text{ and } \mathbf{Z} = \mathbf{W}_0\mathbf{M}_0 + \xi \tag{3}$$

where ξ is observation noise and $\|.\|_F$ is the Frobenius norm. Optimization problem in Eq. (3) assumes the data $\mathbf{Z}$ is the product of the writing weight and the prior memory, and the posterior memory $\mathbf{M}$ is a linear function of $\mathbf{Z}$. When these assumptions hold, Eq. (3) has the unique and explicit solution (see Appendix H).

The solution $\mathbf{M}$ of Eq. (3) tends to preserve information from $\mathbf{M}_0$. However, in practice, what appears in the prior memory might be blurry information of the whole dataset. Forcing the short-term memory $\mathbf{M}$ to be close to $\mathbf{M}_0$ may prevent the posterior memory from storing sufficient information from the current episode, leading to incorrect read-out. To overcome this drawback, we propose a different optimization problem that helps improve read-out accuracy. From now on, we will only consider deterministic memories $\mathbf{M}_0$ and $\mathbf{M}$. Our proposed optimization problem is

$$\min_{\mathbf{M}} \|\mathbf{W}_0(\mathbf{M} - \mathbf{M}_0)\|_F^2 \quad \text{s.t.} \quad \mathbf{Z} = \mathbf{W}_0\mathbf{M}_0 + \xi. \tag{4}$$

Here we omit the linear relation between $\mathbf{M}$ and $\mathbf{Z}$, which means the posterior memory can be any function of the data. If $\mathbf{M}$ is a solution of Eq. (4), then $\mathbf{W}_0\mathbf{M}$ is close to $\mathbf{W}_0\mathbf{M}_0$, which is equal to $\mathbf{Z} - \xi$ due to the optimization constraint. In other words, the temporary read-out is similar to the data written to the memory. Let $\mathbf{Z}_\xi := \mathbf{Z} - \xi$ and substitute $\mathbf{W}_0\mathbf{M}_0 = \mathbf{Z}_\xi$, Eq. (4) becomes

$$\min_{\mathbf{M}} \|\mathbf{W}_0\mathbf{M} - \mathbf{Z}_\xi\|_F^2. \tag{5}$$

Algorithm 1 Single training step of Generative Pseudo-Inverse Memory

---

Sample an episode $\mathbf{X}$ of length T.

Writing

1. Compute episode embedding $\mathbf{Z} = e(\mathbf{X})$.
2. Randomize noise ξ from $\mathcal{N}(\mathbf{0}, \sigma_\xi^2 \mathbf{I})$.
3. Compute weight $\mathbf{W}_0 = \mathbf{Z}_\xi \mathbf{M}_0^+$.
4. Compute posterior memory $\mathbf{M} = \mathbf{W}_0^+ \mathbf{Z}_\xi$.

Reading

1. Compute episode embedding $\mathbf{Z} = e(\mathbf{X})$.
2. Compute weight mean $\overline{\mathbf{W}} = \mathbf{Z}\mathbf{M}^+$.
3. Sample $\mathbf{W} \sim \mathcal{N}(\overline{\mathbf{W}}, \sigma_\mathbf{W}^2 \mathbf{I})$.
4. Compute read-out $\mathbf{Z}_{\text{read-out}} = \mathbf{W}\mathbf{M}$.
5. Compute episode reconstruction $\hat{\mathbf{X}} = d\left(\mathbf{Z}_{\text{read-out}}\right)$.

Updating model parameters

1. Compute the objective $\mathcal{O} = \mathcal{L}_T + \mathcal{L}_{AE}$ using obtained terms from previous steps.
2. Update parameters via gradient ascent to maximize $\mathcal{O}$.

Any solution of Eq. (5) is called the *least-square solution* of the linear system $\mathbf{W}_0\mathbf{M} = \mathbf{Z}_\xi$. However, Eq. (5) may admit more than one least-square solution, thus we are interested in the least-square solution that has the smallest norm, i.e. the *minimum-norm least-square solution*. The minimum-norm condition may help to regularize in the sense that the posterior memory should contain as little redundant information as possible. It can be proved that $\mathbf{M} = \mathbf{W}_0^+ \mathbf{Z}_\xi$ is the minimum-norm least-square solution of the system $\mathbf{W}_0\mathbf{M} = \mathbf{Z}_\xi$ (Ben-Israel and Greville, 2001), where $\mathbf{W}_0^+$ is the *pseudo-inverse* of $\mathbf{W}_0$. The pseudo-inverse of matrix is applicable to classical associative memory which involves finding a linear mapping from input to output (Stiles and Denq, 1985; Yen and Michel, 1991). Readers are referred to Appendix D for more mathematical properties of the pseudo-inverse.

Computing writing and reading weights

The discussion so far is about seeking the posterior memory $\mathbf{M}$ given the data $\mathbf{Z}$ and the writing weight $\mathbf{W}_0$. In our settings, all weights are dynamic and they depend on either the prior memory and data (during writing) or the posterior memory and the query (during reading). Formally written, we need to determine the writing weight $\mathbf{W}_0$ (given prior memory $\mathbf{M}_0$ and noisy data $\mathbf{Z}_\xi$) and reading weight $\mathbf{W}$ (given posterior memory $\mathbf{M}$ and query $\mathbf{Z}$). Ideally, $\mathbf{W}_0$ and $\mathbf{W}$ should satisfy $\mathbf{W}_0\mathbf{M}_0 = \mathbf{Z}_\xi$ (to fit with optimization constraint in Eq. (4)) and $\mathbf{W}\mathbf{M} = \mathbf{Z}_\xi \approx \mathbf{Z}$ (to ensure the read-out is close to the written data). The minimum-norm least-square solutions of those linear systems are $\mathbf{W}_0 = \mathbf{Z}_\xi \mathbf{M}_0^+$ and $\mathbf{W} = \mathbf{Z}\mathbf{M}^+$, where $\mathbf{M}_0^+$ and $\mathbf{M}^+$ are pseudo-inverses of $\mathbf{M}_0$ and $\mathbf{M}$, respectively. While least-square condition is obvious since we would like to find solutions $\mathbf{W}_0$ and $\mathbf{W}$ that best fit the systems, explanation for minimum-norm condition will be given in Appendix J.

Computing pseudo-inverses

We do not always have an explicit formula for the pseudo-inverse, and even in such case, the formula may consist of inverse matrices which are expensive to compute. Ben-Israel and Cohen (1966) provides us an iterative way to approximate the pseudo-inverse, as stated in the following theorem:

Theorem 2.1. (Ben-Cohen algorithm) *Given a real matrix $\mathbf{D}$ and an initial matrix $\mathbf{D}_0$ of the same size with the transpose $\mathbf{D}^\top$. The sequence $\{\mathbf{D}_i\}_{i \geq 0}$ defined recursively as $\mathbf{D}_{i+1} = 2\mathbf{D}_i - \mathbf{D}_i\mathbf{D}\mathbf{D}_i$ will converge to the pseudo-inverse of $\mathbf{D}$. With appropriate $\mathbf{D}_0$, the sequence will converge quadratically.*

Ben-Cohen algorithm allows us to compute the matrix pseudo-inverse efficiently with nearly $O(1)$ time complexity in practice (see Section 3.5 for experimental results). For simplicity, we set the initial term $\mathbf{D}_0 = \alpha\mathbf{D}^\top$, where α is a hyper-parameter dependent of the dataset. Deeper analysis on initial condition for Ben-Cohen algorithm will be given in Appendix G.

Algorithm We are now ready to present the Generative Pseudo-Inverse Memory (GPM) in full. Assume that the observation noise ξ is sampled from $\mathcal{N}(\mathbf{0}, \sigma_\xi^2 \mathbf{I})$. Algorithm 1 illustrates a single training step of GPM. All pseudo-inverses are approximated by the Ben-Cohen algorithm.

2.2.1 REMARK: RELATION WITH EXISTING ALGORITHMS

Several properties of GPM are worth highlighting. GPM can be viewed as 2-step EM algorithm (Dempster et al., 1977). Detail is given in Appendix J. Moreover, in noiseless setting, i.e., $\xi \to 0$, GPM and Dynamic Kanerva Machine (DKM) (Wu et al., 2018b) coincide. In DKM, solving $\overline{\mathbf{W}}$ is related to minimizing $D_{\mathrm{KL}}\left(q(\mathbf{W}) \| p(\mathbf{W}|\mathbf{X}, \mathbf{M})\right)$, which is equivalent to the optimization problem

$$\min_{\overline{\mathbf{W}}} \left(\|\mathbf{Z} - \overline{\mathbf{W}}\mathbf{M}\|_F^2 + \sigma_\xi^2 \|\overline{\mathbf{W}}\|_F^2 \right). \tag{6}$$

This problem has a solution $\overline{\mathbf{W}}_{\sigma_\xi} = \mathbf{Z}\mathbf{M}^\top(\mathbf{M}\mathbf{M}^\top + \sigma_\xi^2\mathbf{I})^{-1}$. According to Theorem D.5, $\overline{\mathbf{W}}_{\sigma_\xi}$ converges to $\overline{\mathbf{W}}^* = \mathbf{Z}\mathbf{M}^+$ as $\sigma_\xi \to 0$. Note that $\overline{\mathbf{W}}^*$ is actually the reading weight of GPM.

2.3 ERROR BOUND

Using pseudo-inverses in Algorithm 1, we establish an error bound for the memory read-out, as stated in the following theorem:

Theorem 2.2. *Let $\|.\|_2$ denote the spectral norm. Suppose there exists $\alpha, \beta \in [0, 1)$ such that*

$$\|\mathbf{I} - \mathbf{Z}_\xi \mathbf{Z}_\xi^\top\|_2 \le \alpha \text{ and } \|\mathbf{I} - \mathbf{Z}_\xi \mathbf{Z}_\xi^+\|_2 \le \beta.$$

Then $\overline{\mathbf{W}}\mathbf{M} = \mathbf{Z}(\mathbf{I} + \mathbf{E})$, where $\mathbf{E}$ is the error matrix satisfying

$$\|\mathbf{E}\|_2 \le \beta + \|\mathbf{I} - \mathbf{W}_0\mathbf{W}_0^+\|_2 \sqrt{\frac{1+\alpha}{1-\alpha}}.$$

Corollary 2.3. *Assume that rank $\mathbf{W}_0 = $ rank $\mathbf{Z}_\xi = T$, i.e. rows of $\mathbf{W}_0$ and $\mathbf{Z}$ are linearly independent. Then $\overline{\mathbf{W}}\mathbf{M} = \mathbf{Z}$.*

Proofs are given in Appendix E. Theorem 2.2 and Corollary 2.3 establish that the error of memory retrieval can be bounded by other errors only dependent of the data $\mathbf{Z}$ and writing weight $\mathbf{W}_0$. When rows of $\mathbf{W}_0$ and $\mathbf{Z}_\xi$ are linearly independent, the retrieval is perfect. The trainable prior memory $\mathbf{M}_0$ helps the model balance approximation errors when ideal conditions are not met.

Corollary 2.3 also suggests that retrieval may be still accurate if rows of $\mathbf{W}_0$ and $\mathbf{Z}$ are sufficiently linearly independent. A well-known property on high dimensional space is two arbitrary vectors are likely to be orthogonal (Gorban and Tyukin, 2018). Thus we can expect that GPM will still work fairly well when $T \gg \max\{K, C\}$, i.e. the episode length is much greater than number of memory slots and size of embedding vectors. Empirical evidence will be given in Section 3.4.

2.4 ATTRACTOR DYNAMICS

We demonstrate that GPM inherits properties of energy-based models. The key property of models induced from dynamical systems is iterative reading, i.e. to iteratively reproduce the correct pattern from a partial broken query. With fixed memory $\mathbf{M}$, the energy function of GPM can be defined as a function of two variables $\mathbf{x}$ and $\mathbf{w}$:

$$\mathcal{E}(\mathbf{x}, \mathbf{w}) := -\ln p(\mathbf{x}|\mathbf{w}, \mathbf{M}) = -p(\mathbf{x}|\mathbf{M}) + \frac{\|e(\mathbf{x}) - \overline{\mathbf{w}}\mathbf{M}\|_F^2}{2\sigma_\xi^2} + \mathbf{r}. \tag{7}$$

Here we replaced $\mathbf{z}$ by $e(\mathbf{x})$ and note that the residual $\mathbf{r}$ is constant after training. Denote $(\mathbf{w}_i, \mathbf{x}_i)$ the pair of weight and reading output of the i-th iterative reading step. The output $\mathbf{x}_i$ is iteratively fed back to the model until convergence. With $\mathbf{x}_i$ as the query for $(i + 1)$-th step, solving for $\mathbf{w}_{i+1}$ minimizes $\|e(\mathbf{x}) - \overline{\mathbf{w}}\mathbf{M}\|_F^2$, which indicates $\mathcal{E}(\mathbf{x}_i, \mathbf{w}_{i+1}) > \mathcal{E}(\mathbf{x}_i, \mathbf{w}_i)$. With $\mathbf{w}_{i+1}$ in hand, the way we train the model encourages $\mathbf{x}_{i+1}$ to maximize the likelihood $p(\mathbf{x}|\mathbf{w}_{i+1}, \mathbf{M})$. If it is the case, $\mathcal{E}(\mathbf{x}_{i+1}, \mathbf{w}_{i+1}) > \mathcal{E}(\mathbf{x}_i, \mathbf{w}_{i+1})$ and therefore $\mathcal{E}(\mathbf{x}_{i+1}, \mathbf{w}_{i+1}) > \mathcal{E}(\mathbf{x}_i, \mathbf{w}_i)$. In ideal cases, $\{\mathbf{x}_i\}_{i \ge 0}$ will converge to a local minimum associated with a stored pattern in the energy landscape.

In practice, the system might not converge to a stored pattern but a spurious state, which is a local minimum different from stored patterns. Even with simple neural networks in low dimensional space, spurious local minima also exist (Safran and Shamir, 2018). This phenomenon is not expected when retrieving, but it may be helpful in generating new images as demonstrated in Section 3.3.

Method	Binarized MNIST 28×28 (nats/image)	Binarized Omniglot 28×28 (nats/image)	Fashion MNIST 28×28 (bits/dim)	CIFAR10 32×32 (bits/dim)	CIFAR100 32×32 (bits/dim)	CelebA 192×192 (bits/dim)
VAE (Kingma and Welling, 2014)	87.86	104.75	-	6.3	-	-
IWAE (Burda et al., 2016)	85.32	103.38	-	-	-	-
Improved decoders						
PixelVAE++ (Sadeghi et al., 2019)	78.00	-	-	**2.90**	-	-
MAE (Ma et al., 2019)	77.98	89.09	-	2.95	-	-
DRAW (Gregor et al., 2015)	87.4	96.5	-	3.58	-	-
MatNet (Bachman, 2016)	78.5	89.5	-	3.24	-	-
Richer priors						
Ordered ACN (Graves et al., 2018)	73.9	-	-	3.07	-	-
VLAE (Chen et al., 2017)	78.53	102.11	-	2.95	-	-
VampPrior (Tomczak and Welling, 2018)	78.45	89.76	-	-	-	-
Memory models						
VMA (Bornschein et al., 2017)	-	103.6	-	-	-	-
KM (Wu et al., 2018a)	-	68.3	-	4.37*	-	-
DNC (Graves et al., 2016)	-	100	-	-	-	-
DKM (Wu et al., 2018b)	75.3	77.2	3.97†	4.79	4.88†	4.71†
Kanerva++ (Ramapuram et al., 2021)	41.58	66.24	**3.40**	3.28	-	-
GPM (ours)	**31.48**	**25.68**	3.96	4.03	**4.05**	**4.63**

Table 1: *Negative evidence lower bound of test likelihood (lower is better).* Results are in nats/image for binarized dataset and bits/dim for continuous dataset. * Training evidence lower bound, estimated from Figure 12 in Wu et al. (2018a). † Our implementation.

3 EXPERIMENTS

We examine GPM on common generative memory benchmarking datasets including binarized MNIST (LeCun et al., 2010), binarized Omniglot (Burda et al., 2016), FashionMNIST (Xiao et al., 2017), CIFAR10, CIFAR100 (Krizhevsky, 2009) and CelebA (Liu et al., 2015). To prove the effectiveness of our memory model, we only use simple encoders and decoders. The details of image preprocessing, network architecture and training procedure are given in Appendix C.

We compare our model to recent generative memory models such as Kanerva Machine (KM), Dynamic Kanerva Machine (DKM) and Kanerva++. In GPM, most of the parameters come from the encoder and the decoder since the trainable prior memory $\mathbf{M}_0$ and the weight variance $\sigma_{\mathbf{W}}^2$ only account for only $KC + 1$ parameters. Hence, the number of parameters of GPM is comparable to other baselines with similar architectures of encoder and decoder.

3.1 RECONSTRUCTION

In this task, we validate the memory model's ability to reconstruct image data. For each dataset, we sample 32 images to form the episode as the input to the memory models during both encoding and decoding phase. We then train all the models to optimize the objective in Eq. (2) for 10,000-15,000 iterations, depending on the dataset. Table 1 reports the negative evidence lower bound of GPM and that of other baselines on 6 datasets. For binarized datasets, we see a significant improvement in the ELBO: **31.48 nats/image** compared to current state-of-the-art 41.58 nats/images on MNIST dataset and **25.68 nats/image** compared to current state-of-the-art 66.24 nats/image on Omniglot dataset. On RGB datasets, GPM shows competitive results, achieving the best performance on 2 out of 4 datasets. We note that for complex image data, the role of the encoder and decoder is very important and GPM's ones are simpler than those of Kanerva++. Hence, we underperform Kanerva++ on 2 tasks. However, compared to models with similar encoder-decoder like KM and DKM, GPM performs much better, which indicates the benefit of our pseudo-inverse memory mechanisms.

To verify that our GPM supports exact memory retrieval, we measure the the cosine similarity between the data written to the memory and memory read-out's of GPM in Omniglot task (see Appendix Figure 7). As expected, GPM almost retrieves exactly what was written to the memory (average similarity ≈ 1), which is much better than that of Dynamic Kanerva Machine (0.82).

3.2 DENOISING

The denoising capability of a memory model resembles human's ability to retrieve old memories with blurry clues. This process can be implemented using iterative reading, where in each step the

	salt & pepper noise (15%)			block noise (12 × 12)			rotation noise (30°)		
	$T = 4$	$T = 8$	$T = 16$	$T = 4$	$T = 8$	$T = 16$	$T = 4$	$T = 8$	$T = 16$
GPM (ours)	**40.59%**	**37.75%**	**16.89%**	**57.42%**	**40.10%**	**18.69%**	**66.09%**	**57.55%**	**39.98%**
DKM (Wu et al., 2018b)	5.20%	1.24%	0.61%	7.18%	2.10%	1.18%	7.67%	4.33%	1.79%

Table 2: *Denoising success rate on binarized Omniglot dataset.* A denoising process is successful if it can retrieve the original image with at most 1% error, which is equivalent to 7 pixels.

model adds some more details to the image to reconstruct the original picture from a noisy query image. Illustration for the denoising process of GPM is given in Appendix B.

To measure the denoising capability of GPM and DKM, we run denoising experiments with different episode lengths, types of noise and levels of noise on the binarized Omniglot dataset. We use the Hamming distance to measure error between denoised images and correct ones. In all experiments, we run iterative reading for 20 steps. Results in Figure 2 demonstrate that overall GPM achieves significantly better performance than DKM. Remarkably, GPM maintains a clear performance gap when the episode lengths or the level of noise vary. To better quantize the difference, we reported the denoising success rate of GPM and DKM in Table 2. Here we consider a denoising process to be successful if it can recover the original image with at most 1% error, which is equivalent to at most 7 pixels for the Omniglot dataset. The results show that GPM also outperforms DKM in all cases with a performance gap ranging from 15% to 58%.

Figure 2: *Hamming error measuring the denoising capibility of GPM and DKM (lower is better).* Experiments are conducted on binarized Omniglot dataset. We test denoising capability of both models with different episode length ($T = 4, 8, 16$), types of noise (salt & pepper noise, block noise, rotation noise) and levels of noise (5% − 20% salt & pepper noise, block noise with block size from 6 × 6 to 15 × 15, rotation noise with rotation angle from 15° to 45°).

3.3 GENERATION

We illustrate the ability to generate new images of GPM using Omniglot and CIFAR10 images in Figure 3. The generation process consists of 2 main steps: (1) sample some images to form an episode and write it to the memory; (2) sample $\mathbf{w} \sim p(\mathbf{w})$ ($\mathbf{w}$ is a vector of size $1 \times K$) and take $\mathbf{z} = \mathbf{wM}$ to be the read-out vector. The generated images will be improved via iterative reading. We observe that GPM can generate images that do not appear in the written episode. This phenomenon can be viewed

in Figure 3a, where we compare generated patterns with their most similar ones in the episode written to the memory in terms of Hamming distance. Here the generated images with additional details are generally different from their nearest neighbors. More interestingly, in Figure 3b, we can see a generated aircraft image that inherits the background of the frog image (the 3rd row). Theoretically speaking, these new images are formed from spurious local minima, as discussed in Section 2.4.

Figure 3: *GPM's generated samples.* **(a)** *Omniglot patterns.* Patterns in the box are the nearest patterns in the episode compared with final generated images on the left. Distance between images is measured by the Hamming distance. **(b)** *CIFAR10 images.* Images in the leftmost is the episode written to memory. Each image is repeated 3 times to help the generations better. Images in the box are nearest images in the episode compared with final generated images on the left. We use Euclidean metric to measure distance between images.

3.4 GPM AS A HUGE STORAGE

We conduct experiments to test the memory capacity of GPM. The experiments still revolve around reconstructing, denoising and generating images, yet on larger episode length. We use the whole Omniglot dataset with $24,345$ training images to train GPM for around $24,000$ iterations for all experiments. For convention, we denote the T-GPM as the GPM trained on episode of length T. Results are shown in Figure 4.

In reconstruction experiment, we keep the memory size fixed and increase the episode length from minimum (equivalent to the number of memory slots) to maximum ($24,345$, which is the whole set of training images). We run the experiment with two memory configurations: 8×100 and 32×100. With the same episode length, the 32×100 memory always performs better, which is reasonable since bigger memory enables better storage capability. We also observe a more interesting phenomenon in both configurations: from a certain point, the reconstruction loss seems to be stable even when we double the episode length. This agrees with earlier discussion in Section 2.2, where we argue GPM can handle big episode thanks to the orthogonality of random vectors on high dimensional space.

We also test the denoising and generating capabilities of GPM when trained with a large episode size. We are curious whether GPM can keep these abilities (to some extent) when storing lots of information. We use the $24,345$-GPM with 32×100 memory in these experiments. At test time, we first write the whole test set of 8070 images to the memory and keep this posterior memory fixed, then we either input noisy queries for denoising or sample from the memory for generating images. Despite the huge amount of information compressed into the memory, the model can still denoise and generate images with moderate quality. The average Hamming error when denoising is 97.08, which is approximately 12.4% of the total pixels.

We note that other baselines such as KM and DKM are inapplicable to such a large scale scenario due to their slow memory mechanisms. In contrast, GPM can be trained efficiently even with episodes of $24,345$ images. More experiments regarding this point are conducted in the next section.

3.5 ABLATION: RUNNING TIME

GPM is designed to avoid the computation complexity $O(K^3)$ of inverting matrices and $O(T)$ of online Bayesian update. We conduct experiments to show the time efficiency of GPM compared to DKM in practice. All operations are computed on a single GPU. We use the `inverse` function of Pytorch 1.8.0 (Paszke et al., 2017) for batch matrix inverse. Results are shown in Figure 5.

In the first experiment, we run GPM with 7 approximation steps for the pseudo-inverses and compare the running time against DKM in different cases of episode and memory size. As expected, the

Figure 4: **(a)** Reconstruction loss of GPM with fixed memory size and increasing episode length. **(b)** Denoising salt and pepper noise (5%) of the 24, 345-GPM with 32×100 memory. Patterns in the first column are original ones; patterns in the blue box are noisy queries; following columns are denoising process during iterative reading. **(c)** Generated patterns of the 24, 345-GPM with 32×100 memory. Patterns in the orange box are closest patterns written to the memory compared with generated patterns on their left.

Figure 5: *Running time per iteration. Left:* Running time per iteration comparison between GPM and DKM. GPM has a time complexity of almost $O(1)$ with respect to the episode size and memory size. *Right:* Running time per iteration of GPM with different number of pseudo-inverse approximation steps.

running time of DKM increases as the memory size K increases while GPM maintains almost same performance. Moreover, we can see a problem of Bayesian update on the running time: if we double the episode size and keep the same memory size, the running time also doubles. In contrast, it only yields a modest increase in the running time of GPM.

In the second experiment, we would like to see how the number of pseudo-inverse approximation steps affects the running time of GPM in two cases: $T = 64, K = 64$ and $T = 128, K = 64$. The running time curves in two cases share a similar trend: they depend linearly on the number of approximation steps. Hence, it is important to choose an appropriate initial term for the approximation sequence to reduce the number of approximation steps. More discussion is given in Appendix G.

4 DISCUSSION

We have proposed Generative Pseudo-Inverse Memory (GPM) to overcome crucial limitations of previous generative memory models. GPM is not only able to operate fast but also store a large amount of data at a time while maintaining abilities of denoising corrupted patterns and generating novel patterns. We derived an associated energy function and shown that iterative updates in GPM induce an attractor dynamics converging toward fixed points. We demonstrated these capacities on an extensive set of experiments, obtaining superior results.

These new capacities of GPM as a generative memory open up new exciting rooms of investigation. A primary direction is positioning GPM as working memory whose size and processing speed are known to be critical for high-level reasoning (Kyllonen and Christal, 1990), i.e., the capacity to deduce new knowledge through manipulating the old. Here the query encoder will support arbitrary query format, and the decoder will support answer generation. As GPM is designed for episodic handling, streaming data can be periodically cached through local registers before sending to GPM. This has been shown to be effective for slot-based memories (Le et al., 2019), and it remains open to theoretically quantify the effect on generative memories.

REFERENCES

D. Addis, Alana T. Wong, and D. Schacter. Remembering the past and imagining the future: Common and distinct neural substrates during event construction and elaboration. *Neuropsychologia*, 45: 1363–1377, 2007.

Philip Bachman. An architecture for deep, hierarchical generative models. In *NIPS*, 2016.

S. Banach. Sur les opérations dans les ensembles abstraits et leur application aux équations intégrales. *Fundamenta Mathematicae*, 3:133–181, 1922.

A. Ben-Israel and D. Cohen. On iterative computation of generalized inverses and associated projections. *SIAM Journal on Numerical Analysis*, 3:410–419, 1966.

A. Ben-Israel and T. Greville. Generalized inverses: theory and applications. 2001.

Jörg Bornschein, Andriy Mnih, Daniel Zoran, and Danilo J Rezende. Variational memory addressing in generative models. *Advances in Neural Information Processing Systems*, pages 3920–3929, 2017.

Yuri Burda, Roger B. Grosse, and R. Salakhutdinov. Importance weighted autoencoders. *ICLR*, 2016.

Xi Chen, Diederik P Kingma, Tim Salimans, Yan Duan, Prafulla Dhariwal, John Schulman, Ilya Sutskever, and Pieter Abbeel. Variational lossy autoencoder. *ICLR*, 2017.

A. Dempster, N. Laird, and D. Rubin. Maximum likelihood from incomplete data via the em algorithm. 1977.

Alexander N. Gorban and Ivan Y. Tyukin. Blessing of dimensionality: mathematical foundations of the statistical physics of data. *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, 376, 2018.

Alex Graves, Greg Wayne, Malcolm Reynolds, Tim Harley, Ivo Danihelka, Agnieszka Grabska-Barwińska, Sergio Gómez Colmenarejo, Edward Grefenstette, Tiago Ramalho, John Agapiou, et al. Hybrid computing using a neural network with dynamic external memory. *Nature*, 538(7626): 471–476, 2016.

Alex Graves, Jacob Menick, and Aaron van den Oord. Associative compression networks for representation learning. *arXiv preprint arXiv:1804.02476*, 2018.

K. Gregor, Ivo Danihelka, A. Graves, Danilo Jimenez Rezende, and Daan Wierstra. Draw: A recurrent neural network for image generation. *ICML*, 2015.

Kaiming He, X. Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 770–778, 2016.

A. Jensen and Ella Munro. Reaction time, movement time, and intelligence. *Intelligence*, 3:121–126, 1979.

P. Kanerva. Self-propagating search: a unified theory of memory (address decoding, cerebellum). 1984.

Diederik P. Kingma and M. Welling. Auto-encoding variational bayes. *ICLR*, 2014.

A. Krizhevsky. Learning multiple layers of features from tiny images. 2009.

P. Kyllonen and R. E. Christal. Reasoning ability is (little more than) working-memory capacity?! *Intelligence*, 14:389–433, 1990.

Hung Le, , Truyen Tran, and Svetha Venkatesh. Learning to remember more with less memorization. In *ICLR 2019: Proceedings of the 7th International Conference on Learning Representations*, 2019.

Yann LeCun, Corinna Cortes, and CJ Burges. Mnist handwritten digit database. *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, 2, 2010.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Xuezhe Ma, Chunting Zhou, and E. Hovy. Mae: Mutual posterior-divergence regularization for variational autoencoders. *ICLR*, 2019.

J. Okuda, T. Fujii, H. Ohtake, T. Tsukiura, K. Tanji, Kyoko Suzuki, R. Kawashima, H. Fukuda, M. Itoh, and A. Yamadori. Thinking of the future and past: the roles of the frontal pole and the medial temporal lobes. *NeuroImage*, 19:1369–1380, 2003.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Prajit Ramachandran, Barret Zoph, and Quoc V. Le. Swish: a self-gated activation function. *arXiv: Neural and Evolutionary Computing*, 2017.

Jason Ramapuram, Yan Wu, and Alexandros Kalousis. Kanerva++: extending the kanerva machine with differentiable, locally block allocated latent memory. *ICLR*, 2021.

Hubert Ramsauer, Bernhard Schäfl, Johannes Lehner, Philipp Seidl, Michael Widrich, Thomas Adler, Lukas Gruber, Markus Holzleitner, Milena Pavlović, Geir Kjetil Sandve, et al. Hopfield networks is all you need. *arXiv preprint arXiv:2008.02217*, 2020.

Hubert Ramsauer, Bernhard Schäfl, Johannes Lehner, Philipp Seidl, Michael Widrich, Lukas Gruber, Markus Holzleitner, Thomas Adler, David Kreil, Michael K Kopp, et al. Hopfield networks is all you need, 2021.

S.M Rump. Verified bounds for singular values, in particular for the spectral norm of a matrix and its inverse. *Bit Numer Math 51, 367â384*, 2011.

Hossein Sadeghi, Evgeny Andriyash, Walter Vinci, Lorenzo Buffoni, and Mohammad H Amin. Pixelvae++: Improved pixelvae with discrete prior. *arXiv preprint arXiv:1908.09948*, 2019.

Itay Safran and O. Shamir. Spurious local minima are common in two-layer relu neural networks. *ICML*, 2018.

Tim Salimans, A. Karpathy, Xi Chen, and Diederik P. Kingma. Pixelcnn++: Improving the pixelcnn with discretized logistic mixture likelihood and other modifications. *ArXiv*, abs/1701.05517, 2017.

D. Schacter, D. Addis, D. Hassabis, Victoria C. Martin, R. N. Spreng, and K. Szpunar. The future of memory: Remembering, imagining, and the brain. *Neuron*, 76:677–694, 2012.

T. Söderström and G. Stewart. On the numerical properties of an iterative method for computing the mooreâpenrose generalized inverse. *SIAM Journal on Numerical Analysis*, 11:61–74, 1974.

G. S. Stiles and Dong-Lih Denq. On the effect of noise on the moore-penrose generalized inverse associative memory. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, PAMI-7: 358–360, 1985.

Jakub Tomczak and Max Welling. Vae with a vampprior. In *International Conference on Artificial Intelligence and Statistics*, pages 1214–1223. PMLR, 2018.

Yan Wu, Greg Wayne, A. Graves, and T. Lillicrap. The kanerva machine: A generative distributed memory. *ICLR*, 2018a.

Yan Wu, Greg Wayne, Karol Gregor, and Timothy Lillicrap. Learning attractor dynamics for generative memory. *NeurIPS*, 2018b.

Han Xiao, Kashif Rasul, and Roland Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *ArXiv*, abs/1708.07747, 2017.

G. Yen and A. Michel. A learning and forgetting algorithm in associative memories: results involving pseudo-inverses. *IEEE Transactions on Circuits and Systems*, 38:1193–1205, 1991.

APPENDIX

A RECONSTRUCTIONS

Figure 6: Reconstructions of GPM. *Left:* original images. *Right:* reconstructions. **(a)** Omniglot **(b)** CIFAR10 **(c)** CIFAR100 **(d)** CelebA

Figure 7: *Average cosine similarity between exact embeddings and read-out's in DKM and GPM.* Train and test on Omniglot dataset.

B   DENOISING

We demonstrate denoising capibility of GPM in Fig. 8. The denoising process consists of two steps: we first write the correct patterns into the memory, then read from the memory using noisy queries. The image will be completed during iterative reading.

Figure 8: *Retrieving pattern with noisy query during iterative reading*. Top rows are correct patterns; rows in the boxes are corrupted patterns; following rows are retrieval process with iterative reading. **(a)** Salt and pepper noise (15%). **(b)** Block noise (12×12 block) to cover a part of the correct pattern. **(c)** Rotation noise (rotation angle uniformly selected from -45 to 45 degrees). **(d)** Gaussian noise with standard deviation 0.5. **(e)** Illustration of energy decrease during retrieving Omniglot patterns. Although sometimes the energy diverges and iterative reading leads to a meaningless pattern, overall, the energy decreases during iterations.

C   TRAINING DETAILS

The encoder consists of 4 layers, each of which is a convolution layer with 4×4 filter with stride 2 followed by a Resnet block with bottleneck (He et al., 2016). The decoder is simply a mirror of the encoder with transpose convolutional layer. We use the swish activation function (Ramachandran et al., 2017) non-linear layers. For binarized datasets, we use 16 filters for all convnets; for real-valued datasets, we use 256 filters to adapt with the complexity of the data.

The Omniglot is a dataset with great diversity, consists of 1623 different classes and 20 images in each class. Following settings in (Burda et al., 2016), the dataset is splitted into 24,345 training and 8,070 test examples. We use a 32×100 memory for this dataset. The data noise when writing is sampled from $\mathcal{N}(\mathbf{0}, 0.5^2\mathbf{I})$. At each training step, we randomly sample 32 images to form an episode. We run the Ben-Cohen algorithm for 7 steps to approximate the pseudo-inverses, with the initial term is 10^{-3} times the transpose of the matrix which we want to calculate the pseudo-inverse. We use the Bernoulli likelihood for all binarized datasets.

For real-valued datasets, we use a 128×512 memory with data noise sampled from $\mathcal{N}(\mathbf{0}, 0.5^2\mathbf{I})$. All other settings are the same with the Omniglot dataset, except for the initial terms of the Ben-Cohen algorithm: 10^{-4} times the transpose of the matrix when approximating pseudo-inverse of the weight matrix and $5 \cdot 10^{-5}$ times the transpose of the matrix when approximating pseudo-inverse of the memory. We use the discretized mixture of logistics (Salimans et al., 2017) for the output distribution.

In all experiments, we use the Adam optimizer with learning rate varying from $5 \cdot 10^{-5}$ to $5 \cdot 10^{-4}$ depending on the dataset. We use weight decay of 10^{-3} along with gradient clipping at threshold 10. For real-valued datasets, we additionally use a scheduler to reduce the learning rate by 0.99995 after each training epoch. We train all models for 500-1000 epochs with exception 30 epochs for CelebA dataset.

D   PROPERTIES OF PSEUDO-INVERSE

In this section, we outline the definition and some important properties of the pseudo-inverse of a matrix. Most of the proofs of following propositions and theorems can be found in (Ben-Israel and Greville, 2001).

Definition D.1. For every real matrix $\mathbf{A}$ (square or rectangular), there is a unique matrix $\mathbf{Y}$ satisfying all following conditions: $\mathbf{AYA} = \mathbf{A}, \mathbf{YAY} = \mathbf{Y}, (\mathbf{AY})^\top = \mathbf{AY}$ and $(\mathbf{YA})^\top = \mathbf{YA}$, where $^\top$ denotes the transpose of a matrix. The matrix $\mathbf{Y}$ is called the *pseudo-inverse* of $\mathbf{A}$, denoted by $\mathbf{A}^+$.

If $\mathbf{A}$ is a square matrix and non-singular, then $\mathbf{A}^+$ is the inverse $\mathbf{A}^{-1}$ of $\mathbf{A}$. If $\mathbf{A}$ is rectangular of size $m \times n$, then $\mathbf{A}^+$ is of size $n \times m$. The following propositions shows some important relations between $\mathbf{A}$ and $\mathbf{A}^+$.

Proposition D.2. *Let $\mathbf{A}$ be a $m \times n$ real matrix. Then*

  1. $\mathbf{A}^+\mathbf{A} = \mathbf{I}_n$ if and only if $\mathrm{rank}\mathbf{A} = n$ (i.e. columns of $\mathbf{A}$ are linearly independent), where $\mathbf{I}_n$ is the $n \times n$ identity matrix;
  2. $\mathbf{A}\mathbf{A}^+ = \mathbf{I}_m$ if and only if $\mathrm{rank}\mathbf{A} = m$ (i.e. rows of $\mathbf{A}$ are linearly independent), where $\mathbf{I}_m$ is the $m \times m$ identity matrix.

Proposition D.3. *For every real matrix $\mathbf{A}$:*

  1. $(\mathbf{A}^+)^+ = \mathbf{A}$;
  2. $(\mathbf{A}^\top)^+ = (\mathbf{A}^+)^\top$;
  3. $\mathbf{A}^+ = (\mathbf{A}^\top\mathbf{A})^+\mathbf{A}^\top = \mathbf{A}^\top(\mathbf{A}\mathbf{A}^\top)^+$.

If $\mathbf{A}$ and $\mathbf{B}$ are square invertible matrices such that $\mathbf{AB}$ is also invertible, then we have the well-known property $(\mathbf{AB})^{-1} = \mathbf{B}^{-1}\mathbf{A}^{-1}$. The same property does not always hold for pseudo-inverse. However, with some sufficient condition of independence, we will get the desired property.

Proposition D.4. *If $\mathbf{A}$ has linearly independent columns or $\mathbf{B}$ has linearly independent rows, then* $(\mathbf{AB})^+ = \mathbf{B}^+\mathbf{A}^+$.

Theorem D.5. *For any real matrix $\mathbf{A}$ of size $m \times n$, the limit $\lim\limits_{\sigma \searrow 0} \mathbf{A}^\top(\mathbf{A}\mathbf{A}^\top + \sigma\mathbf{I}_m)^{-1}$ always exists. Moreover, $\lim\limits_{\sigma \searrow 0} \mathbf{A}^\top(\mathbf{A}\mathbf{A}^\top + \sigma\mathbf{I}_m)^{-1} = \mathbf{A}^+$.*

The concept of pseudo-inverse arose when ones tried to solve the linear system $\mathbf{Ax} = \mathbf{b}$, where $\mathbf{b}$ is some vector with appropriate size. When the system has no solution, it is reasonable to find some vector $\mathbf{x}$ that minimizes the Euclidean norm of the residual $\mathbf{r} = \mathbf{b} - \mathbf{Ax}$. Any solution of the optimization problem $\min_\mathbf{x} \|\mathbf{b} - \mathbf{Ax}\|_F$ (where $\|.\|_F$ is the Frobenius norm) is called the *least-square solution* of the system $\mathbf{Ax} = \mathbf{b}$. It can be proven that $\mathbf{x} = \mathbf{A}^+\mathbf{b}$ is a least-square solution. Moreover, among the least-square solutions of system $\mathbf{Ax} = \mathbf{b}$, $\mathbf{x} = \mathbf{A}^+\mathbf{b}$ is the one of minimum Euclidean norm, i.e. the *minimum-norm least-square solution*. This result can be generalized as in the following proposition.

Proposition D.6. *Let $\mathbf{A}, \mathbf{B}, \mathbf{D}$ be real matrices with appropriate size. The minimum-norm least-square solution of the system $\mathbf{AXB} = \mathbf{D}$ is $\mathbf{X} = \mathbf{A}^+\mathbf{D}\mathbf{B}^+$.*

E   PROOFS OF THEORETICAL RESULTS ON ERROR BOUNDS

We provide the proofs for Theorem 2.2 and Corollary 2.3.

Proof of Theorem 2.2. For convention, let us denote $\mathbf{E}_{\mathbf{W}_0} = \mathbf{W}_0\mathbf{W}_0^+ - \mathbf{I}$. Following Algorithm 1, we get

$$
\begin{aligned}
\overline{\mathbf{W}}\mathbf{M} &= \mathbf{Z}\mathbf{Z}_\xi^+\mathbf{W}_0\mathbf{W}_0^+\mathbf{Z}_\xi \\
&= \mathbf{Z}\mathbf{Z}_\xi^+(\mathbf{I} + \mathbf{E}_{\mathbf{W}_0})\mathbf{Z}_\xi \\
&= \mathbf{Z}\left[\mathbf{I} + (\mathbf{Z}_\xi^+\mathbf{Z}_\xi - \mathbf{I}) + \mathbf{Z}_\xi^+\mathbf{E}_{\mathbf{W}_0}\mathbf{Z}_\xi\right].
\end{aligned}
$$

Since $\|\mathbf{I} - \mathbf{Z}_\xi \mathbf{Z}_\xi^\top\|_2 \le \alpha$, by (Rump, 2011, Lemma 2.2), it follows $\|\mathbf{Z}_\xi\|_2 \le \sqrt{1+\alpha}$ and $\|\mathbf{Z}_\xi^+\|_2 \le \frac{1}{\sqrt{1-\alpha}}$. Since $\|.\|_2$ is a multiplicative norm, we finally have

$$\left\|(\mathbf{Z}_\xi^+ \mathbf{Z}_\xi - \mathbf{I}) + \mathbf{Z}_\xi^+ \mathbf{E}_{\mathbf{W}_0} \mathbf{Z}_\xi\right\|_2 \le \left\|\mathbf{Z}_\xi^+ \mathbf{Z}_\xi - \mathbf{I}\right\|_2 + \left\|\mathbf{Z}_\xi^+ \mathbf{E}_{\mathbf{W}_0} \mathbf{W}_\xi\right\|_2$$
$$\le \beta + \|\mathbf{E}_{\mathbf{W}_0}\|_2 \sqrt{\frac{1+\alpha}{1-\alpha}},$$

which is our desired result.

Proof of Corollary 2.3: This is a special case of Theorem 2.2. When rows of $\mathbf{W}_0$ and $\mathbf{Z}$ are independent, $\mathbf{W}_0 \mathbf{W}_0^+ = \mathbf{I}$ and $\mathbf{Z}_\xi \mathbf{Z}_\xi^+ = \mathbf{I}$, which leads to $\mathbf{E}_{\mathbf{W}_0} = 0$ and $\beta = 0$.

F   ITERATIVE READING FROM THE VIEW OF FIXED POINT

In addition to the discussion in Section 2.4, we can alternatively think about the attractor as the fixed point of the reading operation. Assume that the current query is $\mathbf{q}_t$ and the next query is determined by $\mathbf{q}_{t+1} = f(\mathbf{q}_t)$, where f represents for the reading operation. If $\{\mathbf{q}_t\}$ converges to some $\mathbf{q}^*$, then $\mathbf{q}^* = f(\mathbf{q}^*)$, which means $\mathbf{q}^*$ is a fixed point of f. If the model is well-trained, stored patterns are fixed points of f. (Banach, 1922) provides a sufficient condition for an iterative sequence to converge to a fixed point. Roughly speaking, if $\mathbf{q}^*$ is a fixed point of f such that $\|\mathbf{J}(\mathbf{q}^*)\|_2 < 1$ (where $\mathbf{J}$ is the Jacobian of f) and the whole sequence $\{\mathbf{q}_t\}_{t \ge 0}$ locates in a small neighborhood of $\mathbf{q}^*$, then $\mathbf{q}_t \to \mathbf{q}^*$. This result demonstrates the ability to converge to a correct pattern given a good enough initial query. Similar to spurious local minima in the energy landscape, there also exists many spurious fixed points in the f landscape (see Fig. 9). This phenomenon is not expected when retrieving, but it may be helpful in case we want to generate new images as demonstrated in Section 3.3.

Figure 9: *The three cases of fixed points.* **(a) Fixed point is single pattern:** patterns are stored if they are well separated. Each pattern x_i has a single fixed point x_i^* close to it. **(b) Fixed point is average of similar patterns:** x_i and x_j are similar to each other and not well separated. The fixed point m_x^* is a spurious fixed point that is close to the mean m_x of the similar patterns. **(c) Fixed point is average of all patterns:** no pattern is well separated from the others. A single global fixed point m_x^* exists that is close to the arithmetic mean m_x of all patterns. Images and caption are taken from (Ramsauer et al., 2020).

G   INITIAL CONDITION FOR BEN-COHEN ALGORITHM

Suppose $\mathbf{A}$ is a real matrix. With $0 < \alpha < \frac{2}{\sigma_1^2}$, where σ_1 is the largest eigenvalue of $\mathbf{A}\mathbf{A}^\top$, the sequence defined as $\mathbf{A}_0 = \alpha \mathbf{A}^\top$, $\mathbf{A}_{i+1} = 2\mathbf{A}_i - \mathbf{A}_i \mathbf{A} \mathbf{A}_i$ will converge to $\mathbf{A}^+$ (Ben-Israel and Cohen, 1966). This choice of initial term may lead to slow convergence when the condition number $\kappa(\mathbf{A}) = \|\mathbf{A}\|_2 \|\mathbf{A}^+\|_2$ is large (Söderström and Stewart, 1974). If we start with an $\mathbf{A}_0$ such that $\mathbf{A}_0 \mathbf{A} = (\mathbf{A}_0 \mathbf{A})^\top$ and $\mathbf{A}_0$ is already close to $\mathbf{A}^+$, for example $\mathbf{A}_0 = \mathbf{A}^\top (\mathbf{A}\mathbf{A}^\top + \delta \mathbf{I})^{-1}$ where $\delta > 0$ and small enough, then $\{\mathbf{A}_i\}_{i \ge 0}$ converges quadratically to $\mathbf{A}^+$. However, this requires us to calculate the inverse of $\mathbf{A}\mathbf{A}^\top + \delta \mathbf{I}$, which we tend to completely avoid in GPM. Therefore we keep the original setting of Ben-Cohen for the initial term and let the model adapt with the approximation error.

H SOLUTION OF BAYESIAN UPDATE OPTIMIZATION PROBLEM

Let $\mathbf{M}_0, \mathbf{M}$ denote random variables of the prior and posterior memory, respectively, and suppose that both have matrix Gaussian distributions. Specifically, $\mathbf{M}_0 \sim \mathcal{N}(\mathbf{R}_0, \mathbf{U}_0, \mathbf{I})$ and $\mathbf{M} \sim \mathcal{N}(\mathbf{R}, \mathbf{U}, \mathbf{I})$. Given the prior $\mathbf{M}_0$, the to-be-written data $\mathbf{Z}$ and the writing weight $\mathbf{W}_0$, the optimization problem

$$\min_{\mathbf{A}, \mathbf{B}} \mathbb{E}\left(\|\mathbf{M} - \mathbf{M}_0\|_F^2\right) \quad \text{s.t.} \quad \mathbf{M} = \mathbf{A}\mathbf{Z} + \mathbf{B} \quad \text{and} \quad \mathbf{Z} = \mathbf{W}_0 \mathbf{M}_0 + \xi$$

has a unique solution $\mathbf{M} \sim \mathcal{N}(\mathbf{R}, \mathbf{U}, \mathbf{I})$, where

$$\mathbf{R} = \mathbf{R}_0 + \mathbf{U}_0^\top \mathbf{W}_0^\top \left(\mathbf{W}_0 \mathbf{U}_0 \mathbf{W}_0^\top + \Sigma_\xi\right)^{-1} (\mathbf{Z} - \mathbf{W}\mathbf{R})$$

$$\text{and} \quad \mathbf{U} = \mathbf{U}_0 - \mathbf{U}_0^\top \mathbf{W}_0^\top \left(\mathbf{W}_0 \mathbf{U}_0 \mathbf{W}_0^\top + \Sigma_\xi\right)^{-1} \mathbf{W}_0 \mathbf{U}_0,$$

where Σ_ξ is diagonal matrix whose diagonal elements are σ_ξ^2.

I DERIVATION FOR EVIDENCE LOWER BOUND

The evidence lower bound of the conditional log-likelihood $p(\mathbf{X}|\mathbf{M})$ can be derived as

$$
\begin{aligned}
\ln p(\mathbf{X}|\mathbf{M}) &= \mathbb{E}_{q(\mathbf{W})}\left[\ln \frac{p(\mathbf{X}|\mathbf{M})q(\mathbf{W})}{q(\mathbf{W})}\right] \\
&= \mathbb{E}_{q(\mathbf{W})}\left[\ln \frac{p(\mathbf{X}|\mathbf{W}, \mathbf{M})p(\mathbf{W}|\mathbf{M})q(\mathbf{W})}{p(\mathbf{W}|\mathbf{X}, \mathbf{M})q(\mathbf{W})}\right] \\
&= \mathcal{L}_T + D_{\mathrm{KL}}(q(\mathbf{W})\|p(\mathbf{W}|\mathbf{X}, \mathbf{M})).
\end{aligned}
$$

J RELATION WITH EM ALGORITHM

We show that GPM can be viewed as 2-step EM algorithm (Dempster et al., 1977). Let us remind ourselves the log-likelihood approximation derived in Section 2.1:

$$\ln p(\mathbf{X}|\mathbf{M}) = \mathbb{E}_{q(\mathbf{W})} \ln p(\mathbf{X}|\mathbf{W}, \mathbf{M}) - D_{\mathrm{KL}}(q(\mathbf{W})\|p(\mathbf{W})) + D_{\mathrm{KL}}(q(\mathbf{W})\|p(\mathbf{W}|\mathbf{X}, \mathbf{M})). \quad (8)$$

Keeping $p(\mathrm{vec}(\mathbf{W})) \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$ in mind, we can rewrite the conditional log-likelihood as

$$\ln p(\mathbf{X}|\mathbf{M}) = \mathbb{E}_{q(\mathbf{W})} \ln p(\mathbf{X}|\mathbf{W}, \mathbf{M}) + \frac{\|\mathbf{Z} - \overline{\mathbf{W}}\mathbf{M}\|_F^2}{2\sigma_\xi^2} + \mathbf{R}, \quad (9)$$

where $\mathbf{R}$ is residual term that is independent of $\overline{\mathbf{W}}$. From the perspective of EM algorithm and Eq. ((9)), Algorithm 1 can be thought as a 2-step process to maximize the log-likelihood:

1. Keeping the likelihood unchanged and tightening the bound by minimizing $\|\mathbf{Z} - \overline{\mathbf{W}}\mathbf{M}\|_F^2$;
2. Maximizing $\mathbb{E}_{q(\mathbf{W})} \ln p(\mathbf{X}|\mathbf{W}, \mathbf{M})$, i.e. the negative reconstruction loss.

Note that in training, we maximize the evidence lower bound $\mathcal{L}_T = \mathbb{E}_{q(\mathbf{W})} \ln p(\mathbf{X}|\mathbf{W}, \mathbf{M}) - D_{\mathrm{KL}}(q(\mathbf{W})\|p(\mathbf{W}))$ instead of $\mathbb{E}_{q(\mathbf{W})} \ln p(\mathbf{X}|\mathbf{W}, \mathbf{M})$. Therefore, for the maximum values of $\mathcal{L}_T$ and $\mathbb{E}_{q(\mathbf{W})} \ln p(\mathbf{X}|\mathbf{W}, \mathbf{M})$ to be as close as possible, we look for $\overline{\mathbf{W}}$ that minimizes $D_{\mathrm{KL}}(q(\mathbf{W})\|p(\mathbf{W}))$. Since $p(\mathrm{vec}(\mathbf{W})) \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$, this is equivalent to seeking $\overline{\mathbf{W}}$ with minimum norm. This fits with the step of finding the weight matrix $\overline{\mathbf{W}}$ in the reading phase, where we determine $\overline{\mathbf{W}} = \mathbf{Z}\mathbf{M}^+$, which is the least-square minimum-norm solution of the linear system $\overline{\mathbf{W}}\mathbf{M} = \mathbf{Z}$.