Incorporating Prior Knowledge into Neural Networks through an Implicit Composite Kernel

Abstract

It is challenging to guide neural network (NN) learning with prior knowledge. In contrast, many known properties, such as spatial smoothness or seasonality, are straightforward to model by choosing an appropriate kernel in a Gaussian process (GP). Many deep learning applications could be enhanced by modeling such known properties. For example, convolutional neural networks (CNNs) are frequently used in remote sensing, which is subject to strong seasonal effects. We propose to blend the strengths of NNs and the clear modeling capabilities of GPs by using a composite kernel that combines a kernel implicitly defined by a neural network with a second kernel function chosen to model known properties (e.g., seasonality). We implement this idea by combining a deep network and an efficient mapping function based on either Nyström approximation or random Fourier features, which we call Implicit Composite Kernel (ICK). We then adopt a sample-then-optimize approach to approximate the full GP posterior distribution. We demonstrate that ICK has superior performance and flexibility on both synthetic and real-world datasets including a remote sensing dataset. The ICK framework can be used to include prior information into neural networks in many applications.

1 Introduction

In complex regression tasks, input data often contains *multiple sources of information*. These sources can be presented in both high-dimensional (e.g. images, audios, texts, etc.) and low-dimensional (e.g. timestamps, spatial locations, etc.) forms. A common approach to learn from high-dimensional information is to use neural networks (NNs) (Goodfellow et al., 2016; LeCun et al., 2015), as NNs are powerful enough to capture the relationship between complex high-dimensional data and target variables of interest. In many areas, NNs are standard practice, such as the dominance of Convolutional Neural Networks (CNNs) for image analysis (Jiang et al., 2022; Zheng et al., 2021; 2020). In contrast, for low-dimensional information, we usually have some prior knowledge on how the information relates to the predictions. As a concrete example, consider a remote sensing problem where we predict ground measurements from satellite imagery with associated timestamps. *A priori*, we expect the ground measurements to vary periodically with respect to time between summer and winter due to seasonal effects. We would typically use a CNN to capture the complex relationship between the imagery and the ground measurements. In this case, we want to guide the learning of the CNN with our prior knowledge about the seasonality. This is challenging because knowledge represented in NNs pertains mainly to correlation between network units instead of quantifiable statements (Marcus, 2018).

Conversely, Gaussian processes (GPs) have been used historically to incorporate relevant prior beliefs by specifying the appropriate form of its kernel (or covariance) function (Bishop & Nasrabadi, 2006; Williams & Rasmussen, 2006). One approach to modeling multiple sources of information is to assign a relevant kernel function to each source of information respectively and combine them through addition or multiplication, resulting in a *composite kernel function* (Duvenaud, 2014). This formulation means that specifying a kernel to match prior beliefs on one source of information is straightforward. Such composite kernel learning techniques are extensively used in many application areas such as multi-media data (McFee et al., 2011), neuroimaging (Zhang et al., 2011), spatial data analysis, and environmental data analysis (Kim et al., 2005; Petelin et al.,

2013). In view of the clear modeling capabilities of GP, it is desirable to examine how a NN could be imbued with the same modeling ease.

In recent years, researchers have come up with a variety of methods to incorporate prior knowledge into NNs. These efforts can be broken into many categories, such as those that add prior information through loss terms like physics-informed NNs (Lagaris et al., 1998; Moseley et al., 2020). Here, we focus on the major category of those methods that build integrated models of NNs and GPs with various structures (Van der Wilk et al., 2017; Wilson et al., 2016; 2011). Related to our proposed methodology, Pearce et al. (2020) exploited the fact that a Bayesian neural network (BNN) approximates a GP to construct additive and multiplicative kernels, but they were limited to specific predefined kernels. Matsubara et al. (2020) then resolved this limitation by constructing priors of BNN parameters based on the ridgelet transform and its dual, but they did not explicitly show how their approach works for data with multiple sources of information. To our knowledge, no existing approach allows a modeler to choose any appropriate kernel over multiple sources.

We address this limitation by presenting a simple yet novel Implicit Composite Kernel (ICK) framework, which processes high-dimensional information using a kernel implicitly defined by a neural network and low-dimensional information using a chosen kernel function. The low-dimensional kernels are mapped into the neural network framework to create a straightforward and simple-to-learn implementation. Our key results and contributions are:

- We analytically show our ICK framework, under reasonable assumptions, is approximately equivalent to sampling from a Gaussian process regression (GPR) model with a composite kernel *a priori*.

- We adopt a sample-then-optimize procedure to ICK to approximate the full posterior distribution of a GP with a composite kernel.

- We show that ICK yields better performance on prediction and forecasting tasks, even with limited data.

- We show that ICK can flexibly capture the patterns of the low-dimensional information without bespoke pre-processing procedures or complex NN structures.

Based on these contributions, we believe ICK is useful in learning from complex *hybrid* data with prior knowledge, especially in remote sensing and spatial statistics.

2 Related Work

Equivalence between NNs and GPs   The equivalence between GPs and randomly initialized single-layer NNs with infinite width was first shown by Neal (1996). With the development of modern deep learning, researchers further extended this relationship to deep networks (Lee et al., 2017; Matthews et al., 2018) and convolutional neural networks (CNNs) (Garriga-Alonso et al., 2018). This relationship is crucial for showing the resemblance between GPR and our ICK framework, which is discussed in Section 4.1.

NNs with prior knowledge   As mentioned before, one approach to equip NNs with prior knowledge is to modify the loss function. For example, Lagaris et al. (1998) solved differential equations (DEs) using NNs by setting the loss to be a function whose derivative satisfies the DE conditions. Another approach is to build integrated models of NNs and kernel-based models. For example, Wilson et al. (2011) implemented a regression network with GP priors over latent variables and made inference by approximating the posterior using Variational Bayes or sampling from the posterior using Gibbs sampling scheme. Garnelo et al. (2018) introduced a class of neural latent variable models called Neural Processes (NPs) which are capable of learning efficiently from the data and adapting rapidly to new observations. Our ICK framework fuses prior knowledge into NNs by modulating the learnt features using another set of features outputted from a kernel-based mapping, which can also be viewed as an integrated model of NNs and kernel machines.

GP with composite kernels   Composite kernel GPs are widely used in both machine learning (Duvenaud, 2014; Williams & Rasmussen, 2006) and geostatistical modeling (Datta et al., 2016; Gelfand & Schliep, 2016).

GPR in geostatistical modeling is also known as *kriging* (Journel & Huijbregts, 1976; Krige, 1951), which serves as a surrogate model to replace expensive function evaluations. The inputs for a composite GP are usually low-dimensional (e.g. spatial distance) as GPs do not scale well with the number of samples for high-dimensional inputs (Bouhlel & Martins, 2019; Bouhlel et al., 2016). To overcome this issue, Pearce et al. (2020) and Matsubara et al. (2020) developed BNN analogues for composite GPs. Similar to these studies, our ICK framework can also be viewed as a simulation for composite GPs.

Approximation methods for GP For large data sets, approximation methods are needed as exact kernel learning and inference scales $\mathcal{O}(N^3)$. Nyström low-rank matrix approximation (Drineas et al., 2005; Williams & Seeger, 2000) and Random Fourier Features (Rahimi & Recht, 2007; 2008) are two commonly used methods. Building upon these concepts, several popular frameworks, such as sparse GPs (Snelson & Ghahramani, 2005; Titsias, 2009; Hensman et al., 2013), have been developed to facilitate GP inference on large datasets. In our research, we draw inspiration from these approximation methods and utilize them as *transformation functions* to project the kernel matrix into latent space representations, as discussed in Section 4.2.

3 Background

3.1 Problem Setup

To formalize the problem, we have a training data set which contains N data points $\boldsymbol{X} = [\boldsymbol{x}_i]_{i=1}^N = [\boldsymbol{x}_1, \boldsymbol{x}_2, ..., \boldsymbol{x}_N]^T$ and the corresponding labels of these data points are $\boldsymbol{y} = [y_i]_{i=1}^N = [y_1, y_2, ..., y_N]^T$ where $y_i \in \mathbb{R}$. Each data point $\boldsymbol{x}_i = \{\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_i^{(2)}, ..., \boldsymbol{x}_i^{(M)}\}$ is composed of information from M different sources where the m^{th} source of information of the i^{th} data point is denoted as $\boldsymbol{x}_i^{(m)} \in \mathbb{R}^{D_m}$. Our goal is to learn a function $\hat{y}_i = f(\boldsymbol{x}_i) : \mathbb{R}^{D_1} \times \mathbb{R}^{D_2} \times ... \times \mathbb{R}^{D_M} \to \mathbb{R}$ which takes in a data point $\boldsymbol{x}_i$ and outputs a predicted value $\hat{y}_i$.

3.2 Composite GPs

A Gaussian process (GP) describes a distribution over functions (Williams & Rasmussen, 2006). A key property of GP is that it is completely defined by a mean function $\mu(\boldsymbol{x})$ and a kernel function $K(\boldsymbol{x}, \boldsymbol{x}')$ where $\boldsymbol{x}$ and $\boldsymbol{x}'$ represent different samples from the training dataset. The mean function $\mu(\boldsymbol{x})$ is often assumed to be zero for simplicity. In that case, the outcome function is

$$f(\boldsymbol{x}) \sim \mathcal{GP}\left(0, K(\boldsymbol{x}, \boldsymbol{x}')\right). \tag{1}$$

Any finite subset of random variables has a multivariate Gaussian distribution with mean $\boldsymbol{0}$ and kernel matrix $\boldsymbol{K}$ whose entries can be calculated as $\boldsymbol{K}_{ij} = K(\boldsymbol{x}_i, \boldsymbol{x}_j)$ where $1 \le i, j \le N$. In many situations, the full kernel function is built by a composite kernel by combining simple kernels through addition $K^{\mathrm{comp}}(\boldsymbol{x}, \boldsymbol{x}') = K_1(\boldsymbol{x}, \boldsymbol{x}') + K_2(\boldsymbol{x}, \boldsymbol{x}')$ or multiplication $K^{\mathrm{comp}}(\boldsymbol{x}, \boldsymbol{x}') = K_1(\boldsymbol{x}, \boldsymbol{x}')K_2(\boldsymbol{x}, \boldsymbol{x}')$ (Duvenaud, 2014). A useful property that ICK exploits is that K_1 and K_2 can take different subparts of $\boldsymbol{x}$ as their inputs. For example, $K^{\mathrm{comp}}(\boldsymbol{x}, \boldsymbol{x}') = K_1(\boldsymbol{x}^{(1)}, \boldsymbol{x}^{(1)'}) + K_2(\boldsymbol{x}^{(2)}, \boldsymbol{x}^{(2)'})$ or $K^{\mathrm{comp}}(\boldsymbol{x}, \boldsymbol{x}') = K_1(\boldsymbol{x}^{(1)}, \boldsymbol{x}^{(1)'})K_2(\boldsymbol{x}^{(2)}, \boldsymbol{x}^{(2)'})$.

3.3 Correspondence between GPs and NNs

Neal (1996) proved that a single-hidden layer network with infinite width is *exactly equivalent* to a GP over data indices $i = 1, 2, ..., N$ under the assumption that the weight and bias parameters of the hidden layer are i.i.d. Gaussian with zero mean. This statement was then extended to deep NNs (Lee et al., 2017; Matthews et al., 2018) and convolutional NNs (Garriga-Alonso et al., 2018). Specifically, let $\boldsymbol{z} = f_{\mathrm{NN}}\left(\boldsymbol{x}^{(1)}\right) : \mathbb{R}^{D_1} \to \mathbb{R}^p$ be the latent representation extracted from $\boldsymbol{x}^{(1)}$ where p is the dimension of the extracted representation and f_{NN} is a neural network with zero-mean i.i.d. parameters and continuous activation function ϕ which satisfies the linear envelope property

$$|\phi(u)| \le c + m|u| \quad \forall u \in \mathbb{R}, \tag{2}$$

Figure 1: Given data containing 2 sources of information $\boldsymbol{x}^{(1)}$ and $\boldsymbol{x}^{(2)}$, we can process the data using either (**Left**) a composite Gaussian process regression (GPR) model or (**Right**) our ICK framework where $\boldsymbol{x}^{(1)}$ is processed with a neural network $f_{\mathrm{NN}}(\cdot)$ and $\boldsymbol{x}^{(2)}$ is processed with $g(\cdot)$ where $g(\cdot)$ consists of a kernel function K_2 and some transformation which maps the kernel matrix $\boldsymbol{K}_2$ into the latent space.

if there exists $c, m \geq 0$. This includes many standard nonlinearities. The k^{th} entry of this representation will converge in distribution to a NN-implied GP in the infinite width limit

$$f_{\mathrm{NN}}(\boldsymbol{x}^{(1)})_k \xrightarrow{d} \mathcal{GP}(0, K^{\mathrm{NN}}(\boldsymbol{x}^{(1)}, \boldsymbol{x}^{(1)'})). \tag{3}$$

Here K^{NN} in Equation 3 denotes the covariance function of the equivalent GP as the width of f_{NN} goes to infinity and can be computed numerically in a recursive manner (Lee et al., 2017). That is to say, the k^{th} component z_k of the representation extracted by the network has zero mean $\mathbb{E}_{p(\boldsymbol{\theta}^{(1)})}\left[z_{ik}^{(1)}\right] = 0$ for all $i = 1, 2, ..., N$ where θ represents the network parameters. The covariance between $z_{ik}^{(1)}$ and $z_{jk}^{(1)}$ for *different* data indices $i, j = 1, 2, ..., N$ can be approximated as $\mathrm{cov}(z_{ik}^{(1)}, z_{jk}^{(1)}) = \mathbb{E}_{p(\boldsymbol{\theta}^{(1)})}\left[z_{ik}^{(1)} z_{jk}^{(1)}\right] \approx K^{\mathrm{NN}}\left(\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_j^{(1)}\right)$ where $\boldsymbol{x}_i^{(1)}$ and $\boldsymbol{x}_j^{(1)}$ are the corresponding inputs in case the network width is finite.

4 Implicit Composite Kernel

We show the structure of a composite GPR model and our ICK framework in Figure 1. To make the illustration clear, we limit ourselves to data with information from 2 different sources $\boldsymbol{x} = \left\{\boldsymbol{x}^{(1)}, \boldsymbol{x}^{(2)}\right\}$ where $\boldsymbol{x}^{(1)}$ is high-dimensional and $\boldsymbol{x}^{(2)}$ is low-dimensional (i.e. $D_1 \gg D_2$) with some known relationship with the target y. We are inspired by composite GPR, which computes 2 different kernel matrices $\boldsymbol{K}_1$ and $\boldsymbol{K}_2$ and then combines them into a single composite kernel matrix $\boldsymbol{K}^{\mathrm{comp}}$. However, as discussed before, it is more suitable to use a NN to learn from the high dimensional information $\boldsymbol{x}^{(1)}$. In our ICK framework, we process $\boldsymbol{x}^{(1)}$ with a NN $f_{\mathrm{NN}}(\cdot) : \mathbb{R}^{D_1} \to \mathbb{R}^p$ and $\boldsymbol{x}^{(2)}$ with a mapping $g(\cdot) : \mathbb{R}^{D_2} \to \mathbb{R}^p$, which consists of a kernel function K_2 followed by a kernel-to-latent-space transformation (described in Section 4.2), resulting in two latent representations $\boldsymbol{z}^{(1)}, \boldsymbol{z}^{(2)} \in \mathbb{R}^p$. Then, we make a prediction $\hat{y}$ by doing an *inner product* between these two representations $\hat{y} = f_{\mathrm{NN}}\left(\boldsymbol{x}^{(1)}\right) \cdot g\left(\boldsymbol{x}^{(2)}\right)$. Finally, the parameters of both the NN and the kernel function are learned via gradient-based optimization methods (Bottou et al., 2018).

Besides the formulation in Figure 1, ICK can also process data $\boldsymbol{x} = \left\{x^{(1)}, x^{(2)}, ..., x^{(M)}\right\}$ with $M > 2$ sources of information as shown in Figure 2. Here $K_1, ..., K_M$ represent different types of kernels with trainable parameters. The final prediction is calculated by a chained inner product of all extracted representations $\hat{y} = \sum_{k=1}^{p} \prod_{m=1}^{M} z_k^{(m)}$.

In the sections below, we first show the relationship between ICK and a composite GPR model with a multiplicative kernel *a priori* in Section 4.1, which is used to **motivate the model form**. We then show how we implement the kernel-to-latent-space transformation in Section 4.2. To enable a full GP posterior *approximation* for ICK, we will provide insight into how we derive uncertainty estimates from ICK. This

Figure 2: Given data containing M sources of information $\boldsymbol{x} = \{x^{(1)}, x^{(2)}, ..., x^{(M)}\}$, we can process the data using our ICK framework where high-dimensional information (e.g. $x^{(1)}$ in the figure) is processed using a neural network and low-dimensional information (e.g. $x^{(2)}$ in the figure) is processed using a kernel function and some transformation which maps the kernel matrix into the latent space.

can be achieved either through direct variance calculation (Section 4.3.1) or through the utilization of an ensemble approach (Section 4.3.2).

4.1 Resemblance between Composite GPR and ICK

We will analytically prove the following theorem for data with information from 2 different sources $\boldsymbol{x} = \{\boldsymbol{x}^{(1)}, \boldsymbol{x}^{(2)}\}$ for clarity, and we note this theorem can be straightforwardly extended to $M > 2$.

Theorem 1. *Let $f_{NN} : \mathbb{R}^{D_1} \to \mathbb{R}^p$ be a NN function with random weights and $g : \mathbb{R}^{D_2} \to \mathbb{R}^p$ be a mapping function, and define an inner product between the representations $\hat{y} = f_{ICK}(\boldsymbol{x}^{(1)}, \boldsymbol{x}^{(2)}) = f_{NN}(\boldsymbol{x}^{(1)}) \cdot g(\boldsymbol{x}^{(2)}) = \boldsymbol{z}^{(1)^T} \boldsymbol{z}^{(2)}$. Then f_{ICK} will converge in distribution to a GP*

$$f_{ICK} \xrightarrow{d} \mathcal{GP}(0, K_1^{NN}(\boldsymbol{x}^{(1)}, \boldsymbol{x}^{(1)'}) K_2(\boldsymbol{x}^{(2)}, \boldsymbol{x}^{(2)'})), \tag{4}$$

if f_{NN} is a neural network with zero-mean i.i.d. parameters and continuous activation function ϕ which satisfies the linear envelope property in Equation 2 and g includes the following deterministic kernel-to-latent-space transformation for all $1 \le i, j \le N$

$$K_2(\boldsymbol{x}_i^{(2)}, \boldsymbol{x}_j^{(2)}) \approx \boldsymbol{z}_i^{(2)^T} \boldsymbol{z}_j^{(2)} = g(\boldsymbol{x}_i^{(2)})^T g(\boldsymbol{x}_j^{(2)}), \tag{5}$$

where K_1^{NN} is a NN-implied kernel and K_2 is any valid kernel of our choice.

To prove Theorem 1, we first state following lemma.

Lemma 2. *For latent representations $\boldsymbol{z}_i^{(1)}$ and $\boldsymbol{z}_j^{(1)}$ extracted from different data points $\boldsymbol{x}_i$ and $\boldsymbol{x}_j$ where $i \ne j$, the interactions between different entries of $\boldsymbol{z}_i^{(1)}$ and $\boldsymbol{z}_j^{(1)}$ can be reasonably ignored. In other words, let $\theta^{(1)}$ be the parameters of the neural network which takes in $\boldsymbol{x}^{(1)}$ and outputs $\boldsymbol{z}^{(1)}$, we have $\mathbb{E}_{p(\theta^{(1)})}[z_{ik}^{(1)} z_{jl}^{(1)}] = 0$ for all $k \ne l$.*

A detailed proof of Lemma 2 is provided in Appendix A. With Lemma 2, let $\boldsymbol{\Theta} = \{\boldsymbol{\theta}^{(1)}, \boldsymbol{\theta}^{(2)}\}$ represent the parameters of ICK, we can calculate the covariance between $\hat{y}_i$ and $\hat{y}_j$ for different data indices $i \ne j$:

$$\text{cov}(\hat{y}_i, \hat{y}_j)$$
$$= \mathbb{E}_{p(\boldsymbol{\Theta})}[\hat{y}_i \hat{y}_j] - \mathbb{E}_{p(\boldsymbol{\Theta})}[\hat{y}_i] \mathbb{E}_{p(\boldsymbol{\Theta})}[\hat{y}_j] \tag{6}$$
$$= \mathbb{E}_{p(\boldsymbol{\Theta})}\left[\left(\sum_{k=1}^p z_{ik}^{(1)} z_{ik}^{(2)}\right)\left(\sum_{k=1}^p z_{jk}^{(1)} z_{jk}^{(2)}\right)\right] \tag{7}$$
$$= \mathbb{E}_{p(\boldsymbol{\Theta})}\left[\sum_{k=1}^p \sum_{l=1}^p z_{ik}^{(1)} z_{jl}^{(1)} z_{ik}^{(2)} z_{jl}^{(2)}\right] \tag{8}$$

$$= \mathbb{E}_{p(\boldsymbol{\Theta})} \left[\sum_{k=1}^{p} z_{ik}^{(1)} z_{jk}^{(1)} z_{ik}^{(2)} z_{jk}^{(2)} \right] \tag{9}$$

$$= \sum_{k=1}^{p} \mathbb{E}_{p(\boldsymbol{\theta}^{(1)})} \left[z_{ik}^{(1)} z_{jk}^{(1)} \right] \mathbb{E}_{p(\boldsymbol{\theta}^{(2)})} \left[z_{ik}^{(2)} z_{jk}^{(2)} \right] \tag{10}$$

$$\approx K_1^{\mathrm{NN}} \left(\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_j^{(1)} \right) \sum_{k=1}^{p} \mathbb{E}_{p(\boldsymbol{\theta}^{(2)})} \left[z_{ik}^{(2)} z_{jk}^{(2)} \right]. \tag{11}$$

Here, from Equation 6 to Equation 7, we use the statement $\mathbb{E}_{p(\boldsymbol{\theta}^{(1)})}[z_{ik}^{(1)}] = 0$ in Section 3.3 and $\boldsymbol{\theta}^{(1)} \perp\!\!\!\perp \boldsymbol{\theta}^{(2)}$, which leads to $\mathbb{E}_{p(\boldsymbol{\Theta})}[\hat{y}_i] = \mathbb{E}_{p(\boldsymbol{\Theta})}[\hat{y}_j] = 0$. From Equation 8 to Equation 9, we get rid of all the cross terms using Lemma 2 and $\boldsymbol{\theta}^{(1)} \perp\!\!\!\perp \boldsymbol{\theta}^{(2)}$. Specifically, we have $\mathbb{E}_{p(\boldsymbol{\Theta})}[z_{ik}^{(1)} z_{jl}^{(1)} z_{ik}^{(2)} z_{jl}^{(2)}] = \mathbb{E}_{p(\boldsymbol{\theta}^{(1)})}[z_{ik}^{(1)} z_{jl}^{(1)}]\mathbb{E}_{p(\boldsymbol{\theta}^{(2)})}[z_{ik}^{(2)} z_{jl}^{(2)}] = 0$ for all $k \neq l$. From Equation 9 to Equation 10, we again make use of $\boldsymbol{\theta}^{(1)} \perp\!\!\!\perp \boldsymbol{\theta}^{(2)}$. From Equation 10 to Equation 11, we use the statement $\mathbb{E}_{p(\boldsymbol{\theta}^{(1)})}[z_{ik}^{(1)} z_{jk}^{(1)}] \approx K^{\mathrm{NN}}(\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_j^{(1)})$ from Section 3.3. If the kernel-to-latent-space transformation in $g(\cdot)$ is *deterministic*, we can remove the expectation sign from the summation term in Equation 11 and the covariance can be further expressed as

$$\begin{aligned} \mathrm{cov}(\hat{y}_i, \hat{y}_j) &\approx K_1^{\mathrm{NN}}(\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_j^{(1)})(\boldsymbol{z}_i^{(2)^T} \boldsymbol{z}_j^{(2)}) \\ &= K_1^{\mathrm{NN}}(\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_j^{(1)}) K_2(\boldsymbol{x}_i^{(2)}, \boldsymbol{x}_j^{(2)}), \end{aligned} \tag{12}$$

which means that $\hat{y}$ approximately follows a GP with a multiplicative composite kernel $K^{\mathrm{comp}}(\boldsymbol{x}_i, \boldsymbol{x}_j) = K_1^{\mathrm{NN}} \left(\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_j^{(1)} \right) K_2 \left(\boldsymbol{x}_i^{(2)}, \boldsymbol{x}_j^{(2)} \right)$ *a priori*. This serves as a consise proof of Theorem 1. We also give a more detailed proof in Appendix B.

4.2 Kernel-to-latent-space Transformation

We now show how we can construct an appropriate mapping $g(\cdot)$ that approximately satisfies the assumed form of equation 5 and is used in the derivation of ICK from equation 11 to equation 12. Here we adopt two methods, Nyström approximation and Random Fourier Features (RFF), to map the kernel matrix into the latent space. Below, we elaborate the formulations for both methods, and give the methods and results for the Nyström method. The results of RFF will be presented in Appendix C. We name our framework with N*y*ström method and *r*andom Fourier Features ICK*y* and ICK*r*, respectively.

According to Yang et al. (2012), the Nyström method will yield much better performance than RFF if there exists a large gap in the eigen-spectrum of the kernel matrix. This phenomenon is mainly caused by how these two methods construct their basis functions. In particular, the basis functions used by RFF are sampled from a Gaussian distribution that is independent from the training examples, while the basis functions used by the Nyström method are sampled from the training samples so they are data-dependent.

Figure 3: Eigenvalues of the kernel matrix computed from the first 4 batches of training data where N is the total number of data points.

In our synthetic data experiments, we train our ICK framework using a batch size of 50. The eigenvalues of the kernel matrices computed from the first 4 batches of the synthetic data set are displayed in Figure 3. It can be observed that the first few eigenvalues of the kernel matrix are much larger than the remaining eigenvalues. Namely, we observe a large gap in the eigen-spectrum of the kernel matrix, and Nyström method does generalize much better than RFF in our experiments.

4.2.1 Nyström Approximation

The main idea of Nyström approximation (Williams & Seeger, 2000) is to approximate the kernel matrix $\boldsymbol{K} \in \mathbb{R}^{N \times N}$ with a much smaller low-rank matrix $\boldsymbol{K}_q \in \mathbb{R}^{q \times q}$ where $q \ll N$ so both the computational and space complexity of kernel learning can be significantly reduced, yielding

$$\boldsymbol{K} \approx \hat{\boldsymbol{K}} = \boldsymbol{K}_{nq}\boldsymbol{K}_q^{-1}\boldsymbol{K}_{nq}^T. \qquad (13)$$

The entries of $\boldsymbol{K}_q$ and $\boldsymbol{K}_{nq}$ can be calculated as $(\boldsymbol{K}_q)_{ij} = K(\hat{x}_i, \hat{x}_j), i, j \in \{1, 2, ..., q\}$ and $(\boldsymbol{K}_{nq})_{ij} = K(x_i, \hat{x}_j), i \in \{1, 2, ..., N\}, j \in \{1, 2, ..., q\}$, respectively. x represents the original data points and $\hat{x}$ represents pre-defined inducing points (or pseudo-inputs (Snelson & Ghahramani, 2005)). In our study, these inducing points are chosen by defining an evenly spaced vector over the range of original data points. By performing Cholesky decomposition $\boldsymbol{K}_q^{-1} = \boldsymbol{U}^T\boldsymbol{U}$, where $\boldsymbol{U} \in \mathbb{R}^{q \times q}$, $\hat{\boldsymbol{K}}$ is expressed as

$$\begin{aligned}\hat{\boldsymbol{K}} &= \boldsymbol{K}_{nq}\boldsymbol{K}_q^{-1}\boldsymbol{K}_{nq}^T \\ &= \boldsymbol{K}_{nq}\boldsymbol{U}^T\boldsymbol{U}\boldsymbol{K}_{nq}^T = (\boldsymbol{U}\boldsymbol{K}_{nq}^T)^T(\boldsymbol{U}\boldsymbol{K}_{nq}^T).\end{aligned} \qquad (14)$$

Therefore, if we set $q = p$, then we can use $\boldsymbol{z}_i \triangleq \boldsymbol{U}(\boldsymbol{K}_{np}^T)_{:,i}$ as a kernel-to-latent-space trans-

---

Algorithm 1 Implicit Composite Kernel-Nyström (ICKy)

Input: data $\boldsymbol{X} = \left\{\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_i^{(2)}\right\}_{i=1}^N$, targets $\boldsymbol{y} = [y_i]_{i=1}^N$, $f_{\text{NN}}, \boldsymbol{\theta}^{(1)}, K^{(2)}, \boldsymbol{\theta}^{(2)}$, learning rate β

  Sample a total of N_B minibatches $\{\boldsymbol{X}_B, \boldsymbol{y}_B\}_{B=1}^{N_B}$
  for B from 1 to N_B **do**
    for $\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_i^{(2)}$ in $\boldsymbol{X}_B, i = 1, ..., n_B$ **do**
      $\boldsymbol{z}_i^{(1)} = f_{\text{NN}}\left(\boldsymbol{x}_i^{(1)}\right)$
      Define inducing points $\hat{\boldsymbol{x}}_1^{(2)}, ..., \hat{\boldsymbol{x}}_p^{(2)}$
      Compute $\boldsymbol{K}_p$: $(\boldsymbol{K}_p)_{jk} = K^{(2)}\left(\hat{\boldsymbol{x}}_j^{(2)}, \hat{\boldsymbol{x}}_k^{(2)}\right)$
      Do Cholesky decomposition $(\boldsymbol{K}_p)^{-1} = \boldsymbol{U}^T\boldsymbol{U}$
      Compute $\boldsymbol{K}_{np}$: $(\boldsymbol{K}_{np})_{jk} = K^{(2)}\left(\boldsymbol{x}_j^{(2)}, \hat{\boldsymbol{x}}_k^{(2)}\right)$
      $\boldsymbol{z}_i^{(2)} = \boldsymbol{U}\left(\boldsymbol{K}_{np}^T\right)_{:,i}$
      $\hat{y}_i = \boldsymbol{z}_i^{(1)T}\boldsymbol{z}_i^{(2)}$
    end for
    $\hat{\boldsymbol{y}}_B = \texttt{concat}\left(\hat{y}_1, ..., \hat{y}_{n_B}\right)$
    Compute loss $\mathcal{L} = \mathcal{L}\left(\boldsymbol{y}_B, \hat{\boldsymbol{y}}_B\right)$
    $\boldsymbol{\theta}^{(1)} \leftarrow \boldsymbol{\theta}^{(1)} - \beta\nabla_{\boldsymbol{\theta}^{(1)}}\mathcal{L}$
    $\boldsymbol{\theta}^{(2)} \leftarrow \boldsymbol{\theta}^{(2)} - \beta\nabla_{\boldsymbol{\theta}^{(2)}}\mathcal{L}$
  end for
Return: Predictions $\hat{\boldsymbol{y}}$ and updated parameters $\boldsymbol{\theta}^{(1)}, \boldsymbol{\theta}^{(2)}$

---

formation because each element in $\boldsymbol{K}$ approximately satisfies equation 5 as stated in Theorem 1: $K(x_i, x_j) = K_{ij} \approx \hat{K}_{ij} = \boldsymbol{z}_i^T\boldsymbol{z}_j$. Conveniently, modern deep learning frameworks can propagate gradients through the Cholesky operation, making it straightforward to update the kernel parameters with gradient methods. Note that as we increase the number of inducing points p, the approximation error between $\boldsymbol{K}$ and $\hat{\boldsymbol{K}}$ decreases. However, it is not recommended to set p very large as updating the Cholesky decomposition requires $\mathcal{O}(p^3)$. The empirical impact of p on computational time and performance is shown in Appendix D. In our experiments, only mild values of p are necessary and the impact on computational is relatively small. The full training procedure of ICKy with $M = 2$ is presented in Algorithm 1.

4.2.2 Random Fourier Features

Random Fourier Features (RFF) is another popular approximation method used for kernel learning (Rahimi & Recht, 2007). Unlike the Nyström method which approximates the entire kernel matrix, RFF directly approximates the kernel function K using some randomized feature mapping $\phi : \mathbb{R}^{D_m} \to \mathbb{R}^{2d_m}$ such that $K\left(x_i^{(m)}, x_j^{(m)}\right) \approx \phi\left(x_i^{(m)}\right)^T \phi\left(x_j^{(m)}\right)$. To obtain the feature mapping ϕ, based on Bochner's theorem, we first compute the Fourier transform $p(\omega)$ of kernel K

$$p(\omega) = \frac{1}{(2\pi)^{D_m}} \int_{-\infty}^{+\infty} e^{-j\omega^T\delta} K(\delta)d\delta, \qquad (15)$$

where $\delta = x_i^{(m)} - x_j^{(m)}$. Then we draw d_m i.i.d. samples $\omega_1, \omega_2, ..., \omega_{d_m}$ from $p(\omega)$ and construct the feature mapping ϕ as follows

$$\phi\left(x^{(m)}\right) \equiv d_m^{-1/2}\left[\cos\left(\omega_1^T x^{(m)}\right), ..., \cos\left(\omega_{d_m}^T x^{(m)}\right), \sin\left(\omega_1^T x^{(m)}\right), ..., \sin\left(\omega_{d_m}^T x^{(m)}\right)\right]. \qquad (16)$$

Since $\phi\left(x^{(m)}\right) \in \mathbb{R}^{2d_m}$, we need to set $d_m = p/2$ when using RFF as a kernel-to-latent-space transformation. In addition, since RFF involves sampling from a distribution, the kernel parameters are thus not directly differentiable and we need to apply a reparameterization trick (Maddison et al., 2016) to learn those parameters. The full training procedure of ICKr with $M = 2$ is presented in Algorithm 2.

4.3 Uncertainty Estimation

Since the motivation of ICK discussed in Section 4.1 is closely related to GPs, we present two distinct approaches for estimating uncertainty in the subsequent sections: ensembling method and direct calculation of posterior variance.

4.3.1 Ensembling

One approach for estimating the uncertainty is to adopt a sample-then-optimize approach (Matthews et al., 2017) and construct a deep ensemble posterior approximation for ICK. There are several ways to enable GP posterior interpretation for a deep ensemble trained with SGD. Specifically, let the final layer of each baselearner NN be C-dimensional and denote the deep ensemble as $F = \{f_{n_e}\}_{n_e=1}^{N_e}$, where f_{n_e} is a baselearner NN and N_e is the total number of baselearners in the ensemble. After training, each f_{n_e} can be viewed as i.i.d. samples from a multi-output GP posterior with kernel function K_F in the infinite width limit and the ensemble F thus represents N_e independent draws from the GP posterior, where K_F can be either the *Neural Network Gaussian Process* (NNGP) kernel (Lee et al., 2017) if we make only the last layer trainable or the *Neural Tangent Kernel* (NTK) (He et al., 2020; Jacot et al., 2018) if we add a randomized and untrainable function to each baselearner.

This deep ensemble mechanism can be easily applied to ICKy. Specifically, the final prediction of ICKy $\hat{y} = f_{\text{ICK}y}\left(\boldsymbol{x}^{(1)}, \boldsymbol{x}^{(2)}\right)$ can be viewed as a weighted sum of $\hat{y} = \sum_{k=1}^{p} \alpha_k z_k^{(1)}$ where $\alpha_k = z_k^{(2)} = g\left(\boldsymbol{x}^{(2)}\right)_k$. Hence, if we construct an ensemble of ICKy, $F_{\text{ICK}y} = \{f_1, ..., f_{N_e}\}$ (as shown in Algorithm 3), and f_{NN} is appropriately initialized for all baselearners $f_s \in F_{\text{ICK}y}, s = 1, ..., N_e$, then all trained baselearners in $F_{\text{ICK}y}$ can be *approximately* viewed as i.i.d. posterior samples from a single-output GP with a multiplicative kernel $K_F K_2$. K_F will either be an NNGP or an NTK and K_2 comes from our defined kernel. If the parameters of f_{NN} (i.e. $\boldsymbol{\theta}^{(1)}$) are independently drawn from a zero-mean Gaussian and are fixed except the last layer (as specified by Lee et al. (2019)) for all baselearners in the ensemble, this corresponds to an NNGP. A detailed proof is in Appendix E.

Algorithm 2 Implicit Composite Kernel-RFF (ICKr)

Input: data $\boldsymbol{X} = \left\{\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_i^{(2)}\right\}_{i=1}^{N}$, targets $\boldsymbol{y} = [y_i]_{i=1}^{N}$, $f_{\text{NN}}, \boldsymbol{\theta}^{(1)}, K_2, \boldsymbol{\theta}^{(2)}$, learning rate β

  Sample a total of N_B minibatches $\{\boldsymbol{X}_B, \boldsymbol{y}_B\}_{B=1}^{N_B}$

  for B from 1 to N_B **do**

    for $\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_i^{(2)}$ in $\boldsymbol{X}_B, i = 1, ..., n_B$ **do**

      $\boldsymbol{z}_i^{(1)} = f_{\text{NN}}\left(\boldsymbol{x}_i^{(1)}\right)$

      Compute the Fourier transform $p(\omega)$ of kernel K_2:

      $p(\omega) = \frac{1}{(2\pi)^{D_m}} \int_{-\infty}^{+\infty} e^{-j\omega^T \delta} K(\delta) d\delta$

      where $\delta = x_i^{(2)} - x_j^{(2)}$

      Draw $p/2$ i.i.d. samples $\omega_1, \omega_2, ..., \omega_{p/2}$ from $p(\omega)$.

      Construct feature mapping
$$\boldsymbol{z}_i^{(2)} = \sqrt{p/2}\Big[\cos{(\omega_1^T x^{(2)})}, ..., \cos{(\omega_{p/2}^T x^{(2)})},$$
$$\sin{(\omega_1^T x^{(2)})}, ..., \sin{(\omega_{p/2}^T x^{(2)})}\Big]$$

      $\hat{y}_i = \boldsymbol{z}_i^{(1)^T} \boldsymbol{z}_i^{(2)}$

    end for

    $\hat{\boldsymbol{y}}_B = \texttt{concat}\left(\hat{y}_1, ..., \hat{y}_{n_B}\right)$

    Compute loss $\mathcal{L} = \mathcal{L}\left(\boldsymbol{y}_B, \hat{\boldsymbol{y}}_B\right)$

    $\boldsymbol{\theta}^{(1)} \leftarrow \boldsymbol{\theta}^{(1)} - \beta \nabla_{\boldsymbol{\theta}^{(1)}} \mathcal{L}$

    $\boldsymbol{\theta}^{(2)} \leftarrow \boldsymbol{\theta}^{(2)} - \beta \nabla_{\boldsymbol{\theta}^{(2)}} \mathcal{L}$

  end for

Return: Predictions $\hat{\boldsymbol{y}}$ and updated parameters $\boldsymbol{\theta}^{(1)}, \boldsymbol{\theta}^{(2)}$

Algorithm 3 ICKy Ensemble

Input: data $\boldsymbol{X} = \left\{\boldsymbol{x}_i^{(1)}, \boldsymbol{x}_i^{(2)}\right\}_{i=1}^{N}$, targets $\boldsymbol{y} = [y_i]_{i=1}^{N}$, ensemble $F_{\text{ICK}y} = \{f_1, ..., f_{N_e}\}$ where each function in F consists of f_{NN}, K_2 with parameters $\boldsymbol{\theta}^{(1)}, \boldsymbol{\theta}^{(2)}$, respectively

  for $s = 1, ..., N_e$ **do**

    Apply proper initialization strategy to f_s

    Perform Algorithm 1 on function f_s

  end for

Return: predictive mean $\hat{\boldsymbol{\mu}} = \frac{1}{N_e} \sum_{s=1}^{N_e} f_s(\boldsymbol{X})$, predictive variance $\hat{\boldsymbol{\sigma}}^2 = \frac{1}{N_e} \sum_{s=1}^{N_e} \left(f_s(\boldsymbol{X}) - \hat{\boldsymbol{\mu}}\right)^2$, and updated parameters $\boldsymbol{\theta}^{(1)}, \boldsymbol{\theta}^{(2)}$ for all functions f in $F_{\text{ICK}y}$

To verify our argument, we train an ICKy ensemble $F_{\text{ICK}y}$ containing 300 baselearners with SGD on the same 1D regression task as provided by He et al. (2020) and compare the predictive distribution to its GP posterior counterpart based on the NNGP implementation in the *neural_tangents* (Novak et al., 2020) package. The GP posterior has zero mean and kernel function $K_{\text{NNGP}}K_2$, where K_{NNGP} is the corresponding NNGP kernel of f_{NN} and K_2 is the chosen kernel function for the mapping g in the ICKy ensemble in Figure 4. Here, K_2 is set to be an *exponential-sine-squared* kernel with period $T = 2\pi$. The predictive distribution of ICKy ensemble is very close to the analytic GP posterior, demonstrating the *approximate* equivalence between the two models.

4.3.2 Computing Variance

Another approach to estimate the uncertainty is to directly compute the covariance matrix of the posterior distribution

$$\boldsymbol{\Sigma} = \boldsymbol{K}_{x^*x^*} - \boldsymbol{K}_{x^*x}\left(\boldsymbol{K}_{xx} + \sigma^2\boldsymbol{I}\right)\boldsymbol{K}_{xx^*}, \quad (17)$$

where $\boldsymbol{K}_{x^*x^*} = K(\boldsymbol{X}^*, \boldsymbol{X}^*)$ is the kernel matrix evaluated on the test dataset, $\boldsymbol{K}_{xx} = K(\boldsymbol{X}, \boldsymbol{X})$ is the kernel matrix evaluated on the training dataset, $\boldsymbol{K}_{x^*x} = K(\boldsymbol{X}^*, \boldsymbol{X})$ is the cross-covariance matrix evaluated on both training and test datasets, and $\boldsymbol{K}_{x^*x} = \boldsymbol{K}_{xx^*}^T$. Here K refers to the composite kernel function implied by ICK. Note that if we get rid of $f_{\text{NN}}(\cdot)$ and only keep $g(\cdot)$, then $K = K_2$ and the computation of $\boldsymbol{\Sigma}$ is straightforward. We believe the true uncertainty can be reasonably approximated by ICKy, as indicated by diag($\boldsymbol{\Sigma}$), while maintaining a reasonable computational complexity. To demonstrate this, we sample 100 data points from a sinusoidal function with exponential decay $f(x) = e^{-x}\sin(2\pi x) + \epsilon$ where $\epsilon \sim \mathcal{N}(0, 0.5)$ and see

Figure 4: Predictive distribution from ICKy ensemble and its GP posterior counterpart on a 1D regression task.

how an exact GP and ICKy with radial basis function (RBF) kernel can capture the mean and uncertainty of this function by learning from these samples and directly calculating the covariance $\boldsymbol{\Sigma}$ according to Equation 17. In Figure 5, our results reveal that both GP and ICKy accurately capture the mean function. However, ICKy exhibits a prediction of uncertainty closer to the ground truth when compared to GP.

5 Experiments

We evaluate ICKy on 6 different data sets: 2 synthetic datasets and 4 real-world datasets [1]. In all the experiments, our ICKy framework only consists of 2 kernels (i.e. $M = 2$), one NN-implied kernel and one chosen kernel function with trainable parameters. The implementation details of all the experiments in this section are provided in Appendix F and the data accessibility and restrictions are provided in Appendix G.

5.1 Synthetic Data

5.1.1 Case when $M = 2$

To verify that ICKy can simulate sampling from a GP with *multiplicative kernel*, we create a synthetic data set $y \sim \mathcal{GP}(0, K_1K_2)$ containing 3000 data points where $\boldsymbol{x}^{(1)} \in [0, 1]$ is the input for the linear kernel K_1 and $\boldsymbol{x}^{(2)} \in [0, 2]$ is the input for a *spectral mixture* kernel (Wilson & Adams, 2013) K_2 with 2 components.

We compare ICKy with two models: a multi-layer perceptron (MLP) applied to the concatenated features and a novel multi-layer perceptron-random forest (MLP-RF) joint model employed by Zheng et al. (2021),

---

[1]The code for all the experiments presented in this paper can be accessed at: https://anonymous.4open.science/r/ICK-D4E6/.

Figure 5: Plots of predicted mean and uncertainties for a sinusoidal function with exponential damping with noise $f(x) = e^{-x}\sin(2\pi x) + \epsilon$ using (a) an exact GP with RBF kernel and (b) ICKy with RBF kernel. Here ICKy predicts the uncertainty by directly calculating the covariance matrix $\boldsymbol{\Sigma}$ in Equation 17.

Figure 6: Prediction of $y \sim \mathcal{GP}(0, K_1 K_2)$, where $\boldsymbol{x}^{(1)}$ is input to a linear kernel K_1 and $\boldsymbol{x}^{(2)}$ is input to a spectral mixture kernel K_2. We plot $\boldsymbol{x}^{(2)}$ against the predicted y. We show results from a plain MLP (left), MLP-RF (middle left), and ICKy framework (middle right), and we compare to the true values of y (right).

Figure 7: Prediction of $y \sim \mathcal{GP}(0, K_1 + K_2)$, where $\boldsymbol{x}^{(1)}$ is input to a linear kernel K_1 and $\boldsymbol{x}^{(2)}$ is input to a spectral mixture kernel K_2. We plot $\boldsymbol{x}^{(2)}$ against the predicted y. We show results from a plain MLP (left), MLP-RF (middle left), and ICKy framework (middle right), and we compare to the true values of y (right).

where MLP learns from $\boldsymbol{x}^{(1)}$ and RF learns from $\boldsymbol{x}^{(2)}$. We believe MLP-RF serves as a good benchmark model as it is a joint model with similar architecture to our ICKy framework. To see how ICKy simulates

Figure 8: Visualization of (a) True matrix (b) estimated matrix by our ICKy framework, and (c) absolute difference between the true and estimated matrix for the spectral mixture kernel

Figure 9: Scatter plots of the true values of y against the predicted values of y using our ICKy framework with information from (a) one source $\hat{y} = f_{\mathrm{NN}}\left(x^{(1)}\right)$, (b) 2 sources $\hat{y} = f_{\mathrm{ICK}y}\left(x^{(1)}, x^{(2)}\right)$, and (c) 3 sources $\hat{y} = f_{\mathrm{ICK}y}\left(x^{(1)}, x^{(2)}, x^{(3)}\right)$.

the spectral mixture kernel, we plot only $\boldsymbol{x}^{(2)}$ against the predicted value of y as shown in Figure 6. As can be seen from the figure, plain MLP only captures the linear trend. MLP-RF only captures the mean of the spectral mixture components. In contrast, our ICKy framework captures both the mean and the variance of the spectral mixture kernel. We also repeat this experiment by sampling from GP with an *additive kernel* and we obtain similar observations as shown in Figure 7.

We also examine whether ICKy can retrieve the spectral mixture kernel in this task. After fitting the parameters of the spectral mixture kernel in ICKy, we compute the kernel matrix $\boldsymbol{K}_{\mathrm{ICK}y}$ using these learned parameters and compare it with the true kernel matrix $\boldsymbol{K}_{\mathrm{true}}$ by calculating the absolute difference between them as displayed in Figure 8. As can be observed, $\boldsymbol{K}_{\mathrm{ICK}y}$ and $\boldsymbol{K}_{\mathrm{true}}$ are similar and their absolute difference is relatively small, indicating that ICKy can approximately retrieve the spectral mixture kernel.

5.1.2 Case when $M = 3$

To confirm that ICKy can work with more than 2 sources of information, we construct another synthetic data set with 3000 data points. Each input $\boldsymbol{x} = \left\{x^{(1)}, x^{(2)}, x^{(3)}\right\}$ contains information from 3 difference sources. The output y is generated by $y = x^{(3)} \tanh\left(2x^{(1)} \cos^2\left(\pi x^{(2)}/50\right)\right) + \epsilon$ where ϵ is a Gaussian noise term. We process $x^{(1)}$ with a small single-hidden-layer NN, $x^{(2)}$ with an *exponential sine squared* kernel, and $x^{(3)}$ with a *radial-basis function* (RBF) kernel. Figure 9 shows the prediction results as we progressively add more

sources of information into our ICKy framework with corresponding kernel functions. It can be observed that ICKy yields both smallest error and highest correlation with information from all 3 different sources. Hence, ICKy works well with the $M = 3$ case and the regression performance is improved as we add in more information related to the target.

5.2 Remote Sensing Data

We believe ICKy will be particularly useful for remote sensing applications. In this experiment, we evaluate ICKy on a remote sensing datasets where each data point $\boldsymbol{x} = \{x, t\}$ contains 2 sources of information: a three-band natural color (red-blue-green) satellite image x as the high-dimensional information and the corresponding timestamp as the low-dimensional information. Our goal is to forecast the ground-level PM$_{2.5}$ concentration $\hat{y} = f(x, t)$ using both sources of information.

As PM$_{2.5}$ varies with time on a yearly basis, we use an *exponential-sine-squared* kernel with a period of $T = 365$ (days) to process the low-dimensional information t. The satellite images are processed with a CNN. The results of ICKy are then compared with 2 benchmarks as shown in Table 1: a Convolutional Neural Network-Random Forest (CNN-RF) joint model (Zheng et al., 2020; 2021) (similar to the MLP-RF model in Section 5.1) and a *carefully designed* Seasonal CNN-RF model that maps t into two new features, $\sin(2\pi t/365)$ and $\cos(2\pi t/365)$, to explicitly model seasonality.

We note that the inner product operation in ICK is similar in mathematical structure to attention-based mechanisms (Vaswani et al., 2017), which are popular in many deep learning frameworks. Therefore, we introduce 2 variants of ICKy and compare them with another 4 benchmarks where the CNN is replaced by an attention-based mechanism based off a Vision Transformer (ViT) (Dosovitskiy et al., 2020) and DeepViT (Zhou et al., 2021) architectures. These models include ViT-RF, Seasonal ViT-RF, Seasonal DeepViT-RF, and Seasonal MAE-ViT-RF, where ViT is pretrained by a Masked Autoencoder (He et al., 2022). "Seasonal" here denotes that we use the transformed periodic representation defined previously. We note that we are unaware of Vision Transformers being used in this manner, and we

Table 1: Correlation and error statistics of ICKy and other joint deep models with both convolutional and attention-based architectures on the PM$_{2.5}$ forecasting task. "S." denotes seasonal variants.

	R$_{\text{Spear}}$	RMSE	MAE	MSLL
CNN-RF	0.00	194.63	185.83	-
ViT-RF	0.07	190.82	181.63	-
S. CNN-RF	0.62	53.36	39.38	96.77
S. ViT-RF	0.66	56.45	41.73	14.69
S. Deep-ViT-RF	0.65	56.36	42.46	17.63
S. MAE-ViT-RF	0.67	53.87	40.78	31.09
CNN-ICKy	0.62	53.46	39.76	**10.92**
ViT-ICKy	**0.68**	56.56	41.41	12208
DeepViT-ICKy	0.66	**52.41**	**35.93**	38220

want to evaluate whether it is the model structure or the prior information that is improving the results. Hence, these attention-based models, while not a primary contribution, are novel and represent a good-faith effort to define models with similar forms. As displayed in Table 1, both standard CNN-RF and ViT-RF models yields very large errors on predicting PM$_{2.5}$ values. After including seasonality, CNN-RF performs significantly better and shares similar predictive performance with CNN-ICKy. After replacing CNN with ViT, we observe slight improvement in both RF-joint models (especially when pre-trained by MAE) and ICKy variants. Among the models we present here, ViT-ICKy and DeepViT-ICKy achieve the highest correlation and the smallest prediction error, respectively. To evaluate the uncertainty calibration capability of ICKy, we construct **ICKy ensembles** by following Algorithm 2 and compare them with ensemble formulations of RF-joint model benchmarks. We use a criterion called Mean Standardized Log Loss (MSLL) as defined in Williams & Rasmussen (2006) to evaluate the uncertainty calibration. From Table 1, it can be observed that CNN-ICKy ensemble achieves the smallest MSLL. In addition, we realize ViT-based ICKy variants yield very large MSLL as they make predictions which are far from the true PM$_{2.5}$ labels with high confidence (i.e. small variance). We provide details and possible explanations in Appendix H.

Table 2: Prediction error of actual worker productivity on the test data set with ICKy and other benchmark models.

	MSE $\downarrow$ ($*10^{-3}$)	MAE $\downarrow$ ($*10^{-2}$)
MLP	20.16 ± 1.26	9.93 ± 0.36
Cyclic MLP	20.97 ± 1.98	10.16 ± 0.77
Cyclic MLP-RF	19.05 ± 1.36	9.70 ± 0.48
DKL	21.40 ± 2.85	11.14 ± 0.94
ICKy, $T = 2$	3.43 ± 1.42	4.85 ± 1.00
ICKy, $T = 7$	0.44 ± 0.13	1.43 ± 0.15
ICKy, $T = 30$	$\mathbf{0.31} \pm 0.09$	$\mathbf{1.17} \pm 0.14$

Table 3: Root-mean-square-error (RMSE) and negative log-likelihood (NLL) of ICKy with Matern-3/2 kernel and periodic kernel and two GP benchmarks on power consumption data.

	RMSE	NLL
Exact GP	0.055 ± 0.000	-0.152 ± 0.001
SVGP	0.084 ± 0.005	-1.010 ± 0.039
ICKy, Matérn-3/2	0.036 ± 0.000	-1.424 ± 0.000
ICKy, periodic	$\mathbf{0.033} \pm 0.000$	$\mathbf{-1.737} \pm 0.000$

5.3 Other Regression Datasets

To see if our ICKy framework generalizes to other domains, we acquired two additional regression datasets from the UCI machine learning repository, one for predicting worker productivity (with 1197 samples and 15 features) and the other for predicting power consumption (with 2075259 samples and 9 features). For the worker productivity dataset, we employ ICKy with an *exponential-sine-squared* kernel with different periods and compare them with benchmarks including MLPs (Al Imran et al., 2019) and Deep Kernel Learning (DKL) (Wilson et al., 2016) as shown in Table 2. For the power consumption dataset, we use ICKy with both an *exponential-sine-squared* kernel and a *Matérn 3/2* kernel and compare them with scalable exact GP (Wang et al., 2019) and stochastic variational GP (Hensman et al., 2013) as shown in Table 3. From the results, we observe that ICKy outperforms all the benchmarks in both experiments (especially on the worker productivity data with a margin of almost one order of magnitude).

5.4 Adapting ICK for Classification

While regression tasks are the primary motivation for this paper, there are many ways to adapt GPR for classification tasks. For example, a binary classification model can be created by using a sigmoid (Williams & Barber, 1998) or probit link (Choudhuri et al., 2007) on the output of the GP. Succinctly, given a function $f(\boldsymbol{x}) \sim \mathcal{GP}\left(0, K(\boldsymbol{x}, \boldsymbol{x}')\right)$, the binary outcome probability is be given as $p(y = 1|f(x)) = \sigma(f(x))$. Likewise, a multiple classification model can be constructed by using a multi-output GP (or multiple GPs) and putting the outputs through a softmax function (Williams & Barber, 1998) or multinomial probit link (Girolami & Rogers, 2006). This strategy can be summarized by calculating C different functions $f_c(\boldsymbol{x}) \sim \mathcal{GP}\left(0, K(\boldsymbol{x}, \boldsymbol{x}')\right)$ for $c = 1, ..., C$, where C is the number of classes, and then calculating the class probabilities through a link function, $p(y|\boldsymbol{x}) = \text{softmax}([f_1(\boldsymbol{x}), f_2(\boldsymbol{x}), ..., f_C(\boldsymbol{x})])$.

This same logic can be used to construct a multiple classification model from ICKy. Succinctly, let $r_c = f_{\text{NN},c}(\boldsymbol{x}^{(1)}) \odot \boldsymbol{z}_c^{(2)}$, where $f_{\text{NN},c}$ denotes a neural network specific to the c^{th} class and $z_c^{(2)}$ represents the Nyström approximation specific to the kernel for the c^{th} class. We note that often in a multi-output case the kernel parameters are shared, and so $\boldsymbol{z}_c^{(2)}$ would be an identical vector for each class. Then, the output probabilities for a data sample as $p(y|\boldsymbol{x}) = \text{softmax}([r_1, \ldots, r_C])$. This framework is learned with a cross-entropy loss.

To provide *proof-of-concept* of this multiple classification strategy, we implemented this model on a version of Rotating MNIST. In this task, a dataset was created by rotating each image in the dataset by a uniform random value $\phi \in [0, 2\pi)$, thus creating a dataset with 60,000 images each with an associated rotation covariate ϕ. We implemented the above multiple classification model with a periodic kernel over the rotation angle. This strategy yielded an accuracy of 92.3% on the validation data. This is lower than methods such as spatial transformers (Jaderberg et al., 2015) that report accuracy greater than 99%. However, those models explicitly use the fact that the information is simply rotated, whereas ICK is modeling a smooth transformation in the prediction function as a function of angle. This ICK classification model is much closer in concept to the way Rotating MNIST is used to evaluate unsupervised domain adaptation. While the evaluation strategy is different than our random validation set, the state-of-the-art accuracy on unsupervised

domain adaption is 87.1% (Wang et al., 2020). Due to the lack of complete and fair comparisons, we are not claiming that ICKy is state-of-the-art for classification, but ICKy's classification model does seem reasonable and viable based upon this result.

6 Discussion

Computational Complexity and Flexibility of ICK   Compared to exact composite GP models which scale $\mathcal{O}(N^3)$, the training process of our ICK framework is more efficient as it leverages standard backpropagation to learn both the paramters of NN and the kernel function. Specifically, let N_B be the number of data points in one mini-batch and p be the number of inducing points for Nyström approximation. The computational complexity for $g(\cdot)$ is $\mathcal{O}(p^2 N_B + p^3)$. The computational complexity for the forward pass of $f_{\mathrm{NN}}(\cdot)$ is $\mathcal{O}\left(N_B(k_1 k_2 + \cdots k_{L-1} k_L)\right)$ where $k_1, ..., k_L$ are the widths of each layer for a neural network of depth L. In addition, our ICK framework is more flexible compared to other joint models (i.e. BNNs and CNN-RF). Specifically, the BNNs of Pearce et al. (2020) cannot simulate complicated kernels such as the spectral mixture kernel we use in Section 5.1.

Limitations   A limitation of ICK lies in our method of combining latent representations as the nature of inner product (i.e. the effect of multiplying small numbers) may cause *vanishing gradient* problems when we have a large number of sources of information (i.e. M is large). Furthermore, in some cases, the properties of predictive posterior given by ICK ensemble are dominated by the neural network as shown in Appendix H. It can sometimes be challenging to choose an appropriate NN architecture to make sure it does not interfere with other specified kernels.

Broader Impacts   We believe our framework is extensively applicable to regression problems in many fields of study involving high-dimensional data and multiple sources of information with perceptible trends, such as remote sensing, spatial statistics, or clinical diagnosis. Also, we are not aware of any negative societal impacts of our work.

7 Conclusion

This paper presents a novel yet surprisingly simple Implicit Composite Kernel (ICK) framework to learn from *hybrid* data containing both high-dimensional information and low-dimensional information with prior knowledge. We first analytically show the resemblance between ICK and composite GPR models and then conduct experiments using both synthetic and real-world data. It appears that ICK outperforms various benchmark models in our experiments with lowest prediction errors and highest correlations even with very limited data. Overall, we show that our ICK framework is exceptionally powerful when learning from *hybrid* data with prior knowledge incorporated, and we hope our work can inspire more future research on joint machine learning models, enhancing their performance, efficiency, flexibility, and generalization capability.

References

Abdullah Al Imran, Md Nur Amin, Md Rifatul Islam Rifat, and Shamprikta Mehreen. Deep neural network approach for predicting the productivity of garment employees. In *2019 6th International Conference on Control, Decision and Information Technologies (CoDIT)*, pp. 1402–1407. IEEE, 2019.

Christopher M Bishop and Nasser M Nasrabadi. *Pattern recognition and machine learning*, volume 4. Springer, 2006.

Léon Bottou, Frank E Curtis, and Jorge Nocedal. Optimization methods for large-scale machine learning. *Siam Review*, 60(2):223–311, 2018.

Mohamed A Bouhlel and Joaquim RRA Martins. Gradient-enhanced kriging for high-dimensional problems. *Engineering with Computers*, 35(1):157–173, 2019.

Mohamed Amine Bouhlel, Nathalie Bartoli, Abdelkader Otsmane, and Joseph Morlier. Improving kriging surrogates of high-dimensional design models by partial least squares dimension reduction. *Structural and Multidisciplinary Optimization*, 53(5):935–952, 2016.

Nidhan Choudhuri, Subhashis Ghosal, and Anindya Roy. Nonparametric binary regression using a gaussian process prior. *Statistical Methodology*, 4(2):227–243, 2007.

Abhirup Datta, Sudipto Banerjee, Andrew O Finley, and Alan E Gelfand. Hierarchical nearest-neighbor gaussian process models for large geostatistical datasets. *Journal of the American Statistical Association*, 111(514):800–812, 2016.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

Petros Drineas, Michael W Mahoney, and Nello Cristianini. On the nyström method for approximating a gram matrix for improved kernel-based learning. *journal of machine learning research*, 6(12), 2005.

David Duvenaud. *Automatic model construction with Gaussian processes*. PhD thesis, University of Cambridge, 2014.

Marta Garnelo, Jonathan Schwarz, Dan Rosenbaum, Fabio Viola, Danilo J Rezende, SM Eslami, and Yee Whye Teh. Neural processes. *arXiv preprint arXiv:1807.01622*, 2018.

Adrià Garriga-Alonso, Carl Edward Rasmussen, and Laurence Aitchison. Deep convolutional networks as shallow gaussian processes. *arXiv preprint arXiv:1808.05587*, 2018.

Alan E Gelfand and Erin M Schliep. Spatial statistics and gaussian processes: A beautiful marriage. *Spatial Statistics*, 18:86–104, 2016.

Mark Girolami and Simon Rogers. Variational bayesian multinomial probit regression with gaussian process priors. *Neural Computation*, 18(8):1790–1817, 2006.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

Bobby He, Balaji Lakshminarayanan, and Yee Whye Teh. Bayesian deep ensembles via the neural tangent kernel. *Advances in neural information processing systems*, 33:1010–1022, 2020.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16000–16009, 2022.

James Hensman, Nicolo Fusi, and Neil D Lawrence. Gaussian processes for big data. *arXiv preprint arXiv:1309.6835*, 2013.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *Advances in neural information processing systems*, 31, 2018.

Max Jaderberg, Karen Simonyan, Andrew Zisserman, et al. Spatial transformer networks. *Advances in neural information processing systems*, 28, 2015.

Ziyang Jiang, Tongshu Zheng, Mike Bergin, and David Carlson. Improving spatial variation of ground-level pm2. 5 prediction with contrastive learning from satellite imagery. *Science of Remote Sensing*, pp. 100052, 2022.

Andre G Journel and Charles J Huijbregts. *Mining geostatistics*. The Blackburn Press, 1976.

Hyoung-Moon Kim, Bani K Mallick, and Chris C Holmes. Analyzing nonstationary spatial data using piecewise gaussian processes. *Journal of the American Statistical Association*, 100(470):653–668, 2005.

Daniel G Krige. A statistical approach to some basic mine valuation problems on the witwatersrand. *Journal of the Southern African Institute of Mining and Metallurgy*, 52(6):119–139, 1951.

Isaac E Lagaris, Aristidis Likas, and Dimitrios I Fotiadis. Artificial neural networks for solving ordinary and partial differential equations. *IEEE transactions on neural networks*, 9(5):987–1000, 1998.

Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

Jaehoon Lee, Yasaman Bahri, Roman Novak, Samuel S Schoenholz, Jeffrey Pennington, and Jascha Sohl-Dickstein. Deep neural networks as gaussian processes. *arXiv preprint arXiv:1711.00165*, 2017.

Jaehoon Lee, Lechao Xiao, Samuel Schoenholz, Yasaman Bahri, Roman Novak, Jascha Sohl-Dickstein, and Jeffrey Pennington. Wide neural networks of any depth evolve as linear models under gradient descent. *Advances in neural information processing systems*, 32, 2019.

Chris J Maddison, Andriy Mnih, and Yee Whye Teh. The concrete distribution: A continuous relaxation of discrete random variables. *arXiv preprint arXiv:1611.00712*, 2016.

Gary Marcus. Deep learning: A critical appraisal. *arXiv preprint arXiv:1801.00631*, 2018.

Takuo Matsubara, Chris J Oates, and François-Xavier Briol. The ridgelet prior: A covariance function approach to prior specification for bayesian neural networks. *arXiv preprint arXiv:2010.08488*, 2020.

Alexander G de G Matthews, Jiri Hron, Richard E Turner, and Zoubin Ghahramani. Sample-then-optimize posterior sampling for bayesian linear models. In *NeurIPS Workshop on Advances in Approximate Bayesian Inference*, 2017.

Alexander G de G Matthews, Mark Rowland, Jiri Hron, Richard E Turner, and Zoubin Ghahramani. Gaussian process behaviour in wide deep neural networks. *arXiv preprint arXiv:1804.11271*, 2018.

Brian McFee, Gert Lanckriet, and Tony Jebara. Learning multi-modal similarity. *Journal of machine learning research*, 12(2), 2011.

Ben Moseley, Andrew Markham, and Tarje Nissen-Meyer. Solving the wave equation with physics-informed deep learning. *arXiv preprint arXiv:2006.11894*, 2020.

Radford M Neal. Priors for infinite networks. In *Bayesian Learning for Neural Networks*, pp. 29–53. Springer, 1996.

Roman Novak, Lechao Xiao, Jiri Hron, Jaehoon Lee, Alexander A. Alemi, Jascha Sohl-Dickstein, and Samuel S. Schoenholz. Neural tangents: Fast and easy infinite neural networks in python. In *International Conference on Learning Representations*, 2020. URL https://github.com/google/neural-tangents.

Tim Pearce, Russell Tsuchida, Mohamed Zaki, Alexandra Brintrup, and Andy Neely. Expressive priors in bayesian neural networks: Kernel combinations and periodic functions. In *Uncertainty in artificial intelligence*, pp. 134–144. PMLR, 2020.

Dejan Petelin, Alexandra Grancharova, and Juš Kocijan. Evolving gaussian process models for prediction of ozone concentration in the air. *Simulation modelling practice and theory*, 33:68–80, 2013.

Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. *Advances in neural information processing systems*, 20, 2007.

Ali Rahimi and Benjamin Recht. Weighted sums of random kitchen sinks: Replacing minimization with randomization in learning. *Advances in neural information processing systems*, 21, 2008.

Edward Snelson and Zoubin Ghahramani. Sparse gaussian processes using pseudo-inputs. *Advances in neural information processing systems*, 18, 2005.

Michalis Titsias. Variational learning of inducing variables in sparse gaussian processes. In *Artificial intelligence and statistics*, pp. 567–574. PMLR, 2009.

Mark Van der Wilk, Carl Edward Rasmussen, and James Hensman. Convolutional gaussian processes. *Advances in Neural Information Processing Systems*, 30, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Hao Wang, Hao He, and Dina Katabi. Continuously indexed domain adaptation. *International Conference on Machine Learning*, 2020.

Ke Wang, Geoff Pleiss, Jacob Gardner, Stephen Tyree, Kilian Q Weinberger, and Andrew Gordon Wilson. Exact gaussian processes on a million data points. *Advances in neural information processing systems*, 32, 2019.

Christopher Williams and Matthias Seeger. Using the nyström method to speed up kernel machines. *Advances in neural information processing systems*, 13, 2000.

Christopher K Williams and Carl Edward Rasmussen. *Gaussian processes for machine learning*, volume 2. MIT press Cambridge, MA, 2006.

Christopher KI Williams and David Barber. Bayesian classification with gaussian processes. *IEEE Transactions on pattern analysis and machine intelligence*, 20(12):1342–1351, 1998.

Andrew Wilson and Ryan Adams. Gaussian process kernels for pattern discovery and extrapolation. In *International conference on machine learning*, pp. 1067–1075. PMLR, 2013.

Andrew Gordon Wilson, David A Knowles, and Zoubin Ghahramani. Gaussian process regression networks. *arXiv preprint arXiv:1110.4411*, 2011.

Andrew Gordon Wilson, Zhiting Hu, Ruslan Salakhutdinov, and Eric P Xing. Deep kernel learning. In *Artificial intelligence and statistics*, pp. 370–378. PMLR, 2016.

Tianbao Yang, Yu-Feng Li, Mehrdad Mahdavi, Rong Jin, and Zhi-Hua Zhou. Nyström method vs random fourier features: A theoretical and empirical comparison. *Advances in neural information processing systems*, 25, 2012.

Daoqiang Zhang, Yaping Wang, Luping Zhou, Hong Yuan, Dinggang Shen, Alzheimer's Disease Neuroimaging Initiative, et al. Multimodal classification of alzheimer's disease and mild cognitive impairment. *Neuroimage*, 55(3):856–867, 2011.

Tongshu Zheng, Michael H Bergin, Shijia Hu, Joshua Miller, and David E Carlson. Estimating ground-level pm2. 5 using micro-satellite images by a convolutional neural network and random forest approach. *Atmospheric Environment*, 230:117451, 2020.

Tongshu Zheng, Michael Bergin, Guoyin Wang, and David Carlson. Local pm2. 5 hotspot detector at 300 m resolution: A random forest–convolutional neural network joint model jointly trained on satellite images and meteorology. *Remote Sensing*, 13(7):1356, 2021.

Daquan Zhou, Bingyi Kang, Xiaojie Jin, Linjie Yang, Xiaochen Lian, Zihang Jiang, Qibin Hou, and Jiashi Feng. Deepvit: Towards deeper vision transformer. *arXiv preprint arXiv:2103.11886*, 2021.