A Near-Optimal Algorithm for Stochastic Bilevel Optimization via Double-Momentum

Abstract

This paper proposes a new algorithm – the Single-timescale Double-momentum Stochastic Approximation (SUSTAIN) – for tackling stochastic unconstrained bilevel optimization problems. We focus on bilevel problems where the lower level subproblem is strongly-convex and the upper level objective function is smooth. Unlike prior works which rely on *two-timescale* or *double loop* techniques, we design a stochastic momentum-assisted gradient estimator for both the upper and lower level updates. The latter allows us to control the error in the stochastic gradient updates due to inaccurate solution to both subproblems. If the upper objective function is smooth but possibly non-convex, we show that SUSTAIN requires $\mathcal{O}(\epsilon^{-3/2})$ iterations (each using $\mathcal{O}(1)$ samples) to find an ϵ-stationary solution. The ϵ-stationary solution is defined as the point whose squared norm of the gradient of the outer function is less than or equal to ϵ. The total number of stochastic gradient samples required for the upper and lower level objective functions matches the best-known complexity for single-level stochastic gradient algorithms. We also analyze the case when the upper level objective function is strongly-convex.

1 Introduction

Many learning and inference problems take a "hierarchical" form, wherein the optimal solution of one problem affects the objective function of others [25]. Bilevel optimization is often used to model problems of this kind with two levels of hierarchy [25, 8], where the variables of an *upper level* problem depend on the optimizer of certain *lower level* problem. In this work, we consider unconstrained bilevel optimization problems of the form:

$$
\begin{aligned}
\min_{x \in \mathbb{R}^{d_{\mathsf{up}}}} \ \ell(x) &= f(x, y^*(x)) \coloneqq \mathbb{E}_\xi[f(x, y^*(x); \xi)] \\
\text{s.t.} \quad y^*(x) &= \arg\min_{y \in \mathbb{R}^{d_{\mathsf{lo}}}} \left\{ g(x, y) \coloneqq \mathbb{E}_\zeta[g(x, y; \zeta)] \right\},
\end{aligned}
\tag{1}
$$

where $f, g : \mathbb{R}^{d_{\mathsf{up}}} \times \mathbb{R}^{d_{\mathsf{lo}}} \to \mathbb{R}$ with $x \in \mathbb{R}^{d_{\mathsf{up}}}$ and $y \in \mathbb{R}^{d_{\mathsf{lo}}}$; $f(x, y; \xi)$ with $\xi \sim \pi_f$ (resp. $g(x, y; \zeta)$ with $\zeta \sim \pi_g$) represents a stochastic sample of the upper level objective (resp. lower level objective). Note here that the *upper level objective* f depends on the minimizer of the *lower level objective* g, and we refer to $\ell(x)$ as the *outer function*. Throughout this paper, $g(x, y)$ is assumed to be strongly-convex in y, which implies that $\ell(x)$ is smooth but possibly non-convex.

The applications of (1) include many machine learning problems that have a hierarchical structure. Examples are meta learning [13, 28], data hyper-cleaning [32], hyper-parameter optimization [12, 13, 26], and reinforcement learning [20], etc.. To better contextualize our study, below we describe examples on meta-learning problem and data hyper-cleaning problem:

Example 1: Meta learning. The meta learning problem aims to learn task specific parameters that generalize to a diverse set of tasks [27]. Suppose we have M tasks $\{\mathcal{T}_i, i = 1, \ldots, M\}$ and each task

Algorithm	Sample (Upper, Lower)	Implementation	Batch Size	Per-Iteration Complexity
BSA [14]	$\mathcal{O}(\epsilon^{-2})$, $\mathcal{O}(\epsilon^{-3})$	Double loop	$\mathcal{O}(1)$	$\mathcal{O}(d_{\mathsf{lo}}^2 \cdot \log T)$
stocBiO [19]	$\mathcal{O}(\epsilon^{-2})$, $\mathcal{O}(\epsilon^{-2})$	Double loop	$\mathcal{O}(\epsilon^{-1})$	$\mathcal{O}(d_{\mathsf{lo}}^2 \cdot \log T)$
TTSA [18]	$\mathcal{O}(\epsilon^{-5/2})$, $\mathcal{O}(\epsilon^{-5/2})$	Single loop	$\mathcal{O}(1)$	$\mathcal{O}(d_{\mathsf{lo}}^2 \cdot \log T)$
STABLE [5]	$\mathcal{O}(\epsilon^{-2})$, $\mathcal{O}(\epsilon^{-2})$	Single loop	$\mathcal{O}(1)$	$\mathcal{O}(d_{\mathsf{lo}}^3)$
SVRB [17]	$\mathcal{O}(\epsilon^{-3/2})$, $\mathcal{O}(\epsilon^{-3/2})$	Single loop	$\mathcal{O}(1)$	$\mathcal{O}(d_{\mathsf{lo}}^3 \cdot \log T)$
SUSTAIN (this work)	$\mathcal{O}(\epsilon^{-3/2})$, $\mathcal{O}(\epsilon^{-3/2})$	Single loop	$\mathcal{O}(1)$	$\mathcal{O}(d_{\mathsf{lo}}^2 \cdot \log T)$

Table 1: Comparison of the number of upper and lower level gradient samples required to achieve an ϵ-stationary point in Definition 1.1. For the algorithms with $\mathcal{O}(d_{\mathsf{lo}}^2 \cdot \log T)$ per-iteration dependence, the Hessian inverse can be computed via matrix vector products; algorithms with $\mathcal{O}(d_{\mathsf{lo}}^3)$ dependency requires Hessian inverses and Hessian projections, which incur heavy computational cost.

has a corresponding loss function $L(x, y_i; \xi_i)$ with ξ_i representing a data sample for task $\mathcal{T}_i$, $x \in \mathbb{R}^{d_{\mathsf{up}}}$ the model parameters shared among tasks, and $y_i \in \mathbb{R}^{d_{\mathsf{lo}}^i}$ the task specific parameters. The goal of meta learning is then to solve the following problem:

$$\min_{x \in \mathbb{R}^{d_{\mathsf{up}}}} \left\{ L_{\mathsf{ts}}(x, \bar{y}^*(x)) := \frac{1}{M} \sum_{i=1}^{M} \mathbb{E}_{\xi_i \sim \mathcal{D}_i}[L(x, \bar{y}_i^*(x); \xi_i)] \right\}$$

$$\text{s.t. } \bar{y}^*(x) \in \arg\min_{\bar{y} \in \mathbb{R}^{\Sigma_{i=1}^M d_{\mathsf{lo}}^i}} L_{\mathsf{tr}}(x, \bar{y}) := \frac{1}{M} \sum_{i=1}^{M} \left(\mathbb{E}_{\zeta_i \sim \mathcal{S}_i}[L(x, \bar{y}_i; \zeta_i)] + \mathcal{R}(y_i) \right), \quad (2)$$

where $\mathcal{R}(\cdot)$ is a strongly convex regularizer while $\mathcal{S}_i$ and $\mathcal{D}_i$ are the training and testing datasets for task $\mathcal{T}_i$. Compared to the number of tasks, the dataset sizes are usually small for meta-learning problems, so the stochasticity in tackling (2) results from the fact that at each iteration we can only sample a subset m out of M tasks. Note that this problem is a special case of (1). □

Example 2: Data hyper-cleaning. The data hyper-cleaning is a hyperparameter optimization problem that aims to train a classifier model with a dataset of randomly corrupted labels [32]. The optimization problem is formulated below:

$$\min_{x \in \mathbb{R}^{d_{\mathsf{up}}}} \ell(x) := \sum_{i \in \mathcal{D}_{\mathsf{val}}} L(a_i^\top y^*(x), b_i) \qquad (3)$$

$$\text{s.t. } y^*(x) = \arg\min_{y \in \mathbb{R}^{d_{\mathsf{lo}}}} \left\{ c\|y\|^2 + \sum_{i \in \mathcal{D}_{\mathsf{tr}}} \sigma(x_i) L(a_i^\top y, b_i) \right\}.$$

In this problem, we have $d_{\mathsf{up}} = |\mathcal{D}_{\mathsf{tr}}|$ and d_{lo} is the dimension of the classifier. Moreover, (a_i, b_i) is the ith data point; $L(\cdot)$ is the loss function, with y being the model parameter; x_i is the parameter that determines the weight for the ith data sample, and $\sigma : \mathbb{R} \to \mathbb{R}_+$ is the weight function; $c > 0$ is a regularization parameter; $\mathcal{D}_{\mathsf{val}}$ and $\mathcal{D}_{\mathsf{tr}}$ are validation and training sets, respectively. Clearly, (3) is a special case of (1) where the lower level problem finds the classifier $y^*(x)$ with the training set $\mathcal{D}_{\mathsf{tr}}$, and the upper level problem finds the best weights x with respect to the validation set $\mathcal{D}_{\mathsf{val}}$. □

A natural approach to tackling (1) is to apply alternating stochastic gradient (SG) updates. Let $\beta, \alpha > 0$ be some step sizes, one performs the recursion

$$y^+ \leftarrow y - \beta \hat{\nabla}_y g(x, y), \quad x^+ \leftarrow x - \alpha \hat{\nabla}_x \hat{\ell}(x; y) \qquad (4)$$

such that $\hat{\nabla}_y g(x, y)$, $\hat{\nabla}_x \hat{\ell}(x; y)$ are stochastic estimates of $\nabla_y g(x, y)$, $\nabla \ell(x)$, respectively. Notice that (4) is significantly different from the standard alternating primal-dual gradient algorithm for saddle point problems. Particularly, the design of $\hat{\nabla}_x \hat{\ell}(x; y)$ is crucial to the SG scheme in (4). Observe that $\nabla \ell(x)$ can be computed using the implicit function theorem, and its evaluation requires $f(\cdot, \cdot)$ and $y^\star(x)$, the minimizer of $g(x, y)$ given x (cf. (5)). This gives rise to a unique challenge to bilevel optimization, where $y^\star(x)$ can only be *approximated* by y obtained in the first relation of (4).

In light of the above observations, previous endeavors have considered two approaches to improve the estimate of $y^\star(x)$ while $\hat{\nabla}_x \hat{\ell}(x; y)$ is used as a *biased* approximation of $\nabla \ell(x)$. The first approach is to apply the *double-loop* algorithms. For example, [14] proposed to repeat the y^+ update for multiple times to obtain a better estimate of $y^\star(x)$ before performing the x^+ update, [19] proposed to take a large batch size to estimate $\nabla_y g(x, y)$. While simple to analyze, these algorithms may suffer from a poor sample complexity for the inner problem. The second approach is to apply *single-loop* algorithms where the y^+-updates are performed simultaneously with the x^+-updates. Instead, advanced techniques are utilized that allows y^+ to accurately track $y^\star(x)$. For example, [18] suggested to tune the step size schedule with $\beta \gg \alpha$, [5, 17] proposed single-timescale algorithms

with advanced variance reduction techniques. However, the latter two algorithms require Hessian projections onto a compact set along with Hessian matrices inversion which scales poorly with dimension (i.e., in $\mathcal{O}(d_{\text{lo}}^3)$). We summarize and compare the complexity results of the state-of-the-art algorithms in Table 1.

A careful inspection on the above results reveals a gap in the iteration/sample complexity compared to *single-level* stochastic optimization. For instance, an optimal stochastic gradient algorithm finds an ϵ-stationary solution [cf. Definition 1.1] to $\min_x \mathbb{E}_\xi[\ell(x; \xi)]$ in $\mathcal{O}(\epsilon^{-3/2})$ iterations [10, 7, 34, 39]. For bilevel optimization, the fastest rate available is only $\mathcal{O}(\epsilon^{-2})$ to the best of the authors' knowledge. In comparison, the proposed algorithm achieves a rate of $\mathcal{O}(\epsilon^{-3/2})$. During the preparation of the current paper, a preprint [17] has appeared which extended [5], and achieves an improved rate of $\mathcal{O}(\epsilon^{-3/2})$. We remark that the latter work follows a different design philosophy from ours and maybe less efficient; see the detailed discussion at the end of Sec. 3.

Contributions. In this paper, we depart from the prior developments which focused on finding better inner solutions $y^*(x)$ to approximate $\hat{\nabla}_x \hat{\ell}(x; y) \approx \nabla \ell(x)$. Our idea is to exploit the gradient estimates from prior iterations to improve the quality of the current gradient estimation. This leads to *momentum*-assisted stochastic gradient estimators for *both* $\nabla_y g(x, y)$ and $\nabla \ell(x)$ using similar techniques in [7, 34] for single-level stochastic optimization. The resultant algorithm only requires $O(1)$ samples at each update, and updates x and y using step sizes of the same order, hence the name single-timescale double-momentum stochastic approximation(SUSTAIN) algorithm. Additionally, it is worth noting that our algorithm has a $\mathcal{O}(d_{\text{lo}}^2)$ per iteration complexity, compared to the $\mathcal{O}(d_{\text{lo}}^3)$ complexity of STABLE [5] and SVRB [17]. That is, the SUSTAIN algorithm is both *sample and computation* efficient. Our specific contributions are:

- We propose the SUSTAIN algorithm for bilevel problems which matches the best complexity bounds as the optimal SGD algorithms for single-level stochastic optimization. That is, it requires $\mathcal{O}(\epsilon^{-3/2})$ [resp. $\mathcal{O}(\epsilon^{-1})$] samples to find an ϵ-stationary solution for non-convex (resp. strongly-convex) bilevel problems; see Table 1. Furthermore, the algorithm utilizes a single-loop update with step sizes of the same order for both upper and lower level problems. Such complexity bounds match the optimal sample complexity of stochastic gradient algorithms for single-level problems.

- By developing the Lipschitz continuous property of the (biased) stochastic estimates of $\nabla \ell(x)$, we show that obtaining a good estimate of $\nabla \ell(x)$ does not require explicit (sampled) Hessian inversion. This key result ensures that our algorithm depends favorably on the problem dimension.

- Comparing with prior works such as TTSA [18], BSA [14], STABLE [5] and SVRB [17], our analysis reveals that improving the gradient estimation quality for *both* $\nabla_y g(x, y)$ and $\nabla \ell(x)$ is the key to obtain a sample and computation efficient stochastic algorithm for bilevel optimization.

Related works. The study of the bilevel problem (1) can be traced to that of game theory [33] and was formally introduced in [2–4]. It is also related to the broader class of problems of Mathematical Programming with Equilibrium Constraints [24]. Related algorithms include approximate descent [9, 35], and penalty-based methods [37]; see [6] and [23] for a comprehensive survey.

In addition to the works cited in Table 1, recent works on bilevel optimization have focused on algorithms with provable convergence rates. In [31], the authors proposed BigSAM algorithm for solving simple bilevel problems (with a single variable) with convex lower level problem. Subsequently, the works [22, 21] utilized BigSAM and developed algorithms for a general bilevel problem for the cases when the solution of the lower level problem is not a singleton. Note that all the aforementioned works [31, 22, 21] assumed the upper level problem to be strongly-convex with convex lower level problem. In a separate line of work, backpropagation based algorithms have been proposed to approximately solve bilevel problems [12, 32, 16, 15]. However, the major focus of these works was to develop efficient gradient estimators rather than on developing efficient optimization algorithms.

Notation. For any $x \in \mathbb{R}^d$, we denote $\|x\|$ as the standard Euclidean norm; as for $X \in \mathbb{R}^{n \times d}$, $\|X\|$ is induced by the Euclidean norm. For a multivariate function $f(x, y)$, the notation $\nabla_x f(x, y)$ [resp. $\nabla_y f(x, y)$] refers to the partial gradient taken with respect to (w.r.t.) x [resp. y]. For some $\mu > 0$, a function $f(x, y)$ is said to be μ-strongly-convex in x if $f(x, y) - \frac{\mu}{2}\|x\|^2$ is convex in x. For some $L > 0$, the map $\mathcal{A} : \mathbb{R}^d \to \mathbb{R}^m$ is said to be L-Lipschitz continuous if $\|\mathcal{A}(x) - \mathcal{A}(y)\| \leq L\|x - y\|$ for any $x, y \in \mathbb{R}^d$. A function $f : \mathbb{R}^d \to \mathbb{R}$ is said to be L-smooth if its gradient is L-Lipschitz continuous. Uniform distribution over a discrete set $\{1, \ldots, T\}$ is represented by $\mathcal{U}\{1, \ldots, T\}$.

Finally, we state the following definitions for the optimality criteria of (1).

Definition 1.1 (ϵ-Stationary Point). A point x is called ϵ-stationary if $\|\nabla\ell(x)\|^2 \leq \epsilon$. A stochastic algorithm is said to achieve an ϵ-stationary point in t iterations if $\mathbb{E}[\|\nabla\ell(x_t)\|^2] \leq \epsilon$, where the expectation is over the stochasticity of the algorithm until time instant t.

Definition 1.2 (ϵ-Optimal Point). A point x is called ϵ-optimal if $\ell(x) - \ell^* \leq \epsilon$, where $\ell^* := \min_{x \in \mathbb{R}^{d_{\mathsf{up}}}} \ell(x)$. A stochastic algorithm is said to achieve an ϵ-optimal point in t iterations if $\mathbb{E}[\ell(x_t) - \ell^*] \leq \epsilon$, where the expectation is over the stochasticity of the algorithm until time instant t.

2 Preliminaries

We discuss the assumptions on (1) to specify the problem class of interest. We also preface the proposed algorithm by describing a practical procedure for estimating the stochastic gradients.

Assumption 1 (Upper Level Function). $f(x,y)$ satisfies the following conditions:

   (i) $\nabla_x f(x,y)$ and $\nabla_y f(x,y)$ are Lipschitz continuous w.r.t. $(x,y) \in \mathbb{R}^{d_{\mathsf{up}}} \times \mathbb{R}^{d_{\mathsf{lo}}}$, and with constants $L_{f_x} \geq 0$ and $L_{f_y} \geq 0$, respectively.

   (ii) For any $(x,y) \in \mathbb{R}^{d_{\mathsf{up}}} \times \mathbb{R}^{d_{\mathsf{lo}}}$, we have $\|\nabla_y f(x,y)\| \leq C_{f_y}$, for some $C_{f_y} \geq 0$.

Assumption 2 (Lower level Function). $g(x,y)$ satisfies the following conditions:

   (i) For any $x \in \mathbb{R}^{d_{\mathsf{up}}}$ and $y \in \mathbb{R}^{d_{\mathsf{lo}}}$, $g(x,y)$ is twice continuously differentiable in (x,y).

   (ii) $\nabla_y g(x,y)$ is Lipschitz continuous w.r.t. $(x,y) \in \mathbb{R}^{d_{\mathsf{up}}} \times \mathbb{R}^{d_{\mathsf{lo}}}$, and with constant $L_g \geq 0$.

   (iii) For any $x \in \mathbb{R}^{d_{\mathsf{up}}}$, $g(x,\cdot)$ is μ_g-strongly-convex in y for some $\mu_g > 0$.

   (iv) $\nabla^2_{xy} g(x,y)$ and $\nabla^2_{yy} g(x,y)$ are Lipschitz continuous w.r.t. $(x,y) \in \mathbb{R}^{d_{\mathsf{up}}} \times \mathbb{R}^{d_{\mathsf{lo}}}$, and with constants $L_{g_{xy}} \geq 0$ and $L_{g_{yy}} \geq 0$, respectively.

   (v) For any $(x,y) \in \mathbb{R}^{d_{\mathsf{up}}} \times \mathbb{R}^{d_{\mathsf{lo}}}$, we have $\|\nabla^2_{xy} g(x,y)\|^2 \leq C_{g_{xy}}$ for some $C_{g_{xy}} > 0$.

Assumption 3 (Stochastic Functions). Assumptions 1 and 2 hold for $f(x,y;\xi)$ and $g(x,y;\zeta)$, for all $\xi \in \text{supp}(\pi_f)$ and $\zeta \in \text{supp}(\pi_g)$ where $\text{supp}(\pi)$ is the support of π.

These assumptions are standard in the analysis of bilevel optimization [14]. For example, they are satisfied by a range of applications such as the meta learning problem (2), data hypercleaning problem (3) with linear classifier. Notice that under these assumptions, the gradient $\nabla\ell(\cdot)$ is well-defined. By utilizing Assumption 2–(i) and (ii) along with the implicit function theorem [30], it is easy to show that for a given $\bar{x} \in \mathbb{R}^{d_{\mathsf{up}}}$, the following holds [14, Lemma 2.1]:

$$\nabla\ell(\bar{x}) = \nabla_x f(\bar{x}, y^*(\bar{x})) - \nabla^2_{xy} g(\bar{x}, y^*(\bar{x}))[\nabla^2_{yy} g(\bar{x}, y^*(\bar{x}))]^{-1} \nabla_y f(\bar{x}, y^*(\bar{x})). \quad (5)$$

Obtaining $y^*(x)$ in closed-form is usually a challenging task, so it is natural to use the following gradient surrogate. At any $(\bar{x}, \bar{y}) \in \mathbb{R}^{d_{\mathsf{up}} \times d_{\mathsf{lo}}}$, define:

$$\bar{\nabla} f(\bar{x}, \bar{y}) = \nabla_x f(\bar{x}, \bar{y}) - \nabla^2_{xy} g(\bar{x}, \bar{y})[\nabla^2_{yy} g(\bar{x}, \bar{y})]^{-1} \nabla_y f(\bar{x}, \bar{y}). \quad (6)$$

Evaluating (6) requires computing the exact gradients and Hessian inverse which can be non-trivial. Below, we describe a practical procedure from [14] to generate a *biased* estimate of $\bar{\nabla} f(\bar{x}, \bar{y})$.

Stochastic gradient estimator for $\nabla\ell(x)$. The estimator requires a parameter $K \in \mathbb{N}$ and is based on a collection of $K+3$ independent samples $\bar{\xi} := \{\xi, \zeta^{(0)}, ..., \zeta^{(K)}, \mathsf{k}(K)\}$, where $\xi \sim \mu$, $\zeta^{(i)} \sim \pi_g$, $i = 0, ..., K$, and $\mathsf{k}(K) \sim \mathcal{U}\{0, ..., K-1\}$. We set

$$\bar{\nabla} f(x,y;\bar{\xi}) = \nabla_x f(x,y;\xi) - \frac{K}{L_g} \nabla^2_{xy} g(x,y;\zeta^{(0)}) \prod_{i=1}^{\mathsf{k}(K)} \left(I - \frac{\nabla^2_{yy} g(x,y;\zeta^{(i)})}{L_g} \right) \nabla_y f(x,y;\xi), \quad (7)$$

where we have used the convention $\prod_{i=1}^{j} A_i = I$ if $j = 0$. It has been shown in [14, 18] that the bias with the gradient estimator (7) decays exponentially fast with K, as summarized below:

Lemma 2.1. *Under Assumptions 1, 2. For any $K \geq 1$, the gradient estimator in (7) satisfies*

$$\|\bar{\nabla} f(x,y) - \mathbb{E}_{\bar{\xi}}[\bar{\nabla} f(x,y;\bar{\xi})]\| \leq \frac{C_{g_{xy}} C_{f_y}}{\mu_g} \left(1 - \frac{\mu_g}{L_g} \right)^K, \quad \forall (x,y) \in \mathbb{R}^{d_{\mathsf{up}}} \times \mathbb{R}^{d_{\mathsf{lo}}}. \quad (8)$$

158 The detailed statement of the above lemma is included in Appendix C. We remark that each computa-
159 tion of $\bar{\nabla} f(x, y; \bar{\xi})$ requires at most K Hessian-vector products, and later we will show that setting
160 $K = \mathcal{O}(\log(T))$ is necessary for the proposed algorithm. Since $\nabla_{yy}^2 g(x, y; \zeta)$ is of size $d_{\mathsf{lo}} \times d_{\mathsf{lo}}$, the
161 total complexity of this step is $\mathcal{O}(\log(T) d_{\mathsf{lo}}^2)$. On the contrary, STABLE [5] and SVRB [17] require
162 $\mathcal{O}(d_{\mathsf{lo}}^3)$ to estimate the Hessian inverse, which is more computationally expensive when $d_{\mathsf{lo}} \gg 1$.
163 Indeed, it has been explicitly mentioned in [5] that "*our algorithm (STABLE) is preferable in the*
164 *regime where the sampling is more costly than computation or the dimension d is relatively small*".

165 Notice that (7) is not the only option for estimating the gradient surrogate $\bar{\nabla} f(x, y)$. For ease of
166 presentation, below we abstract out the conditions on the stochastic estimates of $\nabla_y g, \bar{\nabla} f$ required
167 by our analysis as the following assumption:

168 **Assumption 4** (Stochastic Gradients). For any $(x, y) \in \mathbb{R}^{d_{\mathsf{up}}} \times \mathbb{R}^{d_{\mathsf{lo}}}$, there exists constants $\sigma_f, \sigma_g \geq 0$
169 such that the estimates $\nabla_y g(x, y; \zeta), \bar{\nabla} f(x, y; \bar{\xi})$ satisfy:

170 (i) The gradient estimate of the upper level objective satisfies:

$$\mathbb{E}_{\bar{\xi}}\big[\|\bar{\nabla} f(x, y; \bar{\xi}) - \bar{\nabla} f(x, y) - B(x, y)\|^2\big] \leq \sigma_f^2, \tag{9}$$

171   where $B(x, y) = \mathbb{E}_{\bar{\xi}}[\bar{\nabla} f(x, y; \bar{\xi})] - \bar{\nabla} f(x, y)$ is the bias in estimating $\bar{\nabla} f(x, y)$.

172 (ii) The gradient estimate of the lower level objective satisfies

$$\mathbb{E}_{\zeta}\big[\|\nabla_y g(x, y; \zeta) - \nabla_y g(x, y)\|^2\big] \leq \sigma_g^2. \tag{10}$$

173 As observed from Lemma 2.1, the gradient estimator (7) satisfies Assumption 4(i).

174 Lastly, the approximate gradient defined in (6), the true gradient (5), as well as the optimal solution
175 of the lower level problem are Lipschitz continuous, as proven below:

176 **Lemma 2.2.** *[14, Lemma 2.2] Under Assumptions 1, 2 and 3, we have*

$$\|\bar{\nabla} f(x, y) - \nabla \ell(x)\| \leq L\|y^*(x) - y\|, \quad \|y^*(x_1) - y^*(x_2)\| \leq L_y\|x_1 - x_2\|,$$
$$\|\nabla \ell(x_1) - \nabla \ell(x_2)\| \leq L_f\|x_1 - x_2\|, \tag{11}$$

177 *for all $x, x_1, x_2 \in \mathbb{R}^{d_{\mathsf{up}}}$ and $y \in \mathbb{R}^{d_{\mathsf{lo}}}$. The above Lipschitz constants are defined as:*

$$L = L_{f_x} + \frac{L_{f_y} C_{g_{xy}}}{\mu_g} + C_{f_y}\left(\frac{L_{g_{xy}}}{\mu_g} + \frac{L_{g_{yy}} C_{g_{xy}}}{\mu_g^2}\right), \quad L_f = L + \frac{L C_{g_{xy}}}{\mu_g}, \quad L_y = \frac{C_g}{\mu_g}. \tag{12}$$

178 The first result in (11) reveals that $\bar{\nabla} f(x, y)$ approximates $\nabla \ell(x)$ when $y \approx y^*(x)$. This suggests
179 that a *double-loop* algorithm which solves the strongly-convex lower level problem to sufficient
180 accuracy can be applied to tackle (1). Such approach has been pursued in [14, 19]. Next, we propose
181 an algorithm which rely on *single-loop* updates with improved sample efficiency.

3   The proposed **SUSTAIN** algorithm

183 Equipped with a practical stochastic gradient estimator for $\nabla \ell(x)$ [cf. (7)], our next endeavor is to
184 develop a *single-loop* algorithm to tackle (1) through drawing $\mathcal{O}(1)$ samples for upper and lower level
185 problems at each iteration. Our main idea is to adopt the recursive momentum techniques developed
186 in [7, 34]. Notice that these works utilize *unbiased* stochastic gradients evaluated at consecutive
187 iterates to construct a variance reduced gradient estimate for single-level stochastic optimization.

188 In the context of bilevel stochastic optimization (1), a few key challenges are in order:

189 • Recall from Lemma 2.1 that obtaining an unbiased estimator for the outer gradient $\nabla \ell(x)$ requires
190   using $K \to \infty$ samples in (7), this calls for the new techniques to control the bias arising from
191   approximating $\nabla \ell(x)$.
192 • The gradient estimator (7) has a more complicated structure than a plain gradient estimator,
193   as it involves up to three different stochastic vectors/matrices related to $\nabla_x f(x, y), \nabla_y f(x, y)$,
194   $\nabla_{xy} g(x, y)$, and one stochastic inversion that is related to $[\nabla_{yy} g(x, y)]^{-1}$. It is not clear which
195   are the most important objects for which variance reduction shall be applied.

Algorithm 1 The Proposed SUSTAIN Algorithm

1: **Input**: Parameters: $\{\beta_t\}_{t=0}^{T-1}$, $\{\alpha_t\}_{t=0}^{T-1}$, $\{\eta_t^f\}_{t=0}^{T-1}$, and $\{\eta_t^g\}_{t=0}^{T-1}$ with $\eta_0^f = \eta_0^g = 1$

2: **Initialize**: x_0, y_0; set $x_{-1} = y_{-1} = h_{-1}^f = h_{-1}^g = 0$

3: **for** $t = 0$ to $T - 1$ **do**

4: (y-update) Compute the gradient estimator h_t^g by (13) and set $y_{t+1} = y_t - \beta_t h_t^g$.

5: (x-update) Compute the gradient estimator h_t^f by (14) and set $x_{t+1} = x_t - \alpha_t h_t^f$.

6: **end for**

7: **Return:** $x_{a(T)}$ where $a(T) \sim \mathcal{U}\{1, ..., T\}$.

Our key innovation is to develop a useful estimate of $\bar{\nabla} f(x, y)$ by using a novel *double-momentum* technique. First, we build a recursive momentum estimator for $\nabla_y g(x, y)$, based upon which the variable y gets updated. Then, with such a "stabilized" inner iteration, we compute an estimate of $\bar{\nabla} f(x, y)$ as given in (7), by using the four stochastic vectors/matrices mentioned above but without performing any variance reduction. Such a stochastic estimator will then be used to construct a recursive momentum estimator for $\bar{\nabla} f(x, y)$. The intuition is that as long as y is *accurate enough*, then the stochastic terms in (7) are also accurate enough, so they can be used to construct the estimator for the outer gradient. Our approach only tracks two vector estimators, while still being able to leverage the low-complexity sample-based Hessian inversion as given in (7).

The SUSTAIN algorithm is summarized in Algorithm 1. Define $\eta_t^g \in [0, 1]$, $\eta_t^f \in [0, 1]$. For the lower level problem involving y, it utilizes the following momentum-assisted gradient estimator, $h_t^g \in \mathbb{R}^{d_{\text{lo}}}$, defined recursively as

$$h_t^g = \eta_t^g \nabla_y g(x_t, y_t; \zeta_t) + (1 - \eta_t^g)\big(h_{t-1}^g + \nabla_y g(x_t, y_t; \zeta_t) - \nabla_y g(x_{t-1}, y_{t-1}; \zeta_t)\big); \quad (13)$$

For the upper level problem involving x, we utilize a similar estimate, $h_t^f \in \mathbb{R}^{d_{\text{up}}}$, defined as

$$h_t^f = \eta_t^f \bar{\nabla} f(x_t, y_t; \bar{\xi}_t) + (1 - \eta_t^f)\big(h_{t-1}^f + \bar{\nabla} f(x_t, y_t; \bar{\xi}_t) - \bar{\nabla} f(x_{t-1}, y_{t-1}; \bar{\xi}_t)\big). \quad (14)$$

The gradient estimators h_t^g and h_t^f are computed from the current and past gradient estimates $\nabla_y g(x_t, y_t; \zeta_t), \nabla_y g(x_{t-1}, y_{t-1}; \zeta_t)$ and $\bar{\nabla} f(x_t, y_t; \bar{\xi}_t), \bar{\nabla} f(x_{t-1}, y_{t-1}; \bar{\xi}_t)$. Note that the stochastic gradients at two consecutive iterates are computed using the same sample sets ζ_t for h_t^g and $\bar{\xi}_t$ for h_t^f.

Both x and y-update steps mark a major departure of the SUSTAIN algorithm from existing algorithms on bilevel optimization [14, 18, 19]. The latter works apply the direct gradient estimator $\bar{\nabla} f(x_t, y_{t+1}; \bar{\xi}_t)$ [cf. (7)] to serve as an estimate to $\bar{\nabla} f(x, y)$ [and subsequently $\bar{\nabla} \ell(x)$]. To guarantee convergence, these works focused on improving the *tracking performance* of $y_{t+1} \approx y^\star(x_t)$ by employing double-loop updates, e.g., by repeatedly applying SG step multiple times for the inner problem; or a sophisticated two-timescale design for the step sizes, e.g., by setting $\beta_t/\alpha_t \to \infty$.

A recent preprint [17] suggested the SVRB algorithm which applies a similar recursive momentum technique as SUSTAIN. However, the SVRB algorithm is different from SUSTAIN as the momentum estimator is applied exhaustively to *all* the individual random quantities involved in (7) and requires a Hessian projection step. As a result, the SVRB algorithm entails a high complexity in storage and computation as the latter has to store matrix variables of size $d_{\text{lo}} \times d_{\text{lo}}$ and computes a matrix inverse for each iteration. In comparison, the SUSTAIN algorithm only requires storing the gradient estimators h_t^g, h_t^f of size $d_{\text{lo}}, d_{\text{up}}$, respectively, and the computation complexity is only $\mathcal{O}(d_{\text{lo}}^2 K)$ for each iteration.

3.1 Convergence analysis

In the following, we present the convergence analysis for the SUSTAIN algorithm when $\ell(\cdot)$ is a smooth function [cf. consequence of Assumptions 1, 2 and 3]. Before proceeding to the main results, we present a lemma about the Lipschitzness of the gradient estimate $\bar{\nabla} f(x, y; \bar{\xi})$ given in (7):

Lemma 3.1. *Under Assumptions 1, 2 and 3, we have for any* $(x_1, y_1), (x_2, y_2) \in \mathbb{R}^{d_{\text{up}}} \times \mathbb{R}^{d_{\text{lo}}}$,

$$\mathbb{E}_{\bar{\xi}} \|\bar{\nabla} f(x_1, y_1; \bar{\xi}) - \bar{\nabla} f(x_2, y_2; \bar{\xi})\| \le L_K^2 \big\{\|x_1 - x_2\| + \|y_1 - y_2\|\big\}^2,$$

where

$$L_K = \sqrt{2L_{f_x}^2 + \frac{6C_{g_{xy}}^2 L_{f_y}^2 K}{2\mu_g L_g - \mu_g^2} + \frac{6C_{f_y}^2 L_{g_{xy}}^2 K}{2\mu_g L_g - \mu_g^2} + \frac{6C_{g_{xy}}^2 C_{f_y}^2 L_{g_{yy}}^2 K^3}{(L_g - \mu_g)^2(2\mu_g L_g - \mu_g^2)}}, \tag{15}$$

and K is the number of samples required to construct the stochastic gradient estimate given in (7).

The detailed proof can be found in Appendix C. We remark that the above result is crucial for analyzing the error of the gradient estimate h_t^f defined in (14). To see this, let us first define the errors of the gradient estimates for the outer and inner functions as follows

$$e_t^f := h_t^f - \bar{\nabla}f(x_t, y_t) - B_t, \quad e_t^g := h_t^g - \bar{\nabla}_y g(x_t, y_t), \tag{16}$$

where $B_t := B(x_t, y_t)$ denotes the bias. Rewriting e_t^f using (14) gives the following recursion:

$$e_t^f = (1 - \eta_t^f)e_{t-1}^f + (1 - \eta_t^f)\{\bar{\nabla}f(x_t, y_t; \bar{\xi}_t) - \bar{\nabla}f(x_{t-1}, y_{t-1}; \bar{\xi}_t)$$
$$- (\bar{\nabla}f(x_t, y_t) + B_t - \bar{\nabla}f(x_{t-1}, y_{t-1}) - B_{t-1})\} + \eta_t^f(\bar{\nabla}f(x_t, y_t; \bar{\xi}_t) - \bar{\nabla}f(x_t, y_t) - B_t).$$

Lemma 3.1 allows us to control the variance of the second term in the above relation as $\mathcal{O}(\alpha_t^2\|h_{t-1}^f\|^2 + \beta_t^2\|h_{t-1}^g\|^2)$. This subsequently leads to a reduced error magnitude for $\mathbb{E}[\|e_t^f\|^2]$. Similarly, we can show a reduced error magnitude for $\mathbb{E}[\|e_t^g\|^2]$ for the inner gradient estimate.

The above discussion suggests that we can track the gradient $\nabla\ell(x)$ using only stochastic gradient estimates (7), without needing to track each component stochastic vectors/matrices. This allows us to avoid costly Hessian inversions. In contrast, [5, 17] track the individual stochastic vectors/matrices of (7), and then combine them together to yield an estimate of $\nabla\ell(x)$. This approach is unable to utilize the cheap stochastic estimates of Hessian and have to invert it directly.

Turning back to the convergence analysis of the SUSTAIN algorithm, the main idea of our analysis is to demonstrate reduction of a properly constructed potential function across iterations. For smooth (possibly non-convex) objective function, this potential function consists of a linear combination of the norms of the error terms $\mathbb{E}[\|e_t^f\|^2]$ and $\mathbb{E}[\|e_t^g\|^2]$ along with the outer objective function $\ell(x_t)$ and the inner optimality gap $\|y_t - y^*(x_t)\|^2$. We obtain:

Theorem 3.2. *Under Assumptions 1–4. Fix $T \geq 1$ as the maximum iteration number. Set the number of samples used for the gradient estimator in* (7) *as $K = (L_g/\mu_g)\log(C_{g_{xy}}C_{f_y}T/\mu_g)$ and*

$$\alpha_t = \frac{1}{(w + t)^{1/3}}, \quad \beta_t = c_\beta\alpha_t, \quad \eta_t^f = c_{\eta_f}\alpha_t^2, \quad \eta_t^g = c_{\eta_g}\alpha_t^2, \tag{17}$$

where $w, c_\beta, c_{\eta_f}, c_{\eta_g}$ are defined in (28) *of appendix. The iterates generated by Algorithm 1 satisfy*

$$\mathbb{E}\|\nabla\ell(x_{a(T)})\|^2 = \mathcal{O}\left(\frac{\ell(x_0) - \ell^*}{T^{2/3}} + \frac{\|y_0 - y^*(x_0)\|^2}{T^{2/3}} + \frac{\log(T)\sigma_f^2}{T^{2/3}} + \frac{\log(T)\sigma_g^2}{T^{2/3}}\right). \tag{18}$$

Details of the constants in the theorem and its proof can be found in Appendix D. The above result shows that to reach an ϵ-stationary point, the SUSTAIN algorithm requires $\tilde{\mathcal{O}}(\epsilon^{-3/2})$ (omitting logarithmic factors) samples of stochastic gradients from both the upper and lower level functions.

This sample complexity matches the best complexity bounds for single-level stochastic optimization like SPIDER [10], STORM [7], SNVRG [39] and Hybrid SGD [34]. We claim that this is a *near-optimal* sample complexity for bilevel stochastic optimization since for example, we have imposed additional smoothness conditions on the Hessian of the lower level problem. We will leave this as an open question to investigate the lower bound complexity for bilevel stochastic optimization.

Strongly-convex $\ell(x)$. We also discuss the case when in addition to smoothness, $\ell(\cdot)$ is μ_f-strongly-convex. Here, a stronger guarantee can be obtained:

Theorem 3.3. *Under Assumptions 1–4, and suppose $\ell(x)$ is μ_f-strongly-convex. Fix any $T \geq 1$, set the number of samples for the gradient estimator* (7) *as $K = (L_g/2\mu_g)\log(C_{g_{xy}}^2 C_{f_y}^2 T/\mu_g^2)$ and*

$$\alpha_t \equiv \alpha \leq \left\{\frac{1}{\mu_f + 1}, \frac{1}{2\mu_g\hat{c}_\beta}, \frac{\mu_g}{\hat{c}_\beta L_g^2}, \frac{1}{8L_K^2 + L_f}, \frac{L^2 + 2L_y^2}{4L_K^2 L_g^2 \hat{c}_\beta^2}\right\}, \quad \eta_t^f \equiv (\mu_f + 1)\alpha, \quad \beta_t \equiv \hat{c}_\beta\alpha,$$

where $\eta_t^g \equiv 1$, $\hat{c}_\beta = 8L_y^2 + 8L^2 + 2\mu_f/\mu_g$ and L_K is defined in (15). The iterates generated by Algorithm 1 satisfy for any $t \geq 1$ that:

$$\mathbb{E}[\ell(x_t) - \ell^*] \leq (1 - \mu_f \alpha)^t \bar{\Delta}_0 + \frac{1}{\mu_f}\Big\{\frac{2}{T} + \big[(2\hat{c}_\beta^2 + 8\hat{c}_\beta^2 L_K^2)\sigma_g^2 + 2(\mu_f + 1)^2 \sigma_f^2\big]\alpha\Big\}, \quad (19)$$

where $\bar{\Delta}_0 := \ell(x_0) - \ell^* + \sigma_f^2 + \|y_0 - y^*(x_0)\|^2$.

The detailed proof can be found in Appendix E. For large T, setting $\alpha \asymp 1/T$ shows that the bound in (19) decreases at the rate of $\mathcal{O}(1/T)$.

Theorem 3.3 shows that to reach an ϵ-optimal point, the SUSTAIN algorithm requires $\widetilde{\mathcal{O}}(\epsilon^{-1})$ stochastic gradient samples from the upper and lower level problems, also see the detailed calculations in Appendix E. This improves over TTSA [18] which requires $\widetilde{\mathcal{O}}(\epsilon^{-1.5})$ samples, and BSA [14] which requires $\widetilde{\mathcal{O}}(\epsilon^{-1})$, $\mathcal{O}(\epsilon^{-2})$ samples for the upper and lower level problems, respectively. Again, we achieve similar sample complexity as SGD applied on strongly-convex single-level optimization.

Interestingly, in Theorem 3.3, we have selected $\eta_t^g \equiv 1$ where the momentum term in the lower level gradient vanishes. In this way, the SUSTAIN algorithm is reduced into a *single-momentum* algorithm where the recursive momentum acceleration is only applied to the upper level gradient.

4   Numerical experiments

In this section, we evaluate the performance of the SUSTAIN algorithm on two popular machine learning tasks: hyperparameter optimization and meta learning.

Hyperparameter optimization.   We consider the data hyper-cleaning task (3), and compare SUSTAIN with several algorithms such as stocBiO [19] for different batch size choices, and the HOAG algorithm in [26]. Note that in [19], the authors shown that stocBio exhibits better practical performance compared with other bilevel optimization algorithms.

We consider problem (3) with $L(\cdot)$ being the cross-entropy loss (i.e., a data cleaning problem for logistic regression); $\sigma(x) := \frac{1}{1+\exp(-x)}$; $c = 0.001$; see [32]. The problem is trained on the FashionMNIST dataset [38] with 50k, 10k, and 10k image samples allocated for training, validation and testing purposes, respectively. The step sizes for different algorithms are chosen according to their theoretically suggested values. Let the outer iteration be indexed by t, for SUSTAIN we choose $\alpha_t = \beta_t = 0.1/(1+t)^{1/3}$ and tune for c_{η_f} and c_{η_g} (see Theorem 3.2), for stocBIO and HOAG we select $\alpha_t = d_\alpha$, $\beta_t = d_\beta$ and tune for parameters d_α and d_α in the range $[0, 1]$.

In Figure 1, we compare the performance of different algorithms when the dataset has a corruption probability of 0.3. As observed, SUSTAIN outperforms stocBiO and HOAG. We remark that HOAG is a deterministic algorithm and hence requires full batch gradient computations at each iteration. Similarly, stocBio relies on large batch gradients which results in relatively slow convergence. This fast convergence of SUSTAIN results form the single timescale update with reduced variance resulting from the double-momentum variance reduced updates.

Figure 1: **Hyperparameter optimization**: Data hyper-cleaning task on the FashionMNIST dataset. We plot the training loss and testing accuracy against the number of gradients evaluated with corruption rate $p = 0.3$.

Figure 2: **Meta learning**: 5-way 5-shot learning task on the `miniImageNet` dataset. We plot the training and testing accuracy against the number of iterations.

Meta learning. We consider a few-shot meta learning problem [11, 27] (cf. (2)) and compare the performance of SUSTAIN to ITD-BiO [19] and ANIL [27]. The task of interest is 5-way 5-shot learning and we conduct experiments on the `miniImageNet` dataset [36, 29] with 100 classes and 600 images per class. We apply `learn2learn` [1] (available: https://github.com/learnables/learn2learn) to partition the 100 classes from `miniImageNet` into subsets of 64, 16 and 20 for meta training, meta validation and meta testing, respectively. Similar to [1, 19], we implement a 4-layer convolutional neural network (CNN) with ReLU activation for the learning task. At each iteration, we sample a batch of 32 tasks from a set of 20000 tasks allocated for training and 600 each for validation and testing. For each algorithm, we implement 10 inner and 1 outer update. The performance is averaged over 10 Monte Carlo runs.

For ANIL and ITD-BiO, we use the parameter selection suggested in [1, 19]. Specifically, for ANIL, we use inner-loop stepsize of 0.1 and the outer-loop (meta) stepsize as 0.002. For ITD-BiO, we choose the inner-loop stepsize as 0.05 and the outer-loop stepsize to be 0.005. For SUSTAIN, we choose the outer-loop stepsize α_t as $\kappa/(1+t)^{1/3}$ and choose $\kappa \in [0.1, 1]$, we choose the momentum parameter η_t as $\bar{c}\alpha_t^2/\kappa^2$ and tune for $\bar{c} \in \{2, 5, 10, 15, 20\}$, finally, we fix the inner stepsize as 0.05. For the outer loop update ANIL and ITD-BiO utilize SGD optimizer whereas SUSTAIN uses the hybrid gradient estimator.

From Figure 2 which compares the training and testing accuracy against the iteration number, we observe that SUSTAIN achieves a better performance compared to ANIL and ITD-BiO on the meta learning task. Also, notice that in the initial iterations SUSTAIN converges faster but then converges probably as a consequence of diminishing stepsizes (and momentum parameter). In contrast, ANIL and ITD-BiO slowly improve in performance and catch up with SUSTAIN's performance. In the appendix, we show that the SUSTAIN algorithm requires less computation time to achieve better performance compared to the ANIL and ITD-BiO.

For further evaluation of the performance of SUSTAIN, we have included additional experiments on hyperparameter optimization and meta learning tasks on different datasets in the supplementary material.

Conclusions & limitations. We have developed the SUSTAIN algorithm for unconstrained bilevel optimization with strongly convex lower level subproblems. The proposed algorithm executes on a single-timescale, without the need to use either two-timescale updates, large batch gradients, or double-loop algorithm. We showed that SUSTAIN is both *sample* and *computation* efficient, because it matches the best-known sample complexity guarantees on single-level problems with non-convex and strongly convex objective functions, while matching the best-known per-iteration computational complexity for the same class of bi-level problems. In the future, we plan to rigorously show the sample complexity lower bound for the considered class of bilevel problems. Further, we plan to develop sample and communication efficient algorithms for a more general class of bilevel problems, such as those with constraints in the lower level problem.

References

[1] S. M. R. Arnold, P. Mahajan, D. Datta, I. Bunner, and K. S. Zarkias. learn2learn: A library for Meta-Learning research. Aug. 2020. URL http://arxiv.org/abs/2008.12284.

[2] J. Bracken and J. T. McGill. Mathematical programs with optimization problems in the constraints. *Operations Research*, 21(1):37–44, 1973. ISSN 0030364X, 15265463.

[3] J. Bracken and J. T. McGill. Defense applications of mathematical programs with optimization problems in the constraints. *Operations Research*, 22(5):1086–1096, 1974. ISSN 0030364X, 15265463. URL http://www.jstor.org/stable/169661.

[4] J. Bracken, J. E. Falk, and J. T. McGill. Technical note—the equivalence of two mathematical programs with optimization problems in the constraints. *Operations Research*, 22(5):1102–1104, 1974. doi: 10.1287/opre.22.5.1102.

[5] T. Chen, Y. Sun, and W. Yin. A single-timescale stochastic bilevel optimization method. *arXiv preprint arXiv:2102.04671*, 2021.

[6] B. Colson, P. Marcotte, and G. Savard. An overview of bilevel optimization. *Annals of Operations Research*, 153:235–256, 2007.

[7] A. Cutkosky and F. Orabona. Momentum-based variance reduction in non-convex SGD. In *Advances in Neural Information Processing Systems 32*, pages 15236–15245. Curran Associates, Inc., 2019.

[8] S. Dempe. *Foundations of bilevel programming*. Springer Science & Business Media, 2002.

[9] J. E. Falk and J. Liu. On bilevel programming, part I: General nonlinear cases. *Mathematical Programming volume*, 70:47–72, 1995.

[10] C. Fang, C. J. Li, Z. Lin, and T. Zhang. Spider: Near-optimal non-convex optimization via stochastic path-integrated differential estimator. In *Advances in Neural Information Processing Systems*, pages 689–699, 2018.

[11] C. Finn, P. Abbeel, and S. Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pages 1126–1135. JMLR. org, 2017.

[12] L. Franceschi, M. Donini, P. Frasconi, and M. Pontil. Forward and reverse gradient-based hyperparameter optimization. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, page 1165–1173, 2017.

[13] L. Franceschi, P. Frasconi, S. Salzo, R. Grazzi, and M. Pontil. Bilevel programming for hyperparameter optimization and meta-learning. *arXiv preprint arXiv:1806.04910*, 2018.

[14] S. Ghadimi and M. Wang. Approximation methods for bilevel programming, 2018.

[15] R. Grazzi, L. Franceschi, M. Pontil, and S. Salzo. On the iteration complexity of hypergradient computation, 2020.

[16] R. Grazzi, M. Pontil, and S. Salzo. Convergence properties of stochastic hypergradients, 2020.

[17] Z. Guo and T. Yang. Randomized stochastic variance-reduced methods for stochastic bilevel optimization, 2021.

[18] M. Hong, H.-T. Wai, Z. Wang, and Z. Yang. A two-timescale framework for bilevel optimization: Complexity analysis and application to actor-critic, 2020.

[19] K. Ji, J. Yang, and Y. Liang. Bilevel optimization: Nonasymptotic analysis and faster algorithms, 2020.

[20] V. R. Konda and J. N. Tsitsiklis. Actor-critic algorithms. In *Advances in neural information processing systems*, pages 1008–1014, 2000.

[21] J. Li, B. Gu, and H. Huang. Improved bilevel model: Fast and optimal algorithm with theoretical guarantee, 2020.

[22] R. Liu, P. Mu, X. Yuan, S. Zeng, and J. Zhang. A generic first-order algorithmic framework for bi-level programming beyond lower-level singleton, 2020.

[23] R. Liu, J. Gao, J. Zhang, D. Meng, and Z. Lin. Investigating bi-level optimization for learning and vision from a unified perspective: A survey and beyond, 2021.

[24] Z.-Q. Luo, J.-S. Pang, and D. Ralph. *Mathematical Programs with Equilibrium Constraints*. Cambridge University Press, 1996. doi: 10.1017/CBO9780511983658.

[25] A. Migdalas, P. M. Pardalos, and P. Värbrand. *Multilevel optimization: algorithms and applications*, volume 20. Springer Science & Business Media, 2013.

[26] F. Pedregosa. Hyperparameter optimization with approximate gradient. In *International conference on machine learning*, pages 737–746. PMLR, 2016.

[27] A. Raghu, M. Raghu, S. Bengio, and O. Vinyals. Rapid learning or feature reuse? towards understanding the effectiveness of maml. In *ICLR*, 2019.

[28] A. Rajeswaran, C. Finn, S. M. Kakade, and S. Levine. Meta-learning with implicit gradients. In *Advances in Neural Information Processing Systems*, volume 32, pages 113–124. Curran Associates, Inc., 2019.

[29] S. Ravi and H. Larochelle. Optimization as a model for few-shot learning. 2016.

[30] W. Rudin. *Principles of mathematical analysis*. McGraw-Hill New York, 3d ed. edition, 1976. ISBN 007054235.

[31] S. Sabach and S. Shtern. A first order method for solving convex bilevel optimization problems. *SIAM J. Optim.*, 27(2):640–660, 2017. doi: 10.1137/16M105592X. URL https://doi.org/10.1137/16M105592X.

[32] A. Shaban, C.-A. Cheng, N. Hatch, and B. Boots. Truncated back-propagation for bilevel optimization, 2019.

[33] H. V. Stackelberg. *The Theory of Market Economy*. Oxford University Press, 1952.

[34] Q. Tran-Dinh, N. H. Pham, D. T. Phan, and L. M. Nguyen. Hybrid stochastic gradient descent algorithms for stochastic nonconvex optimization. *arXiv preprint arXiv:1905.05920*, 2019.

[35] L. Vicente, , G. Savard, and J. Júdice. Descent approaches for quadratic bilevel programming. *Journal of Optimization Theory and Applications*, pages 379–399, 1994.

[36] O. Vinyals, C. Blundell, T. Lillicrap, k. kavukcuoglu, and D. Wierstra. Matching networks for one shot learning. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/90e1357833654983612fb05e3ec9148c-Paper.pdf.

[37] D. J. White and G. Anandalingam. A penalty function approach for solving bi-level linear programs. *Journal of Global Optimization*, 3:397–419, 1993.

[38] H. Xiao, K. Rasul, and R. Vollgraf. Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms, 2017.

[39] D. Zhou, P. Xu, and Q. Gu. Stochastic nested variance reduction for nonconvex optimization. *arXiv preprint arXiv:1806.07811*, 2018.