# Generalized Laplacian Eigenmaps

**Hao Zhu**[†,§]    **Piotr Koniusz** [∗,§,†]
[§]Data61/CSIRO   [†]Australian National University
allenhaozhu@gmail.com, piotr.koniusz@data61.csiro.au

## Abstract

Graph contrastive learning attracts/disperses node representations for similar/dissimilar node pairs under some notion of similarity. It may be combined with a low-dimensional embedding of nodes to preserve intrinsic and structural properties of a graph. COLES, a recent graph contrastive method combines traditional graph embedding and negative sampling into one framework. COLES in fact minimizes the trace difference between the within-class scatter matrix encapsulating the graph connectivity and the total scatter matrix encapsulating negative sampling. In this paper, we propose a more essential framework for graph embedding, called Generalized Laplacian EigeNmaps (GLEN), which learns a graph representation by maximizing the rank difference between the total scatter matrix and the within-class scatter matrix, resulting in the minimum class separation guarantee. However, the rank difference minimization is an NP-hard problem. Thus, we replace the trace difference that corresponds to the difference of nuclear norms by the difference of LogDet expressions, which we argue is a more accurate surrogate for the NP-hard rank difference than the trace difference. We show that the LogDet loss can be interpreted as an upper bound of the Jensen-Bregman LogDet Divergence (JBLD), and the Affine-invariant Riemannian metric (AIRM) while enjoying a lesser computational burden. We show on popular benchmarks/backbones that GLEN offers favourable accuracy/scalability compared to state-of-the-art baselines.

## 1   Introduction

Laplacian Eigenmaps [3] and IsoMap [32] are graph embedding methods that reduce the dimensionality of data by assuming the data exists on a low-dimensional manifold. The objective function in such models encourages node embeddings to lie near each other in the embedding space if nodes are close to each other in the original space. While the classical methods capture the related node pairs, they neglect modeling unrelated node pairs.

In contrast, modern graph embedding models such as [31, 9, 39] and Graph Contrastive Learning (GCL) [33, 52, 10, 53, 51] are unified under the (Sampled) Noise Contrastive Estimation framework, called (Sampled)NCE [26, 22]. Most of GCL methods do not incorporate the graph information into the loss but follow the setting from computer vision, *i.e.*, they assume that randomly drawn pairs should be dissimilar, whereas the original sample and its augmentations should be similar [35]. In contrast, COntrastive Laplacian EigenmapS (COLES) [51] is a framework which combines a (graph) neural network with Laplacian eigenmaps utilizing the graph Laplacian matrix within a contrastive loss. Based on the NCE framework, COLES minimizes the trace difference of Laplacians.

In this paper, we analyze the relation among within-class, between-class and total scatter matrices under the rank inequality, and prove that, under a simple assumption, the distance between any dissimilar (negative) samples would be greater/equal than the inter-class distance between their corresponding class centers. Based on such a condition, we derive GLEN, a reformulation of graph embedding into a rank difference problem, which is a more general framework than other graph

---

[∗]The corresponding author.    Code: `https://github.com/allenhaozhu/GLEN`.

36th Conference on Neural Information Processing Systems (NeurIPS 2022).

embedding frameworks, *i.e.*, under specific relaxations of the rank difference problem, we can recover different frameworks.To that end, we demonstrate how to optimize the rank difference problem with a difference of LogDet expressions, a differentiable relaxation suitable for use with (graph) neural networks. We consider other surrogates of the rank difference problem, based on the Nuclear norm, $\gamma$-nuclear norm, Schatten norm, and the Geman norm. Moreover, we provide theoretical considerations regarding the low-rank optimization and connection to the Riemannian manifold in order to interpret our approach.

In summary, our contributions are threefold:

i. We propose a rank-based condition connecting within-class, between-class and total scatter matrices under which we provide the minimum class separation guarantee. We propose a loss function, Generalized Laplacian EigenNaps (GLEN), that realizes this condition.

ii. As the rank difference problem is NP-hard, we consider a difference of LogDet surrogate to learn node embeddings, as opposed to the trace difference (an upper bound of the difference of LogDet terms) used by other graph embedding models. We also consider other surrogates.

iii. We study the distance between Symmetric Positive Definite (SPD) matrices realized by the LogDet-based implementation of GLEN which is lower-bounded by Jesen-Bregman LogDet Divergence (JBLD) and the Affine-invariant Riemmanian Metric (AIRM). We also explain how GLEN connects to other graph embedding methods.

## 2 Related Works

**Graph Embeddings.** By assuming that the data lies on a low-dimensional manifold, graph embedding methods such as Laplacian Eigenmaps [3] and IsoMap [32] optimize low-dimensional data embeddings. These methods [5] construct a similarity graph by measuring the similarity of high-dimensional feature vectors and embed the nodes into a low-dimensional space.

DeepWalk [28] uses truncated random walks to explore the graph structure, and the skip-gram model for word embedding to determine the embedding vectors of nodes. By setting the walk length to one and using negative sampling [25], LINE [31] explores a similar idea with an explicit objective function while REFINE [48] imposes additional orthogonality constraints which deem REFINE extremely fast. Node2Vec [8] interpolates between breadth- and depth-first sampling. COLES [51] unifies traditional graph embedding and negative sampling by introducing a positive contrastive term that captures the graph structure, and a negative contrastive random sampling. COLES solves the trace difference problem akin to traditional graph embedding models [38].

In this paper, we propose a more general loss for graph embedding, *i.e.*, COLES solves the trace difference (Nuclear norms difference) relaxation of GLEN.

Graph embedding techniques [38] provide a general framework for dimensionality reduction such as Principal Component Analysis (PCA), Linear Discriminant Analysis (LDA), and Locality Preserving Projections (LPP) [11]. All methods within this category can be considered as solving the same problem under varying assumptions, *i.e.*, maximising the intra- and inter-class separation by optimizing the trace difference, also used in metric learning [20]. However, such a family of objective functions is not motivated by the guarantee on the minimum class separation between feature vectors from different categories. GLEN, in its purest NP-hard form, provides the minimum class separation guarantee and can be realised by several formulations depending on chosen trade-offs.

**Unsupervised Representation Learning for Graph Neural Networks (GNN).** Unsupervised GNN training can be reconstruction-, contrastive- or diffusion-based. To train a graph encoder in an unsupervised manner, GCN [16] minimizes a reconstruction error which only considers the similarity matrix and ignores the dissimilarity information. At various scales of the graph, contrastive methods determine the positive and negative sets. For example, local-local CL and global-local CL strategies are highly popular. GraphSAGE [9], inspired by DeepWalk [28], uses the contrastive loss which encourages neighbor nodes to have similar representations, while preserving dissimilarity between representations of disparate nodes. DGI [33], inspired by Deep InfoMax (DIM) [12], uses an objective with global-local sampling strategy to maximize the Mutual Information (MI) between global and local graph embeddings. Augmented Multiscale Deep InfoMax (AMDIM) [2] maximizes MI between multiple data views. MVRLG [10] contrasts encodings from first-order neighbors and a graph diffusion. Fisher-Bures Adversary GCN [30] treats the graph as generated w.r.t. some observation noise. COSTA [46] constructs the views by injecting features with the random noise.

(a) $\text{Rank}(S_b) = 0$          (b) $\text{Rank}(S_b) = 1$          (c) $\text{Rank}(s_b) = 2$

Figure 1: Three cases under our Condition 1, *i.e.*, $\text{Rank}(\mathbf{S}_t) = \text{Rank}(\mathbf{S}_w) + \text{Rank}(\mathbf{S}_b)$. The red line and plane indicate the space of class centers. The black dots represent class centers. Other colored lines or ellipses represent the spaces of different categories. We show a non-exhaustive set of cases.

However, such contrastive approaches often require thousands of epochs to converge and perform well. In addition, many contrastive losses have an exponential increase in memory overhead w.r.t. the number of nodes. In contrast, our method does not explicitly use the local-local setting but the total scatter matrix, and thus saves computational and storage cost.

Linear GNNs, *i.e.*, SGC [37] and S²GC [49], capture the neighborhood and increasingly larger neighborhoods of each node due to the diffusion, respectively. SGC and S²GC have no projection layer, thus the size of embeddings is equal to the input dimension. GLEN can learn a projection layer in an unsupervised manner with a linear function or Multi-Layer Perceptron (MLP) applied to linear GNNs or any other GNN models [17, 30, 45], *etc.*

## 3 Preliminaries

**Notations.** Let $G = (V, E)$ be a simple, connected and undirected graph with $n = |V|$ nodes and $m = |E|$ edges. Let $i \in \{1, \cdots, n\}$ be the node index of $G$, and $d_j$ be the degree of node $j$ of $G$. Let $\mathbf{W}$ be the adjacency matrix, and $\mathbf{D}$ be the diagonal matrix containing degrees of nodes. Let $\mathbf{X} \in \mathbb{R}^{n \times d}$ denote the node feature matrix where each node $v$ is associated with a feature vector $\mathbf{x}_v \in \mathbb{R}^d$. Let the normalized graph Laplacian matrix be defined as $\mathbf{L} = \mathbf{I} - \tilde{\mathbf{W}} \in \mathbb{S}_+^n$, a symmetric positive semi-definite matrix and $\tilde{\mathbf{W}} = \mathbf{D}^{-1/2}\mathbf{W}\mathbf{D}^{-1/2}$. $\mathbb{S}_{+(+)}^m$ is a set of symmetric positive (semi-)definite matrices. Let $\mathbf{Z} = f_{\boldsymbol{\Theta}}(\mathbf{X}) \in \mathbb{R}^{n \times m}$ be a generalized node embedding, *i.e.*, $\mathbf{X}$ could be identity matrix (*e.g.*, no node attributes), $f_{\boldsymbol{\Theta}}(\mathbf{X})$ could be GNN or a linear function with parameters $\boldsymbol{\Theta}$. Scalars/vectors/matrices are denoted by lowercase regular/lowercase bold/uppercase bold fonts.

### 3.1 Scatter Matrices

Below are given standard definitions of scatter matrices, including the total scatter matrix $\mathbf{S}_t \in \mathbb{S}_{+(+)}^m$, the within-class matrix $\mathbf{S}_w \in \mathbb{S}_{+(+)}^m$, and between-class matrix $\mathbf{S}_b \in \mathbb{S}_{+(+)}^m$:

$$\mathbf{S}_t = \sum_{i=1}^n (\mathbf{z}_i - \bar{\mathbf{z}})(\mathbf{z}_i - \bar{\mathbf{z}})^\top = \mathbf{Z}^\top(\mathbf{I} - \tilde{\mathbf{W}}_t)\mathbf{Z} \qquad \text{where} \quad \tilde{\mathbf{W}}_t = \frac{1}{n}\mathbf{e}\mathbf{e}^\top,$$

$$\mathbf{S}_w = \sum_{i=1}^n (\mathbf{z}_i - \boldsymbol{\mu}_{y_i})(\mathbf{z}_i - \boldsymbol{\mu}_{y_i})^\top = \mathbf{Z}^\top(\mathbf{I} - \tilde{\mathbf{W}}_w)\mathbf{Z} \quad \text{where} \quad \tilde{\mathbf{W}}_w = \sum_{c=1}^C \frac{1}{n_c}\mathbf{e}^c\mathbf{e}^{c\top},$$

$$\mathbf{S}_b = \sum_{c=1}^C n_c (\boldsymbol{\mu}_c - \bar{\mathbf{z}})(\boldsymbol{\mu}_c - \bar{\mathbf{z}})^\top. \tag{1}$$

Let $\mathbf{e}$ be an $n$-dimensional vector with all coefficients equal one, $\mathbf{I}$ be an identity matrix, $\mathbf{S}_t$ be the total scatter (covariance) matrix, and $\bar{\mathbf{z}} \in \mathbb{R}^m$ be the mean of all samples. Let $\boldsymbol{\mu}_{y_i} \in \mathbb{R}^m$ be the class center of the $i$-th sample and $\boldsymbol{\mu}_c \in \mathbb{R}^m$ be the $c$-th class center. Let the total number of categories be given by $C$, whereas $n_c$ be the number of samples for the $c$-th category. Let $\mathbf{e}^c \in \mathbb{R}^n$ be a vector where a given coefficient indexed by node is equal one if its node is of class $c$, otherwise it is equal zero. We note that both $\mathbf{S}_t$ and $\mathbf{S}_w$ can take a form akin to Laplacian eigenmaps such that $\tilde{\mathbf{W}}_t$ and $\tilde{\mathbf{W}}_w$ are the corresponding normalized adjacent matrices. Let us also define graph Laplacian matrices

$\mathbf{L}_t = \mathbf{I} - \tilde{\mathbf{W}}_t \in \mathbb{S}_+^n$ and $\mathbf{L}_w = \mathbf{I} - \tilde{\mathbf{W}}_w \in \mathbb{S}_+^n$ which will be used in the sequel. Importantly, let us assume that a graph Laplacian matrix $\mathbf{L}$ containing graph links could be seen as a noisy version of $\mathbf{L}_w$ in which all nodes of a given class $c$ connect under the weight equal $1/n_c$.

Observe that $\mathbf{S}_t = \mathbf{S}_w + \mathbf{S}_b$. Thus, $\mathrm{Rank}(\mathbf{S}_t) \leq \mathrm{Rank}(\mathbf{S}_w) + \mathrm{Rank}(\mathbf{S}_b)$ due to the rank inequality. Below we highlight the condition underpinning the subsequent motivation:

**Condition 1.** $\mathrm{Rank}(\mathbf{S}_t) = \mathrm{Rank}(\mathbf{S}_w) + \mathrm{Rank}(\mathbf{S}_b)$.

### 3.2 Motivation

Figure 1 shows some three optimal solutions for Condition 1. The rank of between-class scatter matrix $\mathbf{S}_b$ for the whole dataset is at most $C - 1$ (where $C$ is the number of classes). Since $\mathrm{Rank}(AB) \leq \min(\mathrm{Rank}(A), \mathrm{Rank}(B))$, we have[†] $\mathrm{Rank}(\mathbf{S}_w^{-1}\mathbf{S}_b) \leq \mathrm{Rank}(\mathbf{S}_b) \leq C - 1$. The rank is the number of non-zero eigenvalues of a matrix so $\mathbf{S}_w^{-1}\mathbf{S}_b$ has at most $C - 1$ non-zero eigenvalues. Condition 1 implies that $\mathrm{Rank}(\mathbf{S}_w^{-1}\mathbf{S}_b) = 0$ results in the minimum class separation guarantee under that condition.

**Theorem 1.** *Let the feature dimension be larger than the class number (i.e., $m > C$) and Condition 1 hold. Then, the minimum class separation is equal to the distance between class centers. In other words, the distance between any two vectors $\mathbf{z}_i$ and $\mathbf{z}_j$ with labels $y_i \neq y_j$ is greater/equal the distance between class centers $\boldsymbol{\mu}_{y_i}$ and $\boldsymbol{\mu}_{y_j}$:*

$$\|\boldsymbol{\mu}_{y_i} - \boldsymbol{\mu}_{y_j}\|_2 \leq \|\mathbf{z}_i - \mathbf{z}_j\|_2, \ \forall y_i \neq y_j, \ i,j \in \{1, \cdots, C\}. \tag{2}$$

*Proof.* As $\mathbf{S}_w$ is the orthogonal complement of $\mathbf{S}_b$, *i.e.*, $\mathbf{S}_w^{-1}\mathbf{S}_b = \mathbf{0}$, $\mathbf{S}_w + \mathbf{S}_b = \mathbf{U}\boldsymbol{\Sigma}\mathbf{U}^\top$, $\mathbf{S}_w = \mathbf{U}_{1:k}\boldsymbol{\Sigma}_{1:k}\mathbf{U}_{1:k}^\top$ and $\mathbf{S}_b = \mathbf{U}_{k+1:m}\boldsymbol{\Sigma}_{k+1:m}\mathbf{U}_{k+1:m}^\top$ where $1 \leq k < m$. Let $\mathbf{z}_i = \boldsymbol{\mu}_{y_i} + \mathbf{U}^\top \boldsymbol{\epsilon}_i$ where $\boldsymbol{\epsilon}_i$ is the representation under the basis $\mathbf{U}$ and $\boldsymbol{\epsilon}_{(k+1:m),i} = \mathbf{0}$ because only top k components $1:k$ represent $\mathbf{S}_w$. Thus, the orthogonal projection $\mathbf{U}_{k+1:m}$ fulfills $\|\mathbf{U}_{k+1:m}(\mathbf{z}_i - \mathbf{z}_j)\|_2 \leq \|\mathbf{z}_i - \mathbf{z}_j\|_2$. Moreover, $\mathbf{U}_{k+1:m}(\mathbf{z}_i - \boldsymbol{\mu}_{y_i}) = \mathbf{U}_{k+1:m}(\mathbf{U}^\top \boldsymbol{\epsilon}_i) = 0$. That is, all $\{\mathbf{z}_i : y_i = c\}$ are projected onto the mean $\boldsymbol{\mu}_c$. Thus, the inequality in Eq. 2 holds. $\square$

Theorem 1 guarantees the worst inter-class distance[§]. Figure 1 shows some cases that meet Condition 1. Figure 1a shows the case for which the class centers collapse to a single point and thus the inter-class distance equals zero (collapse of the feature space). Figures 1b and 1c show other cases.

## 4 Methodology

Condition 1 points to a promising research direction in learning discriminative feature spaces. However, optimizing over the rank is NP-hard and non-differentiable. In what follows, we provide the formulation of Generalized Laplacian EigeNmaps (GLEN) and its relaxation, which is differentiable.

### 4.1 Generalized Laplacian Eigenmaps

As solving Condition 1 is NP-hard, we propose a relaxation where $\mathrm{Rank}(\mathbf{S}_t)$ is encouraged to be as large as possible (bounded by the feature dimension $m$). On the contrary, if $\mathrm{Rank}(\mathbf{S}_t) \approx \mathrm{Rank}(\mathbf{S}_b)$ then the small $\mathrm{Rank}(\mathbf{S}_w)$ limits the feature diversity. In the extreme case, if $\mathrm{Rank}(\mathbf{S}_w) = 0$, the feature representation collapses. Larger $0 < \mathrm{Rank}(\mathbf{S}_b) \leq C - 1$ improves the inter-class diversity.

> We propose a new **Generalized Laplacian EigeNmaps (GLEN)** framework for unsupervised network embedding. In the most general form, GLEN maximizes the difference of rank terms:
> $$\boldsymbol{\Theta}^* = \arg\max_{\boldsymbol{\Theta}} \ \mathrm{Rank}\big(\mathbf{S}_t\big(f_{\boldsymbol{\Theta}}(\mathbf{X})\big)\big) - \mathrm{Rank}\big(\mathbf{S}_w\big(f_{\boldsymbol{\Theta}}(\mathbf{X})\big)\big). \tag{3}$$

However, the general matrix Rank Minimization Problem (RMP) [7] is NP-hard and the difference of rank terms in Eq. 3 is even harder to solve. Thus, we relax this problem by the difference of LogDet terms that serve as a surrogate of the NP-hard problem.

---

[†]We write $\mathbf{S}_w^{-1}$ but if $\mathbf{S}_w$ is rank-deficient, $^{-1}$ is replaced with the Moore–Penrose inverse (pseudo-inverse).
[§]Other graph embedding models that maximize/minimize inter-/intra-class distances have no such guarantees.

> **GLEN (LogDet relaxation).**
>
> I. Define:
> $$\delta_{rf}(\mathbf{S}_t, \mathbf{S}_w; \alpha) = \log\det(\mathbf{I} + \alpha\mathbf{S}_t) - \lambda\log\det(\mathbf{I} + \alpha\mathbf{S}_w), \quad (4)$$
> where $\lambda \geq 0$ controls the impact of $\log\det(\mathbf{S}_w)$. If $\lambda = 0$, $\delta_{rf}$ encourages $\mathrm{Rank}(f_\Theta(\mathbf{X})) = m$.
>
> II. Let $\mathbf{S}_t = f_\Theta(\mathbf{X})^\top \mathbf{L}_t f_\Theta(\mathbf{X})$ and $\mathbf{S}_w = f_\Theta(\mathbf{X})^\top \mathbf{L}_w f_\Theta(\mathbf{X})$. Then the LogDet relaxation becomes:
> $$\Theta^* = \arg\max_\Theta \ \log\det\left(\mathbf{I} + \alpha f_\Theta(\mathbf{X})^\top \mathbf{L}_t f_\Theta(\mathbf{X})\right) - \log\det\left(\mathbf{I} + \alpha f_\Theta(\mathbf{X})^\top \mathbf{L}_w f_\Theta(\mathbf{X})\right), \quad (5)$$
> where $\mathbf{I}$ ensures $\mathbf{I} + \alpha f_\Theta(\mathbf{X})^\top \mathbf{L} f_\Theta(\mathbf{X}) > 0$ as $f_\Theta(\mathbf{X})^\top \mathbf{L} f_\Theta(\mathbf{X})$ may be $\mathbb{S}_+^m$ leading to $\det(f_\Theta(\mathbf{X})^\top \mathbf{L} f_\Theta(\mathbf{X})) = 0$. Thus, we use $\log\det(\mathbf{I} + \alpha\mathbf{Y})$ as a smooth surrogate for $\mathrm{Rank}(\mathbf{Y})$.

**Proposition 1.** *Let $\sigma(\mathbf{X})$ be the vector of eigenvalues of SPD matrix $\mathbf{X}$, and $\mathrm{Eig}(\mathbf{X})$ be a diagonal matrix with $\sigma(\mathbf{X})$ as its diagonal. Let $\mathbf{X}, \mathbf{X}' \in \mathbb{S}_{++}^m$, and $\alpha > 0$. Then, $\delta_{rf}(\mathbf{X}, \mathbf{X}'; \alpha) = \delta_{rf}(\mathrm{Eig}(\mathbf{X}), \mathrm{Eig}(\mathbf{X}'); \alpha)$, i.e., $\delta_{rf}(\cdot)$ depends on eigenvalues rather than eigenvectors of $\mathbf{X}$ and $\mathbf{X}'$.*

*Proof.* The proof follows from the equality $\det(\mathbf{I} + \alpha\mathbf{X}) = \prod_i \sigma_i(\mathbf{I} + \alpha\mathbf{X}) = \prod_i (1 + \alpha\sigma_i(\mathbf{X})) = \det(\mathbf{I} + \alpha\,\mathrm{Eig}(\mathbf{X}))$. Thus $\delta_{rf}(\mathbf{X}, \mathbf{X}'; \alpha) = \log\det(\mathbf{I} + \alpha\mathbf{X}) - \lambda\log\det(\mathbf{I} + \alpha\mathbf{X}') = \log\det(\mathbf{I} + \alpha\,\mathrm{Eig}(\mathbf{X})) - \lambda\log\det(\mathbf{I} + \alpha\,\mathrm{Eig}(\mathbf{X}')) = \delta_{rf}(\mathrm{Eig}(\mathbf{X}), \mathrm{Eig}(\mathbf{X}'); \alpha)$. □

# 5 Theoretical Analysis

Below, we demonstrate the comparison between our approach and other methods by looking at (i) the low-rank optimization and (ii) the non-Euclidean distances between SPD matrices.

## 5.1 Nuclear Norm *vs*. LogDet for Rank Minimization

**Claim 1.** *COLES [51] is a convex relaxation (using the nuclear norm) of the rank difference in Eq. 3:*

$$\Theta^* = \arg\max_\Theta \mathrm{Tr}\left(f_\Theta(\mathbf{X})^\top \mathbf{L}_t f_\Theta(\mathbf{X})\right) - \lambda\,\mathrm{Tr}\left(f_\Theta(\mathbf{X})^\top \mathbf{L}_w f_\Theta(\mathbf{X})\right) \quad s.t. \ \Omega(f_\Theta(\mathbf{X})) = B, \quad (6)$$

*where* $\mathrm{Tr}\left(f_\Theta(\mathbf{X})^\top \mathbf{L}_t f_\Theta(\mathbf{X})\right) = \|\mathbf{S}_t\|_*$ *and* $\mathrm{Tr}\left(f_\Theta(\mathbf{X})^\top \mathbf{L}_w f_\Theta(\mathbf{X})\right) = \|\mathbf{S}_w\|_*$.

The nuclear norm $\|\cdot\|_*$ can be regarded as the $\ell_1$ norm over singular values. As the $\ell_1$ norm induces sparsity, the nuclear norm encourages sparse singular values leading to low-rank solutions. If $f_\Theta(\mathbf{X})^\top f_\Theta(\mathbf{X})$ is restricted to be diagonal, $\|f_\Theta(\mathbf{X})^\top f_\Theta(\mathbf{X})\|_* = \|\mathrm{Diag}\left(f_\Theta(\mathbf{X})^\top f_\Theta(\mathbf{X})\right)\|_1$ and the nuclear norm surrogate for the rank minimization reduces to the $\ell_1$ norm surrogate for the cardinality (rank) minimization. However, for the $m$-dimensional embedding, the solution of trace difference lies on a subspace of dimension less than $m - 1$ [3]. Thus, the constraint $\Omega(f_\Theta(\mathbf{X})) = B$ prevents the dimensional collapse, *i.e.*, $f_\Theta(\mathbf{X})^\top f_\Theta(\mathbf{X}) = \mathbf{I}$.

Compared with the trace-based relaxation, LogDet is more suitable for cardinality minimization as it is less sensitive to large singular values. Also, the difference of LogDet terms does not require decorrelation of features to prevent the dimensional collapse. We discuss this matter in the supplementary material. In our case, the difference of LogDet terms is always bounded by the difference of trace terms as follows.

**Proposition 2.** *Given an embedding matrix $f_\Theta(\mathbf{X}) \in \mathbb{R}^{n \times m}$, a fixed small constant $\alpha > 0$, we have the following inequality:*
$$\log\det(\mathbf{I} + \alpha\mathbf{S}_t) - \log\det(\mathbf{I} + \alpha\mathbf{S}_w) < \alpha\,\mathrm{Tr}(\mathbf{S}_t - \mathbf{S}_w). \quad (7)$$

*Proof.*
$$\begin{aligned} \log\det(\mathbf{I} + \alpha\mathbf{S}_t) - \log\det(\mathbf{I} + \alpha\mathbf{S}_w) &= \log\det(\mathbf{I} + \alpha\,\mathrm{Eig}(\mathbf{S}_t)) - \log\det(\mathbf{I} + \alpha\,\mathrm{Eig}(\mathbf{S}_w)) \\ &= \mathrm{Tr}\left(\log(\mathbf{I} + \alpha\,\mathrm{Eig}(\mathbf{S}_t)) - \log(\mathbf{I} + \alpha\,\mathrm{Eig}(\mathbf{S}_w))\right) < \alpha\,\mathrm{Tr}(\mathbf{S}_t - \mathbf{S}_w). \end{aligned} \quad (8)$$

□

Proposition 2 follows $\mathrm{Rank}(\mathbf{Y}) \leq \log\det(\mathbf{I} + \mathbf{Y}) \leq \mathrm{Tr}(\mathbf{Y})$ [7].

## 5.2 Distance between Positive Definite Matrices

Below, we provide a perspective on non-Euclidean distances between SPD matrices to compare the proposed method with other graph embeddings, *e.g.*, Laplacian Eigenmaps [3] and COLES [51]. For the sake of comparison, we reformulate the Laplacian eigenmaps and COLES into forms in Prop. 3 and 4.

**Proposition 3.** *Laplacian Eigenmaps [3] equals to maximizing the Frobenius norm:*

$$\boldsymbol{\Theta}^* = \arg\max_{\boldsymbol{\Theta}} \|f_{\boldsymbol{\Theta}}(\mathbf{X})f_{\boldsymbol{\Theta}}(\mathbf{X})^\top - \mathbf{L}_w\|_F^2 \quad s.t. \quad f_{\boldsymbol{\Theta}}(\mathbf{X})^\top f_{\boldsymbol{\Theta}}(\mathbf{X}) = \mathbf{I}. \tag{9}$$

**Proposition 4.** *Contrastive Laplacian Eigenmaps [51] equals to maximizing the difference of Frobenius norm terms:*

$$\boldsymbol{\Theta}^* = \arg\max_{\boldsymbol{\Theta}} \|f_{\boldsymbol{\Theta}}(\mathbf{X})f_{\boldsymbol{\Theta}}(\mathbf{X})^\top - \mathbf{L}_w\|_F^2 - \|f_{\boldsymbol{\Theta}}(\mathbf{X})f_{\boldsymbol{\Theta}}(\mathbf{X})^\top - \mathbf{L}_t\|_F^2 \ s.t. \ f_{\boldsymbol{\Theta}}(\mathbf{X})^\top f_{\boldsymbol{\Theta}}(\mathbf{X}) = \mathbf{I}. \tag{10}$$

*Proof.*

$$\|f_{\boldsymbol{\Theta}}(\mathbf{X})f_{\boldsymbol{\Theta}}(\mathbf{X})^\top - \mathbf{L}\|_F^2 = \mathrm{Tr}(f_{\boldsymbol{\Theta}}(\mathbf{X})f_{\boldsymbol{\Theta}}(\mathbf{X})^\top f_{\boldsymbol{\Theta}}(\mathbf{X})f_{\boldsymbol{\Theta}}(\mathbf{X})^\top - 2f_{\boldsymbol{\Theta}}(\mathbf{X})\mathbf{L}f_{\boldsymbol{\Theta}}(\mathbf{X})^\top + \mathbf{L}^\top\mathbf{L})$$
$$= constant - 2\,\mathrm{Tr}(f_{\boldsymbol{\Theta}}(\mathbf{X})\mathbf{L}f_{\boldsymbol{\Theta}}(\mathbf{X})^\top) \geq 0. \tag{11}$$

$\square$

Note that Eq. 9 encourages the linear kernel matrix $f_{\boldsymbol{\Theta}}(\mathbf{X})f_{\boldsymbol{\Theta}}(\mathbf{X})^\top$ to be close to $\tilde{\mathbf{W}}_w$ while Eq. 10 encourage the linear kernel matrix to be far from the $\tilde{\mathbf{W}}_w$ at the same time.

Our loss follows the non-Euclidean geometry. In the following part, we demonstrate the relation among Eq. 4, the Affine-invariant Riemannian metric (AIRM), and Jessen-Bregman LogDet Divergence (JBLD).

Indeed, our loss function is bounded from both sides by AIRM and AIRM scaled by $\sqrt{m}$ respectively.

**Proposition 5.** *Let $\sigma(\mathbf{X})$ be the vector of eigenvalues of $\mathbf{X}$, for any semi-SPD matrix $\mathbf{S}_t, \mathbf{S}_w \in \mathbb{P}_m^*$ (asterisk * denotes semi-SPD set), we have:*

$$\|\log((\mathbf{I}+\mathbf{S}_t)^{-1/2}(\mathbf{I}+\mathbf{S}_w)(\mathbf{I}+\mathbf{S}_t)^{-1/2})\|_F \leq \log\det(\mathbf{I}+\mathbf{S}_t) - \log\det(\mathbf{I}+\mathbf{S}_w)$$
$$\leq \sqrt{m}\|\log((\mathbf{I}+\mathbf{S}_t)^{-1/2}(\mathbf{I}+\mathbf{S}_w)(\mathbf{I}+\mathbf{S}_t)^{-1/2})\|_F. \tag{12}$$

*Proof.* Given $\mathbf{A} = \mathbf{I} + \mathbf{S}_t$ and $\mathbf{B} = \mathbf{I} + \mathbf{S}_w$, we have:

$$\log\det(\mathbf{A}) - \log\det(\mathbf{B}) = \log(\det(\mathbf{A})\det(\mathbf{B}^{-1})) = \log(\det(\mathbf{A})\det(\mathbf{B}^{-1/2})\det(\mathbf{B}^{-1/2}))$$
$$= \mathrm{Tr}\log(\mathbf{B}^{-1/2}\mathbf{A}\mathbf{B}^{-1/2}). \tag{13}$$

We have $\mathrm{Tr}(\mathbf{A}) = \|\sigma(\mathbf{A})\|_1$, $\|\mathbf{A}\|_F = \|\sigma(\mathbf{A})\|_2$ and $\|\mathbf{x}\|_2 \leq \|\mathbf{x}\|_1 \leq \sqrt{m}\|\mathbf{x}\|_2$. $\square$

Thus, Eq. 4 is trying to find a mapping function maximizing an approximation of AIRM distance between the total scatter matrix and the within-class matrix.

**Definition 1.** *Given any SPD matrix $\mathbf{A}, \mathbf{B} \in \mathbb{P}_m$, we define the regularized Jensen Bregman LogDet Divergence as follows:*

$$J(\mathbf{A}, \mathbf{B}; \alpha) = \log\det\left(\frac{\mathbf{I} + \alpha\mathbf{A} + \alpha\mathbf{B}}{2}\right) - \frac{1}{2}\big(\log\det(\mathbf{I}+\alpha\mathbf{A}) + \log\det(\mathbf{I}+\alpha\mathbf{B})\big) \ for \ \mathbf{A}, \mathbf{B}, \alpha \geq 0, \tag{14}$$

*where $\mathbf{I}$ can be interpreted as a regularization to prevent $\det(\mathbf{A}) = 0$ and $\log(\det(\mathbf{A})) = -\infty$.*

**Proposition 6.** *For any $\mathbf{S}_w, \mathbf{S}_t \in \mathbb{P}_m$ and $\alpha \geq 0$, we have:*

$$\delta_{ld}(\mathbf{S}_t, \mathbf{S}_w; \alpha) \geq J(\mathbf{S}_w, \mathbf{S}_b; \alpha)$$
$$= \log\det\left(\frac{\mathbf{I} + \alpha\mathbf{S}_w + \alpha\mathbf{S}_b}{2}\right) - \frac{1}{2}\left(\log\det(\mathbf{I}+\alpha\mathbf{S}_w) + \log\det(\mathbf{I}+\alpha\mathbf{S}_b)\right), \tag{15}$$

*where the equality holds only if $\alpha = 0$ and then $\det(\mathbf{I}+\alpha\mathbf{S}_b) = 1$.*

*Proof.* Based on Eq. 14, we notice JBLD is a lower bound of our loss:

$$J(\mathbf{S}_w, \mathbf{S}_b; \alpha) = \log\det\left(\frac{\mathbf{I} + \alpha\mathbf{S}_w + \alpha\mathbf{S}_b}{2}\right) - \frac{1}{2}\left(\log\det(\mathbf{I} + \alpha\mathbf{S}_w) + \log\det(\mathbf{I} + \alpha\mathbf{S}_b)\right)$$

$$= \frac{1}{2}\log\det\left(\mathbf{I} + \alpha\mathbf{S}_t\right) - \frac{1}{2}\left(\log\det(\mathbf{I} + \alpha\mathbf{S}_w) + \log\det(\mathbf{I} + \alpha\mathbf{S}_b)\right) \quad (16)$$

$$\leq \frac{1}{2}\left(\log\det\left(\mathbf{I} + \alpha\mathbf{S}_t\right) - \log\det(\mathbf{I} + \alpha\mathbf{S}_w)\right).$$

Thus, Eq. 4 can be also interpreted as find a mapping function maximizing the regularized JBLD between the within-class matrix and the between-class matrix. □

# 6 Experiments

We evaluate GLEN (its relaxation) on transductive and inductive node classification tasks and node clustering. GLEN is compared to popular unsupervised, contrastive, and (semi-)supervised approaches. Except for the classifier, unsupervised models do not use labels. To learn similarity/dissimilarity, contrastive models employ the contrastive setting. Labels are used to train the projection layer and classifier in semi-supervised models. A fraction of nodes (*i.e.*, 5 or 20 per class) used for training are labeled for semi-supervised setting. A SoftMax classifier is used for (semi-)supervised models, while a logistic regression classifier is used for unsupervised and contrastive approaches.

**Datasets.** GLEN is evaluated on four citation networks: Cora, Citeseer, Pubmed, Cora Full [16, 4] for transductive setting. We also employ the large scale Ogbn-arxiv from OGB [13]. Finally, the Reddit [42] dataset is used in inductive setting. See supplementary material for details of datasets.

**Metrics.** As fixed data splits [40] often on transductive models benefit models that overfit, we average results over 50 random splits for each dataset. We evaluate performance for 5 and 20 samples per class. The inductive task is typically tested on graphs that are significantly larger. As in prior works, we use fixed data splits and publish Micro-F1 scores averaged across 10 runs.

**Baseline models.** We group baseline models into unsupervised, contrastive and (semi-)supervised methods, and implement them in the same framework/testbed. Contrastive methods include DeepWalk [28], GCN+SampledNCE developed as an alternative to GraphSAGE+SampledNCE [9], Graph2Gauss [4], SCE [43], DGI [33], GRACE [52], GCA [53], GraphCL [41] and COLES [51], which are our main competitors. Note that GRACE, GCA and GraphCL are based on multi-view and data augmentation, and GraphCL is mainly intended for graph classification. We do not study graph classification as it requires advanced node pooling with mixed- or high-order statistics [36, 18, 19].

Table 1: Mean classification accuracy (%) and the standard dev. over 50 random splits. Numbers of labeled samples per class are in parentheses. The best accuracy per column is in bold. Models are organized into semi-supervised, contrastive and unsupervised groups. OOM means out of memory.

| | Method | Cora | | Citeseer | | Pubmed | | Cora Full | |
|---|---|---|---|---|---|---|---|---|---|
| | | (5) | (20) | (5) | (20) | (5) | (20) | (5) | (20) |
| Semi-supervised | GCN | 67.5±4.8 | 79.4±1.6 | 57.7±4.7 | 69.4±1.4 | 65.4±5.2 | 77.2±2.1 | 49.3±1.8 | 61.5±0.5 |
| | GAT | 71.2±3.5 | 79.6±1.5 | 54.9±5.0 | 69.1±1.5 | 65.5±4.6 | 75.4±2.3 | 43.9±1.5 | 56.9±0.6 |
| | MixHop | 67.9±5.7 | 80.0±1.4 | 54.5±4.3 | 67.1±2.0 | 64.4±5.6 | 75.7±2.7 | 47.5±1.5 | 61.0±0.7 |
| Contrastive | DeepWalk | 60.3±4.0 | 70.5±1.9 | 38.3±2.9 | 45.6±2.0 | 60.3±5.6 | 70.8±2.6 | 38.9±1.4 | 51.1±0.7 |
| | GCN+SampledNCE | 61.3±4.3 | 74.3±1.6 | 42.3±3.4 | 56.8±1.9 | 60.9±5.7 | 70.3±2.5 | 32.7±1.9 | 45.2±0.9 |
| | SAGE+SampledNCE | 65.0±3.5 | 73.8±1.5 | 48.0±3.5 | 56.5±1.6 | 64.1±6.1 | 74.6±1.9 | 35.0±1.4 | 43.6±0.6 |
| | Graph2Gauss | 72.7±2.0 | 76.2±1.1 | 60.7±3.5 | 65.7±1.5 | 67.6±3.9 | 74.1±2.1 | 38.9±1.3 | 49.3±0.5 |
| | SCE | 74.3±2.7 | 80.2±1.1 | 65.4±2.9 | 70.7±1.2 | 65.7±6.0 | 75.8±2.2 | 50.7±1.5 | 60.6±0.6 |
| | DGI | 72.9±4.0 | 78.1±1.8 | 65.7±3.6 | 71.1±1.1 | 65.3±5.7 | 73.9±2.3 | 50.5±1.4 | 58.4±0.6 |
| | COLES-GCN | 73.8±3.4 | 80.8±1.3 | 66.0±2.6 | 69.0±1.3 | 62.7±4.6 | 72.7±2.1 | 47.3±1.5 | 58.9±0.5 |
| | COLES-GCN (Stiefel) | 75.0±3.4 | 81.0±1.3 | 67.9±2.3 | 71.7±0.9 | 62.6±5.0 | 73.2±2.6 | 47.6±1.2 | 59.2±0.5 |
| | COLES-S$^2$GC | 76.5±2.6 | 81.5±1.2 | 67.5±2.2 | 71.3±1.0 | 66.0±5.2 | 77.4±1.9 | 51.2±1.4 | 61.8±0.5 |
| | GLEN-GCN | 77.5±2.6 | 82.7±1.2 | 67.6±2.6 | 72.0±0.9 | 68.7±5.7 | 78.2±2.4 | 52.7±1.5 | 62.0±0.5 |
| | GLEN-S$^2$GC | **78.2±2.4** | **83.0±1.0** | **69.1±2.1** | **72.3±0.9** | **70.6±3.9** | **80.1±1.9** | **53.0±1.5** | **62.6±0.5** |
| Contrastive + Multiview | GraphCL | 72.6±4.2 | 78.3±1.7 | 65.6±3.0 | 71.1±0.8 | OOM | OOM | OOM | OOM |
| | GRACE | 64.9±4.2 | 73.9±1.6 | 61.8±3.9 | 68.4±1.6 | OOM | OOM | OOM | OOM |
| | GCA | 61.5±4.9 | 75.8±1.9 | 43.2±3.6 | 55.7±1.9 | OOM | OOM | OOM | OOM |
| Unsupervised | SGC | 63.9±5.4 | 78.3±1.9 | 59.5±3.4 | 69.8±1.4 | 65.8±4.4 | 76.3±2.3 | 46.0±2.2 | 57.7±1.2 |
| | S$^2$GC | 71.4±4.4 | 81.3±1.2 | 60.3±4.0 | 69.5±1.2 | 67.6±4.2 | 73.3±2.0 | 41.8±1.7 | 60.0±0.5 |
| | PCA-S$^2$GC | 72.1±3.8 | 81.2±1.3 | 61.0±3.5 | 68.8±1.3 | 67.5±4.3 | 73.2±2.0 | 42.3±1.7 | 59.3±0.6 |
| | RP-S$^2$GC | 65.9±4.6 | 78.1±1.2 | 51.4±3.2 | 61.7±1.6 | 66.1±5.0 | 72.5±1.9 | 31.5±1.4 | 48.7±0.6 |

We compare results with representative (semi-)supervised GCN [16], GAT [33] and MixHop [1] models. SGC and $S^2$GC are unsupervised spectral filter networks. They do not have any learnable parameters. COLES and GLEN could be regarded as dimension reduction techniques for SGC and $S^2$GC, thus we compare them to PCA-$S^2$GC and RP-$S^2$GC, which use PCA and random projections to obtain the projection layer. We set hyperparameters based on the settings described in prior papers.

## 6.1 Transductive Learning

In this section, we consider transductive learning where all nodes are available in the training process.

**COLES *vs*. GLEN.** Table 9 shows the performance of GLEN *vs*. COLES on two different backbones, *i.e*., GCN and $S^2$GC. On both backbones, GLEN shows non-trivial improvements on all four datasets. GLEN-$S^2$GC outperforms the COLES by up to 4.6%.

**Contrastive Embedding Baselines *vs*. GLEN.** Table 9 shows that GLEN-GCN and GLEN-$S^2$GC outperform unsupervised models. In particular, GLEN-GCN outperforms GCN+SampledNCE on all four datasets, which shows that GLEN has an advantage over the SampledNCE framework. In addition, GLEN-$S^2$GC outperforms the best contrastive baseline DGI by up to 3.4%. On Cora with 5 training samples, GLEN-$S^2$GC outperforms $S^2$GC by 6.8%. Finally, Table 3 shows that GLEN-$S^2$GC (small number of trainable parameters) outperforms other methods on the challenging Ogbn-arxiv.

**Semi-supervised GNNs *vs*. GLEN.** Table 9 shows that the contrastive GCN baselines perform worse than semi-supervised variants, especially when 20 labeled samples per class are available. In contrast, GLEN-GCN outperformed the semi-supervised GCN on Cora by 10% and 3.4% given 5 and 20 labeled samples per class. GLEN-GCN also outperforms GCN on Citeseer and Pubmed by 9.9% and 5.2% given 5 labeled samples per class. These results show the superiority of GLEN on four datasets when the number of samples per class is 5. Even for 20 labeled samples per class, GLEN-$S^2$GC outperforms the best semi-supervised baselines on all four datasets *e.g*., by 3.3% on Cora. Semi-supervised models (*e.g*., GAT and MixHop) are affected by the low number of labeled samples, which is consistent with [24]. The accuracy of GLEN-GCN and GLEN-$S^2$GC is unaffected.

**Unsupervised GNNs *vs*. GLEN.** SGC and $S^2$GC are unsupervised linear networks based on spectral filters which do not use labels (except for the classifier). As a dimension reduction method, GLEN helps both methods reduce the dimension and achieve discriminative features. Table 9 shows that GLEN-$S^2$GC outperforms RP-$S^2$GC and PCA-$S^2$GC under the same projection size. GLEN-$S^2$GC also outperforms the unsupervised $S^2$GC baseline (high-dimensional representation).

## 6.2 Inductive Learning

In inductive learning, models have no access to the test set, thus they need to generalize well to unseen samples. Table 2 shows that GLEN and COLES enjoy a significant performance gain (1% - 5% in Micro-F1 scores). GLEN (low memory footprint) outperforms SAGE-LSTM. In contrast, DGI on Reddit triggered out-of-memory error on Nvidia GTX 1080 GPU (94.0 Micro-F1 is from [33]).

Table 2: Test Micro F1 Score (%) averaged over 10 runs on Reddit. Results of other models are from original papers.

| Setting | Model | Test F1 |
|---|---|---|
| Supervised | SAGE-mean | 95.0 |
| | SAGE-LSTM | 95.4 |
| | SAGE-GCN | 93.0 |
| Contrastive | SAGE-mean | 89.7 |
| | SAGE-LSTM | 90.7 |
| | SAGE-GCN | 90.8 |
| | FastGCN | 93.7 |
| | DGI | 94.0 |
| | COLES-$S^2$GC | 95.4 |
| | GLEN-$S^2$GC | **95.6** |

Table 3: Mean classification accuracy (%) and the standard dev. over 10 runs on Ogbn-arxiv. Results of other models are from original papers.

| Method | | Test Acc. | #Params |
|---|---|---|---|
| MLP | | 55.50±0.23 | 110,120 |
| Node2Vec | [8] | 70.07±0.13 | 21,818,792 |
| GraphZoom | [6] | 71.18±0.18 | 8,963,624 |
| C&S | [14] | 71.26±0.01 | 5,160 |
| SAGE-mean | [9] | 71.49±0.27 | 218,664 |
| GCN | [16] | 71.74±0.29 | 142,888 |
| DeeperGCN | [23] | 71.92±0.17 | 491,176 |
| SIGN | [29] | 71.95±0.11 | 3,566,128 |
| FrameLet | [47] | 71.97±0.12 | 1,633,183 |
| $S^2$GC | [49] | 72.01±0.25 | 110,120 |
| COLES-$S^2$GC | [51] | 72.48±0.25 | 110,120 |
| GLEN-$S^2$GC | | **72.67±0.26** | 110,120 |

Table 4: The clustering performance on Cora, Citeseer and Pubmed.

| Method | Input | Cora | | | Citeseer | | | Pubmed | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | Acc% | NMI% | F1% | Acc% | NMI% | F1% | Acc% | NMI% | F1% |
| k-means | Feature | 34.65 | 16.73 | 25.42 | 38.49 | 17.02 | 30.47 | 57.32 | 29.12 | 57.35 |
| Spectral-f | Feature | 36.26 | 15.09 | 25.64 | 46.23 | 21.19 | 33.70 | 59.91 | 32.55 | 58.61 |
| Spectral-g | Graph | 34.19 | 19.49 | 30.17 | 25.91 | 11.84 | 29.48 | 39.74 | 3.46 | 51.97 |
| DeepWalk | Graph | 46.74 | 31.75 | 38.06 | 36.15 | 9.66 | 26.70 | 61.86 | 16.71 | 47.06 |
| GAE | Both | 53.25 | 40.69 | 41.97 | 41.26 | 18.34 | 29.13 | 64.08 | 22.97 | 49.26 |
| VGAE | Both | 55.95 | 38.45 | 41.50 | 44.38 | 22.71 | 31.88 | 65.48 | 25.09 | 50.95 |
| ARGE | Both | 64.00 | 44.90 | 61.90 | 57.30 | 35.00 | 54.60 | 59.12 | 23.17 | 58.41 |
| ARVGE | Both | 62.66 | 45.28 | 62.15 | 54.40 | 26.10 | 52.90 | 58.22 | 20.62 | 23.04 |
| GCN | Both | 59.05 | 43.06 | 59.38 | 45.97 | 20.08 | 45.57 | 61.88 | 25.48 | 60.70 |
| SGC | Both | 62.87 | 50.05 | 58.60 | 52.77 | 32.90 | 63.90 | 69.09 | 31.64 | 68.45 |
| S$^2$GC | Both | 68.96 | 54.22 | 65.43 | 69.11 | 42.87 | 64.65 | 68.18 | 31.82 | 67.81 |
| COLES-GCN | Both | 60.74 | 45.49 | 59.33 | 63.28 | 37.54 | 59.17 | 63.46 | 25.73 | 63.42 |
| COLES-GCN (Stiefel) | Both | 62.46 | 47.01 | 59.38 | 65.17 | 38.90 | 60.85 | 63.56 | 25.81 | 63.58 |
| COLES-S$^2$GC | Both | 69.70 | 55.35 | 63.06 | 69.20 | 44.41 | 64.70 | 68.76 | 33.42 | 68.12 |
| GLEN-GCN | Both | 69.27 | 55.34 | 62.14 | 68.25 | 42.98 | 64.10 | 64.64 | 30.08 | 64.12 |
| GLEN-S$^2$GC | Both | **71.01** | **56.69** | **69.01** | **69.89** | **45.37** | **65.70** | **69.62** | **34.97** | **69.33** |

## 6.3 Node Clustering

We compare GLEN-GCN and GLEN-S$^2$GC with three types of clustering methods:

i. Methods that use only node features *e.g.*, k-means and spectral clustering (spectral-f) construct a similarity matrix with the node features by a linear kernel.

ii. Structural clustering methods that only use the graph structure: spectral clustering (spectral-g) that takes the graph adjacency matrix as the similarity matrix, and DeepWalk [28].

iii. Attributed graph clustering methods that use node features and the graph: Graph Autoencoder (GAE), Graph Variational Autoencoder (VGAE) [16], Adversarially Regularized Graph Autoencoder (ARGE), Var. Graph Autoencoder (ARVGE) [27], SGC [37] , S$^2$GC [49], COLES [51].

We measure the performance by the clustering Accuracy (Acc), Normalized Mutual Information (NMI) and macro F1-score (F1). We run each method 10 times on Cora, CiteSeer and PubMed. We set the number of propagation steps to 8 for SGC, S$^2$GC, COLES-S$^2$GC and COLES-S$^2$GC following [44]. Table 4 shows that GLEN-S$^2$GC outperforms other methods in all cases, whereas GLEN-GCN outperforms COLES-GCN, COLES-GCN (Stiefel) and contrastive GCN on all datasets.

**Scalability.** GraphSAGE and DGI require neighbor sampling with redundant forward/backward steps (long runtime). In contrast, GLEN-S$^2$GC enjoys a simple implementation with low memory usage/low runtime. For graphs with over 100 thousands nodes and 10 millions edges (Reddit), GLEN runs fast on NVIDIA 1080 GPU. Even on larger graph benchmarks, GLEN is fast as it optimizes the total scatter and the within-class matrices whose size depends on embedding size rather than the node number. The runtime of GLEN-S$^2$GC is also favourable in comparison to multi-view augmentation-based GraphCL. Specifically, GLEN-S$^2$GC took 0.54s, 0.3s, 5.3s and 15.4s on Cora, Citeseer, Pubmed and Cora Full, respectively. GraphCL took 110.19s, 101.0s, $\geq$ 8h and $\geq$ 8h respectively. Although the LogDet difference is somewhat slower than the trace difference in forward/backward propagation, it converges faster, thus enjoying a similar low runtime.

## 7 Conclusions

In this paper, we model contrastvie learning as a rank difference problem to approximate the condition that the rank of total scatter matrix should equal the sum of ranks of within-scatter and between-scatter matrices. We relax this NP-hard assumption with a differentiable difference of LogDet terms. We also show two perspectives on GLEN and the existing methods based on the low-rank optimization and distance between SPD matrices. In low-rank optimization, we explain why the LogDet difference is a better surrogate function to optimize rank difference compared to the trace difference. We also show that our solution encourages linear kernel of embeddings become the geometric mean between the total scatter matrix and the within-class matrix. Our GLEN works well with many backbones outperforming many unsupervised, contrastive and (semi-)supervised methods.

# References

[1] Sami Abu-El-Haija, Bryan Perozzi, Amol Kapoor, Nazanin Alipourfard, Kristina Lerman, Hrayr Harutyunyan, Greg Ver Steeg, and Aram Galstyan. Mixhop: Higher-order graph convolutional architectures via sparsified neighborhood mixing. In *International Conference on Machine Learning*, pages 21–29, 2019.

[2] Philip Bachman, R Devon Hjelm, and William Buchwalter. Learning representations by maximizing mutual information across views. *arXiv preprint arXiv:1906.00910*, 2019.

[3] Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps for dimensionality reduction and data representation. *Neural computation*, 15(6):1373–1396, 2003.

[4] Aleksandar Bojchevski and Stephan Günnemann. Deep gaussian embedding of graphs: Unsupervised inductive learning via ranking. *arXiv preprint arXiv:1707.03815*, 2017.

[5] Hongyun Cai, Vincent W Zheng, and Kevin Chen-Chuan Chang. A comprehensive survey of graph embedding: Problems, techniques, and applications. *IEEE Transactions on Knowledge and Data Engineering*, 30(9):1616–1637, 2018.

[6] C Deng, Z Zhao, Y Wang, Z Zhang, and Z Feng. Graphzoom: A multi-level spectral approach for accurate and scalable graph embedding. In *International Conference on Learning Representations*, 2020.

[7] Maryam Fazel, Haitham Hindi, and Stephen P Boyd. Log-det heuristic for matrix rank minimization with applications to hankel and euclidean distance matrices. In *Proceedings of the 2003 American Control Conference, 2003.*, volume 3, pages 2156–2162. IEEE, 2003.

[8] Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *ACM SIGKDD international conference on Knowledge discovery and Data Mining*, pages 855–864, 2016.

[9] Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Advances in Neural Information Processing Systems*, pages 1024–1034, 2017.

[10] Kaveh Hassani and Amir Hosein Khasahmadi. Contrastive multi-view representation learning on graphs. In *International Conference on Machine Learning*, pages 4116–4126, 2020.

[11] Xiaofei He and Partha Niyogi. Locality preserving projections. *Advances in Neural Information Processing Systems*, 16(16):153–160, 2004.

[12] R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. *arXiv preprint arXiv:1808.06670*, 2018.

[13] Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. *arXiv preprint arXiv:2005.00687*, 2020.

[14] Qian Huang, Horace He, Abhay Singh, Ser-Nam Lim, and Austin Benson. Combining label propagation and simple models out-performs graph neural networks. In *International Conference on Learning Representations*, 2021.

[15] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[16] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

[17] Thomas N Kipf and Max Welling. Variational graph auto-encoders. *arXiv preprint arXiv:1611.07308*, 2016.

[18] Piotr Koniusz, Lei Wang, and Anoop Cherian. Tensor representations for action recognition. *IEEE Trans. Pattern Anal. Mach. Intell.*, 44(2):648–665, 2022.

[19] Piotr Koniusz and Hongguang Zhang. Power normalizations in fine-grained image, few-shot image and graph classification. In *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.

[20] Brian Kulis et al. Metric learning: A survey. *Foundations and Trends® in Machine Learning*, 5(4):287–364, 2013.

[21] Marc T Law, Raquel Urtasun, and Richard S Zemel. Deep spectral clustering learning. In *International conference on machine learning*, pages 1985–1994. PMLR, 2017.

[22] Omer Levy and Yoav Goldberg. Neural word embedding as implicit matrix factorization. *Advances in Neural Information Processing Systems*, 27:2177–2185, 2014.

[23] Guohao Li, Chenxin Xiong, Ali Thabet, and Bernard Ghanem. Deepergcn: All you need to train deeper gcns. *arXiv preprint arXiv:2006.07739*, 2020.

[24] Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. In *AAAI Conference on Artificial Intelligence*, pages 3538–3545, 2018.

[25] Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013.

[26] Tomas Mikolov, Ilya Sutskever, Kai Chen, Gregory S Corrado, and Jeffrey Dean. Distributed representations of words and phrases and their compositionality. In *Advances in Neural Information Processing Systems*, 2013.

[27] S Pan, R Hu, G Long, J Jiang, L Yao, and C Zhang. Adversarially regularized graph autoencoder for graph embedding. In *International Joint Conference on Artificial Intelligence*, 2018.

[28] Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 701–710, 2014.

[29] Emanuele Rossi, Fabrizio Frasca, Ben Chamberlain, Davide Eynard, Michael Bronstein, and Federico Monti. Sign: Scalable inception graph neural networks. *arXiv preprint arXiv:2004.11198*, 2020.

[30] Ke Sun, Piotr Koniusz, and Zhen Wang. Fisher-bures adversary graph convolutional networks. *Conference on Uncertainty in Artificial Intelligence*, 115:465–475, 2019.

[31] Jian Tang, Meng Qu, Mingzhe Wang, Ming Zhang, Jun Yan, and Qiaozhu Mei. Line: Large-scale information network embedding. In *International Conference on World Wide Web*, pages 1067–1077, 2015.

[32] Joshua B Tenenbaum, Vin De Silva, and John C Langford. A global geometric framework for nonlinear dimensionality reduction. *Science*, 290(5500):2319–2323, 2000.

[33] Petar Velickovic, William Fedus, William L Hamilton, Pietro Lio, Yoshua Bengio, and R Devon Hjelm. Deep graph infomax. In *International Conference on Learning Representations*, 2019.

[34] Kuansan Wang, Zhihong Shen, Chiyuan Huang, Chieh-Han Wu, Yuxiao Dong, and Anshul Kanakia. Microsoft academic graph: When experts are not enough. *Quantitative Science Studies*, 1(1):396–413, 2020.

[35] Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *International Conference on Machine Learning*, volume 119, pages 9929–9939, 2020.

[36] Zhengyang Wang and Shuiwang Ji. Second-order pooling for graph neural networks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.

[37] Felix Wu, Tianyi Zhang, Amauri Holanda de Souza Jr, Christopher Fifty, Tao Yu, and Kilian Q Weinberger. Simplifying graph convolutional networks. *arXiv preprint arXiv:1902.07153*, 2019.

[38] Shuicheng Yan, Dong Xu, Benyu Zhang, Hong-jiang Zhang, Qiang Yang, and Stephen Lin. Graph embedding and extensions: A general framework for dimensionality reduction. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 29(1):40–51, 2007.

[39] Zhen Yang, Ming Ding, Chang Zhou, Hongxia Yang, Jingren Zhou, and Jie Tang. Understanding negative sampling in graph representation learning. In *ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 1666–1676, 2020.

[40] Zhilin Yang, William Cohen, and Ruslan Salakhudinov. Revisiting semi-supervised learning with graph embeddings. In *International Conference on Machine Learning*, pages 40–48, 2016.

[41] Yuning You, Tianlong Chen, Yongduo Sui, Ting Chen, Zhangyang Wang, and Yang Shen. Graph contrastive learning with augmentations. *Advances in Neural Information Processing Systems*, 33:5812–5823, 2020.

[42] Hanqing Zeng, Hongkuan Zhou, Ajitesh Srivastava, Rajgopal Kannan, and Viktor Prasanna. Graphsaint: Graph sampling based inductive learning method. *arXiv preprint arXiv:1907.04931*, 2019.

[43] Shengzhong Zhang, Zengfeng Huang, Haicang Zhou, and Ziang Zhou. Sce: Scalable network embedding from sparsest cut. In *ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 257–265, 2020.

[44] Xiaotong Zhang, Han Liu, Qimai Li, and Xiao-Ming Wu. Attributed graph clustering via adaptive graph convolution. *arXiv preprint arXiv:1906.01210*, 2019.

[45] Yifei Zhang, Hao Zhu, Ziqiao Meng, Piotr Koniusz, and Irwin King. Graph-adaptive rectified linear unit for graph neural networks. In *TheWebConf (WWW)*, pages 1331–1339. ACM, 2022.

[46] Yifei Zhang, Hao Zhu, Zixing Song, Piotr Koniusz, and Irwin King. COSTA: covariance-preserving feature augmentation for graph contrastive learning. In *KDD*, pages 2524–2534. ACM, 2022.

[47] Xuebin Zheng, Bingxin Zhou, Junbin Gao, Yuguang Wang, Pietro Lió, Ming Li, and Guido Montufar. How framelets enhance graph neural networks. In Marina Meila and Tong Zhang, editors, *International Conference on Machine Learning*, volume 139, pages 12761–12771, 2021.

[48] Hao Zhu and Piotr Koniusz. REFINE: Random range finder for network embedding. In *ACM Conference on Information and Knowledge Management*, 2021.

[49] Hao Zhu and Piotr Koniusz. Simple spectral graph convolution. In *International Conference on Learning Representations*, 2021.

[50] Hao Zhu and Piotr Koniusz. EASE: Unsupervised discriminant subspace learning for transductive few-shot learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9078–9088, 2022.

[51] Hao Zhu, Ke Sun, and Piotr Koniusz. Contrastive laplacian eigenmaps. *Advances in Neural Information Processing Systems*, 34, 2021.

[52] Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Deep graph contrastive representation learning. *arXiv preprint arXiv:2006.04131*, 2020.

[53] Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Graph contrastive learning with adaptive augmentation. In *Proceedings of the Web Conference*, pages 2069–2080, 2021.