HIERARCHICALLY-STRUCTURED VARIATIONAL AUTOENCODERS FOR LONG TEXT GENERATION

ABSTRACT

Variational autoencoders (VAEs) have received much attention recently as an end-to-end architecture for text generation. Existing methods primarily focus on synthesizing relatively short sentences (with less than twenty words). In this paper, we propose a novel framework, hierarchically-structured variational autoencoders (*hier*-VAE), for generating long and coherent units of text. To enhance the model's *plan-ahead* ability, intermediate sentence representations are introduced into the generative networks to guide the word-level predictions. To alleviate the typical optimization challenges associated with textual VAEs, we further employ a hierarchy of stochastic layers between the encoder and decoder networks. Extensive experiments are conducted to evaluate the proposed method, where *hier*-VAE is shown to make effective use of the latent codes and achieve lower perplexity relative to language models. Moreover, the generated samples from *hier*-VAE also exhibit superior quality according to both automatic and human evaluations.

1 INTRODUCTION

Probabilistic *generative* models for text have received considerable attention recently, in part because of their ability to leverage abundant *unlabeled* data and learn text representations with strong generalization abilities. Combined with the flexibility of deep neural networks, generative modeling provides a powerful and effective framework to estimate the underlying probability distribution of *sentences* or *documents*, and to potentially capture the rich sequential information inherent in natural language. In this work, we focus on one specific type of generative model: the variational autoencoder (VAE) (Kingma & Welling, 2013).

The VAE maps a text sequence into a continuous latent variable, or *code*, via an inference (encoder) network; a generative (decoder) network is utilized to reconstruct the input sentence, conditioned on samples from the latent code (via its posterior distribution). The inference and generative networks, parametrized by deep neural networks, can be optimized jointly by maximizing a

i went there a few days ago and was told it was horrible , i was told there was a horrible customer service , and they were rude, i would not recommend this location to anyone , i would not recommend this location to anyone .

Table 1: Sentences generated from a baseline text-VAE model, as described in (Bowman et al., 2016).

variational lower bound of the marginal distribution of the training corpus. The advantages of leveraging the neural variational inference (NVI) framework have been demonstrated on a wide range of natural language processing (NLP) tasks (Bowman et al., 2016; Miao et al., 2016; Yang et al., 2017; Serban et al., 2017; Shah & Barber, 2018; Kim et al., 2018; Kaiser et al., 2018; Bahuleyan et al., 2018; Deng et al., 2018). Although NVI-based methods have demonstrated success in modeling (generating) relatively short sentences (typically less than twenty words), there are several challenges that need to be addressed to facilitate *long* text generation with deep latent-variable models.

The first challenge originates from the nature of recurrent neural networks (RNNs), which have become the cornerstone for text generation. RNNs are typically trained with gradient descent, using backpropagation through time (BPTT) (Rumelhart et al., 1986). However, it is very difficult to scale such a training paradigm to long sequences, due to vanishing or exploding gradients (Hochreiter & Schmidhuber, 1997). Moreover, the information of the entire generated sequence needs to be stored in the RNN intermediate hidden states, which could be very demanding for RNNs with the increasing length of generated texts. As shown in Table 1, the sentence sampled from a vanilla text-VAE model (Bowman et al., 2016) tends to repeat itself as the sequence proceeds, leading to inferior

generation results. In addition to the issue of repetitiveness, to generate globally-coherent long text sequences, it is desirable that both the *higher-level* abstract features and *lower-level* concrete details (*e.g.*, specific word choices) of longer texts can be leveraged by the generative network. This intuition is also hard to capture with a single-layer (flat) RNN-based generative network.

Another underlying challenge of generating *long* text relates to the "*posterior collapse*" issue inherent in training variational autoencoders with a strong *autoregressive* decoder (Bowman et al., 2016; Yang et al., 2017; Semeniuta et al., 2017; Shen et al., 2018). Bowman et al. (2016) found that while employing an LSTM-based VAE for text, the posterior distribution of latent codes tends to match the prior distribution regardless of the input sequence (the KL divergence between the two distributions is very close to zero). Consequently, the information from the latent variable is not leveraged by the generative network (Bowman et al., 2016). To mitigate this issue, several strategies have been proposed (see optimization challenges in Section 2) to make the decoder less autoregressive; thus, less *contextual information* is utilized by the decoder network (Yang et al., 2017; Shen et al., 2018). However, reducing the autoregressive power of the decoder to make the latent variable more informative can be suboptimal from a text-generation perspective, since the coherence of the generated paragraphs may be sacrificed.

Motivated by these observations, we propose a hierarchically-structured variational autoencoder (*hier*-VAE), a novel variational approach for generating long sequences of text. To improve the model's plan-ahead capability for capturing long-term dependency, our approach exploits a hierarchical LSTM decoder as the generative network. Specifically, a set of intermediate sentence-level representations are introduced during the decoding process (via a sentence-level LSTM network), providing additional semantic information while making *word-level* predictions.

To ameliorate the *posterior collapse* issue associated with training a VAE for text, we further propose leveraging a hierarchy of latent variables between the convolutional inference networks and recurrent generative networks. With multiple stochastic layers, where the prior of each latent variable is inferred from data, rather than fixed (as in a standard VAE setting (Kingma & Welling, 2013)), the sampled *latent codes* at the bottom level are endowed with more flexibility to abstract meaningful features from the input sequences. We evaluate the proposed *hier*-VAE comprehensively on language modeling, generic (unconditional) text generation, and conditional generation tasks. The proposed model demonstrates substantial improvement relative to several baseline methods, in terms of *perplexity* on language modeling and quality of generated samples (measured by both the BLEU statistics and human evaluation). We further generalize our method to the conditional generation scenario to demonstrate the versatility of the proposed method.

2 RELATED WORK

VAE for text generation   The variational autoencoder, trained under the neural variational inference (NVI) framework, has been widely used for generating text sequences (Bowman et al., 2016; Yang et al., 2017; Semeniuta et al., 2017; Zhao et al., 2017). By encouraging the latent feature space to match a prior distribution within an encoder-decoder architecture, the learned latent variable could potentially encode high-level semantic features and serve as a global representation during the decoding process (Bowman et al., 2016). The generated results are also endowed with better diversity due to the sampling procedure of the latent codes (Zhao et al., 2017). However, existing works have mostly focused on generating one sentence (or multiple sentences with at most twenty words in total). The task of generating relatively longer units of text has been less explored. Our proposed architecture seeks to extend the NVI framework for long-form text generation by exploiting the hierarchical nature of a paragraph (multi-sentence text sequences), where the outputs from a sentence-level LSTM are utilized to guide word-level predictions.

Optimization challenges with text-VAEs   The "posterior collapsing" issue associated with training text-VAEs was first outlined by (Bowman et al., 2016), where they have utilized *KL divergence annealing* and *word dropout* strategies to mitigate the optimization challenge. However, their resulting method still does not outperform a pure language model in terms of the final perplexity. Yang et al. (2017) argue that the small KL term relates to the strong autoregressive nature of an LSTM generative network, and they proposed to utilize a dilated CNN as a decoder to improve the informativeness of the latent variable. (Zhao et al., 2018b) proposed to augment the VAE training objective with an additional mutual information term. Unfortunately, such a strategy results in an intractable integral in the case where the latent variables are continuous. Our work tries to tackle the "posterior

collapse" issue from two perspectives: 1) more flexible priors are assumed over the latent variables (learned from the data); 2) the hierarchical structure within a paragraph is taken into account, so that the latent variables can focus less on the local information (*e.g.*, word-level coherence) but more on the global features.

Hierarchical structures in NLP Natural language is inherently organized in a hierarchical manner (characters from a word, words form a sentence, sentences form a paragraph, paragraphs from a document, *etc.*). Yang et al. (2016) employed hierarchical LSTM encoders at the word- and sentence-level along with an attention mechanism to learn document representations. Li et al. (2015) proposed a hierarchical autoencoder to reconstruct long paragraph of texts. One method conceptually similar to our work is that of (Serban et al., 2017), which produces a stochastic latent variable for each sentence during decoding. In contrast, our model encodes the entire paragraph into one *single* latent variable. As a result, the latent variable learned in our model relates more to the global semantic information of a paragraph, whereas those in (Serban et al., 2017) mainly contain the local information of a specific sentence. Therefore, their model is not suitable for tasks such as latent space interpolation. Modeling hierarchical structures has been shown to be beneficial for generating others types of data as well, such as images (Sønderby et al., 2016; Gulrajani et al., 2016) or music (Roberts et al., 2018).

3 HIERARCHICALLY-STRUCTURED VAE MODEL

Our goal is to build a model that can generate human-generated-like sentences conditioned on random samples from the (prior) latent space. The proposed method, as illustrated in Figure 1, is built upon the VAE framework introduced in (Bowman et al., 2016), and consists of a hierarchical CNN *inference* network (encoder) and a hierarchical LSTM *generative* network (decoder). The encoder attempts to extract features at different semantic levels, which are then leveraged by the decoder to allow long-term planning while synthesizing long-form text. We define long-form text as sequences of sentences (such as a Yelp review on a business, or an abstract of an article) that are arranged in a logical manner and usually follow a definite plan for development.

3.1 VARIATIONAL AUTOENCODER

Recurrent neural network (RNN) language models (Mikolov et al., 2011), which predict each token conditioned on the entire history of previously generated tokens, have been widely employed for unsupervised generative modeling of natural language. Although effective, they typically do not explicitly capture the *global* (*high-level*) features (*e.g.*, topic or style properties) of a paragraph or sentence. Motivated by this, the variational autoencoder (VAE) was introduced by (Bowman et al., 2016) as an alternative for generative text modeling, where a stochastic latent variable is augmented as the additional information to modulate the sequential generation process. Let $\boldsymbol{x}$ denote a text sequence, which consists of L tokens, *i.e.*, $x_1, x_2, ..., x_L$. A continuous latent code $\boldsymbol{z}$ is first sampled from the prior distribution $p(\boldsymbol{z})$ (a multivariate Gaussian prior is typically chosen), and then the text sequence $\boldsymbol{x}$ is generated, conditioned on $\boldsymbol{z}$, via a generative (decoder) network. Therefore, the generating distribution can be written as:

$$p_{\boldsymbol{\theta}}(\boldsymbol{x}|\boldsymbol{z}) = p_{\boldsymbol{\theta}}(x_1|\boldsymbol{z}) \prod_{t=2}^{L} p_{\boldsymbol{\theta}}(x_t|x_1, x_2, ..., x_{t-1}, \boldsymbol{z}) \qquad (1)$$

where $\boldsymbol{\theta}$ are the parameters of the generative network (to be learned). Since the information from latent variable $\boldsymbol{z}$ is incorporated during the entire generation process, the high-level properties of the corresponding paragraph or sentence could be better leveraged (Bowman et al., 2016; Yang et al., 2017). To estimate the parameters $\boldsymbol{\theta}$, one would ideally maximize the marginal distribution $p(\boldsymbol{x}) = \int p(\boldsymbol{z})p(\boldsymbol{x}|\boldsymbol{z})d\boldsymbol{z}$. However, computing this marginal is intractable in most cases of practical interest. Instead, we maximize a variational lower bound, as typically employed in the VAE framework (Kingma & Welling, 2013): $\mathcal{L}_{\text{vae}} = \mathbb{E}_{q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})}[\log p_{\boldsymbol{\theta}}(\boldsymbol{x}|\boldsymbol{z})] - D_{KL}(q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})||p(\boldsymbol{z}))$. Note that $q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$ is employed to approximate the true posterior, which is usually called the inference or encoder network (parameterized by $\boldsymbol{\phi}$). The Kullback-Leibler (KL) divergence term $D_{KL}(q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})||p(\boldsymbol{z}))$, which can be written in closed-form (Kingma & Welling, 2013), encourages the approximate posterior distribution $q_{\boldsymbol{\phi}}(\boldsymbol{z}|\boldsymbol{x})$ to be close to the multivariate Gaussian prior $p(\boldsymbol{z})$. Although the NVI framework has been shown effective for various NLP tasks, directly applying it to *long text generation* is still challenging. The reasons are two-fold: (1) the lack of a long-term planning mechanism, which is critical for generating *semantically-coherent* long texts (Serdyuk et al.,

Figure 1: Schematic diagram of the proposed *hierarchically-structured* VAE.

2017); (2) the *posterior collapse* issue. Concerning (2), it was demonstrated in (Bowman et al., 2016) that due to the autoregressive nature of the RNN, the decoder tends to ignore the information from z entirely, resulting in an extremely small KL term.

3.2 HIERARCHICAL LSTM-BASED GENERATIVE NETWORK

To improve the *plan-ahead* ability of the generative network, we introduce intermediate sentence representations to facilitate the sequential generation process. Instead of directly making word-level predictions merely conditioned on the semantic information from z, a series of *plan vectors* are first generated based upon z with a *sentence-level* LSTM decoder. The hypothesis underlying this design is that explicitly incorporating the knowledge of (inherently hierarchical) paragraph structure is beneficial for the model to capture sentence-level coherence and potentially mitigate repetitiveness. Intuitively, while predicting each token, the information from both previously generated words and sentence-level representations can be utilized (see Figure 1).

Assume that the input paragraph consists of M sentences, and the t-th sentence contains N_t words (for $t = 1, 2, ..., M$). To generate the plan vectors, the sampled latent code z is first sent through a one-layer multi-layered perceptron (MLP), with ReLU activation functions, to obtain the starting state of the sentence-level LSTM decoder. Subsequently, the representations for each sentence, the *plan vectors* are inferred in a sequential manner: $h_t^s = \text{LSTM}^{\text{sent}}(h_{t-1}^s, z)$, for $t = 1, 2, 3, ..., M$ (where h_0^s is a vector of zeros). Note that z is fed to the higher-level LSTM at every time step to predict the sentence representations. This is because the latent code can be regarded as a paragraph-level abstraction, and thus is informative for determining the semantics of each generated subsequence.

The generated sentence-level plan vectors are then passed through a word-level LSTM decoder to generate the words for each sentence. Similar to the sentence-level decoder, the corresponding *plan vector*, h_t^s, is concatenated with the word embedding of the previous word and fed to the LSTM at every time step (see Figure 1). Let $w_{t,i}$ denote the i-th token in the t-th sentence (teacher forcing is employed during training, and we use greedy decoding at test time). This process can be expressed as (for $t = 1, 2, ..., M$ and $i = 1, 2, 3, ..., N_i$):

$$h_{t,i}^w = \text{LSTM}^{\text{word}}(h_{t,i-1}^w, h_t^s, W_e[w_{t,i-1}]), \quad (2)$$

$$p(w_{t,i}|w_{t,<i}, h_t^s) = \text{softmax}(V h_{t,i}^w), \quad (3)$$

where $h_{t,0}^w$ is a vector of zeros. Weight matrix V is used for computing a distribution over words, and W_e are word embeddings to be learned. For each sentence, once the special _END token is generated, the word-level LSTM stops decoding. The parameters of the word-level decoder for each sentence are shared, and are trained jointly with the parameters of sentence-level LSTM.

Inspired by Chen et al. (2016), we hypothesize that with the hierarchical decoder networks described above, the latent codes are encouraged to abstract more global and high-level semantic information from the paragraph. While relatively more detailed information (*e.g.*, word-level (local) coherence) can be captured via the word- and sentence-level LSTM networks, the latent variables can focus more on the global information (*e.g.*, paragraph-level semantic features) (Chen et al., 2016). Empirically, we also found that this strategy helps the generative network to make more effective use of the latent variable z (indicated by a larger KL loss term).

3.3 HIERARCHICALLY-STRUCTURED LATENT VARIABLES

Due to the use of an autoregressive LSTM decoder for word-level predictions, the problem of "posterior collapse", where the model tends to ignore the latent codes while decoding, may still exist. In this work, we consider one effective way to mitigate this problem by making less restrictive assumptions regarding the prior distribution of the latent variable. Specifically, we propose to leverage

a hierarchy of latent variables for text modeling. As shown in Figure 1, the inference network goes upward through each latent variable to infer their prior distributions, while the generative network samples downward to obtain the posterior distributions over the latent variables. In this manner, the prior distributions of z are inferred from data, rather than fixed (as in a standard VAE model). Consequently, the inference network is endowed with more flexibility to abstract useful features from x, which can then be leveraged by the generative network (Gulrajani et al., 2016). Without loss of generality, here we choose to employ a two-layer hierarchy of latent variables, where the bottom and top ones are denoted as z_1 and z_2, respectively. Note that this framework can be extended easily to more latent-variable layers. Empirically, we found that the two-layer setup already gives rise to much more informative latent codes, relative to a standard VAE with one stochastic layer.

The prior distribution over the latent variables is assumed to be conditionally independent given the input x. Thus, the joint prior distribution of the two latent variables can be written as:

$$q_\phi(z_1, z_2|x) = q_\phi(z_2|x)q_\phi(z_1|x) \tag{4}$$

Concerning the generative network, the latent variable at the bottom is sampled conditioning on the one at the top. Thus, we have:

$$p_\theta(z_1, z_2) = p_\theta(z_2)p_\theta(z_1|z_2) \tag{5}$$

To optimize the parameters of the inference and generative networks, the second term in the VAE objective, $D_{KL}(q_\phi(z|x)||p(z))$, can be regarded as the KL divergence between the joint posterior and prior distributions of the two latent variables. Thus, the variational lower bound can be written as (given the assumptions in (4) and (5)):

$$\mathcal{L}_{\text{vae}} = \mathbb{E}_{q_\phi(z_1|x)}[\log p_\theta(x|z_1)] - D_{KL}(q_\phi(z_1, z_2|x)||p_\theta(z_1, z_2)) \tag{6}$$

$$
\begin{aligned}
D_{KL} &= \int_{z_1, z_2} q_\phi(z_2|x)q_\phi(z_1|x) \log \frac{q_\phi(z_2|x)q_\phi(z_1|x)}{p_\theta(z_2)p_\theta(z_1|z_2)} dz_1 dz_2 \\
&= \int_{z_1, z_2} [q_\phi(z_2|x)q_\phi(z_1|x) \log \frac{q_\phi(z_1|x)}{p_\theta(z_1|z_2)} + q_\phi(z_2|x)q_\phi(z_1|x) \log \frac{q_\phi(z_2|x)}{p_\theta(z_2)}]dz_1 dz_2 \\
&= \mathbb{E}_{q_\phi(z_2|x)}[D_{KL}(q_\phi(z_1|x)||p_\theta(z_1|z_2))] + D_{KL}(q_\phi(z_2|x)||p_\theta(z_2))
\end{aligned}
\tag{7}
$$

Note that the left-hand side of (7) is the abbreviation of $D_{KL}(q_\phi(z_1, z_2|x)||p(z_1, z_2))$. Given the Gaussian assumption for both the prior and posterior distributions, both KL divergence terms can be written in closed-form.

4 EXPERIMENTS

4.1 EXPERIMENTAL SETUPS

Datasets We evaluate the proposed hierarchically-structured VAE on both generic (unconditional) long text generation and conditional paragraph generation (with additional text input as auxiliary information). For the former, we employ two datasets: Yelp Reviews (Zhang et al., 2015) and ArXiv Abstracts (Celikyilmaz et al., 2018). For the conditional-generation case, we consider the task of synthesizing a paper abstract (which typically includes several sentences) conditioned on the paper title (with the ArXiv Abstract dataset). We employ a hierarchical CNN architecture as the inference/encoder network. Specifically, a sentence-level CNN encoder is first applied to each sentence to obtain a fixed-length vector. Afterwards, a paragraph-level CNN encoder is utilized to aggregate the vectors with respect to all sentences. Details of the dataset, the experimental setup and model architectures are provided in the Supplementary Materials (SM).

Baselines For the language modeling experiments, we implement several baselines: language model with a flat LSTM decoder (*flat*-LM), VAE with a flat LSTM decoder (*flat*-VAE), language model with a hierarchical LSTM decoder (*hier*-LM). For generic text generation, we further consider two recently proposed generative models as the baselines: Adversarial Autoencoders (AAE) (Makhzani et al., 2015) and Adversarially-Regularized Autoencoders (ARAE) (Zhao et al., 2018a). Instead of penalizing the KL divergence term, AAE introduces a discriminator network to match the prior and posterior distributions of the latent variable. Further, AARE proposes to learn a more flexible prior by assuming no specific forms of the latent space. For the proposed hierarchically-structured VAE, we implement two variants, one with a single latent variable and another with double latent variables, denoted as *hier*-VAE-S and *hier*-VAE-D, respectively. Our code will be released to encourage future research.

hier-VAE	flat-VAE
i have been going to this nail salon for over a year now , the last time i went there , the stylist was nice , but the lady who did my nails , she was very rude and did not have the best nail color i once had .	the staff is very friendly and helpful , **the only reason i** can t give them 5 stars , **the only reason i** am giving the ticket is because of the ticket , **can t help but** the staff is so friendly and helpful , **can t help but** the parking lot is just the same .
i am a huge fan of this place , my husband and i were looking for a place to get some good music , this place was a little bit pricey , but i was very happy with the service , the staff was friendly .	i went here for a grooming and a dog , it was very good , **the owner is very nice and friendly , the owner is really nice and friendly** , i don t know what they are doing .

Table 3: Samples randomly generated from *hier*-VAE-D and *flat*-VAE, which are both trained on the Yelp review dataset. The repetitive patterns within the generated reviews are highlighted. More examples can be found in the supplementary material (Table 11).

4.2 LANGUAGE MODELING RESULTS

We first evaluate our method on language modeling task using Yelp and ArXiv datasets, where we report the negative log likelihood (NLL) and perplexity (PPL). Following (Bowman et al., 2016; Yang et al., 2017; Kim et al., 2018), we utilize the KL loss term to measure the extent of "posterior collapse". For this experiment we use the following baselines: language model with a flat LSTM decoder, VAE with a flat LSTM decoder, language model with a hierarchical LSTM decoder, VAE with a hierarchical LSTM decoder. As shown in Figure 2, on the Yelp dataset, the standard textVAE with a flat LSTM decoder has a KL divergence term very close to zero, indicating that the generative model makes neligible use of the information from latent variable z. Consequently, the *flat*-VAE model obtains slightly worse NNL and PPL relative to a flat LSTM-based language model. In contrast, with a hierarchical LSTM decoder, the KL divergence cost term becomes much larger, demonstrating that the VAE model tends to leverage more information from the latent variable in the decoding stage. Further, the PPL of *hier*-VAE is also decreased from 47.9 to 46.6 (compared with a LM with hierarchical decoder), further showing that the sampled latent codes has indeed helped make word-level predictions.

Moreover, with a hierarchy of latent variables, the *hier*-VAE-D model exhibits an even larger KL divergence cost term (increased from 3.6 to 6.8) than that with a single latent variable, indicating that more information from the latent variable has been utilized by the generative network. This may

Model	Yelp			ArXiv		
	NLL	**KL**	**PPL**	**NLL**	**KL**	**PPL**
flat-LM	162.6	-	48.0	218.7	-	57.6
flat-VAE	≤ 163.1	0.01	≤ 49.2	≤ 219.5	0.01	≤ 58.4
hier-LM	162.4	-	47.9	219.3	-	58.1
hier-VAE-S	≤ 160.8	3.6	≤ 46.6	≤ 216.8	5.3	≤ 55.6
hier-VAE-D	≤ **160.2**	6.8	≤ **45.8**	≤ **215.6**	12.7	≤ **54.3**

Table 2: Results on text modeling for both the Yelp and ArXiv datasets.

be attributed to the fact that the latent variable priors of the *hier*-VAE-D model are inferred from the data, rather than a fixed standard Gaussian distribution. As a result, the model is endowed with more flexibility to encode informative semantic features in the latent variables, yet matching their posterior distributions to the corresponding priors. More importantly, by effectively exploiting the sampled latent codes, *hier*-VAE-D achieves the best PPL results on both datasets (on ArXiv dataset our hieararhical decoder outperforms the LM by reducing the PPL from 58.1 down to 54.3).

4.3 GENERIC TEXT GENERATION

We further evaluate our method by examining the quality of generated paragraphs. In this regard, we randomly sample 1000 latent codes and obtain the generated text sequences by feeding them to the trained generative networks. We employ corpus-level BLEU score (Papineni et al., 2002) to quantitatively evaluate the generated paragraphs. Specifically, we follow the strategy in (Yu et al., 2017; Zhang et al., 2017) and use the entire test set as the reference. The BLEU scores for the 1000 generated sentences are averaged to obtain the final score for each model. As shown in Table 5, VAE tends to be a stronger baseline for paragraph generation, exhibiting higher corpus-level BLEU scores than both AAE and ARAE. This observation is consistent with the results shown in (Cífka et al., 2018). The VAE with hierarchical decoder again demonstrates better BLEU scores than the one with a flat decoder, indicating that the plan-ahead mechanism associated with the hierarchical decoding process indeed benefits the sampling quality. Moreover, *hier*-VAE-D exhibits slightly better results than *hier*-VAE-S. We attribute this to the more flexible prior distribution of *hier*-VAE-D, which improves the ability of the inference networks to extract semantic features from a paragraph and thus yields more informative latent codes.

Model	Yelp				ArXiv			
	BLEU-2	**BLEU-3**	**BLEU-4**	**BLEU-5**	**BLEU-2**	**BLEU-3**	**BLEU-4**	**BLEU-5**
ARAE	0.684	0.524	0.350	0.104	0.624	0.475	0.305	0.124
AAE	0.735	0.623	0.383	0.167	0.729	0.564	0.342	0.153
flat-VAE	0.855	0.705	0.515	0.330	0.784	0.625	0.421	0.247
hier-VAE-S	0.901	0.744	0.531	0.336	0.821	**0.663**	0.447	0.273
hier-VAE-D	**0.912**	**0.755**	**0.549**	**0.347**	**0.825**	0.657	**0.460**	**0.282**

Table 5: Evaluation results for generated sequences by our models and baselines on corpus-level BLEU scores.

Model	BLEU-2	BLEU-3	BLEU-4	Bigrams%	Trigrams%	Quadgrams%	Etp-2
ARAE	0.725	0.544	0.402	36.2	59.7	75.8	7.551
AAE	0.831	0.672	0.483	33.2	57.5	71.4	6.767
flat-VAE	0.872	0.755	0.617	23.7	48.2	69.0	6.793
hier-VAE-S	0.865	0.734	0.591	28.7	50.4	70.7	6.843
hier-VAE-D	0.851	0.723	0.579	30.5	53.2	72.6	6.926

Table 6: The *self-BLEU scores*, *unique n-gram percentages* and 2-*gram entropy score* of 1000 generated sentences. Models are trained on the Yelp Reviews dataset to evaluate the diversity of generated samples.

The Continuity of Latent Space Following (Bowman et al., 2016), we further measure the continuity of the learned latent space. Specifically, two points are randomly sampled from the prior latent space (denoted as A and B, respectively). Sentences are generated based on the equidistant intermediate points along the linear trajectory between A and B. As shown in Table 4, these intermediate samples are all realistic-looking reviews that are syntactically and semantically reasonable, demonstrating the smoothness of the learned VAE latent space. Interestingly, we even observe that the generated sentences gradually transit from positive to negative sentiment along the linear trajectory.

A	the service was great, the receptionist was very friendly and the place was clean, we waited for a while, and then our room was ready .
•	same with all the other reviews, this place is a good place to eat, i came here with a group of friends for a birthday dinner, we were hungry and decided to try it, we were seated promptly.
•	this place is a little bit of a drive from the strip, my husband and i were looking for a place to eat, all the food was good, the only thing i didn t like was the sweet potato fries.
•	this is not a good place to go, the guy at the front desk was rude and unprofessional, it s a very small room, and the place was not clean.
•	service was poor, the food is terrible, when i asked for a refill on my drink, no one even acknowledged me, they are so rude and unprofessional.
B	how is this place still in business, the staff is rude, no one knows what they are doing, they lost my business .

Table 4: With a trained *hier*-VAE-D model on the Yelp Review dataset, intermediate sentences are produced from linear transition between two points in the latent space.

To validate that the sentences are not generated by simply retrieving the training data, we further find the closest instance, among the entire training set, for each generated review. We demonstrate the details of the results in the supplementary material (Table 12).

Diversity of Generated Paragraphs We also evaluate the diversity of random samples from a trained model, since one model might generate realistic-looking sentences while suffering from severe mode collapse (*i.e.*, low diversity). Three metrics are employed to measure the diversity of generated paragraphs: Self-BLEU scores (Zhu et al., 2018), unique n-grams (Fedus et al., 2018) and entropy score (Zhang et al., 2018). Specifically, for a set of sampled sentences, the Self-BLEU metric calculates the BLEU score of each sample with respect to all other samples as the reference (the numbers over all samples are then averaged); the unique score computes the percentage of *unique* n-grams within all the generated reviews; and the entropy score measures how evenly the empirical n-gram distribution is for a given sentence, which does not depend on the size of testing data, as opposed to unique scores. Note that all three metrics are the lower, the better.

Here, we randomly sample 1000 reviews from each model, and the corresponding results are shown in Table 6. Note that a small self-BLEU score must be accompanied with a large BLEU score to justify the effectiveness of a model, *i.e.*, being able to generate realistic-looking as well as diverse samples. Among all the VAE variants, *hier*-VAE-D shows the smallest BLEU score and largest unique n-grams percentage, further demonstrating the advantages of making both the generative networks and latent variables hierarchical. As for AAE and ARAE, although they exhibit better diversity according to both metrics, their corpus-level BLEU scores are much worse relative to *hier*-VAE-D. Thus, we leverage human evaluation for further comparison.

Human Evaluation We conducted human evaluation using Amazon Mechanical Turk to assess the coherence and non-redundancy of the texts generated from our models in comparison to the

we study the effect of disorder on the dynamics of a two-dimensional electron gas in a two-dimensional optical lattice , we show that the superfluid phase is a phase transition , we also show that , in the presence of a magnetic field , the vortex density is strongly enhanced .
in this work we study the dynamics of a colloidal suspension of frictionless , the capillary forces are driven by the UNK UNK , when the substrate is a thin film , the system is driven by a periodic potential , we also study the dynamics of the interface between the two different types of particles .
the problem of finding the largest partition function of a quantum system is equivalent to find the optimal value of the number of states , which is the most important example of the first order approximation of the ising model , the algorithm is based on the computation of the partition function , the results are compared with the results of the monte carlo simulations .

Table 7: Generated samples from *hier*-VAE-D (trained on the arXiv abstract dataset).

baselines, which is difficult to measure based on automated metrics. Given a pair of generated reviews, the judges are asked to select their preferences (no difference between the two reviews is also an option) according to the following four evaluation criteria: *fluency & grammar* (G), *consistency* (C), *non-redundancy* (N), and *overall* (O). Details of the evaluation are provided in the supplementary material. As shown in Table 8, *hier*-VAE generates superior human-looking samples compared to *flat*-VAE on the Yelp Reviews dataset. Even though both models underperfom when compared against the ground-truth real reviews, *hier*-VAE was rated higher in comparison to *flat*-VAE (raters find *hier*-VAE closer to human-generated than the *flat*-VAE) in all the criteria evaluation criteria. We further compare our methods against AAE (the same data preprocessing steps and hyperparameters are employed). The results show that *hier*-VAE again produces more grammatically-correct and semantically-coherent samples relative to the AAE baseline.

4.4 CONDITIONAL PARAGRAPH GENERATION

Title: *Magnetic quantum phase transitions of the antiferromagnetic - Heisenberg model*	**Title**: *Kalman Filtering With UNK Over Wireless UNK Channels*
We study the phase diagram of the model in the presence of a magnetic field, The model is based on the action of the Polyakov loop, We show that the model is consistent with the results of the first order perturbation theory.	The Kalman filter is a powerful tool for the analysis of quantum information, which is a key component of quantum information processing, However, the efficiency of the proposed scheme is not well understood .

Table 9: Conditionally generated paper abstracts based upon a title (trained with the arXiv data).

We further evaluate the proposed VAE model on a conditional generation task. Specifically, we consider the task of generating abstract of a paper based on the corresponding title. The same arXiv dataset is utilized, where title and abstract are given as paired text sequences. The title is used as input of the inference network. For the generative network, instead of reconstructing the same input (*i.e.*, title), the paper abstract is employed as the target for decoding. We compare the *hier*-VAE-D model against *hier*-LM. We observe that the *hier*-VAE-D model achieves a test perplexity of 55.7 (with a KL term of 2.57), which is smaller that the test perplexity of *hier*-LM (58.1). This indicates that the information from the title has indeed been leveraged by the generative network to facilitate the decoding process. In table 9 we show two generated samples from the *hier*-VAE-D model.

Model	G %	C %	N %	O %
hier-VAE	52.0	55.0	53.7	60.0
flat-VAE	30.0	33.0	27.7	32.3
hier-VAE	75.3	86.0	76.7	86.0
AAE	13.3	10.3	15.0	12.0
flat-VAE	19.7	18.7	14.3	19.0
Real data	61.7	74.7	74.3	77.7
hier-VAE	28.0	26.3	25.0	30.3
Real data	48.6	58.7	49.0	61.3

Table 8: A Mechanical Turk blind heads-up evaluation between pairs of models trained on the Yelp Reviews dataset. From columns 2-5: Grammaticality(**G**), Consistency (**C**), Non-Redundancy(**N**), Overall (**O**).

5 CONCLUSION

We introduced a hierarchically-structured variational autoencoder for long text generation. A hierarchical LSTM generative network is employed, which models the semantic coherence at both the word- and sentence-levels. As a result, the VAE model is endowed with stronger *plan-ahead* capability, and the latent variable tends to encode *global* features that are more useful for the decoding/generating process. To mitigate the "posterior collapse" issue, a hierarchy of stochastic layers is further utilized, where the priors of the latent variables are learned from the data. Consequently, more informative latent codes are manifested, indicated by a larger KL loss term yet smaller variational lower bound. More importantly, the generated samples from the proposed model also exhibit superior quality relative to those from several baseline methods (according to automatic metrics). Human evaluations further demonstrate that the samples from *hier*-VAE are less repetitive and more semantically-consistent.

REFERENCES

Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, Manjunath Kudlur, Josh Levenberg, Rajat Monga, Sherry Moore, Derek Gordon Murray, Benoit Steiner, Paul A. Tucker, Vijay Vasudevan, Pete Warden, Martin Wicke, Yuan Yu, and Xiaoqiang Zhang. Tensorflow: A system for large-scale machine learning. In *OSDI*, 2016.

Hareesh Bahuleyan, Lili Mou, Olga Vechtomova, and Pascal Poupart. Variational attention for sequence-to-sequence models. In *COLING*, 2018.

Samuel R. Bowman, Luke Vilnis, Oriol Vinyals, Andrew M. Dai, Rafal Józefowicz, and Samy Bengio. Generating sentences from a continuous space. In *CoNLL*, 2016.

Asli Celikyilmaz, Antoine Bosselut, and Dinghan Shen. Arxgen: Corpus of arxiv articles for deep generative models. In *https://github.com/Microsoft/ARXGEN/tree/master/arxiv*, 2018.

Xi Chen, Diederik P Kingma, Tim Salimans, Yan Duan, Prafulla Dhariwal, John Schulman, Ilya Sutskever, and Pieter Abbeel. Variational lossy autoencoder. *arXiv preprint arXiv:1611.02731*, 2016.

Ondřej Cífka, Aliaksei Severyn, Enrique Alfonseca, and Katja Filippova. Eval all, trust a few, do wrong to none: Comparing sentence generation models. *arXiv preprint arXiv:1804.07972*, 2018.

Yuntian Deng, Yoon Kim, Justin Chiu, Demi Guo, and Alexander M. Rush. Latent alignment and variational attention. *CoRR*, abs/1807.03756, 2018.

William Fedus, Ian Goodfellow, and Andrew M Dai. Maskgan: Better text generation via filling in the __. *arXiv preprint arXiv:1801.07736*, 2018.

Ishaan Gulrajani, Kundan Kumar, Faruk Ahmed, Adrien Ali Taiga, Francesco Visin, David Vazquez, and Aaron Courville. Pixelvae: A latent variable model for natural images. *arXiv preprint arXiv:1611.05013*, 2016.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Zhiting Hu, Zichao Yang, Xiaodan Liang, Ruslan Salakhutdinov, and Eric P. Xing. Toward controlled generation of text. In *ICML*, 2017.

Lukasz Kaiser, Aurko Roy, Ashish Vaswani, Niki Parmar, Samy Bengio, Jakob Uszkoreit, and Noam Shazeer. Fast decoding in sequence models using discrete latent variables. In *ICML*, 2018.

Yoon Kim, Sam Wiseman, Andrew C. Miller, David A Sontag, and Alexander M. Rush. Semi-amortized variational autoencoders. In *ICML*, 2018.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *CoRR*, abs/1412.6980, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Jiwei Li, Minh-Thang Luong, and Daniel Jurafsky. A hierarchical neural autoencoder for paragraphs and documents. In *ACL*, 2015.

Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, and Ian Goodfellow. Adversarial autoencoder. *CoRR*, 2015.

Yishu Miao, Lei Yu, and Phil Blunsom. Neural variational inference for text processing. In *ICML*, 2016.

Tomáš Mikolov, Stefan Kombrink, Lukáš Burget, Jan Černockỳ, and Sanjeev Khudanpur. Extensions of recurrent neural network language model. In *ICASSP*, pp. 5528–5531. IEEE, 2011.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting on association for computational linguistics*, pp. 311–318. Association for Computational Linguistics, 2002.

Adam Roberts, Jesse Engel, Colin Raffel, Curtis Hawthorne, and Douglas Eck. A hierarchical latent vector model for learning long-term structure in music. In *ICML*, 2018.

David E Rumelhart, Geoffrey E Hinton, and Ronald J Williams. Learning representations by back-propagating errors. *nature*, 323(6088):533, 1986.

Stanislau Semeniuta, Aliaksei Severyn, and Erhardt Barth. A hybrid convolutional variational autoencoder for text generation. In *EMNLP*, 2017.

Iulian Serban, Alessandro Sordoni, Ryan Lowe, Laurent Charlin, Joelle Pineau, Aaron C. Courville, and Yoshua Bengio. A hierarchical latent variable encoder-decoder model for generating dialogues. In *AAAI*, 2017.

Dmitriy Serdyuk, Nan Rosemary Ke, Alessandro Sordoni, Christopher Joseph Pal, and Yoshua Bengio. Twin networks: Using the future as a regularizer. *CoRR*, abs/1708.06742, 2017.

Harshil Shah and David Barber. Generative neural machine translation. *arXiv preprint arXiv:1806.05138*, 2018.

Dinghan Shen, Yizhe Zhang, Ricardo Henao, Qinliang Su, and Lawrence Carin. Deconvolutional latent-variable model for text sequence matching. In *AAAI*, 2018.

Casper Kaae Sønderby, Tapani Raiko, Lars Maaløe, Søren Kaae Sønderby, and Ole Winther. Ladder variational autoencoders. In *Advances in neural information processing systems*, pp. 3738–3746, 2016.

Nitish Srivastava, Geoffrey E. Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *Journal of Machine Learning Research*, 15:1929–1958, 2014.

Zichao Yang, Diyi Yang, Chris Dyer, Xiaodong He, Alex Smola, and Eduard Hovy. Hierarchical attention networks for document classification. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 1480–1489, 2016.

Zichao Yang, Zhiting Hu, Ruslan Salakhutdinov, and Taylor Berg-Kirkpatrick. Improved variational autoencoders for text modeling using dilated convolutions. In *ICML*, 2017.

Lantao Yu, Weinan Zhang, Jun Wang, and Yong Yu. Seqgan: Sequence generative adversarial nets with policy gradient. In *AAAI*, 2017.

Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In *NIPS*, pp. 649–657, 2015.

Yizhe Zhang, Zhe Gan, Kai Fan, Zhi Chen, Ricardo Henao, Dinghan Shen, and Lawrence Carin. Adversarial feature matching for text generation. In *ICML*, 2017.

Yizhe Zhang, Michel Galley, Jianfeng Gao, Zhe Gan, Xiujun Li, Chris Brockett, and Bill Dolan. Generating informative and diverse conversational responses via adversarial information maximization. In *NIPS*, 2018.

Junbo Jake Zhao, Yoon Kim, Kelly Zhang, Alexander M. Rush, and Yann LeCun. Adversarially regularized autoencoders. In *ICML*, 2018a.

Tiancheng Zhao, Ran Zhao, and Maxine Eskénazi. Learning discourse-level diversity for neural dialog models using conditional variational autoencoders. In *ACL*, 2017.

Tiancheng Zhao, Kyusong Lee, and Maxine Eskenazi. Unsupervised discrete sentence representation learning for interpretable neural dialog generation. *arXiv preprint arXiv:1804.08069*, 2018b.

Yaoming Zhu, Sidi Lu, Lei Zheng, Jiaxian Guo, Weinan Zhang, Jun Wang, and Yong Yu. Texygen: A benchmarking platform for text generation models. *arXiv preprint arXiv:1802.01886*, 2018.

Supplementary Material for "Hierarchically-Structured Variational Autoencoder for Long Text Generation"

A   DATASETS & EXPERIMENTAL DETAILS

In the following, we provide details of dataset preprocessing as well as the experimental setups used in the experiments. For both Yelp Reviews and ArXiv Abstracts datasets, we truncate the original paragraph to the first five sentences (split by punctuation marks including *comma*, *period* and *point* symbols), where each sentence contains at most 25 words. Therefore, each paragraph has at most 125 words. We further remove those sentences that contain of less than 30 words. The statistics of both datasets are detailed in Table 10. Note that the average length of paragraphs considered here are much larger than previous generative models for text (Bowman et al., 2016; Yu et al., 2017; Hu et al., 2017; Zhang et al., 2017), since these works considered text sequences that contain only one sentence with at most twenty words.

Dataset	Train	Test	Vocabulary	Average Length
Yelp Reviews	244748	18401	12461	48
ArXiv Abstracts	504268	28016	32487	59

Table 10: Summary statistics for the datasets used in the generic text generation experiments.

To abstract meaningful representations from the input sentences, we employ a hierarchical CNN architecture as the inference/encoder network. Specifically, a sentence-level CNN encoder is first applied to each sentence to obtain a fixed-length vector. Afterwards, a paragraph-level CNN encoder is utilized to aggregate the vectors with respect to all sentences. In the single-variable *hier*-VAE, the paragraph feature vector is fed into linear layers to infer the mean and variance of the latent variable z. For the double-variable case, the feature vector is further transformed with two MLP layers, and then is used to compute the mean and variance of the top-level latent variable. The dimension of latent variable z is set to 300. The dimensions of both the sentence-level and word-level LSTM decoders are set to 512.

The model is trained using Adam (Kingma & Ba, 2014) with a learning rate of 3×10^{-4} for all parameters, with a decay rate of 0.99 for every 3000 iterations. Dropout (Srivastava et al., 2014) is employed on both word embedding and latent variable layers, with rates selected from $\{0.3, 0.5, 0.8\}$ on the validation set. We set the mini-batch size to 128. Following (Bowman et al., 2016) we adopt the KL cost annealing strategy to stabilize training: the KL cost term is increased linearly to 1 until 10,000 iterations. All experiments are implemented in Tensorflow (Abadi et al., 2016), using one NVIDIA GeForce GTX TITAN X GPU with 12GB memory.

B ADDITIONAL GENERATED SAMPLES FROM *hier*-VAE-D VS *flat*-VAE

We provide additional examples for the comparison between *hier*-VAE-D vs *flat*-VAE in Table 11, as a continuation of Table 3.

hier-VAE	*flat*-VAE
i would give this place zero stars if i could , the guy who was working the front desk was rude and unprofessional , i have to say that i was in the wrong place , and i m not sure what i was thinking , this is not a good place to go to .	this is a great little restaurant in vegas , i had the shrimp scampi and my wife **had the shrimp scampi**, and my husband **had the shrimp scampi** , it was delicious , i **had the shrimp scampi** which was delicious and seasoned perfectly .
my wife and i went to this place for dinner , we were seated immediately , the food was good , i ordered the shrimp and grits , which was the best part of the meal .	**very good chinese food, very good chinese food**, the service was very slow, i guess that s what they were doing, very slow to get a quick meal.
we got a gift certificate from a store, we walked in and were greeted by a young lady who was very helpful and friendly, so we decided to get a cut, I was told that they would be ready in 15 minutes.	we go there for eakfast, i ve been here 3 times and it s always good, the hot dogs are delicious, and **the hot dogs are delicious**, i ve been there for eakfast and it is so good.
the place was packed, chicken was dry, tasted like a frozen hot chocolate, others were just so so, i wouldn t recommend this place.	do not go here, their food is terrible, they were very slow, in my opinion.
went today with my wife, and received a coupon for a free appetizer, we were not impressed, we both ordered the same thing, and **we were not impressed**.	the wynn is a great place to eat, the food was great and i had the linguine, and it was so good, i **had the linguine** and clams, (i was so excited to try it).
recently visited this place for the first time, i live in the area and have been looking for a good local place to eat, we stopped in for a quick bite and a few beers, always a nice place to sit and relax, wonderful and friendly staffs.	i came here for a quick bite before heading to a friend s recommendation, the place was packed, but the food was delicious, i am a fan of the place, and the place is **packed** with a lot of people.
best haircut i ve had in years, friendly staff and great service, he made sure that i was happy with my hair cut, just a little pricey but worth it, she is so nice and friendly.	had a great experience here today, the delivery was friendly and efficient and the food was good, i would recommend this place to anyone who will work in the future, will be back again.
great place to go for a date night, first time i went here, service is good, the staff is friendly, 5 stars for the food.	best place to get in vegas, ps the massage here is awesome, if you want to spend your money, then go there, ps **the massage is great**.

Table 11: Samples randomly generated from *hier*-VAE-D and *flat*-VAE, which are both trained on the Yelp review dataset. The repetitive patterns within the generated reviews are highlighted.

C RETRIEVED CLOSEST TRAINING INSTANCES OF GENERATED SAMPLES (YELP REVIEWS DATASET)

We provide samples of retrieved instances from the Yelp Review training dataset which are closest to the generated samples. Table 12 shows the closest training samples of each generated Yelp review. The first column indicates the intermediate generated sentences produced from linear transition from a point A to another point B in the prior latent space. The second column on the right are the real sentences retrieved from the training set that are closest to the ones generated on the left (determined by BLEU-2 score). We can see that the retrieved training data is quite different from the generated samples, indicating that our model is indeed generating samples that it has never seen during training.

	Generated samples	**Closest instance (in the training dataset)**
A	the service was great, the receptionist was very friendly and the place was clean, we waited for a while, and then our room was ready .	i ve only been here once myself , and i wasn t impressed , the service was great , staff was very friendly and helpful , we waited for nothing
•	same with all the other reviews, this place is a good place to eat, i came here with a group of friends for a birthday dinner, we were hungry and decided to try it, we were seated promptly.	i really love this place , red robin alone is a good place to eat , but the service here is great too not always easy to find , we were seated promptly , ought drinks promptly and our orders were on point .
•	this place is a little bit of a drive from the strip, my husband and i were looking for a place to eat, all the food was good, the only thing i didn t like was the sweet potato fries.	after a night of drinking , we were looking for a place to eat , the only place still open was the grad lux , its just like a cheesecake factory , the food was actually pretty good .
•	this is not a good place to go, the guy at the front desk was rude and unprofessional, it s a very small room, and the place was not clean.	the food is very good , the margaritas hit the spot , and the service is great , the atmosphere is a little cheesy but overall it s a great place to go .
•	service was poor, the food is terrible, when i asked for a refill on my drink, no one even acknowledged me, they are so rude and unprofessional.	disliked this place , the hostess was so rude , when i asked for a booth , i got attitude , a major .
B	how is this place still in business, the staff is rude, no one knows what they are doing, they lost my business .	i can t express how awful this store is , don t go to this location , drive to any other location , the staff is useless , no one knows what they are doing .

Table 12: Using the *hier*-VAE-D model trained on the Yelp Review dataset, intermediate sentences are produced from linear transition between two points (**A** and **B**) in the prior latent space. Each sentence in the left panel is generated from a latent point on a linear path, and each sentence on the right is the closet sample to the left one within the entire training set (determined by BLEU-2 score).

D HUMAN EVALUATION SETUP AND DETAILS

Some properties of the generated paragraphs, such as (topic) coherence or non-redundancy, can not be easily measured by automated metrics. Therefore, we further conduct human evaluation based on 100 samples randomly generated by each model (the models are trained on the Yelp Reviews dataset for this evaluation). We consider *flat*-VAE, adversarial autoencoders (AAE) and real samples from the test set to compare with our proposed *hier*-VAE-D model. The same hyperparameters are employed for the different model variants to ensure fair comparison. We evaluate the quality of these generated samples with a blind heads-up comparison using Amazon Mechanical Turk. Given a pair of generated reviews, the judges are asked to select their preferences ("no difference between the two reviews" is also an option) according to the following 4 evaluation criteria: (1) *fluency & grammar*, the one that is more grammatically correct and fluent; (2) *consistency*, the one that depicts a sequence of topics and events that is more consistent; (3) *non-redundancy*, the one that is better at non-redundancy (if a review repeats itself, this can be taken into account); and (4) *overall*, the one that more effectively communicates reasonable content. These different criteria help to quantify the impact of the hierarchical structures employed in our model, while the non-redundancy and consistency metrics could be especially correlated with the model's plan-ahead abilities. The generated paragraphs are presented to the judges in a random order and they are not told the source of the samples. Each sample is rated by three judges and the results are averaged across all samples and judges.