SAGE: Structure Aware Graph Expansion for Retrieval of Heterogeneous Data

Abstract

Retrieval-augmented question answering over heterogeneous corpora requires *connected* evidence across text, tables, and graph nodes. While entity-level knowledge graphs support structured access, they are costly to construct and maintain, and inefficient to traverse at query time. In contrast, standard retriever-reader pipelines use flat similarity search over independently chunked text, missing multi-hop evidence chains across modalities. We propose SAGE (**S**tructure **A**ware **G**raph **E**xpansion) framework that (i) constructs a chunk-level graph *offline* using metadata-driven similarities with percentile-based pruning, and (ii) performs *online* retrieval by running an initial baseline retriever to obtain k seed chunks, expanding first-hop neighbors, and then filtering the neighbors using dense+sparse retrieval, selecting k' additional chunks. We instantiate the initial retriever using hybrid dense+sparse retrieval for implicit cross-modal corpora and SPARK (**S**tructure Aware **P**lanning **A**gent for **R**etrieval over **K**nowledge Graphs) an agentic retriever for explicit schema graphs. On OTT-QA and STaRK, SAGE improves retrieval recall by 5.7 and 8.5 points over baselines.

1 Introduction

Retrieval-augmented generation (RAG) (Lewis et al., 2020) grounds large language models in external knowledge and has become a standard paradigm for question answering over domain-specific corpora. Most RAG systems rely on flat retrieval, where independently indexed text chunks are retrieved using sparse, dense, or hybrid similarity search (Mandikal and Mooney, 2024; Arabzadeh et al., 2021; Zhang et al., 2024; Chen et al., 2022). While effective for simple text-centric queries, this design struggles with complex reasoning over heterogeneous data that includes documents, tables, and structured metadata.

Flat retrieval treats each chunk independently, ignoring structural dependencies that often con-

Figure 1: Illustration of SAGE's seed→expand retrieval: starting from an initial relevant chunk, graph expansion retrieves a connected neighbor containing the missing movie/director evidence that flat retrieval fails to surface.

nect relevant evidence across documents or modalities. As a result, intermediate evidence that is weakly related to the query in embedding space but structurally connected to relevant content is frequently missed. For example, answering a question about a television show starring Trevor Eyster and its source book requires linking cast information, adaptation metadata, and author details, connections that are unlikely to be recovered through similarity search alone.

To address these limitations, recent work augments RAG with graph-based representations that model relationships across heterogeneous data and enable multi-hop retrieval (Edge et al., 2024a; Jimenez Gutierrez et al., 2024; Mavromatis and Karypis, 2024). Prior approaches fall into two categories: *knowledge graphs* (KGs) and *similarity graphs*. KGs encode structured knowledge as typed entity-relation triples and support precise symbolic reasoning via traversal or query languages such as Cypher (Francis et al., 2018), and SPARQL (201, 2013), but require costly entity extraction and schema alignment, making them suitable for domains with stable schemas. Similarity graphs represent text chunks, table segments, or semi-structured nodes with edges induced by embedding similarity, naturally supporting heterogeneous data without explicit entity extraction.

However, their effectiveness depends critically on edge construction: overly dense graphs in-

Figure 2: Overview of SAGE. **Offline:** we semantically chunk documents and tables into nodes and create edges using metadata-driven similarity (e.g., title, topic, content, entities) with percentile-based pruning. **Online:** a baseline retriever returns k seed nodes, we expand to n first-hop neighbors in the offline graph, and re-rank to select k' additional nodes, yielding a final context of $k+k'$.

troduce spurious neighbors, while overly sparse graphs hinder multi-hop reasoning. Node granularity also impacts expressiveness, connectivity, and computational cost. **Entity-level graphs** capture fine-grained entities, supporting factoid queries but struggling with contextual or aggregate questions. **Community-level graphs** group entities or documents into clusters, improving scalability but reducing detail. These trade-offs motivate intermediate representations that balance granularity, scalability, and retrieval effectiveness.

We address this gap by introducing a chunk-level graph that improves recall through structure-aware expansion over semantically coherent units. Instead of retrieving many independent chunks, we select a small set of seed nodes and expand them via graph traversal, surfacing evidence that may be weakly similar to the query but strongly connected through document structure, metadata, or shared context. Each node represents a text or table segment, preserving local coherence without requiring entity extraction. The graph is built offline, remains retriever-agnostic, and enables efficient multi-hop evidence aggregation across heterogeneous corpora. Our contributions are as follows:

• We introduce SAGE, a **structure-aware retrieval framework** that augments flat retrieval with chunk-level graph expansion, enabling neighbor-aware reasoning while remaining compatible with existing retrievers and offering a practical path when full KGs are infeasible but structural signals remain in metadata and chunk links.
• Through **similarity-induced graph expansion**, SAGE consistently improves recall over strong flat

hybrid baselines under fixed budgets (+5.7 on OTT-QA, +8.5 on STaRK).
• For explicit schema graphs, we further propose SPARK, a retrieval agent that performs **schema-constrained expansion**, enforcing structural validity during traversal and outperforming naive dense expansion.

2 SAGE **Approach**

Given a corpus represented as a graph $G = (V, E)$ with node content $\text{text}(v)$ and optional metadata $\text{meta}(v)$, the retrieval goal for a query q is to return a ranked list of evidence nodes $R_k(q)$ such that relevant evidence appears in the top-k positions.

2.1 Offline Graph Construction

We construct heterogeneous graphs G over document chunks and table segments (for document graphs) or preserve native entity-relation schemas (for KGs). The graph construction process is dataset-agnostic and occurs offline before query time.

A. Data Processing and Node Creation

1. Semantic chunking of documents. We segment each document into a sequence of sentences and embed overlapping context windows $w_i = [s_{i-1}, s_i, s_{i+1}]$ (with boundary truncation) using a sentence encoder (Reimers and Gurevych, 2019). Let $\mathbf{h}_i$ denote the embedding of w_i. We compute cosine similarity between adjacent windows as $s_i = \cos(\mathbf{h}_i, \mathbf{h}_{i+1})$.

We introduce a boundary at indices where local coherence drops, using a percentile-based rule over $\{s_i\}$: letting $\theta = \text{Percentile}_{20}(\{s_i\})$ (equivalently,

selecting the top-80% "drop" positions), we split at all i such that $s_i \leq \theta$. After chunking, we use an LLM to generate per-chunk metadata (topic, title, and entities) for downstream graph construction.

2. Table segmentation. We use an LLM to generate a short table description and column descriptions; these become part of the table-chunk metadata. For each table, we retain table title/description, column headers, and column descriptions, and 5–10 rows per segment to preserve vertical context while keeping segments within a bounded context size.

3. Semi-structured nodes. For semi-structured nodes, we treat each object as a "chunk" and construct metadata from its textual fields (e.g., name/title and long-form descriptions). These metadata fields are used to build downstream graph connectivity. We discuss metadata quality control, hidden LLM costs, and safeguards against generic generations in Appendix C.2.

B. Edge creation

Graph construction via metadata similarities. We embed these metadata fields using a Sentence-Transformer encoder and connect nodes based on modality-specific similarity signals: (1) **Document–Document** edges capture topic-topic similarity, content-content similarity, and entity overlap; (2) **Table–Table** edges capture column-column similarity, title-title similarity, and entity overlap; (3) **Table–Document** edges capture content-column similarity, topic-title similarity, and entity overlap; (4) **Semi-Structured Chunk** edges connect objects via similarity over their descriptive metadata.

We only keep a similarity edge when its metadata similarity exceeds the 95th percentile of the empirical distribution, which maintains sparsity and reduces dense-neighborhood noise. For large corpora, this threshold can be estimated using ANN-based candidate neighborhoods; further analysis is provided in the Appendix. We also preserve parent/structural links (e.g., chunks from the same source) and retain explicit schema edges when available. Figure 2 illustrates the resulting graph structure.

Edge metadata for traversal. Edges store lightweight metadata to guide controlled graph traversal. Table–table edges record joinable column names, document–document edges record shared entities and confidence scores, and table–document edges record shared entities and, when available, row or column references. This metadata allows multi-hop reasoning to prioritize neighbors that align with query entities or satisfy structural constraints.

2.2 Online Retrieval

At query time, we employ a two-stage retrieval strategy: (i) **initial baseline retrieval** to obtain k seed nodes, and (ii) **graph-based neighbor expansion and pruning** to select k' additional nodes. The baseline retrieval method differs between document graphs and KGs due to their distinct structural properties: hybrid sparse-dense retrieval works well for OTT-QA's text/table data, while SPARK is necessary for STaRK's schema-rich KGs (as hybrid retrieval performs poorly on STaRK, shown in Table 6).

A. Initial baseline retrieval.

1. Similarity graphs For document graphs (tables and text chunks), we use a hybrid sparse-dense retrieval baseline. We compute BM25 (Robertson et al., 2009) scores for lexical matching and cosine similarity over dense embeddings for semantic matching, then combine these scores to select the top-k seed nodes. This approach works well when chunks contain sufficient textual content and when relevance can be determined from surface-level semantic similarity.

2. Semi-Structured Knowledge Bases (SKBs) For semi-structured knowledge bases with explicit schemas (i.e., graphs whose nodes are associated with textual fields), BM25 and cosine similarity are limited. They ignore edge types and typed relations, cannot reason over multi-hop paths, and exhibit type bias, often retrieving nodes of the same type rather than the correct entities required by the query.

Figure 3: SKB baseline initial retrieval: the question and schema metadata guide an LLM agent to generate a retrieval plan interleaving HNSW semantic search with Cypher symbolic queries.

To address this, we introduce SPARK, an LLM-based agent for SKB retrieval. Given a question, the agent accesses entity schemas, relations, and two retrieval tools, and generates a multi-step plan alternating between: **(1) Semantic Candidate Generation**: retrieving nodes via HNSW (Malkov and Yashunin, 2018) based on textual similarity and attributes; and **(2) Structural Expansion**: traversing edges with Cypher queries in Neo4j (Neo4j, Inc., 2026), constrained by entity types and relations to enforce multi-hop correctness.

We execute the generated plan and return the top-k retrieved nodes as seeds. A fallback to BM25 and cosine similarity is used when the plan returns no results to ensure robustness, as the agent may fail to generate correct multi-step queries for certain questions or encounter nodes with sparse textual content. This combination balances the precision of schema-aware traversal with the coverage of traditional retrieval methods.

B. Graph-based neighbor expansion and pruning. Regardless of the baseline, we apply a unified graph expansion strategy to both documents and KGs. SPARK is simply one possible seed retriever specialized for schema-rich KGs; the SAGE expansion operator itself remains invariant across all datasets and seed retrievers. Given the k seed nodes from initial retrieval: (1) **Neighbor Expansion:** collect all first-hop neighbors of the k seeds from the pre-built graph G, producing n candidate nodes; (2) **Neighbor Pruning:** re-rank the n candidates using BM25 and dense embedding similarity with respect to the query, and select the top-k' neighbors; (3) **Final Context:** return the union of the original k seeds and the k' neighbors, yielding $k+k'$ total nodes. Because expansion is query-conditioned and followed by query-aware pruning, highly connected hub nodes do not dominate retrieval unless they are genuinely relevant to the query, hence preventing topic drift.

Listing 1: Unified $k+k'$ retrieval (pseudo-code)

```
Input: query q, budgets k,k', baseline
    retriever BL, graph G
S = TopK(BL(q), k)
N = OneHopNeighbors(G, S)
R = TopK(BM25DenseRank(q, N), k')
Return Union(S, R)
```

This approach is more efficient than computing full node-to-node similarity at runtime. Pre-computed connections capture bridging evidence, reduce noise by focusing on relevant neighbors, preserve multi-hop context, and scale to large graphs without exhaustive pairwise comparisons. While the online seed-expand-prune operator follows graph reranking (Peng et al., 2025), our novelty lies in the granularity of the graph and the construction methodology without any fine-tuned traversal.

3 Experiments

Datasets. We evaluate on OTT-QA(Chen et al., 2020) and STaRK (Wu et al., 2024b). OTT-QA is derived from Wikipedia and includes both text passages and tables, where each table is originally linked to a set of documents. We use the dev split to construct our graph and rebuild all connections from scratch instead of using the predefined links.

STaRK contains semi-structured knowledge graphs across three domains: AMAZON, MAG, and PRIME. We add similarity edges only for nodes with rich textual descriptions (e.g., product details, paper abstracts), while atomic entities with minimal text are handled through lexical Cypher matching. Table 1 summarizes the resulting graph statistics. Each STaRK subset provides synthetic and human evaluation splits. Synthetic queries are generated using relational templates and LLM-extracted properties, while human queries reflect more realistic language and ambiguity.

Dataset	#Nodes	#Node types	#Edges	#Edge Types
OTT-QA	22,886	2	751,836	3
STaRK				
AMAZON	13,920,204	2	40,876,246	4
MAG	1,872,968	4	36,853,636	5
PRIME	129,375	10	9,825,282	19

Table 1: Overview of datasets used in our experiments. Node and edge counts are total numbers in the graph. Node and edge types indicate schema diversity.

These datasets represent two regimes of heterogeneous data. In OTT-QA, structure is implicit, with links induced from similarity and metadata overlap. In STaRK, structure is explicit, with typed entities and schema-defined relations. This contrast tests whether SAGE adapts to different graph topologies.

Further details on node and edge types are in Appendix A .

Baselines for OTT-QA Prior work mainly targets table-level retrieval, such a **CRAFT** (Singh et al., 2025) and **OTTeR** (Huang et al., 2022), rather than chunk-level retrieval. Many methods rely on predefined table-document links, including **COS** (Ma et al., 2023), **RINK** (Park et al., 2023), **CARP** (Zhong et al., 2022), and **Dual Reader-Parser**. Methods that ignore these links use different setups: **ARM** (Chen et al., 2025b) adopts

gold-set evaluation, while **CORE** (Ma et al., 2022) attempts to reconstruct the links, preventing direct comparison. Our extended baseline retrieves the same number of chunks without graph expansion.

Baselines for STaRK We compare our method with the following retrieval baselines: 1) Dense retrievers: (**ada-002**, **multi-ada-002**, **DPR** (Karpukhin et al., 2020)). 2) Sparse retriever: (**BM25**). 3) Hybrid retrievers: (**BM25+Dense**, **4StepFocus** (Boer et al., 2024), **FocusedR** (Boer et al., 2025)). 4) Graph-based retrieval: (**QA-GNN** (Yasunaga et al., 2021)). 5) Query expansion methods: (**HyDE** (Gao et al., 2023), **AGR** (Chen et al., 2024), **RAR** (Shen et al., 2024), **KAR** (Xia et al., 2024)). 6) Agentic systems: (**ReACT** (Yao et al., 2022), **Reflexion** (Shinn et al., 2023)). 7) Fine-tuned retrievers: (**mFAR** (Li et al., 2024a), **MoR** (Lei et al., 2025), **AvaTaR** (Wu et al., 2024a)). Further details on these baselines are in Appendix B.

Evaluation Metrics. For **OTT-QA**, we report Recall@k, measuring how many relevant passages are retrieved. For **STaRK**, we follow the original evaluation and report Hit@1, Hit@5, Recall@20, and MRR to capture ranking quality and retrieval coverage.

3.1 OTT-QA: Hybrid Text-Table Results

Figure 4: OTT-QA retrieval Recall@k . Extended BL is a flat hybrid retriever combining BM25 and dense embeddings. BL+Graph retrieves k_1 seeds with BL and adds k_2 one-hop neighbors from the induced graph. Arrows annotate the absolute gain at each k.

Graph-based retrieval improves Recall@k across all retrieval sizes. Graph-based retrieval improves Recall@k across all retrieval sizes (Figure 4) by incorporating one-hop neighbors from the chunk-level graph, which surfaces additional relevant nodes beyond those found through flat similarity-based retrieval. The gains are most pronounced for smaller retrieval sets: recall improves by 5.7 points at $k = 20$ compared to 2.8 points at $k = 100$, indicating that structural connections are

particularly valuable when retrieval is constrained and fewer items are selected.

Effect of metadata on graph building We analyze metadata similarities to guide graph construction. Table-table pairs show strong correlation between title and description similarity (0.846 , Table 17)), while document-document pairs align across topic and content similarity (0.650, Table 18). Cross-modal document-table correlations range from 0.517 to 0.691 (Table 19). These patterns suggest that similarity along one metadata dimension often predicts similarity along others, helping form coherent graph neighborhoods.

Similarity distributions are roughly bell-shaped with a high-end tail, emphasizing strongly related chunks. Because most chunks contain a single entity, entity overlap becomes a key bridge linking otherwise distinct topics. Retaining the top 5% of similarities preserves meaningful links without over-densifying the graph. Additional statistics, including metadata extraction cost, distributions, scatterplots, and correlation matrices, appear in Appendix C.

Similarity metric	doc–doc	doc–tab	tab–tab
topic_similarity	0.350	0.247	0.263
content_similarity	0.389	0.350	0.404
column_similarity	0.000	0.242	0.409
entity_relationship_overlap	0.013	0.000	0.000
entity_count	0.682	0.477	0.849
topic_title_similarity	0.000	0.221	0.000
topic_summary_similarity	0.000	0.236	0.000
title_similarity	0.000	0.000	0.239
description_similarity	0.000	0.000	0.262

Table 3: Cross-modal similarity statistics across document and table pairs in OTT-QA.

Structural effects of metadata signals Table 3 further reveals three cross-modal structural effects. **1) Entity-centric connectivity dominates but varies by modality:** tables form dense entity hubs, while text supports more semantically blended neighborhoods. **2) Modalities encode complementary signals:** text captures narrative structure, whereas tables provide schema-level alignment. **3) Cross-modal alignment emerges from signal composition:** document-table links arise from aggregating multiple weak but consistent signals rather than a single dominant metric.

3.2 STaRK: Semi-Structured Data Results

Effect of graph on agentic retriever Similar to our observations on OTT-QA, graph-based retrieval also improves Recall@20 for agentic retrievers across all STaRK datasets (Table 2). By

Category	Method	AMAZON		MAG		PRIME	
		Human $n=81$	Synthetic $n=1638$	Human $n=84$	Synthetic $n=2664$	Human $n=98$	Synthetic $n=2801$
Dense	ada-002	35.46	53.29	35.95	48.36	41.09	36.00
	multi-ada-002	40.22	55.12	39.85	50.80	47.21	38.05
	DPR	15.23	44.49	25.00	42.11	10.69	30.13
Sparse	BM25	15.23	53.77	32.46	45.69	42.32	31.25
Structural	QAGNN	21.54	52.05	28.76	46.97	17.62	29.63
Hybrid	4StepFocus	–	56.20	–	65.80	–	55.90
	FocusedR.	–	56.00	–	**78.80**	–	**65.50**
	Dense+BM25	24.30	51.49	46.64	51.49	52.65	39.11
Query Expansion	HyDe	39.25	53.71	37.23	50.02	47.70	43.55
	RAR	36.15	54.63	35.19	50.87	49.01	44.50
	AGR	37.27	53.38	37.23	51.89	49.65	46.63
	KAR	40.62	57.29	46.60	60.28	59.90	50.81
Agentic	ReACT	35.95	50.81	35.95	47.03	41.09	33.63
	Reflexion	35.95	54.70	35.95	49.55	41.09	38.52
Finetuned	AvaTaR	42.43	60.57	35.94	49.70	53.34	42.23
	mFAR	–	58.50	–	71.70	–	68.30
	MoR	–	59.90	–	75.00	–	63.50
SAGE (Ours)	SPARK	33.56	53.95	53.51	66.40	63.56	57.64
	SPARK +SAGE +Edge	36.93	54.12	55.90	68.60	65.85	58.42
	SPARK +SAGE-Edge	**42.05**	**58.28**	**56.40**	70.10	**66.37**	60.98

Table 2: Recall@20 performance on Human and Synthetic queries across all STaRK datasets (AMAZON, MAG, PRIME). Highest non-finetuned method is bolded, second highest non-finetuned method is underlined. Note: FocusedR, 4StepFocus, mFAR, and MoR report results only on the Synthetic split; Human split results are not available from their publications or released artifacts.

expanding the retrieved set to include connected nodes, the graph surfaces additional relevant nodes that the base agent misses, leading to higher recall on both Human and Synthetic queries.

Are there dataset-specific patterns where graph augmentation helps more? Graph augmentation provides larger gains when nodes contain richer textual content. We compare two expansion policies: SPARK +SAGE-Edge skips neighbor expansion when Cypher queries specify explicit edges, while SPARK +SAGE +Edge always expands neighbors. On AMAZON, where nodes include detailed product metadata, SPARK +SAGE-Edge improves R@20 by +8.49 on Human queries and +4.33 on Synthetic queries. Datasets with sparser nodes, such as MAG and PRIME, show smaller gains of about 1-2 points. This suggests chunk-level graphs are most effective when nodes contain enough context to support multi-hop evidence chains that flat retrieval misses.

How does this baseline+graph compare vs other state of the art methods SPARK +SAGE-Edge substantially outperforms traditional baselines, including Dense, Sparse, and Query Expansion methods, across all datasets (Table 2), while matching the performance of finetuned approaches such as AvaTaR, mFAR, and MoR. FocusedR achieves higher scores on MAG and PRIME, where structured KG triples provide a strong signal, but

SPARK +SAGE-Edge performs best on AMAZON by leveraging rich node content for chunk-level expansion. Importantly, SPARK +SAGE-Edge requires only a single LLM call and one retrieval step, making it significantly faster and more practical for large-scale deployment than multi-iteration alternatives.

Method	#Retr.	#LLM	#Iter.	Set Join
4StepFocus	$1 + n$	2	n	Triplet cand.
FocusedR	$\geq 3+n$	3	$n_1 \times n_2$	Sym. cand
AvaTaR	n	$n+1$	n	–
KAR	$e+3$	2	1	–
ReACT	n	$n+1$	n	–
Reflexion	n	$(n+1)E+R$	$nE+R$	–
SAGE	**2**	**1**	**1**	–

Table 4: Theoretical runtime decomposition from method descriptions. #Retr. counts number of retrieval operations. n is a method-dependent number of reasoning steps. n_1, n_2 denote outer/inner iterations. e is the number of extracted entities. E and R denote episodes and calls. Set Join indicate candidate-neighborhood intersections.

How efficient is our Agentic approach vs other state of the art methods Table 4 highlights three common efficiency bottlenecks in existing retrieval methods: repeated LLM calls, iterative retrieval loops, and costly symbolic set joins. Methods such as ReACT, Reflexion, and AvaTaR perform stepwise reasoning with an LLM call at each step, increasing latency as steps grow. Hybrid approaches like 4StepFocus and FocusedR rely on repeated candidate pruning and set intersections, which

scale poorly with query complexity. KAR reduces LLM usage but still requires multiple dataset-wide retrievals. SPARK avoids these costs by using a single LLM call, one retrieval, and one graph expansion, with no iterative loops or symbolic joins. This fixed execution path significantly reduces latency and compute while maintaining competitive recall. Details of the complexity analysis appear in Appendix D.

3.3 Ablation Study

Sensitivity Analysis: Effect of percentile during edge creation We study how percentile-based pruning shapes graph connectivity in OTT-QA by controlling the trade-off between connectivity and noise when adding similarity edges.

We compare two strategies: **OR logic**, which retains edges satisfying any similarity criterion to encourage connectivity, and **AND logic**, which requires all criteria and heavily prunes the graph.

Percentile	Logic	Total Edges	% Cand.	Avg Deg.	Density
80	OR	1,240,504	39.5%	109.2	0.0048
85	OR	969,911	30.9%	85.4	0.0038
90	OR	669,992	21.3%	59.0	0.0026
95	**OR**	**344,955**	**11.0%**	**30.4**	**0.0013**
97	OR	206,461	6.6%	18.2	0.0008
99	OR	60,371	1.9%	5.3	0.0002
80	AND	150,973	4.8%	13.3	0.0006
85	AND	101,963	3.2%	9.0	0.0004
90	AND	63,042	2.0%	5.6	0.0002
95	AND	30,920	1.0%	2.7	0.0001
97	AND	21,553	0.7%	1.9	0.0001
99	AND	13,434	0.4%	1.2	0.0001

Table 5: Impact of pruning percentile and logical edge selection on graph sparsity.

Table 5 shows that AND logic yields very low average degrees (1.2-2.7), fragmenting graphs and hindering multi-hop traversal. We therefore use OR logic, where the 95th percentile threshold balances coverage and sparsity: stricter thresholds fragment neighborhoods, while looser thresholds increase noise. This results in roughly 5-25 effective neighbors per chunk, preserving connectivity and keeping reranking tractable.

How much of the performance gain is due to the graph structure itself versus the graph expansion strategy? Both variants outperform the base SPARK model (Table 2), but SPARK +SAGE-Edge consistently delivers larger gains. For example, on AMAZON Human queries it improves R@20 by +8.49 compared to +6.21 for SPARK +SAGE +Edge, and on MAG Human queries it adds +1.31 versus +0.84. This trend holds across datasets. Selectively skipping expansion for edge-aware queries prevents irrelevant neighbors from

diluting semantically grounded candidates, while expansion remains beneficial for queries without structural constraints. These results indicate that improvements stem from the interaction between the graph and the expansion policy: the graph supplies useful connectivity, and conditioning expansion on query semantics ensures that only meaningful neighbors are introduced.

What is the effect of the initial retriever on the graph-based expansion? Table 6 shows that the benefit of graph augmentation depends on the strength of the initial retriever. For the Hybrid baseline, Recall@20 is lower and graph expansion yields limited gains, sometimes even small drops. This occurs because the hybrid retriever ignores node types, while expansion tends to favor nodes with embeddings similar to the seeds, often of the same type, which can introduce irrelevant nodes.

Method	Human			Synthetic		
	A.	M.	P.	A.	M.	P.
Hybrid	24.3	46.6	52.7	51.5	51.5	39.1
Hybrid+Graph	31.1	46.4	53.4	53.8	52.9	38.4
Change (△)	+6.8	-0.2	+0.7	+2.3	+1.4	-0.7
SPARK	33.6	53.5	63.6	54.1	66.4	58.4
SPARK +SAGE	42.1	56.4	66.4	58.3	70.1	61.0
Change (△)	+8.5	+2.9	+2.8	+4.2	+3.7	+2.6

Table 6: Recall@20 before and after graph augmentation across different baseline retrievers on STaRK datasets. Hybrid refers to BM25+Cosine similarity. A., M., and P. stand for AMAZON, MAG, and PRIME, respectively.

In contrast, the agent retriever starts with higher Recall@20 and identifies node types. Graph expansion then consistently improves performance across all datasets and query types. Stronger initial candidates and type-aware retrieval allow expansion to add relevant nodes and amplify gains. Full Recall@k curves showing these trends are provided in Appendix E.

3.4 Error Analysis on STaRK Human

We manually analyze retrieval failures on STaRK Human set and categorize errors into three classes:

- **Data Errors** reflect limitations in the dataset itself: These contain: **(1) Structural**, where there are missing or misdirected edges in the KG.**(2) Under-Specification**, where queries lack enough constraints to identify the correct entity. **(3) Evaluation Artifacts**, where gold annotations are incomplete, marking only a subset of valid answers.

- **Cypher Generation Errors** arise when translating natural language to graph queries: **(1) Constraint**, where numeric, temporal, or logical filters are not correctly applied; and **(2) Structure**, where

the system fails to select the correct node or edge types for graph traversal.

- Runtime Errors occur during query execution despite syntactically correct Cypher: **(1) Semantic**, where mismatches in units, terminology, or abbreviations prevent correct retrieval; and **(2) Over-Retrieval**, where queries return excessive candidates due to insufficient filtering.

Category	Method	Amazon	MAG	Prime
	Structural	5	6	4
Data	Under-Spec	4	5	3
	Eval Artifacts	7	4	4
Cypher	Constraint	36	30	31
	Structure	0	0	22
Runtime	Semantic	25	37	12
	Over-Retrieval	23	18	22
	Total	100	100	100

Table 7: Error distribution (%) across STaRK datasets.

Constraint extraction failures dominate on AMA-ZON and PRIME, reflecting the difficulty of translating complex product attributes or biomedical predicates into precise graph queries. MAG errors are mainly due to semantic mismatches, as dense technical abstracts often differ in terminology from queries or graph entities. Over-retrieval occurs across datasets when filters are too broad, while PRIME also shows notable graph structure errors due to its richer schema. Data errors are minor but appear in MAG where gold annotations are incomplete (Table 7).

Overall, the results highlight a trade-off between query translation, data quality, and semantic alignment: AMAZON errors arise from heterogeneous terminology and units, MAG from semantically complex content poorly captured by structured traversal, and PRIME from navigating its richer schema.

4 Related Work

Retrieval-augmented QA over heterogeneous corpora must handle both textual relevance and *structure*, including tables with schemas, documents with latent links, and collections with explicit relations. We summarize key techniques below:

Table-centric retrieval and dataset discovery For table repositories, a major focus is retrieving *related* tables using structural criteria such as unionability and joinability. Systems like Starmie (Fan et al., 2022), DeepJoin (Dong et al., 2022), and WarpGate (Cong et al., 2022) learn column or table representations to support efficient join and union search, typically using ANN indexing. Other work explores specialized signals, such as sketch-based indexing for correlated dataset search

(Santos et al., 2022). For end-to-end table QA, cascaded pipelines combining sparse filtering, dense retrieval, and reranking improve practical retrieval quality (Singh et al., 2025), while LLM-based dense retrieval methods like HyDE enable stronger zero-shot retrieval without labeled relevance data.

Graph-based indexing for retrieval and RAG Graph-based RAG methods organize information as graphs to retrieve connected context and aggregate evidence. Microsoft GraphRAG (Edge et al., 2024b) builds an entity graph with community summaries, while GRAG (Peng et al., 2024) retrieves textual subgraphs and incorporates topology into generation. PathRAG (Chen et al., 2025a) focuses on redundancy pruning and path-based prompting. GNN-Ret (Li et al., 2024b) constructs passage graphs using structural and keyword edges and applies a GNN to re-rank results, whereas ATLANTIC (Munikoti et al., 2023) builds document-level graphs with predefined relations and encodes them with a GNN. In multi-document QA, knowledge-graph prompting assembles supporting context via passage graph traversal (Wang et al., 2023), and surveys note that graph structure and domain constraints strongly shape GraphRAG design (Han et al., 2024). Think-on-Graph (Sun et al., 2023) performs iterative neighbor expansion on entity-level KGs along reasoning paths, allowing the LLM to explore multi-hop knowledge graph connections during reasoning.

5 Conclusion

We present SAGE, a structure-aware graph retrieval framework that strikes a balance between the rigidity of KGs and the disjoint nature of flat chunking. Consistent with our contributions, SAGE augments flat retrieval with chunk-level graph expansion and is especially useful when building full KGs is impractical but structural signals remain implicit in metadata and chunk relationships.

On OTT-QA, similarity-driven expansion improves Recall@k by 2.8-5.7 points over hybrid baselines, retrieving more coherent multi-hop evidence. On STaRK, expansion approaches fine-tuned performance without training using Cypher-guided traversal to limit neighbor noise; overall, structure-aware retrieval leveraging graph connectivity can match or outperform strong baselines.

Future work includes instruction tuning the agent for more accurate Cypher generation and extending the framework to multimodal graphs that incorporate images through cross-modal links.

Limitations

Our study focuses on two representative regimes and relies on LLM-based agents for STaRK, which introduces latency and computational cost compared to traditional retrieval. This tradeoff enables training-free symbolic Cypher generation that provides precise schema-aware traversal while avoiding neighbor noise in dense graphs. The framework depends on initial seed quality, as graph expansion amplifies rather than replaces base retrieval. SAGE is most helpful when nodes contain rich text, such as paper abstracts, product descriptions, or disease symptoms, but is less effective for graphs dominated by atomic entities with little textual content, where KG-specific methods such as FocusedR may be more suitable; this helps explain the smaller gains on STaRK MAG and PRIME. Error analysis reveals constraint extraction and filtering (30 to 36 percent of errors) as the dominant failure mode, reflecting the difficulty of mapping informal queries to structured predicates without task-specific training. Despite these limitations, SAGE still improves recall over our agentic baseline and surfaces multi-hop evidence that flat retrieval misses, achieving 2.8 to 5.7 point gains on OTT-QA and approaching fine-tuned baselines on STaRK without training.

Ethical Statement

We evaluate on publicly available benchmarks (OTT-QA and STaRK) released for research use under their respective licenses. Our framework operates on graph structures and does not collect any new user data or infer personal or demographic attributes.

Importantly, our agentic approach accesses only graph topology and schema information rather than actual node content during query planning, which provides an additional layer of privacy protection and reduces exposure to sensitive information. We aim to benefit the research community by enabling more efficient structure-aware retrieval across heterogeneous information sources.

As with any retrieval system, our approach could be misused in real deployments to surface or combine information without authorization. However, our work is intended solely for academic research and is not designed for deployment in surveillance, decision-making, or other high-stakes settings. Any practical use should follow standard data-governance practices (access control, auditing, and privacy safeguards) and undergo appropriate oversight. To support reproducibility, we document dataset splits, prompts, and decoding settings.

We used AI tools to assist with the writing process and improve the presentation.

References

2013. SPARQL 1.1 Query Language. Technical report, W3C.

Negar Arabzadeh, Xinyi Yan, and Charles LA Clarke. 2021. Predicting efficiency/effectiveness trade-offs for dense vs. sparse retrieval strategy selection. In *Proceedings of the 30th ACM International Conference on Information & Knowledge Management*, pages 2862–2866.

Derian Boer, Fabian Koch, and Stefan Kramer. 2024. Harnessing the power of semi-structured knowledge and llms with triplet-based prefiltering for question answering. *arXiv preprint arXiv:2409.00861*.

Derian Boer, Stephen Roth, and Stefan Kramer. 2025. Focus, merge, rank: Improved question answering based on semi-structured knowledge bases. *arXiv preprint arXiv:2505.09246*.

Boyu Chen, Zirui Guo, Zidan Yang, Yuluo Chen, Junze Chen, Zhenghao Liu, Chuan Shi, and Cheng Yang. 2025a. Pathrag: Pruning graph-based retrieval augmented generation with relational paths. *arXiv preprint arXiv:2502.14902*.

Peter Baile Chen, Yi Zhang, Mike Cafarella, and Dan Roth. 2025b. Can we retrieve everything all at once? ARM: An alignment-oriented LLM-based retrieval method. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 30298–30317, Vienna, Austria. Association for Computational Linguistics.

Wenhu Chen, Ming-Wei Chang, Eva Schlinger, William Wang, and William W Cohen. 2020. Open question answering over tables and text. *arXiv preprint arXiv:2010.10439*.

Xilun Chen, Kushal Lakhotia, Barlas Oguz, Anchit Gupta, Patrick Lewis, Stan Peshterliev, Yashar Mehdad, Sonal Gupta, and Wen-tau Yih. 2022. Salient phrase aware dense retrieval: can a dense retriever imitate a sparse one? In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 250–262.

Xinran Chen, Xuanang Chen, Ben He, Tengfei Wen, and Le Sun. 2024. Analyze, generate and refine: Query expansion with LLMs for zero-shot open-domain QA. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 11908–11922, Bangkok, Thailand. Association for Computational Linguistics.

Tianji Cong, James Gale, Jason Frantz, HV Jagadish, and Çağatay Demiralp. 2022. Warpgate: A semantic join discovery system for cloud data warehouses. *arXiv preprint arXiv:2212.14155*.

Yuyang Dong, Chuan Xiao, Takuma Nozawa, Masafumi Enomoto, and Masafumi Oyamada. 2022. Deepjoin: Joinable table discovery with pre-trained language models. *arXiv preprint arXiv:2212.07588*.

Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, Dasha Metropolitansky, Robert Osazuwa Ness, and Jonathan Larson. 2024a. From local to global: A graph rag approach to query-focused summarization. *arXiv preprint arXiv:2404.16130*.

Darren Edge, Ha Trinh, Newman Cheng, Joshua Bradley, Alex Chao, Apurva Mody, Steven Truitt, Dasha Metropolitansky, Robert Osazuwa Ness, and Jonathan Larson. 2024b. From local to global: A graph rag approach to query-focused summarization. *arXiv preprint arXiv:2404.16130*.

Grace Fan, Jin Wang, Yuliang Li, Dan Zhang, and Renée Miller. 2022. Semantics-aware dataset discovery from data lakes with contextualized column-based representation learning. *arXiv preprint arXiv:2210.01922*.

Nadime Francis, Alastair Green, Paolo Guagliardo, Leonid Libkin, Tobias Lindaaker, Victor Marsault, Stefan Plantikow, Mats Rydberg, Petra Selmer, and Andrés Taylor. 2018. Cypher: An evolving query language for property graphs. In *Proceedings of the 2018 international conference on management of data*, pages 1433–1445.

Luyu Gao, Xueguang Ma, Jimmy Lin, and Jamie Callan. 2023. Precise zero-shot dense retrieval without relevance labels. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1762–1777.

Haoyu Han, Yu Wang, Harry Shomer, Kai Guo, Jiayuan Ding, Yongjia Lei, Mahantesh Halappanavar, Ryan A Rossi, Subhabrata Mukherjee, Xianfeng Tang, et al. 2024. Retrieval-augmented generation with graphs (graphrag). *arXiv preprint arXiv:2501.00309*.

Junjie Huang, Wanjun Zhong, Qian Liu, Ming Gong, Daxin Jiang, and Nan Duan. 2022. Mixed-modality representation learning and pre-training for joint table-and-text retrieval in OpenQA. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 4117–4129, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Bernal Jimenez Gutierrez, Yiheng Shu, Yu Gu, Michihiro Yasunaga, and Yu Su. 2024. Hipporag: Neurobiologically inspired long-term memory for large language models. *Advances in Neural Information Processing Systems*, 37:59532–59569.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick SH Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. Dense passage retrieval for open-domain question answering. In *EMNLP (1)*, pages 6769–6781.

Yongjia Lei, Haoyu Han, Ryan A Rossi, Franck Dernoncourt, Nedim Lipka, Mahantesh M Halappanavar, Jiliang Tang, and Yu Wang. 2025. Mixture of structural-and-textual retrieval over text-rich graph knowledge bases. *arXiv preprint arXiv:2502.20317*.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33:9459–9474.

Yihao Li, Ru Zhang, and Jianyi Liu. 2024a. An enhanced prompt-based llm reasoning scheme via knowledge graph-integrated collaboration. In *International Conference on Artificial Neural Networks*, pages 251–265.

Zijian Li, Qingyan Guo, Jiawei Shao, Lei Song, Jiang Bian, Jun Zhang, and Rui Wang. 2024b. Graph neural network enhanced retrieval for question answering of llms.

Kaixin Ma, Hao Cheng, Xiaodong Liu, Eric Nyberg, and Jianfeng Gao. 2022. Open-domain question answering via chain of reasoning over heterogeneous knowledge. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 5360–5374, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Kaixin Ma, Hao Cheng, Yu Zhang, Xiaodong Liu, Eric Nyberg, and Jianfeng Gao. 2023. Chain-of-skills: A configurable model for open-domain question answering. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1599–1618, Toronto, Canada. Association for Computational Linguistics.

Yu A Malkov and Dmitry A Yashunin. 2018. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE transactions on pattern analysis and machine intelligence*, 42(4):824–836.

Priyanka Mandikal and Raymond Mooney. 2024. Sparse meets dense: A hybrid approach to enhance scientific document retrieval. *arXiv preprint arXiv:2401.04055*.

Costas Mavromatis and George Karypis. 2024. Gnn-rag: Graph neural retrieval for large language model reasoning. *arXiv preprint arXiv:2405.20139*.

Sai Munikoti, Anurag Acharya, Sridevi Wagle, and Sameera Horawalavithana. 2023. Atlantic: Structure-aware retrieval-augmented language model for interdisciplinary science.

Neo4j, Inc. 2026. *Neo4j Graph Database*.

OpenAI, :, Aaron Hurst, Adam Lerer, Adam P. Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, and et al. 2024. Gpt-4o system card.

Eunhwan Park, Sung min Lee, Dearyong Seo, Seonhoon Kim, Inho Kang, and Seung-Hoon Na. 2023. Rink: Reader-inherited evidence reranker for table-and-text open domain question answering. In *AAAI Conference on Artificial Intelligence*.

Boci Peng, Yun Zhu, Yongchao Liu, Xiaohe Bo, Haizhou Shi, Chuntao Hong, Yan Zhang, and Siliang Tang. 2024. Graph retrieval-augmented generation: A survey. *ACM Transactions on Information Systems*.

Boci Peng, Yun Zhu, Yongchao Liu, Xiaohe Bo, Haizhou Shi, Chuntao Hong, Yan Zhang, and Siliang Tang. 2025. Graph retrieval-augmented generation: A survey. *ACM Trans. Inf. Syst.*, 44(2).

Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. *arXiv preprint arXiv:1908.10084*.

Stephen Robertson, Hugo Zaragoza, et al. 2009. The probabilistic relevance framework: Bm25 and beyond. *Foundations and Trends® in Information Retrieval*, 3(4):333–389.

AÃĺcio Santos, Aline Bessa, Christopher Musco, and Juliana Freire. 2022. A sketch-based index for correlated dataset search. In *2022 IEEE 38th International Conference on Data Engineering (ICDE)*, pages 2928–2941.

Tao Shen, Guodong Long, Xiubo Geng, Chongyang Tao, Yibin Lei, Tianyi Zhou, Michael Blumenstein, and Daxin Jiang. 2024. Retrieval-augmented retrieval: Large language models are strong zero-shot retriever. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 15933–15946, Bangkok, Thailand. Association for Computational Linguistics.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36:8634–8652.

Adarsh Singh, Kushal Raj Bhandari, Jianxi Gao, Soham Dan, and Vivek Gupta. 2025. Craft: Training-free cascaded retrieval for tabular qa. *arXiv preprint arXiv:2505.14984*.

Jiashuo Sun, Chengjin Xu, Lumingyuan Tang, Saizhuo Wang, Chen Lin, Yeyun Gong, Heung-Yeung Shum, and Jian Guo. 2023. Think-on-graph: Deep and responsible reasoning of large language model with knowledge graph.

Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020. Minilm: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. *Advances in neural information processing systems*, 33:5776–5788.

Yu Wang, Nedim Lipka, Ryan A. Rossi, Alexa Siu, Ruiyi Zhang, and Tyler Derr. 2023. Knowledge graph prompting for multi-document question answering.

Shirley Wu, Shiyu Zhao, Qian Huang, Kexin Huang, Michihiro Yasunaga, Kaidi Cao, Vassilis Ioannidis, Karthik Subbian, Jure Leskovec, and James Y Zou. 2024a. Avatar: Optimizing llm agents for tool usage via contrastive reasoning. *Advances in Neural Information Processing Systems*, 37:25981–26010.

Shirley Wu, Shiyu Zhao, Michihiro Yasunaga, Kexin Huang, Kaidi Cao, Qian Huang, Vassilis N. Ioannidis, Karthik Subbian, James Zou, and Jure Leskovec. 2024b. Stark: Benchmarking llm retrieval on textual and relational knowledge bases. In *NeurIPS Datasets and Benchmarks Track*.

Yu Xia, Junda Wu, Sungchul Kim, Tong Yu, Ryan A Rossi, Haoliang Wang, and Julian McAuley. 2024. Knowledge-aware query expansion with large language models for textual and relational retrieval. *arXiv preprint arXiv:2410.13765*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. 2022. React: Synergizing reasoning and acting in language models. In *The eleventh international conference on learning representations*.

Michihiro Yasunaga, Hongyu Ren, Antoine Bosselut, Percy Liang, and Jure Leskovec. 2021. Qa-gnn: Reasoning with language models and knowledge graphs for question answering. *arXiv preprint arXiv:2104.06378*.

Haoyu Zhang, Jun Liu, Zhenhua Zhu, Shulin Zeng, Maojia Sheng, Tao Yang, Guohao Dai, and Yu Wang. 2024. Efficient and effective retrieval of dense-sparse hybrid vectors using graph-based approximate nearest neighbor search. *arXiv preprint arXiv:2410.20381*.

Wanjun Zhong, Junjie Huang, Qian Liu, Ming Zhou, Jiahai Wang, Jian Yin, and Nan Duan. 2022. Reasoning over hybrid chain for table-and-text open domain qa. *arXiv preprint arXiv:2201.05880*.

A Dataset Statistics

A.1 OTT-QA

OTT-QA consists of a heterogeneous graph connecting document and table chunks (Table 8). While table chunks are relatively few, they are densely linked to documents, enabling cross-modal retrieval between structured and unstructured sources. The large number of document-document edges reflects strong topical overlap across documents, which is particularly useful for graph-based context propagation.

A.2 STaRK

A.2.1 AMAZON

The AMAZON dataset originally contains four node types: review, brand, color, and category.

Component	Count
Document chunks	21,912
Table chunks	974
Total Nodes	**22,886**
Table–Table edges	66,003
Document–Table edges	162,374
Document–Document edges	523,459
Total Edges	**751,836**

Table 8: OTT-QA dataset statistics showing node types, edge types, and their counts.

The latter three (brand, color, category) can alternatively be represented as metadata attributes rather than separate nodes. We observe that all product nodes contain a reviews key that stores tabular review data.

For the dense+sparse (hybrid) retrieval approach, we treat this reviews data as a table for retrieval and expansion (Table 9). Since Neo4j is a graph database and does not natively support tabular structures like SQL databases, we convert each review into a separate node connected to its corresponding product node (Table 10).. This graph-native representation enables efficient querying in cases where we need to aggregate data (e.g., star ratings) across multiple reviews for the same product.

Node Type	Count
Review	957,192
Product	957,192
Total	**1,914,384**

Table 9: AMAZON node type distribution from STaRK dataset for Hybrid retrieval.

Node Type	Count
Review	12,963,012
Product	957,192
Total	**13,920,204**

Table 10: AMAZON node type distribution from STaRK dataset for Neo4j queries.

Edge Type	Count
HAS_REVIEW	12,963,012
ALSO_BUY	1,663,562
ALSO_VIEW	1,362,680
IS_SIMILAR	24,886,992
Total	**40,876,246**

Table 11: AMAZON edge type distribution from STaRK dataset.

A.2.2 MAG

MAG represents a large scholarly graph with diverse entity types but comparatively limited textual richness per node (Tables 12 and 13). While citation and authorship edges provide strong structural signals, the effectiveness of semantic graph expansion is constrained by shorter textual descriptions.

Node Type	Count
Author	1,104,554
Paper	700,244
Field	59,469
Institution	8,701
Total	**1,872,968**

Table 12: MAG node type distribution from STaRK dataset.

Edge Type	Count
CITES	9,719,488
HAS_FIELD	7,243,269
AUTHORED	6,768,883
ASSOCIATED_WITH	167,482
IS_SIMILAR	12,954,514
Total	**36,853,636**

Table 13: MAG edge type distribution from STaRK dataset.

A.2.3 PRIME

PRIME is a highly structured biomedical graph with many fine-grained entity and relation types (Tables 14 and 15). Although the graph is rich in relational semantics, node-level textual content is often sparse, making effective graph expansion more sensitive to the quality of initial retrieval.

Node Type	Count
BiologicalProcess	28,642
Gene	27,671
Disease	17,080
Phenotype	15,311
Anatomy	14,035
MolecularFunction	11,169
Drug	7,957
CellularComponent	4,176
Pathway	2,516
Exposure	818
Total	**129,375**

Table 14: PRIME node type distribution from STaRK dataset.

Edge Type	Count
EXPRESSED_IN	3,036,406
SYNERGISTIC_WITH	2,672,628
AFFILIATED_WITH	1,029,162
INTERACTS_WITH	686,550
INTERACTS_WITH_PROTEIN	642,150
PHENOTYPE_PRESENT	300,634
PARENT_OF	281,744
HAS_SIDE_EFFECT	129,568
CONTRAINDICATED_FOR	61,350
NOT_EXPRESSED_IN	39,774
TARGETS	32,760
INDICATED_FOR	18,776
INHIBITS_ENZYME	10,634
TRANSPORTED_BY	6,184
OFF_LABEL_USE	5,136
LINKED_TO	4,608
PHENOTYPE_ABSENT	2,386
ACTS_AS_CARRIER	1,728
IS_SIMILAR	963,104
Total	**9,825,282**

Table 15: PRIME edge type distribution from STaRK dataset.

B STaRK Baselines

ada-002   This dense retriever embeds each query and node independently using the text-embedding-ada-002 model, then ranks candidates by embedding similarity. It provides a strong semantic retrieval baseline for nodes with descriptive text. However, it does not use relation types, graph topology, or schema constraints during retrieval.

multi-ada-002   This baseline uses a multilingual dense embedding model in the same bi-encoder retrieval setup as ada-002. It is intended to improve robustness to lexical variation and semantic paraphrase across diverse node descriptions. Like other dense retrievers, it remains structure-agnostic and cannot explicitly follow graph relations.

DPR   (Karpukhin et al., 2020) DPR is a supervised dense passage retriever originally designed for open-domain question answering. It encodes queries and candidates separately and ranks them by vector similarity. On STaRK, it serves as a standard neural retrieval baseline but does not exploit typed edges or schema information.

BM25   BM25 is a sparse lexical retriever that ranks nodes using exact and partial term overlap between the query and node text. It is a strong baseline when entity names or attributes appear verbatim in the corpus. Its main limitation is that it cannot capture paraphrases or multi-hop structural dependencies.

BM25+Dense   This hybrid baseline combines sparse lexical matching from BM25 with dense semantic similarity from embedding-based retrieval. The goal is to improve coverage by balancing exact term matches with semantic matches. Despite this stronger initialization, it still treats nodes independently and ignores schema-valid paths during retrieval.

4StepFocus   (Boer et al., 2024) 4StepFocus is a hybrid SKB retriever that first extracts structured constraints, prunes the candidate space symbolically, then applies vector similarity scoring and reranking. It is designed to reduce search space before semantic ranking. This makes it stronger than flat retrieval, but it relies on iterative candidate filtering and more complex execution.

FocusedR   (Boer et al., 2025) FocusedR generates structured graph queries, grounds symbolic constraints, expands candidate sets adaptively, and finally reranks hybrid candidates. It is a strong retrieval baseline for explicit KGs because it uses both graph structure and unstructured text. Its main drawback is higher complexity due to repeated symbolic pruning and candidate expansion.

QA-GNN   (Yasunaga et al., 2021) QA-GNN is a graph-neural baseline that scores candidates by combining node features with graph connectivity in a learned message-passing framework. It represents a structural retrieval baseline that directly encodes topology. Unlike our method, it depends on learned graph reasoning rather than retriever-agnostic expansion over an offline graph.

HyDE   (Gao et al., 2023) HyDE is a query expansion method that first asks an LLM to generate a hypothetical answer document, then retrieves nodes using embeddings of that generated text. The generated pseudo-document helps bridge the gap between short queries and longer candidate descriptions. However, the method remains fundamentally flat and does not use graph structure during retrieval.

AGR   (Chen et al., 2024) AGR is an LLM-based query expansion baseline that enriches the original query with additional context intended to improve downstream retrieval. It aims to recover missing semantic cues before ranking candidates. Like other expansion-only methods, it improves query representation but does not explicitly traverse graph structure.

RAR (Shen et al., 2024) RAR is another retrieval-oriented query rewriting baseline that reformulates the input question to produce a retrieval-friendly query. Its strength lies in better aligning the query with candidate text through reformulation. However, it still operates over flat retrieval and cannot enforce typed multi-hop paths.

KAR (Xia et al., 2024) KAR is a knowledge-aware query expansion method that extracts entities, retrieves their neighbors, constructs supporting triples, and then generates an expanded query for final retrieval. It injects structured context into the query before retrieval rather than expanding over a pre-built graph at inference time. This makes it more structured than flat baselines, but it still requires multiple retrieval operations and LLM calls.

ReACT (Yao et al., 2022) ReACT is an agentic baseline that interleaves reasoning and retrieval in a think-act-observe loop. At each step, the model decides what retrieval action to take next based on prior observations. This enables flexible multi-step exploration, but incurs higher latency because retrieval is embedded inside an iterative LLM loop.

Reflexion (Shinn et al., 2023) Reflexion extends ReACT by adding self-reflection after failed trajectories, allowing the agent to critique prior mistakes and retry with updated reasoning. This can improve difficult retrieval problems by re-planning after failure. The tradeoff is even higher inference cost due to repeated episodes and extra LLM calls.

mFAR (Li et al., 2024a) mFAR is a fine-tuned semi-structured retriever trained specifically for retrieval over structured or semi-structured corpora. It benefits from supervised optimization tailored to the target retrieval task, giving it an advantage over zero-shot baselines. In our comparisons, it serves as a strong learned upper baseline rather than a training-free method.

MoR (Lei et al., 2025) MoR is another fine-tuned retrieval model for semi-structured knowledge bases that learns task-specific ranking behavior from supervision. It is designed to better capture relation-aware retrieval patterns than generic dense or sparse baselines. Like mFAR, it is not directly comparable to training-free methods on efficiency, but provides a useful performance reference.

AvaTaR (Wu et al., 2024a) AvaTaR is a fine-tuned agentic retriever that improves tool-using retrieval through trajectory optimization and contrastive supervision. Instead of relying only on zero-shot prompting, it learns better action policies from successful and failed retrieval traces. This makes it a strong learned agent baseline, especially on structured retrieval tasks.

C OTTQA graph building statistics

C.1 Metadata Extraction Cost Analysis

Modality	Input	Output	Total
Table	1,625,516	3,989,504	5,615,020
Text	53,501,851	21,960,752	75,462,603
Grand Total	**55,127,367**	**25,950,256**	**81,077,623**

Table 16: Token usage by modality for OTT-QA metadata extraction.

As shown in Table 16, text metadata extraction dominates total token usage, accounting for the majority of the 81.1M tokens processed. Using gpt-4o-mini pricing, table metadata extraction costs approximately *$2.64*, while text metadata extraction costs *$21.20*, for a combined total of **$23.84**, **$11.92** if we apply batching. Despite the large aggregate volume, the per-item processing cost remains extremely low, highlighting the cost efficiency of large-scale metadata generation. Open source models can also be used.

C.2 Quality of Metadata Extracted

The edges are created from metadata generated by an LLM, which introduces a dependence on generation quality. If the model produces generic titles or topics, the resulting graph can become overly dense or connect irrelevant chunks.

We therefore do not deploy LLM-generated metadata without checking it first. Instead, we design prompts and test them on a small sample of chunks to inspect the resulting titles, topics, and entities. If the outputs appear too generic or unhelpful, we revise the prompts and repeat the sample-based check until the metadata is clear and discriminative. Only after this validation step do we run the prompts at scale for graph construction. This iterative sampling process reduces the risk of low-quality generations before the full pipeline is executed.

Sections C.3, C.4, and C.5 provide empirical evidence that the metadata does not collapse into generic patterns. Title and description similarity

distributions are bell-shaped with a moderate center around 0.3, far below the 95th-percentile edge threshold of 0.63. If titles were generic, these similarities would cluster in a narrow high-similarity band; instead, the observed spread indicates differentiated, chunk-specific generations.

We further show that LLM-generated metadata aligns with the underlying content. Scatter plots and correlation analyses in Sections C.3, C.4, and C.5 demonstrate strong relationships between titles, descriptions, topics, and source text, including a topic-content correlation of 0.650. These diagonal trends would not appear if the metadata were generic; instead, they indicate that the metadata tracks content rather than reflecting templated labeling. The metadata extraction prompts themselves are provided in Section I.

Finally, 95th-percentile pruning acts as a safeguard. Even if some metadata were generic, it would affect only a small high-similarity tail. The retained graph remains controlled, with average degree around 30 and only about 11% of candidate edges preserved, clearly separated from denser settings. This cutoff limits connectivity and prevents generic metadata from inflating the graph.

C.3 Table-Table Similarity Analysis

We analyze similarity statistics between table chunks in OTT-QA to evaluate whether LLMs are necessary for graph construction.

Column similarity and entity distribution Figure 5 show the distribution of column similarity and number of entities per chunk. Column similarity is roughly bell-shaped (normal distribution), while entity counts are strongly left-skewed - most chunks contain only one entity. These figures highlight that high semantic similarity exists even for single-entity chunks.

Figure 5: Left: column similarity distribution. Right: number of entities per table chunk (left-skewed).

Description and title similarity Figure 6 show the distributions of description and title similarity.

Both are bell-shaped with a slight high-end tail, indicating that some tables are highly similar in title or description.

Figure 6: Left: description similarity. Right: title similarity. Both distributions are similar, with a slight rise at high similarity.

Column-title, column-description, title-description scatter plots Figure 7 show scatter plots of column-title, column-description, and title-description similarities, respectively. Strong diagonal trends indicate that similar columns tend to co-occur with similar titles and descriptions.

Figure 7: Scatter plots of column-title (left), column-description (center), and title-description (right) similarities. Diagonal trends indicate strong alignment.

Correlation matrix Table 17 shows the correlation matrix of all table-level similarity metrics. Column, title, and description similarities are strongly correlated, with title and description similarity correlation 0.846.

	(1)	(2)	(3)	(4)
(1) Col Sim	1.000	0.165	0.577	0.696
(2) Ent Cnt	0.165	1.000	0.179	0.189
(3) Titl Sim	0.577	0.179	1.000	0.846
(4) Desc Sim	0.696	0.189	0.846	1.000

Table 17: Table-Table Correlation Matrix. Abbreviations: (1) column_similarity, (2) entity_count, (3) title_similarity, and (4) description_similarity.

C.4 Document-Document Similarity Analysis

We analyze similarity statistics between document chunks in OTT-QA to assess semantic content and the need for LLM-based processing.

Entity and event counts per chunk Figure 8 shows the number of entities and events per doc-

ument chunk. Both distributions are strongly left-skewed, with most chunks containing only a single entity or event. This indicates that document chunks are small and focused, and additional LLM-based extraction or summarization would provide minimal benefit.

Figure 10: Scatter plot of content similarity versus topic similarity. Diagonal concentration indicates strong alignment between the two metrics.

Figure 8: Distribution of entities and events per document chunk. Most chunks contain only one entity, reducing the need for LLM-based extraction.

Correlation matrix Table 19 shows the correlation matrix of document-table similarity metrics. Column similarity, title similarity, and summary similarity are moderately correlated, confirming that cross-modal semantic alignment can be captured using simple embeddings.

Topic and content similarity distributions Figure 9 shows histograms of topic similarity and content similarity between document chunks. Both distributions are roughly bell-shaped with a small spike near 1, indicating that while most document pairs are moderately similar, a few are nearly identical.

	(1)	(2)	(3)	(4)	(5)
(1) Top Sim	1.000	0.650	0.250	0.253	0.153
(2) Cont Sim	0.650	1.000	0.357	0.339	0.251
(3) Ent Rel	0.250	0.357	1.000	0.530	0.230
(4) Ent Cnt	0.253	0.339	0.530	1.000	0.235
(5) Evt Cnt	0.153	0.251	0.230	0.235	1.000

Table 18: Doc-Doc Correlation Matrix. Abbreviations: (1) topic_similarity, (2) content_similarity, (3) entity_relationship_overlap, (4) entity_count, and (5) event_count.

C.5 Document-Table Similarity Analysis

We analyze the semantic alignment between document and table chunks in OTT-QA to evaluate whether LLM-based processing is necessary.

Figure 9: Histograms of topic similarity (left) and content similarity (right) between document chunks. Bell-shaped distributions with a high-similarity spike are observed.

Topic-content scatter plot Figure 10 shows a scatter plot of content similarity versus topic similarity for each document pair. Most points lie along the diagonal, confirming strong alignment between content and topic similarities.

Topic-title and topic-summary similarity Figure 11 show the distributions of topic-title similarity and topic-summary similarity, respectively. Both curves are bell-shaped, indicating most document-table pairs are moderately similar, with few extreme cases. These two histograms are placed side by side for direct comparison.

Figure 11: Left: topic-title similarity distribution. Right: topic-summary similarity distribution. Both are bell-shaped.

Column similarity and entity counts Figure 12 shows column similarity and number of entities per table chunk. Column similarity exhibits a bell-shaped distribution, while the entity count is left-skewed, consistent with document-document observations. Placing these side by side highlights the distributional patterns across structural and semantic features.

Figure 12: Left: column similarity distribution. Right: entity count per table chunk (left-skewed).

Scatter plots of topic, title, summary, and column similarities Figure 13 shows scatter plots for combinations of topic, title, summary, and column similarities. Diagonal trends indicate strong alignment between document and table chunks across multiple semantic dimensions.

Figure 13: Scatter plots showing alignment between document and table chunks: topic-title vs topic-summary (left), column vs topic-summary (center), column vs topic-title (right). Diagonal trends indicate strong alignment.

Correlation matrix Table 19 shows the correlation matrix of document-table similarity metrics. Column similarity, title similarity, and summary similarity are moderately correlated, confirming that cross-modal semantic alignment can be captured using simple embeddings without LLM-based processing.

	(1)	(2)	(3)	(4)
(1) Col Sim	1.000	0.078	0.517	0.535
(2) Ent Count	0.078	1.000	0.107	0.107
(3) Title Sim	0.517	0.107	1.000	0.691
(4) Summ Sim	0.535	0.107	0.691	1.000

Table 19: Doc-Table Correlation Matrix. Abbreviations: (1) column_similarity, (2) entity_count, (3) topic_title_similarity, and (4) topic_summary_similarity

D Runtime Analysis of all State of the Art baselines for STaRK

D.1 4StepFocus

4StepFocus processes queries over semi-structured knowledge bases (SKBs) through symbolic pre-filtering, followed by vector similarity search and LLM-based reranking.

Pipeline:

1. **LLM Extraction:** The LLM extracts triplets T and the target variable x_{target} from the query q.

2. **Symbolic Prefiltering (SUBSTITUTE):** Iteratively intersects candidate sets with KG neighbors until convergence, producing a filtered candidate set C_{filtered}.

3. **Vector Similarity Scoring (VSS):** Scores C_{filtered} using unstructured data, returning the top-k_{max} candidates along with additional relevant candidates.

4. **LLM Reranking:** Reranks candidates using the SKB context.

SUBSTITUTE Algorithm:
Runtime Analysis:

- **Step 1:** $O(1)$ - single LLM call.

- **Step 2:** $O(n \cdot |T| \cdot \deg)$ - n iterations over $|T|$ triplets with average node degree $\deg$.

- **Step 3:** $O(|C_{\text{filtered}}|)$ - VSS applied to filtered candidates.

- **Step 4:** $O(1)$ - single LLM call for reranking.

Total Complexity:

$$O(n \cdot |T| \cdot \deg + |C_{\text{filtered}}|)$$

Algorithm 1: SUBSTITUTE: Symbolic Prefiltering for Candidate Selection

---

Input: Candidate set C, triplets
$\quad\quad T = \{(h_i, e_i, t_i)\}$, target variable
$\quad\quad x_{\text{target}}$
Output: Filtered candidate set C_{filtered}
foreach *variable x* **do**
$\quad$ substitute$[x] \leftarrow \{c \in C \mid \text{type}(c) = \text{type}(x)\}$
end
repeat
$\quad$ **foreach** $(h_i, e_i, t_i) \in T$ **do**
$\quad\quad$ substitute$[h_i] \leftarrow$
$\quad\quad\quad$ substitute$[h_i] \cap$ neighbors$(h_i, e_i, -)$

$\quad\quad$ substitute$[t_i] \leftarrow$
$\quad\quad\quad$ substitute$[t_i] \cap$ neighbors$(t_i, e_i, +)$
$\quad$ **end**
until *no changes in any substitute$[x]$*
$C_{\text{filtered}} \leftarrow$ substitute$[x_{\text{target}}]$
return C_{filtered}

D.2 FocusedR

FocusedR combines Cypher query generation, symbolic grounding, and hybrid retrieval (Cypher-constrained plus fallback Vector similarity search(VSS)) before LLM-based reranking.

Pipeline:

1. **LLM Cypher Generation:** The LLM generates a Cypher query q_{cypher} from q using node and edge types.

2. **Regex Parsing:** Parse q_{cypher} into target y, triplets T, and symbol constraints S_{raw}.

3. **Symbolic Grounding:**

   - **SYMBOL_CANDIDATES:** Perform VSS for symbol constants.
   - **GROUND_TRIPLETS:** Iteratively prune candidate sets via neighbor intersections.

4. **Adaptive Candidate Expansion:** While $|C_{\text{cypher}}| < k$, exponentially increase $\hat{k}$ and repeat Step 3.

5. **Hybrid VSS Retrieval:** Perform two VSS calls:

   - Y_{cypher}: Cypher-constrained candidates
   - Y_{vss}: Fallback unstructured candidates

6. **LLM Reranking:** Rerank concatenated candidates $Y = Y_{\text{cypher}} + Y_{\text{vss}}$.

GROUND_TRIPLETS Algorithm:

Algorithm 2: GROUND_TRIPLETS: Iterative Candidate Pruning

Input: Triplets $T = \{(h_i, e_i, t_i)\}$, symbol candidate sets S
Output: Pruned symbol candidate sets S
repeat
$\quad$ **foreach** $(h_i, e_i, t_i) \in T$ **do**
$\quad\quad$ $S(h_i) \leftarrow$
$\quad\quad\quad$ $S(h_i) \cap$ neighbors$(h_i, e_i, -)$
$\quad\quad$ $S(t_i) \leftarrow S(t_i) \cap$ neighbors$(t_i, e_i, +)$
$\quad$ **end**
until *no changes in any $S(x)$*
return S

Runtime Analysis:

- **Step 1:** $O(1)$ - single LLM call.

- **Steps 2–4:** $O(n_1 \cdot n_2 \cdot |T| \cdot \deg)$ - n_1 outer $\hat{k}$ expansions, n_2 inner convergence iterations, $|T|$ triplets, $\deg$ average degree.

- **Step 5:** $O(|C_{\text{cypher}}| + |C(y'.\text{type})|)$ - two VSS calls.

- **Step 6:** $O(1)$ - single LLM call for reranking.

Total Complexity:

$$O(n_1 \cdot n_2 \cdot |T| \cdot \deg + |C_{\text{cypher}}|)$$

D.3 AvaTaR

AvaTaR is an agent optimization framework that improves tool-calling LLMs through contrastive reasoning. It is typically instantiated as a ReAct-style agent operating over retrieval tools.

Pipeline:

1. **Agent Initialization:** Initialize the agent with query q and a toolset (e.g., retrieval APIs over an SKB).

2. **Agent Loop:** Repeat for m steps:

   - The LLM generates a *thought* and an *action* (tool call).
   - Execute the action and append the resulting observation to the trajectory.

3. **Termination:** Continue until maximum steps, success condition, or a final answer is generated.

4. **AvaTaR Optimization (Training-time):** Perform contrastive fine-tuning using successful vs. failed trajectories to improve future performance.

Runtime Analysis:

- Per trajectory: $O(m)$ LLM calls and $O(m_r)$ retrievals (m = total steps, $m_r \leq m$ = number of retrieval actions).

- No explicit set operations; reasoning is implicit in the LLM.

- No dedicated reranker; retrieval results are fed directly to the agent prompt.

- Inference can be amortized over multiple queries via the trained policy.

Total Complexity (per query):

$$O(m) \text{ LLM calls} + O(m_r) \text{ retrievals}$$

where m is the trajectory length until stopping condition.

D.4 KAR

KAR performs knowledge-aware query expansion through entity extraction, neighbor retrieval, document relation filtering, triple construction, and final retrieval.

Pipeline:

1. **Entity Extraction:** The LLM extracts entities $E = \{e_1, \ldots, e_e\}$ from query q.

2. **Neighbor and Document Retrieval:** For each entity e_i, retrieve neighbors $N(e_i)$ and associated documents D_i (total $e + 1$ retrievals).

3. **Document Relation Filtering:** Filter retrieved documents based on cosine similarity over the $e + 1$ neighbor sets.

4. **Triple Construction:** Construct triples (e_i, r_j, d_k) from the filtered neighbor sets.

5. **Query Expansion:** Feed all triples to the LLM to generate an expanded query q_{exp}.

6. **Final Retrieval:** Execute a single retrieval over the expanded query q_{exp}.

Runtime Analysis:

- Step 1: $O(1)$ - single LLM call for entity extraction.

- Step 2: $O(e)$ - e entity neighbor retrievals plus 1 document retrieval.

- Step 3: $O((e + 1) \cdot \deg_D)$ - cosine similarity over neighbor documents, $\deg_D$ = average doc neighbors.

- Step 4: $O(|T|)$ - triple construction, where $|T|$ is total triples.

- Step 5: $O(1)$ - single LLM call for query expansion.

- Step 6: $O(1)$ - single final retrieval.

Total Complexity:

$$O(e \cdot \deg_D + |T|)$$

with exactly two LLM calls.

D.5 ReAct

ReAct interleaves LLM reasoning with tool calls (typically retrieval) in a think-act-observe loop until task completion or a step limit.

Pipeline:

1. **Initial LLM Reasoning:** The LLM generates an initial thought and first action (retrieval tool call).

2. **Execute Action:** Execute the retrieval action and append results as an observation to the trajectory.

3. **Subsequent Reasoning:** LLM reasons over the observation and generates the next thought and action.

4. **Iteration:** Repeat Steps 2–3 for m iterations until a final answer is obtained or maximum steps are reached.

Runtime Analysis:

- Per trajectory: $O(m)$ LLM calls and $O(m_r)$ retrievals.

- m: total steps until stopping condition (max steps, success, or final answer).

- $m_r \leq m$: number of retrieval actions (subset of total actions).

- No explicit set operations; reasoning is implicit in the LLM.

- No dedicated reranker; retrievals are fed directly to the agent prompt.

Total Complexity (per query):

$$O(m) \text{ LLM calls} + O(m_r) \text{ retrievals}$$

where m is the trajectory length until stopping.

D.6 Reflexion

Reflexion extends ReAct agents with self-reflection: after each failed episode, an LLM analyzes the trajectory to generate verbal feedback for the next episode.

Pipeline:

- **Step 1:** Run ReAct episode: m iterations of LLM call $\rightarrow$ retrieval $\rightarrow$ observation.

- **Step 2:** Evaluate episode outcome (success/failure).

- **Step 3:** If failed, LLM generates reflection r_i analyzing trajectory and errors.

- **Step 4:** Append reflection to prompt, repeat Steps 1–3 for E episodes total.

Runtime analysis:

- Per episode: $O(m)$ LLM calls + $O(m_r)$ retrievals (m: steps, m_r: retrievals).

- Per reflection: $O(1)$ LLM call (self-critique).

- E: total episodes until success or cap.

- R: reflections ($R \leq E - 1$, one per failed episode).

- Total: $O(E \cdot m + R)$ LLM calls + $O(E \cdot m_r)$ retrievals.

Total: $O(E \cdot m + R)$ LLM calls + $O(E \cdot m_r)$ retrievals, where E is episodes, m is steps per episode, R is reflections.

D.7 SAGE **using** SPARK

SAGE using SPARK queries through a single-pass agentic retrieval pipeline with hybrid dense+sparse expansion.

Pipeline:

1. **Query Generation:** Agent LLM generates a Cypher/HNSW query from the natural language input q.

2. **Initial Retrieval:** Retrieve the top-k nodes N_k using the generated query.

3. **Graph Expansion:** Retrieve 1-hop neighbors $N(N_k)$ of the top-k nodes.

4. **Hybrid Retrieval:** Apply dense+sparse retrieval over $N(N_k)$ to produce the final $k + k'$ candidate set.

Runtime Analysis:

- Step 1: $O(1)$ - single agent LLM call.

- Step 2: $O(k)$ - initial retrieval (HNSW/Cypher).

- Step 3: $O(k \cdot \deg)$ - neighbor expansion (deg = average node degree).

- Step 4: $O(k \cdot \deg)$ - hybrid dense+sparse retrieval over neighbors.

Total Complexity:

$$O(k \cdot \deg)$$

with exactly one LLM call and no iterative loops.

Latency is a potential concern when combining graph and vector retrieval; however, the system is designed to mitigate this through parallel execution of both components. Graph traversal is performed using Neo4j, while vector retrieval relies on an HNSW index, with both operations typically completing within milliseconds in practice. The dominant latency arises not from database access but from Cypher query generation using GPT-4o-mini, which averages approximately 0.5 seconds. This step is deliberate, as it converts the user query into structured graph constraints, enabling targeted graph expansion rather than unguided neighborhood exploration.

E Effect of Dense+Sparse Retriever + Graph Expansion on STaRK Dataset

E.1 AMAZON

Figures 14 and 15 show recall@k for Synthetic and Human queries on the AMAZON subset. Graph expansion consistently improves recall across all k values. This aligns with our observation that nodes in AMAZON contain rich product descriptions and feature-rich metadata, providing ample semantic content for propagation. The one-hop expansion strategy reliably increases coverage of relevant nodes without introducing noise, yielding a consistent gain over the Dense+Sparse baseline.

Figure 14: Recall@k for Synthetic queries on AMAZON. Graph expansion improves recall across all k.

Figure 15: Recall@k for Human queries on AMAZON. Graph expansion consistently increases recall.

E.2 MAG

Figures 16 and 17 show recall@k for MAG. Here, graph expansion helps primarily at higher k values ($k \gtrsim 10$), while recall may drop at lower k. MAG nodes contain shorter titles and abstracts, so expanding the graph at small k can introduce weakly relevant neighbors, hurting early-rank retrieval. At larger k, however, graph augmentation still provides additional relevant nodes, boosting recall and

demonstrating its utility when more candidates are available.

Figure 16: Recall@k for Synthetic queries on MAG. Graph expansion improves recall at higher k, but hurts at low k.

Figure 17: Recall@k for Human queries on MAG. Graph expansion shows gains only at larger k.

E.3 PRIME

Figures 18 and 19 show recall@k for PRIME. Similar to MAG, graph expansion benefits are observed primarily at higher k values ($k \gtrsim 20$), while lower k sees slight drops in recall. PRIME nodes contain concise drug, pathway, and disease descriptions, limiting semantic propagation. These trends reinforce our finding that graph-based expansion is most effective when nodes have rich textual content.

Figure 18: Recall@k for Synthetic queries on PRIME. Graph expansion is effective only at higher k.

Figure 19: Recall@k for Human queries on PRIME. Graph expansion helps mainly at larger k.

F Implementation Details.

Our system follows a two-stage design with offline preprocessing and online query processing. Offline, we perform semantic chunking and graph construction using the all-MiniLM-L6-v2 embedding model (384-d), (Wang et al., 2020) and build ANN indices with HNSW (M=64); preprocessing is executed once on a single NVIDIA A100 GPU. For explicit schema graphs, we store and query the structured data in Neo4j, and extract lightweight metadata such as titles and entities from nodes/fields to support linking and retrieval. Online, we answer each query by combining sparse and dense signals via linear fusion ($\alpha = 0.6$ for BM25, $\beta = 0.4$ for embeddings), and we use GPT-4o-mini-2024-07-18 (OpenAI et al., 2024) where LLM-based extraction/planning is required.

G Scalability of Graph Construction

Naively computing full pairwise similarities between all nodes scales quadratically, $O(N^2)$, which becomes infeasible for very large corpora. To address this, similarity computation can be restricted to an approximate nearest neighbor (ANN) candidate pool rather than the entire corpus.

For each node, the nearest K candidates (e.g., 10K–30K) can be retrieved using HNSW, and exact similarities computed only within this neighborhood. The 95$^{\text{th}}$ percentile pruning is then applied locally over these candidates. This reduces graph construction from $O(N^2)$ to $O(NK)$ for similarity evaluation, where $K \ll N$, making large-scale offline graph construction practical.

To evaluate whether such ANN-restricted neighborhoods preserve relevant connections, we analyze recall at different candidate sizes on the STARK-AMAZON corpus, our largest dataset. Table 20 reports Hit@K and Recall@K as the candidate pool grows.

K	Hit@K	Recall@K
100	0.716	0.321
1,000	0.840	0.605
5,000	0.926	0.806
10,000	0.938	0.863
20,000	0.988	0.935
30,000	1.00	1.00

Table 20: Recall of relevant neighbors under ANN-restricted candidate pools on the STARK-AMAZON corpus.

The high recall and hit rates indicate that most relevant neighbors are preserved within these candidate sets. These results suggest that large-scale graph construction can rely on ANN-local neighborhoods without materially degrading graph quality while avoiding quadratic computational cost.

H Additional Metrics for STaRK

Table 21 presents Hits@1, Hits@5, and MRR scores for all methods across AMAZON, MAG, and PRIME datasets.

Method	Amazon						MAG						Prime					
	Human			Synthetic			Human.			Synthetic			Human.			Synthetic		
	H1	H5	M	H1	H5	M	H1	H5	M	H1	H5	M	H1	H5	M	H1	H5	M
Dense																		
ada-002	39.50	64.19	52.65	29.08	49.61	38.62	28.57	41.67	35.81	29.08	49.61	38.62	17.35	34.69	26.35	12.63	31.49	21.41
m-ada	46.91	72.84	58.74	40.07	64.98	51.55	23.81	41.67	31.43	25.92	50.43	36.94	24.49	39.80	32.98	15.10	33.56	23.49
DPR	16.05	39.51	27.21	15.29	47.93	30.20	4.72	9.52	7.90	10.51	35.23	21.34	2.04	9.18	7.05	4.46	21.85	12.38
Sparse																		
BM25	27.16	51.85	18.79	25.85	45.25	34.91	32.14	41.67	37.42	25.85	45.25	34.91	22.45	41.84	30.37	12.75	27.92	19.84
Structural																		
QAGNN	22.22	49.38	31.33	12.88	39.01	29.12	20.24	26.19	25.53	12.88	39.01	29.12	6.12	13.27	26.35	8.85	21.35	14.73
Hybrid																		
4Step	–	–	–	47.60	67.60	56.50	–	–	–	53.80	69.20	61.40	–	–	–	39.30	53.20	45.80
FocusR	–	–	–	64.00	76.20	69.30	–	–	–	74.10	84.20	78.80	–	–	–	46.40	63.90	53.70
D+B	32.14	44.05	38.46	29.72	49.64	38.71	32.14	44.05	38.46	29.72	49.64	38.71	24.77	43.12	33.25	13.71	31.13	21.39
Query Expansion																		
HyDe	45.68	72.84	57.56	28.98	50.10	39.58	33.33	44.05	38.95	28.98	50.10	39.58	24.77	42.20	33.65	16.85	37.59	26.56
RAR	55.56	71.60	62.15	39.02	52.87	39.58	38.10	45.24	42.04	39.02	52.87	39.58	31.19	43.12	37.72	22.23	40.84	30.93
AGR	55.56	71.60	63.54	39.29	53.66	46.20	33.33	44.05	38.95	39.29	53.66	46.20	32.11	49.54	39.27	25.85	44.41	35.04
KAR	61.73	72.84	66.32	50.47	65.37	57.51	51.20	58.30	54.20	50.47	65.37	57.51	44.95	60.55	44.51	30.35	49.30	39.22
Agentic																		
AvaTaR	58.32	76.54	65.91	49.97	69.16	52.01	33.33	42.86	38.62	46.08	59.32	52.01	33.03	51.37	41.00	20.10	39.89	29.18
ReACT	45.65	71.73	58.81	42.14	64.56	52.30	27.27	40.00	33.94	31.07	49.49	39.25	21.73	33.33	28.20	15.28	31.95	22.76
Reflex	49.38	64.19	52.91	42.79	65.05	52.91	28.57	39.29	36.53	40.71	54.44	47.06	16.52	33.03	23.99	14.28	34.99	24.82
Finetuned																		
mFAR	–	–	–	41.20	70.00	54.20	–	–	–	49.00	69.60	58.20	–	–	–	40.90	62.80	51.20
MoR	–	–	–	52.20	74.60	62.20	–	–	–	58.20	78.30	67.10	–	–	–	36.40	60.00	46.90
Ours																		
SPARK	22.22	58.03	39.93	26.72	54.27	36.24	44.40	54.80	49.40	41.00	56.41	49.30	41.66	61.14	52.53	29.12	48.31	41.94
A+G+E	25.18	55.13	37.75	25.18	53.45	36.18	45.10	55.60	48.90	41.70	57.20	48.80	42.20	61.60	51.53	30.14	49.56	42.79
A+G-E	28.41	63.84	42.48	28.41	55.13	42.48	43.20	58.70	49.40	43.20	60.00	49.30	40.23	65.40	52.53	30.86	51.48	43.20

Table 21: Hits@1 (H@1), Hits@5 (H@5), and Mean Reciprocal Rank (MRR) scores on STaRK datasets. A = SPARK, G=SAGE, E=Edge

I Prompt for LLM Metadata Extraction

I.1 Entity Extraction for Table Chunks

Listing 2: Table metadata extraction prompt

```
You are a table metadata extraction
    engine. Given table data with
    headers and rows, parse it into a
    single valid JSON object following
    exactly this schema:

{{
  " table_title ": "<verbatim table
      title or inferred title if
      unavailable>",
  " table_description ": "<one-sentence
      explanation of the table content
      >",
  " table_summary ": "<concise
      interpretation or insight derived
      from the data>",
  " col_desc ": {{
    "<ColumnName1>": "<contextual
        description of the column's
        representation and purpose>",
    ...
  }},
  " col_format ": {{
    "<ColumnName1>": "<data format
        specification: string, number,
        date (format), etc.>",
    ...
  }},
  " entities ": {{
    "<EntityName1>": {{
      "type": "<person/place/
          organization/event/concept/
          thing>",
      "category": "<named/non-named>",
      "description": "<brief
          description of the entity>"
    }},
    ...
  }}
}}

 Instructions:
1.  table_title : Use the source name if
     available; otherwise, infer a
    descriptive title from the data.
2.  table_description : Provide one
    sentence explaining the information
     contained in this table.
3.  table_summary : Provide a brief
    insight or interpretation of the
    overall data patterns.
4.  col_desc : For each column header,
    provide a contextual description of
     what the column represents, its
    purpose, and significance.
5.  col_format : For each column header,
     specify the data format (e.g.,
    string - names, number - scores,
    date (Month Day)).
6.  entities : Extract all unique
     entities  mentioned in the table
    with detailed information:
    - type: person, place, organization
        , event, concept, thing, etc.
    - category: named (proper nouns) or
         non-named (common nouns/
        concepts)
    - description: brief explanation of
        what this entity represents

Output: Pure JSON only. No markdown or
    comments.

One-Shot  Example :

Table Source Name: "1911 Notre Dame
    Fighting Irish football team -
    Schedule"
Table Data:
[
  {{
    "Date": "October 7",
    "Opponent": "Ohio Northern",
    "Site": "Cartier Field South Bend
        , IN",
    "Result": "W 32-6"
  }},
  {{
    "Date": "October 14",
    "Opponent": "St. Viator",
    "Site": "Cartier Field South Bend
        , IN",
    "Result": "W 43-0"
  }},
  {{
    "Date": "October 21",
    "Opponent": "Butler",
    "Site": "Cartier Field South Bend
        , IN",
    "Result": "W 27-0"
  }}
]

Expected Output:
{{
  " table_title ": "1911 Notre Dame
      Fighting Irish football team -
      Schedule",
  " table_description ": "This table
      presents the football schedule
      and results for the 1911 Notre
      Dame Fighting Irish football team
      .",
  " table_summary ": "Notre Dame had a
      strong season with multiple wins
      at home field, scoring
      consistently high points against
      various opponents.",
  " col_desc ": {{
    "Date": "The scheduled date when
        each football game was played
        during the 1911 season",
    "Opponent": "The opposing football
        team that Notre Dame played
        against in each game",
    "Site": "The venue and location
        where each game took place,
        including home and away games",
    "Result": "The final outcome and
        score of each game showing
        Notre Dame's performance"
  }},
```

```
    "col_format": {{
      "Date": "string - date (Month Day
          format)",
      "Opponent": "string - team names",
      "Site": "string - locations with
          venue details",
      "Result": "string - game results (
          W/T/L followed by score)"
    }},
    "entities": {{
      "Notre Dame Fighting Irish": {{
        "type": "organization",
        "category": "named",
        "description": "College football
            team from the University of
            Notre Dame"
      }},
      "Ohio Northern": {{
        "type": "organization",
        "category": "named",
        "description": "Opposing college
            football team"
      }},
      "St. Viator": {{
        "type": "organization",
        "category": "named",
        "description": "Opposing college
            football team"
      }},
      "Butler": {{
        "type": "organization",
        "category": "named",
        "description": "Opposing college
            football team"
      }},
      "Cartier Field": {{
        "type": "place",
        "category": "named",
        "description": "Notre Dame's
            home football stadium"
      }},
      "South Bend": {{
        "type": "place",
        "category": "named",
        "description": "City in Indiana
            where Notre Dame is located"
      }},
      "IN": {{
        "type": "place",
        "category": "named",
        "description": "Indiana state
            abbreviation"
      }}
    }}
}}

Now, analyze this table data:

Table Source Name: "{ source_name }"
Table Data:
{ table_content }
```

I.2 Entity Extraction for Document Chunks

Listing 3: Document metadata extraction prompt

```
You are a metadata extraction engine.
    Given a block of text, parse it
    into a single valid JSON object
    following exactly this schema:

{
  "entities": {
    "<EntityName1>": {
      "details": [
        "<detailed attribute or
            description sentence>",
        âĂę
      ]
    },
    âĂę
  },
  "events": {
    "<EventName1>": {
      "date": "<YYYY-MM-DD or null>",
      "details": "<one-sentence
          context or significance>"
    },
    âĂę
  },
  "timeline": [
    "<ISO date - description>",
    âĂę
  ],
  "topic": "<one-sentence description
      of the overall content>"
}

 Instructions:
1. entities: One key per unique NAMED
   entity (not a noun phrase).
   Nicknames and abbreviations count
   as separate entities, but the
   original must be mentioned in
   details (e.g., ORIGINAL: ...).
   - details: Distinguishing
     descriptive sentences or
     attributes where the entity is
     the subject.
2. events: One key per named event.
   - date: ISO date or null.
   - details: A single-sentence
     summary of its significance.
3. timeline: Chronological array of "<
   date> - <brief description>" for
   all dated mentions.
4. topic: One sentence summarizing the
     overall theme.

Output: Pure JSON only. No markdown or
    comments.
Note: Each object must have unique
   keys.

OneâĂŘShot Example

Input Text

Bixente Jean Michel Lizarazu (Basque
    pronunciation: [biËĹÊĊente
    liËĹsÌłaraËŃsÌłu], born 9 December
    1969) is a French former
    professional footballer who played
    as a left-back.

He rose through the ranks at Bordeaux
    and finished second in the French
    First Division in 1989-1990. The
```

```
        team was relegated but won
        promotion from Second Division in
        1991-92. His Bordeaux team finished
         runners-up in the 1995-96 UEFA Cup
        .

In 1997, he joined Bayern Munich and
    won six Bundesliga championships
    and the 2000-01 UEFA Champions
    League, scoring in the final
    shootout.

Expected Output
{
   "entities": {
     "Bixente Jean Michel Lizarazu": {
        "details": [
          "Basque pronunciation: [
              biɛĹÊČente liɛĹsÌłaraɛŃsÌłu
              ]",
          "Former professional
              footballer",
          "Represented France at
              international level",
          "Born 9 December 1969",
          "Played as a left-back"
        ]
     },
     "Bordeaux FC": {
        "details": [
          "French football club",
          "Club where Lizarazu began his
              professional career"
        ]
     },
     "Bayern Munich": {
        "details": [
          "German club Lizarazu joined
              in 1997",
          "Top-tier Bundesliga club"
        ]
     },
     "Bundesliga": {
        "details": [
          "Top division of German
              football"
        ]
     },
     "France": {
        "details": [
          "Country where Lizarazu was
              born and began his football
              career"
        ]
     },
     "French First Division": {
        "details": [
          "Top-tier football league in
              France (now Ligue 1)"
        ]
     },
     "French Second Division": {
        "details": [
          "Second-tier football league
              in France (now Ligue 2)"
        ]
     }
   },
   "events": {
```

```
     "1989-1990 French First Division
         season": {
       "date": "1989-1990",
       "details": "Early top-tier
           success in France"
     },
     "1991-1992 French Second Division
         promotion": {
       "date": "1991-1992",
       "details": "Return to French
           First Division after
           relegation"
     },
     "1995-1996 UEFA Cup Final": {
       "date": "1996-05-08",
       "details": "Major European final
           for a French club"
     },
     "1997 Transfer to Bayern Munich":
         {
       "date": "1997-07-01",
       "details": "Transfer from French
           to German football"
     },
     "2001 UEFA Champions League Final
         ": {
       "date": "2001-05-23",
       "details": "Lizarazu secured
           European title with German
           club"
     }
   },
   "timeline": [
     "1969-12-09 - Birth of Bixente
         Jean Michel Lizarazu in France
         ",
     "1989-08-xx - Start of 1989-1990
         French First Division season",
     "1991-08-xx - Start of 1991-1992
         French Second Division season",
     "1996-05-08 - 1995-1996 UEFA Cup
         Final",
     "1997-07-01 - Lizarazu joins
         Bayern Munich in the Bundesliga
         ",
     "2001-05-23 - 2001 UEFA Champions
         League Final"
   ],
   "topic": "Club career progression
       and major achievements of Bixente
       Lizarazu across France and
       Germany, including French and
       German domestic leagues"
}

CRITICAL REQUIREMENTS:
- Include EVERY entity or event
   mentioned directly or indirectly in
    the text.
- Ensure all delimiters and quotes are
    correctly placed.
- Verify that your output is valid
   JSON.
- Use only the specified keys; do not
   add additional keys.
- Output a JSON object only (no
   variable assignments or equal signs
   ).
```

```
Given any new text chunk, output
    exactly this JSON structure with
    all fields populated from the text.

This is the text you must parse and
    provide metadata for:
Document Title: "{ doc_title }"
Document Content: { doc_content }
```

J   Prompts for Agentic baseline

J.1   AMAZON

Listing 4: Neo4j prompt for schema-aware retrieval on Amazon graph

```
### Neo4j Graph Database (Write Cypher
    Queries Directly)
For ALL graph traversal, write Cypher
    queries directly. Do NOT use
    function calls for graph traversal.

All graph data is in Neo4j. You must:
1) Understand the question: which
    entities and relationships are
    involved?
2) Plan the traversal: which node
    labels, relationships, and
    constraints are needed?
3) Write Cypher: output ONE Cypher
    query that returns the answer
    candidates.

Neo4j graph schema:
(Product)-[:HAS_REVIEW]->(Review)
                Products have customer
    reviews
(Product)-[:ALSO_BUY]-(Product)
                Co-purchase
    recommendations
(Product)-[:ALSO_VIEW]-(Product)
                Co-view recommendations

Product properties (selected):
- p.nodeId (int, unique)
- p.asin (str, unique)
    Amazon Standard Identification
    Number
- p.title (str)
- p.brand (str)
- p.price (str)
    String format: "$11.80"
- p.color (str/list)
- p.globalCategory (str)
    High-level category
- p.category (list[str])
    Specific categories
- p.feature (list[str])
    Product features/specifications
- p.description (list[str])
    Product descriptions
- p.details (str)
    JSON-encoded specifications
- p.rank (str)
    Sales rank

Review properties (selected):
```

```
- r.nodeId (int, unique)
- r.asin (str)
    Product ASIN
- r.reviewerID (str)
- r.overall (float)
    Star rating (1.0 to 5.0)
- r.reviewText (str)
- r.summary (str)
    Review title
- r.verified (bool)
    Verified purchase
- r.reviewTime (str)
    Review date
- r.vote (str)
    Helpful vote count
- r.style (str)
    Product variant info (JSON)

Cypher examples:

Example 1: Products by brand in a
    category
MATCH (p:Product)
WHERE toLower(p.brand) CONTAINS 'nike'
RETURN p.nodeId

Example 2: Products with specific
    features
MATCH (p:Product)
WHERE toLower(p.title) CONTAINS '
    backpack'
  AND (toLower(p.feature) CONTAINS '
    waterproof'
      OR toLower(p.description)
          CONTAINS 'waterproof')
RETURN p.nodeId

Example 3: Products with specific
    rated reviews, sorted by average
    rating
MATCH (p:Product)-[:HAS_REVIEW]->(r:
    Review)
WHERE toLower(p.title) CONTAINS '
    baseball cap'
  AND r.overall >= 4.0
RETURN p.nodeId, avg(r.overall) AS
    avgRating, count(r) AS reviewCount
ORDER BY avgRating DESC, reviewCount
    DESC

Example 4: Products under a price
    threshold
MATCH (p:Product)
WHERE toLower(p.title) CONTAINS 'knife
    '
  AND toFloat(substring(p.price, 1)) <
      20.0
RETURN p.nodeId

Example 5: Recommendations based on co
    -purchase
MATCH (bought:Product)-[:ALSO_BUY]-(p:
    Product)
WHERE bought.asin = '0000032042'
  AND toLower(p.title) CONTAINS '
    accessories'
RETURN DISTINCT p.nodeId
```

J.2 MAG

Listing 5: Neo4j prompt for schema-aware retrieval

```
### Neo4j Graph Database (Write Cypher
    Queries Directly)
For ALL graph traversal, write Cypher
    queries directly. Do NOT use
    function calls for graph traversal.

All graph data is in Neo4j. You must:
1) Understand the question: which
    entities and relationships are
    involved?
2) Plan the traversal: which node
    labels, relationships, and
    constraints are needed?
3) Write Cypher: output ONE Cypher
    query that returns the answer
    candidates.

Neo4j graph schema:
(Author)-[:AUTHORED]->(Paper)
                      Authors write
    papers
(Paper)-[:CITES]->(Paper)
                      Citation
    network
(Paper)-[:HAS_FIELD]->(Field)
                      Fields of study
(Author)-[:AFFILIATED_WITH]->(
    Institution)    Author affiliations

Paper properties (selected):
- p.paperId (int, unique)
- p.title (str)
- p.abstract (str)
- p.year (int)
- p.date (str)  Use p.date for exact
    date constraints (e.g.,
    '2016-02-11')
- p.journalDisplayName (str)
- p.docType (str)
- p.paperCitationCount (int)  Use for
    "most cited" constraints

Author properties (selected):
- a.authorId (int, unique)
- a.name (str)
- a.displayName (str)

Field properties (selected):
- f.fieldId (int, unique)
- f.name (str)

Institution properties (selected):
- i.institutionId (int, unique)
- i.name (str)

Cypher examples:

 Example  1: Papers by an author in a
    given year
MATCH (:Author {authorId: 324400})-[:
    AUTHORED]->(p:Paper)
WHERE p.year = 2017
RETURN p.paperId

 Example  2: Papers by exact date (use p
    .date, not only p.year)
```

```
MATCH (p:Paper)
WHERE p.date = '2016-02-11'
RETURN p.paperId

 Example  3: Most cited paper matching a
    textual constraint
MATCH (p:Paper)
WHERE toLower(p.title) CONTAINS
    toLower('graph retrieval')
   OR toLower(p.abstract) CONTAINS
       toLower('graph retrieval')
RETURN p.paperId, p.paperCitationCount
ORDER BY p.paperCitationCount DESC
LIMIT 1
```

J.3 PRIME

Listing 6: Neo4j prompt for schema-aware retrieval on PRIME graph

```
### Neo4j Graph Database (Write Cypher
    Queries Directly)
For ALL graph traversal, write Cypher
    queries directly. Do NOT use
    function calls for graph traversal.

All graph data is in Neo4j. You must:
1) Understand the question: which
    entities and relationships are
    involved?
2) Plan the traversal: which node
    labels, relationships, and
    constraints are needed?
3) Write Cypher: output ONE Cypher
    query that returns the answer
    candidates.

Neo4j graph schema:
(Gene)-[:INTERACTS_WITH_PROTEIN]-(Gene
    )              Protein-protein
    inter actions
(Drug)-[:TARGETS]->(Gene)
                      Drug
    targets gene/protein
(Drug)-[:INDICATED_FOR]->(Disease)
                  Drug treats
    disease
(Drug)-[:CONTRAINDICATED_FOR]->(
    Disease)          Drug should
    NOT be used
(Drug)-[:SYNERGISTIC_WITH]-(Drug)
                      Drug synergy
(Drug)-[:HAS_SIDE_EFFECT]->(Phenotype)
                  Drug side effects
(Gene)-[:ASSOCIATED_WITH]-(Disease)
                      Gene-disease
    associations
(Gene)-[:EXPRESSED_IN]->(Anatomy)
                      Gene expression
    in tissue
(Gene)-[:INTERACTS_WITH]->(Pathway)
                      Gene in pathway
(Gene)-[:INTERACTS_WITH]->(
    MolecularFunction)      Gene
    function
(Gene)-[:INTERACTS_WITH]->(
    BiologicalProcess)      Gene in
    process
```

```
(Disease)-[:PHENOTYPE_PRESENT]->(
    Phenotype)           Disease
    symptoms
(Disease)-[:LINKED_TO]->(Exposure)
                         Disease
    environmental links

Node properties (selected):
Gene:
- g.nodeId (int, unique)
- g.name (str)
- g.sourceId (str)
- g. details Json (str)
    Contains: summary, aliases,
    location

Disease:
- d.nodeId (int, unique)
- d.name (str)
- d.sourceId (str)
- d. details Json (str)
    Contains: definition, symptoms

Drug:
- drug.nodeId (int, unique)
- drug.name (str)
- drug.sourceId (str)
- drug. details Json (str)
    Contains: mechanism, indication

Phenotype:
- p.nodeId (int, unique)
- p.name (str)

Pathway:
- pw.nodeId (int, unique)
- pw.name (str)
- pw.stId (str)
    Reactome stable ID
- pw. details Json (str)

Anatomy:
- a.nodeId (int, unique)
- a.name (str)

MolecularFunction, BiologicalProcess,
    CellularComponent:
- nodeId, name (standard properties)

Cypher examples:

 Example  1: Disease with multiple
    phenotypes
MATCH (d:Disease)-[:PHENOTYPE_PRESENT
    ]->(p:Phenotype)
WHERE p.name IN ['pharyngitis', '
    chemosis']
RETURN DISTINCT d.nodeId, d.name

 Example  2: Drug for a disease
MATCH (drug:Drug)-[:INDICATED_FOR]->(d
    :Disease)
WHERE d.name = 'sclerosing cholangitis
    '
RETURN drug.nodeId, drug.name

 Example  3: Gene with protein-protein
    inter actions
MATCH (g:Gene)-[:
    INTERACTS_WITH_PROTEIN]-(g2:Gene)
```

```
WHERE g2.name IN ['hbq1', 'sirt5']
RETURN DISTINCT g.nodeId, g.name

 Example  4: Gene in pathway and
    biological process
MATCH (g:Gene)-[:INTERACTS_WITH]->(bp:
    BiologicalProcess)
MATCH (g)-[:INTERACTS_WITH]->(pw:
    Pathway)
WHERE bp.name = 'cellular response to
    manganese ion'
  AND toLower(pw.name) CONTAINS 'atp'
RETURN g.nodeId, g.name

 Example  5: Drug with target and
    contraindication
MATCH (drug:Drug)-[:TARGETS]->(g:Gene)
MATCH (drug)-[:CONTRAINDICATED_FOR]->(
    d:Disease)
WHERE g.name = 'ccr5'
  AND d.name = 'gout'
RETURN drug.nodeId, drug.name
```