FREE ENERGY-BASED REINFORCEMENT LEARNING USING A QUANTUM PROCESSOR

ABSTRACT

Recent theoretical and experimental results suggest the possibility of using current and near-future quantum hardware in challenging sampling tasks. In this paper, we introduce free energy-based reinforcement learning (FERL) as an application of quantum hardware. We propose a method for processing a quantum annealer's measured qubit spin configurations in approximating the free energy of a quantum Boltzmann machine (QBM). We then apply this method to perform reinforcement learning on the grid-world problem using the D-Wave 2000Q quantum annealer. The experimental results show that our technique is a promising method for harnessing the power of quantum sampling in reinforcement learning tasks.

1 INTRODUCTION

Reinforcement learning Sutton & Barto (1998); Bertsekas & Tsitsiklis (1996) has been successfully applied in fields such as engineering Derhami et al. (2013); Syafiie et al. (2007), sociology Erev & Roth (1998); Shteingart & Loewenstein (2014), and economics Matsui et al. (2011); Sui et al. (2010). The training samples in reinforcement learning are provided by the interaction of an agent with an ambient environment. For example, in a motion planning problem in uncharted territory, it is desirable for the agent to learn in the fastest way possible to correctly navigate, making the fewest blind decisions. That is, neither exploration nor exploitation can be pursued exclusively without either facing a penalty or failing at the task. Our goal is, therefore, not only to design an algorithm that eventually converges to an optimal policy, but for the algorithm to be able to generate suboptimal policies early in the learning process.

Free energy-based reinforcement learning (FERL) using a restricted Boltzmann machine (RBM), as suggested by Sallans & Hinton (2004), relies on approximating a utility function for the agent, called the Q-function, using the free energy of an RBM. RBMs have the advantage that their free energy can be efficiently calculated using closed formulae. RBMs can represent any joint distribution over binary variables Martens et al. (2013); Hornik et al. (1989); Le Roux & Bengio (2008); however, this property of universality may require exponentially large RBMs Martens et al. (2013); Le Roux & Bengio (2008).

Crawford et al. (2016) generalize this method by proposing the use of a quantum or quantum-inspired algorithm for efficiently approximating the free energy of a general Boltzmann machine (GBM) (in general, using GBMs involves the NP-hard problem of sampling from a Boltzmann distribution). Using numerical simulations, Crawford et al. show that FERL using a deep Boltzmann machine (DBM) can provide a drastic improvement in the early stages of learning. A quantum annealer consisting of a network of quantum bits (qubits) can provide samples that approximate a Boltzmann distribution of a system of pairwise interacting qubits called the transverse-field Ising model (TFIM). The free energy of the Hamiltonian of a TFIM contains not only information about the qubits in the measurement basis, but also about their spin in a transverse direction. Using numerical simulation, Crawford et al. show that this richer, many-body system can provide the same (in fact, slightly better) learning efficiency.

In this paper, we report the results of using the D-Wave 2000Q quantum processor to experimentally verify the conjecture of Crawford et al. (2016): the applicability of a quantum annealer in reinforcement learning.

2 PRELIMINARIES

We refer the reader to Sutton & Barto (1998) and Yuksel (2016) for an exposition on Markov decision processes (MDP), controlled Markov chains, and the various broad aspects of reinforcement learning. A *Q-function* is defined by mapping a tuple (π, s, a) of a given *stationary policy* π, a current state s, and an immediate action a of a controlled Markov chain to the expected value of the instantaneous and future discounted rewards of the Markov chain that begins with taking action a at initial state s and continuing according to π:

$$Q(\pi, s, a) = \mathbb{E}[r\,(s,\,a)] + \mathbb{E}\left[\sum_{i=1}^{\infty} \gamma^i\, r\,(\Pi_i^s,\, \pi(\Pi_i^s))\right].$$

Here, $r(s,a)$ is a random variable, perceived by the agent from the environment, representing the immediate reward of taking action a from state s, and Π is the Markov chain resulting from restricting the controlled Markov chain to the policy π. The fixed real number $\gamma \in (0,1)$ is the *discount factor* of the MDP. From $Q^*(s,a) = \max_\pi Q(\pi, s, a)$, the optimal policy for the MDP can be retrieved via

$$\pi^*(s) = \mathrm{argmax}_a\, Q^*(s, a). \tag{1}$$

This reduces the MDP task to computing $Q^*(s,a)$. Through the Bellman optimality equation Bellman (1956), we get

$$Q^*(s,a) = \mathbb{E}[r\,(s,\,a)] + \gamma \sum_{s'} \mathbb{P}(s'|s,a) \max_{a'} Q^*(s', a'), \tag{2}$$

so Q^* is the fixed point of the following operator defined on $L_\infty(S \times A)$:

$$T(Q) : (s,a) \mapsto \mathbb{E}[r\,(s,\,a)] + \gamma \int \max_{a'} Q.$$

In this paper, we focus on the TD(0) Q-learning method, with the Q-function parametrized by neural networks in order to find $\pi^*(s)$ and $Q^*(s,a)$, which is based on minimizing the distance between $T(Q)$ and Q.

2.1 CLAMPED BOLTZMANN MACHINES

A clamped Boltzmann machine is a GBM in which all visible nodes **v** are prescribed fixed assignments and removed from the underlying graph. Therefore, the energy of the clamped Boltzmann machine may be written as

$$\mathcal{H}_{\mathbf{v}}(\mathbf{h}) = - \sum_{v \in V,\, h \in H} w^{vh} v h - \sum_{\{h, h'\} \subseteq H} w^{hh'} h h', \tag{3}$$

where V and H are the sets of visible and hidden nodes, respectively, and by a slight abuse of notation, a letter v stands both for a graph node $v \in V$ and for the assignment $v \in \{0, 1\}$. The interactions between the variables represented by their respective nodes are specified by real-valued weighted edges of the underlying undirected graph represented by w^{vh}, and $w^{hh'}$ denotes the weights between visible and hidden, or hidden and hidden, nodes of the Boltzmann machine, respectively.

A clamped quantum Boltzmann machine (QBM) has the same underlying graph as a clamped GBM, but instead of a binary random variable, qubits are associated to each node of the network. The energy function is substituted by the quantum Hamiltonian of an induced TFIM, which is mathematically a Hermitian matrix

$$\mathcal{H}_{\mathbf{v}} = - \sum_{v \in V,\, h \in H} w^{vh} v \sigma_h^z - \sum_{\{h, h'\} \subseteq H} w^{hh'} \sigma_h^z \sigma_{h'}^z - \Gamma \sum_{h \in H} \sigma_h^x, \tag{4}$$

where σ_h^z represent the Pauli z-matrices and σ_h^x represent the Pauli x-matrices. Thus, a clamped QBM with $\Gamma = 0$ is equivalent to a clamped classical Boltzmann machine. This is because, in this case, $\mathcal{H}_{\mathbf{v}}$ is a diagonal matrix in the σ^z-basis, the spectrum of which is identical to the range of the classical Hamiltonian (3). We note that (4) is a particular instance of a TFIM:

$$\mathcal{H} = - \sum_{i,j} J_{i,j} \sigma_i^z \sigma_j^z - \sum_i h_i \sigma_i^z - \Gamma \sum_i \sigma_i^x. \tag{5}$$

The remainder of this section is formulated for the clamped QBMs, acknowledging that it can easily be specialized for clamped classical Boltzmann machines.

2.2 FREE ENERGY-BASED REINFORCEMENT LEARNING

Let $\beta = \frac{1}{k_B T}$ be a fixed thermodynamic beta. For an assignment of visible variables $\mathbf{v}$, $F(\mathbf{v})$ denotes the *equilibrium free energy*, and is given via

$$F(\mathbf{v}) := -\frac{1}{\beta} \ln Z_{\mathbf{v}} = \langle \mathcal{H}_{\mathbf{v}} \rangle + \frac{1}{\beta} \operatorname{tr}(\rho_{\mathbf{v}} \ln \rho_{\mathbf{v}}). \tag{6}$$

Here, $Z_{\mathbf{v}} = \operatorname{tr}(e^{-\beta \mathcal{H}_{\mathbf{v}}})$ is the partition function of the clamped QBM and $\rho_{\mathbf{v}}$ is the density matrix $\rho_{\mathbf{v}} = \frac{1}{Z_{\mathbf{v}}} e^{-\beta \mathcal{H}_{\mathbf{v}}}$. The term $-\operatorname{tr}(\rho_{\mathbf{v}} \ln \rho_{\mathbf{v}})$ is the entropy of the system. The notation $\langle \cdots \rangle$ is used for the expected value of any observable with respect to the Gibbs measure (i.e., the Boltzmann distribution), in particular,

$$\langle \mathcal{H}_{\mathbf{v}} \rangle = \frac{1}{Z_{\mathbf{v}}} \operatorname{tr}(\mathcal{H}_{\mathbf{v}} e^{-\beta \mathcal{H}_{\mathbf{v}}}).$$

Inspired by the ideas of Sallans & Hinton (2004) and Amin et al. (2016), we use the negative free energy of a QBM to approximate the Q-function through the relationship

$$Q(s, a) \approx -F(\mathbf{s}, \mathbf{a}) = -F(\mathbf{s}, \mathbf{a}; \boldsymbol{w})$$

for each admissible state–action pair $(s, a) \in S \times A$. Here, $\mathbf{s}$ and $\mathbf{a}$ are binary vectors encoding the state s and action a on the state nodes and action nodes, respectively, of a QBM. In reinforcement learning, the visible nodes of a GBM are partitioned into two subsets of state nodes S and action nodes A. Here, $\boldsymbol{w}$ represents the vector of weights of a QBM as in (4). Each entry w of $\boldsymbol{w}$ can now be trained using the TD(0) update rule:

$$\Delta w = -\varepsilon (r_n(s_n, a_n) - \gamma F(s_{n+1}, a_{n+1}) + F(s_n, a_n)) \frac{\partial F}{\partial w}.$$

As shown in Crawford et al. (2016), from (6) we obtain

$$\Delta w^{vh} = \varepsilon (r_n(s_n, a_n) \tag{7}$$
$$- \gamma F(s_{n+1}, a_{n+1}) + F(s_n, a_n)) v \langle \sigma_h^z \rangle \quad \text{and}$$

$$\Delta w^{hh'} = \varepsilon (r_n(s_n, a_n) \tag{8}$$
$$- \gamma F(s_{n+1}, a_{n+1}) + F(s_n, a_n)) \langle \sigma_h^z \sigma_{h'}^z \rangle.$$

This concludes the development of the FERL method using QBMs. We refer the reader to Algorithm 3 in Crawford et al. (2016) for more details. What remains to be done is to approximate values of the free energy $F(s, a)$ and also the expected values of the observables $\langle \sigma_h^z \rangle$ and $\langle \sigma_h^z \sigma_{h'}^z \rangle$. In this paper, we demonstrate how quantum annealing can be used to address this challenge.

2.3 ADIABATIC EVOLUTION OF OPEN QUANTUM SYSTEMS

The evolution of a quantum system under a slowly changing, time-dependent Hamiltonian is characterized by Born & Fock (1928). The *quantum adiabatic theorem* (QAT) in Born & Fock (1928) states that the system remains in its instantaneous steady state, provided there is a gap between the eigen-energy of the steady state and the rest of the Hamiltonian's spectrum at every point in time. QAT motivated Farhi et al. (2000) to introduce a paradigm of quantum computing known as quantum adiabatic computation which is closely related to the quantum analogue of simulated annealing, namely *quantum annealing* (QA), introduced by Kadowaki & Nishimori (1998).

The history of QA and QAT inspired manufacturing efforts towards physical realizations of adiabatic evolution via quantum hardware Johnson et al. (2011). In reality, the manufactured chips are operated at a non-zero temperature and are not isolated from their environment. Therefore, the existing adiabatic theory does not cover the behaviour of these machines. A contemporary investigation in quantum adiabatic theory was therefore initiated to study adiabaticity in open quantum systems Sarandy & Lidar (2005); Venuti et al. (2016); Albash et al. (2012); Avron et al. (2012); Bachmann et al. (2016). These sources prove adiabatic theorems for open quantum systems under various assumptions, in particular when the quantum system is coupled to a thermal bath satisfying the Kubo–Martin–Schwinger condition, implying that the instantaneous steady state is the instantaneous Gibbs state. This work in progress shows promising opportunities to use quantum annealers to sample from the Gibbs state of a TFIM.

Figure 1: (left) Two adjacent unit cells of the D-Wave 2000Q chip. The intra-cell couplings provide a fully connected bipartite subgraph. However, there are only four inter-cell couplings. (right) The Chimera graph representing the connectivity of the two unit cells of qubits.

In practice, due to additional complications (e.g., level crossings and gap closure, described in the references above), the samples gathered from the quantum annealer are far from the Gibbs state of the final Hamiltonian. In fact, Amin (2015) suggests that the distribution of the samples would instead correspond to an instantaneous Hamiltonian at an intermediate point in time, called the *freeze-out point*. Unfortunately, this point and, consequently, the strength Γ of the transverse field at this point, is not known a priori, and also depends on the TFIM undergoing evolution. Our goal is simply to associate a single (average) *virual* Γ to all TFIMs constructed through FERL. Another unknown parameter is the inverse temperature β, at which the Gibbs state, the partition function, and the free energy are attained. In a similar fashion, we wish to associate a single *virtual* β to all TFIMs encountered.

The quantum annealer used in our experiments is the D-Wave 2000Q, which consists of a chip of superconducting qubits connected to each other according to a sparse adjacency graph called the *Chimera graph*. The Chimera graph structure looks significantly different from the frequently used models in machine learning, e.g., RBMs and DBMs, which consist of consecutive fully connected bipartite graphs. Fig 1 shows two adjacent blocks of the Chimera graph which consist of 16 qubits, which, in this paper, serve as the clamped QBM used in FERL.

Another complication when using a quantum annealer as a QBM is that the spin configurations of the qubits can only be measured along a fixed axis (here the z-basis of the Bloch sphere). Once σ^z is measured, all of the quantum information related to the projection of the spin along the transverse field (i.e., the spin σ^x) collapses and cannot be retrieved. Therefore, even with a choice of virtual Γ, virtual β, and all of the measured configurations, the energy of (5) is still unknown. We propose a method for overcoming this challenge based on the Suzuki–Trotter expansion of the TFIM, which we call *replica stacking*, the details of which are explained in §3.4. In §4, we perform a grid search over values of the virtual parameters β and Γ. The accepted virtual parameters are the ones that result in the most-effective learning for FERL in the early stages of training.

3 FREE ENERGY OF QUANTUM BOLTZMANN MACHINES

3.1 SUZUKI–TROTTER REPRESENTATION

By the Suzuki–Trotter decomposition Suzuki (1976), the partition function of the TFIM defined by the Hamiltonian (4) can be approximated using the partition function of a classical Hamiltonian denoted by $\mathcal{H}_{\mathbf{v}}^{\mathrm{eff}}$ and called an effective Hamiltonian, which corresponds to a classical Ising model of one dimension higher. More precisely,

$$\mathcal{H}_{\mathbf{v}}^{\mathrm{eff}}(\mathbf{h}) = -\sum_{h,h'}\sum_{k=1}^{r}\frac{w^{hh'}}{r}h_k h_k' - \sum_{v,h}\sum_{k=1}^{r}\frac{w^{vh}v}{r}h_k \qquad (9)$$

$$-w^+\left(\sum_h\sum_{k=1}^{r}h_k h_{k+1} + \sum_h h_1 h_r\right),$$

Figure 2: (left) A transverse-field Ising model consisting of 16 qubits arranged on a two-dimensional lattice with nearest neighbour couplings. (right) The corresponding effective classical Ising model with ten replicas arranged in a three-dimensional solid torus.

where r is the number of replicas, $w^+ = \frac{1}{2\beta} \log \coth \left(\frac{\Gamma\beta}{r} \right)$, and h_k represent spins of the classical system of one dimension higher. Note that each hidden node's Pauli z-matrices σ_h^z are represented by r classical spins, denoted by h_k, with a slight abuse of notation. In other words, the original Ising model with a non-zero transverse field represented through non-commuting operators can be mapped to a classical Ising model of one dimension higher. Fig. 2 shows the underlying graph of a TFIM on a two-dimensional lattice and a corresponding ten-replica effective Hamiltonian in three dimensions.

3.2   APPROXIMATION OF FREE ENERGY USING GIBBS SAMPLING

To approximate the right-hand side of (7) and (8), we sample from the Boltzmann distribution of the effective Hamiltonian using (Suzuki, 1976, Theorem 6). We find the expected values of the observables $\langle \sigma_h^z \rangle$ and $\langle \sigma_h^z \sigma_{h'}^z \rangle$ by averaging the corresponding classical spin values. To approximate the Q-function, we use (Suzuki, 1976, Theorem 4) to substitute (6) by

$$F(\mathbf{v}) = \langle \mathcal{H}_{\mathbf{v}}^{\text{eff}} \rangle + \frac{1}{\beta} \sum_{c_{\text{eff}}} \mathbb{P}(c_{\text{eff}}|\mathbf{v}) \log \mathbb{P}(c_{\text{eff}}|\mathbf{v}) \,, \tag{10}$$

where $\mathcal{H}_{\mathbf{v}}^{\text{eff}}$ is the effective Hamiltonian and c_{eff} ranges over all spin configurations of the effective classical Ising model of one dimension higher, defined by $\mathcal{H}_{\mathbf{v}}^{\text{eff}}$.

The above argument also holds in the absence of the transverse field, that is, for the classical Boltzmann machine. In this case, the TD(0) update rule is given by

$$\Delta w^{vh} = \varepsilon(r_n(s_n, a_n) \tag{11}$$
$$+ \gamma Q(s_{n+1}, a_{n+1}) - Q(s_n, a_n))v\langle h \rangle \quad \text{and}$$
$$\Delta w^{hh'} = \varepsilon(r_n(s_n, a_n) \tag{12}$$
$$+ \gamma Q(s_{n+1}, a_{n+1}) - Q(s_n, a_n))\langle hh' \rangle \,,$$

where $\langle h \rangle$ and $\langle hh' \rangle$ are the expected values of the variables and the products of the variables, respectively, in the binary encoding of the hidden nodes with respect to the Boltzmann distribution of the classical Hamiltonian (3). The values of the Q-functions in (11) and (12) can also be approximated

empirically, since, in a classical Boltzmann machine,

$$F(\mathbf{v}) = \sum_{\mathbf{h}} \mathbb{P}(\mathbf{h}|\mathbf{v}) \mathscr{E}_{\mathbf{v}}(\mathbf{h}) + \frac{1}{\beta} \sum_{\mathbf{h}} \mathbb{P}(\mathbf{h}|\mathbf{v}) \log \mathbb{P}(\mathbf{h}|\mathbf{v}) \qquad (13)$$

$$= -\sum_{\substack{s \in S \\ h \in H}} w^{sh} s \langle h \rangle - \sum_{\substack{a \in A \\ h \in H}} w^{ah} a \langle h \rangle - \sum_{\{h,h'\} \subseteq H} u^{hh'} \langle hh' \rangle$$

$$+ \frac{1}{\beta} \sum_{\mathbf{h}} \mathbb{P}(\mathbf{h}|\mathbf{s}, \mathbf{a}) \log \mathbb{P}(\mathbf{h}|\mathbf{s}, \mathbf{a}).$$

3.3 SIMULATED QUANTUM ANNEALING

One way to sample spin values from the Boltzmann distribution of the effective Hamiltonian is to use the simulated quantum annealing algorithm (SQA) (see (Anthony Brabazon, 2015, p. 422) for an introduction). SQA is one of the many flavours of quantum Monte Carlo methods, and is based on the Suzuki–Trotter expansion described above. This algorithm simulates the quantum annealing phenomena of a TFIM by slowly reducing the strength of the transverse field at finite temperature to the desired target value. In our implementation, we have used a single spin-flip variant of SQA with a linear transverse-field schedule as in Martoňák et al. (2002) and Heim et al. (2015). Experimental studies have shown similarities in the behaviour of SQA and that of quantum annealing Isakov et al. (2015); Albash et al. (2014) and its physical realization Brady & van Dam (2016); Shin et al. (2014) by D-Wave Systems.

The classical counterpart of SQA is conventional simulated annealing (SA), which is based on thermal annealing. This algorithm can be used to sample from Boltzmann distributions that correspond to an Ising spin model in the absence of a transverse field (i.e., $\Gamma = 0$ in (5)). Unlike SA, it is possible to use SQA not only to approximate the Boltzmann distribution of a classical Boltzmann machine, but also that of a quantum Hamiltonian in the presence of a transverse field. This can be done by reducing the strength of the transverse field to the desired value defined by the model, rather than to zero. It has been proven by Morita & Nishimori (2006) that the spin system defined by SQA converges to the Boltzmann distribution of the effective classical Hamiltonian of one dimension higher that corresponds to the quantum Hamiltonian. Therefore, it is straightforward to use SQA to approximate the free energy in (10) as well as the observables $\langle \sigma_h^z \rangle$ and $\langle \sigma_h^z \sigma_{h'}^z \rangle$.

3.4 REPLICA STACKING

As explained in §2.3, a quantum annealer provides measurements of σ^z spins for each qubit in the TFIM. The observables $\langle \sigma_h^z \rangle$ and $\langle \sigma_h^z \sigma_{h'}^z \rangle$ can therefore be approximated by averaging over the spin configurations measured by the quantum annealer. Moreover, by (Suzuki, 1976, Theorem 6) and translation invariance, each replica of the effective classical model is an approximation of the spin measurements of the TFIM in the measurement bases σ^z. Therefore, a σ^z-configuration sampled by a quantum annealer that operates at a given *virtual* inverse temperature β and anneals up to a *virtual* transverse-field strength Γ, may be viewed as an instance of a classical spin configuration from a replica of the classical effective Hamiltonian of one dimension higher.

This suggests the following method to approximate the free energy from (10) for a TFIM. We gather a pool $\mathscr{C}$ of configurations sampled by the quantum annealer for the TFIM considered, allowing repetitions. Let r be the number of replicas. We write $c_{\text{eff}} = (c_1, \ldots, c_r)$ to indicate an effective configuration c_{eff} with the classical configurations c_1 to c_r as its replicas. We write $\underline{c_{\text{eff}}}$ to denote the underlying set $\{c_1, \ldots, c_r\}$ of replicas of c_{eff} (forgetting their ordering). We have

$$\mathbb{P}\left[c_{\text{eff}} = (c_1, \ldots, c_r)\right]$$
$$= \mathbb{P}\left[c_{\text{eff}} = (c_1, \ldots, c_r)|\underline{c_{\text{eff}}} = \{c_1, \ldots, c_r\}\right]$$
$$\times \mathbb{P}\left[\underline{c_{\text{eff}}} = \{c_1, \ldots, c_r\}\right]$$
$$= \mathbb{P}\left[c_{\text{eff}} = (c_1, \ldots, c_r)|\underline{c_{\text{eff}}} = \{c_1, \ldots, c_r\}\right]$$
$$\times \mathbb{P}\left[\underline{c_{\text{eff}}} = \{c_1, \ldots, c_r\}|\underline{c_{\text{eff}}} \subseteq \mathscr{C}\right] \times \mathbb{P}\left[\underline{c_{\text{eff}}} \subseteq \mathscr{C}\right]. \quad (14)$$

The argument in the previous paragraph can now be employed to allow the assumption

$$\mathbb{P}\left[\underline{c_{\text{eff}}} \subseteq \mathscr{C}\right] \simeq 1.$$

Figure 3: (left) A 3×5 grid-world problem instance with one reward, one wall, and one penalty. (right) An optimal policy for this problem instance is a selection of directional arrows indicating movement directions.

In other words, the probability mass function of the effective configurations is supported in the subset of those configurations synthesized from the elements of $\mathscr{C}$ as *candidate replicas*.

The conditional probability $\mathbb{P}[\underline{c}_{\text{eff}} = \{c_1, \ldots, c_r\}|\underline{c}_{\text{eff}} \subseteq \mathscr{C}]$ can be sampled from by drawing r elements $c_1, \ldots, c_r$ from $\mathscr{C}$. We then sample from $\mathbb{P}\left[c_{\text{eff}} = (c_1, \ldots, c_r)|\underline{c}_{\text{eff}} = \{c_1, \ldots, c_r\}\right]$, according to the following distribution over c_{eff}:

$$\pi(c_{\text{eff}}) \stackrel{\Delta}{=} \mathbb{P}\left[c_{\text{eff}} = (c_1, \ldots, c_r)|\underline{c}_{\text{eff}} = \{c_1, \ldots, c_r\}\right]$$
$$= \frac{e^{\beta w^+ \sum_h \left(\sum_{k=1}^{r-1} h_{c_k} h_{c_{k+1}} + h_{c_1} h_{c_r}\right)}}{\sum_{\underline{c}_{\text{eff}} = \{c_1, \ldots, c_k\}} e^{\beta w^+ \sum_h \left(\sum_{k=1}^{r-1} h_{c_k} h_{c_{k+1}} + h_{c_1} h_{c_r}\right)}}.$$

We consider $\pi(c_{\text{eff}})$ our target distribution and construct the following Markov Chain Monte Carlo (MCMC) method for which the limiting distribution is $\pi(c_{\text{eff}})$. We first attach the r classical spin configurations to the SQA's effective configuration structure uniformly at random. We then transition to a different arrangement with Metropolis acceptance probability. For example, we may choose two classical configurations at random and exchange them with probability

$$p(c_{\text{eff}}, c'_{\text{eff}}) = \min\left\{1, \exp\left(\beta(E(c'_{\text{eff}}) - E(c_{\text{eff}}))\right)\right\},$$

where $E(c_{\text{eff}}) = w^+ \sum_h \left(\sum_{k=1}^{r-1} h_{c_k} h_{c_{k+1}} + h_{c_1} h_{c_r}\right)$. It is well-known that such a stochastic process satisfies the detailed balance condition. Consequently, the MCMC allows us to sample from the effective spin configurations. This procedure of sampling and then performing MCMC creates a pool of effective spin configurations, which are then employed in equation (10) in order to approximate the free energy of the TFIM empirically.

However, we consider a relatively small number of hidden nodes in our experiments, so the number of different σ^z-configurations sampled by the quantum annealer is limited. As a consequence, there is no practical need to perform the MCMC defined above. Instead, we attach classical spin configurations from the pool to the SQA effective configuration structure at random. In other words, in r iterations, a spin configuration is sampled from the pool of classical spin configurations described above and inserted as the next replica of the effective classical Hamiltonian consisting of r replicas.

4 THE EXPERIMENTS

We benchmark our various FERL methods on a 3×5 grid-world problem Sutton (1990) with an agent capable of taking the actions up, down, left, or right, or standing still, on a grid-world with one deterministic reward, one wall, and one penalty, as shown in Fig. 3 (left). The task is to find an optimal policy, as shown in Fig. 3 (right), for the agent at each state in the grid-world. All of the Boltzmann machines used in our algorithms consist of 16 hidden nodes.

The discount factor, as explained in §2, is set to 0.8. The agent attains the reward $R = 200$ in the top-left corner, the neutral value of moving to any empty cell is 100, and the agent is penalized by not receiving any reward if it moves to the penalty cell with value $P = 0$.

For T_r independent runs of every FERL method, T_s training samples are used. The fidelity measure at the i-th training sample is defined by

$$\text{fidelity}(i) = (T_r \times |S|)^{-1} \sum_{l=1}^{T_r} \sum_{s \in S} \mathbb{1}_{A(s,i,l) \in \pi^*(s)}, \tag{15}$$

where π^* denotes the best known policy and $A(s, i, l)$ denotes the action assigned at the l-th run and i-th training sample to the state s. In our experiments, each algorithm is run 100 times.

Fig. 4 demonstrates the performance of a fully connected deep Q-network Mnih et al. (2015) consisting of an input layer of 14 state nodes, two layers of eight hidden nodes each, and an output layer of five nodes representing the values of the Q-function for different actions, given a configuration of state nodes. We use the same number of hidden nodes in the fully connected deep Q-network as in the other networks described in this paper.

4.1 GRID SEARCH FOR VIRTUAL PARAMETERS ON THE D-WAVE 2000Q

We treat the network of superconducting qubits represented in Fig. 1 as a clamped QBM with two hidden layers, represented using blue and red colours. The state nodes are considered fully connected to the blue qubits and the action nodes are fully connected to the red qubits.

For a choice of virtual parameters $\Gamma \neq 0$ and β, which appear in (9) and (10), and for each query to the D-Wave 2000Q chip, we construct 150 effective classical configurations of one dimension higher, out of a pool of 3750 reads, according to the replica stacking method introduced in §3.4. The 150 configurations are, in turn, employed to approximate the free energy of the quantum Hamiltonian. We conduct 10 independent runs of FERL in this fashion and find the average fidelity over the 10 runs and over the $T_s = 300$ training samples.

Fig. 5 shows a heatmap of the average fidelity of each choice of virtual parameters β and Γ. In the $\Gamma = 0$ row, each query to the D-Wave 2000Q is considered to be sampling from a classical GBM with Fig. 1 as the underlying graph.

4.2 FERL FOR THE GRID-WORLD PROBLEM

Fig. 6 shows the growth of the average fidelity of the best known policies generated by different FERL methods. For each method, the fidelity curve is an average over 100 independent runs, each with $T_s = 500$ training samples.

In this figure, the "D-Wave $\Gamma = 0.5$, $\beta = 2.0$" curve corresponds to the D-Wave 2000Q replica stacking-based method with the choice of the best virtual parameters $\Gamma = 0.5$ and $\beta = 2.0$, as shown in the heatmap in Fig. 5. The training is based on formulae (7), (8), and (10). The "SQA Bipartite $\Gamma = 0.5$, $\beta = 2.0$" and "SQA Chimera $\Gamma = 0.5$, $\beta = 2.0$" curves are based on the same formulae with the underlying graphs being a bipartite (DBM) and a Chimera graph, respectively, with the same choice of virtual parameters, but the effective Hamiltonian configurations generated using SQA as explained in §3.3.

Figure 4: The learning curve of a fully connected deep Q-network with two hidden layers, each with eight hidden nodes, for the grid-world problem instance as shown in Fig. 3.

Figure 5: Heatmap of average fidelity observed using various choices of virtual parameters β and Γ. The $\Gamma = 0$ row tests the performance of FERL with samples obtained from the quantum annealer treated as classical configurations of a GBM. In all other rows, samples are interpreted as σ^z-measurements of a QBM.

Figure 6: Comparison of different FERL methods for the grid-world problem instance in Fig. 3.

The "SA Bipartite $\beta = 2.0$" and "SA Chimera $\beta = 2.0$" curves are generated by using SA to train a classical DBM and a classical GBM on the Chimera graph, respectively, using formulae (11), (12), and (13). SA is run with a linear inverse temperature schedule, where $\beta = 2.0$ indicates the final value. The "D-Wave Classical $\beta = 2.0$" curve is generated using the same method, but with samples obtained using the D-Wave 2000Q. The "RBM" curve is generated using the method in Sallans & Hinton (2004).

5 DISCUSSION

We solve the grid-world problem using various Q-learning methods with the Q-function parametrized by different neural networks. For comparison, we demonstrate the performance of a fully connected

deep Q-network method that can be considered state of the art. This method efficiently processes every training sample, but, as shown in Fig. 4, requires very large number of training samples to converge to the optimal policy. Another conventional method is free energy-based reinforcement learning using an RBM. This method is also very successful at the scale of the reinforcement learning task considered in our experiment. Although this method is not outperforming other FERL methods that take advantage of a highly efficient sampling oracle, the processing of each training sample is efficient, as it is based on closed formulae. In fact, for the size of problem considered, the RBM-based FERL outperforms the fully connected deep Q-network method.

The comparison of results in Fig. 6 suggests that replica stacking is a successful method for estimating effective classical configurations obtained from a quantum annealer, given that the spins can only be measured in measurement bases. For practical use in reinforcement learning, this method provides a means of treating the quantum annealer as a QBM. FERL using the quantum annealer, in conjunction with the replica stacking technique, provides significant improvement over FERL using classical Boltzmann machines. The curve representing SQA-based FERL using a Boltzmann machine on the Chimera graph is almost coincident with the one obtained using the D-Wave 2000Q, whereas the SQA-based FERL using a DBM slightly outperforms it. This suggests that quantum annealing chips with greater connectivity and more control over annealing time can further improve the performance of the replica stacking method applied to reinforcement learning tasks. This is further supported by comparing the performance of SA-based FERL using a DBM versus SA-based FERL using the Chimera graph. This result shows that DBM is a better choice of neural network compared to the Chimera graph, due to its additional connections.

For practical reasons, we aim to associate an identical choice of virtual parameters β and Γ to all of the TFIMs constructed using FERL. Benedetti et al. (2016) and Raymond et al. (2016) provide methods for estimating the effective inverse temperature β for other applications. However, in both studies, the samples obtained from the quantum annealer are matched to the Boltzmann distribution of a classical Ising model. In fact, the transverse-field strength is a second virtual parameter that we consider. The optimal choice $\Gamma = 0.5$ corresponds to $2/3$ of the annealing time, in agreement with the work of Amin (2015), who also consider TFIM with 16 qubits.

The agreement of FERL using quantum annealer reads treated as classical Boltzmann samples with that of FERL using SA and classical Boltzmann machines suggests that, at least for this task and this size of Boltzmann machine, the measurements provided by the D-Wave 2000Q can be considered good approximations of Boltzmann distribution samples of classical Ising models.

6 CONCLUSION

In this paper, we describe a free energy-based reinforcement learning algorithm using existing quantum hardware, namely the D-Wave 2000Q. Our method relies on the Suzuki–Trotter decomposition and the use of the measured configurations by the D-Wave 2000Q as replicas of an effective classical Ising model of one dimension higher. Future research can employ these principles to solve larger-scale reinforcement learning tasks in the emerging field of quantum machine learning.

REFERENCES

T. Albash, T. F. Rønnow, M. Troyer, and D. A. Lidar. Reexamining classical and quantum models for the D-Wave One processor. *ArXiv e-prints*, September 2014.

T. Albash, S. Boixo, D. A. Lidar, and P. Zanardi. Quantum adiabatic markovian master equations. *New Journal of Physics*, 14(12):123016, 2012. URL http://stacks.iop.org/1367-2630/14/i=12/a=123016.

M. H. Amin. Searching for quantum speedup in quasistatic quantum annealers. *Phys. Rev. A*, 92(5): 052323, 2015.

M. H. Amin, E. Andriyash, J. Rolfe, B. Kulchytskyy, and R. Melko. Quantum Boltzmann machine. *arXiv:1601.02036*, 2016.

S. McGarraghy, A. Brabazon, and M. O'Neill. *Natural Computing Algorithms*. Springer-Verlag Berlin Heidelberg, 2015.

J. E. Avron, M. Fraas, G. M. Graf, and P. Grech. Adiabatic theorems for generators of contracting evolutions. *Communications in Mathematical Physics*, 314(1):163–191, 2012. ISSN 1432-0916. doi: 10.1007/s00220-012-1504-1. URL http://dx.doi.org/10.1007/s00220-012-1504-1.

S. Bachmann, W. De Roeck, and M. Fraas. The Adiabatic Theorem for Many-Body Quantum Systems. *ArXiv e-prints*, December 2016.

R. Bellman. Dynamic programming and Lagrange multipliers. *Proceedings of the National Academy of Sciences*, 42(10):767–769, 1956.

M. Benedetti, J. Realpe-Gómez, R. Biswas, and A. Perdomo-Ortiz. Estimation of effective temperatures in quantum annealers for sampling applications: A case study with possible applications in deep learning. *Phys. Rev. A*, 94:022308, Aug 2016. doi: 10.1103/PhysRevA.94.022308. URL https://link.aps.org/doi/10.1103/PhysRevA.94.022308.

D.P. Bertsekas and J.N. Tsitsiklis. *Neuro-dynamic Programming*. Anthropological Field Studies. Athena Scientific, 1996. ISBN 9781886529106. URL https://books.google.ca/books?id=WxCCQgAACAAJ.

M. Born and V. Fock. Beweis des Adiabatensatzes. *Zeitschrift fur Physik*, 51:165–180, March 1928. doi: 10.1007/BF01343193.

L. T. Brady and W. Van Dam. Quantum Monte Carlo simulations of tunneling in quantum adiabatic optimization. *Phys. Rev. A*, 93(3):032304, 2016.

D. Crawford, A. Levit, N. Ghadermarzy, J. S. Oberoi, and P. Ronagh. Reinforcement Learning Using Quantum Boltzmann Machines. *ArXiv e-prints*, December 2016.

V. Derhami, E. Khodadadian, M. Ghasemzadeh, and A. M. Z. Bidoki. Applying reinforcement learning for web pages ranking algorithms. *Applied Soft Computing*, 13(4):1686–1692, 2013.

I. Erev and A. E. Roth. Predicting how people play games: Reinforcement learning in experimental games with unique, mixed strategy equilibria. *American Economic Review*, pp. 848–881, 1998.

E. Farhi, J. Goldstone, S. Gutmann, and M. Sipser. Quantum Computation by Adiabatic Evolution. *eprint arXiv:quant-ph/0001106*, January 2000.

B. Heim, T. F. Rønnow, S. V. Isakov, and M. Troyer. Quantum versus classical annealing of Ising spin glasses. *Science*, 348(6231):215–217, 2015.

K. Hornik, M. Stinchcombe, and H. White. Multilayer feedforward networks are universal approximators. *Neural Networks*, 2(5):359–366, 1989.

S. V. Isakov, G. Mazzola, V. N. Smelyanskiy, Z. Jiang, S. Boixo, H. Neven, and M. Troyer. Understanding quantum tunneling through quantum Monte Carlo simulations. *arXiv:1510.08057*, 2015.

M. W. Johnson, M. H. S. Amin, S. Gildert, T. Lanting, F. Hamze, N. Dickson, R. Harris, A. J. Berkley, J. Johansson, P. Bunyk, E. M. Chapple, C. Enderud, J. P. Hilton, K. Karimi, E. Ladizinsky, N. Ladizinsky, T. Oh, I. Perminov, C. Rich, M. C. Thom, E. Tolkacheva, C. J. S. Truncik, S. Uchaikin, J. Wang, B. Wilson, and G. Rose. Quantum annealing with manufactured spins. *Nature*, 473(7346):194–198, 05 2011. URL http://dx.doi.org/10.1038/nature10012.

T. Kadowaki and H. Nishimori. Quantum annealing in the transverse ising model. *Phys. Rev. E*, 58: 5355–5363, Nov 1998. doi: 10.1103/PhysRevE.58.5355. URL https://link.aps.org/doi/10.1103/PhysRevE.58.5355.

N. Le Roux and Y. Bengio. Representational power of restricted Boltzmann machines and deep belief networks. *Neural Computation*, 20(6):1631–1649, 2008.

J. Martens, A. Chattopadhya, T. Pitassi, and R. Zemel. On the representational efficiency of restricted Boltzmann machines. In *Advances in Neural Information Processing Systems*, pp. 2877–2885, 2013.

R. Martoňák, G. E. Santoro, and E. Tosatti. Quantum annealing by the path-integral Monte Carlo method: The two-dimensional random Ising model. *Phys. Rev. B*, 66(9):094203, 2002.

T. Matsui, T. Goto, K. Izumi, and Y. Chen. Compound reinforcement learning: theory and an application to finance. In *European Workshop on Reinforcement Learning*, pp. 321–332. Springer, 2011.

V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Ried-miller, A. K. Fidjeland, G. Ostrovski, S. Petersen, C. Beattie, A. Sadik, I. Antonoglou, H. King, D. Kumaran, D. Wierstra, S. Legg, and D. Hassabis. Human-level control through deep reinforce-ment learning. *Nature*, 518(7540):529–533, 02 2015. URL http://dx.doi.org/10.1038/nature14236.

S. Morita and H. Nishimori. Convergence theorems for quantum annealing. *Journal of Physics A: Mathematical and General*, 39(45):13903, 2006.

J. Raymond, S. Yarkoni, and E. Andriyash. Global warming: Temperature estimation in annealers. *Frontiers in ICT*, 3:23, 2016. ISSN 2297-198X. doi: 10.3389/fict.2016.00023. URL http://journal.frontiersin.org/article/10.3389/fict.2016.00023.

B. Sallans and G. E. Hinton. Reinforcement learning with factored states and actions. *JMLR*, 5: 1063–1088, Aug 2004.

M. S. Sarandy and D. A. Lidar. Adiabatic approximation in open quantum systems. *Phys. Rev. A*, 71:012331, Jan 2005. doi: 10.1103/PhysRevA.71.012331. URL https://link.aps.org/doi/10.1103/PhysRevA.71.012331.

S. W. Shin, G. Smith, J. A. Smolin, and U. Vazirani. How "Quantum" is the D-Wave Machine? *ArXiv e-prints*, January 2014.

H. Shteingart and Y. Loewenstein. Reinforcement learning and human behavior. *Current Opinion in Neurobiology*, 25:93–98, 2014.

Z. Sui, A. Gosavi, and L. Lin. A reinforcement learning approach for inventory replenishment in vendor-managed inventory systems with consignment inventory. *Engineering Management Journal*, 22(4):44–53, 2010.

R. S. Sutton. Integrated architectures for learning, planning, and reacting based on approximating dynamic programming. In *In Proceedings of the Seventh International Conference on Machine Learning*, pp. 216–224. Morgan Kaufmann, 1990.

R. S. Sutton and A. G. Barto. *Reinforcement Learning : An Introduction*. MIT Press, 1998.

M. Suzuki. Relationship between d-dimensional quantal spin systems and $(d+1)$-dimensional Ising systems equivalence, critical exponents and systematic approximants of the partition function and spin correlations. *Progress of Theoretical Physics*, 56(5):1454–1469, 1976.

S. Syafiie, F. Tadeo, and E. Martinez. Model-free learning control of neutralization processes using reinforcement learning. *Engineering Applications of Artificial Intelligence*, 20(6):767–782, 2007.

L. C. Venuti, T. Albash, Daniel A. Lidar, and Paolo Zanardi. Adiabaticity in open quantum systems. *Phys. Rev. A*, 93:032118, Mar 2016. doi: 10.1103/PhysRevA.93.032118. URL http://link.aps.org/doi/10.1103/PhysRevA.93.032118.

S. Yuksel. Control of stochastic systems. Course lecture notes, Queen's University (Kingston, ON Canada), Retrieved in May 2016, May 2016. URL http://www.mast.queensu.ca/~math472/Math472872LectureNotes.pdf.