AN EXPERIMENTAL STUDY OF LAYER-LEVEL TRAINING SPEED AND ITS IMPACT ON GENERALIZATION

ABSTRACT

How optimization influences the generalization ability of a DNN is still an active area of research. This work aims to unveil and study a factor of influence: we show that the speed at which each layer trains, measured by the rotation rate of each layer's weight vector (or *layer rotation rate*), has a consistent and substantial impact on generalization. We develop a visualization technique and an optimization algorithm to monitor and control the layer rotation rates during training, and show across multiple tasks and training settings that rotating all the layers' weights synchronously and at high rate repeatedly induces the best generalization performance. Going further, our experiments suggest that weight decay is an essential ingredient for inducing such beneficial layer rotation rates with SGD, and that the impact of adaptive gradient methods on training speed and generalization is solely due to the modifications they induce to each layer's training speed compared to SGD. Besides these fundamental findings, we also expect that the tools we introduce will reduce the meta-parameter tuning required to get the best generalization out of a deep network.

1 INTRODUCTION

Generalization and gradient propagation are two popular themes in the deep learning literature. Concerning generalization, it has been observed that a network's ability to generalize depends on a subtle interaction between the optimization procedure and the training data (Zhang et al., 2017a; Arpit et al., 2017). Concerning gradient propagation, several works have shown that the norm of gradients can gradually increase or decrease as a function of layer depth (*i.e.* vanishing and exploding gradients (Bengio et al., 1994; Hochreiter, 1998; Glorot & Bengio, 2010)), so that some layers are trained faster than others. This work explores an interaction between generalization and the intricate nature of gradient propagation in deep networks, and focuses on the following research question: how does the speed at which each layer trains influence generalization?

Our endeavour is motivated by the following intuition: if the training data influences a neural network's generalization ability when using gradient-based optimization (Zhang et al., 2017a; Arpit et al., 2017), the input and feedback signals that a layer receives could also influence the generalization ability induced by the layer's training. Figure 1 supports our intuition with a toy example where training a single layer of an 11 layer MLP network, although always reaching 100% train accuracy, results in different test accuracies depending on the layer's localisation in the network's architecture. If our intuition holds (i.e. the signals presented to a layer influence generalization), the layer-level training speed configuration used in the full network training scenario should matter, since it directly influences how the input and feedback signals of each layer evolve over training.

Our study of layer-level training speed's impact on generalization is composed of three steps:

1. Developing tools to monitor and control layer rotation rates, a tentative measure of layer-level training speed.
2. Using our controlling tool to systematically explore layer rotation rate configurations, varying the layers which are prioritized (first layers, last layers, or no prioritization) and the global rotation rate value (high or low rate, for all layers).[1]
3. Using our monitoring tool to study the layer rotation rates that emerge from standard training settings.[1]

The first outcome of our study is that, both in controlled and standard training settings, layer rotation rates seem to have a consistent and substantial impact on the generalization ability that will emerge from training. In particular, high and uniform layer rotation rates outperform low and/or non-uniform layer rotation rates across all our experiments, leading to differences of up to 20% test accuracy. The second outcome is that the study of layer-level training speed can shine new light on deep learning techniques whose behaviour still escape our understanding. In particular, we provide considerable evidence that both weight decay's and adaptive gradient methods' impact on generalization is solely due to their influence on layer rotation rates.

While still at an experimental stage, the consistency of our empirical results provides important evidence for our claims. To encourage further validation, the tools and source code used to create all the figures of this paper are provided at -*github link hidden to preserve anonymity*- (code uses the Keras (Chollet et al., 2015) and TensorFlow (Agarwal et al., 2016) libraries). We also encourage interested readers to browse the supplementary material of this paper, as additional results are presented and discussed.

Figure 1: An eleven layer MLP network composed of 10 identical layers (each containing 784 ReLU neurons (Nair & Hinton, 2010)) is applied on a reduced MNIST dataset (LeCun et al., 1998), such that training any of the 10 layers in isolation is sufficient to get 100% training accuracy. But will training of each layer result in the same test accuracy? This figure shows the test accuracy in function of the index of the trained layer (in forward pass ordering), after averaging over 10 experiments. In this specific example, the test accuracy mostly degrades with the depth of the trained layer, with a final difference of nearly 20%. The generalization ability induced by a layer's training thus depends on the input and feedback signals it received in the course of training (everything else being equal for each layer index).

2   RELATED WORK

Recent works have demonstrated that generalization in deep neural networks was largely due to the optimization procedure and its puzzling interaction with the training data (Zhang et al., 2017a; Arpit et al., 2017). Our paper discloses an aspect of the optimization procedure that influences generalization in deep learning: the rate at which each layer's weight vector is rotated. This novel factor complements batch size and global learning rate, two parameters that have been extensively studied in the light of generalization (Keskar et al., 2017; Jastrzebski et al., 2017; Smith & Le, 2017; Smith & Topin, 2017; Hoffer et al., 2017; Masters & Luschi, 2018).

The works studying the vanishing and exploding gradients problems (Bengio et al., 1994; Hochreiter, 1998; Glorot & Bengio, 2010) heavily inspired this paper. These works introduce two ideas which are central to our investigation: the notion of layer-level training speed and the fact that SGD does not necessarily train all layers at the same speed during training. Our work explores the same phenomena, but studies them in the light of generalization instead of trainability and speed of convergence.

Our paper also proposes Layca, an algorithm to control the rate at which each layer's weight is rotated during training. It is related to the works that sought solutions to the gradient propagation problems at optimization level (Pascanu et al., 2013; Hazan et al., 2015; Singh et al., 2015). These works, however, do not use weight rotation as a measure of layer-level training speed, and also focus on speed of convergence instead of generalization. Recently, a series of papers proposed

---

[1]Our preliminary study focuses on convolutional neural networks used for image classification.

optimization algorithms similar to Layca and observed an impact on generalization (Yu et al., 2017; Zhang et al., 2017b; Ginsburg et al., 2018). Our paper complements these works by providing an extensive analysis of the reasons behind such observations.

3 MONITORING AND CONTROLLING LAYER-LEVEL TRAINING SPEED

This paper's goal is to extensively study the relation between layer-level training speed and generalization. However, the notion of layer-level training speed is unclear, and its control through SGD is potentially difficult because of the intricate nature of gradient propagation (cfr. vanishing and exploding gradients). This section's purpose is to present tools to monitor and control training speed at layer level, such that its impact on generalization can be studied in Sections 4 and 5.

3.1 HOW TO DEFINE LAYER-LEVEL TRAINING SPEED?

Training speed can be understood as the speed with which a model converges to its optimal solution -not to be confounded with learning rate, which is only one of the parameters that affect training speed in current deep learning applications. The notion of *layer-level* training speed is ill-posed, since a layer does not have a loss of its own: all layers optimize the same global loss function. Given a training step, how can we know by how much each layer's update contributed to the improvement of the global loss?

Previous work on vanishing and exploding gradients focused on the norm and variance of gradients as a measure of layer-level training speed (Bengio et al., 1994; Hochreiter, 1998; Glorot & Bengio, 2010). Provided the empirical work on activation and weight binarization during (Courbariaux & David, 2015; Rastegari et al., 2016; Hubara et al., 2016) or after training (Agrawal et al., 2014; Carbonnelle & De Vleeschouwer, 2018), we argue that the norm of a weight vector does not matter, but only its orientation. Therefore, we suggest to measure training speed through the rotation rate of a layer's weight vector (also denoted by layer rotation rate in this paper). More precisely, let w_l^t be the flattened weight tensor of the l^{th} layer at optimization step t, then the rotation rate of layer l between steps t_1 and t_2 is defined as the angle between $w_l^{t_1}$ and $w_l^{t_2}$ divided by the number of performed steps $t_2 - t_1$. [2] In order to visualize how fast layers rotate during training, we propose to inspect how the cosine distance between each layer's current weight vector and its initialization evolves across training steps. We denote this visualization tool by *layer-wise angle deviation curves* hereafter.

3.2 LAYCA: AN ALGORITHM TO CONTROL LAYER ROTATION RATES

Given our definition of layer-level training speed, we now develop an algorithm to control it. Ideally, the layer rotation rates should be directly controllable with layer-wise learning rate parameters, ignoring the peculiarities of gradient propagation. We propose Layca (SGD-guided LAYer-level Controlled Amount of weight rotation), an algorithm where the layer-wise learning rates directly determine the amount of rotation performed by each layer's weight vector during an optimization step, in a direction specified by an optimizer (SGD being the default choice). Inspired by techniques for optimization on manifolds (Absil et al., 2010), and on spheres in particular, Layca applies layer-wise orthogonal projection and normalization operations on SGD's updates, as detailed in Algorithm 1. While Layca enables control over the rotation performed during one unique training step, the presence of noise or inconsistent directions can influence the overall rotation over multiple training steps in an uncontrolled way. Fortunately, such behaviour can be detected by inspecting the layer-wise angle deviation curves and did not hinder our experiments.

4 EXPLORATION OF LAYER ROTATION RATE CONFIGURATIONS WITH LAYCA

Section 3 provides tools to monitor and control layer rotation rates, a tentative definition of layer-level training speed. The purpose of this section is to use these tools to conduct a systematic exper-

---

[2]It is worth noting that our measure focuses on weights that multiply the inputs of a layer (*e.g.* kernels of fully connected and convolutional layers). Studying and controlling the training of additive weights (biases) is left as future work.

Algorithm 1 Layca, an algorithm that enables control over the amount of weight rotation per step for each layer through its learning rate parameter (cfr. Section 3.2).

Require: o, an optimizer (SGD is the default choice)
Require: T, the number of training steps
L is the number of layers in the network
for l=0 **to** L-1 **do**
    Require: $\rho_l(t)$, a layer's learning rate schedule
    Require: w_0^l, the initial multiplicative weights of layer l
end for
$t \leftarrow 0$
while $t < T$ **do**
    $s_t^0, ..., s_t^{L-1} = \text{getStep}(o, w_t^0, ..., w_t^{L-1})$ (get the updates of the selected optimizer)
    for l=0 **to** L-1 **do**
        $s_t^l \leftarrow s_t^l - \frac{(s_t^l \cdot w_t^l) w_t^l}{w_t^l \cdot w_t^l}$ (project step on space orthogonal to w_t^l)
        $s_t^l \leftarrow \frac{s_t^l \|w_t^l\|_2}{\|s_t^l\|_2}$ (rotation-based normalization)
        $w_{t+1}^l \leftarrow w_t^l + \rho_l(t) s_t^l$ (perform update)
        $w_{t+1}^l \leftarrow w_{t+1}^l \frac{\|w_0^l\|_2}{\|w_{t+1}^l\|_2}$ (project weights back on sphere)
    end for
    $t \leftarrow t + 1$
end while

Table 1: Summary of the tasks used for our experiments[3]

Name	Architecture	Dataset
C10-CNN1	25 layers deep CNN	CIFAR-10
C100-resnet	ResNet-32	CIFAR-100
tiny-CNN	11 layers deep CNN	Tiny ImageNet
C10-CNN2	deep CNN from torch blog	CIFAR-10 + data augm.
C100-WRN	Wide ResNet 28-10 with 0.3 dropout	CIFAR-100 + data augm.

imental study of the relation between layer rotation rates and generalization. The experiments are conducted on three different tasks which vary in network architecture and dataset complexity, and are further described in Table 1.

4.1 LAYER-WISE LEARNING RATE CONFIGURATIONS

Layca enables us to specify layer rotation rate configurations by setting the layer-wise learning rates. To explore the large space of possible layer rotation rate configurations, our study restricts itself to two directions of variation. First, we vary the initial global learning rate $\rho(0)$, which affects the training speed of all the layers. During training, the global learning rate $\rho(t)$ drops following a fixed decay scheme (hence the dependence on t), as is common in the literature. Notice that the impact of the global learning rate on generalization has already been studied when using SGD (Jastrzebski et al., 2017; Smith & Le, 2017; Smith & Topin, 2017; Hoffer et al., 2017; Masters & Luschi, 2018), but not with an algorithm like Layca where learning rate directly determines rotation rate. The second direction of variation is prioritization. We explore the impact of prioritization amongst layers by applying static, layer-wise learning rate multipliers that exponentially increase/decrease with layer depth (which is typically encountered with exploding/vanishing gradients). The multipliers are parametrized by the layer index l (in forward pass ordering) and a parameter $\alpha \in [-1, 1]$ such that the learning rate of layer l becomes:

$$\rho_l(t) = \begin{cases} (1-\alpha)^{5\frac{(L-1-l)}{L-1}} \rho(t) & \text{if} \quad \alpha > 0 \\ (1+\alpha)^{5\frac{l}{L-1}} \rho(t) & \text{if} \quad \alpha \leq 0 \end{cases} \tag{1}$$

---

[3]References: ResNet (He et al., 2016), torch blog (Zagoruyko, 2015), Wide ResNet (Zagoruyko & Komodakis, 2016), CIFAR-10 (Krizhevsky & Hinton, 2009), Tiny ImageNet (Deng et al., 2009; CS231N, 2016).

Values of α close to -1 correspond to prioritizing first layers, 0 corresponds to no prioritization, and values close to 1 to prioritization of last layers. Visualization of the layer-wise multipliers for different α values is provided in Supplementary Material.

To study the impact of global learning rate, we evaluate 10 logarithmically spaced values of $\rho(0)$ $(3^{-7}, 3^{-6}, ..., 3^2)$ in the $\alpha = 0$ setting. To study the impact of prioritization, we compare 13 different values of α, and tune the initial global learning rate $\rho(0)$ for each value separately through an iterative grid search procedure (described in Supplementary Material).

4.2 How layer rotation rates influence generalization

Figure 2a shows, for each of the three tasks, the test accuracies obtained for the different α and $\rho(0)$ values. From these results, we extract two rules of thumb. First, the rotation rates should be uniform across layers, as prioritizing the first or last layers reduces the test accuracy by up to 20%. Second, we observe that the layer rotation rates should be selected as high as training allows it (when too high, training diverges), enabling gains of up to 30% in test accuracy. The observations generalize across the three tasks, and our preliminary exploration indicates that ***layer rotation rate configurations have a consistent and substantial impact on generalization***. Let us also notice that in extreme prioritization schemes ($\mid \alpha \mid \geq 0.6$), the observations are in line with Figure 1's results, as prioritizing the first layers generalizes better than prioritizing the last layers.

Figure 2b presents the layer-wise angle deviation curves (cfr. Section 3.1) generated by the different configurations. This visualization enables us to check that, up to small deviations, Layca enables good control over the rotation rates in the tasks we consider. For example, the $\alpha = 0$ setting used in the fifth column indeed leads all layers to rotate quasi synchronously. Moreover, it is useful to visualize how the layer-wise angle deviation curves look like for the different layer rotation rate configurations, as the same visualization tool will be used in Section 5 to analyse standard training settings where layer rotation rates are not controlled during training. In particular, it is useful to remember that for the three tasks, the best generalization performance is obtained when nearly all layers synchronously reach a cosine distance of 1 from their initialization.

4.3 How layer rotation rates influence network convergence

It is commonly assumed that vanishing and exploding gradients slow down or even prevent training of neural networks. One might thus be tempted to believe that the bad performances on the test set obtained in Figure 2 for low and/or non-uniform layer rotation rates are caused by an equally bad performance on the training set. However, not only do these layer rotation rate configurations result in close to perfect training performance (*cfr.* Supplementary Material), but they also often lead the network to converge faster than the high and uniform layer rotation rate configuration. Figure 3 depicts the loss curves obtained for different values of α and $\rho(0)$. It appears that the higher or the more uniform the layer rotation rates are, the higher the plateaus in which loss curves get stuck into. The fact that plateaus are the most prominent when all layers are rotated at high rate suggests that they are caused by some kind of interference between the layers during training. Moreover, it also suggests that, following our rules of thumb, high plateaus are additional indicators of good generalization performance.

5 A study of layer rotation rates emerging from standard training settings

Section 4 uses Layca to study the impact of layer rotation rates on generalization and speed of convergence in a controlled setting. This section investigates the layer rotation rates that naturally emerge when using SGD and adaptive gradient methods for training. First of all, these experiments will provide supplementary evaluation of the rules of thumb proposed in Section 4. Second, analysing SGD and adaptive gradient methods in the light of layer rotation rates' impact on generalization will provide useful insights to explain previous observations around these methods that currently escape our understanding.

The experiments of this section are performed on the three tasks used in Section 4 and on two supplementary, extensively tuned networks from state of the art (cfr. Table 1). Meta-parameters for

(a)

(b)

Figure 2: Analysis of the generalization ability induced by different layer rotation rate configurations (using Layca for training) on the three first tasks of Table 1. The configurations are parametrized by α, that controls which layers are prioritized (first layers for $\alpha < 0$, last layers for $\alpha > 0$, or no prioritization for $\alpha = 0$), and $\rho(0)$, the initial global learning rate value shared by all layers. **(a)** Test accuracy in function of α and $\rho(0)$. Two rules of thumb emerge: layer rotation rates should be uniform across layers (*i.e.* $\alpha = 0$) and be as high as training allows it (*i.e.* high $\rho(0)$ values). **(b)** Layer-wise angle deviation curves (cfr. Section 3.1) generated by different configurations, and their accompanying test accuracy (η). $\Delta\eta$ is computed with respect to the high and uniform layer rotation rate configuration (last column), which corresponds to $\alpha = 0$ and $\rho(0) = 3^{-3}$ for the three tasks. Train accuracies are provided in Supplementary Material ($\approx 100\%$ in all configurations).

Figure 3: Loss curves obtained for different α and $\rho(0)$ values on the tiny-CNN task (for the two other tasks, see Supp. Mat.), using Layca for training. The more uniform or the higher the layer rotation rates, the higher the plateaus in which the loss gets stuck into. The sudden drop at epoch 70 corresponds to a reduction of the global learning rate by a factor 5.

these two tasks are taken from their original implementation when using SGD and from Wilson et al. (2017) when using adaptive gradient methods for training. For the other three tasks, the learning rate is determined by grid search over 10 logarithmically spaced values ($3^{-7}, 3^{-6}, ..., 3^2$) independently for each (task,optimizer) pair.

5.1 ANALYSIS OF SGD AND WEIGHT DECAY

Figure 4 (1^{st} line) depicts the layer-wise angle deviation curves generated by SGD and the corresponding test accuracies for each of the five tasks. We observe that the curves are far from the ideal scenario disclosed in Section 4, where the majority of the layers synchronously reached a cosine distance of 1 from their initialization. Moreover, in accordance with our rules of thumb, SGD induces a considerably lower test performance than Layca (in the high and uniform rotation rate configuration). Extensive tuning of the learning rate did not help SGD to solve its two systematic problems: 1) layers don't train at the same speed and 2) the layers' weights stop rotating before reaching a cosine distance of 1.

At this point, it is tempting to believe that Layca will improve the performance of all the deep networks trained with SGD. However, we observed that, with the unexpected help of weight decay (*i.e.* L_2-regularization), SGD gains the ability to induce high and uniform layer rotation rates and the accompanying good test performance. Figure 4 (2^{nd} line) displays, for the 5 tasks, the layer-wise angle deviation curves generated by SGD when combined with weight decay. We observe that all layers are rotated synchronously, reaching a cosine distance of 1 from their initialization, and that the resulting test performances are on par with the ones obtained with Layca. ***This experiment not only provides important supplementary evidence for our rules of thumb, but also suggests a radically novel explanation of weight decay's regularization ability in deep nets***: by enabling the emergence of high and uniform layer rotation rates during SGD training.[4] On a practical level, since the same regularization effect can be elegantly achieved with tools that control layer rotation rates, without an extra parameter to tune, our results could potentially lead weight decay to disappear from the standard deep learning toolkit.

Figure 4: Layer-wise angle deviation curves and the corresponding test accuracies generated by SGD without (1^{st} line) or with (2^{nd} line) weight decay. Colour code, axes and $\Delta\eta$ computation are the same as in Figure 2b.[5]Despite extensive learning rate tuning, SGD without weight decay induces test performances that are significantly below Layca. These results are coherent with our rules of thumb, as SGD is not able to induce high and uniform layer rotation rates (cfr. 5^{th} column of Figure 2b). Surprisingly, weight decay solves SGD's problems, leading to high and uniform layer rotation rates and test accuracies that are on par with Layca.

---

[4]Notice that this observation is also consistent with the systematic occurence of high plateaus (*cfr.* Section 4.3) in the loss curves of state of the art networks (He et al., 2016; Zagoruyko & Komodakis, 2016) (which usually use SGD with weight decay).

[5]On the two supplementary tasks, the reference accuracy (η) is also obtained by Layca with $\alpha = 0$ and $\rho(0) = 3^{-3}$ and equals 92.33% and 80.69% on C10-CNN2 and C100-WRN respectively.

5.2 ANALYSIS OF ADAPTIVE GRADIENT METHODS

The recent years have seen the rise of adaptive gradient methods in the context of machine learning (*e.g.* RMSProp (Tieleman & Hinton, 2012), Adagrad (Duchi et al., 2011), Adam (Kingma & Ba, 2015)). Initially introduced for improving training speed, Wilson et al. (2017) demonstrated that these methods also had a considerable impact on generalization. Figure 5 provides the layer-wise angle deviation curves and test accuracies obtained when using adaptive gradient methods for training of the 5 tasks described in Table 1. Again, our rules of thumb can be applied: the overall worse generalization ability compared to Layca corresponds to low and/or non-uniform layer rotation rate configurations. But we'll focus here on the fact that the layer rotation rates are considerably different from the ones induced by SGD (cfr. Figure 4). Previous results of this paper indicate that these differences could be the reason behind adaptive gradient methods' influence on both training speed and generalization. Figure 6 confirms this hypothesis by showing that ***the training and test curves of adaptive methods become indistinguishable from their non-adaptive equivalents when Layca is used to enforce a fixed layer rotation rate configuration***. This result suggests a radically different understanding of adaptive gradient methods in deep learning (previously focussing on their parameter-level adaptivity), and further challenges their pertinence as methods developed for layer-level adaptivity seem more appropriate.

Figure 5: Layer-wise angle deviation curves and the corresponding test accuracies generated by adaptive gradient methods (RMSProp, Adam, Adagrad, RMSProp+L2 and Adam+L2 respectively for each task/column) after extensive learning rate tuning. Colour code, axes and $\Delta\eta$ computation are the same as in Figure 2b. Our rules of thumb still apply: the overall worse generalization ability compared to Layca corresponds to low and/or non-uniform layer rotation rate configurations. We also notice that the curves are significantly different from the ones of SGD (Figure 4). Could this explain adaptive gradient methods' impact on training speed and generalization?

Figure 6: Training and test curves of adaptive gradient methods and their non-adaptive equivalents[6] when Layca is applied on the updates of each method to fix the layer rotation rate configuration. The curves become indistinguishable, suggesting that adaptive gradient methods' impact on training speed and generalization is only due to their influence on layer rotation rates.

---

[6] SGD_AMom corresponds to SGD with a momentum scheme similar to Adam (see Supp. Mat.).

6 CONCLUSION

Inspired by the works on generalization and gradient propagation in deep networks, this paper's ambition is to disclose and study a novel way, unique to deep learning, by which optimization influences generalization: through the rate at which each layer's weight vector is rotated. While the premises of our work are based on intuitions that escape any theoretical framework, the value of our tools and claims is supported by the consistent experimental results and the useful insights they provide. Indeed, the rules of thumb we extract about the relation between layer rotation rates and generalization could be successfully applied to all the considered tasks and training settings, explaining substantial differences in test accuracies (sometimes of the order of 20%). Moreover, we show considerable evidence that this novel way by which optimization impacts generalization could be the reason behind weight decay's and adaptive gradient methods' generalization properties, which have remained a mystery despite their ubiquity in current deep learning applications. Both methods, which are source of heavy meta-parameter tuning, could even become obsolete as practitioners start using our tools, exemplifying the practical benefit of our work.

ACKNOWLEDGEMENTS

To be filled in

REFERENCES

P.-A. Absil, R. Mahony, and R. Sepulchre. Optimization On Manifolds : Methods And Applications. In *Recent Advances in Optimization and its Applications in Engineering*, pp. 125—-144. Springer, 2010. ISBN 9783642125973.

Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Man, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Vi, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow : Large-Scale Machine Learning on Heterogeneous Distributed Systems. *arXiv preprint arXiv:1603.04467*, 2016.

Pulkit Agrawal, Ross Girshick, and Jitendra Malik. Analyzing the Performance of Multilayer Neural Networks for Object Recognition. In *ECCV*, pp. 329–344, 2014.

Devansh Arpit, Stanisław Jastrzebski, Nicolas Ballas, David Krueger, Emmanuel Bengio, Maxinder S Kanwal, Tegan Maharaj, Asja Fischer, Aaron Courville, Yoshua Bengio, and Simon Lacoste-Julien. A Closer Look at Memorization in Deep Networks. In *ICML*, 2017.

Yoshua Bengio, Patrice Simard, and Paolo Frasconi. Learning long-term dependencies with gradient descent is difficult. *IEEE transactions on neural networks*, 5(2):157–166, 1994.

Simon Carbonnelle and Christophe De Vleeschouwer. Discovering the mechanics of hidden neurons. *https://openreview.net/forum?id=H1srNebAZ*, 2018.

François Chollet et al. Keras, 2015. URL `https://github.com/fchollet/keras`.

Matthieu Courbariaux and Jean-Pierre David. BinaryConnect : Training Deep Neural Networks with binary weights during propagations. In *NIPS*, pp. 3123—-3131, 2015.

Stanford CS231N. Tiny ImageNet Visual Recognition Challenge. *https://tiny-imagenet.herokuapp.com/*, 2016.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *CVPR*, pp. 248–255, 2009.

John Duchi, Elad Hazan, and Yoram Singer. Adaptive Subgradient Methods for Online Learning and Stochastic Optimization. *Journal of Machine Learning Research*, 12(Jul):2121–2159, 2011.

Boris Ginsburg, Igor Gitman, and Yang You. Large Batch Training of Convolutional Networks with Layer-wise Adaptive Rate Scaling, 2018. URL `https://openreview.net/forum?id=rJ4uaX2aW`.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *AISTATS*, pp. 249–256, 2010.

Elad Hazan, Kfir Levy, and Shai Shalev-Shwartz. Beyond convexity: Stochastic quasi-convex optimization. In *NIPS*, pp. 1594—-1602, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. In *CVPR*, pp. 770–778, 2016.

Sepp Hochreiter. The vanishing gradient problem during learning recurrent neural nets and problem solutions. *IJUFKS*, 6(2):1–10, 1998.

Elad Hoffer, Itay Hubara, and Daniel Soudry. Train longer , generalize better : closing the generalization gap in large batch training of neural networks. In *NIPS*, pp. 1729—-1739, 2017.

I. Hubara, M. Courbariaux, D. Soudry, R. El-Yaniv, and Y. Bengio. Binarized Neural Networks. In *NIPS*, 2016.

Stanislaw Jastrzebski, Zachary Kenton, Devansh Arpit, Nicolas Ballas, Asja Fischer, Yoshua Bengio, and Amos Storkey. Three Factors Influencing Minima in SGD. *arXiv:1711.04623*, 2017.

Leonard Kaufman and Peter J Rousseeuw. *Finding groups in data: an introduction to cluster analysis*. John Wiley & Sons, 2009.

Nitish Shirish Keskar, Dheevatsa Mudigere, Jorge Nocedal, Mikhail Smelyanskiy, and Ping Tak Peter Tang. On Large-Batch Training for Deep Learning: Generalization Gap and Sharp Minima. In *ICLR*, 2017.

Diederik P Kingma and Jimmy Lei Ba. Adam: A method for stochastic optimization. In *ICLR*, 2015.

Alex Krizhevsky and Geoffrey Hinton. Learning Multiple Layers of Features from Tiny Images. Technical report, University of Toronto, 2009.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2323, 1998. ISSN 00189219. doi: 10.1109/5.726791.

Dominic Masters and Carlo Luschi. Revisiting Small Batch Training for Deep Neural Networks. *arXiv:1804.07612*, 2018.

Vinod Nair and Geoffrey E Hinton. Rectified Linear Units Improve Restricted Boltzmann Machines. In *ICML*, pp. 807—-814, 2010.

Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural networks. In *ICML*, pp. 1310—-1318, 2013.

Mohammad Rastegari, Vicente Ordonez, Joseph Redmon, and Ali Farhadi. Xnor-net: Imagenet classification using binary convolutional neural networks. In *ECCV*, pp. 525–542. Springer, 2016.

Bharat Singh, Soham De, Yangmuzi Zhang, Thomas Goldstein, and Gavin Taylor. Layer-specific adaptive learning rates for deep networks. In *ICMLA*, pp. 364—-368, 2015.

Leslie N Smith and Nicholay Topin. Super-Convergence: Very Fast Training of Residual Networks Using Large Learning Rates. *arXiv:1708.07120*, 2017.

Samuel L Smith and Quoc V Le. A bayesian perspective on generalization and stochastic gradient descent. In *Proceedings of Second workshop on Bayesian Deep Learning (NIPS 2017)*, 2017.

Tijmen Tieleman and Geoffrey Hinton. Lecture 6.5RmsProp: Divide the gradient by a running average of its recent magnitude. COURSERA: Neural Networks for Machine Learning, 2012.

Ashia C Wilson, Rebecca Roelofs, Mitchell Stern, Nathan Srebro, and Benjamin Recht. The Marginal Value of Adaptive Gradient Methods in Machine Learning. In *NIPS*, pp. 4151–4161, 2017.

Adams Wei Yu, Qihang Lin, Ruslan Salakhutdinov, and Jaime Carbonell. Normalized gradient with adaptive stepsize method for deep neural network training. *arXiv:1707.04822*, 2017.

Sergey Zagoruyko. 92.45% on CIFAR-10 in Torch. *http://torch.ch/blog/2015/07/30/cifar.html*, 2015.

Sergey Zagoruyko and Nikos Komodakis. Wide Residual Networks. In *BMVC*, 2016.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires re-thinking generalization. In *ICLR*, 2017a.

Zijun Zhang, Lin Ma, Zongpeng Li, and Chuan Wu. Normalized Direction-preserving Adam. *arXiv:1709.04546*, 2017b.

Supplementary Material

The supplementary material of this paper is divided into two sections. Section A contains supplementary results, which are not essential for the main message of the paper but could be useful for researchers interested in pursuing our line of work. Section B contains supplementary information about the experimental procedure used for generating the results of our paper.

A Supplementary results

A.1 Discussing the first layers' superior performance in Figure 1.

Figure 1 shows that in our toy example, the first layers of the MLP network receive input and feedback signals of better quality, i.e. that lead to better generalization properties (hereafter, *quality* of signals will refer to the generalization performance that results from training the layers that receive these signals, high quality signals leading to good generalization performance). Importantly, this example shows that the quality of the original input and error signals is altered when going through the forward and backward pass. To explain the first layers' superior performance, the first idea that came to our mind was that, in the randomly initialized network, the quality of layer inputs degrades faster during the forward pass than the quality of feedbacks does during the backward pass. Accordingly, the first layers gained their good test accuracy from their good quality input signals (since these do not result from many random transformations applied on the original inputs) and good feedback signals (since these are robust to random transformations).

This interpretation comes from a static view of the phenomenon: it implicitly assumes that the transformations applied to the input and feedback signals before reaching a layer don't change when this layer is trained in isolation. However, while the transformations applied on the input signals of a layer are not modified, the transformations applied on the feedback signals change in a non-negligible way: a layer's training influences the way errors backpropagate through every subsequent layer, because ReLU's derivative depends on the activations of the forward pass. Thus, the backwards pass, which transforms the feedback signal before reaching the trained layer, is not a series of random non-linear transformations any more after training has started.

We believe that this could be a key factor that enables the first layers' superior performance. Indeed, in addition to their good quality input signals, the first layers could also potentially receive good quality feedback signals, as these can be improved by the layers' training. Figure 7 provides some evidence in favour of this hypothesis. Using the Silhouette coefficient (Kaufman & Rousseeuw, 2009) (with cosine distance as distance metric), the figure shows that even when only the first layer is trained, the feedback it receives gets more correlated with the classes/targets through training, which we believe could be a sign of better signal quality (it remains to be proven however).

Figure 7: Supplementary result suggesting that the capacity of layers to improve their own feedback signal could be a key asset enabling the first layers' superior generalization performance in Figure 1. Indeed, this figure shows how the Silhouette score of the first layer's feedback with respect to the classes/targets increases even when only the first layer is trained.

A.2 All operations of Layca are not always necessary in practice.

The 4 main operations of Layca are repeated in Algorithm 2. The first operation projects the step on the space orthogonal to the current weights of the layer. Having a step orthogonal to the current

---

Algorithm 2 Main operations of Layca (cfr. Algorithm 1). We've noticed that in practice, operations 1 and 4 are not strictly necessary for controlling layer rotation rates.

$s_t^0, ..., s_t^{L-1} = \text{getStep}(o, w_t^0, ..., w_t^{L-1})$ (get the updates of the selected optimizer)

for l=0 **to** L-1 **do**

$\quad s_t^l \leftarrow s_t^l - \frac{(s_t^l \cdot w_t^l) w_t^l}{w_t^l \cdot w_t^l}$ (1: project step on space orthogonal to w_t^l)

$\quad s_t^l \leftarrow \frac{s_t^l \|w_t^l\|_2}{\|s_t^l\|_2}$ (2: rotation-based normalization)

$\quad w_{t+1}^l \leftarrow w_t^l + \rho_l(t) s_t^l$ (3: perform update)

$\quad w_{t+1}^l \leftarrow w_{t+1}^l \frac{\|w_0^l\|_2}{\|w_{t+1}^l\|_2}$ (4: project weights back on sphere)

end for

---

weights is necessary for operation 2 to normalize the rotation performed during the update. However, since a layer typically has more than thousands of parameters (*i.e.* has a lot of dimensions), the step proposed by an optimizer has a high probability of being approximately orthogonal to the current weights. Explicitly orthogonalizing the step and the weights through operation 1 is thus potentially redundant.

Operation 4 keeps the norm of weights fixed during the whole training process. First, this operation emphasizes our claim that the norm of weights doesn't really matter. Indeed, disabling changes to the norm of weights doesn't prevent the network from reaching 100% training accuracy. Second, this operation prevents the weights from increasing too much (the first three operations lead the norm of weights to increase at every training step), which causes numerical problems. However, this operation is not fundamental for controlling the layer rotation rates.

We experimented with a sub-version of Layca that does not perform Layca's operations 1 and 4. Interestingly, the resulting algorithm is equivalent to NG$_{\text{adap}}$ and LARS introduced by Yu et al. (2017) and Ginsburg et al. (2018) respectively. Both works reported improved test performance when using this algorithm. Figure 8 shows the layer-wise angle deviation curves and associated test accuracies when applying LARS (or equivalently, NG$_{\text{adap}}$) on tasks C10-CNN1, C100-resnet and tiny-CNN.[7] The layer rotation rate configuration parameters are $\alpha = 0$ and $\rho(0) = 3^{-3}$. We observe that this configuration also induces high and uniform rotation rates, and that the test accuracies are on par with Layca. This observation indicates that operations 1 and 4 of Layca can be removed in at least some practical applications.

Figure 8: Layer-wise angle deviation curves and the corresponding test accuracies generated by LARS with $\alpha = 0$ and $\rho(0) = 3^{-3}$. Colour code, axes and $\Delta\eta$ computation are the same as in Figure 2b. Although not performing operations 1 and 4 of Algorithm 2, LARS seems to control layer rotation rates as well as Layca. Indeed, the layer-wise angle deviation curves are indistinguishable from the ones in the 5^{th} column of Figure 2b, and the test accuracies are nearly identical.

---

[7]While the norm of each layer's weight vector was not fixed by LARS, we still had to limit the amount of norm increase per training step to prevent numerical errors. We limited it to 0.0001 times the initial norm of each layer's weight vector.

A.3   IMPACT OF LAYER ROTATION RATES ON CONVERGENCE FOR C10-CNN1 AND C100-RESNET TASKS.

Figure 3 shows on the tiny-CNN task that the α and $\rho(0)$ parameters, which determine the layer rotation rate configuration when using Layca for training, enable precise control over the height of the plateaus in which the loss curve gets stuck into. Figure 9 extends the results to the C10-CNN1 and C100-resnet tasks. Conclusions are identical. Moreover, the experiment on C10-CNN1 was performed with negative α values, showing that prioritizing the training of the first layers of the network also decreases the height of the plateaus (at the cost of generalization ability however).

Figure 9: Loss curves of C10-CNN1 and C100-resnet for different α and $\rho(0)$ values. The results confirm the observations made on tiny-CNN, and extend the analysis to negative α values.

A.4   FURTHER ANALYSIS OF WEIGHT DECAY.

Figure 4 shows that weight decay is an essential ingredient for inducing high and uniform layer rotation rates with SGD. This is a rather surprising observation, as weight decay was not introduced with its impact on layer rotation rates in mind, and has never been studied with this respect neither. This section provides further analysis of the mechanisms at play and presents a partial explanation of the phenomenon.

The first row of Figure 10 displays, for each layer, the cosine distance between its weights at the start and at the end of each epoch, when weight decay is used and when it isn't (the three first tasks of Table 1 are considered). This provides us a measure of the layer rotation rates during each epoch independently. The more the curves of the different layers coincide, the more uniform the layer rotation rates. The higher the curves, the higher the layer rotation rates. We observe from these visualizations that weight decay slightly increases the uniformity of the layer rotation rates across layers (especially for C10-CNN1). The most considerable impact, however, seems to be weight decay's ability to keep the layer rotation rates high during the course of training. For example, while the rates remain more or less constant for each layer from epoch 10 to 80 when weight decay is used on C10-CNN1, it is reduced by a factor of $\sim 10^3$ on the same training period when weight decay is not used.

To understand weight decay's impact on layer rotation rates further, we monitor the norm of gradients[8] and weights of each layer during the course of training. As expected, the norm of weights are smaller when weight decay is used (row 3 of Fig. 10). However, and more surprisingly, weight decay seems to have a much stronger impact on the norm of gradients (row 2 of Fig. 10). This impact seems to be the main factor behind the previous paragraph's observations. Our current hypothesis is that the relatively smaller weights promoted by weight decay lead to smaller logits and thus less confident predictions, such that gradients remain high even for well-classified samples. A thourough explanation of this phenomenon is however left as future work.

Figure 10: **Row 1:** Visualizing the rotation rates per epoch suggests that weight decay's biggest impact is on the overall level of the layer rotation rates, not on their uniformity across layers. **Rows 2 and 3:** The evolution of the norm of each layer's gradients and weights during training suggests that preventing the drastic decrease of the norm of gradients is weight decay's key asset to keep layer rotation rates high.

A.5 FURTHER ANALYSIS OF ADAPTIVE GRADIENT METHODS.

Section 5.2 shows considerable evidence that adaptive gradient methods' impact on training speed and generalization is solely due to their influence on layer rotation rates. The key element distinguishing adaptive gradient methods from their non-adaptative equivalents is a parameter-level tuning of the learning rate based on the statistics of each parameter's partial derivative. Our results suggest that the resulting parameter-level learning rates differ mostly across layers and negligibly inside layers. To test this claim, we monitored Adam's estimate of the second raw moment when training on the C10-CNN1 task. The estimate is computed by:

$$v_t = \beta_2 \cdot v_{t-1} + (1 - \beta_2) \cdot g_t^2$$

where g_t and v_t are vectors containing respectively the gradient and the estimates of the second raw moment at training step t, and β_2 is a parameter specifying the decay rate of the moment estimate. While our experiment focuses on Adam, the other adaptive methods (RMSprop, Adagrad) also use statistics of the squared gradients to compute parameter-level learning rates.

Figure 11 displays the 10^{th}, 50^{th} and 90^{th} percentiles of the moment estimations, for each layer separately, as measured at the end of epochs 1, 10 and 50. The conclusion is clear: the estimates indeed vary much more across layers than inside layers. While parameter-level adaptivity could

---

[8]Here, the computation of the gradients does not take the L_2 loss term of weight decay into account for making comparisons of both training settings pertinent.

make sense in other applications, deep neural networks seem to lend themselves better to layer-level adaptivity.

Figure 11: Adam's parameter-wise estimates of the second raw moment (uncentered variance) of the gradient during training on C10-CNN1, described for each layer separately through the 10^{th}, 50^{th} and 90^{th} percentiles. The results provide supplementary evidence that the parameter-level statistics used by adaptive gradient methods vary mostly between layers and negligibly inside layers.

B   SUPPLEMENTARY INFORMATION

B.1   VISUALIZING THE α PARAMETER.

The α parameter is used in Section 4 to characterize the layer prioritization schemes used during training. While the specific parametrization is provided in Equation 1, Figure 12 provides a graphical illustration of it.

Figure 12: Visualization of the prioritization schemes as parametrized by α (cfr. Section 4). The colours of the lines represent the absolute value of α. Illustration is separated for prioritization of the first layers (negative α values) and of the last layers (positive α values). The layer-wise learning rate multipliers (y-axis) depend on the layer's location in the network (x-axis), which is represented by the layer index l (in forward pass ordering) divided by the number of layers L.

B.2   GRID SEARCH PROCEDURE FOR LEARNING RATE SELECTION IN SECTION 4

In Section 4, the global initial learning rate parameter $\rho(0)$ is optimized through grid search for each α value. While in the other experiments, learning rate selection is performed through grid search over 10 logarithmically spaced values $(3^{-7}, 3^{-6}, ..., 3^{2})$, such method is to demanding computationally for this experiment (it must be repeated 39 times = 13 α values * 3 tasks).

The grid search procedure starts by trying 3 values: $3^{-4}, 3^{-3}$ and 3^{-2}. Then, iteratively until convergence, if the current best value is the lowest or highest of the tried values, the next value (lower or higher by a factor 3 respectively) is tried. After this first stage, the optimal $\rho(0)$ values of

two successive α values are compared (successive after sorting the values in increasing order). If the optima of two successive α values are different by a factor 3, the intermediate $\rho(0)$ is also tried (current value multiplied or divided by $3^{0.5}$). The increased precision of the second stage was used to get smoother curves in Figure 2a.

B.3 TRAINING ERRORS ASSOCIATED TO THE LAYER-WISE ANGLE DEVIATION CURVES.

In Figures 2b, 4 and 5, the test accuracies corresponding to each visualization of the layer-wise angle deviation curves are provided. While it is briefly mentioned that training accuracy is close to perfect in most cases (cfr. Section 4.3), Tables 2, 3 and 4 provide the exact values for completeness.

Table 2: Train accuracies associated to Figure 2b

	$\alpha = 0.6$	$\alpha = -0.6$	$\rho(0) = 3^{-5}$	$\rho(0) = 3^{-4}$	Best
C10-CNN1	100%	99.55%	100%	100%	99.99%
C100-resnet	97.38%	97.9%	99.87%	99.99%	99.75%
tiny-CNN	99.98%	98.64%	99.97%	99.97%	98.91%

Table 3: Train accuracies associated to Figure 4

	C10-CNN1	C100-resnet	tiny-CNN	C10-CNN2	C100-WRN
SGD	100%	100%	100%	91%	100%
SGD + L_2	100%	100%	89.8%	99.5%	100%

Table 4: Train accuracies associated to Figure 5

	C10-CNN1	C100-resnet	tiny-CNN	C10-CNN2	C100-WRN
Adaptive methods	100%	99.98%	99.97%	98.72%	99.92%

B.4 MOMENTUM SCHEME USED BY SGD_AMOM AND ADAM.

SGD_AMom was designed for Section 5.2, as a non-adaptive equivalent of Adam. In particular, SGD_AMom uses the same momentum scheme as Adam:

$$\begin{aligned} v_t &= m \cdot v_{t-1} + (1 - m) \cdot g_t \\ w_t &= w_{t-1} - \rho \cdot v_t \end{aligned}$$

where g_t is the gradient at step t, ρ the learning rate, m the momentum parameter.

B.5 FURTHER INFORMATION.

Other details about our experiments can be found in our code at *-github link hidden to preserve anonymity-*.