MULTI-STEP DECENTRALIZED DOMAIN ADAPTATION

ABSTRACT

Despite the recent breakthroughs in unsupervised domain adaptation (uDA), no prior work has studied the challenges of applying these methods in practical machine learning scenarios. In this paper, we highlight two significant bottlenecks for uDA, namely excessive centralization and poor support for distributed domain datasets. Our proposed framework, MDDA, is powered by a novel collaborator selection algorithm and an effective distributed adversarial training method, and allows for uDA methods to work in a decentralized and privacy-preserving way.

1 Introduction

In practical machine learning systems, test samples are often drawn from a different data distribution than the training samples, due to variations in data acquisition processes between the training and test sets – caused by for example, different illumination conditions and cameras in the context of visual tasks. This shift in data distributions, known as domain shift, is a core reason which hinders the generalizability of predictive models to new domains. As manual labeling of data in each test domain is prohibitively expensive, unsupervised domain adaptation **(uDA)** has emerged as a promising solution to transfer the knowledge from a labeled source domain to unlabeled target domains (Long et al. (2015; 2017); Ganin et al. (2016); Tzeng et al. (2017); Hoffman et al. (2018); Shen et al. (2018); Sankaranarayanan et al. (2018); Hoffman et al. (2018)).

While these methods are indeed effective, little attention has been paid on how they would be incorporated in real-world machine learning systems. In this paper, we study and propose solutions for the practical issues that arise while applying uDA techniques in ML systems, namely the challenges of distributed domain datasets and the overly centralized nature of existing uDA approaches. As a motivating example, consider a scenario wherein a model is trained for the task of fetal head detection from labeled ultrasound images collected in a hospital in Finland (source domain S_{fin}). Subsequently, this pre-trained model has to be deployed in three target hospitals - one in the US (T_{us1}) and two in China (T_{cn1} and T_{cn2}). Due to variations in sonogram machines and medical training of sonographers, a domain shift is likely to occur in the test samples; hence we need to apply uDA to adapt the source classifier in the target domains.

Existing uDA methods are centralized by design, in that they assume that each target domain would *always* adapt from the labeled source domain (S_{fin}). This raises two issues: firstly, if the machine hosting the labeled source dataset is unavailable (e.g., it is undergoing maintenance or has connectivity issues), then clearly adaptation is not possible. More importantly, we argue that this choice of *always* adapting from a labeled source is not optimal from an adaptation perspective, because the domain discrepancy between the labeled source and a potential target domain could be high in some cases. Our work seeks to explore an interesting proposition: *in addition to adapting from the labeled source, can we also perform uDA with other target domains, which themselves may have undergone domain adaptation in the past.*

Further, existing uDA methods do not support distributed domain datasets and assume that source and target data are available on the same machine. Clearly, this raises severe privacy and legal concerns since either the source domain (S_{fin}) or the target domains (T_{us1}, T_{cn1}, T_{cn2}) will have to send their sensitive data (i.e., sonograms) to each other in order to perform adaptation. In addition, such transfer of potentially large datasets also incurs severe communication costs. In summary, this paper makes the following contributions:

- We formulate and study a brand-new problem focusing on the challenges of uDA in practical machine learning systems.

- We propose a multi-step uDA framework, wherein target domains can adapt not only from the labeled source, but also from other target domains. Powering this framework is a novel collaborator selector algorithm that chooses the optimal adaptation collaborator for each target domain, before initiating the adaptation.

- We propose an effective technique for allowing uDA algorithms and adversarial training to work across distributed datasets. Through extensive experiments on five image and speech datasets, we demonstrate the efficacy of our proposed solution.

2 Problem Formulation and Related Work

Consider a practical scenario of deploying an unlabeled domain adaptation (uDA) method in a real-world ML system. Assume that a data collection exercise yields a labeled dataset upon which a model is trained using supervised learning. Thereafter, this model needs to be deployed to a population of users (or targets) whose data is unlabeled and divergent from the training dataset. Mathematically, we are presented with a single source domain $S = (\mathbb{R}^n, p_S(x, y))$, with input data X_S and labels Y_S. There are multiple target domains $\{T^j | j = 1, \ldots, K\}$, with target data X_T^j drawn from target distribution $p_T^j(x, y)$, but *no labeled observations are available*. Using supervised learning, we train a representation mapping, $\mathcal{M}_S$, and a classifier, $\mathcal{C}_S$ for the source domain. However, for target domain T^j, due to the absence of labeled observations, supervised learning is not possible and hence we would like to do adaptation with the source domain. We assume that target domains are introduced sequentially, one at a time, into the system.

Under this problem formulation, we highlight two unexplored research challenges:

Collaborator Selection. For each target domain that joins the system, how do we select an optimal collaborator for domain adaptation that will lead to highest post-adaptation accuracy for the target domain? Existing uDA methods (e.g., Hoffman et al. (2018); Tzeng et al. (2017); Ganin et al. (2016) always use the labeled source domain $\mathcal{S}$ as the adaptation collaborator for each target domain, however we argue that it is not optimal to *always* adapt for the labeled source domain for two reasons: i) if the domain shift between the target domain and the labeled source is high, we may not achieve a good adaptation performance (Wulfmeier et al. (2017)); (ii) from a practical perspective, it makes the entire system centralized and prone to failure if the device hosting the source dataset is unavailable for adaptation (e.g., due to connectivity issues). Instead, we propose a multi-step decentralized domain adaptation approach built upon the idea that a new target domain can adapt not only from the labeled source domain, but also from other target domains in the system which have already undergone domain adaptation.

More concretely, we define a collaborator set $\mathcal{C}$ as the set of domains that are available to collaborate with a target domain on an adaptation task. At step $\tau = \tau_0$, only the source domain is present in the system, hence $\mathcal{C}_0 = \{\mathcal{S}\}$. At step $\tau = \tau_1$, the first target domain T^1 joins the system – at this moment, only the source domain S has a learned representation $\mathcal{M}_S$. Thereafter, T^1 performs uDA with the source S and learns a representation $\mathcal{M}_{T^1}$. Subsequently, we have $\mathcal{C}_1 = \{S, T^1\}$, i.e., future target domains now have two candidates with whom they can collaborate to perform domain adaptation. In general, at step $\tau = \tau_K$, $\mathcal{C}_K = \{S\} \cup \{T^j | k = 1, \ldots, K\}$.

In §3.3, we propose an algorithm to select an optimal collaborator $c \in \mathcal{C}_K$ for each target domain, that is likely to yield the best accuracy post-adaptation. Once the optimal collaborator is chosen, any existing uDA method could be employed to perform the pairwise adaptation between the chosen collaborator and the target domain. Our results in §4 demonstrate the effectiveness of multi-step adaptation against a number of existing baselines and across a number of uDA techniques.

Distributed and Private Data. Existing uDA methods assume that the datasets from the source domain $\mathcal{S}$ and a given target domain T^j are available on the same compute unit (e.g., on a server). However, as we explained earlier, this assumption is violated in practical scenarios, as the datasets are often private, and users or companies may not be allowed to share them with other parties due to legal reasons such as the data privacy law (GDPR) in Europe. In addition to the privacy issue, exchanging potentially large datasets incur high communication costs, making it undesirable in practical settings. This raises the question: can we make domain adaptation methods to work in a distributed and privacy-preserving manner such that the collaborators in the domain adaptation process can keep their data private and still receive the benefits of adaptation?

These challenges about making uDA algorithms work in a decentralized and distributed way are closely related, and addressing them is critical for widespread usage of uDA methods in practical ML systems. In what follows, we first describe (in §3.2) how we address the challenge of distributed datasets in uDA using a combination of model parallelism and data parallelism. Our key idea is to

exchange knowledge between the adaptation collaborators only using the gradients of Discriminator, which allows for the raw data and encoded features of each domain to remain private. Next, in §3.3, we build upon our idea of distributed adaptation to propose an algorithm for selecting an optimal adaptation collaborator.

2.1 Related Work

Bobu et al. (2018) presented the problem of continuous unsupervised adaptation wherein the target domain is smoothly varying temporally. They proposed an iterative uDA method with a replay loss to prevent the model from forgetting knowledge from past domains. Although our solution of multi-step domain adaptation is also iterative, we do not assume any smooth ordering between target domains, hence warranting the need for collaboration selection. Zhao et al. (2018) proposed MDAN where a target domain can adapt from multiple labeled source domains. As there is only one labeled source domain in our setup, this method cannot be directly applied. However, we can still combine the adversarial losses from multiple domains as proposed in MDAN - as such, we implement a variant of MDAN as a baseline for our method.

In our paper, the training data from different domains is distributed in separate nodes, which relates our problem to distributed training. The motivation of most existing works in this field is to accelerate the training process by partitioning the training data into multiple computational nodes and calculating the gradients in parallel. If the results from all nodes are aggregated globally by a central node (e.g., parameter server (Li et al. (2014); Dai et al. (2015))), or by message passing process (e.g., All-Reduce (Sergeev & Del Balso (2018))), then it is called centralized distributed training. By contrast, if the system does not require to exchange information and synchronize globally (Lian et al. (2017a); Tang et al. (2018b)), it is called decentralized training, which eliminates the dependency on the central node. Besides, decentralized training can be further accelerated by its conjunction with low-precision training (Tang et al. (2018a)), or asynchronous training (Lian et al. (2017b)). In addition to acceleration, federated learning (Bonawitz et al. (2019); Konečnỳ et al. (2016); Yang et al. (2019)) considers a training setting where the training data is stored over a large number of separate devices and cannot be shared due to privacy reasons. Our work builds upon the distributed training literature and we show, for the first time, how distributed training can be used in the context of uDA. Further, it is important to clarify that we use 'decentralization' in this paper in the context of domain adaptation, i.e., target domains can choose to adapt from any one of the available domains, instead of a single source domain (akin to a central node). This makes our techniques and their subsequent evaluation different from traditional decentralized learning papers.

Finally, an important goal of our paper is to support uDA while keeping the domain datasets private. There has been active research recently at the intersection of privacy and ML. Melis et al. (2019) showed that collaborative learning is vulnerable to membership inference attacks and leakage of dataset properties, and suggested employing dimensionality reduction and Dropout as ways to mitigate these attacks. Aono et al. (2017) demonstrated that the gradients of a classifier exchanged in distributed training can be used to reconstruct the raw training data and proposed using additively homomorphic encryption to fix the problem. Geyer et al. (2017) proposed a differential privacy approach to hide a single client's data contribution during federated learning. Finally, Nasr et al. (2018) did an in-depth analysis of passive and active white-box attacks on deep learning models. To the best of our knowledge, no prior work has shown that sharing gradients of a discriminator in adversarial learning – which is the key component of our approach – can leak raw training data. As such, our approach provides clear privacy benefits over conventional uDA techniques. That said, we do not discount the possibility that privacy attacks could be developed on our technique in the future, and leave it open as a topic of further research.

3 Our Approach

3.1 Primer on Adversarial Domain Adaptation

Before describing our approach, we provide a primer on adversarial domain adaptation which is a widely used approach for uDA and serves as the basic foundation of our solution. The core idea here is to use adversarial learning to align the feature representations of the source and target domains, thereby allowing a source classifier to be used in the target domain. Initially, a source extractor E_S

and a source classifier C_S are trained using supervised learning by solving the optimization problem:

$$\min_{E_S, C_S} \mathcal{L}_{cls} = -\mathbb{E}_{(x_s, y_s) \sim (X_S, Y_S)} \sum_{k=1}^{K} \mathbb{1}_{[k=y_s]} [\log(C_S(E_S(x_s)))]$$

The goal of the adaptation process is to learn a target extractor E_T using adversarial learning. To this end, the source extractor E_S is used to initialize the target extractor E_T. The weights of the source model are fixed during adversarial training. As in standard adversarial learning, two losses are optimized in the training process, a discriminator loss $\mathcal{L}_{adv_D}$ and a mapping loss $\mathcal{L}_{adv_M}$. Different uDA methods compute these two losses in their own way, e.g., ADDA (Tzeng et al. (2017)) uses the following loss formulations:

$$\min_{D} \mathcal{L}_{adv_D} = -\mathbb{E}_{x_s \sim \mathcal{X}_S} [\log(D(E_S(x_s)))] - \mathbb{E}_{x_t \sim \mathcal{X}_T} [\log(1 - D(E_T(x_t)))] \tag{1}$$

$$\min_{E_T} \mathcal{L}_{adv_M} = -\mathbb{E}_{x_t \sim \mathcal{X}_T} [\log(D(E_T(x_t)))] \tag{2}$$

where D represents a domain discriminator which aims to distinguish source domain data and target domain data. Details about other uDA methods are provided in §A.3 in the Appendix.

Our work in general applies to any feature-alignment based uDA technique, which allows for source and target encoders to be trained independently. We note that there are indeed uDA approaches which optimize the source classification loss and adversarial loss in the same batch during training, but they are not compatible with our problem formulation wherein a pre-trained source model is to be deployed on a set of target domains. Further, uDA approaches based on generative modeling (Hoffman et al. (2018); Hosseini-Asl et al. (2018)) are also out of scope of our work.

3.2 Distributed Domain Adaptation

Prior adversarial uDA methods assume that source and target data is available on the same compute unit to perform adversarial learning. However as discussed in §2, data from different domains is often distributed and private in realistic applications, and sharing it could be legally prohibited. We present an approach of performing domain adaptation with distributed domain datasets. In this vein, two key questions are: a) how to distribute the adversarial network architecture across nodes?, b) how to exchange information between the source and target nodes during training?

Figure 3 in Appendix A illustrates our distributed training strategy. We propose to split each constituent neural network in the adversarial training framework across source and target nodes. Consequently, the *extractor*, *domain discriminator* and *task classifier* have source components (E_S, D_S, C_S) and target components (E_T, D_T, C_T). Source data and target data can therefore be fed separately into their own model components to prevent any exchange of raw data or feature representations across nodes. Given this network architecture, we now present our training strategy (also summarized in Algorithm 1). The first step is pre-training and initialization. We assume that the extractor and classifier (E_S and C_S) of the source domain have been trained either using supervised learning or through prior domain adaptation, and the source discriminator D_S is initialized randomly. Thereafter, the target domain components, E_T, C_T and D_T, are initialized with the respective source components.

During adversarial training, for each step, source and target domains sample a training batch from their own domain data and calculate stochastic gradients for D_S on source domain data and for E_T, D_T on target domain data accordingly. However, as shown in Eq.1, the discriminator needs to be trained on data from both the source and target domains, therefore we need a mechanism to transfer knowledge across between source and target domains. As opposed to transferring the raw data or extracted features across nodes, our approach performs knowledge exchange through the *gradients of the discriminators*. This in turn does afford certain privacy benefits as we are not sharing raw data or the extracted features or even the gradients of the feature extractor which can potentially leak raw data Aono et al. (2017). To the best of our knowledge, no prior work has shown that discriminator gradients can leak training data, however we do not discount the possibility that privacy attacks can be developed on our method in the future, and leave their study and mitigation as a future work.

A simple strategy for knowledge transfer between nodes would be to exchange and average the gradients of the two discriminators after each step, and then update D_S and D_T with the averaged gradients. While this will ensure that the discriminators are synchronized, it incurs a significant communication cost for each step. Instead, we propose a simple but effective method, called *Lazy*

Synchronization, to reduce the communication cost of the algorithm. The basic idea is to synchronize the source and target discriminators every p training steps. We refer to the training steps at which the synchronization takes place as the *sync-up steps* while the other steps during which both nodes are computing the gradients locally are called *local steps*. For discriminators D_S and D_T, their local gradients are accumulated during *local steps* and during the *sync-up steps*, the accumulated gradients on each node will be averaged and applied to D_S and D_T. Through this, we can ensure there is no divergence between the discriminators, and at the same time we are able to decrease the communication cost to $1/p$.

Algorithm 1: DISTRIBUTED_UDA: Lazy-Synchronized Distributed Domain Adaptation

---

Result: E_T and C_T

1 **Input**: Pre-trained E_S and C_S; Randomly Initialize D_S; Initialize $E_T = E_S$, $D_T = D_S$, and $C_T = C_S$; Sync up step p; number of total steps N;

2 **for** $n = 1, 2, ..., N$ **do**

3   Source node and target node sample a batch of data respectively, $\xi_s^{(n)}$ and $\xi_t^{(n)}$;

4   Calculate gradients $\nabla g(D_S, \xi_s^{(n)})$ on source node, gradients $\nabla g(E_T, \xi_t^{(n)})$ and $\nabla g(D_T, \xi_t^{(n)})$ on target node ;

5   **if** *isTargetNode* **then**

6   Apply $\nabla g(E_T, \xi_t^{(n)})$ to E_T

7   **end**

8   Add $\nabla g(D_S, \xi_s^{(n)})$ to source gradients buffer G_S, add $\nabla g(D_T, \xi_t^{(n)})$ to target gradients buffer G_T;

9   **if** $n\%p == 0$ **then**

10   Exchange gradients buffer and calculate averaged gradients $g_{avg} = \frac{G_S + G_T}{2p}$;

11   Apply g_{avg} to D_S and D_T ;

12   Clear G_S and G_T ;

13   **end**

14 **end**

Algorithm 2: COLAB_SELECT: Wasserstein-Distance Guided Collaborator Selection

---

1 **Input**: Candidate set $\mathbb{C} = \{(p_1, E_1, C_1), (p_2, E_2, C_2)...(p_N, E_N, C_N)\}$, Target Dataset p_T;

2 **for** (p_i, E_i, C_i) *in* $\mathbb{C}$ **do**

3   W_i = compute_wasserstein_distance(p_i, p_T);

4   Compute source error ϵ_s using a small labeled test set.;

5   Compute the Lipschitz Constant K for the source extractor E_i and classifier C_i. ;

6    $\epsilon_{t_{max}}^i = \epsilon_s + 2.K.\mathbf{W}_i$;

7 **end**

8 Optimal Collaborator $O = \underset{i=1...N}{\arg\min} (\epsilon_{t_{max}}^i)$;

9 Return E_O and C_O;

Algorithm 3: MDDA: Multi-step Decentralized Domain Selection

---

1 **Input**: Initial Candidate set $\mathbb{C} = \{(E_S, C_S)\}$, Ordering of K target domains $\mathbb{T} = T_1, T_2 ... T_K$;

2 **for** T_i *in* $\mathbb{T}$ **do**

3   Obtain the optimal collaborator $O \in \mathbb{C}$ using COLAB_SELECT;

4   Run DISTRIBUTED_DA between O and T_i to obtain E_{T_i} and C_{T_i} ;

5    $\mathbb{C} \leftarrow \mathbb{C} \cup \{(E_{T_i}, C_{T_i})\}$;

6 **end**

The target extractor E_T is independent of the source data, therefore it is updated for each batch using the adversarial formulation proposed by the underlying adaptation algorithm. For instance, Equation 9 shows the loss function to update E_T as proposed in ADDA. On the other hand, GRL (Ganin et al. (2016)) uses a gradient reversal technique which results in $\mathcal{L}_{\text{adv}_M} = -L_{\text{adv}_D}$, Shen et al. (2018) uses the Wasserstein Distance as a metric for adversarial training. Details about the adversarial loss functions of different algorithms used in this paper are provided in Appendix A. Finally, the target classifier C_T is initialized with C_S and is not updated in the training process. The intuition is that if the feature space of the target domain can be successfully aligned with the source domain, then C_S can directly be used in the target domain without any adaptation.

In §4.2, we empirically show that our method can obtain comparable accuracy to non-distributed training algorithms, while at the same time, preserving private user data and minimizing the communication costs in the training process.

3.3 Wasserstein distance guided collaborator selection

We now discuss how to select an optimal adaptation collaborator $c \in \mathcal{C}_K$ for each target domain. Indeed, we should select a collaborator that is likely to yield the lowest target error post adaptation, but can we choose the optimal collaborator even before performing domain adaptation? In a seminal theoretical work, Ben-David et al. (2010) showed that the target error is bounded by the

sum of source error and the divergence between source and target distributions. Redko et al. (2017) and Shen et al. (2018) did a similar analysis using the Wasserstein distance, which, together with Lipschitz functions, forms the basis for our collaborator selection method.

A function $f : X \to \mathbb{R}$ is θ-Lipschitz if it satisfies the inequality $\|f(x) - f(y)\| \leq \theta \|x - y\|$ for some $\theta \in \mathbb{R}_+$. The smallest such θ is called the Lipschitz constant $\mathrm{Lip}(f)$ of f. Further, the 1-Wasserstein distance (Villani (2008)) between two distributions p_1 and p_2 – using the duality formula – is

$$W_1(p_1, p_2) = \sup_{f:\mathrm{Lip}(f) \leq 1} \mathbb{E}_{p_1}[f] - \mathbb{E}_{p_2}[f] \qquad (3)$$

Shen et al. (2018) computed the following robustness bound

$$\epsilon_{p_2}(h, h') \leq \epsilon_{p_1}(h, h') + 2\theta W_1(p_1, p_2) \qquad (4)$$

for any two θ-Lipschitz hypotheses h and h', where we denoted

$$\epsilon_p(h, h') = \mathbb{E}_p\left[\|h - h'\|\right]. \qquad (5)$$

Our method is motivated by the observation that the above bound is a good approximation of the error $\epsilon_{p_2}(h) = \epsilon_{p_2}(h, h^{\mathrm{true}})$, provided that both the true hypothesis h^{true} and the learned hypotheses $h = E \circ C$ are θ-Lipschitz, and the push-forward measures $E_* p$ are close together in the Wasserstein distance, for a sufficiently small θ. These conditions are motivated by the fact that the domains should be well aligned for unsupervised domain adaptation to be effective. Using a Lipschitz continuous extractor allows us to perform adversarial alignment of higher order features, while maintaining a Lipschitz continuity guarantee on the true hypothesis as a function of the encoded features $E(x)$, where $x \sim p_2$.

Now assume we are trying to use domain adaptation to find a model for a domain $D = (\mathbb{R}^n, p)$ and we have a set of *candidate* domains $D_k = (\mathbb{R}^n, p_k)$, $k = 1, \ldots, K$ each with a pre-trained model $\mathcal{M}_k = (E_k, C_k)$, obtained by using either supervised learning or prior domain adaptation. We use the estimate provided by Equation 4 to select the optimal collaborator domain

$$D_{opt} = \underset{k=1,\ldots,K}{\mathrm{argmin}}\ \epsilon_{p_k}(E_k \circ C_k) + 2\theta W_1(p_k, p) \qquad (6)$$

and thereafter perform adaptation from D_{opt} to D.

Enforcing Lipschitz continuity and computing the Wasserstein distance. Training neural networks with minimal Lipschitz constants can be done by directly regularizing the spectral norm of the linear part of each layer Mises & Pollaczek-Geiringer (1929); Gouk et al. (2018), or a gradient penalty Gulrajani et al. (2017), or indirectly by using $L1$ or $L2$ weight decay. Enforcing a hard constraint on θ can be done by rescaling the linear part of each layer or, indirectly, by weight clipping. For the feature extractor and classifier neural networks, we employ Spectral Norm regularization proposed by Gouk et al. (2018). Further, to compute the Wasserstein distance between distributions, we train a Wasserstein critic with gradient penalty as proposed by Gulrajani et al. (2017). This critic can also be trained in a distributed manner following our lazy synchronization strategy (§ 3.2).

3.4 Multi-Step Decentralized Domain Adaptation (MDDA)

Using the two core ideas discussed § 3.2 and § 3.3, we now summarize our multi-step DA algorithm MDDA (Algorithm 3). Assume we are given a source domain with pre-trained model and an arbitrary ordering of K unlabeled target domains. For every target domain that joins the system, we run collaborator selection with the candidates available in the system. Upon selecting an optimal collaborator, we run the distributed DA algorithm to enable uDA in a privacy-preserving manner. The adaptation process results in a feature extractor E_T and a classifier C_T for the target domain. Finally, the recently adapted target domain is added to the candidate set, and may serve as a potential collaborator for future domains.

4 Evaluation

4.1 Implementation

Datasets. We conduct experiments on five image and audio datasets: Rotated MNIST, Digits, and Office-Caltech, DomainNet and Mic2Mic. *Rotated MNIST* is a variant of MNIST with numbers rotated from 0°to 330°at increments of 30°. Each rotation is considered a separate domain. The

Digits adaptation task has five domains: MNIST (M), USPS (U), SVHN (S) (Netzer et al. (2011)), MNIST-M and SynNumbers (SYN) (Ganin & Lempitsky (2014)). Each domain consists of 10 digit classes ranging from 0-9 in different styles. The *Office-Caltech* dataset contains object images from 10 classes obtained from Amazon (A), DSLR camera (D), Web camera (W), and Caltech-256 (C). *DomainNet* (Peng et al. (2018)) is a new dataset with four labeled image domains containing 345 classes each: Real (R), QuickDraw (Q), Infograph (I), and Sketch (S). Finally, Mic2Mic (Mathur et al. (2019)) is a speech-based keyword detection dataset wherein the keywords are recorded with four different microphones: Matrix Creator (C), Matrix Voice (V), ReSpeaker (R) and USB (U). Each microphone represents a domain.

Baselines. To evaluate our collaborator selection strategy, we compare it against the following:

- **Labeled Source.** This represents the most commonly used approach in uDA works, wherein every target domain performs a pairwise adaptation with the labeled source domain S.
- **Random Collaborator.** Here, we randomly choose a collaborator $c \in \mathcal{C}_K$ from the collaborator set and perform adaptation with the target domain.
- **Multi-Collaborator.** This approach is based on MDAN proposed by Zhao et al. (2018), wherein all available candidate domains are used for adaptation, however the contribution of each domain is dynamically re-weighted in the adversarial training process. However, note that MDAN assumes that all the candidate domains are labeled and jointly optimize the classification loss with the adversarial training. In our scenario, only one candidate domain has labeled data (S) while others are unlabeled. As such, we implement a modified version of MDAN which only optimizes their proposed adversarial loss in line with our problem formulation in §3.1.

Further, we compare our proposed distributed adversarial learning architecture against (i) a centralized uDA baseline wherein the source and target data reside on the same node and adversarial training takes place in a non-distributed manner, and (ii) D-PSGD proposed by Lian et al. (2017a) for decentralized training of neural networks.

Experiment Setup. We follow the same evaluation protocol as earlier uDA works (Hoffman et al. (2018); Tzeng et al. (2017)) wherein the unlabeled training instances from source and target domains are used for adversarial training, and the adapted model is evaluated on a held-out test dataset from target domain. In addition, we use a small subset of the training instances (10% of the total instances) for doing collaborator selection. Further, as we explained earlier, we assume that target domains join the system sequentially in an order, one at a time. Therefore, for each dataset, we randomly select different orderings of source and target domains and present average results across them. Our system is implemented with Tensorflow 2.0 and trained on Nvidia V100 GPUs. For more details about domain orderings, neural network architectures and the training hyper-parameters, please see Appendix A.

4.2 Results

We now present our results of applying MDDA on five datasets. Overall, our results show that MDDA selects the right collaborator for adaptation in 82% of the cases, which result in the highest mean target domain accuracy when compared to other baselines.

Performance of Collaborator Selection. For each dataset, we choose three random orderings of source and target domains, e.g., for *Office-Caltech*, we choose O_1=**W**,A,D,C; O_2=**D**,C,A,W; and O_3=**A**,D,W,C. Here the first domain in the order (in bold) represents the labeled source domain, while the others are unlabeled target domains in the order in which they join the system. Please refer to Appendix A for details about the orderings used for other datasets.

Figure 1 shows the accuracy of our collaborator selection algorithm. For this experiment, we perform adaptation between a target domain and each available candidate, and based on the target accuracy after each pairwise adaptation, we obtain the collaborator that yields the highest accuracy for each target domain. This serves as the ground truth for our algorithm. Thereafter, we run our collaborator selection algorithm on each ordering and obtain the optimal collaborator based on Algorithm 2. By comparing the output of our algorithm with the ground truth, we obtain Figure 1 which shows that on average, our algorithm has a selection accuracy of 82%. On further analysis, we found that our algorithm primarily makes mistakes when two candidates have similar domain discrepancy (estimated using the W_1 distance) with the target domain and we pick the second most

optimal collaborator. In such scenarios, although the top-1 collaborator selection accuracy drops, it typically does not impact the target error significantly because adapting with the second-most optimal domain also yields a good adaptation performance.

	RMNIST			Mic2Mic			Digits			Office-Caltech			DomainNet	
	O_1	O_2	O_3	O_1	O_2	O_3	O_1	O_2	O_3	O_1	O_2	O_3	O_1	O_2
No Adaptation	36.23	36.23	35.80	73.11	73.38	74.7	64.34	73.42	57.80	93.41	87.15	92.32	19.09	19.03
Random	42.89	39.73	43.49	76.9	79.1	78.0	65.11	78.41	59.5	95.45	90.10	95.69	32.21	33.19
Labeled Source	53.62	54.53	46.47	**78.07**	**80.96**	**79.96**	66.02	81.46	**65.89**	95.45	**91.98**	95.57	**34.28**	34.21
Multi-Collaborator	36.08	37.88	37.84	74.34	75.19	75.37	60.63	64.19	62.91	87.64	88.33	92.37	25.3	24.1
MDDA (Ours)	**86.08**	**70.84**	**79.19**	**78.07**	80.12	**79.96**	**81.87**	**89.03**	64.85	**95.82**	89.58	**96.01**	34.21	**34.34**
Ideal	86.38	71.77	79.52	78.07	80.96	79.96	83.84	89.03	69.32	95.82	92.09	96.01	34.28	34.34

Table 1: Target accuracy under different techniques of selecting a collaborator using ADDA. *Ideal* refers to the best achievable performance if the most optimal collaborator is picked for each target.

Table 1 shows, for three different orderings, the mean accuracy across all target domains with MDDA and other baselines. We observe that in majority of the scenarios, MDDA outperforms the labeled-source adaptation baseline which is commonly used in uDA methods. This confirms our key intuition that a labeled source domain is not always optimal for domain adaptation, and demonstrates the value of a more flexible and decentralized approach like MDDA. Interestingly, we observe that while the multi-collaborator baseline is less accurate than MDDA in general, its performance is particularly poor on Rotated MNIST in which the number of collaborators are quite high – while a detailed investigation of this finding is outside the scope of this paper, we surmise that this technique does not scale well as the number of collaborator domains increase. MDDA, on the contrary, only performs pairwise adaptation once an optimal collaborator is selected, as such it scales gracefully as the number of target domains increase.

The results presented so far used the adversarial loss formulation from Eq. 1 and 9 which was proposed in ADDA. In Table 2, we evaluate the applicability of MDDA to methods that use other forms of adversarial losses. More specifically, we evaluate MDDA a) when a Gradient Reversal Layer (GRL) is used to compute the mapping loss and b) in cases where Wasserstein Distance is used as a loss metric for domain discriminator (Shen et al. (2018)). More details about these losses are provided in the Appendix A. We observe that while different loss formulations yield different target accuracies, MDDA can work in conjunction with all of them to improve the overall accuracy over a labeled source-only adaptation.

Figure 1: Mean accuracy of collaborator selection for three orderings for Rotated MNIST (RM), Digits (DI), Mic2Mic (M2M), OfficeCaltech (OC) and DomainNet(DN).

	RMNIST (O_1)			Digits (O_2)		
	ADDA	GRL	WassDA	ADDA	GRL	WassDA
No Adaptation	36.23	36.23	36.23	73.42	73.42	73.42
Random	42.89	39.33	43.78	78.41	79.22	74.91
Labeled Source	53.62	45.60	37.99	81.46	76.66	77.31
MDDA(Ours)	**86.08**	**63.49**	**85.6**	**89.03**	**85.24**	**79.48**
Ideal	86.38	68.92	86.94	68.92	85.42	79.9

Table 2: Mean target accuracy for a random order of domains for different adaptation methods.

Performance of Distributed Domain Adaptation. We now evaluate our Lazy-synchronized DA algorithm from a domain adaptation lens. As such, our key objective is to evaluate the target accuracy and communication trade-off, i.e., can we save communication costs associated with distributed training while ensuring similar levels of target domain accuracy as the conventional non-distributed DA algorithms. In Figure 2, we plot the target domain accuracy with the number of adversarial training steps for three uDA tasks. It can be observed that even with lazy synchronization (sync-up step size $p = 4$), we can achieve similar target accuracy and convergence rate as non-distributed and synchronized training methods, while incurring only 25% of the communication costs (as we are exchanging data every 4 steps). We also note that the distributed training baseline (DPSGD) performs poorly for adversarial training.

Table 3 expands this finding to show the target domain accuracy for 10 adaptation tasks under different training mechanisms. Further, we also report the average time taken to perform the adversarial training for different datasets. Note that the training time is the sum of local computation time and communication time across nodes. In conventional non-distributed DA, it is assumed that the do-

main datasets are available on the same node, as such there is no communication required during the training, which expectedly results in the fastest training process, at the expense of user privacy. In the fully-synchronized case, the amount of communication equals to the size of discriminator gradients multiplied by the number of training steps, whereas in the lazy-synchronized case, the communication amount is one pth of the amount of fully synchronized case, where p is the sync-up step. Based on the amount of data communicated across nodes, we estimate the communication time by assuming a bandwidth of 40Mbps which is roughly the average upload speed for broadband connections globally[1]. The computation time is measured for each training step and aggregated to get the total computation time. By adding the total computation time with the total communication time, we obtain the total training time, which we report as one of the metrics to evaluate our distributed method.

As shown in Table 3, the Lazy-Synchronized approach achieves target accuracy close to non-distributed and fully-synchronized approaches. For example, in the D $\rightarrow$ A task in Office-Caltech, our approach – while ensuring that domain data remains private – results in 91.77% target domain accuracy, which is indeed close to the 92.01% and 92.13% accuracy of non-distributed and fully-synchronized training mechanism. Further, we observe that the training time of our approach is significantly less than the fully-synchronized approach due to the reduced communication.

Figure 2: Comparison of target domain accuracy and training convergence across non-distributed and distributed training methods. For Lazy-synchronized approach, we use sync-up step $p = 4$. For Mic2Mic, the PSGD baseline did not improve the accuracy, as such we omit it from the figure.

	RMNIST			Office-Caltech			Digits			DomainNet			Mic2Mic		
Training	0 $\rightarrow$ 60	150 $\rightarrow$ 180	t (min)	W $\rightarrow$ C	D $\rightarrow$ A	t (min)	M-M $\rightarrow$ U	Syn $\rightarrow$ U	t (min)	S $\rightarrow$ R	Q $\rightarrow$ R	t (min)	C $\rightarrow$ R	R $\rightarrow$ C	t (min)
Source-Only	32.68	61.51	-	87.81	85.28	-	57.54	79.32	-	34.34	30.75	-	69.65	69.11	-
Non-Distributed	69.61	91.86	0.15	91.74	92.01	11	82.1	90.1	0.67	54.91	50.67	1.12	78.02	77.94	5.8
Synchronized	69.30	91.21	6.8	91.02	92.13	28	82.13	89.9	20.7	54.23	49.95	17.5	81.5	81.1	22.5
Lazy Synchronized	68.34	90.16	1.8	90.56	91.77	15.3	81.66	89.78	5.7	53.25	49.02	5.2	77.48	81.03	10

Table 3: Target Domain Accuracy and Training Time (averaged across two adaptation tasks) for each dataset. As expected, the *Non-Distributed* approach is the fastest as it does not require any communication during training, at the expense of user privacy. Our Lazy-Synchronized approach (p=4) provides the best trade-off between accuracy and training time, while preserving user privacy.

5 Limitations and Conclusion

In this paper, we introduced a novel perspective on uDA research and explored practical challenges associated with deploying uDA methods in real-world ML systems. Our proposed framework MDDA is the first-ever solution aiming to make uDA methods work in a decentralized and distributed manner.

As uDA is a rapidly evolving field, we did not study every class of uDA algorithms (e.g., those which combine feature-level adaptations with instance-level adaptations) in this paper and we leave it as a future work. We also made an assumption that target domains are introduced sequentially in the system, however there could indeed be other ways in which ML models would evolve in practice (e.g., multiple target domains join together or in batches). We leave those scenarios as future work.

Finally, our method provides user privacy by only sending discriminator gradients across nodes. While no prior work has shown that discriminator gradients can leak raw data, we do not discount the possibility that privacy attacks could be developed on MDDA in the future. We leave a detailed privacy study of MDDA as a future work.

---

[1]https://www.speedtest.net/global-index

References

Yoshinori Aono, Takuya Hayashi, Lihua Wang, Shiho Moriai, et al. Privacy-preserving deep learning via additively homomorphic encryption. *IEEE Transactions on Information Forensics and Security*, 13(5):1333–1345, 2017.

Shai Ben-David, John Blitzer, Koby Crammer, Alex Kulesza, Fernando Pereira, and Jennifer Wortman Vaughan. A theory of learning from different domains. *Machine learning*, 79(1-2), 2010.

Andreea Bobu, Eric Tzeng, Judy Hoffman, and Trevor Darrell. Adapting to continuously shifting domains. 2018.

Keith Bonawitz, Hubert Eichner, Wolfgang Grieskamp, Dzmitry Huba, Alex Ingerman, Vladimir Ivanov, Chloe Kiddon, Jakub Konecny, Stefano Mazzocchi, H Brendan McMahan, et al. Towards federated learning at scale: System design. *arXiv preprint arXiv:1902.01046*, 2019.

Wei Dai, Abhimanu Kumar, Jinliang Wei, Qirong Ho, Garth Gibson, and Eric P Xing. High-performance distributed ml at scale through parameter server consistency models. In *Twenty-Ninth AAAI Conference on Artificial Intelligence*, 2015.

Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. *arXiv preprint arXiv:1409.7495*, 2014.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *The Journal of Machine Learning Research*, 17(1):2096–2030, 2016.

Robin C Geyer, Tassilo Klein, and Moin Nabi. Differentially private federated learning: A client level perspective. *arXiv preprint arXiv:1712.07557*, 2017.

Henry Gouk, Eibe Frank, Bernhard Pfahringer, and Michael Cree. Regularisation of neural networks by enforcing lipschitz continuity. *arXiv preprint arXiv:1804.04368*, 2018.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In *Advances in neural information processing systems*, pp. 5767–5777, 2017.

Judy Hoffman, Eric Tzeng, Taesung Park, Jun-Yan Zhu, Phillip Isola, Kate Saenko, Alexei Efros, and Trevor Darrell. Cycada: Cycle-consistent adversarial domain adaptation. In *International Conference on Machine Learning*, pp. 1994–2003, 2018.

Ehsan Hosseini-Asl, Yingbo Zhou, Caiming Xiong, and Richard Socher. A multi-discriminator cyclegan for unsupervised non-parallel speech domain adaptation. *arXiv preprint arXiv:1804.00522*, 2018.

Jakub Konečnỳ, H Brendan McMahan, Felix X Yu, Peter Richtárik, Ananda Theertha Suresh, and Dave Bacon. Federated learning: Strategies for improving communication efficiency. *arXiv preprint arXiv:1610.05492*, 2016.

Mu Li, David G Andersen, Jun Woo Park, Alexander J Smola, Amr Ahmed, Vanja Josifovski, James Long, Eugene J Shekita, and Bor-Yiing Su. Scaling distributed machine learning with the parameter server. In *11th {USENIX} Symposium on Operating Systems Design and Implementation ({OSDI} 14)*, pp. 583–598, 2014.

Xiangru Lian, Ce Zhang, Huan Zhang, Cho-Jui Hsieh, Wei Zhang, and Ji Liu. Can decentralized algorithms outperform centralized algorithms? a case study for decentralized parallel stochastic gradient descent. In *Advances in Neural Information Processing Systems*, pp. 5330–5340, 2017a.

Xiangru Lian, Wei Zhang, Ce Zhang, and Ji Liu. Asynchronous decentralized parallel stochastic gradient descent. *arXiv preprint arXiv:1710.06952*, 2017b.

Mingsheng Long, Yue Cao, Jianmin Wang, and Michael I Jordan. Learning transferable features with deep adaptation networks. *arXiv preprint arXiv:1502.02791*, 2015.

Mingsheng Long, Han Zhu, Jianmin Wang, and Michael I Jordan. Deep transfer learning with joint adaptation networks. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 2208–2217. JMLR. org, 2017.

Akhil Mathur, Anton Isopoussu, Nadia Berthouze, Nicholas D Lane, and Fahim Kawsar. Unsupervised domain adaptation for robust sensory systems. In *Proceedings of the 2019 ACM International Joint Conference on Pervasive and Ubiquitous Computing and Proceedings of the 2019 ACM International Symposium on Wearable Computers*, pp. 505–509. ACM, 2019.

Luca Melis, Congzheng Song, Emiliano De Cristofaro, and Vitaly Shmatikov. Exploiting unintended feature leakage in collaborative learning. In *2019 IEEE Symposium on Security and Privacy (SP)*, pp. 691–706. IEEE, 2019.

RV Mises and Hilda Pollaczek-Geiringer. Praktische verfahren der gleichungsauflösung. *ZAMM-Journal of Applied Mathematics and Mechanics/Zeitschrift für Angewandte Mathematik und Mechanik*, 9(2):152–164, 1929.

Milad Nasr, Reza Shokri, and Amir Houmansadr. Comprehensive privacy analysis of deep learning: Stand-alone and federated learning under passive and active white-box inference attacks. *arXiv preprint arXiv:1812.00910*, 2018.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Y Ng. Reading digits in natural images with unsupervised feature learning. 2011.

Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. *arXiv preprint arXiv:1812.01754*, 2018.

Ievgen Redko, Amaury Habrard, and Marc Sebban. Theoretical analysis of domain adaptation with optimal transport. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 737–753. Springer, 2017.

Swami Sankaranarayanan, Yogesh Balaji, Carlos D Castillo, and Rama Chellappa. Generate to adapt: Aligning domains using generative adversarial networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8503–8512, 2018.

Alexander Sergeev and Mike Del Balso. Horovod: fast and easy distributed deep learning in tensorflow. *arXiv preprint arXiv:1802.05799*, 2018.

Jian Shen, Yanru Qu, Weinan Zhang, and Yong Yu. Wasserstein distance guided representation learning for domain adaptation. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Hanlin Tang, Shaoduo Gan, Ce Zhang, Tong Zhang, and Ji Liu. Communication compression for decentralized training. In *Advances in Neural Information Processing Systems*, pp. 7652–7662, 2018a.

Hanlin Tang, Xiangru Lian, Ming Yan, Ce Zhang, and Ji Liu. D ²: Decentralized training over decentralized data. *arXiv preprint arXiv:1803.07068*, 2018b.

Eric Tzeng, Judy Hoffman, Kate Saenko, and Trevor Darrell. Adversarial discriminative domain adaptation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 7167–7176, 2017.

Cédric Villani. *Optimal transport: old and new*, volume 338. Springer Science & Business Media, 2008.

Markus Wulfmeier, Alex Bewley, and Ingmar Posner. Addressing appearance change in outdoor robotics with adversarial domain adaptation. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 1551–1558. IEEE, 2017.

Qiang Yang, Yang Liu, Tianjian Chen, and Yongxin Tong. Federated machine learning: Concept and applications. *ACM Transactions on Intelligent Systems and Technology (TIST)*, 10(2):12, 2019.

Han Zhao, Shanghang Zhang, Guanhang Wu, José MF Moura, Joao P Costeira, and Geoffrey J Gordon. Adversarial multiple source domain adaptation. In *Advances in Neural Information Processing Systems*, pp. 8559–8570, 2018.

A   Appendix

Here we provide details about our experiment setup and model architectures. We are also in the process of obtaining necessary clearances to release our source code to the community.

A.1   Domain Orderings.

As we mentioned in the paper, the order of target domains joining the system can effect the decisions of our collaborator selecting algorithm, and then cause different adaptation results. To measure the effect of target orders, we reported three different orders for each data set in our experiments. We specify these order as follows:

	O_1	O_2	O_3
RMNIST	**0**,30,60,90,120,150 180,210,240,270,300,330	**0**,180,210,240,270,300,330,30,60,90,120,150 300,330,30,60,90,120,150	**30**,0,180,210,240 330,60,90,270,300,120,150
Mic2Mic	**C**,V,R,U	**R**,U,C,V	**V**,R,U,C
Digits	svhn,mnist,mnist_modified,synth_digits,usps	synth_digits,usps,mnist,mnist_modified,svh	mnist_modified,mnist,svhn,usps,synth_digits
Office-Caltech	**W**-A-D-C	**D**-C-A-W	**A**-D-W-C
DomainNet	S,R,I,Q	S,Q,I,R	R,I,Q,S

Table 4

A.2   Model Architectures and Hyperparameters.

We now describe the neural architectures used for each dataset along with the hyperparameters used in supervised and adversarial learning.

Rotated MNIST: We use the well-known LeNet architecture for this dataset as shown below. The model was trained for each source domain with a learning rate of 10^{-4} using the Adam optimizer and a batch size of 32.

```
Conv2D(filters = 20, kernel_size = 5, activation='relu'),
MaxPooling2D(pool_size = 2, strides = 2),
Conv2D(filters = 50, kernel_size = 5, activation='relu'),
MaxPooling2D(pool_size = 2, strides = 2),
Flatten(),
Dense(500, activation='relu'),
Dense(10, activation='softmax')
```

In order to enforce the Lipschitz continuity, we added spectral norm regularization during the training process. In the adversarial training process, we used the ADDA losses to perform domain adaptation with a learning rate of 10^{-5} for the target extractor and 10^{-4} for the discriminator.

Office-Caltech: We used Keras Inception-V3 pre-trained on ImageNet as the base model for this task. We added a bottleneck layer and a final classification layer. The model was trained for each source domain with a learning rate of 10^{-5} using the Adam optimizer and a batch size of 32.

```
InceptionV3(include_top=False, input_shape=(299, 299, 3),avg='pool'),
Dense(256, activation='relu')
Dense(10, activation='softmax')
```

In order to enforce the Lipschitz continuity, we added spectral norm regularization during the training process. In the adversarial training process, we used the ADDA losses to perform domain adaptation with a learning rate of 10^{-5} for the target extractor and 1e-4 for the discriminator.

DomainNet: We used Keras ResNet50-v2 pre-trained on ImageNet as the base model for this task. The model was trained for each source domain with a learning rate of 1e-5 using the Adam optimizer and a batch size of 64.

```
ResNet50V2(include_top=False, input_shape=(224, 224,3), avg='pool'),
```

```
Dense(245, activation='softmax')
```

In order to enforce the Lipschitz continuity, we added spectral norm regularization during the training process. In the adversarial training process, we used the ADDA losses to perform domain adaptation with a learning rate of 10^{-6} for the target extractor and 10^{-4} for the discriminator.

Mic2Mic: We mainly used three convolutional layers for this task. The model was trained for each source domain with a learning rate of 10^{-5} using the Adam optimizer and a batch size of 64.

```
Conv2D(filters = 64, kernel_size = (8,20), activation='relu')
MaxPooling2D(pool_size = (2,2)),
Conv2D(filters = 128, kernel_size = (4,10), activation='relu'),
MaxPooling2D(pool_size = (1,4)),
Conv2D(filters = 512, kernel_size = (2,2)),
Flatten(),
Dense(256, activation='relu'),
Dense(31)
```

In order to enforce the Lipschitz continuity, we added spectral norm regularization during the training process. In the adversarial training process, we used the ADDA losses to perform domain adaptation with a learning rate of 10^{-6} for the target extractor and 10^{-4} for the discriminator.

Digits: We constructed a neural network with three convolutional layer and some additional techniques like Dropout, BatchNormalization, for this task. The model was trained for each source domain with a learning rate of 10^{-5} using the Adam optimizer and a batch size of 64.

```
inputs = tf.keras.Input(shape=(32,32,3), name='img')
x = Conv2D(filters = 64, kernel_size = 5, strides=2)(inputs)
x = BatchNormalization()(x, training=is_training)
x = Dropout(0.1)(x, training=is_training)
x = ReLU()(x)
x = Conv2D(filters = 128, kernel_size = 5, strides=1)(x)
x = BatchNormalization()(x, training=is_training)
x = Dropout(0.3)(x, training=is_training)
x = ReLU()(x)
x = Conv2D(filters = 256, kernel_size = 5, strides=1)(x)
x = BatchNormalization()(x, training=is_training)
x = Dropout(0.5)(x, training=is_training)
x = ReLU()(x)
x = Flatten()(x)
x = Dense(512)(x)
x = BatchNormalization()(x, training=is_training)
x = ReLU()(x)
x = Dropout(0.5)(x, training=is_training)
outputs = Dense(10)(x)
```

In order to enforce the Lipschitz continuity, we added spectral norm regularization during the training process. In the adversarial training process, we used the ADDA losses to perform domain adaptation with a learning rate of 10^{-6} for the target extractor and 10^{-4} for the discriminator.

A.3 Details of Domain Adaptation Algorithms

We now discuss the adversarial training formulation of the various uDA algorithms with which we evaluated the efficacy of our proposed MDDA framework. As shown in Table 4.2, we evaluate our method with three domain adaptation techniques: ADDA (Tzeng et al. (2017)), Gradient Reversal (Ganin et al. (2016)) and Wasserstein DA (Shen et al. (2018)). Below are the adversarial training formulations of these techniques as proposed in their original papers.

ADDA. Following the same notations used earlier in the paper, the adversarial loss formulations of ADDA can be represented mathematically as:

$$\min_D \mathcal{L}_{adv_D} = -\mathbb{E}_{x_s \sim \mathcal{X}_S}[\log(D(E_S(x_s)))] - \mathbb{E}_{x_t \sim \mathcal{X}_T}[\log(1 - D(E_T(x_t)))] \tag{7}$$

$$\min_{E_T} \mathcal{L}_{adv_M} = -\mathbb{E}_{x_t \sim \mathcal{X}_T}[\log(D(E_T(x_t)))] \tag{8}$$

The Discriminator D is optimized according to L_{adv_D} where the source domain data is assigned label 1 and target domain data is assigned label 0. To update the feature extractor E_T, ADDA proposes to invert the domain labels, which results in the loss formulation given in L_{adv_M}.

In order to run ADDA in a distributed manner, we decompose the discriminator D into D_S and D_T which results in the following loss functions:

$$\mathcal{L}_{adv_{D_S}} = -\mathbb{E}_{x_s \sim \mathcal{X}_S}[\log(D_S(E_S(x_s)))] \tag{9}$$

$$\mathcal{L}_{adv_{D_T}} = -\mathbb{E}_{x_t \sim \mathcal{X}_T}[\log(1 - D_T(E_T(x_t)))] \tag{10}$$

$$\min_{E_T} \mathcal{L}_{adv_M} = -\mathbb{E}_{x_t \sim \mathcal{X}_T}[\log(D_T(E_T(x_t)))] \tag{11}$$

Thereafter, we compute local gradients for D_S and D_T,

$$\nabla g(D_S, x_s) = \frac{\delta L_{adv_{D_S}}}{\delta D_S} \tag{12}$$

$$\nabla g(D_T, x_t) = \frac{\delta L_{adv_{D_T}}}{\delta D_T} \tag{13}$$

and aggregate them in the sync-up step as shown in Algorithm 1. The aggregated gradients are used to optimize D_S and D_T, while E_T is optimized using the loss function in Equation 11.

Gradient Reversal. The Gradient Reversal approach uses the same loss formulation for the discriminators D_S and D_T as ADDA as shown in Equations 7, 9, 10.

However, to update the target extractor E_T, it leverages the gradient reversal strategy, resulting in the following loss function.

$$\begin{aligned} \min_{E_T} \mathcal{L}_{adv_M} &= -\mathcal{L}_{adv_{DT}} \\ &= \mathbb{E}_{x_t \sim \mathcal{X}_T}[\log(1 - D_T(E_T(x_t)))] \end{aligned} \tag{14}$$

Wasserstein DA. In this recently published technique, authors use the Wasserstein distance as the loss function for discriminator. Wasserstein distance between two datasets is defined as

$$\text{Wasserstein}(X_s, X_t) = \frac{1}{n_s} \sum_{x_s \sim \mathcal{X}_S} D(E_S(x_s)) - \frac{1}{n_t} \sum_{x_t \sim \mathcal{X}_T} D(E_T(x_t)) \tag{15}$$

where n_s and n_t are the number of samples in the dataset. The discriminator loss is computed as:

$$\min_D \mathcal{L}_{adv_D} = -\mathbb{E}_{x_s \sim \mathcal{X}_S, x_t \sim \mathcal{X}_T}[\text{Wasserstein}(x_s, x_t)] + \gamma L_{grad} \tag{16}$$

where L_{grad} is the gradient penalty used to enforce the Lipschitz constraint on the discriminator. Further, the target extractor is optimized using the following loss function:

$$\min_{E_T} \mathcal{L}_{adv_M} = \mathbb{E}_{x_s \sim \mathcal{X}_S, x_t \sim \mathcal{X}_T}[\text{Wasserstein}(x_s, x_t)] \tag{17}$$

We use the same strategy to compute local gradients for D_S and D_T as shown in Equations 12 and 13.

Finally, Figure 3 shows the general distributed architecture of our distributed domain adaptation method.

Figure 3: Distributed Adversarial Training of MDDA