ADASHIFT: DECORRELATION AND CONVERGENCE OF ADAPTIVE LEARNING RATE METHODS

ABSTRACT

Adam is shown not being able to converge to the optimal solution in certain cases. Researchers recently propose several algorithms to avoid the issue of non-convergence of Adam, but their efficiency turns out to be unsatisfactory in practice. In this paper, we provide a new insight into the non-convergence issue of Adam as well as other adaptive learning rate methods. We argue that there exists an inappropriate correlation between gradient g_t and the second moment term v_t in Adam (t is the timestep), which results in that a large gradient is likely to have small step size while a small gradient may have a large step size. We demonstrate that such unbalanced step sizes are the fundamental cause of non-convergence of Adam, and we further prove that decorrelating v_t and g_t will lead to unbiased step size for each gradient, thus solving the non-convergence problem of Adam. Finally, we propose AdaShift, a novel adaptive learning rate method that decorrelates v_t and g_t by temporal shifting, i.e., using temporally shifted gradient g_{t-n} to calculate v_t. The experiment results demonstrate that AdaShift is able to address the non-convergence issue of Adam, while still maintaining a competitive performance with Adam in terms of both training speed and generalization.

1 INTRODUCTION

First-order optimization algorithms with adaptive learning rate play an important role in deep learning due to their efficiency in solving large-scale optimization problems. Denote $g_t \in \mathbb{R}^n$ as the gradient of loss function f with respect to its parameters $\theta \in \mathbb{R}^n$ at timestep t, then the general updating rule of these algorithms can be written as follows (Reddi et al., 2018):

$$\theta_{t+1} = \theta_t - \frac{\alpha_t}{\sqrt{v_t}} m_t. \tag{1}$$

In the above equation, $m_t \triangleq \phi(g_1, \ldots, g_t) \in \mathbb{R}^n$ is a function of the historical gradients; $v_t \triangleq \psi(g_1, \ldots, g_t) \in \mathbb{R}^n_+$ is an n-dimension vector with non-negative elements, which adapts the learning rate for the n elements in g_t respectively; α_t is the base learning rate; and $\frac{\alpha_t}{\sqrt{v_t}}$ is the adaptive step size for m_t.

One common choice of $\phi(g_1, \ldots, g_t)$ is the exponential moving average of the gradients used in Momentum (Qian, 1999) and Adam (Kingma & Ba, 2014), which helps alleviate gradient oscillations. The commonly-used $\psi(g_1, \ldots, g_t)$ in deep learning community is the exponential moving average of squared gradients, such as Adadelta (Zeiler, 2012), RMSProp (Tieleman & Hinton, 2012), Adam (Kingma & Ba, 2014) and Nadam (Dozat, 2016).

Adam (Kingma & Ba, 2014) is a typical adaptive learning rate method, which assembles the idea of using exponential moving average of first and second moments and bias correction. In general, Adam is robust and efficient in both dense and sparse gradient cases, and is popular in deep learning research. However, Adam is shown not being able to converge to optimal solution in certain cases. Reddi et al. (2018) point out that the key issue in the convergence proof of Adam lies in the quantity

$$\Gamma_t \triangleq \left(\frac{\sqrt{v_t}}{\alpha_t} - \frac{\sqrt{v_{t-1}}}{\alpha_{t-1}} \right), \tag{2}$$

which is assumed to be positive, but unfortunately, such an assumption does not always hold in Adam. They provide a set of counterexamples and demonstrate that the violation of positiveness of Γ_t will lead to undesirable convergence behavior in Adam.

tReddi et al. (2018) then propose two variants, AMSGrad and AdamNC, to address the issue by keeping Γ_t positive. Specifically, AMSGrad defines $\hat{v}_t$ as the historical maximum of v_t, i.e., $\hat{v}_t = \max \{v_i\}_{i=1}^t$, and replaces v_t with $\hat{v}_t$ to keep v_t non-decreasing and therefore forces Γ_t to be positive; while AdamNC forces v_t to have "long-term memory" of past gradients and calculates v_t as their average to make it stable. Though these two algorithms solve the non-convergence problem of Adam to a certain extent, they turn out to be inefficient in practice: they have to maintain a very large v_t once a large gradient appears, and a large v_t decreases the adaptive learning rate $\frac{\alpha_t}{\sqrt{v_t}}$ and slows down the training process.

In this paper, we provide a new insight into adaptive learning rate methods, which brings a new perspective on solving the non-convergence issue of Adam. Specifically, in Section 3, we study the counterexamples provided by Reddi et al. (2018) via analyzing the accumulated step size of each gradient g_t. We observe that in the common adaptive learning rate methods, a large gradient tends to have a relatively small step size, while a small gradient is likely to have a relatively large step size. We show that the unbalanced step sizes stem from the inappropriate positive correlation between v_t and g_t, and we argue that this is the fundamental cause of the non-convergence issue of Adam.

In Section 4, we further prove that decorrelating v_t and g_t leads to equal and unbiased expected step size for each gradient, thus solving the non-convergence issue of Adam. We subsequently propose AdaShift, a decorrelated variant of adaptive learning rate methods, which achieves decorrelation between v_t and g_t by calculating v_t using temporally shifted gradients. Finally, in Section 5, we study the performance of our proposed AdaShift, and demonstrate that it solves the non-convergence issue of Adam, while still maintaining a decent performance compared with Adam in terms of both training speed and generalization.

2 PRELIMINARIES

Adam. In Adam, m_t and v_t are defined as the exponential moving average of g_t and g_t^2:

$$m_t = \beta_1 m_{t-1} + (1-\beta_1)g_t \text{ and } v_t = \beta_2 v_{t-1} + (1-\beta_2)g_t^2, \tag{3}$$

where $\beta_1 \in [0,1)$ and $\beta_2 \in [0,1)$ are the exponential decay rates for m_t and v_t, respectively, with $m_0 = 0$ and $v_0 = 0$. They can also be written as:

$$m_t = (1-\beta_1)\sum_{i=1}^t \beta_1^{t-i}g_i \text{ and } v_t = (1-\beta_2)\sum_{i=1}^t \beta_2^{t-i}g_i^2. \tag{4}$$

To avoid the bias in the estimation of the expected value at the initial timesteps, Kingma & Ba (2014) propose to apply bias correction to m_t and v_t. Using m_t as instance, it works as follows:

$$m_t = \frac{(1-\beta_1)\sum_{i=1}^t \beta_1^{t-i}g_i}{(1-\beta_1)\sum_{i=1}^t \beta_1^{t-i}} = \frac{\sum_{i=1}^t \beta_1^{t-i}g_i}{\sum_{i=1}^t \beta_1^{t-i}} = \frac{(1-\beta_1)\sum_{i=1}^t \beta_1^{t-i}g_i}{1-\beta_1^t}. \tag{5}$$

Online optimization problem. An online optimization problem consists of a sequence of cost functions $f_1(\theta), \ldots, f_t(\theta), \ldots, f_T(\theta)$, where the optimizer predicts the parameter θ_t at each timestep t and evaluate it on an unknown cost function $f_t(\theta)$. The performance of the optimizer is usually evaluated by regret $R(T) \triangleq \sum_{t=1}^T [f_t(\theta_t) - f_t(\theta^*)]$, which is the sum of the difference between the online prediction $f_t(\theta_t)$ and the best fixed-point parameter prediction $f_t(\theta^*)$ for all the previous steps, where $\theta^* = \arg\min_{\theta \in \vartheta} \sum_{t=1}^T f_t(\theta)$ is the best fixed-point parameter from a feasible set ϑ.

Counterexamples. Reddi et al. (2018) highlight that for any fixed β_1 and β_2, there exists an online optimization problem where Adam has non-zero average regret, i.e., Adam does not converge to optimal solution . The counterexamples in the sequential version are given as follows:

$$f_t(\theta) = \begin{cases} C\theta, & \text{if t mod } d = 1; \\ -\theta, & \text{otherwise}, \end{cases} \tag{6}$$

where C is a relatively large constant and d is the length of an epoch. In Equation 6, most gradients of $f_t(\theta)$ with respect to θ are -1, but the large positive gradient C at the beginning of each epoch

makes the overall gradient of each epoch positive, which means that one should decrease θ_t to minimize the loss. However, according to (Reddi et al., 2018), the accumulated update of θ in Adam under some circumstance is opposite (i.e., θ_t is increased), thus Adam cannot converge in such case. Reddi et al. (2018) argue that the reason of the non-convergence of Adam lies in that the positive assumption of $\Gamma_t \triangleq (\sqrt{v_t}/\alpha_t - \sqrt{v_{t-1}}/\alpha_{t-1})$ does not always hold in Adam.

Basic Solutions Reddi et al. (2018) propose maintaining the strict positiveness of Γ_t as solution, for example, keeping v_t non-decreasing or using increasing β_2. In fact, keeping Γ_t positive is not the only way to guarantee the convergence of Adam. Another important observation is that for any fixed sequential online optimization problem with infinitely repeating epochs (e.g., Equation 6), Adam will converge as long as β_1 (or β_2) is large enough. Formally, we have the following theorem:

Theorem 1 (The influence of β_1). For any fixed sequential online convex optimization problem with infinitely repeating of finite length epochs, let the length of an epoch be d, if $\exists G \in \mathbb{R}$ such that $\|\nabla f_t(\theta)\|_\infty \leq G$ and $\exists T \in \mathbb{N}, \exists \epsilon_2 > \epsilon_1 > 0$ such that $\epsilon_1 < d\frac{\alpha_t}{\sqrt{v_t}}G^2 < \epsilon_2$ holds for all $t > T$, then, for any fixed $\beta_2 \in [0,1)$, there exists a $\beta_1 \in [0,1)$ such that Adam has average regret $\leq \epsilon_2$;

The intuition behind Theorem 1 is that, if $\beta_1 \to 1$, then $m_t \to \sum_{i=1}^d g_i/d$, i.e., m_t approaches the average gradient of an epoch, according to Equation 5. Therefore, no matter what the adaptive learning rate $\alpha_t/\sqrt{v_t}$ is, Adam will always converge along the correct direction.

3 THE CAUSE OF NON-CONVERGENCE: UNBALANCED STEP SIZE

In this section, we study the non-convergence issue by analyzing the counterexamples provided by Reddi et al. (2018). We show that the fundamental problem of common adaptive learning rate methods is that: v_t is positively correlated to the scale of gradient g_t, which results in a small step size $\alpha_t/\sqrt{v_t}$ for a large gradient, and a large step size for a small gradient. We argue that such an unbalanced step size is the cause of non-convergence.

We will first define net update factor for the analysis of the accumulated influence of each gradient g_t, then apply the net update factor to study the behaviors of Adam using Equation 6 as an example. The argument will be extended to the stochastic online optimization problem and general cases.

3.1 NET UPDATE FACTOR

When $\beta_1 \neq 0$, due to the exponential moving effect of m_t, the influence of g_t exists in all of its following timesteps. For timestep i ($i \geq t$), the weight of g_t is $(1-\beta_1)\beta_1^{i-t}$. We accordingly define a new tool for our analysis: the net update $net(g_t)$ of each gradient g_t, which is its accumulated influence on the entire optimization process:

$$net(g_t) \triangleq \sum_{i=t}^{\infty} \frac{\alpha_i}{\sqrt{v_i}}[(1-\beta_1)\beta_1^{i-t}g_t] = k(g_t) \cdot g_t, \text{ where } k(g_t) = \sum_{i=t}^{\infty} \frac{\alpha_i}{\sqrt{v_i}}(1-\beta_1)\beta_1^{i-t}, \quad (7)$$

and we call $k(g_t)$ the net update factor of g_t, which is the equivalent accumulated step size for gradient g_t. Note that $k(g_t)$ depends on $\{v_i\}_{i=t}^{\infty}$, and in Adam, if $\beta_1 \neq 0$, then all elements in $\{v_i\}_{i=t}^{\infty}$ are related to g_t. Therefore, $k(g_t)$ is a function of g_t.

It is worth noticing that in Momentum method, v_t is equivalently set as 1. Therefore, we have $k(g_t) = \alpha_t$ and $net(g_t) = \alpha_t g_t$, which means that the accumulated influence of each gradient g_t in Momentum is the same as vanilla SGD (Stochastic Gradient Decent). Hence, the convergence of Momentum is similar to vanilla SGD. However, in adaptive learning rate methods, v_t is function over the past gradients, which makes its convergence nontrivial.

3.2 ANALYSIS ON SEQUENTIAL ONLINE OPTIMIZATION COUNTEREXAMPLES

Note that v_t exists in the definition of net update factor (Equation 7). Before further analyzing the convergence of Adam using the net update factor, we first study the pattern of v_t in the sequential online optimization problem in Equation 6. Since Equation 6 is deterministic, we can derive the formula of v_t as follows:

Theorem 2 (Limit of v_t). In the sequential online optimization problem in Equation 6, denote $\beta_1, \beta_2 \in [0, 1)$ as the decay rates, $d \in \mathbb{N}$ as the length of an epoch, $n \in \mathbb{N}$ as the index of epoch, and $i \in \{1, 2, ..., d\}$ as the index of timestep in one epoch. Then the limit of v_{nd+i} when $n \to \infty$ is:

$$\lim_{n \to \infty} v_{nd+i} = \frac{1 - \beta_2}{1 - \beta_2^d}(C^2 - 1)\beta_2^{i-1} + 1 . \tag{8}$$

Given the formula of v_t in Equation 8, we now study the net update factor of each gradient. We start with a simple case where $\beta_1 = 0$. In this case we have

$$\lim_{n \to \infty} k(g_{nd+i}) = \lim_{n \to \infty} \frac{\alpha_t}{\sqrt{v_{nd+i}}}. \tag{9}$$

Since the limit of v_{nd+i} in each epoch monotonically decreases with the increase of index i according to Equation 8, the limit of $k(g_{nd+i})$ monotonically increases in each epoch. Specifically, the first gradient $g_{nd+1} = C$ in epoch n represents the correct updating direction, but its influence is the smallest in this epoch. In contrast, the net update factor of the subsequent gradients -1 are relatively larger, though they indicate a wrong updating direction.

The above problem stems from the inappropriate correlation between v_t and g_t. Recall that $v_t = \beta_2 v_{t-1} + (1 - \beta_2)g_t^2$, and we assume v_{t-1} is independent of g_t. When a new gradient g_t arrives, if g_t is large, v_t is likely to be larger; and if g_t is small, v_t is also likely to be smaller. As a result, a large gradient is likely to have a small net update factor, while a small gradient is likely to have a large net update factor in Adam.

We further consider the general case where $\beta_1 \neq 0$. The result is presented in the following theorem:

Theorem 3 (Unbalanced net update factor). In the sequential online optimization problem in Equation 6, when $n \to \infty$, the limit of net update factor $k(g_{nd+i})$ of epoch n is:

$$\lim_{n \to \infty} k(g_{nd+i}) = \sum_{t=nd+i}^{\infty} \frac{(1 - \beta_1)\beta_1^{t-nd-i}}{\sqrt{\frac{1-\beta_2}{1-\beta_2^d}(C^2 - 1)\beta_2^{(t-1) \bmod d} + 1}}. \tag{10}$$

And there exists $1 \leq j \leq d$ such that

$$\lim_{n \to \infty} k(C) = \lim_{n \to \infty} k(g_{nd+1}) < \lim_{n \to \infty} k(g_{nd+2}) < \cdots < \lim_{n \to \infty} k(g_{nd+j}), \tag{11}$$

and

$$\lim_{n \to \infty} k(g_{nd+j}) > \lim_{n \to \infty} k(g_{nd+j+1}) > \cdots > \lim_{n \to \infty} k(g_{nd+d+1}) = \lim_{n \to \infty} k(C), \tag{12}$$

where $k(C)$ denotes the net update factor for gradient $g_i = C$.

Theorem 3 tells us that, in sequential online optimization problem in Equation 6, the net update factors are unbalanced. Specifically, the net update factor for the large gradient C is the smallest in the entire epoch, while all gradients -1 have larger net update factors. Such unbalanced net update factors will possibly lead Adam to a wrong accumulated update direction.

3.3 ANALYSIS ON STOCHASTIC ONLINE OPTIMIZATION COUNTEREXAMPLES

The counterexamples are also extended to stochastic cases in Reddi et al. (2018), where a finite set of cost functions appear in a stochastic order. Compared with sequential online optimization counterexample, the stochastic version is more general and closer to the practical situation. For the simplest one dimensional case, at each timestep t, the function $f_t(\theta)$ is chosen as i.i.d.:

$$f_t(\theta) = \begin{cases} C\theta, & \text{with probability } p = \frac{1+\delta}{C+1}; \\ -\theta, & \text{with probability } 1 - p = \frac{C-\delta}{C+1}, \end{cases} \tag{13}$$

where δ is a small positive constant that is smaller than C. The expected cost function of the above problem is $F(\theta) = \frac{1+\delta}{C+1}C\theta - \frac{C-\delta}{C+1}\theta = \delta\theta$, therefore, one should decrease θ to minimize the loss. Reddi et al. (2018) prove that when C is large enough, the expectation of accumulated parameter update in Adam is positive and results in increasing θ.

To conduct more rigorous study on the stochastic online optimization problem in Equation 13, we derive the expectation of the net update factor for each gradient in the following theorem:

Theorem 4 (Unbalanced net update factor in stochastic online optimization problem). In the stochastic online optimization problem in Equation 13, assuming $\alpha_t = 1$, the expectation of net update factors are as follows:

$$k(C) = \sum_{t=0}^{\infty}(1-\beta_1)\beta_1^t \left[\frac{1}{\sqrt{(1-\beta_2)\beta_2^t C^2+(1+\beta_2^{t+1}-\beta_2^k)\mathbb{E}[g_i^2]}} + \frac{D_t}{8[(1-\beta_2)\beta_2^t C^2+(1+\beta_2^{t+1}-\beta_2^t)\mathbb{E}[g_i^2]]^{\frac{5}{2}}} \right], \quad (14)$$

and

$$k(-1) = \sum_{t=0}^{\infty}(1-\beta_1)\beta_1^t \left[\frac{1}{\sqrt{(1-\beta_2)\beta_2^t+(1+\beta_2^{t+1}-\beta_2^k)\mathbb{E}[g_i^2]}} + \frac{D_t}{8[(1-\beta_2)\beta_2^t+(1+\beta_2^{t+1}-\beta_2^t)\mathbb{E}[g_i^2]]^{\frac{5}{2}}} \right], \quad (15)$$

where $k(C)$ denotes the net update factor for $g_i = C$ and $k(-1)$ denotes the net update factor for $g_i = -1$. D_t is a positive value.

Though the formulas of net update factors in the stochastic case are more complicated than those in deterministic case, the analysis is actually more easier: the gradients with the same scale share the same expected net update factor, so we only need to analyze $k(C)$ and $k(-1)$. We can see that each term in the infinite series of $k(C)$ is smaller than the corresponding one in $k(-1)$, therefore, the accumulated influence of gradient C is smaller than gradient -1.

The above observation can also be interpreted as a direct consequence of the inappropriate correlation between v_t and g_t: given $v_t = \beta_2 v_{t-1} + (1 - \beta_2)g_t^2$, not only v_t positively correlates with g_t, but also the entire infinite sequence $\{v_i\}_{i=t}^{\infty}$ positively correlates with g_t. Since the net update factor $k(g_t) = \sum_{i=t}^{\infty} \alpha_i/\sqrt{v_i}(1-\beta_1)\beta_1^{i-t}$ negatively correlates with each v_i in $\{v_i\}_{i=t}^{\infty}$, it also negatively correlates with g_t. That is, $k(g_t)$ for a large gradient is likely to be smaller, while $k(g_t)$ for a small gradient is likely to be larger.

The unbalanced net update factor causes the non-convergence problem of Adam as well as all other adaptive learning rate methods where v_t correlates with g_t. All these counterexamples follow the same pattern: the large gradient is along the "correct" direction, while the small gradient is along the opposite direction. Due to the fact that the accumulated influence of a large gradient is small while the accumulated influence of a small gradient is large, Adam may update parameters along the wrong direction. Even if Adam updates parameters along the right direction in general, the unbalanced net update factors are still unfavorable since they slow down the convergence.

4 THE PROPOSED METHOD: DECORRELATION VIA TEMPORAL SHIFTING

According to the previous discussion, we conclude that the main cause of the non-convergence of Adam is the inappropriate correlation between v_t and g_t. Currently we have two possible solutions: (1) making v_t act like a constant, which declines the correlation, e.g., using a large β_2 or keep v_t non-decreasing (Reddi et al., 2018); (2) using a large β_1 (Theorem 1), where the aggressive momentum term helps to mitigate the impact of unbalanced net update factors. However, neither of them solves the problem fundamentally.

The dilemma caused by v_t enforces us to rethink its role. In adaptive learning rate methods, v_t plays the role of estimating the second moments of gradients, which reflects the scale of gradient on average. With the adaptive learning rate $\alpha_t/\sqrt{v_t}$, the update step of g_t is scaled down by $\sqrt{v_t}$ and achieves rescaling invariance with respect to the scale of g_t, which is practically useful to make the training process easy to control and the training system robust. However, the current scheme of v_t, i.e., $v_t = \beta_2 v_{t-1} + (1 - \beta_2)g_t^2$, brings a positive correlation between v_t and g_t, which results in reducing the effect of large gradients and increasing the effect of small gradients, and finally causes the non-convergence problem. Therefore, the key is to let v_t be a quantity that reflects the scale of the gradients, while at the same time, be decorrelated with current gradient g_t. Formally, we have the following theorem:

Theorem 5 (Decorrelation leads to convergence). For any fixed online optimization problem with infinitely repeating of a finite set of cost functions $\{f_1(\theta), \ldots, f_t(\theta), \ldots f_n(\theta)\}$, assuming $\beta_1 = 0$ and α_t is fixed, we have, if v_t follows a fixed distribution and is independent of the current gradient g_t, then the expected net update factor for each gradient is identical.

Let P_v denote the distribution of v_t. In the infinitely repeating online optimization scheme, the expectation of net update factor for each gradient g_t is

$$\mathbb{E}[k(g_t)] = \sum_{i=t}^{\infty} \mathbb{E}_{v_i \sim P_v} \left[\frac{\alpha_i}{\sqrt{v_i}} (1 - \beta_1) \beta_1^{i-t} \right]. \tag{16}$$

Given P_v is independent of g_t, the expectation of the net update factor $\mathbb{E}[k(g_t)]$ is independent of g_t and remains the same for different gradients. With the expected net update factor being a fixed constant, the convergence of the adaptive learning rate method reduces to vanilla SGD.

Momentum (Qian, 1999) can be viewed as setting v_t as a constant, which makes v_t and g_t independent. Furthermore, in our view, using an increasing β_2 (AdamNC) or keeping $\hat{v}_t$ as the largest v_t (AMSGrad) is also to make v_t almost fixed. However, fixing v_t is not a desirable solution, because it damages the adaptability of Adam with respect to the adapting of step size.

We will next introduce the proposed solution to make v_t independent of g_t, which is based on temporal independent assumption among gradients. The proposed solution decorrelates v_t and g_t with a simple temporal shifting.

4.1 TEMPORAL DECORRELATION

In practical setting, $f_t(\theta)$ usually involves different mini-batches x_t, i.e., $f_t(\theta) = f(\theta; x_t)$. Given the randomness of mini-batch, we assume that the mini-batch x_t is independent of each other and further assume that $f(\theta; x)$ keeps unchanged over time, then the gradient $g_t = \nabla f(\theta; x_t)$ of each mini-batch is independent of each other. Then we present the temporal decorrelation algorithm as follows.

Algorithm 1 Temporal Decorrelation

Input: $\theta_0, g_0, \{f_t(\theta)\}_{t=1}^T, \{\alpha_t\}_{t=1}^T$ and β_2
1: set $v_0 = 0$
2: **for** $t = 1$ **to** T **do**
3:      $g_t = \nabla f_t(\theta_t)$
4:      $v_t = \beta_2 v_{t-1} + (1 - \beta_2) g_{t-1}^2$
5:      $\theta_t = \theta_{t-1} - \alpha_t / \sqrt{v_t} \cdot g_t$
6: **end for**
7: // we ignore the bias-correction and epsilon for the sake of clarity

---

The key change is that the update rule for v_t now involves g_{t-1} instead of g_t (line 4), which makes v_t and g_t temporally shifted and hence decorrelated. Note that in the sequential online optimization problem, the assumption "g_t is independent of each other" does not hold. However, in the stochastic online optimization problem and practical neural network settings, our assumption generally holds.

4.2 TEMPORAL-SPATIAL DECORRELATION

In most optimization schemes, there exists many parameters, i.e., the dimension of θ is high, thus g_t and v_t are also of high dimension. However, in Algorithm 1, v_t is element-wisely computed; that is, we only use the i-th dimension of g_{t-1} to calculate i-th dimension of v_t. In other words, it only makes use of the independence between $g_{t-1}[i]$ and $g_t[i]$, where $g_t[i]$ denotes the i-th element of g_t.

Actually, in the case of high-dimensional g_t and v_t, we can further assume that all elements of gradient g_{t-1} at previous timestep are independent of the i-th dimension of g_t. Thus all elements in g_{t-1} can be used to compute v_t without introducing correlation. We propose introducing a function ϕ over all elements of g_{t-1} to achieve this goal, i.e., $v_t = \beta_2 v_{t-1} + (1 - \beta_2)[\phi(g_{t-1})]^2$. For easy of reference, we name the elements of g_{t-1} other than $g_{t-1}[i]$ as the spatial elements of g_{t-1} and name ϕ the spatial function or spatial operation.

There is no restriction on the choice of ϕ, and we use $\phi(x) = \max_i x[i]$ for most of our experiments, which is shown to be a good choice. The $\max_i x[i]$ operation has a side effect that turns the adaptive learning rate v_t into a shared scalar. An important thing here is that, we no longer interpret v_t as the

second moment of g_t. It is merely a random variable that is independent of g_t, while at the same time, reflects the overall gradient scale. We leave further investigations on ϕ as future work.

Algorithm 2 Block-wise Temporal-Spatial Decorrelation

Input: θ_0, g_0, $\{f_t(\theta)\}_{t=1}^T$, $\{\alpha_t\}_{t=1}^T$ and β_2
 1: set $v_0 = 0$
 2: **for** $t = 1$ **to** T **do**
 3:     $g_t = \nabla f_t(\theta_t)$
 4:     **for** $i = 1$ **to** M **do**
 5:         $v_t[i] = \beta_2 v_{t-1}[i] + (1 - \beta_2)[\phi(g_{t-1}[i])]^2$
 6:         $\theta_t[i] = \theta_{t-1}[i] - \alpha_t / \sqrt{v_t[i]} \cdot g_t[i]$
 7:     **end for**
 8: **end for**
 9: // if $v_t[i]$ outputs a scalar, it turns out to be "block-wise adaptive learning rate SGD"

4.3 BLOCK-WISE TEMPORAL-SPATIAL DECORRELATION

In practical setting, e.g., deep neural network, θ usually consists of many parameter blocks, e.g., the weight and bias for each layer. In deep neural network, the gradient scales (i.e., the variance) for different layers tend to be different (Glorot & Bengio, 2010; He et al., 2015). Different gradient scales make it hard to find a learning rate that is suitable for all layers, when using SGD and Momentum methods. In traditional adaptive learning rate methods, they apply element-wise rescaling for each gradient dimension, which achieves rescaling-invariance and somehow solves the above problem. However, Adam sometimes does not generalize better than SGD (Wilson et al., 2017; Keskar & Socher, 2017), which might relate to the excessive learning rate adaptation in Adam.

In our temporal-spatial decorrelation scheme, we can solve the "different gradient scales" issue more naturally, by applying ϕ block-wisely and outputs a shared adaptive learning rate scalar $v_t[i]$ for each block. It makes the algorithm work like an adaptive learning rate SGD, where each block has an adaptive learning rate $\alpha_t / \sqrt{v_t[i]}$ while the relative gradient scale among in-block elements keep unchanged. The corresponding algorithm is illustrated in Algorithm 2, where the parameters θ_t including the related g_t and v_t are divided into M blocks. Every block contains the parameters of the same type or same layer in neural network.

4.4 INCORPORATING FIRST MOMENT: MOVING AVERAGING WINDOWS

First moment estimation, i.e., defining m_t as a moving average of g_t, is an important technique of modern first order optimization algorithms, which alleviates mini-batch oscillations. In this section, we extend our algorithm to incorporate first moment estimation.

We have argued that v_t needs to be decorrelated with g_t. Similarly, when introducing the first moment estimation, we need to make v_t and m_t independent to make the expected net update factor unbiased. Based on our assumption of temporal and spatial independence, we further keep out the latest n gradients $\{g_{t-i}\}_{i=0}^{n-1}$, and update v_t and m_t via

$$v_t = \beta_2 v_{t-1} + (1 - \beta_2)[\phi(g_{t-n})]^2 \quad \text{and} \quad m_t = \frac{\sum_{i=0}^{n-1} \beta_1^i g_{t-i}}{\sum_{i=0}^{N-1} \beta_1^i}. \tag{17}$$

In Equation 17, $\beta_1 \in [0, 1]$ plays the role of decay rate for temporal elements. It can be viewed as a truncated version of exponential moving average that only applied to the latest few elements. Since we use truncating, it is feasible to use large β_1 without taking the risk of using too old gradients. In the extreme case where $\beta_1 = 1$, it becomes vanilla averaging.

The pseudo code of the algorithm that unifies all proposed techniques is presented in the Appendix with the following parameters: spatial operation ϕ, $n \in \mathbb{N}^+$, $\beta_1 \in [0, 1]$, $\beta_2 \in [0, 1)$ and α_t.

Summary The key difference between Adam and the proposed method is that the latter temporally shifts the gradient g_t for n-step, i.e., using g_{t-n} for calculating v_t and using the kept-out n gradients

to evaluate m_t (Equation 17), which makes v_t and m_t decorrelated and consequently solves the non-convergence issue. In addition, based on our new perspective on adaptive learning rate methods, v_t is not necessarily the second moment and it is valid to further involve the calculation of v_t with the spatial elements of previous gradients. And we found that when the spatial operation ϕ outputs a shared scalar for each block, the resulting algorithm turns out to be closely related to SGD, where each block has an overall adaptive learning rate and the relative gradient scale in each block is maintained. This is what we call "block-wise adaptive learning rate SGD". We name the proposed method that makes use of temporal-shifting to decorrelated v_t and m_t **AdaShift**, which means "ADAptive learning rate method with temporal SHIFTing".

5 EXPERIMENTS

In this section, we empirically study the proposed method and compare them with Adam, AMSGrad and SGD, on various tasks in terms of training performance and generalization. Without additional declaration, the reported result for each algorithm is the best we have found via parameter grid search. The anonymous code is provided at http://bit.ly/2NDXX6x.

5.1 ONLINE OPTIMIZATION COUNTEREXAMPLES

Firstly, we verify our analysis on the stochastic online optimization problem in Equation 13, where we set $C = 101$ and $\delta = 0.02$. We compare Adam, AMSGrad and AdaShift in this experiment. For fair comparison, we set $\alpha = 0.001$, $\beta_1 = 0$ and $\beta_2 = 0.999$ for all these methods. The results are shown in Figure 1a. We can see that Adam tends to increase θ, that is, the accumulate update of θ in Adam is along the wrong direction, while AMSGrad and AdaShift update θ in the correct direction. Furthermore, given the same learning rate, AdaShift decreases θ faster than AMSGrad, which validates our argument that AMSGrad has a relatively higher v_t that slows down the training. In this experiment, we also verify Theorem 1. As shown in Figure 1b, Adam is also able to converge to the correct direction with a sufficiently large β_1 and β_2. Note that (1) AdaShift still converges with the fastest speed; (2) a small β_1 (e.g., $\beta_1 = 0.9$, the light-blue line in Figure 1b) does not make Adam converge to the correct direction. We do not conduct the experiments on the sequential online optimization problem in Equation 6, because it does not fit our temporal independence assumption. To make it converge, one can use a large β_1 or β_2, or set v_t as a constant.

(a) Comparison of Adam, AMSGrad and AdaShift. (b) Adam and Adam with large β_1 and β_2.

Figure 1: Experiments on stochastic counterexample.

5.2 LOGISTIC REGRESSION AND MULTILAYER PERCEPTRON ON MNIST

We further compare the proposed method with Adam, AMSGrad and SGD by using Logistic Regression and Multilayer Perceptron on MNIST, where the Multilayer Perceptron has two hidden layers and each has 256 hidden units with no internal activation. The results are shown in Figure 2 and Figure 3, respectively. We find that in Logistic Regression, these learning algorithms achieve very similar final results in terms of both training speed and generalization. In Multilayer Perceptron, we compare Adam, AMSGrad and AdaShift with reduce-max spatial operation (max-AdaShift) and without spatial operation (non-AdaShift). We observe that max-AdaShift achieves the lowest training loss, while non-AdaShift has mild training loss oscillation and at the same time achieves better

generalization. The worse generalization of max-AdaShift may be due to overfitting in this task, and the better generalization of non-AdaShift may stem from the regularization effect of its relatively unstable step size.

(a) Training loss (b) Test accuracy
Figure 2: Logistic Regression on MNIST.

(a) Training loss (b) Test accuracy
Figure 3: Multilayer Perceptron on MNIST.

5.3 DENSENET AND RESNET ON CIFAR-10

ResNet (He et al., 2016) and DenseNet (Huang et al., 2017) are two typical modern neural networks, which are efficient and widely-used. We test our algorithm with ResNet and DenseNet on CIFAR-10 datasets. We use a 18-layer ResNet and 100-layer DenseNet in our experiments. We plot the best results of Adam, AMSGrad and AdaShift in Figure 4 and Figure 5 for ResNet and DenseNet, respectively. We can see that AMSGrad is relatively worse in terms of both training speed and generalization. Adam and AdaShift share competitive results, while AdaShift is generally slightly better, especially the test accuracy of ResNet and the training loss of DenseNet.

Figure 4: ResNet on Cifar-10. Left: Training Loss. Right: Test Accuracy.

Figure 5: DenseNet on Cifar-10. Left: Training Loss. Right: Test Accuracy.

5.4 DENSENET WITH TINY-IMAGENET

We further increase the complexity of dataset, switching from CIFAR-10 to Tiny-ImageNet, and compare the performance of Adam, AMSGrad and AdaShift with DenseNet. The results are shown in Figure 6, from which we can see that the training curves of Adam and AdaShift are basically overlapped, but AdaShift achieves higher test accuracy than Adam. AMSGrad has relatively higher training loss, and its test accuracy is relatively lower at the initial stage.

Figure 6: DenseNet on Tiny-ImageNet. Left: Training Loss. Right: Test Accuracy.

5.5 GENERATIVE MODEL AND RECURRENT MODEL

We also test our algorithm on the training of generative model and recurrent model. We choose WGAN-GP (Gulrajani et al., 2017) that involves Lipschitz continuity condition (which is hard to optimize), and Neural Machine Translation (NMT) (Luong et al., 2017) that involves typical recurrent unit LSTM, respectively. In Figure 7a, we compare the performance of Adam, AMSGrad and AdaShift in the training of WGAN-GP discriminator, given a fixed generator. We notice that AdaShift is significantly better than Adam, while the performance of AMSGrad is relatively unsatisfactory. The test performance in terms of BLEU of NMT is shown in Figure 7b, where AdaShift achieves a higher BLEU than Adam and AMSGrad.

(a) Training WGAN Discriminator. (b) Neural Machine Translation BLEU.

Figure 7: Generative and Recurrent model.

6 CONCLUSION

In this paper, we study the non-convergence issue of adaptive learning rate methods from the perspective of the equivalent accumulated step size of each gradient, i.e., the net update factor defined in this paper. We show that there exists an inappropriate correlation between v_t and g_t, which leads to unbalanced net update factor for each gradient. We demonstrate that such unbalanced step sizes are the fundamental cause of non-convergence of Adam, and we further prove that decorrelating v_t and g_t will lead to unbiased expected step size for each gradient, thus solving the non-convergence problem of Adam. Finally, we propose AdaShift, a novel adaptive learning rate method that decorrelates v_t and g_t via calculating v_t using temporally shifted gradient g_{t-n}.

In addition, based on our new perspective on adaptive learning rate methods, v_t is no longer necessarily the second moment of g_t, but a random variable that is independent of g_t and reflects the overall gradient scale. Thus, it is valid to calculate v_t with the spatial elements of previous gradients. We further found that when the spatial operation ϕ outputs a shared scalar for each block, the resulting algorithm turns out to be closely related to SGD, where each block has an overall adaptive learning rate and the relative gradient scale in each block is maintained. The experiment results demonstrate that AdaShift is able to solve the non-convergence issue of Adam. In the meantime, AdaShift achieves competitive and even better training and testing performance when compared with Adam.

REFERENCES

Timothy Dozat. Incorporating nesterov momentum into adam. 2016.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256, 2010.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In *Advances in Neural Information Processing Systems*, pp. 5767–5777, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. 2017.

Nitish Shirish Keskar and Richard Socher. Improving generalization performance by switching from adam to sgd. *arXiv preprint arXiv:1712.07628*, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Minh-Thang Luong, Eugene Brevdo, and Rui Zhao. Neural machine translation (seq2seq) tutorial. *https://github.com/tensorflow/nmt*, 2017.

Ning Qian. On the momentum term in gradient descent learning algorithms. *Neural networks*, 12 (1):145–151, 1999.

Sashank J. Reddi, Satyen Kale, and Sanjiv Kumar. On the convergence of adam and beyond. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=ryQu7f-RZ.

Tijmen Tieleman and Geoffrey Hinton. Lecture 6.5-rmsprop: Divide the gradient by a running average of its recent magnitude. *COURSERA: Neural networks for machine learning*, 4(2):26–31, 2012.

Ashia C Wilson, Rebecca Roelofs, Mitchell Stern, Nati Srebro, and Benjamin Recht. The marginal value of adaptive gradient methods in machine learning. In *Advances in Neural Information Processing Systems*, pp. 4148–4158, 2017.

Matthew D Zeiler. Adadelta: an adaptive learning rate method. *arXiv preprint arXiv:1212.5701*, 2012.

(a) Final result of θ for sequential problem after 2000 updates, varied with β_1 and β_2.

(b) Critical value of C with varying β_1 and β_2 under the sequential optimization setting.

(c) Final result of θ for stochastic problem after 2000 updates, varied with β_1 and β_2.

(d) Critical value of C with varying β_1 and β_2 under the stochastic optimization setting.

Figure 8: Both β_1 and β_2 influence the direction and speed of optimization in Adam. Critical value of C_t, at which Adam gets into non-convergence, increases as β_1 and β_2 getting large. Leftmost two for the sequential online optimization problem and rightmost two for stochastic online problem.

A THE RELATION AMONG β_1, β_2 AND C

To provide an intuitive impression on the relation among C, d, β_1, β_2 and the convergence of Adam, we let $C = d = 6$, initialize $\theta_1 = 0$, vary β_1 and β_2 among $[0, 1)$ and let Adam go through 2000 timesteps (iterations). The final result of θ is shown in Figure 8a. It suggests that for a fixed sequential online optimization problem, both of β_1 and β_2 determine the direction and speed of Adam optimization process. Furthermore, we also study the threshold point of C and d, under which Adam will change to the incorrect direction, for each fixed β_1 and β_2 that vary among $[0, 1)$. To simplify the experiments, we keep $d = C$ such that the overall gradient of each epoch being $+1$. The result is shown in Figure 8b, which suggests, at the condition of larger β_1 or larger β_2, it needs a larger C to make Adam stride on the opposite direction. In other words, large β_1 and β_2 will make the non-convergence rare to happen.

We also conduct the experiment in the stochastic problem to analyze the relation among C, β_1, β_2 and the convergence behavior of Adam. Results are shown in the Figure 8c and Figure 8d and the observations are similar to the previous: larger C will cause non-convergence more easily and a larger β_1 or β_2 somehow help to resolve non-convergence issue. In this experiment, we set $\delta = 1$.

Theorem 6 (Critical condition). In the sequential online optimization problem Equation 6, let α_t being fixed, define $\mathcal{S}(\beta_1, \beta_2, C, d)$ to be the sum of the limits of step updates in a d-step epoch:

$$\mathcal{S}(\beta_1, \beta_2, C) \triangleq \sum_{i=1}^{d} \lim_{nd \to \infty} \frac{m_{nd+i}}{\sqrt{v_{nd+i}}} \,. \tag{18}$$

Let $\mathcal{S}(\beta_1, \beta_2, C) = 0$, assuming β_2 and C are large enough such that $v_t \gg 1$, we get the equation:

$$C + 1 = \frac{(1 - \beta_1^d)(\sqrt{\beta_2^d} - \beta_1^d)(1 - \sqrt{\beta_2})}{(1 - \beta_1)(\sqrt{\beta_2} - \beta_1)(1 - \sqrt{\beta_2^d})} \,. \tag{19}$$

Equation 19, though being quite complex, tells that both β_1 and β_2 are closely related to the counterexamples, and there exists a critical condition among these parameters.

B THE ADASHIFT PSEUDO CODE

Algorithm 3 AdaShift: This algorithm incorporate the moving average window of gradients to the algorithm 2 and unify all proposed techniques. We use a queue Q to denote the average window with the length of n. $Push(Q, g_t)$ denotes pushing vector g_t to the tail of Q, while $Pop(Q)$ pops and returns the head vector of Q. And W is the weight vector calculated via β_1

Input: $\theta_0, \{f_t(\theta)\}_{t=1}^T, \{\alpha_t\}_{t=1}^T, \beta_1, \beta_2, n$ and ϕ
1: set $v_0 = 0$
2: $W = [\beta_1^{n-1}, \beta_1^{n-2}, \ldots, \beta_1, 1]/\sum_{i=0}^{n-1} \beta_1^n$
3: **for** $t = 1$ **to** T **do**
4: $\quad g_t = \nabla f_t(\theta_t)$
5: $\quad Push(Q, g_t)$
6: $\quad$ **if** $t > n$ **then**
7: $\quad\quad g_{t-n} = Pop(Q)$
8: $\quad\quad m_t = W \cdot Q$
9: $\quad\quad$ **for** $i = 1$ **to** M **do**
10: $\quad\quad\quad v_t[i] = \beta_2 v_{t-1}[i] + (1 - \beta_2)[\phi(g_{t-n}[i])]^2$
11: $\quad\quad\quad \theta_t[i] = \theta_{t-1}[i] - \alpha_t/\sqrt{v_t[i]} \cdot m_t[i]$
12: $\quad\quad$ **end for**
13: $\quad$ **end if**
14: **end for**

C CORRELATION BETWEEN g_t AND v_t

In order to verify the correlation between g_t and v_t in Adam and AdaShift, we conduct experiments to calculate the correlation coefficient between g_t and v_t. We train the Multilayer Perceptron on MNIST until converge and gather the gradient of the second hidden layer of each step. Based on these data, we calculate v_t and the correlation coefficient between $g_t[i]$ and $g_{t-n}[i]$, between $g_t[i]$ and $g_{t-n}[j]$ and between $g_t[i]$ and $v_t[i]$ of the last 10 epochs using the Pearson correlation coefficient, which is formulated as follows:

$$\rho = \frac{\sum_{i=1}^n (X_i - \bar{X})(Y_i - \bar{Y})}{\sqrt{\sum_{i=1}^n (X_i - \bar{X})^2}\sqrt{\sum_{i=1}^n (Y_i - \bar{Y})^2}}.$$

To verify the temporal correlation between $g_t[i]$ and $g_{t-n}[i]$, we range n from 1 to 10 and calculate the average temporal correlation coefficient of all variables i. Results are shown in Table 1.

Table 1: Temporal correlation coefficient between $g_t[i]$ and $g_{t-n}[i]$.

n	1	2	3	4	5
ρ	-0.000368929	-0.000989286	-0.001540511	-0.00116966	-0.001613395
n	6	7	8	9	10
ρ	-0.001211721	0.000357474	-0.00082293	-0.001755237	-0.001267641

To verify the spatial correlation between $g_t[i]$ and $g_{t-n}[j]$, we again range n from 1 to 10 and randomly sample some pairs of i and j and calculate the average spatial correlation coefficient of all the selected pairs. Results are shown in Table 2.

Table 2: Spatial correlation coefficient between $g_t[i]$ and $g_{t-n}[j]$.

n	1	2	3	4	5
ρ	-0.000609471	-0.001948853	-0.001426661	0.000904615	0.000329359
n	6	7	8	9	10
ρ	0.000971337	-0.000644563	-0.00137805	-0.001147973	-0.000592037

To verify the correlation between $g_t[i]$ and $v_t[i]$ within Adam, we calculate v_t and the average correlation coefficient between g_t^2 and v_t of all variables i. The result is **0.435885276**.

To verify the correlation between $g_{t-n}[i]$ and $v_t[i]$ within non-AdaShift and between $g_{t-n}[i]$ and v_t within max-AdaShift, we range the keep number n from 1 to 10 to calculate v_t and the average correlation coefficient of all variables i. The result is shown in Table 3 and Table 4.

Table 3: Correlation coefficient between $g_{t-n}^2[i]$ and $v_t[i]$ in non-AdaShift.

n	1	2	3	4	5
ρ	-0.010897023	-0.010952548	-0.010890854	-0.010853069	-0.010810747
n	6	7	8	9	10
ρ	-0.010777789	-0.01075946	-0.010739279	-0.010728553	-0.010720019

Table 4: Correlation coefficient between $g_{t-n}^2[i]$ and v_t in max-AdaShift.

n	1	2	3	4	5
ρ	-0.000706289	-0.000794959	-0.00076306	-0.000712474	-0.000668459
n	6	7	8	9	10
ρ	-0.000623162	-0.000566573	-0.000542046	-0.000598015	-0.000592707

D   PROOF OF THEOREM 1

Proof.

With bias correction, the formulation of m_t is written as follows

$$m_t = \frac{(1-\beta_1)\sum_{i=1}^t \beta_1^{t-i} g_i}{(1-\beta_1)\sum_{i=1}^t \beta_1^{t-i}} = \frac{\sum_{i=1}^t \beta_1^{t-i} g_i}{\sum_{i=1}^t \beta_1^{t-i}}. \tag{20}$$

According to L'Hospitals rule, we can draw the following:

$$\lim_{\beta_1 \to 1} \sum_{i=1}^t \beta_1^{t-i} = \lim_{\beta_1 \to 1} \frac{1-\beta_1^t}{1-\beta_1} = t.$$

Thus,

$$\lim_{\beta_1 \to 1} m_t = \frac{\sum_{i=1}^t g_i}{t}.$$

According to the definition of limitation, let $g^* = \frac{\sum_{i=1}^t g_i}{t}$, we have, $\forall \epsilon > 0, \exists \beta_1 \in (0,1)$, such that

$$\|m_t - g^*\|_\infty < \epsilon.$$

We set ϵ to be $|\frac{g^*}{2}|$, then for each dimension of m_t, i.e. $m_t[i]$,

$$\frac{g^*[i]}{2} \le m_t[i] \le \frac{3g^*[i]}{2}$$

So, m_t shares the same sign with g^* in every dimension.

Given it is a convex optimization problem, let the optimal parameter be θ^*, and the maximum step size is $\frac{\alpha_t}{\sqrt{v_t}}G$ that holds $\epsilon_1/dG < \frac{\alpha_t}{\sqrt{v_t}}G < \epsilon_2/dG$, we have,

$$\lim_{t \to \infty} \|\theta_t - \theta^*\|_\infty < \epsilon_2/dG. \tag{21}$$

Given $\|\nabla f_t(\theta)\|_\infty \le G$, we have $f_t(\theta) - f_t(\theta^*) < \epsilon_2/d < \epsilon_2$, which implies the average regret

$$R(T)/T = \sum_{t=1}^T [f_t(\theta_t) - f_t(\theta^*)]/T < \epsilon_2. \tag{22}$$

$\square$

E   PROOF OF THEOREM 2

Proof. Let $\beta_1, \beta_2 \in [0, 1)$, $d \in \mathbb{N}$, $1 \le i \le d$ and $i \in \mathbb{N}$.

$$
\begin{aligned}
m_{nd+i} &= (1 - \beta_1) \sum_{j=1}^{nd+i} \beta_1^{nd+i-j} g_j \\
&= (1 - \beta_1) \left[(C+1) \sum_{j=0}^{n} \beta_1^{jd+i-1} - \sum_{j=0}^{nd+i-1} \beta_1^j \right] \\
&= (1 - \beta_1) \left[\frac{1 - \beta_1^{(n+1)d}}{1 - \beta_1^d} \beta_1^{i-1}(C+1) - \frac{1 - \beta_1^{nd+i}}{1 - \beta_1} \right] \\
&= \frac{1 - \beta_1^{(n+1)d}}{1 - \beta_1^d}(1 - \beta_1)\beta_1^{i-1}(C+1) - (1 - \beta_1^{nd+i})
\end{aligned}
$$

For a fixed d, as n approach infinity, we get the limit of m_{nd+i} as:

$$
\lim_{nd \to \infty} m_{nd+i} = \frac{1 - \beta_1}{1 - \beta_1^d}(C+1)\beta_1^{i-1} - 1
$$

Similarly, for v_{nd+i}:

$$
\begin{aligned}
v_{nd+i} &= (1 - \beta_2) \sum_{j=1}^{nd+i} \beta_2^{nd+i-j} g_j^2 \\
&= (1 - \beta_2) \left[(C^2 - 1) \sum_{j=0}^{n} \beta_2^{jd+i-1} + \sum_{j=0}^{nd+i-1} \beta_2^j \right] \\
&= (1 - \beta_2) \left[\frac{1 - \beta_2^{(n+1)d}}{1 - \beta_2^d} \beta_2^{i-1}(C^2-1) + \frac{1 - \beta_2^{nd+i}}{1 - \beta_2} \right] \\
&= \frac{1 - \beta_2^{(n+1)d}}{1 - \beta_2^d}(1 - \beta_2)\beta_2^{i-1}(C+1) - (1 - \beta_2^{nd+i})
\end{aligned}
$$

For a fixed d, as n approach infinity, we get the limit of v_{nd+i} as:

$$
\lim_{nd \to \infty} v_{nd+i} = \frac{1 - \beta_2}{1 - \beta_2^d}(C^2 - 1)\beta_2^{i-1} + 1 \ .
$$

$\square$

F   PROOF OF THEOREM 6

Proof. From theorem 2, we can get:

$$
\lim_{nd \to \infty} \frac{m_{nd+i}}{\sqrt{v_{nd+i}}} = \frac{\frac{1-\beta_1}{1-\beta_1^d}(C+1)\beta_1^{i-1} - 1}{\sqrt{\frac{1-\beta_2}{1-\beta_2^d}(C^2-1)\beta_2^{i-1} + 1}}
$$

We sum up all updates in an epoch, and define the summation as $\mathcal{S}(\beta_1, \beta_2, C)$.

$$
\mathcal{S}(\beta_1, \beta_2, C) = \sum_{i=1}^{d} \lim_{nd \to \infty} \frac{m_{nd+i}}{\sqrt{v_{nd+i}}}
$$

Assume β_2 and C are large enough such that $v_t \gg 1$, we get the approximation of limit of v_{nd+i} as:

$$\lim_{nd \to \infty} v_{nd+i} \approx \frac{1 - \beta_2}{1 - \beta_2^d}(C^2 - 1)\beta_2^{i-1}$$

Then we can draw the expression of $\mathcal{S}(\beta_1, \beta_2, C)$ as:

$$
\begin{aligned}
\mathcal{S}(\beta_1, \beta_2, C) &= \sum_{i=1}^{d} \frac{\frac{1-\beta_1}{1-\beta_2^d}(C+1)\beta_1^{i-1} - 1}{\sqrt{\frac{1-\beta_2}{1-\beta_2^d}(C^2-1)\beta_2^{i-1}}} \\
&= \sum_{i=1}^{d} \frac{\frac{1-\beta_1}{1-\beta_1^d}(C+1)\beta_1^{i-1}}{\sqrt{\frac{1-\beta_2}{1-\beta_2^d}(C^2-1)\beta_2^{i-1}}} - \sum_{i=1}^{d} \frac{1}{\sqrt{\frac{1-\beta_2}{1-\beta_2^d}(C^2-1)\beta_2^{i-1}}} \\
&= \sqrt{\frac{1-\beta_2^d}{(1-\beta_2)\beta_2^{d-1}}}\sqrt{\frac{C+1}{C-1}} \cdot \frac{1-\beta_1}{1-\beta_1^d} \cdot \frac{\sqrt{\beta_2^d} - \beta_1^d}{\sqrt{\beta_2} - \beta_1} - \sqrt{\frac{1-\beta_2^d}{(1-\beta_2)\beta_2^{d-1}}} \cdot \frac{1}{\sqrt{C^2-1}} \frac{\sqrt{\beta_2^d} - 1}{\sqrt{\beta_2} - 1} \\
&= \sqrt{\frac{1-\beta_2^d}{(1-\beta_2)\beta_2^{d-1}(C-1)}}\left[\frac{(1-\beta_1)(\beta_2^d - \beta_1^d)\sqrt{C+1}}{(1-\beta_1^d)(\sqrt{\beta_2} - \beta_1)} - \frac{\sqrt{\beta_2^d} - 1}{\sqrt{C+1}(\sqrt{\beta_2} - 1)}\right]
\end{aligned}
$$

Let $\mathcal{S}(\beta_1, \beta_2, C) = 0$, we get the equation about critical condition:

$$C + 1 = \frac{(1 - \beta_1^d)(\sqrt{\beta_2^d} - \beta_1^d)(1 - \sqrt{\beta_2})}{(1 - \beta_1)(\sqrt{\beta_2} - \beta_1)(1 - \sqrt{\beta_2^d})}$$

$\square$

G PROOF OF THEOREM 3

Proof. First, we define $\widetilde{V}_i$ as:

$$\widetilde{V}_i = \lim_{nd \to \infty} \frac{1}{\sqrt{v_{nd+i}}} = \frac{1}{\sqrt{\frac{1-\beta_2}{1-\beta_2^d}(C^2 - 1)\beta_2^{(i-1)} + 1}}$$

where $1 \le i \le d$ and $i \in \mathbb{N}$. And $\widetilde{V}_i$ has a period of d. Let $t' = t - nd$, then we can draw:

$$
\lim_{nd\to\infty} k(g_{nd+i}) = \sum_{t=nd+i}^{\infty} \frac{(1-\beta_1)\beta_1^{t-nd-i}}{\sqrt{\frac{1-\beta_2}{1-\beta_2^d}(C^2-1)\beta_2^{(t-1)\,\%\,d}+1}}
$$

$$
= \sum_{t'=i}^{\infty} \frac{(1-\beta_1)\beta_1^{t'-i}}{\sqrt{\frac{1-\beta_2}{1-\beta_2^d}(C^2-1)\beta_2^{(t'-1)\,\%\,d}+1}}
$$

$$
= \sum_{l=1}^{\infty} \sum_{j''=(l-1)d+i}^{ld+i-1} (1-\beta_1)\beta_1^{j''-i} \cdot \widetilde{V}_{j''}
$$

$$
= \sum_{l=1}^{\infty} \beta_1^{(l-1)d} \sum_{j'=i}^{i+d-1} (1-\beta_1)\beta_1^{j'-i} \cdot \widetilde{V}_{j'}
$$

$$
= \sum_{l=1}^{\infty} \beta_1^{(l-1)d} \sum_{j=0}^{d-1} (1-\beta_1)\beta_1^{j} \cdot \widetilde{V}_{j+i}
$$

$$
= \sum_{l=1}^{\infty} \beta_1^{(l-1)d} \left[\beta_1 \sum_{j=0}^{d-1} (1-\beta_1)\beta_1^{j} \cdot \widetilde{V}_{j+i+1} + (1-\beta_1)(1-\beta_1^d) \cdot \widetilde{V}_i \right]
$$

$$
= \beta_1 \cdot \lim_{nd\to\infty} k(g_{nd+i+1}) + \sum_{l=1}^{\infty} \beta_1^{(l-1)d}(1-\beta_1)(1-\beta_1^d) \cdot \widetilde{V}_i
$$

Thus, we can get the forward difference of $k(g_{nd+i})$ as:

$$
\lim_{nd\to\infty} k(g_{nd+i+1}) - \lim_{nd\to\infty} k(g_{nd+i}) = \sum_{l=1}^{\infty} \beta_1^{(l-1)d} \left[(1-\beta_1)^2 \sum_{j=0}^{\infty} \beta_1^{j} \cdot \widetilde{V}_{j+i+1} + (1-\beta_1)^2 \sum_{j=0}^{\infty} \beta_1^{j} \cdot \widetilde{V}_i \right]
$$

$$
= (1-\beta_1)^2 \sum_{l=1}^{\infty} \beta_1^{(l-1)d} \sum_{j=0}^{d-1} \beta_1^{j} \cdot \left[\widetilde{V}_{j+i+1} - \widetilde{V}_i \right]
$$

$\widetilde{V}_{nd+1i}$ monotonically increases within one period, when $1 \le i \le d$ and $i \in \mathbb{N}$. And the weigh β_1^j for every difference term $\left[\widetilde{V}_{j+i+1} - \widetilde{V}_i \right]$ is fixed when i varies. Thus, the weighted summation $\sum_{j=0}^{d-1} \beta_1^j \cdot \left[\widetilde{V}_{j+i+1} - \widetilde{V}_i \right]$ is monotonically decreasing from positive to negative. In other words, the forward difference is monotonically decreasing, such that there exists j, $1 \le j \le d$ and $\lim_{nd\to\infty} k(g_{nd+1})$ is the maximum among all net updates. Moreover, it is obvious that $\lim_{nd\to\infty} k(g_{nd+1})$ is the minimum.

Hence, we can draw the conclusion: $\exists 1 \le j \le d$, such that

$$
\lim_{nd\to\infty} k(C) = \lim_{nd\to\infty} k(g_{nd+1}) < \lim_{nd\to\infty} k(g_{nd+2}) < \cdots < \lim_{nd\to\infty} k(g_{nd+j})
$$

and

$$
\lim_{nd\to\infty} k(g_{nd+j}) > \lim_{nd\to\infty} k(g_{nd+j+1}) > \cdots > \lim_{nd\to\infty} k(g_{nd+d+1}) = \lim_{nd\to\infty} k(C),
$$

where $K(C)$ is the net update factor for gradient $g_i = C$.

$\square$

H   PROOF OF THEOREM 4

Lemma 7. [1] For a bounded random variable X and a differentiable function $f(x)$, the expectation of $f(X)$ is as follows:

$$\mathbb{E}[f(X)] = f(\mathbb{E}[X]) + \frac{f''(\mathbb{E}[X])}{2} D(X) + R_3 \tag{23}$$

where $D(X)$ is variance of X, and R_3 is as follows:

$$R_3 = \frac{f^{[3]}(\alpha)}{3} \mathbb{E}(X - \mathbb{E}[X])^3 + \tag{24}$$

$$+ \int_{|x - \mathbb{E}[X]| > c} \left(f(\mathbb{E}[X]) + f'(\mathbb{E}[X])(x - \mathbb{E}[X])^2 + f(X) \right) dF(x) \tag{25}$$

$F(x)$ is the distribution function of X. R_3 is a small quantity under some condition. And c is large enough, such that: for any $\epsilon > 0$,

$$P(X \in [\mathbb{E}[X] - c, \mathbb{E}[X] + c]) = P(|X - \mathbb{E}[X]| \leq c) \leq 1 - \epsilon \tag{26}$$

Proof. (**Proof of Theorem 4**) In the stochastic online optimization problem equation 13, the gradient subjects the distribution as:

$$g_i = \begin{cases} C, & \text{with probability } p := \frac{1+\delta}{C+1}; \\ -1, & \text{with probability } 1 - p := \frac{C-\delta}{C+1} . \end{cases} \tag{27}$$

Then we can get the expectation of g_i :

$$\mathbb{E}[g_i] = \delta \tag{28}$$

$$\mathbb{E}[g_i^2] = C^2 \cdot \frac{1+\delta}{C+1} + \frac{C-\delta}{C+1} = C + \delta(C+1) \tag{29}$$

$$D[g_i] = C + \delta(C+1) - \delta^2 \tag{30}$$

$$\mathbb{E}[g_i^4] = C(C^2 - C + 1) + \delta(C-1)(C^2 + 1) \tag{31}$$

$$D[g_i^2] = C^3 - 2C^2 + C + \delta(C^3 - 3C^2 - C - 1) - \delta^2(C+1)^2 \tag{32}$$

Meanwhile, under the assumption that gradients are i.i.d., the expectation and variance of v_i are as following when $nd \to \infty$:

$$\mathbb{E}[v_i] = \lim_{i \to \infty} (1 - \beta_2) \sum_{j=1}^{i} \beta_2^{i-j} \mathbb{E}[g_j^2] = \lim_{i \to \infty} (1 - \beta_2^i) \mathbb{E}[g_j^2] = C + \delta(C+1) \tag{33}$$

$$D[v_i] = \lim_{i \to \infty} (1 - \beta_2) \sum_{j=1}^{i} \beta_2^{i-j} D[g_j^2] = \lim_{i \to \infty} (1 - \beta_2^i) D[g_j^2] = D[g_j^2] \tag{34}$$

Then, for the gradient g_i, the net update factor is as follows:

$$k(g_i) = \sum_{t=0}^{\infty} \frac{(1 - \beta_1)\beta_1^t}{\sqrt{\beta_2^{t+1} v_{i-1} + (1 - \beta_2)\beta_2^t \cdot g_i^2 + (1 - \beta_2) \sum_{j=1}^{t} \beta_2^{t-j} g_{i+j}^2}}$$

It should to be clarified that we define $\sum_{j=1}^{t} \beta_2^{t-j} g_{i+j}^2$ equal to zero when $t = 0$. Then we define X_t as:

$$X_t = \beta_2^{t+1} v_{i-1} + (1 - \beta_2)\beta_2^t \cdot g_i^2 + (1 - \beta_2) \sum_{j=1}^{t} \beta_2^{t-j} g_{i+j}^2$$

---

[1]See detial in: https://stats.stackexchange.com/questions/5782/variance-of-a-function-of-one-random-variable

$$\mathbb{E}[X_t] = \beta_2^{t+1}\mathbb{E}[v_{i-1}] + (1-\beta_2)\beta_2^t \cdot g_i^2 + (1-\beta_2)\sum_{j=1}^t \beta_2^{t-j}\mathbb{E}[g_{i+j}^2] \tag{35}$$

$$= \beta_2^{t+1}\mathbb{E}[g^2] + (1-\beta_2)\beta_2^t \cdot g_i^2 + (1-\beta_2^t)\mathbb{E}[g^2] \tag{36}$$

$$= (1 + \beta_2^{t+1} - \beta_2^t)\mathbb{E}[g^2] + (1-\beta_2)\beta_2^t \cdot g_i^2 \tag{37}$$

$$D[X_t] = \beta_2^{2(t+1)}D[v_{i-1}] + \frac{(1-\beta_2)^2(1-\beta_2^{2t})}{1-\beta_2^2}D[g_{i+j}^2] \tag{38}$$

$$= \left[\beta_2^{2(t+1)} + \frac{(1-\beta_2)^2(1-\beta_2^{2t})}{1-\beta_2^2}\right]D[g^2] \tag{39}$$

For the function $f(x) = \frac{1}{\sqrt{x}}$:

$$f''(x) = \frac{3 \cdot x^{-5/2}}{8}$$

According to lemma 7, we can the expectation of $f(X_t)$ as follows:

$$\mathbb{E}[f(X_t)] = (\mathbb{E}[X_t])^{-1/2} + \frac{3}{8}(\mathbb{E}[X_t])^{-5/2} \cdot D[X_t] \tag{40}$$

$\mathbb{E}[X_t]$ and $D[X_t]$ are expressed by equation 35 and equation 38. Then we can obtain the expectation expression of net update factor as follows:

$$k(g_i) = \sum_{t=0}^{\infty}(1-\beta_1)\beta_1^t\left[\frac{1}{\sqrt{(1-\beta_2)\beta_2^t g_i^2 + (1+\beta_2^{t+1}-\beta_2^k)\mathbb{E}[g_i^2]}} + \frac{3D_t}{8[(1-\beta_2)\beta_2^t g_i^2 + (1+\beta_2^{t+1}-\beta_2^t)\mathbb{E}[g_i^2]]^{\frac{5}{2}}}\right] \tag{41}$$

where $D_t = D[X_k]$. Then for gradient C and -1, the net update factor is as follows:

$$k(C) = \sum_{t=0}^{\infty}(1-\beta_1)\beta_1^t\left[\frac{1}{\sqrt{(1-\beta_2)\beta_2^t C^2 + (1+\beta_2^{t+1}-\beta_2^k)\mathbb{E}[g_i^2]}} + \frac{3D_t}{8[(1-\beta_2)\beta_2^t C^2 + (1+\beta_2^{t+1}-\beta_2^t)\mathbb{E}[g_i^2]]^{\frac{5}{2}}}\right] \tag{42}$$

and

$$k(-1) = \sum_{t=0}^{\infty}(1-\beta_1)\beta_1^t\left[\frac{1}{\sqrt{(1-\beta_2)\beta_2^t + (1+\beta_2^{t+1}-\beta_2^k)\mathbb{E}[g_i^2]}} + \frac{3D_t}{8[(1-\beta_2)\beta_2^t + (1+\beta_2^{t+1}-\beta_2^t)\mathbb{E}[g_i^2]]^{\frac{5}{2}}}\right] \tag{43}$$

$\square$