Asymmetric DQN for Partially Observable Reinforcement Learning

Abstract

Offline training in simulated partially observable environments allows reinforcement learning methods to exploit privileged state information through a mechanism known as asymmetry. Such privileged information has the potential to greatly improve the optimal convergence properties, if used appropriately. However, current research in asymmetric reinforcement learning is often heuristic in nature, with few connections to underlying theory or theoretical guarantees, and is primarily tested through empirical evaluation. In this work, we develop the theory of *asymmetric policy iteration*, an exact model-based dynamic programming solution method, and then apply relaxations which eventually result in *asymmetric DQN*, a model-free deep reinforcement learning algorithm. Our theoretical findings are complemented and validated by empirical experimentation performed in environments which exhibit significant amounts of partial observability, and require both information gathering strategies and memorization.

1 INTRODUCTION

Offline training and online execution (OTOE) is a modern reinforcement learning (RL) paradigm in which a learning agent is trained *offline* (i.e., in simulation) before becoming operational *online* (i.e., in the "real" environment). Advantages of OTOE are broad and include safety guarantees, training speed, flexibility, and—the focus of our work—access to privileged information. For all these reasons, OTOE has even become the paradigm of preference in some research cliques, such as that of multi-agent RL, where it is often called centralized training and decentralized execution (CTDE). Privileged information is data which is accessible during offline training, but not during standard on-line training and/or execution. This can take different forms depending on the type of control problem, e.g., other agents' actions and observations in multi-agent RL, or the system's state in partially observable RL (PORL). In OTOE, access to this information is a temporary privilege, available exclusively in the offline phase due to access of the simulation's internal state. However, despite being not available during online execution, such information has the potential (when used appropriately) to improve the agent's overall training performance and/or convergence speed, and therefore its online performance.

In PORL, OTOE and privileged information is most commonly associated with actor-critic methods through a mechanism called *asymmetry*. Asymmetry has a very specific etymological meaning described below; however, we use the term "asymmetry" more loosely to also refer to the general idea of exploiting privileged information during offline training—two concepts which overlap strongly in this work. In actor-critic methods, two separate models are being trained: a *policy* model (representing the agent's behavior) and a *critic* model (representing the agent's evaluation of its situation). Standard actor-critic methods can be said to be implicitly *symmetric* in the sense that both models receive the same information—in PORL, the agent's history. In *asymmetric* actor-critic, this symmetry is broken by providing privileged information to the critic [Pinto et al., 2017, Foerster et al., 2018, Lowe et al., 2017, Yang et al., 2018, Li et al., 2019, Wang et al., 2020, Warrington et al., 2021, Xiao et al., 2021, Baisero and Amato, 2022, Lyu et al., 2022]. This is possible because the critic is exclusively a training construct which is not used or needed during the execution phase. Asymmetry has also been used in some DQN-like RL methods [Rashid et al., 2018, Mahajan et al., 2019, Rashid et al., 2020, Xiao et al., 2020, de Witt et al., 2021], where normally there would not be a secondary model analogous to the critic which is only used during training. In such cases, a second value-based model is introduced exclusively as a means through which to achieve a form of asymmetric training.

Submitted to the 38th Conference on Uncertainty in Artificial Intelligence (UAI 2022). **To be used for reviewing only**.

However, a substantial majority of prior work in asymmetric RL has proposed heuristic forms of asymmetry primarily verified through empirical evaluations, but which lack the support of a theoretical framework which guarantees the state information is used in an appropriate fashion. We argue that, if unverified by proper theoretical analysis, such methods could quite simply make use of state information in ways which actually hinders the training of a partially observable agent. For example, a trivial result in partially observable control is that the optimal action for a partially observable agent can differ greatly from that of an optimal fully observable agent. The ultimate goal of this work is to develop a state-of-the-art asymmetric value-based deep RL algorithm for partially observable control that is supported by a sound theoretical analysis. To reach this goal, we employ a bottom-up approach, focusing first on developing the theory of *asymmetric policy improvement*, i.e., mechanisms through which privileged state information can be integrated into a policy improvement process while retaining optimal convergence guarantees. In practice, we begin by developing *Asymmetric Policy Iteration* (API) and *Asymmetric Action-Value Iteration*, model-based dynamic programming solution methods. We then introduce elements of stochastic training which result in *Asymmetric Q-Learning* (AQL), a successor to API and AAVI for RL by means of sample experience. Finally, we introduce value-function approximation which results in *Asymmetric DQN* (ADQN). To the best of our knowledge, our work is the first to develop theoretically-driven asymmetric value-based RL.

2 RELATED WORK

Privileged information available offline has been used to improve training performances in a wide range of prior single-agent and multi-agent methods which include both policy-based and value-based methods.

In sigle-agent control, Pinto et al. [2017] employ DDPG with an asymmetric state-based critic to handle robot manipulation tasks; belief-grounded networks [Nguyen et al., 2020] uses a belief-based form of asymmetry and a belief-reconstruction task to train the history representation; Warrington et al. [2021], Chen et al. [2020] use imitation learning to train a partially observable agent via a fully observable agent trained offline. Baisero and Amato [2022] show theoretical issues with state-only forms of asymmetry for policy-gradients, and develop a history-state variant.

In multi-agent control, COMA [Foerster et al., 2018] uses a single centralized asymmetric critic which employs the joint observations and/or the environment state. MADDPG [Lowe et al., 2017] and M3DDPG [Li et al., 2019] use multiple centralized asymmetric critics, one for each agent, which employ the joint observations and/or the environment state. R-MADDPG [Wang et al., 2020] uses a recurrent model and a centralized critic which uses the entire histo-

ries of all agents; CM3 [Yang et al., 2018] uses a state-only critic for reactive control; MacDec-DDRQN [Xiao et al., 2020] uses a centralized value model to learn individual centralized value models. ROLA [Xiao et al., 2021] uses both centralized and individual asymmetric critics which employ local history and/or state information to estimate individual advantage values. QMIX [Rashid et al., 2018], MAVEN [Mahajan et al., 2019], and WQMIX [Rashid et al., 2020] use a centralized but factored value model to train individual agent value models. Lyu et al. [2022] extend the theory by Baisero and Amato [2022] to the multi-agent case.

3 BACKGROUND

In the next subsection, we present some of the background required to understand our work. Section 3.1 formally describes partially observable control problems. Section 3.2 contains a review of non-asymmetric value-based control, in the form of DQN. Section 3.3 covers the definition of *history-state* value functions. In Section 3.4, we present operator notation and useful operators.

3.1 POMDPS

A partially observable Markov decision process (POMDP) is a discrete-time control problem represented by tuple $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, b_0, T, O, R, \gamma \rangle$, where (a) $\mathcal{S}$, $\mathcal{A}$, and $\mathcal{O}$ are state, action, and observation spaces, (b) $b_0 \in \Delta\mathcal{S}$ is an initial state distribution, (c) $T \colon \mathcal{S} \times \mathcal{A} \to \Delta\mathcal{S}$ is a stochastic state transition function, (d) $O \colon \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \Delta\mathcal{O}$ is a stochastic observation emission function, (e) $R \colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ is a reward function, and (f) $\gamma \in [0, 1)$ is a discount factor.

Partially observable control is based on observable *histories*, i.e., the sequences of past actions and observations. The *history* space $\mathcal{H} \doteq (\mathcal{A} \times \mathcal{O})^*$ represents such sequences. To simplify notation, we overload symbol R to also denote the expected reward function on histories $R(h, a) \doteq \mathbb{E}_{s|h} [R(s, a)]$. General partially observable policies take the form of mappings from *histories* to action distributions $\pi \colon \mathcal{H} \to \Delta\mathcal{A}$; however, in this work, we will focus exclusively on *deterministic* policies $\pi \colon \mathcal{H} \to \mathcal{A}$. The goal of the control problem is to find a policy which maximizes the episodic expected *return* $\mathbb{E} \left[\sum_t \gamma^t R(s_t, a_t) \right]$.

Every policy π is associated with an action-value function $Q^\pi(h, a)$ which represents the expected return associated with the agent observing history h, taking action a, and then following the policy π. Q^π is the unique solution to the Bellman equation,

$$Q^\pi(h, a) = R(h, a) + \gamma \, \mathbb{E}_{o|h,a} \left[Q^\pi(hao, \pi(hao)) \right] . \quad (1)$$

The action-value function associated with the optimal policy π^* is denoted as Q^*, and is the unique solution to the

Bellman *optimality* equation,

$$Q^*(h,a) = R(h,a) + \gamma \, \mathbb{E}_{o|h,a} \left[\max_{a'} Q^*(hao,a') \right] . \quad (2)$$

Notation We use symbols Q, Q^π, Q^*, and $\hat{Q}$ to denote similar but separate concepts. $Q \colon \mathcal{H} \times \mathcal{A} \to \mathbb{R}$ denotes an arbitrary real-valued function, not necessarily associated with any policy, Q^π denotes the value function associated with a policy, Q^* denotes the value function associated with an optimal policy, while $\hat{Q}$ denotes a (deep) parametric model. We denote the space of all such history-action real functions as $\mathcal{Q} \doteq \{Q \mid Q \colon \mathcal{H} \times \mathcal{A} \to \mathbb{R}\}$. Further, we use $g(Q)$ to denote the policy which acts greedily on Q, i.e., $\pi = g(Q) \implies \pi(h) = \mathrm{argmax}_a Q(h,a)$.

3.2 DQN

Deep Q-Network (DQN) [Mnih et al., 2015] is a highly successful algorithm for training deep neural networks to control high-dimensional MDPs[1] based on reward feedback. The algorithm achieved human-level performance on a majority of the Atari 2600 games for the first time.

Rather than relying on a lookup table to track the estimated expected return for each state-action pair (s,a), DQN learns a parametric function $\hat{Q} \colon \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ to generalize over state-action pairs. The algorithm reformulates the incremental Q-Learning update [Watkins, 1989] as a squared-error minimization problem:

$$\mathcal{L}(s,a,r,s') \doteq \left(r + \gamma \max_{a' \in \mathcal{A}} \hat{Q}(s',a';\theta^-) - \hat{Q}(s,a;\theta) \right)^2 ,$$

where θ is a set of parameters and θ^- is a time-delayed copy of θ to stabilize learning. The agent interacts with the environment and stores transitions (s,a,r,s') in a replay memory, periodically updating θ via gradient descent on randomly sampled minibatches of experience [Lin, 1992]. This approach approximates the i.i.d. supervised training setting commonly used for neural networks and required for first-order optimization methods.

3.3 HISTORY-STATE VALUE FUNCTIONS

Recent theoretical work in asymmetric actor-critic for PORL has employed the notion of a history-state value function $U^\pi(h,s,a)$ [Baisero and Amato, 2022, Lyu et al., 2022], which represents the expected return associated with the agent observing history h, the environment being in state s, taking action a, and then following policy π. U^π is the unique solution to the *history-state* Bellman equation,

$$U^\pi(h,s,a) = R(s,a) + \gamma \, \mathbb{E}_{s',o|s,a} \left[U^\pi(hao,s',\pi(hao)) \right] . \quad (3)$$

---

[1]Generalization to POMDPs is possible by considering that histories are the Markov states of equivalent History-MDPs.

Despite using the state context to represent a more informed measure of the agent's expected return, U^π still relates to a partially observable agent which is unable to exploit that privileged information, i.e., the state determines future rewards, observations, and states, but it does not directly determine future actions, which are rather determined indirectly by the history. U^π is related to Q^π via a simple identity,

$$Q^\pi(h,a) = \mathbb{E}_{s|h} \left[U^\pi(h,s,a) \right] . \quad (4)$$

We denote the history-state value function associated with the optimal policy as U^*. Once again, this notion of optimality is relative to the space of partially observable policies. Among other things, this means that an optimal partially observable policy cannot be recovered by maximizing U^*, i.e., generally, there is no guarantee that $\pi^*(h) = \mathrm{argmax}_a U^*(h,s,a)$ for any given value of s.

Notation We use symbols U, U^π, U^*, and $\hat{U}$ to denote similar but separate concepts. $U \colon \mathcal{H} \times \mathcal{S} \times \mathcal{A} \to \mathbb{R}$ denotes an arbitrary real-valued function, not necessarily associated with any policy, U^π denotes the value function associated with a policy, U^* denotes the value function associated with an optimal policy, while $\hat{U}$ denotes a (deep) parametric model. We denote the space of all such history-state-action real functions as $\mathcal{U} \doteq \{U \mid U \colon \mathcal{H} \times \mathcal{S} \times \mathcal{A} \to \mathbb{R}\}$.

3.4 OPERATOR NOTATION

To simplify the upcoming math, we make extensive use of operator notation for mappings between Q and U functions.

Operator $B_\pi \colon \mathcal{Q} \to \mathcal{Q}$ is the Bellman operator defined as $B_\pi Q(h,a) \doteq R(h,a) + \gamma \, \mathbb{E}_{o|h,a} \left[Q(hao, \pi(hao)) \right]$, with which Equation (1) can be rewritten as $Q^\pi = B_\pi Q^\pi$.

Lemma 3.1. B_π *is a contraction with fixed point Q^π (proof in Appendix A.1.)*

Operator $B \colon \mathcal{Q} \to \mathcal{Q}$ is the Bellman *optimality* operator, defined as $BQ(h,a) \doteq R(h,a) + \gamma \, \mathbb{E}_{o|h,a} \left[\max_{a'} Q(hao,a') \right]$ or, equivalently, $Q \mapsto B_{g(Q)} Q$, and with which Equation (2) can be rewritten as $Q^* = BQ^*$.

Lemma 3.2. B *is a contraction with fixed point Q^* (proof in Appendix A.2.)*

Some operators for U are analogous to those for Q. To avoid introducing a separate set of symbols for such cases, we overload the previously defined symbols to include these new meanings; the distinction will remain clear from context, usually as the type of the operator's input/output.

Operator $B_\pi \colon \mathcal{U} \to \mathcal{U}$ is the Bellman operator defined as $B_\pi U(h,s,a) \doteq R(s,a) + \gamma \, \mathbb{E}_{s',o|s,a} \left[U(hao,s',\pi(hao)) \right]$, with which Equation (3) can be rewritten as $U^\pi = B_\pi U^\pi$.

Lemma 3.3. B_π *is a contraction with fixed point* U^π *(proof in Appendix A.3.)*

Operator $E: \mathcal{U} \to \mathcal{Q}$ converts U functions to Q functions by taking the conditional expectation over states, and is defined as $EU(h, a) \doteq \mathbb{E}_{s|h}[U(h, s, a)]$.

Definition 3.4 (Mutual Consistency). We say that functions Q and U are *mutually consistent* iff $Q = EU$ holds.

4 ASYMMETRIC VALUE-BASED PORL

In this section, we present the core of our theoretical and algorithmic contributions, which focus on computing or learning optimal action-values $Q^*(h, a)$ by means of asymmetry. In Section 4.1 we present *asymmetric policy iteration* (API), a solution method for tabular models with optimal convergence guarantees. In Section 4.2 we present *asymmetric action-value iteration* (AAVI), an eager variant with similar optimal convergence guarantees. In Section 4.3 we relax aspects of AAVI to make it suitable for learning by means of sample experience, and present *asymmetric Q-learning* (AQL). In Section 4.4 we introduce value function approximation to address generalization concerns, and present *asymmetric DQN* (ADQN), and some variants of interest.

Introducing Asymmetry to Value-Based Methods Two fundamental issues make the use of state information in value-based methods not directly possible: (a) because an action-value model $\hat{Q}(h, a)$ is eventually used for online control, it is constrained by the control problem and cannot directly employ privileged state information; and (b) typical value-based methods do not feature a separate model for the purpose of offline training which may access privileged information (akin to the critic in AC). As such, value-based methods seem fundamentally incompatible with the notion of asymmetry and the use of privileged information. We resolve both issues, and introduce an auxiliary history-state model $\hat{U}(h, s, a)$, trained to model the optimal history-state value function $U^*(h, s, a)$, and used exclusively as a training construct through which to implement asymmetry. Our ultimate goal is to train $\hat{U}$ and $\hat{Q}$ jointly so as to converge to the optimal value functions U^* and Q^*.

4.1 ASYMMETRIC POLICY ITERATION

Consider *asymmetric policy iteration* (API), an iterative process analogous to Policy Iteration [Sutton and Barto, 2018], with the primary difference being that API implements asymmetry by employing both history-state and history values. API starts from arbitrary initial values and policy U_0, Q_0, and π_0, and then uses the following update rules

---

Algorithm 1 Asymmetric Policy Iteration (API)

Require: U_0, Q_0, π_0 arbitrarily initialized tabular models.
Ensure: $\lim_{k \to \infty}\{U_k, Q_k, \pi_k\} = \{U^*, Q^*, \pi^*\}$.
1: **for** $k \leftarrow 0, 1, 2, 3, \ldots$ **do**
2:     $U_{k+1} \leftarrow U_k$
3:     **repeat**
4:         $U_{k+1} \leftarrow B_{\pi_k} U_{k+1}$
5:     **until** convergence
6:     $Q_{k+1} \leftarrow EU_{k+1}$
7:     $\pi_{k+1} \leftarrow g(Q_{k+1})$
8: **end for**

---

to generate sequences U_k, Q_k, and π_k,

$$U_{k+1} \leftarrow \lim_{n \to \infty} B_{\pi_k}^n U_k, \qquad \text{(U-evaluation)} \quad (5)$$

$$Q_{k+1} \leftarrow EU_{k+1}, \qquad \text{(Q-evaluation)} \quad (6)$$

$$\pi_{k+1} \leftarrow g(Q_{k+1}). \qquad \text{(improvement)} \quad (7)$$

Theorem 4.1 (API Optimality). *The sequences* U_k, Q_k, *and* π_k *generated by API converge to* U^*, Q^*, *and* π^*.

Proof. By Lemma 3.1, U_{k+1} equals the fixed point of B_{π_k}, i.e., $U_{k+1} = U^{\pi_k}$. Then, by Equation (4), $Q_{k+1} = EU^{\pi_k} = Q^{\pi_k}$ and consequently $\pi_{k+1} = g(Q^{\pi_k})$. Therefore, in each iteration and until π^* is reached, the next policy π_{k+1} is a strict improvement on the previous policy π_k (Policy Improvement Theorem, [Sutton and Barto, 2018]). Let k^* be the smallest index such that π_{k^*} is optimal; for $k > k^*$, we conclude that $U_k = U^*$ and $Q_k = Q^*$. $\qquad\square$

The U_{k+1} in the U-evaluation step can be practically computed in either of two ways. Either by solving the system of linear equations $U_{k+1} = R + \gamma P_{\pi_k} U_{k+1}$, or by mapping U_k through B_{π_k} until convergence (see Algorithm 1).

Limitations While API is formally guaranteed to converge optimally, it also has significant practical limitations: (a) API is a solution method which requires a model of the environment, as well as efficient and accurate methods to compute the expectations in the U-evaluation and the Q-evaluation steps. (b) A practical approximation of the limit operator in the U-evaluation step (see Algorithm 1) might itself require multiple iterations to achieve an adequate precision. (c) API requires tabular models U and Q, which is not only impractical given that the space of histories grows exponentially with episode lengths, but also makes it not applicable to control problems which have continuous observations or states. (d) Perhaps most importantly, API does not offer any significant advantage compared to its non-asymmetric counterpart PI. Ultimately, both API and PI converge to the same optimal value function Q^*; if anything, API requires more memory and computation to achieve the same goal, resulting in a less practical solution method.

Algorithm 2 Asymmetric Action-Value Iteration (AAVI)

Require: U_0, Q_0 arbitrarily initialized tabular models.
Ensure: $\lim_{k\to\infty}\{U_k, Q_k\} = \{U^*, Q^*\}$.
  1: **for** $k \leftarrow 0, 1, 2, 3, \dots$ **do**
  2:      $U_{k+1} \leftarrow B_{g(Q_k)} U_k$
  3:      $Q_{k+1} \leftarrow EU_{k+1}$
  4: **end for**

Why API? In light of the above limitations, particularly the last one, what is then the purpose of API? We argue that API plays two crucial roles: (a) The first is to show that privileged and asymmetric information such as the system state *can* be properly included into a value-based solution process while maintaining formal optimality guarantees. This theoretical aspect is often overlooked in modern asymmetric RL research, which instead tends to focus on heuristic methods and empirical results, and API represents the first theoretical guarantee of this kind for value-based RL. (b) The second is to serve as a basis for other algorithms which do provide practical advantages compared to their non-asymmetric counterparts. Starting from the next subsection, we relax various aspects of API and develop asymmetric value-based algorithms which address each of API's limitations.

4.2 ASYMMETRIC ACTION-VALUE ITERATION

The first limitation of API which we address is the presence of the limiting operator in its U-step, which makes practical implementations approximate, and/or inefficient. To this end, consider *asymmetric action-value iteration* (AAVI), an eager variant of API which uses the following update rules,

$$U_{k+1} \leftarrow B_{g(Q_k)} U_k, \qquad \text{(U-evaluation)} \quad (8)$$
$$Q_{k+1} \leftarrow EU_{k+1}. \qquad \text{(Q-evaluation)} \quad (9)$$

Compared to API, the improvement step has been folded in the U-evaluation step, removing the need for an explicit policy representation. Further, the U-evaluation step has been simplified to apply operator $B_{g(Q_k)}$ a single time, making for a simple, faster, and more practical implementation (see Algorithm 2) without compromising optimality guarantees. Both aspects make AAVI analogous to Value Iteration [Sutton and Barto, 2018], with the primary differences being the use of action-values and asymmetry.

Lemma 4.2 (Asymmetric Bellman Equivalence). *For mutually consistent U and Q, the identity $EB_{g(Q)}U = BQ$ holds (proof in Appendix A.4.)*

Theorem 4.3 (AAVI Optimality). *The sequences U_k and Q_k generated by AAVI converge to U^* and Q^*.*

Proof. We can combine the U-evaluation and Q-evaluation steps, and then use Lemma 4.2 to obtain $Q_{k+1} = EU_{k+1} = EB_{g(Q_k)}U_k = BQ_k$. By induction, $Q_k = B^k Q_0$, which

Algorithm 3 Asymmetric Q-Learning (AQL)

Require: U, Q mutually consistent tabular models.
Ensure: $\{U, Q\} \to \{U^*, Q^*\}$.
  1: **while** True **do**
  2:     Initialize history and state (h, s)
  3:     **while** s is not terminal **do**
  4:        Choose action a from ϵ-greedy policy on Q
  5:        Take action a, observe r, s', o
  6:        $y \leftarrow r + \gamma U(hao, s', \text{argmax}_{a'} Q(hao, a'))$
  7:        $U(h, s, a) \leftarrow (1-\alpha)U(h, s, a) + \alpha y$
  8:        $Q(h, a) \leftarrow (1-\alpha)Q(h, a) + \alpha y$
  9:        $(s, h) \leftarrow (s', hao)$
10:     **end while**
11: **end while**

---

converges to the fixed point of B: i.e., $Q_k \to Q^*$. This guarantees the existence of some iteration k^* such that $g(Q_k) = \pi^*, \forall k \geq k^*$. Therefore, $U_k = B_{\pi^*}^{k-k^*} U_{k^*}, \forall k \geq k^*$, and U_k converges to the fixed point of B_{π^*}: i.e., $U_k \to U^*$. □

4.3 ASYMMETRIC Q-LEARNING

Like all dynamic programming methods, API and AAVI make extensive and often unrealistic assumptions like the model of the environment and being able to compute exact expectations. To bypass many of these requirements, we can employ incremental stochastic updates based on sequentially sampled transitions. We call this new method *Asymmetric Q-Learning* (AQL), as it generalizes the iterative Q-Learning algorithm [Watkins, 1989] to asymmetric PORL.

To handle the randomness induced by the sample transitions, the algorithm must average over the samples using a variable stepsize parameter $\alpha_k \in [0, 1]$. At each iteration k, the agent samples a transition $(h_k, s_k, a_k, r_k, s_{k+1}, o_k)$ and conducts AAVI-like updates[2] on the respective entries of U_k and Q_k.

For notational brevity, we first define the following targets:

$$Y_k(h, s, a) \doteq \begin{cases} \left(B_{g(Q_k)}U_k + w_k\right)(h, s, a) & \text{for } (h_k, s_k, a_k) \\ U_k(h, s, a) & \text{otherwise} \end{cases}, \quad (10)$$

$$Z_k(h, a) \doteq \begin{cases} \left(EB_{g(Q_k)}U_k + v_k\right)(h, a) & \text{for } (h_k, a_k) \\ Q_k(h, a) & \text{otherwise} \end{cases}. \quad (11)$$

Here, $w_k \in \mathcal{U}$ and $v_k \in \mathcal{Q}$ are zero-mean noise processes that represent the randomness in the environment and action selection at iteration k. AQL then conducts the following

---

[2] The Q-evaluation step of AAVI (Equation (9)) can equivalently be expressed as $Q_{k+1} \leftarrow EB_{g(Q_k)}U_k$, which is the form AQL employs to guarantee optimal convergence.

Algorithm 4 Asymmetric DQN (ADQN)

Require: $\hat{U}, \hat{Q}$ deep models parameterized by θ.
1: Initialize parameters θ
2: Initialize and prepopulate episode buffer
3: **while** True **do**
4:    From the simulated environment, sample episodes and append them to the episode buffer
5:    From the episode buffer, sample batch of transitions $\{(h_i, s_i, a_i, r_i, s'_i, o_i)\}_{i=1}^N$
6:    $L_U \leftarrow \frac{1}{N} \sum_{i=1}^N \mathcal{L}_{\hat{U}}(h_i, s_i, a_i, r_i, s'_i, o_i)$.
7:    $L_Q \leftarrow \frac{1}{N} \sum_{i=1}^N \mathcal{L}_{\hat{Q}}(h_i, s_i, a_i, r_i, s'_i, o_i)$.
8:    Perform a gradient step on θ using $\nabla_\theta (L_U + L_Q)$
9: **end while**

---

updates based on the stochastic targets Y_k and Z_k:

$$U_{k+1} \leftarrow U_k + \alpha_k (Y_k - U_k), \qquad (12)$$

$$Q_{k+1} \leftarrow Q_k + \alpha_k (Z_k - Q_k) \Pr(s_k \mid h_k). \qquad (13)$$

Note that the targets Y_k and Z_k are defined elementwise such that only one entry of U_k and Q_k—the one associated with (h_k, s_k, a_k)—is updated for any given index k. When the stepsizes α_k are annealed towards zero at an appropriate rate, AQL converges optimally despite the noisy updates.

Theorem 4.4 (AQL Optimality). *Assume the following conditions on the stepsizes hold:*

$$\sum_{k=0}^\infty \alpha_k = \infty, \qquad \sum_{k=0}^\infty \alpha_k^2 < \infty.$$

If Q_0, U_0 are mutually consistent ($Q_0 = EU_0$), then the sequences Q_k and U_k generated by AQL converge to Q^* and U^* with probability 1 (proof in Appendix A.5.)

Factor $\Pr(s_k \mid h_k)$ is necessary to ensure that U_k and Q_k remain mutually consistent throughout the process; a necessary condition for optimal convergence. $\Pr(s_k|h_k)$ can be interpreted as a scaling factor which makes U_k and Q_k update at relatively comparable rates. For any given "full" update on $U_k(h_k, s_k, a_k)$ the corresponding update on $Q_k(h_k, a_k)$ should be scaled down to a "partial amount" relative to the likelihood of s_k. While we were able to remove other forms of model-based requirements, $\Pr(s_k \mid h_k)$ remains, leaving AQL just shy from reaching both optimal convergence and concrete practicality at the same time. While it may be possible to approximate this factor in other model-free ways, AQL remains primarily a conceptual algorithm also due to the requirement of a tabular model over histories. Either way, AQL serves as a fundamental basis to derive the next iteration of asymmetric value-based RL.

4.4 ASYMMETRIC DQN

When acting in POMDPs whose observations and states comprise high-dimensional or continuous data, a tabular-

lookup method such as AQL becomes infeasible. In such instances, we must introduce function approximation to generalize over similar experiences. The use of approximation sacrifices the optimal convergence guarantee established by Theorem 4.4, but is necessary to scale algorithms to significantly more challenging partially observable environments. Nevertheless, the approximations introduced are an orthogonal matter to how privileged state information is used, we therefore expect the sound theoretical principles that underlie AQL will help guide the development of asymmetric deep methods even if they rely on function approximation.

Our primary algorithmic contribution here is *Asymmetric DQN* (ADQN), an asymmetric variant of DQN derived by introducing value function approximation to AQL. We first replace the tabular-lookup models U and Q of AQL with parametric differentiable models $\hat{U}$ and $\hat{Q}$. In practice, these are implemented as deep neural networks whose architectures are chosen according to the structure of the states and observations emitted by the POMDP.

To facilitate the substitution, we must reformulate the stochastic update rules of AQL as squared-error loss minimization. For the rest of the section, due to spacing concerns, we will use $\hat{\pi} = g(\hat{Q})$ as a shorthand to represent actions selected greedily on $\hat{Q}$, i.e., $\hat{\pi}(h) = \arg\max_a \hat{Q}(h, a)$. Given a single environment interaction (h, s, a, r, s', o), the corresponding losses can be defined as

$$\mathcal{L}_{\hat{U}} = \left(r + \gamma \, \text{SG} \left[\hat{U}(hao, s', \hat{\pi}(hao))\right] - \hat{U}(h, s, a)\right)^2, \tag{14}$$

$$\mathcal{L}_{\hat{Q}} = \left(r + \gamma \, \text{SG} \left[\hat{U}(hao, s', \hat{\pi}(hao))\right] - \hat{Q}(h, a)\right)^2, \tag{15}$$

where SG is the *stop-gradient* function which indicates that gradient calculation should not consider the enclosed terms. It is worth noting that $\mathcal{L}_{\hat{U}}$ and $\mathcal{L}_{\hat{Q}}$ use the same target to train $\hat{U}$ and $\hat{Q}$. The crucial difference is that $\hat{U}$ is in able to model the target as a function of s, while $\hat{Q}$ is unable to do so, and can at only model the expectation of the target over values of s. In a way, these losses approximately enforce a "loose" form of mutual consistency $\hat{Q} \approx E\hat{U}$. In practice, the term is generated by "target networks" that rely on stale parameters to stabilize learning when bootstrapping [Mnih et al., 2015]; the stale parameters are periodically updated by copying the main parameters. The total loss $\mathcal{L}_{\hat{U}} + \mathcal{L}_{\hat{Q}}$ can be jointly minimized with respect to the parameters by a single backpropagation step, efficiently approximating the interleaved updates of AQL.

When the function approximators are nonlinear (as is often the case for neural networks), training will fail if the gradient updates are conducted on sequentially collected transitions that are not i.i.d. [Mnih et al., 2015]. The second critical modification to AQL is therefore the adoption of experience replay [Lin, 1992] in order to decorrelate training experiences. Rather than training on a sample immediately when

it is collected, each POMDP transition (h, s, a, r, s', o) is deferred to a first-in first-out replay memory. Periodically, when it is time to train the networks, a minibatch of several experiences is sampled from the replay memory; gradients for these samples are computed and averaged together to estimate the true gradient of the joint loss $\mathcal{L}_{\hat{U}} + \mathcal{L}_{\hat{Q}}$, which in turn is used to improve the parameters.

Why ADQN? Having finally addressed the practical disadvantages of API, it is worthwhile to reconsider the "why" question again, this time focusing on why one would prefer to use ADQN compared to DQN. Ultimately, the purpose of both algorithms is to train an approximate $\hat{Q} \approx Q^*$ through which optimal control can be executed, and both algorithms should *in theory* converge to very similar approximations. What is then the advantage of ADQN over DQN? Similarly to the asymmetric actor-critic case [Baisero and Amato, 2022], the advantage is a practical one associated with the difficulties of learning an appropriate representation of history $\phi(h)$, which is one of the major bottlenecks in PORL. History representations are sequence models which notoriously requires lots of data and processing power for proper training. To further compound on this issue, the quality of the data used to train the history representation in PORL is directly related to the quality of $\hat{Q}(\phi(h), \cdot, \cdot)$, which in turn depends on the quality of the history representation itself; unsurprisingly, it can be quite hard to bootstrap the training of an improved history representation when starting from a poor history representation. Note, however, that learning an appropriate state representation $\phi(s)$ is much simpler due to the non-sequential nature of states. In ADQN, the issues associated with learning a proper history representation are alleviated by the fact that its training is bootstrapped not only on the history representation itself, but also on the state representation. Even when the history representation is poor, we can expect the state representation to contain sufficient contextual information to allow $\hat{U}(\phi(h), \phi(s), \cdot)$ to model meaningful values, which in turns helps further bootstrap the learning of the history representation.

Next, we consider some variants of interest of ADQN.

4.4.1 Variance-Reduced ADQN

In this variant, we approximate the target of $\mathcal{L}_{\hat{Q}}$ from Equation (15) as $r + \gamma \hat{U}(hao, s', \hat{\pi}(hao)) \approx \hat{U}(h, s, a)$, which holds particularly well once $\hat{U}$ has been trained sufficiently. Therefore, this variant uses the following losses,

$$\mathcal{L}_{\hat{U}} = (\text{SG}\left[r + \gamma \hat{U}(hao, s', \hat{\pi}(hao))\right] - \hat{U}(h, a))^2 , \quad (16)$$

$$\mathcal{L}_{\hat{Q}} = (\text{SG}\left[\hat{U}(h, s, a)\right] - \hat{Q}(h, a))^2 . \quad (17)$$

This approximate target results in lower variance throughout the entire training process at the cost of introducing bias

primarily in the early stages of training; a trade-off which may result advantageous in some control problems.

4.4.2 State-Only ADQN

Some prior work in asymmetric RL has adopted heuristic forms of asymmetry which uses state-only (i.e., history-less) value functions $U(s, a)$. Such form of asymmetry is however associated with fundamental theoretical issues which may severely compromise the learning performance, raniging from potentially being ill-defined, to introducing bias into the learning process [Baisero and Amato, 2022]. Such issues are inherently related to partial observability, and their effects scale with the amount of partial observability that the agent is subject to, as well as the agent's "reactiveness", i.e. the amount of history that is willfully ignored by the agent itself to select actions. Nonetheless, this state-only form of value function may be more useful than others in control problems which have small amounts of partial observability, such as vision-based tasks with an occlusion-free view of the environment [Pinto et al., 2017, Baisero and Amato, 2022]. Although our main focus is control problems with significant amounts of partial observability, we are still interested in formulating a state-only variant of ADQN as an additional baseline, and as reference for future work which may focus on the kinds of control problems where it thrives.

In this state-only variant, we redefine the parametric model $\hat{U}(s, a)$ to ignore history, and adopt the following losses,

$$\mathcal{L}_{\hat{U}} = (r + \gamma \, \text{SG}\left[\hat{U}(s', \hat{\pi}(hao))\right] - \hat{U}(s, a))^2 , \quad (18)$$

$$\mathcal{L}_{\hat{Q}} = (r + \gamma \, \text{SG}\left[\hat{U}(s', \hat{\pi}(hao))\right] - \hat{Q}(h, a))^2 . \quad (19)$$

4.4.3 Reduced-Variance State-Only ADQN

This variant applies the variance reduction approximation from Section 4.4.1 to state-only ADQN,

$$\mathcal{L}_{\hat{U}} = (r + \gamma \, \text{SG}\left[\hat{U}(s', \pi(hao))\right] - \hat{U}(s, a))^2 , \quad (20)$$

$$\mathcal{L}_{\hat{Q}} = (\text{SG}\left[\hat{U}(s, a)\right] - \hat{Q}(h, a))^2 . \quad (21)$$

5 EVALUATION

We perform an empirical evaluation of ADQN and its variants in a variety of environments which feature significant amounts of partial observability. We compare the performances of 5 value-based PORL algorithms: **DQN** is the standard non-asymmetric DQN; **ADQN** and **ADQN-vr** are the history-state asymmetric DQN algorithms from Sections 4.4 and 4.4.1; **ADQN-state** and **ADQN-state-vr** are the state-only ADQN algorithms from Sections 4.4.2 and 4.4.3. Evaluations are run on 4 partially observable navigation tasks which require information gathering strategies and memorization of the past: **Heaven-Hell-3** and

Figure 1: Performance curves showing episodic returns averaged over the last 100 completed episodes, with statistics computed over 5 independent runs. The shaded areas represent one standard error around the mean.

Heaven-Hell-4 [Bonet, 1998], **Car-Flag** [Nguyen, 2021], and **Cleaner** [Jiang and Amato, 2021]. A thorough description of these environments can be found in the Appendix of Baisero and Amato [2022].

For each environment and algorithm, we perform an independent grid-search over some hyper-parameters of interest (see Appendix), and select the combination of hyper-parameters which results in the best final performance and learning stability (prioritizing final performance if necessary). To improve the statistical significance of the results, we run each combination of environment, algorithm, and hyper-parameters 5 independent times.

5.1 RESULTS AND DISCUSSION

Figure 1 shows the results of these evaluations, which largely confirms the theoretical analysis from our work and prior work concerning the importance of employing correct forms of asymmetry for partially observable control.

Across the board, **ADQN** outperforms all other methods in final performance, convergence speed, and/or overall learning stability. The contrast is particularly stark in Figures 1a and 1b, where **ADQN** and **ADQN-vr** are not just the only methods that demonstrate a substantial improvement on the initial conditions, but also the only ones that reach optimality. On the other hand, the state-only variants fail to outperform even the **DQN** baseline, which further confirms the theoretical issues which have been recently associated with state-only forms of asymmetry. Broadly, the variance-reduced variants **ADQN-vr** and **ADQN-state-vr** only differ in relatively minor ways from their default counterparts. Such differences can be found in Figures 1a and 1d, where **ADQN** is more stable or has better convergence properties than **ADQN-state-vr**, and in Figures 1c and 1d, where **ADQN-state-vr** has better final convergence values than **ADQN-state**. This seems to indicate that the forms of asymmetry (history-state or state-only) is a much larger component in performance than the choice of using a standard or variance-reduced formulation.

6 CONCLUSIONS

OTOE is a RL framework where agents are trained offline in a simulated environment, which allows temporary access to privileged information which would otherwise be unavailable, like the partially observable environment's state. Asymmetry is a common mechanism through which such privileged information is used during training, but is otherwise unnecessary during online execution, and has the potential to greatly boost learning performance and efficiency, when implemented correctly. However, modern work in asymmetric RL tends to focus on unproven heuristics which lack a theoretical justification. We filled this gap and developed the theory of asymmetric value-based RL. Our main goal was to develop a theoretically-sound asymmetric value-based RL algorithm, a goal which we reached by employing a bottom-up approach, by first developing the base theory of asymmetric policy improvement. This takes the form of API, a theoretical solution method with strict optimal convergence guarantees, but concrete practical limitations. Then, we apply a series of relaxations to API which address those limitations, and which ultimately lead to ADQN, a practical and competitive deep RL algorithm. We perform an empirical evaluation to compare the performances of ADQN and its variants to standard non-asymmetric DQN in a series of environments which are specifically selected to exhibit high levels of partial observability, which require memorization of the past, and in which specific information gathering strategies need to be executed. In these environments, ADQN achieves the best performance, even solving control problems which standard DQN could not. Overall, these results are a confirmation of the potential offered by privileged information, the importance of using it in principled and theoretically-guided ways, and the overall success our ADQN algorithm in partially observable control problems. Future work may focus on extending ADQN to the multi-agent control case, which poses further learning challenges, on finding applications where state-only ADQN may thrive (such as vision-based robotic tasks with little partial observability), and on extending the evaluation of ADQN in more complicated partially observable vision-based tasks.

References

Andrea Baisero and Christopher Amato. Unbiased asymmetric reinforcement learning under partial observability, 2022.

Dimitri P Bertsekas and John N Tsitsiklis. *Neuro-Dynamic Programming*. Athena Scientific, 1996.

Blai Bonet. Solving large POMDPs using real time dynamic programming. In *AAAI Fall Symposium on POMDPs*, 1998.

Dian Chen, Brady Zhou, Vladlen Koltun, and Philipp Krähenbühl. Learning by cheating. In *Conference on Robot Learning*, pages 66–75. PMLR, 2020.

Christian Schroeder de Witt, Bei Peng, Pierre-Alexandre Kamienny, Philip Torr, Wendelin Böhmer, and Shimon Whiteson. Deep multi-agent reinforcement learning for decentralized continuous cooperative control. 2021.

Jakob Foerster, Gregory Farquhar, Triantafyllos Afouras, Nantas Nardelli, and Shimon Whiteson. Counterfactual multi-agent policy gradients. *Proceedings of the AAAI Conference on Artificial Intelligence*, 32(1), 2018.

Shuo Jiang and Christopher Amato. Multi-agent reinforcement learning with directed exploration and selective memory reuse. In *Proceedings of the ACM Symposium on Applied Computing*, pages 777–784, 2021.

Shihui Li, Yi Wu, Xinyue Cui, Honghua Dong, Fei Fang, and Stuart Russell. Robust multi-agent reinforcement learning via minimax deep deterministic policy gradient. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 4213–4220, 2019.

Long-Ji Lin. Self-improving reactive agents based on reinforcement learning, planning and reaching. *Machine Learning*, 8(3-4):293–321, 1992.

Ryan Lowe, Yi I. Wu, Aviv Tamar, Jean Harb, OpenAI Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. In *Advances in Neural Information Processing Systems*, pages 6379–6390, 2017.

Xueguang Lyu, Andrea Baisero, Yuchen Xiao, and Christopher Amato. A Deeper Understanding of State-Based Critics in Multi-Agent Reinforcement Learning. *arXiv preprint arXiv:2201.01221*, 2022.

Anuj Mahajan, Tabish Rashid, Mikayel Samvelyan, and Shimon Whiteson. Maven: Multi-agent variational exploration. In *Advances in Neural Information Processing Systems*, pages 7613–7624, 2019.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, , et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Hai Nguyen. POMDP robot domains. https://github.com/hai-h-nguyen/pomdp-domains, 2021.

Hai Nguyen, Brett Daley, Xinchao Song, Chistopher Amato, and Robert Platt. Belief-grounded networks for Accelerated Robot learning under partial observability. 2020.

Lerrel Pinto, Marcin Andrychowicz, Peter Welinder, Wojciech Zaremba, and Pieter Abbeel. Asymmetric actor critic for image-based robot learning. *arXiv preprint arXiv:1710.06542*, 2017.

Tabish Rashid, Mikayel Samvelyan, Christian Schroeder De Witt, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. QMIX: Monotonic value function factorisation for deep multi-agent reinforcement learning. *arXiv preprint arXiv:1803.11485*, 2018.

Tabish Rashid, Gregory Farquhar, Bei Peng, and Shimon Whiteson. Weighted QMIX: Expanding Monotonic Value Function Factorisation. *arXiv preprint arXiv:2006.10800*, 2020.

Richard S. Sutton and Andrew G. Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Rose E. Wang, Michael Everett, and Jonathan P. How. R-maddpg for partially observable environments and limited communication. 2020.

Andrew Warrington, J. Wilder Lavington, Adam Scibior, Mark Schmidt, and Frank Wood. Robust asymmetric learning in POMDPs. 139:11013–11023, 2021.

Christopher John Cornish Hellaby Watkins. *Learning from Delayed Rewards*. PhD thesis, King's College, Cambridge, 1989.

Yuchen Xiao, Joshua Hoffman, Tian Xia, and Christopher Amato. Learning multi-robot decentralized macro-action-based policies via a centralized Q-net. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 10695–10701. IEEE, 2020.

Yuchen Xiao, Xueguang Lyu, and Christopher Amato. Local advantage actor-critic for robust multi-agent deep reinforcement learning. In *International Symposium on Multi-Robot and Multi-Agent Systems*, pages 155–163. IEEE, 2021.

Jiachen Yang, Alireza Nakhaei, David Isele, Kikuo Fujimura, and Hongyuan Zha. Cm3: Cooperative multi-goal multi-stage multi-agent reinforcement learning. 2018.