On-the-fly Adaptation of Patrolling Strategies in Changing Environments

Abstract

We consider the problem of adaptation of patrolling strategies in a changing environment where the topology of Defender's moves and the importance of guarded targets unpredictably change. The Defender must instantly switch to a new strategy optimized for the new environment, not disrupting the ongoing patrolling task, and the new strategy must be computed promptly under all circumstances. Since strategy switching may cause unintended security risks compromising the achieved protection, our solution includes mechanisms for detecting and mitigating this problem. The efficiency of our framework is evaluated experimentally.

1 INTRODUCTION

In *patrolling games*, a *Defender* moves among vulnerable targets and strives to detect a possible ongoing attack. The targets are modeled as vertices in a directed graph, where the edges correspond to admissible moves of the Defender.

An attack at a target τ takes $d(\tau)$ time units to complete successfully. If an initiated attack is *not* discovered in the next $d(\tau)$ time units, the Defender loses a utility determined by the cost of τ. The *protection value* of a Defender's strategy σ is the expected Defender's utility guaranteed by σ against an arbitrary Attacker's strategy.

Adversarial patrolling games assume a powerful Attacker capable of observing Defender's moves, knowing the Defender's strategy, and using this information to identify the best attack opportunity. The Defender's moving strategy is typically *randomized* to prevent the Attacker from fully anticipating future moves. The adversarial setting is particularly apt when the real Attacker's abilities are *unknown* and certain protection degree is required even in the worst case.

Figure 1: The coverage of the attack initiated at time t_1 short before the strategy switch can be very low due to the "incompatibility" of strategies σ_1 and σ_2.

Existing works focus on computing a Defender's strategy (moving plan) maximizing the protection value in a *fixed* patrolling graph. This is challenging on its own because even special variants of the problem are PSPACE-hard. However, having the underlying graph fixed is a significant limitation since the environment *does* change in real-life use cases over time and the Defender is required to adapt its strategy on the fly. For instance, admissible moves of a police patrol are influenced by car accidents or traffic intensity, patrolling drones are affected by weather etc. The target costs also naturally evolve; for example, the cost of a storage place decreases when emptied, etc.

When the patrolling graph G_1 changes into G_2, the current Defender's strategy σ_1 must be promptly replaced with another strategy σ_2 optimized for the new graph. In principle, σ_2 can be computed by one of the existing strategy synthesis algorithms for *fixed* patrolling graphs with G_2 on input. However, we show that this approach has a major *conceptual flaw*. Namely, ignoring the functionality of σ_1 when constructing σ_2 may lead to creating unnecessary *security holes* caused by the "incompatibility" of σ_1 and σ_2. Furthermore, existing algorithms for fixed patrolling graphs are *not* sufficiently efficient to be run under real-time constraints.

To understand the origin and impact of security holes, consider the scenario of Fig. 1. Here a patrolling graph G_1 changes into G_2 at time t, and a Defender's strategy σ_1 is replaced with σ_2. Since σ_1 and σ_2 are optimized for G_1 and G_2 respectively, they plan visits to all targets (including τ) so that the expected damage is constrained by the protec-

tion values of σ_1 and σ_2. An attack at τ initiated at time $t_0 \leq t - d(\tau)$ is fully covered by σ_1, and an attack initiated at time $t_2 \geq t$ is fully covered by σ_2. Hence, these attacks are no more dangerous than others. Now consider an attack initiated at time t_1 "short before" the strategy switch. If σ_2 ignores the functionality of σ_1, it may happen that σ_1 does not patrol τ in the first $t - t_1$ time units, and σ_2 omits τ in the next $d(\tau) - (t - t_1)$ time units (i.e., both strategies plan to visit τ "later"). If this happens, switching from σ_1 to σ_2 at time t creates a temporary but *exceptionally dangerous* attack opportunity, i.e., a *security hole*. A simple concrete instance with quantitative analysis is given in Example 2.

Large security holes are particularly awkward when environmental changes are frequent. Regardless of their frequency, security holes compromise the protection quality and cannot be ignored when we aim at providing robust security guarantees under all circumstances. In general, the difference between G_1 and G_2 may be so large that creating security holes becomes *unavoidable* (see Example 3). This motivates the problems of algorithmic *detection*, *analysis*, and *mitigation* of security holes for a given pair of strategies σ_1 and σ_2.

The term "Defender" actually refers to the whole patrolling infrastructure, including systems for observing environmental changes, synthesizing new strategies, and deploying them to the moving agents. Hence, we assume the Defender observes environmental changes when they happen, and it has sufficient computational resources at its disposal. For the Attacker, we keep the *worst-case* approach, assuming it can observe Defender's moves, environmental changes when they happen and knows the Defender's strategies before/after the change. Furthermore, when evaluating the achieved protection, we assume the environment changes at the moment *least convenient* for the Defender. Consequently, the constructed strategies are *resistant even to sophisticated attacks when the Attacker utilizes all of this information*.

Contribution *We efficiently solve the problem of on-the-fly patrolling strategy adaptation in a changing adversarial environment*. Our approach overcomes the aforementioned problems and is applicable to real-world scenarios. Namely:

(1) We introduce an appropriate formal model for changing environments and strategy switching.

(2) We formalize the concept of a security hole. We design an efficient algorithm for detecting and estimating security holes caused by a given strategy switch.

(3) We design an algorithm for computing a Defender's strategy σ_2 replacing the original strategy σ_1 when the underlying patrolling graph G_1 changes into G_2. This algorithm reduces the danger of creating large security holes and it is *sufficiently efficient* to be run on the fly.

(4) We show that, under certain conditions, security holes can be *mitigated* by randomized strategy switching.

(5) We confirm the efficiency of our algorithms experimentally on instances of considerable size.

As a byproduct of our effort, we obtain a strategy synthesis algorithm for fixed patrolling graphs outperforming the best existing algorithm by a margin.

Existing works on patrolling in dynamic environments are applicable to special graph topologies, non-adversarial environment, or concentrate on collaborative problems such as optimal reassigning the targets to agents (see Related Work). To the best of our knowledge, the presented results are the *first attempt* to solve the problem of *dynamic adaptation of moving strategies in adversarial changing environment with general topology*. We believe that the introduced concept of a security hole is of broader interest. The underlying observations may help to handle similar issues in a larger class of dynamic planning problems with recurrent time-bounded objectives, where the new strategy is obliged to satisfy the commitments not fully accomplished by the old strategy.

1.1 RELATED WORK

Our paper fits the *security games* line of work studying optimal allocation of limited security resources for achieving optimal target coverage [Tambe, 2011]. Practical applications of security games include the deployment of police checkpoints at the Los Angeles International Airport [Pita et al., 2008], the scheduling of federal air marshals over the U.S. domestic airline flights [Tsai et al., 2009], the arrangement of city guards in Los Angeles Metro [Fave et al., 2014], the positioning of U.S. Coast Guard patrols to secure selected locations [An et al., 2014], and also applications to wildlife protection in Uganda [Ford et al., 2014].

Most of the previous results about *adversarial patrolling games* where the Defender is mobile, the environment is actively hostile, and the game horizon is infinite concentrate on computing an optimal moving strategy for certain graph topologies. The underlying solution concept is the *Stackelberg equilibrium* [Sinha et al., 2018, Yin et al., 2010], where the Defender/Attacker play the role of the Leader/Follower.

For general topologies, the existence of a perfect Defender's strategy discovering all attacks in time is PSPACE-complete [Ho and Ouaknine, 2015]. Consequently, computing an optimal Defender's strategy is PSPACE-hard. Moreover, computing an ε-optimal strategy for $\varepsilon \leq 1/2n$, where n is the number of vertices, is NP-hard [Klaška et al., 2020]. Hence, no feasible strategy synthesis algorithm can *guarantee* (sub)optimality for all inputs, and finding high-quality strategy in reasonable time is challenging. The existing methods are based on mathematical programming, reinforcement learning, or gradient descent. The first approach suffers from scalability issues caused by non-linear constraints [Basilico et al., 2012, 2009]. Reinforcement learning has so far been successful mainly for patrolling with finite horizon,

such as green security games [Wang et al., 2019, Biswas et al., 2021, Xu, 2021, Karwowski et al., 2019]. Gradient descent techniques for finite-memory strategies [Kučera and Lamser, 2016, Klaška et al., 2018, 2021] are applicable to patrolling graphs of reasonable size. Strategy synthesis for restricted topologies has been studied for lines, circles [Agmon et al., 2008a,b], or fully connected environments [Brázdil et al., 2018].

Dynamically changing environments have so far been considered mainly in the context of multi-agent patrolling where the task is to dynamically reassign the targets to agents [Othmani-Guibourg et al., 2017, Seok et al., 2017, Chen et al., 2016, Hoshino and Takahashi, 2019, Das et al., 2019].

2 BACKGROUND

We recall the standard notions of a patrolling graph, Defender's and Attacker's strategies and their values. Since our experiments also involve comparison with state-of-the-art strategy synthesis algorithm for fixed patrolling graphs [Klaška et al., 2021], we adopt the same setup.

Patrolling graph   A (static) *patrolling graph* is a tuple $G = (V, T, E, time, d, \alpha)$ where

- V is a finite set of *vertices* (Defender's positions);
- $T \subseteq V$ is a non-empty set of *targets*;
- $E \subseteq V \times V$ is a set of *edges* (admissible moves);
- $time \colon E \to \mathbb{N}_+$ specifies the time to travel an edge;
- $d \colon T \to \mathbb{N}_+$ assigns the time to complete an attack;
- $\alpha \colon T \to \mathbb{R}_+$ defines the costs of targets.

We write $u \to v$ instead of $(u, v) \in E$, and denote $\alpha_{\max} = \max_{\tau \in T} \alpha(\tau)$ and $d_{\max} = \max_{t \in T} d(t)$. In the sequel, let G be a fixed patrolling graph.

Defender's strategy   In general, the Defender may choose the next vertex randomly depending on the whole history of previously visited vertices. As observed by Klaška et al. [2021], a subclass of *regular* Defender's strategies achieves the same limit protection as general strategies, and it is more convenient for algorithmic synthesis.

In the area of graph games, regular strategies are also known as *finite-memory strategies with stochastic memory update*. Intuitively, such a strategy is represented by a finite-state probabilistic automaton $\mathcal{A}$ that "reads" the sequence of vertices visited so far. When a new vertex v is read, $\mathcal{A}$ changes its current state m into another state m' chosen randomly according to a fixed probability distribution determined by m and v. The decision taken by the strategy then depends only on the vertex currently visited and the current state of $\mathcal{A}$. Hence, the set of states of $\mathcal{A}$, denoted by mem, can be seen as a finite memory where some information about

the history of visited vertices is stored (we also refer to the states of $\mathcal{A}$ as *memory elements*).

Formally, let mem be a finite set. The corresponding set of *augmented vertices* $\widehat{V}$ is defined as $V \times mem$, and we use $\widehat{v}$ to denote an augmented vertex of the form (v, m). An *augmented edge* is a pair $\widehat{e} \equiv (\widehat{v}, \widehat{u})$ of augmented vertices where $e \equiv (v, u) \in E$. The set of all augmented edges is denoted by $\widehat{E}$.

A *regular Defender's strategy* for G is a function σ assigning to every $\widehat{v} \in \widehat{V}$ a probability distribution over $\widehat{V}$ so that $\sigma(\widehat{v})(\widehat{u}) > 0$ only if $v \to u$. Intuitively, the Defender starts in some $v \in V$ where the state of $\mathcal{A}$ is initialized to some $m \in mem$, and then it randomly selects the next vertex and the next memory element according to σ. Thus, σ encodes both the selection of the next vertex and the choice of the next state performed by $\mathcal{A}$ (there is no need to specify the transitions of $\mathcal{A}$ explicitly).

Let us fix an initial augmented vertex $\widehat{v}$. For every finite sequence $h = \widehat{v}_1, \ldots, \widehat{v}_n$, we use $\mathrm{Prob}(h)$ to denote the probability of executing h under σ when the Defender starts patrolling in $\widehat{v}$. That is, $\mathrm{Prob}(h) = 0$ if $\widehat{v} \neq \widehat{v}_1$, otherwise $\mathrm{Prob}(h) = \prod_{i=1}^{n-1} \sigma(\widehat{v}_i)(\widehat{v}_{i+1})$. Whenever we write $\mathrm{Prob}(h)$, the associated σ and $\widehat{v}$ are clearly determined by the context.

Attacker's strategy   In the patrolling graph, the time is spent by traversing edges. Adversarial patrolling assumes a powerful Attacker capable of determining the next edge taken by the Defender immediately after its departure from the vertex currently visited. For the Attacker, this is an optimal moment to attack because delaying the attack gains no advantage (as we shall see, this is no longer true in a *changing* environment). Furthermore, the Attacker can attack *at most once* during a play.

An *observation* is a sequence $o = v_1, \ldots, v_n, v_n \to v_{n+1}$, where $v_1, \ldots, v_n$ is a path in G. Intuitively, $v_1, \ldots, v_n$ is the sequence of vertices visited by the Defender, v_n is the currently visited vertex, and $v_n \to v_{n+1}$ is the edge taken next. The set of all observations is denoted by Ω. An *Attacker's strategy* is a function $\pi \colon \Omega \to \{wait, attack_\tau : \tau \in T\}$. As usual, we require that if $\pi(v_1, \ldots, v_n, v_n \to u) = attack_\tau$ for some $\tau \in T$, then $\pi(v_1, \ldots, v_i, v_i \to v_{i+1}) = wait$ for all $1 \leq i < n$. Intuitively, this ensures that the Attacker can attack at most once (this assumption is standard; see, e.g., [Klaška et al., 2018, 2021] for a more detailed explanation).

Evaluating Defender's strategy   Let σ be a regular Defender's strategy and π an Attacker's strategy.

Let us fix an initial augmented vertex $\widehat{v}$ where the Defender starts patrolling. The *expected Attacker's utility* for σ, π and $\widehat{v}$ is defined as

$$\mathrm{EAU}^{\sigma,\pi}(\widehat{v}) = \sum_{\tau, \widehat{e}} \mathbf{P}^{\sigma,\pi}(\widehat{e}, \tau) \cdot \mathrm{Steal}^\sigma(\widehat{e}, \tau)$$

where $\mathbf{P}^{\sigma,\pi}(\widehat{e},\tau)$ is the probability of initiating an attack at τ when the Defender starts moving along $\widehat{e}$, and $\mathrm{Steal}^{\sigma}(\widehat{e},\tau)$ is the expected cost "stolen" by this attack.

More precisely, let $Att(\pi,\widehat{e},\tau)$ be the set of all $(\widehat{v}_1,\ldots,\widehat{v}_{n+1})$ such that $\pi(v_1,\ldots,v_n,v_n{\rightarrow}v_{n+1}) = \tau$ and $\widehat{e} = \widehat{v}_n \rightarrow \widehat{v}_{n+1}$. We put

$$\mathbf{P}^{\sigma,\pi}(\widehat{e},\tau) = \sum_{h \in Att(\pi,\widehat{e},\tau)} \mathrm{Prob}(h).$$

Furthermore, let $\mathbf{M}^{\sigma}(\widehat{e},\tau)$ be the probability of missing (i.e., not visiting) an augmented vertex of the form $\widehat{\tau}$ in the first $d(\tau) - time(e)$ time units by a Defender's walk initiated in $\widehat{u}$, where $\widehat{u}$ is the destination of $\widehat{e}$. We define $\mathrm{Steal}^{\sigma}(\widehat{e},\tau) = \alpha(\tau) \cdot \mathbf{M}^{\sigma}(\widehat{e},\tau)$.

Intuitively, $\mathrm{EAU}^{\sigma,\pi}(\widehat{v})$ is the expected amount "stolen" by the Attacker. The Defender and Attacker aim to minimize and maximize $\mathrm{EAU}^{\sigma,\pi}(\widehat{v})$, respectively. The *Attacker's value of σ in $\widehat{v}$* is the expected Attacker's utility achievable when the Defender commits to σ and starts patrolling in $\widehat{v}$, i.e.,

$$\mathrm{AVal}_G(\sigma)(\widehat{v}) = \sup_\pi \mathrm{EAU}^{\sigma,\pi}(\widehat{v}).$$

The Defender can choose the initial $\widehat{v}$, and hence we also define the *Attacker's value of σ* as

$$\mathrm{AVal}_G(\sigma) = \min_{\widehat{v}} \mathrm{AVal}_G(\sigma)(\widehat{v}).$$

The *Defender's value* (or simply the *value*) is defined by

$$\mathrm{DVal}_G(\sigma)(\widehat{v}) = \alpha_{\max} - \mathrm{AVal}_G(\sigma)(\widehat{v})$$
$$\mathrm{DVal}_G(\sigma) = \alpha_{\max} - \mathrm{AVal}_G(\sigma).$$

Intuitively, $\mathrm{DVal}_G(\sigma)$ corresponds to the protection guaranteed by σ against an arbitrary Attacker's strategy (in the Introduction, we refer to $\mathrm{DVal}_G(\sigma)$ as "the protection value of σ"). We omit the 'G' subscript if it is clear from the context.

3 CHANGING ENVIRONMENT

In this section, we introduce a formal model of changing environments, formalize the concept of strategy switching, and show how to evaluate a switching strategy in a changing environment.

We consider two types of environmental changes: *topological changes* influencing the admissible Defender's moves, i.e., inserting/deleting edges or modifying edge traversal time, and *utility changes* modifying the targets costs.

Formally, a *changing environment* is a pair $G_1 \mapsto G_2$ where G_1 and G_2 are patrolling graphs with the same set of vertices V, the same set of targets T, and the same d specifying the

attack times. We write E_i, $time_i$, and α_i to denote the edges, traversal times, and target costs of G_i for $i \in \{1,2\}$.

For the rest of this section, we fix a changing environment $G_1 \mapsto G_2$, and a pair of regular Defender's strategies σ_1 and σ_2 for G_1 and G_2, respectively. We assume that σ_1 and σ_2 use the same set mem of memory elements.

Strategy switching Let $t \in \mathbb{N}$ be a *switching time*. We use $G_1 \mapsto_t G_2$ to denote the scenario where the patrolling graph G_1 changes into the patrolling graph G_2 at time t, and $\sigma_1 \mapsto_t \sigma_2$ to denote the Defender's strategy for $G_1 \mapsto_t G_2$ obtained by "switching" from σ_1 into σ_2 at time t, defined as follows.

The Defender keeps executing σ_1 in all augmented vertices visited strictly before time t. Let (v,m) be the first augmented vertex visited by the Defender at or after time t (observe that the m is still determined by σ_1). From now on, the Defender should play according to σ_2. We distinguish three possibilities.

(a) There is $m' \in mem$ such that $\mathrm{DVal}_{G_2}(\sigma_2) = \mathrm{DVal}_{G_2}(\sigma_2)(v,m')$. Then, the Defender selects such an m' and starts applying σ_2 from (v,m').

(b) The condition of (a) does not hold, but there exist (v',m') and a path from v to v' in G_2 such that $\mathrm{DVal}_{G_2}(\sigma_2) = \mathrm{DVal}_{G_2}(\sigma_2)(v',m')$. Then, the strategy $\sigma_1 \mapsto_t \sigma_2$ follows the selected path from v to v', and then starts applying σ_2 from (v',m') for the selected m'.

(c) None of the conditions (a) and (b) holds. Then, it is *impossible* to perform a switch from σ_1 to σ_2 preserving the protection value of σ_2, and the strategy $\sigma_1 \mapsto_t \sigma_2$ is undefined.

In all scenarios considered in our experiments, Condition (a) holds for every t. Condition (b) corresponds to a situation when some vertex v visited by σ_1 is no longer visited by σ_2. Condition (c) covers pathological cases when a "drastic" environmental change prevents switching σ_1 into σ_2 (e.g., all edges disappear). From now on, we assume that Condition (a) or (b) holds and the strategy $\sigma_1 \mapsto_t \sigma_2$ is defined.

Remark 1. *Our algorithm for constructing σ_2 (see Preventing and Mitigating Security Holes) "adapts" σ_1 to the new environment G_2. Hence, the elements of mem may represent similar information about the history of visited vertices in σ_1 and σ_2, and Condition (a) may hold even for $m' = m$. In this case, the information encoded by m is passed on to σ_2 during the switch, decreasing the danger of creating large security holes.*

Evaluating a switching strategy The notions defined for static environments (Attacker's strategy, expected utility, strategy value, etc.) also apply to changing environments,

and the technical adjustments are trivial. However, the notion of Attacker's observation requires revision for the reasons described below.

In static scenarios, it is safe to assume the Attacker initiates his attack when the Defender leaves a vertex (see the paragraph *Attacker's strategy* in the previous section). However, in $G_1 \mapsto_t G_2$, the Attacker *may* increase its expected utility by initiating an attack in the middle of a Defender's move. This is because a short delay may suffice for completing the attack *after* time t when the target becomes more valuable, but postponing the attack to the moment when the Defender completes the move would already increase the probability of discovering the attack too much. In case of deeper interest, see a concrete example in Supplementary material.

Technically, we define an *observation* in $G_1 \mapsto_t G_2$ as a pair (o, δ), where $o = v_1, \ldots, v_n, v_n \rightarrow v_{n+1}$ is defined as for static environments and $\delta \in \mathbb{N}$ is a *delay* strictly smaller than $time_i(v_n \rightarrow v_{n+1})$, where $i = 1$ if the move $v_n \rightarrow v_{n+1}$ is initiated before time t, and $i = 2$ otherwise.

Now we define the expected Attacker's utility $\mathrm{EAU}^{\sigma_1 \mapsto_t \sigma_2, \pi}(\widehat{v})$ similarly as for static environments, i.e., as a sum

$$\sum_{\tau, \widehat{e}, \delta, t_0} \mathbf{P}^{\sigma_1 \mapsto_t \sigma_2, \pi}(\widehat{e}, \tau, \delta, t_0) \cdot \mathrm{Steal}^{\sigma_1 \mapsto_t \sigma_2}(\widehat{e}, \tau, \delta, t_0).$$

(1)

Here, $t_0 \in \mathbb{N}$ denotes the attack time. The symbol $\mathbf{P}^{\sigma_1 \mapsto_t \sigma_2, \pi}(\widehat{e}, \tau, \delta, t_0)$ is the probability of initiating an attack at τ at time t_0 when the Defender has been going along $\widehat{e}$ for δ time units (note that this also depends on the Defender's initial position $\widehat{v}$). $\mathrm{Steal}^{\sigma_1 \mapsto_t \sigma_2}(\widehat{e}, \tau, \delta, t_0)$ denotes the expected cost "stolen" by this attack. Detailed technical definitions are in Supplementary material. Although the delay δ further complicates our technical definitions, it describes a *real phenomenon* which must be properly reflected by a realistic formal model.

The time t when G_1 changes into G_2 is unpredictable, and the strategy σ_2 must guarantee a reasonable protection on G_2 for all t's. Hence, the *Attacker's value of $\sigma_1 \mapsto \sigma_2$ in $G_1 \mapsto G_2$* is defined as

$$\mathrm{AVal}_{G_1 \mapsto G_2}(\sigma_1 \mapsto \sigma_2) = \min_{\widehat{v}} \sup_{\pi} \sup_{t} \mathrm{EAU}^{\sigma_1 \mapsto_t \sigma_2, \pi}(\widehat{v}).$$

Note that the "$\sup_\pi$" in the above definition ensures that *all* Attacker's strategies are taken into account, including those taking advantage of observing the environmental change, Defender's moves, and analyzing the functionality of σ_1, σ_2.

4 SECURITY HOLES

Strategy switching may result in temporarily decreasing the protection of some targets. Clearly, the Defender cannot protect $G_1 \mapsto G_2$ by $\sigma_1 \mapsto \sigma_2$ better than it is protecting

G_1 by σ_1 and G_2 by σ_2. In terms of Attacker's values,

$$\mathrm{AVal}_{G_1 \mapsto G_2}(\sigma_1 \mapsto \sigma_2) \geq \mathrm{AVal}_{G_1}(\sigma_1),$$
$$\mathrm{AVal}_{G_1 \mapsto G_2}(\sigma_1 \mapsto \sigma_2) \geq \mathrm{AVal}_{G_2}(\sigma_2).$$

The first inequality is simple because the switching time t can be arbitrarily large. With increasing t, the Attacker can perform more and more of his attacks scheduled by a given strategy π against σ_1 in G_1 also in $G_1 \mapsto G_2$, achieving the expected utility arbitrarily close to the expected utility received in G_1. The second inequality is also immediate because the Attacker can "simulate" an arbitrary strategy π against σ_2 also in $G_1 \mapsto G_2$ by performing his attacks after the switching time.

However, it may also happen that $\mathrm{AVal}_{G_1 \mapsto G_2}(\sigma_1 \mapsto \sigma_2)$ is *strictly larger* than the maximum of $\mathrm{AVal}_{G_1}(\sigma_1)$ and $\mathrm{AVal}_{G_2}(\sigma_2)$ due to the new attack opportunities offered in the limited time window short before the switching time caused by the "incompatibility" between σ_1 and σ_2 (see Fig. 1). Note that although the Attacker cannot enforce an environmental change at a particular time, in our adversarial setting we consider the worst possibility, i.e., we assume the change happens in the least convenient moment. Formally, the *security hole* of $\sigma_1 \mapsto \sigma_2$, denoted by $Hole_{G_1 \mapsto G_2}(\sigma_1, \sigma_2)$, is defined as

$$\mathrm{AVal}_{G_1 \mapsto G_2}(\sigma_1 \mapsto \sigma_2) - \max\{\mathrm{AVal}_{G_1}(\sigma_1), \mathrm{AVal}_{G_2}(\sigma_2)\}.$$

Intuitively, $Hole_{G_1 \mapsto G_2}(\sigma_1, \sigma_2)$ is the extra amount stolen by the Attacker due to the incompatibility between σ_1 and σ_2. Note that if $Hole_{G_1 \mapsto G_2}(\sigma_1, \sigma_2) = 0$, then the new attack opportunities caused by the switch are no more dangerous than the ones offered by σ_1 in G_1 and σ_2 in G_2.

Example 2. *Let G_1 and G_2 be the patrolling graphs of Fig. 2. Let σ_1 be a trivial strategy walking among v_1, v_2, v_3 clockwise. Since every target is revisited within the next 6 time units, all attacks are discovered in time and hence $\mathrm{AVal}_{G_1}(\sigma_1) = 0$. When the environment changes into G_2 by removing the edge $v_2 \rightarrow v_3$, the Defender's strategy is changed into σ_2 walking among v_1, v_2, v_3 anticlockwise. Clearly, $\mathrm{AVal}_{G_2}(\sigma_2) = 0$, and hence both σ_1 and σ_2 achieve perfect protection in G_1 and G_2, respectively.*

Now consider the scenario where v_3 is attacked at time ℓ when the Defender is in the middle of the move $v_3 \rightarrow v_1$ in G_1. The Defender arrives in v_1 at time $\ell + 1$, and the environment changes from G_1 into G_2 at time $t = \ell + 2$. In v_1, the Defender still uses σ_1 to determine the next move, and arrives in v_2 at time $\ell + 3$. In v_2, the Defender already uses the new strategy σ_2, and therefore visits v_3 at time $\ell + 7$. That is, the attack at v_3 initiated at time ℓ (short before the switching time) succeeds with probability one. Consequently, $\mathrm{AVal}_{G_1 \mapsto G_2}(\sigma_1 \mapsto \sigma_2) = 100$ and hence $Hole_{G_1 \mapsto G_2}(\sigma_1, \sigma_2) = 100$.

G_1; σ_1 walks clockwise. G_2; σ_2 walks anti-clockwise.

Figure 2: Exemplifying $Hole_{G_1 \mapsto G_2}(\sigma_1, \sigma_2) = 100$. Target costs are 100, traversing every edge takes 2 time units, completing an attack takes 6 time units. If the Attacker attacks v_3 when the Defender is in the middle of the edge $v_3 \to v_1$ and the environment changes in 2 more time units, the attack succeeds with probability 1.

Estimating security holes Here we present an algorithm for computing an upper bound on $Hole_{G_1 \mapsto G_2}(\sigma_1, \sigma_2)$. Since $\mathrm{AVal}_{G_1}(\sigma_1)$ and $\mathrm{AVal}_{G_2}(\sigma_2)$ are computable by the standard strategy evaluation algorithm [see, e.g., Klaška et al., 2021], we only need to compute an *upper bound on* $\mathrm{AVal}_{G_1 \mapsto G_2}(\sigma_1 \mapsto \sigma_2)$.

According to Eq. (1), it suffices to compute the maximum of all the values $\mathrm{Steal}^{\sigma_1 \mapsto_t \sigma_2}(\widehat{e}, \tau, \delta, t_0)$. Since there are *infinitely many* $t, t_0 \in \mathbb{N}$, this task is not trivial.

If $t_0 < t - d(\tau)$ or $t_0 \geq t$, then the attack at τ is fully covered by σ_1 or σ_2, respectively. Hence, the only interesting case is when $1 \leq t - t_0 \leq d(\tau)$. Although there are still infinitely many t, t_0 satisfying this condition, the above Steal is *fully determined* just by the difference $t - t_0$, and can thus be written as $\mathrm{Steal}(\widehat{e}, \tau, \delta, \Delta t)$, where Δt denotes the difference and ranges over *finitely many values* bounded by $d(\tau)$. Furthermore, we show that we can safely assume $\delta = 0$, and also reduce the set of relevant Δt and $\widehat{e}$.

Thus, we obtain a finite set of *eligible* $\mathrm{Steal}(\widehat{e}, \tau, \Delta t)$ such that $\mathrm{AVal}_{G_1 \mapsto G_2}(\sigma_1 \mapsto \sigma_2)$ is bounded from above by the maximum of $\mathrm{AVal}_{G_1}(\sigma_1)$, $\mathrm{AVal}_{G_2}(\sigma_2)$, and all eligible $\mathrm{Steal}(\widehat{e}, \tau, \Delta t)$.

Since the total number of all eligible $\mathrm{Steal}(\widehat{e}, \tau, \Delta t)$ is high, their values cannot be computed naively. Roughly speaking, this is overcome by identifying mutual dependencies among these values, inventing a specific search routine, and performing several non-trivial precomputations, thereby reducing the computational time. The overall functionality is subtle and described in Supplementary material.

Preventing security holes Our approach to preventing large security holes is based on taking the functionality of σ_1 into account when computing the strategy σ_2 for a given $G_1 \mapsto G_2$. This is achieved by *adapting* the strategy σ_1 to G_2. Since σ_1 may not be directly executable in G_2 (for example, some edges of G_1 used by σ_1 may disappear in G_2), we first perform some adjustments to σ_1. Then, we *improve* this initial strategy in G_2 by an *efficient strategy improvement algorithm* described below, and thus obtain σ_2. Intuitively, since σ_2 tends to be "similar" to σ_1, the chance of producing *unnecessary* security holes decreases. This

intuition is confirmed in Experiments.

The starting point for designing our strategy improvement algorithm is REGSTAR, currently the best strategy synthesis algorithm for fixed patrolling graphs recently presented by Klaška et al. [2021]. REGSTAR repeatedly picks a random initial strategy and tries to improve its value. The algorithm consists of two subroutines: *Evaluation*, i.e., computing of the value and a gradient of a given strategy and *Optimization* using gradient descent. After hundreds of trials, the best strategy found is chosen.

However, the authors of REGSTAR report [see Klaška et al., 2021, Sec. 3.5] that the percentage of trials converging to the best strategy found can be rather low ($\approx 2\%$). For this reason, our initial attempt to construct σ_2 by applying the strategy-improvement subroutine of REGSTAR to σ_1 in the graph G_2 *failed*. This calls for REGSTAR re-design.

First, we replace the optimization scheme using dedicated tools for differentiable programming (PyTorch with Adam optimizer). We also add decaying Gaussian noise to the gradient allowing for different outcomes when optimizing from σ_1 and hence enlarging the chance of hitting high-valued σ_2. In contrast, the optimization loop of REGSTAR is purely deterministic. Furthermore, the REGSTAR's evaluation computes gradients in forward mode. We re-design this part by employing the reverse mode, yielding improvement by a factor of $|\widehat{E}|$.

Our modifications drastically improve REGSTAR's convergence ratio and speed (see the analysis in Experiments) and allow for *on the fly strategy adaptation*. Implementation details are documented, and the code is provided in Supplementary material.

Mitigating security holes In general, the structural difference between G_1 and G_2 in a changing environment $G_1 \mapsto G_2$ can make the creation of security holes *unavoidable*, as demonstrated by the following example.

Example 3. *Consider the setup of Example 2. There is only one* σ_2 *such that* $\mathrm{DVal}_{G_2}(\sigma_2) = 100$ *(the "anticlockwise walk"), and hence there is no reasonable alternative to* σ_2. *Since* $\mathrm{DVal}_{G_1}(\sigma_1) = \mathrm{DVal}_{G_2}(\sigma_2) = 100$, *we inevitably obtain the largest conceivable security hole equal to* 100.

However, we show that under the conditions given below, the security holes can be *mitigated without harming the protection achieved by* σ_2 by *randomized strategy switching*.

Let us assume the following:

- σ_1 is executable in G_2 and[1] $Hole_{G_1 \mapsto G_2}(\sigma_1, \sigma_1) = 0$.

---

[1]This is *not* a typo. If G_2 has the same topology as G_1 but edge traversal times change, then setting $\sigma_2 = \sigma_1$ *may* cause a security hole. The assumption $Hole_{G_1 \mapsto G_2}(\sigma_1, \sigma_1) = 0$ says that this does not happen.

- For every (v, m) visited by σ_1 with positive probability, there is (v, m') such that $\mathrm{DVal}_{G_2}(\sigma_2)(v, m') = \mathrm{DVal}_{G_2}(\sigma_2)$.

Under these conditions, the Defender may perform a *randomized switch from σ_1 to σ_2*. That is, the Defender flips a κ-biased coin when it arrives in a vertex and switches to σ_2 only with probability κ. With the remaining probability $1 - \kappa$, the Defender continues executing σ_1 and flipping the coin in the next vertex again. This goes on until the switch to σ_2 is performed. We have the following:

Theorem 4. *The expected number of time units needed to perform the κ-randomized switch is bounded by $max\text{-}time_2/\kappa$, where $max\text{-}time_2$ is the maximal traversal time of an edge in G_2.*

The security hole caused by the κ-randomized switch is bounded by

$$\varrho + \left(1 - (1 - \kappa)^{d_{\max}}\right) \cdot \alpha_{\max}(G_2)$$

where $\alpha_{\max}(G_2)$ is the maximal target cost in G_2 and ϱ is defined as

$$\max\left\{0, \ \mathrm{AVal}_{G_2}(\sigma_1) - \max\{\mathrm{AVal}_{G_1}(\sigma_1), \mathrm{AVal}_{G_2}(\sigma_2)\}\right\}$$

Hence, the security hole can be pushed arbitrarily close to ϱ by choosing a suitably small $\kappa > 0$.

A proof of Theorem 4 is in Supplementary material. The usefulness of randomized strategy switching is documented on a concrete scenario in Experiments.

5 EXPERIMENTS

5.1 STRATEGY IMPROVEMENT ANALYSIS

We assess our strategy synthesis algorithm in comparison with REGSTAR on the set of patrolling graphs used to evaluate REGSTAR by Klaška et al. [2021]. These graphs model office buildings, and their structure is recalled in Supplementary material.

Here we present the outcomes for a graph modeling a 2-floor building achieved for mem with $1, \ldots, 8$ elements, cf. [Klaška et al., 2021, Experiment 5.3]. Fig. 3 shows boxplot statistics of values of strategies found by 200 trials of REGSTAR (blue) and our improved (red) method. Note that our method consistently produces values concentrated around the best value found, i.e., the chance of producing a strategy with a high value from a random initial strategy is *high*. Furthermore, the value of the *best* strategy found by our method is *higher* than the one found by REGSTAR in all cases except for $|mem| = 8$ (where the difference is negligible). Similar results are obtained for *all* patrolling graphs analyzed by Klaška et al. [2021]. These datasets together with a detailed setup description are supplemented.

Figure 3: Values of strategies synthesized by REGSTAR (blue) and our method (red) for a 2-floor building graph where mem has $1, \ldots, 8$ elements. The red values are tightly distributed close to the maxima.

Next, we report runtimes of the forward (value) and backward (gradient) computations of the strategy-evaluation module. Tab. 1 summarizes the mean of 200 passes through the strategy evaluation on the same 2-floor building graph with various mem sizes. Reverse-mode gradient computation improved the backward times by *three orders of magnitude* (note that the time is given in *seconds* for REGSTAR and in *miliseconds* for our method).

| | forward [ms] | | backward | |
m	REGSTAR	Ours	REGSTAR [s]	Ours [ms]
2	50 ± 3	48 ± 5	0.64 ± 0.04	4 ± 0
4	217 ± 4	198 ± 19	10.2 ± 0.7	14 ± 2
6	492 ± 4	451 ± 44	57.4 ± 3.9	33 ± 3
8	913 ± 9	805 ± 80	186.3 ± 12.0	60 ± 7

Table 1: Effect of differentiation of $\sigma \mapsto \mathrm{DVal}(\sigma)$ in reverse mode (Ours) compared to forward mode (REGSTAR).

5.2 CHANGING ENVIRONMENT

We evaluate our algorithms for concrete changing environments. Specifically, we quantify the impact of our approach to preventing security holes and examine the effectiveness of randomized strategy switching on mitigating security holes.

We fix one patrolling graph G_1 consisting of 15 locations in the downtown of Vancouver. The target costs are set between 80 and 100 at random. Furthermore, we select 72 edges connecting the targets with lengths measured in taxicab distance in hundreds of meters. Attack times are fixed to 64, giving the Defender chance to discover an attack starting 6.4km far away. For G_1, we find and fix a strategy σ_1 with $\mathrm{DVal}_{G_1}(\sigma_1) = 42.1$.

We perform three sets of experiments, modifying G_1 to

G_2 by either changing the target costs, edge lengths, or removing some edges. The experiments are parameterized by the *change size*, denoted by CS. For all types we report two CS values representing small and large change impact. More values are reported in Supplementary material.

Utility changes The cost of each node is increased by its CS% with probability 1/3, decreased by CS% with probability 1/3, or left unchanged. Note that utility changes can modify $\alpha_{\max}$ and thus influence DVal. To compare, we normalize all results by $100/\alpha_{\max}$ for each G_2 and its $\alpha_{\max}$.

Variable edge length As in the previous case, the length of each edge is increased/decreased by CS% or kept unchanged (with the same probability).

Removed edges We randomly delete CS edges so that G_2 remains strongly connected.

For each CS, we generate 10 modified graphs G_2. For every G_2, we take the highest value and security gap from 10 optimization trials with 0, 50, 100, 200, and 400 optimization steps initiated in σ_1 (recall that the optimization step in our algorithm uses noising and hence the output is different for each of the 10 trials). We report the means and standard deviations over all 10 modified graphs G_2. The same statistics are reported for the runs that start from random initialization instead of from σ_1. This is repeated for every CS. Hence, for each line of Tab. 2, we run 2×100 optimization trials. For setup details, see Supplementary material.

Summary All experiments unanimously confirm that, for small CS, the initialization in σ_1 leads to higher DVal and much smaller security holes in fewer iterations. For small CS, strategies obtained after 50 optimization steps from σ_1 are not outperformed even by 400 steps of optimization initiated in a randomly chosen strategy.

Only for large CS in edge length, the optimizations initiated in a random strategy reach higher values than the optimization initiated in σ_1. However, the security gap is huge.

In all our experiments, the average time needed for performing one optimization step is 110 milliseconds, which is sufficient for performing our algorithm on the fly.

Mitigating Security Holes The conditions enabling randomized strategy switching are satisfied for all σ_2 summarized in utility changes of Tab. 2. We have that $\text{DVal}_{G_1}(\sigma_1) = 42.1$ and $\text{DVal}_{G_2}(\sigma_1) = 40.9$, which means $\text{AVal}_{G_1}(\sigma_1) = 57.9$ and $\text{AVal}_{G_2}(\sigma_1) = 59.1$. By Theorem 4, the security hole can be reduced arbitrarily close to 1.2 for *all* σ_2, including those constructed from randomly chosen initial strategies. Note that the improvement is *significant* in almost all cases.

	CS steps	DVal from σ_1	DVal from rnd	Security Hole from σ_1	Security Hole from rnd
utility changes	0	40.9 ± 0.9	12.7 ± 3.2	0.0 ± 0.0	4.6 ± 2.7
	50	43.4 ± 0.6	27.4 ± 0.8	2.8 ± 1.2	14.4 ± 1.2
5	100	43.6 ± 0.5	37.3 ± 1.2	3.9 ± 1.9	25.3 ± 2.6
	200	43.8 ± 0.6	41.3 ± 0.6	5.2 ± 2.8	30.2 ± 4.4
	400	43.8 ± 0.6	42.7 ± 0.5	6.9 ± 4.4	33.7 ± 3.9
	0	40.9 ± 0.9	14.7 ± 4.2	0.0 ± 0.0	6.1 ± 2.2
	50	50.4 ± 3.4	38.2 ± 4.4	9.7 ± 1.9	19.6 ± 3.3
30	100	51.4 ± 3.6	48.7 ± 2.8	11.3 ± 3.1	30.1 ± 5.6
	200	52.4 ± 3.8	52.8 ± 3.5	14.0 ± 2.3	39.4 ± 4.1
	400	52.9 ± 3.7	54.0 ± 3.3	15.2 ± 3.2	40.0 ± 5.6
variable edge length	0	36.4 ± 2.2	9.4 ± 0.3	0.6 ± 1.0	2.9 ± 0.3
	50	40.3 ± 0.9	24.3 ± 0.6	5.0 ± 1.9	13.0 ± 1.1
5	100	40.6 ± 0.9	34.7 ± 0.7	6.5 ± 2.6	26.2 ± 2.5
	200	40.9 ± 0.9	39.3 ± 0.7	8.8 ± 3.1	31.9 ± 2.3
	400	41.0 ± 0.9	40.4 ± 0.8	9.4 ± 3.1	33.8 ± 2.7
	0	16.3 ± 10.1	8.1 ± 1.1	0.1 ± 0.4	1.7 ± 1.2
	50	33.6 ± 5.0	24.0 ± 2.5	5.4 ± 5.4	13.2 ± 2.8
30	100	36.4 ± 3.7	37.8 ± 2.4	10.2 ± 4.6	27.5 ± 2.3
	200	38.7 ± 3.2	42.7 ± 2.2	14.2 ± 5.3	33.9 ± 2.6
	400	40.8 ± 2.6	44.4 ± 2.9	20.9 ± 3.8	34.1 ± 3.5
removed edges	0	39.5 ± 5.3	9.6 ± 0.3	0.0 ± 0.0	3.1 ± 0.4
	50	42.0 ± 0.2	24.6 ± 0.3	0.9 ± 1.5	13.3 ± 0.8
1	100	42.1 ± 0.1	35.1 ± 0.7	0.9 ± 1.5	24.9 ± 2.1
	200	42.1 ± 0.1	39.4 ± 0.3	0.9 ± 1.4	31.9 ± 3.3
	400	42.1 ± 0.1	40.9 ± 0.5	1.3 ± 1.2	34.5 ± 2.3
	0	17.0 ± 11.4	9.8 ± 0.9	0.0 ± 0.0	3.3 ± 0.6
	50	36.1 ± 9.1	24.8 ± 0.3	8.2 ± 5.3	13.2 ± 1.7
8	100	39.7 ± 1.9	35.3 ± 0.9	10.3 ± 5.1	25.5 ± 2.4
	200	40.4 ± 1.4	39.0 ± 0.7	10.9 ± 5.1	29.8 ± 2.1
	400	40.9 ± 1.0	40.5 ± 0.7	11.8 ± 5.5	34.4 ± 2.6

Table 2: Values and security holes of strategies in changed graph G_2 optimized from old strategy or from scratch. Initialization in σ_1 leads to higher DVal and much smaller security holes in fewer iterations, unless the changes (CS) are too large.

6 CONCLUSIONS, FUTURE WORK

We designed an efficient algorithmic framework for solving the problem of on-the-fly strategy adaptation in adversarial changing environment with arbitrary topology. Our experiments show that our strategy adaptation algorithm is sufficiently efficient to be run on-the-fly, outperforming the best existing strategy synthesis algorithm REGSTAR by three orders of magnitude. Furthermore, the experiments demonstrate the effectiveness of the designed methods for preventing and mitigating security holes.

An interesting open question is whether the Defender can effectively decrease the potential negative impact of environmental changes by *preventive* adaptations of its current strategy. This may help in cases when the probability of these changes happening in a near future is known.

References

N. Agmon, S. Kraus, and G. Kaminka. Multi-robot perimeter patrol in adversarial settings. In *Proceedings of ICRA 2008*, pages 2339–2345. IEEE Computer Society Press, 2008a.

N. Agmon, V. Sadov, G.A. Kaminka, and S. Kraus. The impact of adversarial knowledge on adversarial planning in perimeter patrol. In *Proceedings of AAMAS 2008*, pages 55–62, 2008b.

B. An, E. Shieh, R. Yang, M. Tambe, C. Baldwin, J. Di-Renzo, B. Maule, and G. Meyer. Protect—a deployed game theoretic system for strategic security allocation for the United States coast guard. *AI Magazine*, 33(4): 96–110, 2014.

N. Basilico, N. Gatti, and F. Amigoni. Leader-follower strategies for robotic patrolling in environments with arbitrary topologies. In *Proceedings of AAMAS 2009*, pages 57–64, 2009.

N. Basilico, N. Gatti, and F. Amigoni. Patrolling security games: Definitions and algorithms for solving large instances with single patroller and single intruder. *Artificial Inteligence*, 184–185:78–123, 2012.

A. Biswas, G. Aggarwal, P. Varakantham, and M. Tambe. Learn to intervene: An adaptive learning policy for restless bandits in application to preventive healthcare. In *Proceedings of IJCAI 2021*, 2021.

T. Brázdil, A. Kučera, and V. Řehák. Solving patrolling problems in the internet environment. In *Proceedings of IJCAI 2018*, pages 121–127, 2018.

Shaofei Chen, Feng Wu, Lincheng Shen, Jing Chen, and Sarvapali D. Ramchurn. Decentralized patrolling under constraints in dynamic environments. *IEEE Transactions on Cybernetics*, 46(12):3364–3376, 2016.

Shantanu Das, Giuseppe A. Di Luna, and Leszek A. Gasieniec. Patrolling on dynamic ring networks. In *SOFSEM 2019: Theory and Practice of Computer Science*, pages 150–163. Springer, 2019.

F.M. Delle Fave, A.X. Jiang, Z. Yin, C . Zhang, M. Tambe, S. Kraus, and J. Sullivan. Game-theoretic security patrolling with dynamic exe cution uncertainty and a case study on a real transit system. *Journal of Artificial Intelligence Research*, 50:321–367, 2014.

B. Ford, D. Kar, F.M. Delle Fave, R. Yang, and M. Tambe. PAWS: adaptive game-theoretic patrolling for wildlife protection. In *Proceedings of AAMAS 2014*, pages 1641–1642, 2014.

Hsi-Ming Ho and J. Ouaknine. The cyclic-routing UAV problem is PSPACE-complete. In *Proceedings of FoS-SaCS 2015*, volume 9034 of *LNCS*, pages 328–342. Springer, 2015.

Satoshi Hoshino and Kazuki Takahashi. Dynamic partitioning strategies for multi-robot patrolling systems. *Journal of Robotics and Mechatronics*, 31(4):535–545, 2019.

J. Karwowski, J. Mandziuk, A. Zychowski, F. Grajek, and B. An. A memetic approach for sequential security games on a plane with moving targets. In *Proceedings of AAAI 2019*, pages 970–977, 2019.

D. Klaška, A. Kučera, T. Lamser, and V. Řehák. Automatic synthesis of efficient regular strategies in adversarial patrolling games. In *Proceedings of AAMAS 2018*, pages 659–666, 2018.

D. Klaška, A. Kučera, and V. Řehák. Adversarial patrolling with drones. In *Proceedings of AAMAS 2020*, pages 629–637, 2020.

D. Klaška, A. Kučera, V. Musil, and V. Řehák. Regstar: Efficient strategy synthesis for adversarial patrolling games. In *Proceedings of UAI 2021*, 2021.

A. Kučera and T. Lamser. Regular strategies and strategy improvement: Efficient tools for solving large patrolling problems. In *Proceedings of AAMAS 2016*, pages 1171–1179, 2016.

Mehdi Othmani-Guibourg, Amal El Fallah-Seghrouchni, Jean-Loup Farges, and Maria Potop-Butucaru. Multi-agent patrolling in dynamic environments. In *2017 IEEE International Conference on Agents (ICA)*, pages 72–77, 2017. doi: 10.1109/AGENTS.2017.8015305.

J. Pita, M. Jain, J. Marecki, F. Ordóñez, C. Portway, M. Tambe, C. Western, P. Paruchuri, and S. Kraus. Deployed ARMOR protection: The application of a game theoretic model for security at the Los Angeles Int. Airport. In *Proceedings of AAMAS 2008*, pages 125–132, 2008.

Jinwoo Seok, Mariam Faied, and Anouck Girard. Unpredictably dynamic environment patrolling. *Unmanned Systems*, 5(4):223–236, 2017.

A. Sinha, F. Fang, B. An, C. Kiekintveld, and M. Tambe. Stackelberg security games: Looking beyond a decade of success. In *Proceedings of IJCAI 2018*, pages 5494–5501, 2018.

M. Tambe. *Security and Game Theory. Algorithms, Deployed Systems, Lessons Learned*. Cambridge University Press, 2011.

J. Tsai, S. Rathi, C. Kiekintveld, F. Ordóñez, and M. Tambe. IRIS—a tool for strategic security allocation in transportation networks categories and subject descriptors. In *Proceedings of AAMAS 2009*, pages 37–44, 2009.

Y. Wang, Z.R. Shi, L. Yu, Y. Wu, R. Singh, L. Joppa, and F. Fang. Deep reinforcement learning for green security games with real-time information. In *Proceedings of AAAI 2019*, pages 1401–1408, 2019.

L. Xu. Learning and planning under uncertainty for green security. In *Proceedings of IJCAI 2021*, 2021.

Z. Yin, D. Korzhyk, C. Kiekintveld, V. Conitzer, and M. Tambe. Stackelberg vs. Nash in security games: Interchangeability, equivalence, and uniqueness. In *Proceedings of AAMAS 2010*, pages 1139–1146, 2010.