# A Joint Training Framework for Open-World Knowledge Graph Embeddings

## Abstract

Knowledge Graphs(KGs) represent factual information as graphs of entities connected by relations. Knowledge graph embeddings have emerged as a popular approach to encode this information for various downstream tasks like natural language inference, question answering and dialogue generation. As knowledge bases expand, we are presented with newer (open-world) entities, often with textual descriptions. We require techniques to embed new entities as they arrive using the textual information at hand. This task of open-world KG completion has received some attention in recent years. However, we find that existing approaches suffer from one or more of four drawbacks – 1) They are not modular with respect to the choice of the KG embedding model 2) They ignore best practices for aligning two embedding spaces 3) They do not account for differences in training strategy needed when presented with datasets with different description sizes and 4) They do not produce entity embeddings for use by downstream tasks. To address these problems, we propose FOlK (**F**ramework for **O**pen-World **K**G embeddings) - a technique that jointly learns embeddings for KG entities from descriptions and KG structure for open-world knowledge graph completion. Additionally, we modify existing data sources and make available YAGO3-10-Open and WN18RR-Open two datasets that are well suited for demonstrating the efficacy of open-world KG completion approaches. Finally, we empirically demonstrate the effectiveness of our model in improving upon state-of-the-art baselines on several tasks resulting in performance increases of up to 72% on mean reciprocal rank.

## 1. Introduction

Knowledge graphs (KG) are facts structured in the form of a graph, where the nodes are the entities, and the edges are the relationships between those entities. For example, consider the fact "Narendra Modi is the Prime Minister of India and lives in India.". In this example, `Narendra Modi` and `India` are two entities connected by relations *isPrimeMinister* and *livesIn*. KGs are often represented in the form of triples, example, (`Narendra Modi`, *isPrimeMinister*, `India`). KG embeddings are continuous multi-dimensional vectors of entities and relations that, through a predefined scoring function, rank real facts in a knowledge base over spurious ones. KG embeddings have a number of applications ranging

from KG completion [Bordes et al., 2013] to natural language inference [Peters et al., 2019], knowledge-aware conversation generation [Zhou et al., 2018], question-answering [Saxena et al., 2020] and recommendation [Chen et al., 2019].

Large knowledge bases like DBpedia [Auer et al., 2007] rely on unstructured information sources like Wikipedia, which is growing at the rate of 602 new articles per day[1]. Applications or tasks that rely on knowledge graph embeddings require approaches to embed new entities introduced due to evolving knowledge bases. Traditional (or closed-world) KG embedding models, are limited to the transductive settings, where all the entities and the relations are known during learning. Thus, these approaches are not suitable for KG where the entities and the relations are augmented over time. An ideal KG embedding model should be able to generalise to newer (or open-world) entities and relations in the KGs without re-learning on the updated KGs. We require a method to embed any new (or open-world) entities based on the rich semantic information that exist about it in the form of new articles, and also based on the existing connections in the KG. This brings up two tasks that make use of an entity's description- (1) *Open-World KG Completion* which is the task of relating the new entity to the rest of the KG, and (2) *Open-World Entity Embedding* which is the task of producing an embedding for a new entity.

There have been a few approaches in recent years for the task of open-world KG completion or embedding generation. Studying the literature, we identify few critical properties that make an open-world KG embedding approach efficient, robust and useful for a variety of applications.

1. **Open-world Embedding Generation:** The applications created on KG like question answering or conversation generation require the embeddings of the entities and relations. The techniques like ConMask [Shi and Weninger, 2018] which are optimised for KG Completion and do not produce entity/relation embeddings cannot be used for such downstream applications. So, in addition to the task of open-world KG completion, the approaches must also embed open-world KG entities.

2. **Joint Training:** To embed open-world entities using their descriptions, we need to align two spaces – description space and KG structure space. Techniques that learn this alignment while keeping one or both of these spaces fixed are said to be *offline* training. Techniques that learn the alignment operation and individual embeddings at the same time are called *joint* training. Studies [Ormazabal et al., 2019] have shown that embeddings produced by jointly training of two spaces have significantly improved geometric properties as compared to offline training. These geometric properties are important to retain the KG structure information in the embeddings on introduction of new entities, thus, resulting in better results on downstream applications.

3. **Efficient Ranking:** To connect a new entity to the rest of KG requires ranking of potential connections. The score is generated for all possible triples which are ranked to determine top connections. In order to perform the complete ranking procedure followed by closed-world models [Bordes et al., 2013, Yang et al., 2015, Trouillon et al., 2016] the score for any triple must be of the order of the embedding dimensions. Thus the large neural networks models are not efficient as a scoring function to score all possible triples.

4. **Modular:** As observed by Chang et al.[Chang et al., 2020], different closed-world KG

---

1. https://en.wikipedia.org/wiki/Wikipedia:Statistics

embedding approaches are suitable for different applications. For instance, translational methods [Bordes et al., 2013] are better at clustering and entity classification applications, whereas multiplicative methods [Trouillon et al., 2016, Yang et al., 2015] are better at KG completion. For this reason, our open-world approach must be modular with respect to the choice of the structural embeddings to accommodate for plethora of applications.

5. **Sequence-Size Aware:** Few KGs have entities with long descriptions while others have entities with short descriptions. Any proposed approach must be efficient and perform competitively well when run on datasets with either short or long descriptions. Our contributions are summarised below. Our code and datasets are available. The key contributions of the work are:

1. We propose FO1K - the first-ever **joint**, **modular**, **efficient** and **sequence size aware** framework to produce open-world KG entity **embeddings**.
2. We empirically evaluate performance of our model on open-world KG completion, closed-world KG completion and entity classification. We demonstrate significant improvement of upto 72% on mean reciprocal rank over the state-of-the-art.

## 2. Problem Definition

Before discussing existing approaches and our solution, we give a brief introduction to the problem of learning embeddings for open-world KG entities. Knowledge graphs primarily consist of a set of entities $\mathcal{E} = \{e_1, e_2, ...e_{|\mathcal{E}|}\}$, a set of relations $\mathcal{R} = \{r_1, r_2, ...r_{|\mathcal{R}|}\}$ and a set of (head,*relation*,tail) triples $\mathcal{T} \subseteq \{\tau_i : (h_i, r_i, t_i)|h_i, t_i \in \mathcal{E}, r_i \in \mathcal{R}\}$. We refer to the entity set $\mathcal{E}$ that we have relationship information for as the *closed* or *structural* entity set. In many real world scenarios we often have the descriptions of each entity in our knowledge graph. We denote the description set as $\mathcal{D} = \{d_1, d_2, ...d_{|\mathcal{E}|}\}$. $\boldsymbol{e_i}$ and $\boldsymbol{r_i}$ are real (or complex valued) vectors or embeddings. $\boldsymbol{e_i}, \boldsymbol{r_i} \in \mathbb{R}^\delta$ (where $\delta$ denotes the embedding dimension), in the case of models like TransE [Bordes et al., 2013] or DistMult [Yang et al., 2015]. $\boldsymbol{e_i}, \boldsymbol{r_i} \in \mathbb{C}^\delta$ in the case of models like ComplEx [Trouillon et al., 2016]. Throughout we use boldface to indicate the vector embedding corresponding to an entity or relation. We use $\boldsymbol{h}$, $\boldsymbol{r}$ and $\boldsymbol{t}$ to denote head, relation and tail embeddings respectively, in a triple. Entities in a knowledge graph may appear as heads, tails or both. As knowledge bases expand we are presented with a new set of entities $\mathcal{E}' = \{e_1', e_2', ...e_{|\mathcal{E}'|}'\}$ and their corresponding descriptions $\mathcal{D}' = \{d_1', d_2', ...d_{|\mathcal{E}'|}'\}$. Our task is to embed the open entity set $\mathcal{E}'$ using $\mathcal{D}'$.

## 3. Related Work

In this section, we briefly summarise state of the art closed-world or structural KG embedding approaches, approaches with open-world entities and their limitations.

**Structural KG Embeddings:** These models use only the triple or structural information available in KG. Most models are learnt by minimising an energy function on $(\boldsymbol{h}, \boldsymbol{r}, \boldsymbol{t})$ triples through negative sampling. TransE [Bordes et al., 2013] uses a translational energy function whereas DistMult [Yang et al., 2015] and ComplEx [Trouillon et al., 2016] uses multiplicative energy functions. The energy and loss functions of all three methods are detailed in Table 8.

**Approaches with open-world entities:** These models use additional textual descriptions of the entities along with structural information available in KG.(1) **DKRL** [Xie et al., 2016], constructs two separate spaces - the structural embedding space and the description embedding space and align the two using a version of the cross-completion loss we discuss in Section 6.3.1. A key limitation of this approach is its inability to generate embeddings for new open-world entities as a consequence of training the two embeddings in separate spaces. (2) **JointE** [Zhao et al., 2017], uses tf-idf weighted bag-of-words features to encode a description and propose a custom multiplicative energy function to score a triple. The approach is not modular hence limits the usability of approach for specific applications. Similarly, (3) **ConMask** [Shi and Weninger, 2018] model also uses a custom energy function to score a triple. A triple is scored using a combination of multiple features generated using masked fusion of the entity description with entity and relation names. The usage large neural network model to score a triple limits the scalability of model to score all possible triples, thus filtering based methods are used to filter out certain triples resulting in information loss. Further details to be discussed in Sections 6.2 and 6.3. In (4) **OWE**, the authors induce new embeddings in KG entity space by learning a projection matrix offline to align descriptions to KG structure. Such a technique is offline as the KG embeddings are pre-trained and not modified at alignment time. We discuss the limitations of such an approach in Section 6.3.

## 4. Proposed FO1K Model

Figure 1: An illustration of FO1K's architecture

Overall architecture of our framework, FO1K, is represented in Figure 1. It has three components (1) Structural Embedding module to learn the embeddings of the entities and relations already existing in KG (2) Description Embedding module which is an encoder to represent the textual information of open-world as well as closed-world entities. (3) Description projection module to project the description to a space where the structure and description embeddings are aligned, this represents the KG embedding space used for any of the downstream task like KG completion or entity classification. When presented with a new entity, we induce the KG embedding by encoding it's description and projecting

it to KG embedding space. Below sections will discuss these modules in details along with various training strategies that we have used.

## 4.1 Structural Embeddings

Our framework is agnostic to the choice of the structural KG embedding model. Unless otherwise specified, we use ComplEx as our default method as it has out-performed other structural embedding methods as reported in a recent survey paper [Dai et al., 2020].

We briefly explain a few notations before discussing how structural embeddings are trained. Let $\mathcal{E}^{test}$ and $\mathcal{E}^{valid}$ be the open-world test and validation sets of entities that are not available in training set. We denote the train, validation and test splits of the triple set $\mathcal{T}$ by $\mathcal{T}_{train}$, $\mathcal{T}_{valid}$ and $\mathcal{T}_{test}$. $\mathcal{T}_{test}^{open}$ and $\mathcal{T}_{valid}^{open}$ denote the test and validation sets of triples where either the head or tail of each triple occurs in $\mathcal{E}^{test}$ or $\mathcal{E}^{valid}$ respectively. We augment the train split $\mathcal{T}_{train}$ with corrupted triplets, i.e, $\mathcal{T}_{corr} \subseteq \{\tau_{corr.i} : (h_i, r_i, t_i)|h_i, t_i \in \mathcal{E}, r_i \in \mathcal{R}, (h_i, r_i, t_i) \notin \mathcal{T}_{train}\}$ to obtain $\mathcal{T}^{\circ} = \mathcal{T}_{train} \cup \mathcal{T}_{corr}$. We use the indicator variable $I_{h,r,t} \in \{1, -1\}$ to return 1 (or -1) corresponding to whether $(h, r, t) \in \mathcal{T}_{train}$ (or not). We denote the parameters of this module (the real or complex embeddings) by $\mathbf{\Theta_S}$. The energy and loss functions of TransE, DistMult and ComplEx can be found in Table 8. We also include a regularization loss term $\mathscr{L}_{reg}$ which is the average squared $\ell_2$-norm of all the structural embeddings with the regularization parameter $\lambda$.

## 4.2 Induced Embeddings

To induce new embeddings for open-world entities, we learn to encode and project entity descriptions to KG entity space at train time.

**Description Encoding:** In order to make our framework sequence-size-aware, we use various text embedding approaches to encode description of an entity depending on the size of description. When presented with short (ten or fewer words) entity descriptions, we use Continuous Bag-of-words (CBOW) encoder which assumes that similar entities should have related keywords. The representation of the entity, $\mathbf{\Theta_{D_s}}$ (where $s$ denotes *short* description), is determined with the summation of the representation of the keywords. The representation of the keywords is learned using pre-trained word2vec [Mikolov et al., 2013] embedding of 256 dimensions. When presented with long entity description we need to capture more complex interactions hence we use transformer-based model RoBERTa[Devlin et al., 2018] which uses attention or differential weighing of different part of the description to capture most significant information. To the best of our knowledge, FO1K is the first framework to use a transformer-based encoder to embed open-world entities. RoBERTa tokenizes each input sentence, the output at the final layer is a 768-dimensional vector. The entity description $\mathbf{\Theta_{D_l}}$ (where $l$ denotes *long* description) is generated by taking the average embedding of all the tokens.

**Description Projection:**  We use an affine transformation function to project the description encoding of an embedding $\phi_{D}(e)$ to the KG embedding space such that it is aligned with structural embedding space. The projection parameters are trained jointly, in tandem with the rest of the model.

$$\phi_P(e) = M\phi_D(e) + b + i(M_i\phi_D(e) + b_i) \tag{1}$$

$M$ and $b$ project the description embedding to to the real space and $M_i$ and $b_i$ project to the imaginary space. Equation 1 is applicable when projecting to the embedding space of ComplEx which uses both real and imaginary space. If the embedding space only has a real component as in TransE or DistMult, we only use the real transformation matrix and bias. We denote these parameters of the projection module by $\mathbf{\Theta_P}$.

### 4.3 Cross-Domain Alignment

For cross-domain alignment we have used skipgram objective similar the work of BiSkip, [Luong et al., 2015] from cross-lingual learning domain, which uses skipgram objective to maximize the probability of a target language word given the source language context. We find that including such cross-modality objectives in addition to vanilla projection loss consistently improves performance. We treat an entity's immediate graph neighbourhood as its context and use skipgram objective to maximize the probability of the entity given the neighbourhood entities. The loss term $\mathscr{L}_X$ (X for cross) is represented in Equation 2. We call this the cross-domain KG completion or cross-completion term.

$$\mathscr{L}_X(h,r,t) = \mathscr{L}(\boldsymbol{h}, \boldsymbol{r}, \boldsymbol{\phi_P}(\boldsymbol{\phi_D}(\boldsymbol{t}))) + \mathscr{L}(\boldsymbol{\phi_P}(\boldsymbol{\phi_D}(\boldsymbol{h})), \boldsymbol{r}, \boldsymbol{t}) \tag{2}$$

The overall loss function is represented in Equation 3. We demonstrate the effectiveness of the cross-domain terms empirically in Table 6 and Section 6.3.

$$\mathscr{L}_{\texttt{FO1K}} = \overbrace{\mathscr{L} + \lambda\mathscr{L}_{reg}}^{\text{closed-world completion}} + \overbrace{\alpha\mathscr{L}_{proj} + \beta\mathscr{L}_X}^{\text{open-world alignment}} \tag{3}$$

### 4.4 Training Strategy

Utilising a large contextual model like RoBERTa necessitates an appropriate training strategy. This is because RoBERTa takes a few hours per epoch to fine-tune and converges in around 2-3 epochs for long descriptions, while structural KG embedding methods takes a few minutes per epoch and requires anywhere between 100-400 epochs to converge. So we adopt a novel phase-wise training approach to train all three modules. We optimise the same loss term $\mathscr{L}_{\texttt{FO1K}}$ but separate the training of the closed-world embedding module ($\mathbf{\Theta_S}$) and the description encoding and projection modules ($\mathbf{\Theta_D}$ and $\mathbf{\Theta_P}$) into separate phases, each trained to convergence. The detailed algorithm is present in supplemetary section 1.

We minimise the objective $\mathscr{L}_{\texttt{FO1K}}$ (Equation 3) using batch-wise stochastic gradient descent, with $\mathbf{\Theta_S}$ and $\mathbf{\Theta_P}$ initialised at random. We minimise $\mathscr{L}_{\texttt{FO1K}}$ training all 3 sets of parameters - $\mathbf{\Theta_S}$, $\mathbf{\Theta_{D_s}}$ and $\mathbf{\Theta_P}$.

## 5. Datasets

We have evaluated our model on following datasets: **FB15k-237-OWE** [Shah et al., 2019] & **FB15k-237-OWE(L):** FB15k-237-OWE paired with descriptions from Freebase which are of longer lengths, is called the FB15k-237-OWE(L) dataset. **YAGO3-10-Open:** YAGO3-10 [Dettmers et al., 2018] is a subset of the YAGO[2] knowledge base. We use DBpedia to extract long descriptions of the entities. **WN18RR-Open** WN18RR [Dettmers

---

2. https://yago-knowledge.org/

et al., 2018] derived from WordNet, we use the synset definitions from WordNet as descriptions. For the statistics of our datasets please refer to Table 1.

Table 1: Dataset Statistics. $\overline{|d|}$ is the average entity description length. $|c.c|$ is the number of connected components in the train graph. DSA is the Description-Structure Alignment score. Please refer to Section 5 for more details.

| Dataset | Entities Statistics | | | | | | Relationships Statistics | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | $|\mathcal{E}|$ | $|\mathcal{E}'|$ | $|\mathcal{R}|$ | $\overline{|d|}$ | DSA | $|c.c|$ | $|\mathcal{T}_{train}|$ | $|\mathcal{T}_{test}^{open}|$ | $|\mathcal{T}_{valid}^{open}|$ | $|\mathcal{T}_{test}|$ | $|\mathcal{T}_{valid}|$ |
| FB15k-237-OWE | 12324 | 2081 | 235 | 4.9 | 12.4 | 2 | 242489 | 22393 | 9424 | 7806 | 5000 |
| FB15k-237-OWE(L) | | | | 138.7 | 12.6 | | | | | | |
| YAGO3-10-Open | 107327 | 11443 | 32 | 94.0 | 4.4 | 1 | 769694 | 56334 | 37557 | 39794 | 26533 |
| WN18RR-Open | 36119 | 4824 | 11 | 12.9 | 4.9 | 1 | 69122 | 4962 | 3308 | 3133 | 2086 |

**DSA Score**: We report a simple heuristic to measure the relative difficulties of aligning the description and structure embedding spaces across datasets. The Description-Structure Alignment (DSA) score is a measure of the pre-existing alignment between the descriptions of the entities and the KG structure embeddings. We construct a nearest-neighbour graph from the pre-trained KG embeddings in $\mathcal{E}$ with an average out-degree of 100. We follow the same procedure to construct a nearest-neighbour description graph using the averaged Word2Vec embeddings of the descriptions. The DSA score is the edge-overlap between the two graphs, divided by the number of nodes: $|ES_{.1} \cap ES_2|/|\mathcal{E}|$, where $ES_{.1}$ and $ES_2$ are the two edge sets. A higher value indicates better initial alignment, and therefore an easier alignment task.

## 6. Experiments

Through our experiments, we address the following research questions:
- **RQ1:** What is the quality of the open-world embeddings generated by FO1K?
- **RQ2:** How well does FO1K satisfy the properties outlined in Section 1?
- **RQ3:** What are the contributions of each of our model components?

### 6.1 Training

We train both FO1K(s) and FO1K(l) through batch-wise stochastic gradient descent (SGD). For FO1K(s), the learning rate and negative sample rate are the same as the best parameters for the structural model. For information on the hyperparameters of the structural model, please refer to the additional material. Training the structural model by minimising $\mathbf{\Theta_S}$ on $\mathcal{L} + \lambda\mathcal{L}_{reg}$ is an initialisation step for FO1K(l). In phase 2 of FO1K(l), we train $\mathbf{\Theta_{D_l}}$ and $\mathbf{\Theta_P}$ using Adam with a learning rate of 0.00005. In phase 1, $\mathbf{\Theta_S}$ is trained using the same hyperparameters used by the structural model. $\beta$ is always set to 1. For both FO1K(s) and phase 1 of FO1K(l), we find that an optimal value of $\alpha$ is 0.001, across datasets. During phase 2 of FO1K(l), $\alpha$ is always set to 1.

### 6.2 Experimental Setup

We study our research questions using four tasks – (1) Open-World KG Completion (2) Closed world KG Completion (3) Entity Classification (4) Geometric properties of the in-

Table 2: Comparing open-world KG completion results on FB15k-237-OWE, a dataset with short description.[3]

| Model | FB15k-237-OWE | | | |
|---|---|---|---|---|
| | MRR | H@1 | H@3 | H@10 |
| JointE | 6.7 | 2.5 | 7.0 | 14.2 |
| DKRL-CNN | 19.0 | 13.0 | 21.2 | 31.0 |
| DKRL-CBOW | 19.3 | 13.1 | 21.5 | 31.9 |
| ConMask | 9.1 | 3.7 | 9.5 | 20.5 |
| OWE | 35.2 | 27.8 | 38.6 | 49.1 |
| FO1K(l) iter. 1 | 38.8 | 29.9 | 42.6 | 54.5 |
| FO1K(l) iter. 2 | **39.1** | **32.1** | 42.5 | 52.1 |
| FO1K(s) | **39.1** | 30.3 | **43.0** | **56.1** |

Table 3: Performance comparison on closed-world KG completion on FB15k-237-OWE.

| Model | FB15k-237-OWE | | | |
|---|---|---|---|---|
| | MRR | H@1 | H@3 | H@10 |
| ComplEx | 35.6 | 24.3 | 41.2 | 57.3 |
| FO1K(s) | **38.1** | **26.5** | **44.3** | **61.6** |

duced embeddings. The details of these tasks are discussed in this section.

**Open-World KG Completion and Closed-World KG Completion:** For the KG completion tasks (Tables 2, 4, 3, 11), we follow the filtered ranking procedure introduced by Bordes et al. [Bordes et al., 2011]. In *filtered* ranking, we remove the correct answers that occur in the training set from $\mathcal{E}$ before performing the ranking operation. That is, when ranking tails for $(h_i, r_i)$ we remove all $\{t|(h_i, r_i, t) \in \mathcal{T}_{train}\}$ from $\mathcal{E}$.

**Entity Classification:** We follow the same procedure as in [Xie et al., 2016] to identify entity type information from Freebase for classification. We set up a classification task on the embeddings by training one-vs-rest logistic classifiers on entities in $\mathcal{E}$. We then test the performance of our model on the open-world embeddings generated for entities in $\mathcal{E}'$. We report micro-f1 and macro-f1 scores.

### 6.3 Analysis

Table 4: Performance comparison on open-world KG completion across various datasets with long description. The results reported are for filtered evaluation (not target-filtered)[3]. More details in Sections 6.2 and 6.3.

| Model | YAGO3-10-Open | | | | WN18RR-Open | | | | FB15k-237-OWE(L) | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | MRR | H@1 | H@3 | H@10 | MRR | H@1 | H@3 | H@10 | MRR | H@1 | H@3 | H@10 |
| JointE | 5.1 | 1.8 | 4.5 | 11.0 | 8.2 | 4.5 | 8.2 | 16.0 | 10.3 | 5.1 | 10.9 | 20.0 |
| DKRL-CNN | 2.6 | 1.5 | 2.2 | 4.1 | 2.5 | 1.1 | 2.4 | 5.1 | 19.9 | 13.9 | 21.7 | 32.1 |
| DKRL-CBOW | 2.7 | 1.6 | 2.4 | 4.2 | 2.4 | 1.0 | 2.3 | 4.9 | 20.7 | 14.5 | 22.6 | 33.4 |
| ConMask | 17.3 | 10.3 | 18.9 | 31.3 | 23.3 | 10.3 | 22.7 | 38.4 | 21.1 | 14.0 | 23.4 | 34.6 |
| OWE | 21.6 | 14.9 | 23.3 | 34.3 | 21.7 | 17.3 | 23.4 | 29.4 | 32.4 | 25.1 | 35.6 | 46.0 |
| FO1K(l). iter. 1 | 25.7 | 19.0 | 27.5 | 38.9 | 35.6 | 30.9 | 37.9 | 45.5 | 42.4 | 33.6 | 45.7 | 57.2 |
| FO1K(l). iter. 2 | **26.5** | **19.5** | **28.0** | **40.0** | **40.3** | **32.2** | **40.8** | **50.0** | **43.6** | **34.8** | **47.6** | **59.8** |

---

3. Please take note of the filtering used when comparing results across papers. In OWE, the results reported in Table 3 of the original paper are target-filtered. The results in Table 4 of the original paper are filtered. For reasons explained in Section 6.2 we only report filtered results in this work.

6.3.1 RQ1 - Open-World Embedding Quality:

The results of FO1K on open-world KG completion are presented in Tables 2 and 4. Table 2 presents results on FB15k-237-OWE, a dataset with short descriptions. Table 4 presents results on datasets with long descriptions. FO1K significantly outperforms baselines with an average MRR improvement of 35% across all datasets and an improvement of 72% on WN18RR-Open. YAGO3-10-Open, FB15k-237-OWE and FB15k-237-OWE(L) (along with Dbpedia and FB20k used by other baselines) all have either entities or descriptions derived from Wikipedia. Hence, WN18RR-Open is an important dataset to compare with to evaluate the performance on KGs from other domains. RoBERTa's large-scale pre-training ensures that FO1K is fairly robust to such domain shifts.

DKRL's poor performance on YAGO3-10-Open and WN18RR-Open is partly due to alignment issues. As can be seen in Table 1, WN18RR-Open and YAGO3-10-Open have Description-Structure Alignment scores 60% and 65% lower than that of FB15k-237-OWE respectively, making them harder alignment problems. Part of the problem is also the specifics of DKRL's training strategy being unable to scale to large graphs.

We note another drawback of the target-filtered setting used by ConMask here. In addition to limiting the connections we can discover, target-filtering also obscures poor performance. In a target-filtered setting for ConMask and FB15k-237-OWE, we get similar results as those reported in OWE. But without target-filtering we see a large performance drop-off of 83% in Hits@1 (Table 2).

On the task of open-world entity classification also, we see dramatic improvements (Table 5), with an macro-f1 score improvement of 33%. Wherever we use FO1K(l), we also indicate the performance improvement across iterations.

Table 5: Comparing open-world KG embedding techniques for the task of entity classification.

|  | FB15k-237-OWE(L) | |
| Model | macro-f1 | micro-f1 |
|---|---|---|
| OWE | 56.1 | 58.5 |
| FO1K(l). iter. 1 | 73.2 | 80.3 |
| FO1K(l). iter. 2 | **74.8** | **81.7** |

Table 6: Ablation Studies on FB15k-237-OWE(L)

| Model | MRR | H@1 | H@3 | H@10 |
|---|---|---|---|---|
| M1. FO1K(s) w/out $\beta\mathcal{L}_X$ | 33.6 | 25.6 | 36.9 | 49.0 |
| M2. FO1K(s) w/out $\alpha\mathcal{L}_{proj}$ | 34.5 | 26.2. | 37.1 | 50.9 |
| M3. FO1K(s) | 37.5 | 29.0 | 40.9 | 55.7 |
| M4. FO1K(l) w/out $\beta\mathcal{L}_X$ | 42.5 | 34.5 | 46.2 | 57.7 |
| M5. FO1K(l) w/out $\alpha\mathcal{L}_{proj}$ | 15.8 | 11.2 | 18.1 | 26.0 |
| M6. FO1K(l) | **43.6** | **34.8** | **47.6** | **59.8** |

Table 7: FO1K's performance on open-world KG completion, paired with different closed-world embedding approaches. OWE's results are taken directly from their paper. We use FO1K(s) as the dataset is FB15k-237-OWE.

|  | TransE | | | | DistMult | | | | ComplEx | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
|  | MRR | H@1 | H@3 | H@10 | MRR | H@1 | H@3 | H@10 | MRR | H@1 | H@3 | H@10 |
| OWE | 28.7 | 21.9 | 31.7 | 41.0 | 34.4 | 26.6 | 37.7 | 49.2 | 35.2 | 27.8 | 38.6 | 49.1 |
| FO1K(s) | **42.3** | **33.2** | **46.4** | **59.4** | **37.0** | **28.5** | **40.0** | **53.2** | **39.1** | **30.3** | **43.0** | **56.1** |

**RQ2 - Properties: (1)Ranking**: We computed the time taken to complete filtered ranking on $\mathcal{T}_{test}^{open}$ on an NVIDIA Tesla V100 with 32GB of VRAM. We observe, on aver-

age, a 22x speedup using simple embedding energy functions for scoring rather than large networks. ConMask's ranking is inefficient to enumerate every possible fact in a graph. For e.g., on Yago3-10-open ConMask takes 371 seconds, while `FO1K` takes 71 seconds. **(2 and 3) Joint Training and Embedding Generation:** The effect of generating embeddings for open-world entities is that we can perform downstream tasks on them without having to retrain our knowledge base. For instance, we can not perform the open-world classification (5) experiment on DKRL or ConMask as they do not generate embeddings for open-world entities. We also note that the embeddings generated with joint training are more homogeneous in the embedded space. **(4) Modular:** From Table 7 we observe that `FO1K` can accomodate a variety of structural energy functions, obtaining an average MRR improvement of 23%. It is interesting to observe here that despite TransE having 8% improved open-world performance on `MRR` over ComplEx, ComplEx has superior closed-world performance (not shown in the table - `MRR` of 38.6 vs `MRR` of 26.5). This lends further support to allowing modular energy functions, based on the application. **(5) Sequence Size Aware:** The results presented in Tables 4 and 2 indicate that `FO1K`(l) performs competitively regardless of description length. Table 2 indicates that `FO1K`(s) has similar performance and is sufficient for SOTA results on datasets with short descriptions. We don't observe a performance benefit to using a CNN in DKRL (Tables 4, 2). This suggests that incorporating larger encoders is non-trivial and requires a more careful consideration of training strategy.

(a) `FO1K`(s) on FB15k-237-OWE

(b) `FO1K`(l) on FB15k-237-OWE(L)

(c) OWE on FB15k-237-OWE

(d) OWE on FB15k-237-OWE(L)

Figure 2: Visualization of embeddings using PCA to project to 3D space. The closed-world and projected embeddings are differentiated by red and blue dots respectively. `FO1K` embeddings are indistinguishable from each other. In OWE, the two embeddings cluster separately.

**RQ3: Contributions of Our Model Components** Ablation studies on FB15k-237-OWE(L) are presented in Table 6. `FO1k`(s) (M1,M2,M3) in the Table 6 only denotes a model choice, the dataset used is FB15k-237-OWE(L) throughout. We observe that using RoBERTa contributes to a 16% `MRR` improvement (M6 vs M3). Omitting $\alpha\mathcal{L}$ results in an average decrease of 35% in `MRR`. Similarly, omitting $\beta\mathcal{L}_{\mathcal{X}}$ results in an average decrease of 6%. The performance variation across the iterations of `FO1K`(l) is indicated in Tables 2, 4 and 5. The fact that performance increases uniformly (10% in Hits@10 in the case of WN18RR, Table 4) across iterations lends strong support to iterative phasewise alignment.

## References

Sören Auer, Christian Bizer, Georgi Kobilarov, Jens Lehmann, Richard Cyganiak, and Zachary Ives. Dbpedia: A nucleus for a web of open data. In *The semantic web*, pages 722–735. Springer, 2007.

Antoine Bordes, Jason Weston, Ronan Collobert, and Yoshua Bengio. Learning structured embeddings of knowledge bases. In *Proceedings of AAAI 2011*, AAAI'11, page 301–306. AAAI Press, 2011.

Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. In *NIPS*, pages 2787–2795, 2013.

David Chang, Ivana Balazevic, C. Allen, Daniel G Chawla, C. Brandt, and R. Taylor. Benchmark and best practices for biomedical knowledge graph embeddings. *ArXiv*, abs/2006.13774, 2020.

Qibin Chen, Junyang Lin, Yichang Zhang, Ming Ding, Yukuo Cen, Hongxia Yang, and Jie Tang. Towards knowledge-based recommender dialog system. In *EMNLP-IJCNLP 2019*, pages 1803–1813. ACL, November 2019. doi: 10.18653/v1/D19-1189.

Yuanfei Dai, Shiping Wang, Naixue Xiong, and Wenzhong Guo. A survey on knowledge graph embedding: Approaches, applications and benchmarks. *Electronics*, 9:750, 05 2020. doi: 10.3390/electronics9050750.

Tim Dettmers, Minervini Pasquale, Stenetorp Pontus, and Sebastian Riedel. Convolutional 2d knowledge graph embeddings. In *Proceedings of AAAI 2018*, pages 1811–1818, February 2018.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Thang Luong, Hieu Pham, and Christopher D. Manning. Bilingual word representations with monolingual quality in mind. In *Proceedings of the 1st Workshop on Vector Space Modeling for NLP*, pages 151–159. ACL, June 2015. doi: 10.3115/v1/W15-1521.

Tomas Mikolov, Kai Chen, Greg S. Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space, 2013.

Aitor Ormazabal, Mikel Artetxe, Gorka Labaka, Aitor Soroa, and Eneko Agirre. Analyzing the limitations of cross-lingual word embedding mappings. In *Proceedings of ACL 2019*, pages 4990–4995. ACL, July 2019. doi: 10.18653/v1/P19-1492.

Matthew E. Peters, Mark Neumann, Robert L Logan, Roy Schwartz, Vidur Joshi, Sameer Singh, and Noah A. Smith. Knowledge enhanced contextual word representations. In *EMNLP*, 2019.

Apoorv Saxena, Aditay Tripathi, and Partha Talukdar. Improving multi-hop question answering over knowledge graphs using knowledge base embeddings. In *Proceedings ACL 2020*, pages 4498–4507. ACL, July 2020.

Haseeb Shah, Johannes Villmow, Adrian Ulges, Ulrich Schwanecke, and Faisal Shafait. An open-world extension to knowledge graph completion models. In *Proceedings of AAAI 2019*, volume 33, pages 3044–3051, 2019.

Baoxu Shi and Tim Weninger. Open-world knowledge graph completion. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *Proceedings of ICML 2016*, ICML'16, page 2071–2080. JMLR.org, 2016.

Ruobing Xie, Zhiyuan Liu, Jia Jia, Huanbo Luan, and Maosong Sun. Representation learning of knowledge graphs with entity descriptions. In *AAAI*, 2016.

Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. Embedding entities and relations for learning and inference in knowledge bases. In Yoshua Bengio and Yann LeCun, editors, *ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015.

Yu Zhao, Sheng Gao, Patrick Gallinari, and Jun Guo. Zero-shot embedding for unseen entities in knowledge graph. *IEICE Transactions on Information and Systems*, E100.D: 1440–1447, 07 2017. doi: 10.1587/transinf.2016EDP7446.

Hao Zhou, Tom Young, Minlie Huang, Haizhou Zhao, Jingfang Xu, and Xiaoyan Zhu. Commonsense knowledge aware conversation generation with graph attention. In *Proceedings IJCAI 2018*, IJCAI'18, page 4623–4629. AAAI Press, 2018. ISBN 9780999241127.

## 7. Appendix

### 7.1 The Energy and Loss functions we use in our model

Table 8: The Energy and Loss functions we use in our model

| Embedding Method | Energy Function ($\mathscr{E}$) | Loss Function ($\mathscr{L}$) |
|---|---|---|
| TransE | $\mathscr{E}(h,r,t) = \|\boldsymbol{h} + \boldsymbol{r} - \boldsymbol{t}\|_2$ | $\mathscr{L} = \sum\limits_{(h,r,t)\in\mathcal{T}} \sum\limits_{(h^\circ,r^\circ,t^\circ)\in\mathcal{T}^{corr}} [\alpha + \mathscr{E}(h,r,t) - \mathscr{E}(h^\circ,r^\circ,t^\circ)]_+$ |
| DistMult | $\mathscr{E}(h,r,t) = \langle\boldsymbol{h},\boldsymbol{r},\boldsymbol{t}\rangle$ | $\mathscr{L} = \sum\limits_{(h,r,t)\in\mathcal{T}^\circ} log(1 + exp(-I_{h,r,t}\mathscr{E}(h,r,t)))$ |
| ComplEx | $\mathscr{E}(h,r,t) = Re(\langle\boldsymbol{h},\boldsymbol{r},\bar{\boldsymbol{t}}\rangle)$ | $\mathscr{L} = \sum\limits_{(h,r,t)\in\mathcal{T}^\circ} log(1 + exp(-I_{h,r,t}\mathscr{E}(h,r,t)))$ |

Figure 3: The probability contour plots for $\hat{\boldsymbol{h}}$, $\hat{\boldsymbol{r}}$ and $\hat{\boldsymbol{t}}$ are shown in green. Fig. (a) depicts the variance around $\boldsymbol{t}$ using only $\hat{\boldsymbol{t}}$ as an estimate. Fig. (b) depicts the variance around $\boldsymbol{t}$ using only $\hat{\boldsymbol{h}} + \hat{\boldsymbol{r}}$ as an estimate. Fig. (c) depicts the variance around $\mathbf{t}$ using an average of the two as the true estimate.

## 7.2 Folk training algorithm

---
**Algorithm 1:** Algorithm for `FOlK`(l)

---
**Input:** Triplets: $\mathcal{T}_{train}$, $\mathcal{T}_{valid}$, $\mathcal{T}_{valid}^{open}$
**Output:** $\boldsymbol{\Theta_S}, \boldsymbol{\Theta_{D_l}} \boldsymbol{\Theta_P}$
Initialise $\boldsymbol{\Theta_{D_l}}$ on RoBERTa's pre-training tasks
Initialise $\boldsymbol{\Theta_S}$ and $\boldsymbol{\Theta_P}$
**while** *MRR no longer improves on* $\mathcal{T}_{valid}$ **do**
  | Train $\boldsymbol{\Theta_S}$ by optimising $\mathscr{L} + \lambda\mathscr{L}_{reg}$;
**end**
$i \leftarrow 0$
**while** *MRR no longer improves on* $\mathcal{T}_{valid}^{open}$ **do**
  | Phase 1: Freeze $\boldsymbol{\Theta_{D_l}}$ and $\boldsymbol{\Theta_P}$
  | **if** $i \neq 0$ **then**
  |   | Train $\boldsymbol{\Theta_S}$ by optimising $\mathscr{L} + \lambda\mathscr{L}_{reg} + \alpha\mathscr{L}_{proj} + \beta\mathscr{L}_X$; // `Until MRR no`
  |   |   `longer improves on` $\mathcal{T}_{valid}$
  | **end**
  | Phase 2: Freeze $\Theta_S$
  | Train $\boldsymbol{\Theta_{D_l}}$ and $\boldsymbol{\Theta_P}$ by optimising $\alpha\mathscr{L}_{proj} + \beta\mathscr{L}_X$; // `//Until MRR no longer`
  |   `improves on` $\mathcal{T}_{valid}^{open}$
  | `//`
  | $i \leftarrow i + 1$;
**end**

---

## 7.3 Loss Terms — Intuition

We explain why we need additional loss terms when they seem to enforce the same objective as $\mathscr{L}_{proj}$. We argue that in a stochastic setting, the three loss terms' summation gives us the lowest variance estimate of the ideal embeddings. The reasoning is along the same lines as how bagging reduces model variance as long as the errors are uncorrelated. We explain the

intuition behind this through Fig. 3 and demonstrate the effectiveness of the cross-domain tasks empirically in Table 6.

Let's consider for simplicity, the translational framework of TransE. Consider three embeddings - $\hat{h}, \hat{r}, \hat{t}$ normally distributed around the *ideal* embeddings - $h, r, t$ with approximately equal diagonal variance $\sigma^2$. During training we'd like to align the projected embedding tail to the ideal tail embedding $\mathbf{t}$. If we minimise $\mathscr{L}_{proj}$ on its own we use $\hat{t}$ as an estimate of $t$, resulting in a variance of $\sigma^2$ around the true tail. Similarly using $\mathscr{L}_X$ gives us a variance of $2\sigma^2$. Averaging the two estimates, i.e. minimising $\mathscr{L}_X + \mathscr{L}_{proj}$ gives us the lowest variance - $3/4\sigma^2$ (follows from the addition of uncorrelated gaussian random variables), *provided* $\hat{h} + \hat{r}$ and $\hat{t}$ are uncorrelated. We observe that this is the case empirically. The mean absolute correlation between any two dimensions of the two vectors starts off at 0.02 and tapers off at 0.07

### 7.4 Structural Embeddings — Hyperparameters

We use pre-trained structural embeddings as an initialization for `FO1K`(l). For this, we only perform a hyperparameter search on ComplEx. Our hyperparameter choice here is based on the best `MRR` performance on the closed-world validation set and so, can be computed efficiently using fast KG embedding libraries like OpenKE[4]. For many popular KG datasets and embedding models, these values are publically available. We don't finetune these parameters to improve open-world performance. For training ComplEx embeddings, as recommended by the original paper we vary the learning rate in {1.0, 0.5, 0.1, 0.05, 0.01}, the number of negative samples in {1,10,100} and $\lambda$ in {0, 0.1, 1}.

We use 300-dimensional embeddings throughout. We use the same optimal parameters for `FO1K`(s). During the training of `FO1K`(s) and subsequent iterations of phase 1 of `FO1K`(l), we reduce the number of negative samples for WN18RR-Open and YAGO3-10-Open to 10 for computational efficiency.

Table 9: Hyperparameter settings for training the structural embeddings of ComplEx on different datasets.

| Dataset | Learning Rate | # -ve samples | $\lambda$ |
|---------|---------------|---------------|-----------|
| WN18RR-Open | 0.01 | 100 | 1 |
| FB15k-237-OWE | 0.03 | 1 | 0 |
| YAGO3-10-Open | 0.05 | 100 | 0.1 |

We take the optimal hyperparamters for FB15k-237-OWE on ComplEx, DistMult and TransE from the implementation of OWE. TransE's margin parameter is set to 1.

Table 10: Hyperparameter setting for different structural models on FB15k-237-OWE

| Structural Model | Learning Rate | # -ve samples | $\lambda$ |
|------------------|---------------|---------------|-----------|
| TransE | 0.1 | 1 | 0 |
| DistMult | 0.01 | 1 | 0 |
| ComplEx | 0.03 | 1 | 0 |

---

4. https://github.com/thunlp/OpenKE

### 7.5 Closed-World Performance:

The closed-world KG completion performance of FO1K compared to the performance of the base KG embedding method, ComplEx is presented in Tables 3 and 11. Rather than affecting closed-world performance, joint training elicits an average MRR improvement of 5%. We observe that this improvement is largely due to entities missing key relations in the KG. Training jointly with descriptions acts as a regularizer, ensuring these entities are embedded in correct local neighbourhoods, despite the missing relations.

Table 11: Performance on closed-world KG completion compared with our base KG embedding model, ComplEx. All of the datasets in this comparison have long descriptions.

| Model | YAGO3-10-Open | | | | WN18RR-Open | | | | FB15k-237-OWE(L) | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | MRR | H@1 | H@3 | H@10 | MRR | H@1 | H@3 | H@10 | MRR | H@1 | H@3 | H@10 |
| ComplEx | 40.4 | 31.8 | 45.0 | 57.2 | 48.5 | **45.8** | 50.0 | 53.5 | 35.6 | 24.3 | 41.2 | 57.3 |
| FO1K(l) iter. 2 | **41.2** | **32.3** | **46.2** | **60.8** | **50.4** | 45.5 | **50.4** | **55.6** | **37.6** | **27.5** | **43.6** | **59.3** |