Efficient and Differentiable Conformal Prediction with General Function Classes

Abstract

Quantifying the data uncertainty in learning tasks is often done by learning a prediction interval or prediction set of the label given the input. Two commonly desired properties for learned prediction sets are *valid coverage* and *good efficiency* (such as low length or low cardinality). Conformal prediction is a powerful technique for learning prediction sets with valid coverage, yet by default its conformalization step only learns a single parameter, and does not optimize the efficiency over more expressive function classes.

In this paper, we propose a generalization of conformal prediction to multiple learnable parameters, by considering the constrained empirical risk minimization (ERM) problem of finding the most efficient prediction set subject to valid empirical coverage. This meta-algorithm generalizes existing conformal prediction algorithms, and we show that it achieves approximate valid population coverage and near-optimal efficiency within class, whenever the function class in the conformalization step is low-capacity in a certain sense. Next, this ERM problem is challenging to optimize as it involves a non-differentiable coverage constraint. We develop a gradient-based algorithm for it by approximating the original constrained ERM using differentiable surrogate losses and Lagrangians. Experiments show that our algorithm is able to learn valid prediction sets and improve the efficiency significantly over existing approaches in several applications such as prediction intervals with improved length, minimum-volume prediction sets for multi-output regression, and label prediction sets for image classification.

1 Introduction

Modern machine learning models can yield highly accurate predictions in many applications. As these predictions are often used in critical decision making, it is increasingly important to accompany them with an uncertainty quantification of how much the true label may deviate from the prediction. A common approach to quantifying the uncertainty in the data is to learn a *prediction set*—a set-valued analogue of usual (point) predictions—which outputs a *subset* of candidate labels instead of a single predicted label. For example, this could be a prediction interval for regression, or a discrete label set for multi-class classification. A common requirement for learned prediction sets is that it should achieve *valid coverage*, i.e. the set should cover the true label with high probability (such as 90%) on a new test example (Lawless & Fredette, 2005). In addition to coverage, the prediction set is often desired to have a good *efficiency*, such as a low length or small cardinality (Lei et al., 2018; Sadinle et al., 2019), in order for it to be informative. Note that coverage and efficiency typically come as a trade-off, as it is in general more likely to achieve a better coverage using a larger set.

This paper is concerned with the problem of finding the most efficient prediction set with valid coverage. Our approach builds on conformal prediction (Vovk et al., 2005), a powerful framework for generating prediction sets from (trained) base predictors with finite-sample coverage guarantees. Conformal prediction has been used for learning prediction sets in a variety of tasks in regression (Lei & Wasserman, 2014; Lei et al., 2018; Romano et al., 2019), classification (Cauchois et al., 2020b; Romano et al., 2020; Angelopoulos et al., 2020), structured prediction (Bates et al., 2021), and so on. However, the conformalization step in conformal prediction by default does not offer the flexibility for optimizing additional efficiency metrics, as the efficiency is already determined by the associated score function and the target coverage level (cf. Figure 1 Left). For certain efficiency

Figure 1: Comparison of vanilla conformal prediction and our CP-Gen for learning a prediction interval with 90% nominal coverage on a real-world regression task. Left: The function class $\{C_t\}$ is the prediction intervals used by Conformalized Quantile Regression. Right: $\{C_{\theta,t}\}$ is a larger class of intervals used by our conformal quantile finetuning procedure with the same base predictor (cf. Appendix E.3 for more details).

metrics such as the length or cardinality, several approaches have been proposed, for example by designing a better score function (Angelopoulos et al., 2020), using base predictors of a specific form (Izbicki et al., 2019; 2020; Sadinle et al., 2019), or selecting a best training hyperparameter (Yang & Kuchibhotla, 2021). However, these approaches either rely on specific structures of the particular efficiency loss or prediction set, or often involve a computationally-intensive search in the implementation. So far, there is a lack of a more principled and computationally efficient algorithm for optimizing any efficiency metric subject to valid coverage over any class of prediction sets.

In this paper, we cast the above as a constrained empirical risk minimization (ERM) problem of optimizing the efficiency subject to the coverage constraint, over any general function class of prediction sets with potentially multiple learnable parameters. This is motivated by a simple observation that vanilla conformal prediction is already equivalent to solving such a constrained ERM with one learnable parameter (Section 2.1). The promise of our extension is that it optimizes the efficiency over a larger function class, and hence will yield an improvement whenever the function class does contain a valid prediction set with better efficiency, and we do not suffer too much from the generalization error brought by learning multiple parameters at once.

Our contributions are summarized as follows.

- We propose CP-Gen (Conformal Prediction with General Function Class), a generalization of conformal prediction to learning multiple parameters. CP-Gen selects within an arbitrary class of prediction sets by solving the constrained ERM problem of best efficiency subject to valid empirical coverage (Section 3.1), and is a systematic extension of existing algorithms.

- We show theoretically that CP-Gen achieves approximately valid coverage and near-optimal efficiency within class, whenever the class is low-capacity with respect to both the coverage and the efficiency loss (Section 3.2). We also provide a practical variant CP-Gen-Recal using data splitting and reconformalization, which achieves exact coverage, as well as good efficiency under additional assumptions (Section 3.3).

- To address the issue that CP-Gen and CP-Gen-Recal involve a non-differentiable coverage constraint, we develop a differentiable approximation using surrogate losses and Lagrangians (Section 4). This allows us to solve the constrained ERM problem over higher-dimensional continuous parameter spaces via gradient-based optimization, and is more flexible than existing algorithms that require discretization and brute-force search.

- We empirically demonstrate that CP-Gen-Recal with our gradient-based implementation can learn prediction sets with valid coverage and significantly improved efficiency on three real-data tasks: prediction intervals for regression with improved length, minimum-volume prediction sets for multi-output regression, and label prediction sets for ImageNet (Section 5 & Appendix F).

We illustrate our main insight via the coverage-vs-efficiency trade-off plots in Figure 1: While vanilla conformal prediction only learns a single parameter (within its conformalization step) by a simple thresholding rule over a coverage-efficiency *curve*, our CP-Gen is able to further improve the efficiency by thresholding a *region* formed by a larger function class.

1.1 RELATED WORK

Learning prediction sets via conformal prediction   The framework of conformal prediction for learning prediction sets is originated in the early works of (Vovk et al., 1999; 2005; Shafer & Vovk, 2008). The main advantage of conformal prediction is that it yields (marginal) coverage guarantees regardless of the data distribution (i.e. distribution-free). More recently, conformal prediction has been applied to a variety of uncertainty quantification tasks, such as prediction intervals for regression (Papadopoulos, 2008; Vovk, 2012; 2015; Lei & Wasserman, 2014; Vovk et al., 2018; Lei et al., 2018; Romano et al., 2019; Izbicki et al., 2019; Guan, 2019; Gupta et al., 2019; Kivaranovic et al., 2020; Barber et al., 2021; Foygel Barber et al., 2021), label prediction sets for classification problems (Lei et al., 2013; Sadinle et al., 2019; Romano et al., 2020; Cauchois et al., 2020b;a; Angelopoulos et al., 2020), and prediction sets for structured output (Bates et al., 2021).

Optimizing efficiency in addition to valid coverage   A few recent works study the problem of optimizing the efficiency over a larger class of prediction sets in addition to guaranteeing valid coverage. Chen et al. (2021) consider the problem of finding the shortest prediction interval subject to coverage constraint, but do not use conformal prediction. Yang & Kuchibhotla (2021) propose to minimize the length of the conformal interval over either a finite class or a linear aggregation of base predictors, and provides coverage and efficiency guarantees. Both works formulate this task as a risk minimization problem, yet are restricted to considering either finite classes or specific efficiency loss functions. Our work is inspired by and improves upon the above works by allowing any function class and efficiency loss, along with providing more flexible implementations.

The problem of optimizing the efficiency can also be done by utilizing structures of the particular efficiency loss to choose a specific base predictor and an associated prediction set (Lei & Wasserman, 2014; Sadinle et al., 2019; Izbicki et al., 2019; 2020). By contrast, our approach does not require either the efficiency loss or the base predictor to possess any structure, and is thus complementary.

Other algorithms and theory   An alternative line of work constructs prediction intervals / prediction sets by aggregating the prediction over multiple base predictors through Bayesian neural network (Mackay, 1992; Gal & Ghahramani, 2016; Kendall & Gal, 2017; Malinin & Gales, 2018; Maddox et al., 2019) or ensemble methods (Lakshminarayanan et al., 2016; Ovadia et al., 2019; Huang et al., 2017; Malinin et al., 2019). However, these methods do not typically come with (frequentist) coverage guarantees. The recent work of Hoff (2021) studies ways of enhancing Bayes-optimal prediction with frequentist coverage. Prediction intervals can also be obtained by parameter estimation using a parametric model for the data (Cox, 1975; Bjornstad, 1990; Beran, 1990; Barndorff-Nielsen & Cox, 1996; Hall et al., 1999; Lawless & Fredette, 2005). See (Tian et al., 2020) for a review. However, the coverage of such prediction intervals relies heavily on the parametric model being correct (well-specified), and can even fail in certain high-dimensional regimes where the model is indeed correct (Bai et al., 2021).

2 PRELIMINARIES

Uncertainty quantification via prediction sets   We consider standard learning problems in which we observe a dataset D of examples $(x_i, y_i) \in \mathcal{X} \times \mathcal{Y}$ from some data distribution, and wish to predict the label y from the input x. A *prediction set* is a set-valued function $C : \mathcal{X} \to 2^{\mathcal{Y}}$ where $C(x)$ is a subset of $\mathcal{Y}$. Two prevalent examples are regression ($\mathcal{Y} = \mathbb{R}$) in which we can choose $C(x) \subset \mathbb{R}$ as a **prediction interval**, and (multi-class) classification ($\mathcal{Y} = [K] := \{1, \dots, K\}$) in which we can choose $C(x) \subset [K]$ as a (discrete) **label prediction set**.

Coverage and efficiency   The (marginal) coverage probability (henceforth *coverage*) of a prediction set C is defined as

$$\mathrm{Coverage}(C) := \mathbb{P}(Y \in C(X))$$

where (X, Y) is a test example from the same data distribution. We also define the (mis)-coverage loss $L_{\mathrm{coverage}}(C) := 1 - \mathrm{Coverage}(C) = \mathbb{P}(Y \notin C(X))$. A learned prediction set is often desired to achieve *valid coverage* in the sense that $\mathrm{Coverage}(C) \geq 1 - \alpha$ for some $\alpha \in (0, 1)$. Here $1 - \alpha$ is a pre-determined target coverage level; typical choices are e.g. $1 - \alpha \in \{90\%, 95\%\}$, which corresponds to picking $\alpha \in \{0.1, 0.05\}$.

In addition to valid coverage, it is often desired that the prediction set has a good *efficiency* (such as small size). This is motivated by the fact that valid coverage can be achieved trivially if we do not care about the size, e.g. by always outputting $C = \mathcal{Y}$, which is not informative. Throughout this paper we will use ℓ_{eff} to denote the particular efficiency loss we care about, where $\ell_{\text{eff}}(C; (x, y))$ measures the efficiency loss of C on an example (x, y), such as the length (Lebesgue measure) of prediction intervals, or the size (cardinality) of label prediction sets.

Nested set framework   We adopt the nested set framework of (Gupta et al., 2019) for convenience for our presentation and analysis. A family $\{C_t\}_{t \in \mathcal{T} \subset \mathbb{R}}$ is said to be a (family of) nested sets if $t \leq t'$ implies that $C_t(x) \subset C_{t'}(x)$ for all $x \in \mathcal{X}$. Throughout this paper out notation C_t or $C_{\theta,t}$ are assumed to be nested sets with respect to t. We assume that our efficiency loss ℓ_{eff} is non-decreasing w.r.t. its (set-valued) argument, i.e. $\ell_{\text{eff}}(C; (x, y)) \leq \ell_{\text{eff}}(C'; (x, y))$ if $C \subseteq C'$. Therefore, for nested sets the loss $t \mapsto \ell_{\text{eff}}(C_t; (x, y))$ is non-decreasing in t. As the coverage loss $L(C_t) = \mathbb{P}(Y \notin C_t(X))$ (and its empirical version) is instead non-increasing in t, the efficiency loss and the coverage loss always comes as a trade-off.

2.1   Conformal prediction

Conformal prediction (Vovk et al., 2005; Lei & Wasserman, 2014) is a powerful technique for learning prediction sets with coverage guarantees. The core of conformal prediction is its *conformalization* step, which turns any base prediction function (or training algorithm) into a prediction set.

We here briefly review conformal prediction using the vanilla (split) conformal regression method of (Lei et al., 2018), and refer the readers to (Angelopoulos & Bates, 2021) for more examples. Given any *base predictor* $f : \mathcal{X} \to \mathbb{R}$ (potentially learned on a training dataset D_{train}), conformal prediction outputs a prediction interval

$$C_{\widehat{t}}(x) := \left[f(x) - \widehat{t}, f(x) + \widehat{t} \right], \tag{1}$$

where $\widehat{t} \in \mathbb{R}_{\geq 0}$ is chosen as the $(1 - \alpha)$-quantile[1] of $|y - f(x)|$ on a calibration dataset D_{cal} with size $n_{\text{cal}} := |D_{\text{cal}}|$ using the following conformalization step:

$$\widehat{t} = \lceil (1 - \alpha) n_{\text{cal}} \rceil \text{ -th largest of } \{|y_i - f(x_i)|\}_{i=1}^{n_{\text{cal}}}. \tag{2}$$

The main guarantee for the learned interval $C_{\widehat{t}}$ is that it achieves a $(1 - \alpha)$ coverage guarantee of the form $\mathbb{P}_{D_{\text{cal}}, (X,Y)}(Y \in C_{\widehat{t}}(X)) \geq 1 - \alpha$ (Lei et al., 2018, Theorem 2.2). The proof relies on the exchangeability between the scores $\{|y_i - f(x_i)|\}_{i=1}^{n_{\text{cal}}}$ and $|Y - f(X)|$, which allows this guarantee to hold in a distribution-free fashion (i.e. for any data distribution).

Conformal prediction as a constrained ERM with one parameter   We start by a simple reinterpretation that the conformalization step (2) is equivalent to solving a constrained empirical risk minimization (ERM) problem with a single learnable parameter t (cf. Appendix A for the proof).

Proposition 1 (Conformal regression as a constrained ERM with one learnable parameter). *The parameter $\widehat{t} \in \mathbb{R}$ defined in (2) is the solution to the following constrained ERM problem*

$$\begin{aligned} &\underset{t \geq 0}{\text{minimize }} \widehat{L}_{\text{eff}}(C_t) := \frac{1}{n_{\text{cal}}} \sum_{i \in D_{\text{cal}}} \ell_{\text{eff}}(C_t; (x_i, y_i)) = 2t \\ &\text{subject to } \widehat{L}_{\text{coverage}}(C_t) := \frac{1}{n_{\text{cal}}} \sum_{i \in D_{\text{cal}}} \mathbf{1}\{y_i \notin C_t(x_i)\} \leq \alpha. \end{aligned} \tag{3}$$

Above, $\ell_{\text{eff}}(C; (x, y)) = \text{length}(C(x))$ is the length of the interval $C(x)$.

Though simple, this re-interpretation suggests a limitation to the conformalization step (2) as well as its analogue in other existing conformal methods: It only learns a single parameter t, and thus cannot further optimize the efficiency due to the coverage-efficiency trade-off (cf. Figure 1). However, the form of the constrained ERM problem (3) suggests that it can be readily extended to more general function classes with more than one learnable parameters, which is the focus of this work.

---

[1]Technically (2) requires the $\lceil (1 - \alpha)(n_{\text{recal}} + 1) \rceil$-th largest element to guarantee valid coverage (Angelopoulos & Bates, 2021); here we choose the close $\lceil (1 - \alpha) n_{\text{recal}} \rceil$-th largest to allow the following insight.

Algorithm 1 Conformal Prediction with General Function Class (`CP-Gen`)

Input: Class of prediction sets $\mathcal{C} = \{C_{\theta,t}\}_{\theta\in\Theta, t\in\mathcal{T}}$; target miscoverage level $\alpha \in (0,1)$; $\varepsilon_0 \geq 0$.
  Efficiency loss ℓ_{eff}; Calibration dataset D_{cal} with size n_{cal}.
1: Solve the following constrained ERM problem on dataset D_{cal} (with relaxation parameter ε_0):

$$
\begin{aligned}
(\widehat{\theta}, \widehat{t}) &\leftarrow \underset{\theta\in\Theta, t\in\mathcal{T}}{\arg\min}\ \widehat{L}_{\mathrm{eff}}(C_{\theta,t}) := \frac{1}{n_{\mathrm{cal}}} \sum_{i\in D_{\mathrm{cal}}} \ell_{\mathrm{eff}}(C_{\theta,t}(x_i), y_i) \\
&\text{subject to}\ \ \widehat{L}_{\mathrm{coverage}}(C_{\theta,t}) := \frac{1}{n_{\mathrm{cal}}} \sum_{i\in D_{\mathrm{cal}}} \mathbf{1}\{y_i \notin C_{\theta,t}(x_i)\} \leq \alpha + \varepsilon_0.
\end{aligned}
\tag{5}
$$

Output: Prediction set $C_{\widehat{\theta},\widehat{t}}$.

---

3 CONFORMAL PREDICTION WITH GENERAL FUNCTION CLASSES

3.1 ALGORITHM

Our algorithm, Conformal Prediction with General Function Classes (`CP-Gen`; full description in Algorithm 1), is an extension of the constrained ERM problem (3) into the case of general function classes with multiple learnable parameters. `CP-Gen` takes in a function class of prediction sets

$$
\mathcal{C} := \{C_{\theta,t}(x) : \theta \in \Theta, t \in \mathcal{T} \subset \mathbb{R}\}, \tag{4}
$$

where (as mentioned) we assume that $\{C_{\theta,t}\}_{t\in\mathcal{T}}$ is a nested set for each $\theta \in \Theta$. The parameter set Θ as well as the form of $C_{\theta,t}$ in (4) can be arbitrary, depending on applications and the available base predictors at hand. Given $\mathcal{C}$, our algorithm then solves the constrained ERM problem (5) of finding the smallest interval among $\mathcal{C}$ subject to valid coverage on dataset D_{cal}.

Compared with vanilla conformal prediction, Algorithm 1 allows more general tasks with an arbitrary function class and efficiency loss; for example, this encompasses several recent algorithms such as finite hyperparameter selection and linear aggregation (Yang & Kuchibhotla, 2021; Chen et al., 2021). We remark that (5) includes an additional relaxation parameter $\varepsilon_0 \geq 0$ for the coverage constraint. This is for analysis purposes only; our practical implementation uses the vanilla $\varepsilon = 0$.

3.2 THEORY

A fundamental theoretical question about `CP-Gen` is whether it achieves coverage and efficiency guarantees on the population (test data). This section showcases that, by standard generalization theory, `CP-Gen` achieves approximate validity and near-optimal efficiency whenever function class is low-capacity in a certain sense.

Let $L_{\{\mathrm{eff},\mathrm{coverage}\}} := \mathbb{E}_{D_{\mathrm{cal}}}[\widehat{L}_{\{\mathrm{eff},\mathrm{coverage}\}}]$ denote the population coverage and efficiency losses. We define the following uniform concentration quantities:

$$
\varepsilon_{\mathrm{eff}} := \sup_{\theta\in\Theta, t\in\mathcal{T}} \left| \widehat{L}_{\mathrm{eff}}(C_{\theta,t}) - L_{\mathrm{eff}}(C_{\theta,t}) \right|, \tag{6}
$$

$$
\varepsilon_{\mathrm{coverage}} := \sup_{\theta\in\Theta, t\in\mathcal{T}} \left| \widehat{L}_{\mathrm{coverage}}(C_{\theta,t}) - L_{\mathrm{coverage}}(C_{\theta,t}) \right|. \tag{7}
$$

The following proposition connects the generalization of `CP-Gen` to the above uniform concentration quantities by standard arguments (see Appendix B.1 for the proof).

Proposition 2 (Generalization of `CP-Gen`). *The prediction set $C_{\widehat{\theta},\widehat{t}}$ learned by Algorithm 1 satisfies*

(a) (Approximately valid population coverage) We have

$$
L_{\mathrm{coverage}}(C_{\widehat{\theta},\widehat{t}}) \leq \alpha + \varepsilon_0 + \varepsilon_{\mathrm{coverage}},
$$

i.e. the population coverage of $C_{\widehat{\theta},\widehat{t}}$ is at least $1 - \alpha - (\varepsilon_0 + \varepsilon_{\mathrm{coverage}})$.

(b) (Near-optimal efficiency) Suppose $\varepsilon_0 \geq \varepsilon_{\mathrm{coverage}}$, then we further have

$$
L_{\mathrm{eff}}(C_{\widehat{\theta},\widehat{t}}) \leq \inf_{\substack{(\theta,t)\in\Theta\times\mathcal{T} \\ L_{\mathrm{coverage}}(C_{\theta,t})\leq\alpha}} L_{\mathrm{eff}}(C_{\theta,t}) + 2\varepsilon_{\mathrm{eff}},
$$

i.e. $C_{\hat{\theta},\hat{t}}$ *achieves* $2\varepsilon_{\text{eff}}$*-near-optimal efficiency against any prediction set within* $\mathcal{C}$ *with at least* $(1 - \alpha)$ *population coverage.*

Examples of good generalization We provide two concrete examples where the concentration terms ε_{eff} and $\varepsilon_{\text{coverage}}$ are small with high probability, in which case Proposition 2 guarantees that `CP-Gen` learns an prediction set with approximate validity and near-optimal efficiency.

Assumption A (Bounded and Lipschitz efficiency loss). *The loss function* ℓ_{eff} *satisfies*

A1 (Bounded loss). $|\ell_{\text{eff}}(C_{\theta,t}; (x,y))| \leq M$ *for all* $(\theta, t) \in \Theta \times \mathcal{T}$ *and all* $(x,y) \in \mathcal{X} \times \mathcal{Y}$.

A2 (t-Lipschitzness). $t \mapsto \ell_{\text{eff}}(C_{\theta,t}; (x,y))$ *is* $L_{\mathcal{T}}$*-Lipschitz for all* $(\theta, x, y) \in \Theta \times \mathcal{X} \times \mathcal{Y}$.

Assumption B (Bounded $\mathcal{T}$). *The parameter space* $\mathcal{T} \subset \mathbb{R}$ *is bounded:* $\sup_{t \in \mathcal{T}} |t| \leq B_{\mathcal{T}}$.

Proposition 3 (Finite class). *Suppose* Θ *is a finite set (*$N_\Theta := |\Theta| < \infty$*), and suppose Assumptions A1, A2, B hold. Then, we have with probability at least* $1 - \delta$ *that*

$$\varepsilon_{\text{coverage}} \leq C\sqrt{\log(N_\Theta/\delta)/n_{\text{cal}}} \ \ \text{and} \ \ \varepsilon_{\text{eff}} \leq C \cdot \left[M\sqrt{\log(N_\Theta/\delta)} + L_{\mathcal{T}} B_{\mathcal{T}} \right] / \sqrt{n_{\text{cal}}},$$

where $C > 0$ *is an absolute constant.*

Next, for any class $\mathcal{C}$, let $\text{VC}(\mathcal{C}) := \text{VC}(\{(x,y) \mapsto \mathbf{1}\{y \notin C_{\theta,t}(x)\} : \theta \in \Theta, t \in \mathcal{T}\})$ denote its VC dimension with respect to the coverage loss.

Proposition 4 (VC/Rademacher class). *We have for some absolute constant* $C > 0$ *that*

(a) Suppose $\text{VC}(\mathcal{C}) = K + 1 < \infty$*, then with probability at least* $1 - \delta/2$,

$$\varepsilon_{\text{coverage}} \leq C\sqrt{(K + 1 + \log(1/\delta))/n_{\text{cal}}}.$$

(b) Suppose Assumption A1 holds. Then we have with probability at least $1 - \delta/2$ *that*

$$\varepsilon_{\text{eff}} \leq C\left[R^{\text{eff}}_{n_{\text{cal}}}(\mathcal{C}) + \sqrt{M^2 \log(1/\delta)/n_{\text{cal}}} \right],$$

where $R^{\text{eff}}_{n_{\text{cal}}}(\mathcal{C}) := \mathbb{E}_{(x_i,y_i),\varepsilon_i}\left[\sup_{(\theta,t) \in \Theta \times \mathcal{T}} \left| \frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \varepsilon_i \ell_{\text{eff}}(C_{\theta,t}; (x_i, y_i)) \right| \right]$ *is the Rademacher complexity of the class* $\mathcal{C}$ *with respect to* ℓ_{eff} *(above* $\varepsilon_i \overset{\text{iid}}{\sim} \text{Unif}(\{\pm 1\})$*).*

Implications Combined with Proposition 2, both examples above feature roughly an $1 - \alpha - \sqrt{\text{Comp}(\mathcal{C})/n_{\text{cal}}}$ approximate coverage guarantee and $\sqrt{\text{Comp}(\mathcal{C})/n_{\text{cal}}}$ near-optimal efficiency guarantee, where $\text{Comp}(\mathcal{C})$ is a certain complexity measure of $\mathcal{C}$. The proofs for both results use standard concentration arguments, and are deferred to Appendix B.2 & B.3. In particular, our Proposition 3 recovers the coverage guarantee for the finite-class selection algorithm of (Yang & Kuchibhotla, 2021, Theorem 1) though our efficiency guarantee is more general.

We remark that both examples above—though seemingly abstract—contains important applications. The finite class contains e.g. optimizing over a K-dimensional hyperparameter to use via grid search, with e.g. $N_\Theta = (1/\delta)^K$ and thus $\text{Comp}(\mathcal{C}) = \log N_\Theta = K\log(1/\delta)$. The VC/Rademacher class contains the important special case of linear classes with K base predictors (we defer the formal statement and proof to Appendix C). Also, these examples are not necessarily exhaustive. Our take-away is rather that we may expect `CP-Gen` to generalize well (and thus achieves good coverage and efficiency) more broadly in practice, for instance whenever it learns $K \ll n_{\text{cal}}$ parameters.

3.3 ALGORITHM WITH EXACT COVERAGE VIA RECONFORMALIZATION

Although `CP-Gen` enjoys theoretical bounds on the coverage and efficiency, a notable drawback is that it does not guarantee exact $1 - \alpha$ coverage like usual conformal prediction, and its approximate coverage bound depends on the uniform concentration quantity $\varepsilon_{\text{coverage}}$ that is not computable from the observed data without concrete assumptions on the function class $\mathcal{C}$.

To remedy this, we incorporate a simple reconformalization technique on another recalibration dataset D_{recal} (e.g. a further data split), which guarantees exact finite-sample coverage by exchangeability. We call this algorithm `CP-Gen-Recal` and provide the full description in Algorithm 2.

Algorithm 2 Conformal Prediction with General Fn. Class and Recalibration (`CP-Gen-Recal`)

Input: Class of prediction sets $\mathcal{C} = \{C_{\theta,t}\}_{\theta \in \Theta, t \in \mathcal{T}}$; target miscoverage level $\alpha \in (0, 1)$; $\varepsilon_0 \geq 0$.
  Efficiency loss ℓ_{eff}; Calibration datasets $D_{\mathrm{cal}}, D_{\mathrm{recal}}$ with size $n_{\mathrm{cal}}, n_{\mathrm{recal}}$.
1: Run Algorithm 1 on dataset D_{cal} (with relaxation parameter ε_0) to obtain $(\widehat{\theta}, \widehat{t})$.
2: Keep $\widehat{\theta}$, and reconformalize $t \in \mathcal{T}$ on the recalibration dataset D_{recal}:

$$\widehat{t}_{\mathrm{recal}} \leftarrow \inf\left\{t \in \mathcal{T} : y_i \in C_{\widehat{\theta},t}(x_i) \text{ for at least } \lceil (1-\alpha)(n_{\mathrm{recal}}+1) \rceil \text{ examples } (x_i, y_i) \in D_{\mathrm{recal}} \right\}.$$

Output: Prediction set $C_{\widehat{\theta}, \widehat{t}_{\mathrm{recal}}}$.

We remark that this reconformalization technique for obtaining guaranteed $1 - \alpha$ coverage is widely used in the conformal prediction literature, e.g. (Angelopoulos et al., 2020). However, to the best of our knowledge, there is no known analysis for our `CP-Gen-Recal` algorithm for general function classes, for which we provide a result below (formal statement and proof deferred to Proposition 7 in Appendix D).

Proposition 5 (Coverage and efficiency guarantee for `CP-Gen-Recal`; Informal version)**.** *The prediction set $C_{\widehat{\theta}, \widehat{t}_{\mathrm{recal}}}$ learned by Algorithm 2 achieves $(1 - \alpha)$ finite-sample coverage: $\mathbb{P}_{D_{\mathrm{recal}},(X,Y)}(Y \in C_{\widehat{\theta}, \widehat{t}_{\mathrm{recal}}}) \geq 1 - \alpha$. Further, it achieves $O(\varepsilon_{\mathrm{eff}} + \varepsilon_{\mathrm{coverage}} + 1/\sqrt{n_{\mathrm{recal}}})$ near-optimal efficiency under additional regularity assumptions.*

4 DIFFERENTIABLE OPTIMIZATION

Our (meta) algorithms `CP-Gen` and `CP-Gen-Recal` involve solving the constrained ERM problem (5). One feasible case is when Θ is finite and small, in which we enumerate all possible $\theta \in \Theta$ and find the optimal $\widehat{t}$ for each θ efficiently using quantile computation. However, this optimization is significantly more challenging when the underlying parameter set Θ is continuous and we wish to jointly optimize over (θ, t): The coverage loss $\widehat{L}_{\mathrm{coverage}}(C_{\theta,t})$ is *non-differentiable* and its "gradient" is zero almost everywhere as it uses the zero-one loss. This makes the coverage constraint challenging to deal with and not amenable to any gradient-based algorithm.

To address this non-differentiability, we develop a gradient-based practical implementation by approximating the coverage constraint. We first rewrite each individual coverage loss into the form

$$\mathbf{1}\{y \notin C_{\theta,t}(x)\} = \mathbf{1}\{s_{\theta,t}(x,y) < 0\} = \ell_{01}(s_{\theta,t}(x,y)).$$

where $\ell_{01}(z) := \mathbf{1}\{z < 0\}$ is the zero-one loss. (Such a rewriting is possible in most cases by taking $s_{\theta,t}$ as a suitable "score-like" function; see Appendix E for instantiations in our experiments.) Then, inspired by the theory of surrogate losses (Bartlett et al., 2006), we approximate $\ell_{01}(z)$ by the hinge loss $\ell_{\mathrm{hinge}}(z) = [1 - z]_+$ which is (almost everywhere) differentiable with a non-trivial gradient. We find the hinge loss to perform better empirically than alternatives such as the logistic loss.

To deal with the (modified) constraint, we turn it into an exact penalty term with penalty parameter $\lambda \geq 0$, and use a standard primal-dual formulation (Bertsekas, 1997) to obtain an unconstrained min-max optimization problem on the Lagrangian:

$$\min_{\theta, t} \max_{\lambda \geq 0} \widehat{L}_{\mathrm{eff}}(C_{\theta,t}) + \lambda \left[\widehat{L}_{\mathrm{hinge}}(C_{\theta,t}) - \alpha\right]_+, \tag{8}$$

where $\widehat{L}_{\mathrm{hinge}}(C_{\theta,t}) := \frac{1}{n_{\mathrm{cal}}} \sum_{i=1}^{n_{\mathrm{cal}}} \ell_{\mathrm{hinge}}(s_{\theta,t}(x_i, y_i))$ is the empirical hinge loss on the calibration dataset D_{cal}. Our final practical implementation of (5) solves the problem (8) by Stochastic Gradient Descent-Ascent (with respect to (θ, t) and λ) to yield an approximate solution $(\widehat{\theta}, \widehat{t})$. We remark that in our experiments where we use the reconformalized version `CP-Gen-Recal`, we only keep the $\widehat{\theta}$ obtained from (8) and perform additional reconformalization to compute $\widehat{t}_{\mathrm{recal}}$ to guarantee coverage.

We also emphasize that the approximamtion in (8) makes the problem differentiable at the cost of deviating from the true constrained ERM problem (5) and thus potentially may sacrifice in terms of the efficiency. However, our experiments in Section 5 show that such an implementation can still improve the efficiency over existing approaches in practice, despite the approximation.

Table 1: **Results for conformal quantile finetuning** on real-data regression tasks at level $1 - \alpha = 90\%$. For each method we report the (test) coverage, length, and pinball loss of the corresponding base quantile predictor. All results are averaged over 8 random seeds.

	CQR			QR + CP-Gen-Recal (ours)		
Dataset	Coverage(%)	Length	$L_{\text{pinball}}^{\text{test}}$	Coverage(%)	Length	$L_{\text{pinball}}^{\text{test}}$
MEPS_19	89.98	1.167	0.112	90.09	**0.890**	0.131
MEPS_20	89.72	1.165	0.117	89.99	**0.830**	0.141
MEPS_21	89.81	1.145	0.107	90.22	**0.962**	0.129
Facebook_1	90.12	0.555	0.052	90.34	**0.384**	0.090
Facebook_2	90.13	0.491	0.044	90.02	**0.364**	0.092
kin8nm	90.03	1.214	0.076	89.31	**1.173**	0.078
naval	89.70	3.095	0.164	89.71	**3.077**	0.166
bio	90.26	2.271	0.130	90.20	**2.164**	0.148
blog_data	90.19	0.605	0.058	90.01	**0.496**	0.107
Nominal $(1 - \alpha)$	90.00	-	-	90.00	-	-

5 EXPERIMENTS

We empirically test our CP-Gen-Recal algorithm (using the practical implementation (8)) on three representative real-data tasks. The concrete construction of $\{C_{\theta,t}\}$ will be described within each application. Throughout this section we choose $1 - \alpha = 90\%$ as the nominal coverage level, and use the CP-Gen-Recal algorithm to guarantee coverage in expectation. We provide ablations with $\alpha \in \{80\%, 95\%\}$ in Appendix G.1 and G.2 and the CP-Gen algorithm in Appendix G.3.

5.1 IMPROVED PREDICTION INTERVALS VIA CONFORMAL QUANTILE FINETUNING

Setup We consider regression tasks in which we use quantile regression (pinball loss) to train a base quantile predictor $\widehat{F}(x) = [\widehat{f}_{\text{lo}}(x), \widehat{f}_{\text{hi}}(x)] = \widehat{\theta}_0^\top \widehat{\Phi}(x)$ on D_{train} (with lr decay by monitoring validation loss on D_{cal}). Here $\widehat{\Phi} : \mathcal{X} \to \mathbb{R}^{d_h}$ is the learned representation function and $\widehat{\theta}_0 \in \mathbb{R}^{d_h \times 2}$ is the last linear layer. Given $\widehat{F}$, we learn a baseline prediction interval of the form $[\widehat{f}_{\text{lo}}(x) - t, \widehat{f}_{\text{hi}}(x) + t]$ on D_{recal} via Conformalized Quantile Regression (CQR) (Romano et al., 2019).

We then attempt to improve the length over CQR by *conformal quantile finetuning*: Fix the representation function $\widehat{\Phi}$ and finetune the linear layer θ using our CP-Gen-Recal algorithm, so that $C_{\theta,t}(x) = [\theta_{\text{lo}}^\top \widehat{\Phi}(x) - t, \theta_{\text{hi}}^\top \widehat{\Phi}(x)]$ (where $\theta = [\theta_{\text{lo}}, \theta_{\text{hi}}]$). We learn a new $\widehat{\theta}$ on D_{cal} via (8) (where ℓ_{eff} is chosen as the length), and then compute $\widehat{t}_{\text{recal}}$ on D_{recal} as in Algorithm 2.

We perform the above on 9 real-world regression datasets with a 3-layer MLP with width $d_h = 64$, similar as (Romano et al., 2019; Feldman et al., 2021). Additional details about the setup can be found in Appendix E.1.

Results Table 1 compares the (test) coverage and length between CQR and the finetuned linear layer via our CP-Gen-Recal. While both CQR and CP-Gen-Recal achieves valid 90% coverage, CP-Gen-Recal can systematically improve the length over CQR on all tasks. Table 1 also reports the pinball loss for both the base $\widehat{\theta}_0 \widehat{\Phi}(x)$ as well as the fine-tuned $\widehat{\theta}^\top \widehat{\Phi}(x)$ on the test set D_{test}. Intriguingly, our conformal finetuning made the pinball loss *worse* while managing to improve the length. This suggests the unique advantage of our constrained ERM objective, as it rules out the simple explanation that the length improvement is just because of a lower test loss.

5.2 MINIMUM-VOLUME PREDICTION SETS FOR MULTI-OUTPUT REGRESSION

Setup This task aims to learn a box-shaped prediction set for multi-output regression with a *small volume*. Our learning task is regression with output dimension $d_{\text{out}} > 1$. We first learn a based predictor $\widehat{f} : \mathbb{R}^d \to \mathbb{R}^{d_{\text{out}}}$ by minimizing the MSE loss on D_{train}. We then learn a *box-shaped* prediction set of the form $C_u(x) = \prod_{i=1}^{d_{\text{out}}} [\widehat{f}_i(x) - \widehat{u}_i, \widehat{f}_i(x) + \widehat{u}_i]$ by one of the following methods:

Table 2: **Results for multi-output regression** on next-state prediction tasks, at level $1 - \alpha = 90\%$. For each method we report the (test) coverage and volume of its learned box-shaped prediction set. All results are averaged over 8 random seeds.

Dataset	Coord-wise		Coord-wise-Recal		CP-Gen-Recal (ours)	
	Coverage(%)	Volume	Coverage(%)	Volume	Coverage(%)	Volume
Cartpole	94.28	1.20×10^{-5}	90.17	5.10×10^{-6}	90.12	$\mathbf{2.30 \times 10^{-6}}$
Half-Cheetah	93.90	1.10×10^{-5}	90.06	1.23×10^{-6}	90.02	$\mathbf{9.07 \times 10^{-7}}$
Ant	93.56	3.37×10^{-3}	89.99	1.70×10^{-4}	90.02	$\mathbf{8.25 \times 10^{-5}}$
Walker	94.42	2.59×10^{-5}	90.01	7.33×10^{-7}	89.94	$\mathbf{3.47 \times 10^{-7}}$
Swimmer	95.62	2.80×10^{-5}	89.90	2.22×10^{-6}	90.13	$\mathbf{1.46 \times 10^{-7}}$
Hopper	92.87	2.81×10^{-9}	90.02	1.01×10^{-9}	89.92	$\mathbf{8.25 \times 10^{-10}}$
Humanoid	94.75	4.28×10^{-4}	89.95	8.53×10^{-8}	89.94	$\mathbf{4.95 \times 10^{-8}}$
Nominal $(1 - \alpha)$	90.00	-	90.00	-	90.00	-

- (Coord-wise): Each $\widehat{u}_i$ is obtained by vanilla conformalization (2) over the i-th output coordinate on $D_{\mathrm{cal}} \cup D_{\mathrm{recal}}$. To guarantee $1 - \alpha$ coverage, each coordinate is conformalized at level $1 - \alpha/d_{\mathrm{out}}$, motivated by the union bound.

- (Coord-wise-Recal): Perform the above on D_{cal} to learn $\widehat{u}_i$, and reconformalize an additional $t \geq 0$ on D_{recal} to reshape the prediction set *proportionally*:

$$C_{\widehat{u},t}(x) = \prod_{i=1}^{d_{\mathrm{out}}} [\widehat{f}_i(x) - t\widehat{u}_i, \widehat{f}_i(x) + t\widehat{u}_i]. \tag{9}$$

- (CP-Gen-Recal, ours): Optimize the volume directly over all $u \in \mathbb{R}^{d_{\mathrm{out}}}$ using (8) on D_{cal}, where $\ell_{\mathrm{eff}}(C_u; (x, y)) = \prod_{i=1}^{d_{\mathrm{out}}} (2u_i)$ is chosen as the volume loss. We then reconformalize an additional $\widehat{t} \geq 0$ on D_{recal} to reshape the prediction set same as in (9). Note that this reconformalization step is equivalent to Algorithm 2 with the re-parametrization $\widehat{u} \mapsto (\widehat{\theta}, \widehat{t})$ where $\widehat{\theta} \in \mathbb{R}_{>0}^{d_{\mathrm{out}}-1}$ denotes the ratio between $\widehat{u}_i$, and $\widehat{t} \in \mathbb{R}_{>0}$ denotes a common scale.

Our datasets is a collection of *next-state prediction tasks* with multi-dimensional continuous states in offline reinforcement learning (RL), constructed similarly as D4RL (Fu et al., 2020) with some differences. Additional details about the dataset and experimental setup can be found in Appendix E.2.

Results Table 2 reports the (test) coverage and volume of the above three methods. The Coord-wise method achieves valid coverage but is quite conservative (over-covers), which is as expected as the union bound is worst-case in nature and the coordinate-wise conformalization does not utilize the potential correlation between the output coordinates. Coord-wise-Recal achieves approximately 90% coverage with a much smaller volume. Our CP-Gen-Recal also achieves valid 90% coverage but a further lower volume across all tasks. This suggests that optimizing the volume over all possible $u \in \mathbb{R}^{d_{\mathrm{out}}}$ data-dependently using our CP-Gen-Recal is indeed more flexible than pre-determined conformalization schemes such as Coord-wise.

Additional experiment: label prediction sets for ImageNet We show that CP-Gen-Recal can learn label prediction sets for ImageNet (Angelopoulos et al., 2020) with valid coverage and improved size over existing approaches, by finding an optimized set of ensemble weights over multiple base neural networks (Table 5). Due to space limit, we defer the setup and results to Appendix F.

6 CONCLUSION

This paper proposes Conformal Prediction with General Function Class, a conformal prediction algorithm that optimizes the efficiency metric subject to valid coverage over a general function class of prediction sets. We provide theoretical guarantees for its coverage and efficiency in certain situations, and develop a gradient-based practical implementation which performs well empirically on several large-scale tasks. We believe our work opens up many directions for future work, such as stronger theoretical guarantees via more structured function classes, further improving the gradient-based approximate implementation, or experiments on other uncertainty quantification tasks.

REFERENCES

Physicochemical properties of protein tertiary structure data set. https://archive.ics.uci.edu/ml/datasets/Physicochemical+Properties+of+Protein+Tertiary+Structure. Accessed: January, 2019.

Blogfeedback data set. https://archive.ics.uci.edu/ml/datasets/BlogFeedback. Accessed: January, 2019.

Facebook comment volume data set. https://archive.ics.uci.edu/ml/datasets/Facebook+Comment+Volume+Dataset. Accessed: January, 2019.

Kinematics of an 8 link robot arm. http://ftp.cs.toronto.edu/pub/neuron/delve/data/tarfiles/kin-family/. Accessed: May, 2021.

Medical expenditure panel survey, panel 19. https://meps.ahrq.gov/mepsweb/data_stats/download_data_files_detail.jsp?cboPufNumber=HC-181, a. Accessed: January, 2019.

Medical expenditure panel survey, panel 20. https://meps.ahrq.gov/mepsweb/data_stats/download_data_files_detail.jsp?cboPufNumber=HC-181, b. Accessed: January, 2019.

Medical expenditure panel survey, panel 21. https://meps.ahrq.gov/mepsweb/data_stats/download_data_files_detail.jsp?cboPufNumber=HC-192, c. Accessed: January, 2019.

Condition based maintenance of naval propulsion plants data set. http://archive.ics.uci.edu/ml/datasets/Condition+Based+Maintenance+of+Naval+Propulsion+Plants. Accessed: May, 2021.

Anastasios Angelopoulos, Stephen Bates, Jitendra Malik, and Michael I Jordan. Uncertainty sets for image classifiers using conformal prediction. *arXiv preprint arXiv:2009.14193*, 2020.

Anastasios N Angelopoulos and Stephen Bates. A gentle introduction to conformal prediction and distribution-free uncertainty quantification. *arXiv preprint arXiv:2107.07511*, 2021.

Yu Bai, Song Mei, Huan Wang, and Caiming Xiong. Understanding the under-coverage bias in uncertainty estimation. *arXiv preprint arXiv:2106.05515*, 2021.

Rina Foygel Barber, Emmanuel J Candes, Aaditya Ramdas, and Ryan J Tibshirani. Predictive inference with the jackknife+. *The Annals of Statistics*, 49(1):486–507, 2021.

Ole E Barndorff-Nielsen and David R Cox. Prediction and asymptotics. *Bernoulli*, pp. 319–340, 1996.

Peter L Bartlett, Michael I Jordan, and Jon D McAuliffe. Convexity, classification, and risk bounds. *Journal of the American Statistical Association*, 101(473):138–156, 2006.

Stephen Bates, Anastasios Angelopoulos, Lihua Lei, Jitendra Malik, and Michael I Jordan. Distribution-free, risk-controlling prediction sets. *arXiv preprint arXiv:2101.02703*, 2021.

Rudolf Beran. Calibrating prediction regions. *Journal of the American Statistical Association*, 85 (411):715–723, 1990.

Dimitri P Bertsekas. Nonlinear programming. *Journal of the Operational Research Society*, 48(3): 334–334, 1997.

Jan F Bjornstad. Predictive likelihood: A review. *Statistical Science*, pp. 242–254, 1990.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

Maxime Cauchois, Suyash Gupta, Alnur Ali, and John C Duchi. Robust validation: Confident predictions even when distributions shift. *arXiv preprint arXiv:2008.04267*, 2020a.

Maxime Cauchois, Suyash Gupta, and John Duchi. Knowing what you know: valid confidence sets in multiclass and multilabel prediction. *arXiv preprint arXiv:2004.10181*, 2020b.

Haoxian Chen, Ziyi Huang, Henry Lam, Huajie Qian, and Haofeng Zhang. Learning prediction intervals for regression: Generalization and calibration. In *International Conference on Artificial Intelligence and Statistics*, pp. 820–828. PMLR, 2021.

DR Cox. Prediction intervals and empirical bayes confidence intervals. *Journal of Applied Probability*, 12(S1):47–55, 1975.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Shai Feldman, Stephen Bates, and Yaniv Romano. Improving conditional coverage via orthogonal quantile regression. *arXiv preprint arXiv:2106.00394*, 2021.

Rina Foygel Barber, Emmanuel J Candes, Aaditya Ramdas, and Ryan J Tibshirani. The limits of distribution-free conditional predictive inference. *Information and Inference: A Journal of the IMA*, 10(2):455–482, 2021.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning, 2020.

Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pp. 1050–1059. PMLR, 2016.

Leying Guan. Conformal prediction with localization. *arXiv preprint arXiv:1908.08558*, 2019.

Chirag Gupta, Arun K Kuchibhotla, and Aaditya K Ramdas. Nested conformal prediction and quantile out-of-bag ensemble methods. *arXiv preprint arXiv:1910.10562*, 2019.

Peter Hall, Liang Peng, and Nader Tajvidi. On prediction intervals based on predictive likelihood or bootstrap methods. *Biometrika*, 86(4):871–880, 1999.

Peter Hoff. Bayes-optimal prediction with frequentist coverage control. *arXiv preprint arXiv:2105.14045*, 2021.

Gao Huang, Yixuan Li, Geoff Pleiss, Zhuang Liu, John E Hopcroft, and Kilian Q Weinberger. Snapshot ensembles: Train 1, get m for free. *arXiv preprint arXiv:1704.00109*, 2017.

Rafael Izbicki, Gilson T Shimizu, and Rafael B Stern. Flexible distribution-free conditional predictive bands using density estimators. *arXiv preprint arXiv:1910.05575*, 2019.

Rafael Izbicki, Gilson Shimizu, and Rafael B Stern. Cd-split and hpd-split: efficient conformal regions in high dimensions. *arXiv preprint arXiv:2007.12778*, 2020.

Alex Kendall and Yarin Gal. What uncertainties do we need in bayesian deep learning for computer vision? *arXiv preprint arXiv:1703.04977*, 2017.

Danijel Kivaranovic, Kory D Johnson, and Hannes Leeb. Adaptive, distribution-free prediction intervals for deep networks. In *International Conference on Artificial Intelligence and Statistics*, pp. 4346–4356. PMLR, 2020.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. *arXiv preprint arXiv:1612.01474*, 2016.

JF Lawless and Marc Fredette. Frequentist prediction intervals and predictive distributions. *Biometrika*, 92(3):529–542, 2005.

Jing Lei and Larry Wasserman. Distribution-free prediction bands for non-parametric regression. *Journal of the Royal Statistical Society: Series B: Statistical Methodology*, pp. 71–96, 2014.

Jing Lei, James Robins, and Larry Wasserman. Distribution-free prediction sets. *Journal of the American Statistical Association*, 108(501):278–287, 2013.

Jing Lei, Max G'Sell, Alessandro Rinaldo, Ryan J Tibshirani, and Larry Wasserman. Distribution-free predictive inference for regression. *Journal of the American Statistical Association*, 113 (523):1094–1111, 2018.

David John Cameron Mackay. *Bayesian methods for adaptive models*. PhD thesis, California Institute of Technology, 1992.

Wesley J Maddox, Pavel Izmailov, Timur Garipov, Dmitry P Vetrov, and Andrew Gordon Wilson. A simple baseline for bayesian uncertainty in deep learning. *Advances in Neural Information Processing Systems*, 32:13153–13164, 2019.

Andrey Malinin and Mark Gales. Predictive uncertainty estimation via prior networks. *arXiv preprint arXiv:1802.10501*, 2018.

Andrey Malinin, Bruno Mlodozeniec, and Mark Gales. Ensemble distribution distillation. *arXiv preprint arXiv:1905.00076*, 2019.

Pascal Massart. The tight constant in the dvoretzky-kiefer-wolfowitz inequality. *The annals of Probability*, pp. 1269–1283, 1990.

Yaniv Ovadia, Emily Fertig, Jie Ren, Zachary Nado, David Sculley, Sebastian Nowozin, Joshua Dillon, Balaji Lakshminarayanan, and Jasper Snoek. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems*, pp. 13991–14002, 2019.

Harris Papadopoulos. Inductive conformal prediction: Theory and application to neural networks. In *Tools in artificial intelligence*. Citeseer, 2008.

Benjamin Recht, Rebecca Roelofs, Ludwig Schmidt, and Vaishaal Shankar. Do imagenet classifiers generalize to imagenet? In *International Conference on Machine Learning*, pp. 5389–5400. PMLR, 2019.

Yaniv Romano, Evan Patterson, and Emmanuel J Candès. Conformalized quantile regression. *arXiv preprint arXiv:1905.03222*, 2019.

Yaniv Romano, Matteo Sesia, and Emmanuel J Candès. Classification with valid and adaptive coverage. *arXiv preprint arXiv:2006.02544*, 2020.

Mauricio Sadinle, Jing Lei, and Larry Wasserman. Least ambiguous set-valued classifiers with bounded error levels. *Journal of the American Statistical Association*, 114(525):223–234, 2019.

Glenn Shafer and Vladimir Vovk. A tutorial on conformal prediction. *Journal of Machine Learning Research*, 9(3), 2008.

Qinglong Tian, Daniel J Nordman, and William Q Meeker. Methods to compute prediction intervals: A review and new results. *arXiv preprint arXiv:2011.03065*, 2020.

Aad Van Der Vaart and Jon A Wellner. A note on bounds for vc dimensions. *Institute of Mathematical Statistics collections*, 5:103, 2009.

Roman Vershynin. *High-dimensional probability: An introduction with applications in data science*, volume 47. Cambridge university press, 2018.

Vladimir Vovk. Conditional validity of inductive conformal predictors. In *Asian conference on machine learning*, pp. 475–490. PMLR, 2012.

Vladimir Vovk. Cross-conformal predictors. *Annals of Mathematics and Artificial Intelligence*, 74 (1):9–28, 2015.

Vladimir Vovk, Alexander Gammerman, and Glenn Shafer. *Algorithmic learning in a random world*. Springer Science & Business Media, 2005.

Vladimir Vovk, Ilia Nouretdinov, Valery Manokhin, and Alexander Gammerman. Cross-conformal predictive distributions. In *Conformal and Probabilistic Prediction and Applications*, pp. 37–51. PMLR, 2018.

Volodya Vovk, Alexander Gammerman, and Craig Saunders. Machine-learning applications of algorithmic randomness. 1999.

Yachong Yang and Arun Kumar Kuchibhotla. Finite-sample efficient conformal prediction. *arXiv preprint arXiv:2104.13871*, 2021.

A PROOF OF PROPOSITION 1

Recall that $C_t(x) = [f(x) - t, f(x) + t]$ satisfies $\ell_{\text{eff}}(C_t; (x, y)) = \text{length}(C_t(x)) = 2t$ for any (x, y). Also, we have

$$\mathbf{1}\left\{y \notin C_t(x)\right\} = \mathbf{1}\left\{y \notin [f(x) - t, f(x) + t]\right\} = \mathbf{1}\left\{|y - f(x)| > t\right\},$$

or equivalently $\mathbf{1}\left\{y \in C_t(x)\right\} = \mathbf{1}\left\{|y - f(x)| \leq t\right\}$. Therefore, problem (3) is equivalent to

$$\underset{t \geq 0}{\text{minimize}} \ \ t$$

$$\text{subject to } 1 - \widehat{L}_{\text{coverage}}(C_t) := \frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \mathbf{1}\left\{|y_i - f(x_i)| \leq t\right\} \geq 1 - \alpha.$$

By definition of quantiles, this problem is solved at

$$\widehat{t} = \lceil(1 - \alpha)n_{\text{cal}}\rceil \text{-th largest element of } \{|y_i - f(x_i)|\}_{i=1}^{n_{\text{cal}}},$$

which is the desired result. □

B PROOFS FOR SECTION 3

B.1 PROOF OF PROPOSITION 2

(a) As $C_{\widehat{\theta},\widehat{t}}$ solves problem (5), it satisfies the constraint $\widehat{L}_{\text{coverage}}(C_{\widehat{\theta},\widehat{t}}) \leq \alpha + \varepsilon_0$. Therefore,

$$L_{\text{coverage}}(C_{\widehat{\theta},\widehat{t}}) = \underbrace{\widehat{L}_{\text{coverage}}(C_{\widehat{\theta},\widehat{t}})}_{\leq \alpha + \varepsilon_0} + L_{\text{coverage}}(C_{\widehat{\theta},\widehat{t}}) - \widehat{L}_{\text{coverage}}(C_{\widehat{\theta},\widehat{t}})$$

$$\leq \alpha + \varepsilon_0 + \sup_{(\theta,t) \in \Theta \times \mathcal{T}} \left| L_{\text{coverage}}(C_{\theta,t}) - \widehat{L}_{\text{coverage}}(C_{\theta,t}) \right|$$

$$= \alpha + \varepsilon_0 + \varepsilon_{\text{coverage}}.$$

(b) Suppose $\varepsilon_{\text{coverage}} \leq \varepsilon_0$. Taking any $(\theta, t) \in \Theta \times \mathcal{T}$ such that $L_{\text{coverage}}(C_{\theta,t}) \leq \alpha$, we have

$$\widehat{L}_{\text{coverage}}(C_{\theta,t}) \leq L_{\text{coverage}}(C_{\theta,t}) + \varepsilon_{\text{coverage}} \leq \alpha + \varepsilon_{\text{coverage}} \leq \alpha + \varepsilon_0.$$

This shows that (θ, t) lies within the constraint set of problem (5). Thus as $(\widehat{\theta}, \widehat{t})$ further minimizes the loss $\widehat{L}_{\text{eff}}$ within the constraint set, we have $\widehat{L}_{\text{eff}}(C_{\widehat{\theta},\widehat{t}}) \leq \widehat{L}_{\text{eff}}(C_{\theta,t})$. This shows that

$$L_{\text{eff}}(C_{\widehat{\theta},\widehat{t}}) - L_{\text{eff}}(C_{\theta,t})$$

$$\leq \underbrace{\widehat{L}_{\text{eff}}(C_{\widehat{\theta},\widehat{t}}) - \widehat{L}_{\text{eff}}(C_{\theta,t})}_{\leq 0} + 2 \sup_{(\theta,t) \in \Theta \times \mathcal{T}} \left| \widehat{L}_{\text{eff}}(C_{\theta,t}) - L_{\text{eff}}(C_{\theta,t}) \right|$$

$$\leq 2\varepsilon_{\text{eff}}.$$

As the above holds simultaneously for all $(\theta, t) \in \Theta \times \mathcal{T}$ with at most α coverage loss, taking the sup over the left-hand side yields

$$L_{\text{eff}}(C_{\widehat{\theta},\widehat{t}}) - \inf_{\substack{(\theta,t) \in \Theta \times \mathcal{T} \\ L_{\text{coverage}}(C_{\theta,t}) \leq \alpha}} L_{\text{eff}}(C_{\theta,t}) \leq 2\varepsilon_{\text{eff}}.$$

□

B.2   PROOF OF PROPOSITION 3

We first bound $\varepsilon_{\text{coverage}}$. Fix any $\theta \in \Theta$, define

$$t_\theta(x, y) := \inf\left\{t \in \mathcal{T} : C_{\theta, t}(x) \ni y\right\} \tag{10}$$

to be the smallest possible $t \in \mathcal{T}$ such that the $C_{\theta, t}(x)$ contains y. Observe that, as $\{C_{\theta, t}(x)\}_{t \in \mathcal{T}}$ are nested sets, the coverage event can be rewritten as $\mathbf{1}\left\{y \in C_{\theta, t}(x)\right\} = \mathbf{1}\left\{t \geq t_\theta(x, y)\right\}$ for any (x, y). Therefore, we have

$$\sup_{t \in \mathcal{T}} \left|\widehat{L}_{\text{coverage}}(C_{\theta, t}) - L_{\text{coverage}}(C_{\theta, t})\right|$$

$$= \sup_{t \in \mathcal{T}} \left|\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \mathbf{1}\left\{y_i \notin C_{\theta, t}(x_i)\right\} - \mathbb{P}(Y \notin C_{\theta, t}(X))\right|$$

$$= \sup_{t \in \mathcal{T}} \left|\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \mathbf{1}\left\{y_i \in C_{\theta, t}(x_i)\right\} - \mathbb{P}(Y \in C_{\theta, t}(X))\right|$$

$$= \sup_{t \in \mathcal{T}} \left|\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \mathbf{1}\left\{t_\theta(x, y) \leq t\right\} - \mathbb{P}_{(x, y)}(t_\theta(X, Y) \leq t)\right|$$

$$= \sup_{t \in \mathcal{T}} \left|\widehat{F}_\theta(t) - F_\theta(t)\right|,$$

where we have defined $F_\theta : \mathbb{R} \to [0, 1]$ as the CDF of the random variable $t_\theta(X, Y)$ and similarly $\widehat{F}_\theta$ as the empirical CDF of the same random variable over the finite dataset D_{cal}. Applying the Dvoretzky-Kiefer-Wolfowitz (DKW) inequality (Massart, 1990, Corollary 1) yields that

$$\sup_{t \in \mathcal{T}} \left|\widehat{F}_\theta(t) - F_\theta(t)\right| \leq \sqrt{\frac{\log(2/\delta)}{2n_{\text{cal}}}}$$

with probability at least $1 - \delta$. Now, taking the union bound with respect to $\theta \in \Theta$ (where for each θ we plug in tail probability $\delta/2N_\Theta$) we get that with probability at least $1 - \delta/2$,

$$\varepsilon_{\text{coverage}} = \sup_{\theta \in \Theta} \sup_{t \in \mathcal{T}} \left|\widehat{L}_{\text{coverage}}(C_{\theta, t}) - L_{\text{coverage}}(C_{\theta, t})\right|$$

$$= \sup_{\theta \in \Theta} \sup_{t \in \mathcal{T}} \left|\widehat{F}_\theta(t) - F_\theta(t)\right| \leq \sqrt{\frac{\log(4N_\Theta/\delta)}{2n_{\text{cal}}}} \leq C\sqrt{\frac{\log(N_\Theta/\delta)}{n_{\text{cal}}}}. \tag{11}$$

for some absolute constant $C > 0$.

We next bound ε_{eff}. Fix any $\theta \in \Theta$. We have by standard symmetrization argument that

$$\mathbb{E}\left[\sup_{t \in \mathcal{T}} \left|\widehat{L}_{\text{coverage}}(C_{\theta, t}) - L_{\text{coverage}}(C_{\theta, t})\right|\right]$$

$$= \mathbb{E}\left[\sup_{t \in \mathcal{T}} \left|\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \ell_{\text{eff}}(C_{\theta, t}; (x_i, y_i)) - \mathbb{E}[\ell_{\text{eff}}(C_{\theta, t}; (X, Y))]\right|\right]$$

$$\leq 2\mathbb{E}_{(x_i, y_i), \varepsilon_i}\left[\sup_{t \in \mathcal{T}} \left|\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \varepsilon_i \ell_{\text{eff}}(C_{\theta, t}; (x_i, y_i))\right|\right]$$

$$\overset{(i)}{\leq} 2L_{\mathcal{T}} \cdot \mathbb{E}_{\varepsilon_i}\left[\sup_{t \in \mathcal{T}} \left|\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \varepsilon_i \cdot t\right|\right] = 2L_{\mathcal{T}} \cdot \mathbb{E}_{\varepsilon_i}\left[\left|\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \varepsilon_i\right| \cdot \sup_{t \in \mathcal{T}} |t|\right]$$

$$\overset{(ii)}{\leq} 2L_{\mathcal{T}} \cdot B_{\mathcal{T}} \cdot \mathbb{E}_{\varepsilon_i}\left[\left|\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \varepsilon_i\right|\right] \overset{(iii)}{\leq} 2L_{\mathcal{T}} \cdot B_{\mathcal{T}}/\sqrt{n_{\text{cal}}}.$$

Above, (i) used the Lipschitzness Assumption A2 and the Rademacher contraction inequality (Vershynin, 2018, Exercise 6.7.7); (ii) used Assumption B, and (iii) used $\mathbb{E}_{\varepsilon_i}\left[\left|\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \varepsilon_i\right|\right] \leq \left(\mathbb{E}_{\varepsilon_i}\left[\left(\frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \varepsilon_i\right)^2\right]\right)^{1/2} = 1/\sqrt{n_{\text{cal}}}$.

Next, as each loss $|\ell_{\text{eff}}(C_{\theta,t}; (x, y))| \leq M$ by Assumption A1, the random variable

$$\sup_{t \in \mathcal{T}} \left| \widehat{L}_{\text{coverage}}(C_{\theta,t}) - L_{\text{coverage}}(C_{\theta,t}) \right|$$

satisfies the M/n_{cal} finite-difference property. Therefore by McDiarmid's Inequality, we have with probability at least $1 - \delta$ that

$$\sup_{t \in \mathcal{T}} \left| \widehat{L}_{\text{coverage}}(C_{\theta,t}) - L_{\text{coverage}}(C_{\theta,t}) \right|$$

$$\leq \mathbb{E} \left[\sup_{t \in \mathcal{T}} \left| \widehat{L}_{\text{coverage}}(C_{\theta,t}) - L_{\text{coverage}}(C_{\theta,t}) \right| \right] + \sqrt{\frac{M^2 \log(1/\delta)}{2n_{\text{cal}}}}$$

$$\leq C \cdot \frac{L_{\mathcal{T}} B_{\mathcal{T}} + M \sqrt{\log(1/\delta)}}{\sqrt{n_{\text{cal}}}}.$$

Finally, by union bound over $\theta \in \Theta$ (where we plug in $\delta/2N_\Theta$ as tail probability into the above), we have with probability at least $1 - \delta/2$ that

$$\varepsilon_{\text{eff}} = \sup_{\theta \in \Theta} \sup_{t \in \mathcal{T}} \left| \widehat{L}_{\text{coverage}}(C_{\theta,t}) - L_{\text{coverage}}(C_{\theta,t}) \right|$$

$$\leq C \cdot \frac{L_{\mathcal{T}} B_{\mathcal{T}} + M \sqrt{\log(N_\Theta/\delta)}}{\sqrt{n_{\text{cal}}}}. \tag{12}$$

(11) together with (12) is the desired result. $\qquad\square$

B.3 PROOF OF PROPOSITION 4

(a) By assumption, the class of Boolean functions $\{(x, y) \mapsto \mathbf{1}\{y \notin C_{\theta,t}(x)\}\}_{(\theta,t) \in \Theta \times \mathcal{T}}$ has VC dimension $K + 1 < \infty$. Therefore by the standard Rademacher complexity bound for VC classes (Vershynin, 2018, Theorem 8.3.23) and McDiarmid's Inequality, we have with probability at least $1 - \delta/2$ that

$$\varepsilon_{\text{coverage}} = \sup_{(\theta,t) \in \Theta \times \mathcal{T}} \left| \frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \mathbf{1}\{y_i \notin C_{\theta,t}(x_i)y_i\} - \mathbb{P}(Y \notin C_{\theta,t}(X)) \right|$$

$$\leq C\sqrt{\frac{K+1}{n_{\text{cal}}}} + \sqrt{\frac{\log(2/\delta)}{2n_{\text{cal}}}} \leq C\sqrt{\frac{K + 1 + \log(1/\delta)}{n_{\text{cal}}}}.$$

(b) We have by standard symmetrization argument that

$$\mathbb{E}[\varepsilon_{\text{eff}}] = \mathbb{E} \left[\sup_{\theta \in \Theta, t \in \mathcal{T}} \left| \widehat{L}_{\text{eff}}(C_{\theta,t}) - L_{\text{eff}}(C_{\theta,t}) \right| \right]$$

$$= \mathbb{E} \left[\sup_{\theta \in \Theta, t \in \mathcal{T}} \left| \frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \ell_{\text{eff}}(C_{\theta,t}; (x_i, y_i)) - \mathbb{E}[\ell_{\text{eff}}(C_{\theta,t}; (X, Y))] \right| \right]$$

$$\leq 2\mathbb{E}_{(x_i,y_i),\varepsilon_i} \left[\sup_{\theta \in \Theta, t \in \mathcal{T}} \left| \frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \varepsilon_i \ell_{\text{eff}}(C_{\theta,t}; (x_i, y_i)) \right| \right] = 2R_n(\mathcal{C}).$$

Further by Assumption A1, the quantity ε_{eff} satisfies M/n_{cal} bounded-difference, so applying McDiarmid's Inequality gives that with probability at least $1 - \delta/2$,

$$\varepsilon_{\text{eff}} \leq \mathbb{E}[\varepsilon_{\text{eff}}] + \sqrt{\frac{2M^2 \log(2/\delta)}{n_{\text{cal}}}} \leq C \left[R_n(\mathcal{C}) + \sqrt{\frac{M^2 \log(1/\delta)}{n}} \right].$$

$\qquad\square$

C CASE STUDY: LINEAR CLASS

In this section, we study prediction intervals with a specific linear structure and show that it satisfies the conditions of the VC/Rademacher class of Proposition 4.

Concretely, suppose we have a regression task ($\mathcal{Y} = \mathbb{R}$), and the prediction interval $C_{\theta,t}(x)$ takes a linear form

$$C_{\theta,t}(x) = [\theta^\top \Phi_{\mathrm{lo}}(x) - t\sigma(x), \theta^\top \Phi_{\mathrm{hi}}(x) + t\sigma(x)], \tag{13}$$

where $\theta \in \Theta \subset \mathbb{R}^K$, $\Phi_{\mathrm{hi}}, \Phi_{\mathrm{lo}} : \mathcal{X} \to \mathbb{R}^K$ are feature maps such that $\Phi_{\mathrm{lo}}(x)_i \leq \Phi_{\mathrm{hi}}(x)_i$ for all $i \in [K]$, $\sigma : \mathcal{X} \to \mathbb{R}_{>0}$.

For intuitions, we can think of $\Phi_{\{\mathrm{hi,lo}\}}$ as pretrained representation functions and σ as an (optional) pretrained function for modeling the variability of $y|x$. Note that this encompasses linear ensembling of several existing methods, such as vanilla conformal regression (Lei et al., 2018) by taking $\Phi_{\mathrm{hi}} = \Phi_{\mathrm{lo}} = \Phi$ where each $\Phi_i : \mathcal{X} \to \mathbb{R}$ is a base predictor, as well as Conformalized Quantile Regression (Romano et al., 2019) where each $(\Phi_{\mathrm{lo},i}, \Phi_{\mathrm{hi},i})$ is a pair of learned lower and upper quantile functions.

Our goal is to find an optimal linear function of this representation that yields a shortest prediction interval (with fixed width) subject to valid coverage.

We assume that both the features and the parameters are bounded:

Assumption C (Bounded features and parameters). *We have $\sup_{\theta \in \Theta} \|\theta\| \leq B_\Theta$, $\sup_{x \in \mathcal{X}} \|\Phi(x)\| \leq B_\Phi$, $\sup_{x \in \mathcal{X}} \sigma(x) \leq B_\sigma$, and $\sup_{t \in \mathcal{T}} |t| \leq B_\mathcal{T}$.*

The following result shows that Proposition 4 is applicable on the linear class.

Corollary 6 (Coverage and length guarantees for linear class). *For the $(K+1)$-dimensional linear class (13), suppose Assumption C holds, and we take the efficiency loss to be the length of the interval: $\ell_{\mathrm{eff}}(C; (x,y)) := \mathrm{length}(C(x))$. Then, we have with probability at least $1 - \delta$ (over the calibration dataset D_{cal}) that*

$$\varepsilon_{\mathrm{coverage}} \leq C\sqrt{\frac{K + 1 + \log(1/\delta)}{n_{\mathrm{cal}}}}, \quad \text{and} \quad \varepsilon_{\mathrm{eff}} \leq C[B_\Theta B_\Phi + B_\mathcal{T} B_\sigma] \cdot \sqrt{\frac{\log(1/\delta)}{n_{\mathrm{cal}}}},$$

where $C > 0$ is an absolute constant.

Proof. We verify the conditions of Proposition 4. First, we have

$$\mathbf{1}\left\{y \notin C_{\theta,t}(x)\right\} = \mathbf{1}\left\{\max\left\{y - \theta^\top \Phi_{\mathrm{hi}}(x), \theta^\top \Phi_{\mathrm{lo}}(x) - y\right\} > t\sigma(x)\right\}.$$

The set within the indicator above is the union of two sets $\left\{(x,y) : y - \theta^\top \Phi_{\mathrm{hi}}(x) - t\sigma(x) > 0\right\}$ and $\left\{(x,y) : \theta^\top \Phi_{\mathrm{lo}}(x) - y - t\sigma(x) > 0\right\}$. Note that each family of sets (over $(\theta, t) \in \mathbb{R}^K \times \mathbb{R}$ are linear halfspaces with feature dimension $K + 2$), and thus has VC-dimension $\leq K + 2$. Applying the VC dimension bound for unions of sets (Van Der Vaart & Wellner, 2009, Theorem 1.1), we get $\mathrm{VC}(\mathcal{C}) \leq C'(K + 2 + K + 2) \leq C(K + 1)$ for some absolute constant $C > 0$. Therefore the condition of Proposition 4(a) holds from which we obtain the desired bound for $\varepsilon_{\mathrm{coverage}}$.

To bound $\varepsilon_{\mathrm{eff}}$, we first note that for any $(x, y) \in \mathcal{X} \times \mathbb{R}$,

$$|\ell_{\mathrm{eff}}(C_{\theta,t}; (x,y))| = |\mathrm{length}(C_{\theta,t}(x))|$$
$$= \theta^\top(\Phi_{\mathrm{hi}}(x) - \Phi_{\mathrm{lo}}(x)) + 2t\sigma(x) \leq \|\theta\| \|\Phi_{\mathrm{hi}}(x) - \Phi_{\mathrm{lo}}(x)\| + 2t\sigma(x)$$
$$\leq 2B_\Theta B_\Phi + 2B_\mathcal{T} B_\sigma =: M,$$

and thus the boundedness assumption (Assumption A1) holds with M defined above. Next, we have the following bound on the Rademacher complexity

$$R_{n_{\mathrm{cal}}}^{\mathrm{eff}}(\mathcal{C}) = \mathbb{E}\left[\sup_{(\theta,t) \in \Theta \times \mathcal{T}} \left|\frac{1}{n_{\mathrm{cal}}} \sum_{i=1}^{n_{\mathrm{cal}}} \varepsilon_i\left(\theta^\top(\Phi_{\mathrm{hi}}(x_i) - \Phi_{\mathrm{lo}}(x_i)) + 2t\sigma(x_i)\right)\right|\right]$$

$$\leq \mathbb{E}\left[\sup_{\theta\in\Theta}\left|\left\langle \theta, \frac{1}{n_{\text{cal}}}\sum_{i=1}^{n_{\text{cal}}}\varepsilon_i(\Phi_{\text{hi}}(x_i)-\Phi_{\text{lo}}(x_i))\right\rangle\right|\right] + \mathbb{E}\left[\sup_{t\in\mathcal{T}}\left|2t\cdot\frac{1}{n_{\text{cal}}}\sum_{i=1}^{n_{\text{cal}}}\varepsilon_i\sigma(x_i)\right|\right]$$

$$\leq \sup_{\theta\in\Theta}\|\theta\|\cdot\mathbb{E}\left[\left\|\frac{1}{n_{\text{cal}}}\sum_{i=1}^{n_{\text{cal}}}\varepsilon_i(\Phi_{\text{hi}}(x_i)-\Phi_{\text{lo}}(x_i))\right\|^2\right]^{1/2} + 2\sup_{t\in\mathcal{T}}|t|\cdot\mathbb{E}\left[\left(\frac{1}{n_{\text{cal}}}\sum_{i=1}^{n_{\text{cal}}}\varepsilon_i\sigma(x_i)\right)^2\right]^{1/2}$$

$$\leq B_{\Theta}\cdot\mathbb{E}\left[\frac{1}{n_{\text{cal}}}\|\Phi_{\text{hi}}(x_1)-\Phi_{\text{lo}}(x_1)\|^2\right]^{1/2} + 2B_{\mathcal{T}}\cdot\mathbb{E}\left[\frac{1}{n_{\text{cal}}}\sigma^2(x_1)\right]^{1/2}$$

$$\leq C\cdot\frac{B_{\Theta}B_{\Phi}+B_{\mathcal{T}}B_{\sigma}}{\sqrt{n_{\text{cal}}}}.$$

Applying Proposition 4(b), we get $\varepsilon_{\text{eff}} \leq C\cdot[B_{\Theta}B_{\Phi}+B_{\mathcal{T}}B_{\sigma}]\cdot\sqrt{\log(1/\delta)/n_{\text{cal}}}$ with probability at least $1-\delta$. This is the desired bound for ε_{eff}. $\qquad\square$

D   THEORETICAL GUARANTEE FOR `CP-Gen-Recal`

In this section we state and prove the formal theoretical guarantee for the `CP-Gen-Recal` algorithm (Algorithm 2).

Define the score $t_{\theta}(X,Y) := \inf\{t\in\mathcal{T} : Y\in C_{\theta,t}(X)\}$ and let $F_{\theta}(t) := \mathbb{P}(Y\in C_{\theta,t}(X)) = \mathbb{P}(t_{\theta}(X,Y)\leq t)$ denote its CDF.

Assumption D (Lower bounded density for score function). *For any $\theta\in\Theta$, $t_{\theta}(X,Y)$ has a positive density $f_{\theta}(t) = F'_{\theta}(t) > 0$ on $t\in\mathcal{T}$. Further, let $t_{\theta,1-\alpha} := \inf\{t\in\mathcal{T} : F_{\theta}(t)\geq 1-\alpha\}$ denote its $(1-\alpha)$ quantile, then there exists some constants $\underline{c}_0, \delta_0 > 0$ such that*

$$\inf_{t\in[t_{\theta,1-\alpha}-\delta_0, t_{\theta,1-\alpha}+\delta_0]}f_{\theta}(t) \geq \underline{c}_0.$$

Proposition 7 (Valid coverage and near-optimal efficiency for reconformalized algorithm). *The following holds for Algorithm 2:*

(a) (Valid coverage) For any possible $\widehat{\theta}\in\Theta$ learned in Line 1 and the resulting $\widehat{t}_{\text{recal}}$, we have

$$\mathbb{E}_{D_{\text{recal}}}\left[L_{\text{coverage}}(C_{\widehat{\theta},\widehat{t}_{\text{recal}}})\right] \leq \alpha, \quad\text{and thus}\quad \mathbb{P}_{D_{\text{recal}},(X,Y)}\left(Y\in C_{\widehat{\theta},\widehat{t}_{\text{recal}}}(X)\right)\geq 1-\alpha.$$

(b) (Efficiency) Suppose Assumptions A2 and D hold, $\max\left\{\varepsilon_{\text{coverage}}+1/n_{\text{cal}}, 2\sqrt{\log(1/\delta)/n_{\text{recal}}}\right\} \leq \underline{c}_0\delta_0$ (recall the definition of $\varepsilon_{\text{coverage}}$ in (7)), and $\varepsilon_{\text{coverage}}\leq\varepsilon_0$. Then for $\delta\leq 0.5$, we have with probability at least $1-\delta$ that

$$L_{\text{eff}}(C_{\widehat{\theta},\widehat{t}_{\text{recal}}}) \leq \min_{\substack{(\theta,t)\in\Theta\times\mathcal{T}\\ L_{\text{coverage}}(C_{\theta,t})\leq\alpha}} L_{\text{eff}}(C_{\theta,t}) + 2\varepsilon_{\text{eff}} + CL_{\mathcal{T}}\cdot\left[\varepsilon_{\text{coverage}}+\frac{1}{n_{\text{cal}}}+\sqrt{\frac{\log(1/\delta)}{n_{\text{recal}}}}\right]/\underline{c}_0.$$

Proof. (a) As the learned parameter $\widehat{\theta}$ (and thus the family of nested sets $C_{\widehat{\theta},t}$) is independent of the recalibration dataset D_{recal}, we have that the scores $t_{\widehat{\theta}}(x,y)$ on dataset D_{recal} and a new test point (X,Y) are exchangeable given any $\widehat{\theta}$. Therefore by (Gupta et al., 2019, Proposition 1), we have for any $\widehat{\theta}\in\Theta$ that

$$\mathbb{P}_{D_{\text{recal}},(X,Y)}\left(Y\in C_{\widehat{\theta},\widehat{t}_{\text{recal}}}(X)\right)\geq 1-\alpha,$$

or equivalently $\mathbb{E}_{D_{\text{recal}}}\left[L_{\text{coverage}}(C_{\widehat{\theta},\widehat{t}_{\text{recal}}})\right]\leq\alpha$.

(b) For any $\theta\in\Theta$, define the score function $t_{\theta}(x,y)$ the same as in (10), and similarly define the CDF $F_{\theta}(t) := \mathbb{P}(t_{\theta}(X,Y)\leq t)$ and its empirical counterpart $\widehat{F}_{\theta}^{\text{cal}}(t)$ and $\widehat{F}_{\theta}^{\text{recal}}(t)$ as the finite-sample version on dataset D_{cal} and D_{recal} respectively.

We first analyze $\widehat{t}$. By the same derivation as in (11), we have

$$\sup_{t \in \mathcal{T}} \left| \widehat{F}_{\widehat{\theta}}^{\mathrm{cal}}(t) - F_{\widehat{\theta}}(t) \right| \leq \sup_{(\theta, t) \in \Theta \times \mathcal{T}} \left| \widehat{F}_{\theta}^{\mathrm{cal}}(t) - F_{\theta}(t) \right| = \varepsilon_{\mathrm{coverage}}.$$

As $(\widehat{\theta}, \widehat{t})$ solves the constrained ERM (5) and the assumption that $\ell_{\mathrm{eff}}(C_{\theta, t}; (x, y))$ is monotone in t, we have that $\widehat{t}$ is the minimal value of $t \in \mathcal{T}$ such that $\widehat{F}_{\widehat{\theta}}^{\mathrm{cal}}(t) \geq 1 - \alpha$. Therefore, (as $|D_{\mathrm{cal}}| = n_{\mathrm{cal}}$ and $\{t_\theta(x_i, y_i)\}_{i \in D_{\mathrm{cal}}}$ are almost surely distinct by Assumption D,) we have

$$1 - \alpha \leq \widehat{F}_{\widehat{\theta}}^{\mathrm{cal}}(\widehat{t}) \leq 1 - \alpha + 1/n_{\mathrm{cal}}.$$

This shows that

$$\left| F_{\widehat{\theta}}(\widehat{t}) - F_{\widehat{\theta}}(t_{\widehat{\theta}, 1-\alpha}) \right| = \left| F_{\widehat{\theta}}(\widehat{t}) - (1 - \alpha) \right| \leq \varepsilon_{\mathrm{coverage}} + 1/n_{\mathrm{cal}},$$

where we recall that $t_{\widehat{\theta}, 1-\alpha}$ is the $(1 - \alpha)$ (population) quantile of $t_{\widehat{\theta}}(X, Y)$. Note that $F'_\theta(t) = f_\theta(t) \geq \underline{c}_0$ on $t \in [t_{\widehat{\theta}, 1-\alpha} - \delta_0, t_{\widehat{\theta}, 1-\alpha} + \delta_0]$ by Assumption D. Further, $\varepsilon_{\mathrm{coverage}} + 1/n_{\mathrm{cal}} \leq \underline{c}_0 \delta_0$. Therefore, by monotonicity of F_θ, we must have $\widehat{t} \in [t_{\widehat{\theta}, 1-\alpha} - \delta_0, t_{\widehat{\theta}, 1-\alpha} + \delta_0]$, and thus

$$\left| \widehat{t} - t_{\widehat{\theta}, 1-\alpha} \right| \leq (\varepsilon_{\mathrm{coverage}} + 1/n_{\mathrm{cal}})/\underline{c}_0. \tag{14}$$

We next analyze $\widehat{t}_{\mathrm{recal}}$. As the dataset D_{recal} is independent of $\widehat{\theta}$, we can apply the DKW Inequality (Massart, 1990, Corollary 1) to obtain that

$$\sup_{t \in \mathcal{T}} \left| \widehat{F}_{\widehat{\theta}}^{\mathrm{recal}}(t) - F_{\widehat{\theta}}(t) \right| \leq \sqrt{\frac{\log(1/\delta)}{2 n_{\mathrm{recal}}}}$$

with probability at least $1 - \delta$. Using a similar argument as above, we get (for $\delta \leq 0.5$)

$$\left| F_{\widehat{\theta}}(\widehat{t}_{\mathrm{recal}}) - F_{\widehat{\theta}}(t_{\widehat{\theta}, 1-\alpha}) \right| \leq \sqrt{\frac{\log(1/\delta)}{2 n_{\mathrm{recal}}}} + \frac{1}{n_{\mathrm{recal}}} \leq 2\sqrt{\frac{\log(1/\delta)}{n_{\mathrm{recal}}}}.$$

As $2\sqrt{\log(1/\delta)/n_{\mathrm{recal}}} \leq \underline{c}_0 \delta_0$, we can apply the similar argument as above to deduce that

$$\left| \widehat{t}_{\mathrm{recal}} - t_{\widehat{\theta}, 1-\alpha} \right| \leq 2\sqrt{\log(1/\delta)/n_{\mathrm{recal}}}/\underline{c}_0. \tag{15}$$

Combining (14) and (15) and using the Lipschitzness of the efficiency loss (Assumption A2), we get

$$L_{\mathrm{eff}}(C_{\widehat{\theta}, \widehat{t}_{\mathrm{recal}}}) - L_{\mathrm{eff}}(C_{\widehat{\theta}, \widehat{t}})$$
$$\leq L_{\mathcal{T}} \cdot |\widehat{t}_{\mathrm{recal}} - \widehat{t}| \leq L_{\mathcal{T}} \cdot \left(\left| \widehat{t}_{\mathrm{recal}} - t_{\widehat{\theta}, 1-\alpha} \right| + \left| t_{\widehat{\theta}, 1-\alpha} - \widehat{t} \right| \right)$$
$$\leq C L_{\mathcal{T}} \cdot \left[\varepsilon_{\mathrm{coverage}} + n_{\mathrm{cal}}^{-1} + \sqrt{\frac{\log(1/\delta)}{n_{\mathrm{recal}}}} \right] / \underline{c}_0.$$

Finally, as we assumed $\varepsilon_{\mathrm{coverage}} \leq \varepsilon_0$, the condition of Proposition 2(b) holds, so we have

$$L_{\mathrm{eff}}(C_{\widehat{\theta}, \widehat{t}}) \leq \inf_{\substack{(\theta, t) \in \Theta \times \mathcal{T} \\ L_{\mathrm{coverage}}(C_{\theta, t}) \leq \alpha}} L_{\mathrm{eff}}(C_{\theta, t}) + 2\varepsilon_{\mathrm{eff}}.$$

Summing the preceding two bounds, we get

$$L_{\mathrm{eff}}(C_{\widehat{\theta}, \widehat{t}_{\mathrm{recal}}}) \leq \inf_{\substack{(\theta, t) \in \Theta \times \mathcal{T} \\ L_{\mathrm{coverage}}(C_{\theta, t}) \leq \alpha}} L_{\mathrm{eff}}(C_{\theta, t}) + 2\varepsilon_{\mathrm{eff}} + C L_{\mathcal{T}} \cdot \left[\varepsilon_{\mathrm{coverage}} + n_{\mathrm{cal}}^{-1} + \sqrt{\frac{\log(1/\delta)}{n_{\mathrm{recal}}}} \right] / \underline{c}_0.$$

which is the desired result.

$$\square$$

Table 3: Information about the regression datasets. Here (n, d) denotes the (sample size, feature dim).

Dataset	n	d
MEPS_19 (mep, a)	15785	139
MEPS_20 (mep, b)	17541	139
MEPS_21 (mep, c)	15656	139
Facebook_1 (fac)	40948	53
Facebook_2 (fac)	81311	53
kin8nm (kin)	8192	8
naval (nav)	11934	17
bio (bio)	45730	9
blog_data (blo)	52397	280

E ADDITIONAL EXPERIMENTAL DETAILS

E.1 CONFORMAL QUANTILE FINETUNING

Datasets Our choice of the datasets follows (Feldman et al., 2021). We provide information about these datasets in Table 3.

All datasets are standardized so that inputs and labels have mean 0 and standard deviation 1, and split into (train, cal, recal, test) with size 70%, 10%, 10%, 10% (varying with the random seed).

Base predictor and optimization Our network architecture is a 3-layer MLP with width 64 and output dimension 2 (for the lower and upper quantile). We use momentum SGD with initial learning rate 10^{-3} and momentum 0.9, batch-size 1024, and run the optimization for a max of 10000 epochs. A 10x learning rate decay is performed if the validation loss on D_{cal} has not decreased in 10 epochs, and we stop the learning whenever the learning rate decay happens for 3 times. The loss function used in the summed pinball loss of level $\alpha/2$ for $\widehat{f}_{\text{lo}}$ and $1 - \alpha/2$ for $\widehat{f}_{\text{hi}}$, following (Romano et al., 2019).

Optimization details for `CP-Gen-Recal` For the conformal quantile finetuning procedure with our `CP-Gen-Recal`, we rewrite the miscoverage loss for the quantile-based prediction interval as

$$\mathbf{1}\left\{y \notin C_{\theta,t}(x)\right\} = \mathbf{1}\left\{t - \max\left\{\theta_{\text{lo}}^\top \widehat{\Phi}(x) - y, y - \theta_{\text{hi}}^\top \widehat{\Phi}(x)\right\} < 0\right\}.$$

(In practice our θ also includes a trainable bias same as the original top linear layer; here we abuse notation slightly to allow easier presentation.) We approximate the right-hand side above with the hinge loss to obtain the formulation (8). To solve that optimization problem, we use SGD on (θ, t) with learning rate 0.01 and (ascent on) λ with learning rate 0.1. The batch-size here is 256 and the number of episodes is 1000. To ensure $t > 0$ we use a log parametrization for t. Finally, t_{recal} is computed by the reconformalization step in Algorithm 2 on D_{recal}.

E.2 MULTI-OUTPUT REGRESSION

Datasets We generate offline datasets consisting of (state, action, next_state) pairs within RL tasks within the OpenAI Gym (Brockman et al., 2016). For each task, the data is generated by executing a medium-performing *behavior policy* that is extracted from standard RL training runs. All tasks are continuous state and continuous action. Table 4 summarizes the state and action dimension, along with the reward of the policies used for generating the data. All datasets contain 200K examples.

All datasets are standardized so that inputs and labels have mean 0 and standard deviation 1, and split into (train, cal, recal, test) with size 70%, 10%, 10%, 10% (varying with the random seed).

Base predictor and optimization Our network architecture is a 3-layer MLP with width 64, input dimension $d_{\text{in}} = d_S + d_A$, and output dimension $d_{\text{out}} = d_S$. We use momentum SGD with initial learning rate 10^{-3}, momentum 0.9, and batch-size 512. We run the optimization for 1000 epochs with a 10x learning rate decay at epoch 500. The loss function for training the network is the standard MSE loss.

Table 4: Information about the next-state prediction datasets. Here (d_S, d_A) denotes the (state, action) dimension of the corresponding RL task. For datasets with a (slim) note only extract a subset of the full state (so that d_S is less than the full state dimension). We also report the mean reward of the behavior policies.

RL Task	d_S	d_A	mean reward
Cartpole	4	1	107
Half-Cheetah	17	6	8015
Ant (slim)	27	8	4645
Walker	17	6	3170
Swimmer	8	2	51
Hopper	11	3	2066
Humanoid (slim)	45	17	1357

Optimization details for `CP-Gen-Recal` For the conformal quantile finetuning procedure with our `CP-Gen-Recal`, we rewrite the miscoverage loss for the box-shaped prediction set as

$$\mathbf{1}\{y \notin C_u(x)\} = \mathbf{1}\left\{y \notin \prod_{i=1}^{d_{\text{out}}}[\widehat{f}_i(x) - u_i, \widehat{f}_i(x) + u_i]\right\} = \mathbf{1}\left\{1 - \max_{1 \le i \le d_{\text{out}}}|y_i - \widehat{f}_i(x)|/u_i < 0\right\}.$$

where we recall $u \in \mathbb{R}^{d_{\text{out}}}$ is the learnable parameter within the initial optimization stage of `CP-Gen-Recal` as discussed in Section 5.2. We approximate the right-hand side above with the hinge loss to obtain the formulation (8). To solve that optimization problem, we use SGD on (θ, t) with learning rate 0.01 and (ascent on) λ with learning rate 0.01. The batch-size here is 1024 and the number of episodes is 1000. To ensure $u > 0$ we use a log parametrization for u.

For the reconformalization step, we keep the (relative) ratios of the $\widehat{u}$ obtained above (as the $\widehat{\theta}$), and then reconformalize an additional $t_{\text{recal}} > 0$ on D_{recal} via the proportional reshaping of (9).

E.3 Details for Figure 1

Figure 1 is obtained on one run of our conformal quantile finetuning experiment on the MEPS_19 dataset, and illustrates the coverage-efficiency tradeoff. Both figures there compute the coverage and length on the (unseen) test set D_{test}, for better illustration. Figure 1 Left plots the family $[\widehat{f}_{\text{lo}}(x) - t, \widehat{f}_{\text{hi}}(x) + t]$ used by Conformalized Quantile Regression. Figure 1 Right plots the family

$$C_{\theta,t}(x) = [\theta_{\text{lo}}^\top \widehat{\Phi}(x) - t, \theta_{\text{hi}}^\top \widehat{\Phi}(x)].$$

The specific function class of θ shown in the thinner lines is a finite set of linear interpolations of the original $\widehat{\theta}_0$ obtained in QR and the new $\widehat{\theta}$ obtained by conformal quantile finetuning, with combination weights within $\{-0.3, -0.2, \ldots, 1.0\}$. The shaded region is then obtained by filling in the area.

F Results for label prediction sets on ImageNet

Here we present the ImageNet label prediction set experiment abbreviated in Section 5.

Dataset and model We take $K = 9$ large-scale pretrained neural networks on the ImageNet training set (Deng et al., 2009). Our models are {ResNeXt101, ResNet152, ResNet101, DenseNet161, ResNet18, ResNet50, VGG16, Inception, ShuffleNet}, similar as in (Angelopoulos et al., 2020).

We then consider task of constructing label prediction sets with valid coverage and small cardinality. We train and test out conformal procedures on the following two datasets, neither seen by the pretrained models:

(1) ImageNet-Val: The original validation set of ImageNet with 50000 images. We randomly split (varying with seed) this into $|D_{\text{cal}}| = 10000$, $|D_{\text{recal}}| = 10000$, and $|D_{\text{test}}| = 30000$.

(2) ImageNet-V2 (Recht et al., 2019): A new validation set following the roughly the same collection routines of the original images in ImageNet, however believed to have a mild distribution shift and thus slightly harder for classifiers pretrained on ImageNet. This dataset contains 10000 images, which we randomly split (varying with seed) into $|D_{\text{cal}}| = 4000$, $|D_{\text{recal}}| = 1000$, and $|D_{\text{test}}| = 5000$.

Table 5: **Results for ImageNet Prediction Sets with Conformal Ensembling.** For each method we report the (test) coverage and set size. Each entry reports the (mean, std) over 8 random seeds.

	Best single model		Uniform ensemble		Ensemble via `CP-Gen-Recal` (ours)	
Dataset	Coverage(%)	Size	Coverage(%)	Size	Coverage(%)	Size
ImageNet-Val	90.10 ± 0.29	1.70 ± 0.03	90.13 ± 0.21	1.62 ± 0.02	90.11 ± 0.33	$\mathbf{1.51 \pm 0.03}$
ImageNetV2	90.01 ± 0.71	5.00 ± 0.24	89.93 ± 0.71	4.66 ± 0.22	90.18 ± 0.85	$\mathbf{4.39 \pm 0.44}$

Methods for learning prediction sets Our constructions of the prediction sets are based on the Least Ambiguous Set-Valued Classifier (LAC) method of (Sadinle et al., 2019), which turns any base predictor p where $p(\cdot|x)$ denotes the predicted distribution of the $L = 1000$ labels into a prediction set $C_t(x)$ via

$$C_t(x) = \{y \in [L] : p(y|x) > t\},$$

where t is found by conformal prediction.

We consider learning a valid prediction set with smaller set size by finding an optimized *ensemble weight* of the K base predictors using our `CP-Gen-Recal` algorithm. This means we learn prediction sets of the form

$$C_{\theta,t}(x) = \left\{ y \in [L] : p_\theta(y|x) := \sum_{i=1}^{K} \theta_i p_i(y|x) > t \right\},$$

where $\{p_i\}_{i \in [K]}$ are the base predictors.

Our `CP-Gen-Recal` algorithm (and its practical implementation (8)) would solve a primal-dual optimization problem with the efficiency loss and hinge approximate coverage constraint to optimize (θ, t). However, here the efficiency loss we care about (the cardinality) is non-differentiable. We make a further approximation by considering the L_p^p norm with $p = 0.5$ as the surrogate efficiency loss:

$$\ell_{\text{eff}}(\theta, t; (x_i, y_i)) := \sum_{y'=1}^{L} [p_\theta(y'|x_i) - t]_+^p,$$

with the intuition that the $p \to 0$ limit is exactly the cardinality of $C_{\theta,t}(x_i)$. Our final optimization problem is then

$$\min_{\theta \in \Delta_K, t > 0} \max_{\lambda > 0} \frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \sum_{y'=1}^{L} [p_\theta(y'|x_i) - t]_+^p + \lambda \frac{1}{n_{\text{cal}}} \sum_{i=1}^{n_{\text{cal}}} \ell_{\text{hinge}}(p_\theta(y_i|x_i) - t).$$

We solve this by SGD on (θ, t) and (ascent on) λ, with the softmax parameterization for θ ($\theta \in \Delta_K$ as an ensemble weight is a probability distribution) and log parametrization for $t > 0$. The learning rate is 10^{-2} for (θ, t) and 10^{-4} for λ. We perform this optimization for 500 epochs over D_{cal} with batch-size 256 for ImageNet-Val and 64 for ImageNet-V2.

After we obtain the iterates $\left\{\widehat{\theta}_i\right\}$ (where i denotes the epoch count), we perform a further iterate selection of first re-computing the $\widehat{t}(\widehat{\theta}_i)$ by conformalizing on D_{cal}, and then choosing the iterate i with the best average set size also on D_{cal}, before feeding it into the reconformalization step with D_{recal}. As the D_{recal} is only used in the reconformalization step, such as method still guarantees valid coverage like the original Algorithm 2.

We compare our above algorithm against two baselines: conformalizing each individual model and reporting the best one, or conformalizing the uniform ensemble (which uses weights $\theta_{\text{unif}} = \frac{1}{K}\mathbf{1}_K$). For these two baselines, for fairness of comparison, we allow them to use the whole $D_{\text{cal}} \cup D_{\text{recal}}$ as the calibration set, as their construction (apart from pre-training) is not data-dependent.

Results Table 5 shows that our algorithm is able to learn label prediction sets with valid coverage and improved set sizes over the baselines. This demonstrates the advantage of our method even in applications where the efficiency loss (here set size) is non-differentiable and needs to be further approximated to allow gradient-based algorithms.

G ABLATION STUDIES

G.1 CONFORMAL QUANTILE FINETUNING

We report ablation results for the conformal quantile finetuning problem with nominal coverage level $1 - \alpha \in \{80\%, 95\%\}$, and otherwise exactly the same setup as Section 5.1. The conclusions are qualitatively the same as the 90% version presented in Table 1.

Table 6: **Results for conformal quantile finetuning** on real-data regression tasks at level $1 - \alpha = 80\%$. For each method we report the (test) coverage, length, and pinball loss of the corresponding base quantile predictor. All results are averaged over 8 random seeds.

Dataset	CQR			QR + CP-Gen-Recal (ours)		
	Coverage(%)	Length	$L_{\text{pinball}}^{\text{test}}$	Coverage(%)	Length	$L_{\text{pinball}}^{\text{test}}$
MEPS_19	80.42	0.702	0.154	80.45	**0.514**	0.190
MEPS_20	80.44	0.707	0.161	80.48	**0.466**	0.200
MEPS_21	79.91	0.696	0.151	79.85	**0.618**	0.192
Facebook_1	80.38	0.348	0.072	80.01	**0.198**	0.137
Facebook_2	79.96	0.329	0.063	79.80	**0.189**	0.138
kin8nm	79.59	0.865	0.119	78.69	**0.832**	0.125
naval	79.91	2.777	0.311	79.76	**2.721**	0.311
bio	80.07	1.791	0.222	80.54	**1.674**	0.248
blog_data	80.64	0.399	0.082	80.10	**0.272**	0.158
Nominal $(1 - \alpha)$	80.00	-	-	80.00	-	-

Table 7: **Results for conformal quantile finetuning** on real-data regression tasks at level $1 - \alpha = 95\%$. For each method we report the (test) coverage, length, and pinball loss of the corresponding base quantile predictor. All results are averaged over 8 random seeds.

Dataset	CQR			QR + CP-Gen-Recal (ours)		
	Coverage(%)	Length	$L_{\text{pinball}}^{\text{test}}$	Coverage(%)	Length	$L_{\text{pinball}}^{\text{test}}$
MEPS_19	94.60	1.674	0.078	95.10	**1.292**	0.091
MEPS_20	94.72	1.650	0.081	94.78	**1.261**	0.097
MEPS_21	94.64	1.633	0.071	94.99	**1.351**	0.086
Facebook_1	94.96	0.797	0.036	95.04	**0.601**	0.061
Facebook_2	95.17	0.700	0.031	94.98	**0.560**	0.060
kin8nm	95.15	1.602	0.047	94.95	**1.557**	0.048
naval	94.87	3.308	0.084	94.83	**3.265**	0.088
bio	95.17	2.698	0.073	95.22	**2.587**	0.084
blog_data	95.07	0.862	0.040	95.09	**0.744**	0.068
Nominal $(1 - \alpha)$	95.00	-	-	95.00	-	-

G.2 MULTI-OUTPUT REGRESSION

We report ablation results for the multi-output regression problem with nominal coverage level $1 - \alpha \in \{80\%, 95\%\}$, and otherwise exactly the same setup as Section 5.2. The conclusions are qualitatively the same as the 90% version presented in Table 2, except for one dataset at level 95%.

G.3 COMPARISON OF CP-Gen AND CP-Gen-Recal

We compare the performance of CP-Gen and CP-Gen-Recal on the multi-output regression tasks using the same setup as Section 5.2. Recall that the vanilla CP-Gen optimizes both $(\widehat{\theta}, \widehat{t})$ on D_{cal} (we additionally reconformalize $\widehat{t}$ on the same D_{cal} to address the potential bias in $\widehat{t}$ brought by the approximate optimization (8)), whereas our main CP-Gen-Recal algorithm optimizes $\widehat{\theta}$ on D_{cal} and reconformalizes $\widehat{t}_{\text{recal}}$ on D_{recal}.

Table 10 reports the results. Observe that, except for the volume on one dataset (Humanoid), there is no significant difference in both the coverage and the volume for the two methods. For practice we recommend CP-Gen-Recal whenever the exact coverage guarantee is important, yet this result

Table 8: **Results for multi-output regression** on next-state prediction tasks, at level $1 - \alpha = 80\%$. For each method we report the (test) coverage and volume of its learned box-shaped prediction set. All results are averaged over 8 random seeds.

Dataset	Coord-wise Coverage(%)	Volume	Coord-wise-Recal Coverage(%)	Volume	CP-Gen-Recal (ours) Coverage(%)	Volume
Cartpole	87.82	1.74×10^{-6}	80.08	7.83×10^{-7}	80.09	$\mathbf{7.45 \times 10^{-7}}$
Half-Cheetah	88.28	4.26×10^{-7}	79.96	2.42×10^{-8}	80.04	$\mathbf{1.37 \times 10^{-8}}$
Ant	87.77	1.97×10^{-5}	80.12	3.97×10^{-7}	80.06	$\mathbf{1.75 \times 10^{-7}}$
Walker	90.25	5.88×10^{-7}	80.28	3.13×10^{-9}	80.28	$\mathbf{1.45 \times 10^{-9}}$
Swimmer	91.49	1.33×10^{-6}	79.99	6.18×10^{-8}	79.97	$\mathbf{4.32 \times 10^{-9}}$
Hopper	86.47	3.25×10^{-10}	79.87	7.40×10^{-11}	79.97	$\mathbf{4.41 \times 10^{-11}}$
Humanoid	90.84	2.86×10^{-7}	80.05	9.47×10^{-13}	80.02	$\mathbf{2.41 \times 10^{-13}}$
Nominal $(1 - \alpha)$	80.00	-	80.00	-	80.00	-

Table 9: **Results for multi-output regression** on next-state prediction tasks, at level $1 - \alpha = 95\%$. For each method we report the (test) coverage and volume of its learned box-shaped prediction set. All results are averaged over 8 random seeds.

Dataset	Coord-wise Coverage(%)	Volume	Coord-wise-Recal Coverage(%)	Volume	CP-Gen-Recal (ours) Coverage(%)	Volume
Cartpole	97.21	1.07×10^{-4}	95.10	4.60×10^{-5}	95.12	$\mathbf{8.61 \times 10^{-6}}$
Half-Cheetah	96.80	2.37×10^{-4}	95.03	4.03×10^{-5}	95.01	$\mathbf{3.29 \times 10^{-5}}$
Ant	96.65	5.30×10^{-1}	95.02	4.87×10^{-2}	95.09	$\mathbf{2.39 \times 10^{-2}}$
Walker	97.01	8.08×10^{-4}	94.94	6.21×10^{-5}	94.99	$\mathbf{4.27 \times 10^{-5}}$
Swimmer	97.74	3.44×10^{-4}	94.95	3.77×10^{-5}	95.01	$\mathbf{5.34 \times 10^{-6}}$
Hopper	96.27	1.76×10^{-8}	94.96	$\mathbf{8.23 \times 10^{-9}}$	94.96	1.19×10^{-8}
Humanoid	97.22	3.58×10^{-1}	94.99	7.69×10^{-4}	94.91	$\mathbf{7.49 \times 10^{-4}}$
Nominal $(1 - \alpha)$	95.00	-	95.00	-	95.00	-

shows that—perhaps originating from the fact that here $n_{\mathrm{cal}} = 20000$ is large—the coverage (generalization error) of CP-Gen is also nearly valid, which may be better than what our Proposition 2 suggests.

Table 10: Comparison of CP-Gen and CP-Gen-Recal on the multi-output regression tasks.

Dataset	CP-Gen-Recal Coverage(%)	Volume	CP-Gen Coverage(%)	Volume
Cartpole	90.12	2.30×10^{-6}	90.09	2.30×10^{-6}
Half-Cheetah	90.02	9.07×10^{-7}	89.96	8.83×10^{-7}
Ant	90.02	8.25×10^{-5}	89.98	8.21×10^{-5}
Walker	89.94	3.47×10^{-7}	89.91	3.30×10^{-7}
Swimmer	90.13	1.46×10^{-7}	89.96	1.29×10^{-7}
Hopper	89.92	8.25×10^{-10}	89.92	8.23×10^{-10}
Humanoid	89.94	4.95×10^{-8}	90.05	7.08×10^{-8}
Nominal	90.00	-	90.00	-