FedBABU: Toward Enhanced Representation for Federated Image Classification

Abstract

Federated learning has evolved to improve a single global model under data heterogeneity (as a curse) or to develop multiple personalized models using data heterogeneity (as a blessing). However, little research has considered both directions simultaneously. In this paper, we first investigate the relationship between them by analyzing Federated Averaging (McMahan et al., 2017) at the client level and determine that a better federated global model performance does not constantly improve personalization. To elucidate the cause of this personalization performance degradation problem, we decompose the entire network into the body (i.e., extractor), which is related to universality, and the head (i.e., classifier), which is related to personalization. We then point out that this problem stems from training the head. Based on this observation, we propose a novel federated learning algorithm, coined FedBABU, which only updates the body of the model during federated training (i.e., the head is randomly initialized and *never* updated), and the head is fine-tuned for personalization during the evaluation process. Extensive experiments show consistent performance improvements and an efficient personalization of FedBABU. The code is available at `https://anonymous.4open.science/r/ICLR2022-FedBABU`.

1 Introduction

Federated learning (FL) (McMahan et al., 2017), which is a distributed learning framework with personalized data, has become an attractive field of research. From the early days of this field, improving *a single global model* across devices has been the main objective (Zhao et al., 2018; Duan et al., 2019; Li et al., 2018; Acar et al., 2021), where the global model suffers from data heterogeneity. Many researchers have recently focused on *multiple personalized models* by leveraging data heterogeneity across devices as a blessing in disguise (Chen et al., 2018; Dinh et al., 2021; Zhang et al., 2020; Fallah et al., 2020; Shamsian et al., 2021; Smith et al., 2017). Although many studies have been conducted on each research line, a lack of research remains on how to train a good global model for personalization purposes (Ji et al., 2021; Jiang et al., 2019). In this study, for personalized training, each local client model starts from a global model that learns information from all clients and leverages the global model to fit its own data distribution.

Jiang et al. (2019) analyzed personalization methods that adapt to the global model through fine-tuning on each device. They observed that the effects of fine-tuning are encouraging and that training in a central location increases the initial accuracy (of a single global model) while decreasing the personalized accuracy (of on-device fine-tuned models). We focus on *why* opposite changes in the two performances appear. This suggests that the factors for universality and personalization must be dealt with separately, inspiring us to decouple the entire network into the body (i.e., extractor) related to generality and the head (i.e., classifier) related to specialty, as in previous studies (Kang et al., 2019; Yu et al., 2020; Yosinski et al., 2014; Devlin et al., 2019) for advanced analysis. Note that popular networks have one linear layer (e.g., MobileNet (Howard et al., 2017) and ResNet (He et al., 2016)), and the head is defined as this linear layer whereas the body is defined as all of the layers except the head. The body of the model is related to representation learning and the head of the model is related to linear decision boundary learning. We shed light on the cause of the personalization performance degradation by decoupling parameters, pointing out that such a problem stems from training the head.

(a) FedAvg.

(b) FedBABU.

Figure 1: **Difference in the local update and aggregation stages between FedAvg and FedBABU**. In the figure, the lines represent the decision boundaries defined by the head (i.e., the last linear classifier) of the network; different shapes indicate different classes. It is assumed that each client has two classes. (a) FedAvg updates the entire network during local updates on each client and then the local networks are aggregated entirely. Therefore, the heads of all clients and the head of the server are different. Whereas, (b) FedBABU only updates the body (i.e., all of the layers except the head) during local updates on each client and then the local networks are aggregated body-partially. Therefore, the heads of all clients and the head of the server are the same.

Inspired by the above observations, we propose an algorithm to learn a single global model that can be efficiently personalized by simply changing the Federated Averaging (FedAvg) (McMahan et al., 2017) algorithm. FedAvg consists of four stages: client sampling, broadcasting, local update, and aggregation. In the client sampling stage, clients are sampled because the number of clients is so large that not all clients can participate in each round. In the broadcasting stage, the server sends a global model (i.e., an initial random model at the first broadcast stage or an aggregated model afterward) to participating clients. In the local update stage, the broadcast model of each device is trained based on its own data set. In the aggregation stage, locally updated models are sent to the server and are aggregated by averaging. Among the four stages, we focus on the *local update* stage from both the universality and personalization perspectives. *Here, we only update the body of the model in the local update stage, i.e., the head is never updated during federated training.* From this, we propose FedBABU, **Fed**erated Averaging with **B**ody **A**ggregation and **B**ody **U**pdate. Figure 1 describes the difference during the local update and aggregation stages between FedAvg and FedBABU. *Intuitively, our approach is representation learning based on the same fixed criteria across all clients during federated training*. This simple change improves the representation power of a single global model and enables the more accurate and rapid personalization of the trained global model than FedAvg.

Our contributions are summarized as follows:

- We investigate the connection between a single global model and fine-tuned personalized models by analyzing the FedAvg algorithm at the client level and show that training the head using shared data on the server negatively impacts personalization.
- We demonstrate that a fixed random classifier can have comparable performance to a learned classifier in the centralized setting. From this observation, we suggest that sharing a fixed random classifier across all clients can be more potent than averaging each learned classifier in federated settings.
- We propose a novel algorithm, **FedBABU**, that reduces the update and aggregation parts from the entire model to the body of the model during federated training. We show that FedBABU is efficient, particularly under more significant data heterogeneity. Furthermore, a single global model trained with the FedBABU algorithm can be personalized rapidly (even with one fine-tuning epoch), and the personalization performance of FedBABU outshines that of FedAvg and other existing personalization FL algorithms.
- We adapt the body update and body aggregation idea to the regularization-based global federated learning algorithm (such as FedProx (Li et al., 2018)). We show that regularization reduces the personalization capabilities and that this problem is mitigated through BABU.

2 RELATED WORKS

FL for a Single Global Model Canonical federated learning, FedAvg proposed by McMahan et al. (2017), aims to learn a single global model that collects the benefits of affluent data without storing the clients' raw data in a central server, thus reducing the communication costs through local updates. However, it is difficult to develop a globally optimal model for non-independent and identically distributed (non-IID) data derived from various clients. To solve this problem, studies have been conducted that make the data distribution of the clients IID-like or add regularization to the distance from the global model during local updates. Zhao et al. (2018) suggested that all clients share a subset of public data, and Duan et al. (2019) augmented data to balance the label distribution of clients. Recently, two studies (Li et al., 2018; Acar et al., 2021) penalized local models that have a large divergence from the global model, adding a regularization term to the local optimization process and allowing the global model to converge more reliably. However, it should be noted that the single global model trained using the above methods is not optimized for each client.

Personalized FL Personalized federated learning aims to learn personalized local models that are stylized to each client. Although local models can be developed without federation, this method suffers from data limitations. Therefore, to maintain the benefits of the federation and personalized models, many other methods have been applied to FL: clustering, multi-task learning, transfer learning, regularized loss function, and meta-learning. Two studies (Briggs et al., 2020; Mansour et al., 2020) clustered similar clients to match the data distribution within a cluster and learned separate models for each cluster without inter-cluster federation. Similar to clustering, multi-task learning aims to learn models for related clients simultaneously. Note that clustering ties related clients into a single cluster, whereas multi-task learning does not. The generalization of each model can be improved by sharing representations between related clients. Smith et al. (2017) and Dinh et al. (2021) showed that multi-task learning is an appropriate learning scheme for personalized FL. Transfer learning is also a recommended learning scheme because it aims to deliver knowledge among clients. In addition, Yang et al. (2020) and Chen et al. (2020b) utilized transfer learning to enhance local models by transferring knowledge between related clients. T Dinh et al. (2020) and Li et al. (2021) added a regularizer toward the global or average personalized model to prevent clients' models from simply overfitting their own dataset. Unlike the aforementioned methods that developed local models during training, Chen et al. (2018) and Fallah et al. (2020) attempted to develop a good initialized shared global model using bi-level optimization through a Model-Agnostic Meta-Learning (MAML) approach (Finn et al., 2017). A well-initialized model can be personalized through updates on each client (such as inner updates in MAML). Jiang et al. (2019) argued that the FedAvg algorithm could be interpreted as a meta-learning algorithm, and a personalized local model with high accuracy can be obtained through fine-tuning from a global model learned using FedAvg. In addition, various technologies and algorithms for personalized FL have been presented and will be helpful to read; see Tan et al. (2021) and Kulkarni et al. (2020) for more details.

Decoupling the Body (Extractor) and the Head (Classifier) for Personalized FL The training scheme that involves decoupling the entire network into the body and the head has been used in various fields, including long-tail recognition (Kang et al., 2019; Yu et al., 2020), noisy label learning (Zhang & Yao, 2020), and meta-learning (Oh et al., 2021; Raghu et al., 2019).[1] For personalized FL, there have been attempts to use this decoupling approach. For a consistent explanation, we describe each algorithm from the perspective of local update and aggregation parts. FedPer (Arivazhagan et al., 2019) learns the entire network jointly during local updates and only aggregates the bottom layers. When the bottom layers are matched with the body, the body is shared on all clients and the head is personalized to each client. LG-FedAvg (Liang et al., 2020) learns the entire network jointly during local updates and only aggregates the top layers based on the pre-trained global network via FedAvg. When the top layers are matched with the head, the body is personalized to each client and the head is shared on all clients. FedRep (Collins et al., 2021) learns the entire network sequentially during local updates and only aggregates the body. In the local update stage, each client first learns a classifier only with the aggregated representation and then learns an extractor only with its own classifier within a single epoch. Unlike the above decoupling methods, we propose a FedBABU algorithm that learns only the body with a randomly initialized classifier during local updates and aggregates only the body. It is thought that fixing a classifier during the entire federated training provides the same guidelines on learning representations across all clients. Then, personalized local models can be obtained by fine-tuning the head.

---

[1]Although there are more studies related to decoupling parameters (Rusu et al., 2018; Lee & Choi, 2018; Flennerhag et al., 2019; Chen et al., 2019b), we focus on decoupling the entire network into the body and head.

3 PRELIMINARIES

FL training procedure   We summarize the training procedure of FL following the aforementioned four stages with formal notations. Let $\{1, \cdots, N\}$ be the set of all clients. Then, the participating clients in the communication round k with client fraction ratio f is $C^k = \{C_i^k\}_{i=1}^{\lfloor Nf \rfloor}$. By broadcasting, the local parameters of the participating clients $\{\theta_i^k(0)\}_{i=1}^{\lfloor Nf \rfloor}$ are initialized by the global parameter θ_G^{k-1}, that is, $\theta_i^k(0) \leftarrow \theta_G^{k-1}$ for all $i \in [1, \lfloor Nf \rfloor]$ and $k \in [1, \mathrm{K}]$. Note that θ_G^0 is randomly initialized first. On its own device, each local model is updated using a locally kept data set. After local epochs τ, the locally updated models become $\{\theta_i^k(\tau I_i^k)\}_{i=1}^{\lfloor Nf \rfloor}$, where I_i^k is the number of iterations of one epoch on client C_i^k (i.e., $\lceil \frac{n_{C_i^k}}{B} \rceil$), $n_{C_i^k}$ is the number of data samples for client C_i^k, and B is the batch size. Therefore, τI_i^k is the total number of updates in one communication interval. Note that our research mainly deals with a balanced environment in which all clients have the same size data set (i.e., I_i^k is a constant for all k and i).[2] Finally, the global parameter θ_G^k is aggregated by $\sum_{i=1}^{\lfloor Nf \rfloor} \frac{n_{C_i^k}}{n} \theta_i^k(\tau I_i^k)$, where $n = \sum_{i=1}^{\lfloor Nf \rfloor} n_{C_i^k}$, at the server. For our algorithm, the parameters θ are decoupled into the extractor parameters θ_{ext} and the classifier parameters $\theta_{cls} \in \mathbb{R}^{C \times d}$, where d is the dimension of the last representations and C is the number of classes.

Experimental setup   We mainly use MobileNet on CIFAR100.[3] We set the number of clients to 100 and then each client has 500 training data and 100 test data; the classes in the training and test data sets are the same. For the heterogeneous distribution of client data, we refer to the experimental setting in McMahan et al. (2017). We sort the data by labels and divide the data into the same-sized shards. Because there is no overlapping data between shards, the size of a shard is defined by $\frac{|D|}{N \times s}$, where $|D|$ is the data set size, N is the total number of clients, and s is the number of shards per user. We control FL environments with three hyperparameters: client fraction ratio f, local epochs τ, and shards per user s. f is the number of participating clients out of the total number of clients in every round and a small f is natural in the FL settings because the total number of clients is numerous. The local epochs τ are equal to the interval between two consecutive communication rounds. To fix the number of total updates to ensure the consistency in all experiments, we fix the product of communication rounds and local epochs to 320 (e.g., if local epochs are four, then the total number of communication rounds is 80). The learning rate starts with 0.1 and is decayed 0.1 times at half and three-quarters of total updates. τ is closely related to the trade-off between accuracy and communication costs. A small τ provides an accurate federation but requires considerable communication costs. s is related to the maximum number of classes each user can have; hence, as s decreases, the degree of data heterogeneity increases.

Evaluation   We calculate the *initial accuracy* and *personalized accuracy* of FedAvg and FedBABU following the federated personalization evaluation procedure proposed in Wang et al. (2019) to analyze the algorithms at the client level: (1) the learned global model is broadcast to all clients and is then evaluated on the test data set of each client D_i^{ts} (referred to as the *initial accuracy*), (2) the learned global model is personalized using the training data set of each client D_i^{tr} by fine-tuning with the fine-tuning epochs of τ_f; the personalized models are then evaluated on the test data set of each client D_i^{ts} (referred to as the *personalized accuracy*). In addition, we calculate the *personalized accuracy* of other personalized FL algorithms (such as FedPer, LG-FedAvg, and FedRep). Algorithm 2 in Appendix A describes the evaluation procedure. The values (X$\pm$Y) in all tables indicate the mean$\pm$standard deviation of the accuracies *across all clients*, not across multiple seeds. Here, reducing the variance over the clients could be interesting but goes beyond the scope of this study.

4 PERSONALIZATION OF A SINGLE GLOBAL MODEL

We first investigate personalization of a single global model using the FedAvg algorithm, following Wang et al. (2019) and Jiang et al. (2019), to connect a single global model to multiple personalized

---

[2]Appendix H reports the results under unbalanced and non-IID derived Dirichlet distribution.

[3]We also use 3convNet on EMNIST, 4convNet on CIFAR10, and ResNet on CIFAR100. Appendix I, F, and G report results, respectively. Appendix A presents the details of the architectures used.

Table 1: Initial and personalized accuracy of FedAvg on CIFAR100 under various FL settings with 100 clients. MobileNet is used. The initial and personalized accuracy indicate the evaluated performance without fine-tuning and after five fine-tuning epochs for each client, respectively.

FL settings		s=100 (heterogeneity ↓)		s=50		s=10 (heterogeneity ↑)	
f	τ	Initial	Personalized	Initial	Personalized	Initial	Personalized
	1	46.93±5.47	51.93±5.19	45.68±5.50	57.84±5.08	37.27±6.97	77.46±5.78
1.0	4	37.44±4.98	42.66±5.09	36.05±4.04	47.17±4.26	24.17±5.50	70.41±6.83
	10	29.58±4.87	34.62±4.97	29.57±4.29	40.59±5.23	17.85±7.38	63.51±7.38
	1	39.07±5.22	43.92±5.55	38.20±5.73	49.55±5.36	29.12±7.11	71.24±7.82
0.1	4	35.39±4.58	39.67±5.21	33.49±4.72	43.63±4.77	21.14±6.86	67.14±6.72
	10	28.18±4.83	33.13±5.22	27.34±4.96	38.09±5.17	14.40±5.64	62.67±6.52

Table 2: Initial and personalized accuracy of FedAvg on CIFAR100 under a realistic FL setting (N=100, f=0.1, τ=10) according to p, which is the percentage of all client data that the server also has. Here, the entire network (F) or body (B) is updated on the server using the available data.

	s=100 (heterogeneity ↓)		s=50		s=10 (heterogeneity ↑)	
p	Initial	Personalized	Initial	Personalized	Initial	Personalized
0.00	28.18±4.83	33.13±5.22	27.34±4.96	38.09±5.17	14.40±5.64	62.67±6.52
0.05 (F)	29.23±5.03	32.59±5.24	27.13±4.34	34.34±4.78	18.22±5.64	54.68±6.77
0.10 (F)	30.59±4.93	33.34±5.30	29.62±4.27	35.50±4.84	19.24±5.15	49.62±7.48
0.05 (B)	28.50±4.93	33.03±5.36	27.96±4.86	39.10±5.55	14.78±5.59	60.19±6.46
0.10 (B)	32.90±4.77	36.82±4.66	32.81±4.97	40.80±5.62	18.35±6.75	60.94±7.30

models. We evaluate both the initial accuracy and the personalized accuracy, assuming that the test data sets are not gathered in the server but scattered on the clients. Table 1 describes the accuracy of FedAvg on CIFAR100 according to different FL settings (f, τ, and s) with 100 clients. The initial and personalized accuracies indicate the evaluated performance without fine-tuning and with five fine-tuning epochs for each client, respectively. As previous studies have shown, the more realistic the setting (i.e., a smaller f, larger τ, and smaller s), the lower the initial accuracy. Moreover, the tendency of the personalized models to converge higher than the global model observed in Jiang et al. (2019) is the same. More interestingly, it is shown that the gap between the initial accuracy and the personalized accuracy increases significantly as the data become more heterogeneous. It is thought that a small s makes local tasks easier because the label distribution owned by each client is limited and the number of samples per class increases.

In addition, we conduct an intriguing experiment in which the initial accuracy increases but the personalized accuracy decreases, maintaining the FL training procedures. In Jiang et al. (2019), the authors showed that centralized trained models are more difficult to personalize. Similarly, we design an experiment in which the federated trained models are more difficult to personalize. We assume that the server has a small portion of p of the non-private client data of the clients[4] such that the non-private data can be used in the server to mitigate the degradation derived from data heterogeneity. We update the global model using this shared non-private data after every aggregation with only one epoch. Table 2 describes the result of this experiment. We update the entire network (F in Table 2) on the server. As p increases, the initial accuracy increases, as expected. However, the personalized accuracy decreases under significant data heterogeneity (s=10). This result implies that boosting a single global model can hurt personalization, which may be considered more important than the initial performance. Therefore, we agree that the development of an excellent global model should consider the ability to be adequately fine-tuned or personalized.

To investigate the cause of personalization performance degradation, we hypothesize that unnecessary and confusing information for personalization (i.e., the information of similar classes that a certain client does not have) is injected into a model, particularly a classifier, when a global model is trained on the server. To capture this, we only update the body (B in Table 2) on the server by zeroing the learning rate corresponding to a classifier. By narrowing the update parts, the personalization degradation problem can be remedied significantly without affecting the initial accuracy. From this observation, we argue that training the head using shared data negatively impacts the personalization.[5]

---

[4]Non-private data are sampled randomly in our experiment, which can violate the FL environments. However, this experiment is conducted simply as a motivation for our study.

[5]We also investigate personalization of centralized trained models such as (Jiang et al., 2019), and the results are reported in Appendix C. In the centralized training case, training the head also has a negative impact on personalization.

5 FEDBABU: FEDERATED AVERAGING WITH BODY AGGREGATION AND BODY UPDATE

We propose a novel algorithm that learns a better single global model to be personalized efficiently. Inspired by prior studies on long-tailed recognition (Yu et al., 2020; Kang et al., 2019), fine-tuning (Devlin et al., 2019), and self-supervised learning (He et al., 2020), as well as our data-sharing experiment, we decouple the entire network into the body and the head. Extractors (i.e., body) are trained for generalization and classifiers (i.e., head) are then trained for specialization. We apply this idea to federated learning by *never* training classifiers in the federated training phase (i.e., developing a single global model) and by fine-tuning classifiers for personalization (in the evaluation process).

5.1 FROZEN CLASSIFIER IN THE CENTRALIZED SETTING

Before proposing our algorithm, we empirically demonstrate that a model with an initialized and fixed classifier (body in Figure 2) has comparable performance to a model that jointly learns an extractor and a classifier (full in Figure 2). Figure 2 depicts the test accuracy curve of MobileNet on CIFAR100 for various training scenarios in the centralized setting, where total epochs are 160 and learning rate starts with 0.1 and is decayed 0.1 times at 80 and 120 epochs. The blue line represents the accuracy when all layers are trained, the red line represents the accuracy when only the body of the model is trained, and the green line represents the accuracy when only the head of the model is trained. The fully trained model and the fixed classifier have almost the same performance, whereas the fixed extractor performs poorly. Thus, we claim that *randomly initialized fixed classifiers are acceptable, whereas randomly initialized fixed extractors are unacceptable; initialized classifiers are thought to serve as guidelines*. This characteristic is derived from the orthogonality on the head, as is explained in Appendix B.

Figure 2: Test accuracy curves according to the update part in the centralized setting.

5.2 FEDBABU ALGORITHM

Based on the insights and results in Section 5.1, we propose a new FL algorithm called FedBABU (**Fed**erated Averaging with **B**ody **A**ggregation and **B**ody **U**pdate). Only extractors are trained, whereas classifiers are never trained during federated training; therefore, there is no need to aggregate the head. Formally, the model parameters θ are decoupled into the extractor parameters θ_{ext} and the classifier parameters θ_{cls}. Note that θ_{cls} on any client is fixed with the classifier parameters of a randomly initialized global parameters θ_G^0 until a single global model converges. This is implemented by zeroing the learning rate that corresponds to the classifier. *Intuitively, it is believed that the same fixed classifier on all clients serves as the same criteria on learning representations across all clients despite the passage of training time.*

Algorithm 1 Training procedure of FedBABU.

1: initialize $\theta_G^0 = \{\theta_{G,ext}^0, \theta_{G,cls}^0\}$
2: **for** each round $k = 1, \cdots, \text{K}$ **do**
3:     $m \leftarrow max(\lfloor Nf \rfloor, 1)$
4:     $C^k \leftarrow$ random subset of m clients
5:     **for** each client $C_i^k \in C^k$ in parallel **do**
6:         $\theta_i^k(0) \leftarrow \theta_G^{k-1} = \{\theta_{G,ext}^{k-1}, \theta_{G,cls}^0\}$
7:         $\theta_{i,ext}^k(\tau I_i^k) \leftarrow$ **ClientBodyUpdate**$(\theta_i^k(0), \tau)$
8:     **end for**
9:     $\theta_{G,ext}^k \leftarrow \sum_{i=1}^m \frac{n_{C_i^k}}{n} \theta_{i,ext}^k(\tau I_i^k), n = \sum_{i=1}^m n_{C_i^k}$
10: **end for**
11: **return** $\theta_G^{\text{K}} = \{\theta_{G,ext}^{\text{K}}, \theta_{G,cls}^0\}$
12: **function** CLIENTBODYUPDATE(θ_i^k, τ)
13:     $I_i^k \leftarrow \lceil \frac{n_{C_i^k}}{B} \rceil$
14:     **for** each local epoch $1, \cdots, \tau$ **do**
15:         **for** each iteration $1, \cdots, I_i^k$ **do**
16:             $\theta_{i,ext}^k \leftarrow SGD(\theta_{i,ext}^k, \theta_{G,cls}^0)$
17:         **end for**
18:     **end for**
19:     **return** $\theta_{i,ext}^k$
20: **end function**

Algorithm 1 describes the training procedure of FedBABU. All notations are explained in the FL training procedure paragraph in Section 3. Lines 3-4, Line 6, Line 7, and Line 9 correspond to the client sampling, broadcasting, local update, and aggregation stage, respectively. In the ClientBodyUpdate function, a local extractor parameter $\theta_{i,ext}^k$ is always updated based on the same classifier $\theta_{G,cls}^0$ (Line 16). Then, only the global extractor parameter $\theta_{G,ext}^k$ is aggregated (Line 9). Therefore, the final global parameter θ_G^{K} (Line 11) and the initialized global parameter θ_G^0 (Line 1) have the same classifier parameter $\theta_{G,cls}^0$.

In this section, we first investigate the representation power after federated training (Section 5.2.1). Next, we demonstrate the ability related to personalization (Section 5.2.2 to Section 5.2.4). We further show our algorithm's applicability (Section 5.2.5).

5.2.1 REPRESENTATION POWER OF GLOBAL MODELS TRAINED BY FEDAVG AND FEDBABU

Table 3: Initial accuracy of FedAvg and FedBABU on CIFAR100 under various settings with 100 clients. The trained classifier is replaced with the nearest template to calculate "w/o classifier" accuracy and MobileNet is used.

Hyperparameter			FedAvg		FedBABU	
s	f	τ	w/ classifier	w/o classifier	w/ classifier	w/o classifier
100	1.0	1	46.93±5.47	46.23±4.53	48.61±4.75	49.97±4.69
		4	37.44±4.98	33.48±5.09	37.32±4.39	37.20±4.35
		10	29.58±4.87	25.11±4.60	26.69±4.50	27.70±4.51
	0.1	1	39.07±5.22	36.69±5.82	41.02±4.99	41.19±4.96
		4	35.39±4.58	32.58±4.37	36.77±4.47	36.61±4.64
		10	28.18±4.83	24.34±4.58	29.38±4.74	29.36±4.46
50	1.0	1	45.68±5.50	53.87±5.39	47.19±4.77	55.70±5.48
		4	36.05±4.04	42.65±4.76	37.27±5.25	45.25±5.45
		10	29.57±4.29	34.13±4.44	28.43±4.72	36.19±4.93
	0.1	1	38.20±5.73	44.57±5.34	41.33±5.10	49.18±5.73
		4	33.49±4.72	40.01±5.49	34.68±4.58	42.43±5.11
		10	27.34±4.96	33.10±5.08	27.91±5.27	36.49±5.37
10	1.0	1	37.27±6.97	67.18±7.27	45.32±8.52	71.23±6.71
		4	24.17±5.50	58.70±6.74	32.91±7.07	64.41±7.44
		10	17.85±7.38	51.72±7.65	22.15±5.72	55.63±7.24
	0.1	1	29.12±7.11	60.42±7.89	35.05±7.63	65.98±6.43
		4	21.14±6.86	54.91±6.72	25.67±7.31	59.44±6.43
		10	14.40±5.64	50.25±6.27	18.50±7.82	54.93±7.85

Higher initial accuracy is often required because some clients may not have data for personalization in practice. In addition, the representation power of the initial models is related to the performance of downstream or personal tasks. To capture the representation power, the "without (w/o) classifier" accuracy is calculated by replacing the trained classifier with the nearest template following previous studies (Kang et al., 2019; Snell et al., 2017; Raghu et al., 2019; Oh et al., 2021): (1) Using the trained global model and training data set on each client, the representations of each class are averaged into the template of each class. Then, (2) the cosine similarity between the test samples and the templates are measured and the test samples are classified into the nearest template's class. Templates are created for each client because raw data cannot be moved.

Table 3 describes the initial accuracy of FedAvg and FedBABU according to the existence of the classifier. Because all clients share the same criteria and learn representations based on that criteria during federated training in FedBABU, improved representation power is expected.[6] When evaluated without a classifier, FedBABU has improved performance compared to FedAvg in all cases, particularly under large data heterogeneity. Specifically, when $s = 100$ (i.e., each client has most of the classes of CIFAR100), the performance gap depends on whether the classifier exists in FedAvg, but not in FedBABU. This means that the features through FedBABU are well-represented to the extent that there is nothing to be supplemented through the classifier. When s is small, the performance improves when there is no classifier. Because templates are constructed based on the training data set for each client, it is not possible to classify test samples into classes that the client does not have. In other words, restrictions on the output distribution of each client lead to tremendous performance gains, even without training the global model. Therefore, it is expected that fine-tuning the global models with a strong representation can boost personalization.

5.2.2 PERSONALIZATION OF FEDAVG AND FEDBABU

To investigate the dominant factor for personalization of FedBABU, we compare the performance according to the fine-tuned part. Table 4a describes the results of this experiment. Global models are fine-tuned with five epochs based on the training data set of each client. It is shown that fine-tuning including the head (i.e., Head or Full in Table 4a) is better for personalization than body-partially fine-tuning (i.e., Body in Table 4a). It is noted that the computational costs can be reduced by fine-tuning only the head in the case of FedBABU without performance degradation.

---

[6]Appendix O provides the results of FedAvg with different learning rates between the head and the body, which shows the freezing the head completely is critical. Appendix P further provides class-wise analysis during federated training, which shows that freezing the head makes less damage to out-of-class during local updates.

Table 4: Personalized accuracy of FedAvg and FedBABU on CIFAR100 according to the fine-tuned part. The fine-tuning epochs is 5 and f is 0.1.

(a) FedBABU.

Hyperparameter		Update part for personalization		
s	τ	Body	Head	Full
100	1	44.26±5.12	49.76±5.03	49.67±4.92
	4	39.61±4.68	44.74±5.02	44.74±5.10
	10	32.45±5.42	36.48±5.04	35.94±5.06
50	1	48.54±5.23	56.76±5.68	56.69±5.16
	4	41.27±5.04	49.45±5.41	49.55±5.58
	10	35.42±5.60	42.55±5.70	42.63±5.59
10	1	72.81±7.32	75.97±6.29	76.02±6.29
	4	69.12±6.70	70.74±6.47	71.00±6.63
	10	64.77±7.14	66.28±6.77	66.32±7.02

(b) FedAvg.

Hyperparameter		Update part for personalization		
s	τ	Body	Head	Full
100	1	41.00±5.35	43.18±5.34	43.92±5.55
	4	37.43±4.98	38.29±4.96	39.67±5.21
	10	30.62±4.95	31.92±5.04	33.13±5.22
50	1	43.61±5.54	47.51±5.61	49.55±5.36
	4	37.99±4.68	41.48±4.61	43.63±4.77
	10	32.20±4.92	36.06±5.31	38.09±5.17
10	1	56.00±8.66	69.70±7.88	71.24±7.82
	4	34.49±7.92	65.32±6.81	67.14±6.72
	10	27.94±6.96	60.24±6.16	62.67±6.52

However, in the case of FedAvg, a performance gap appears. Table 4b describes the personalized accuracy of FedAvg according to the fine-tuned parts. It is shown that fine-tuning the entire network (Full in Table 4b) is better for personalization than partial fine-tuning (Body or Head in Table 4b). Therefore, for FedAvg, it is recommended to personalize global models by fine-tuning the entire network for better performance. For consistency of the evaluation, for both FedAvg and FedBABU, we fine-tuned the entire model in this paper.

5.2.3 PERSONALIZATION PERFORMANCE COMPARISON

Table 5: Personalized accuracy comparison on CIFAR100 under various settings with 100 clients and MobileNet is used.

Hyperparameter			Personalized accuracy							
s	f	τ	FedBABU (Ours)	FedAvg (2017)	FedPer (2019)	LG-FedAvg (2020)	FedRep (2021)	Per-FedAvg (2020)	Ditto (2021)	Local-only
100	1.0	1	55.79±4.57	51.93±5.19	51.95±5.30	53.01±5.26	18.29±3.59	47.09±7.35	39.31±4.46	
		4	44.49±4.91	42.66±5.09	40.87±5.05	43.09±4.74	15.32±3.79	39.07±7.59	30.49±5.13	
		10	33.20±4.54	34.62±4.97	32.91±4.97	34.64±5.03	13.45±3.26	30.22±6.59	20.88±4.14	20.6±3.15
	0.1	1	49.67±4.92	43.92±5.55	45.17±4.70	40.91±5.50	23.84±3.92	48.10±7.42	45.39±5.33	
		4	44.74±5.10	39.67±5.21	39.30±4.92	37.87±4.99	16.01±3.48	33.70±7.04	31.80±4.62	
		10	35.94±5.06	33.13±5.22	32.08±4.97	30.08±5.34	11.11±3.13	25.82±5.83	23.75±4.41	
50	1.0	1	61.09±4.91	57.84±5.08	57.16±5.26	58.44±5.53	24.75±5.02	43.75±7.94	43.38±5.06	
		4	51.56±5.04	47.17±4.26	48.89±5.40	47.78±4.72	21.55±4.36	37.59±7.87	36.45±5.81	
		10	42.09±5.12	40.59±5.23	39.90±5.54	40.32±4.70	19.92±4.50	28.75±6.40	26.48±4.59	28.02±4.01
	0.1	1	56.69±5.16	49.55±5.36	51.63±5.27	42.64±5.55	32.88±5.09	43.96±7.40	43.59±5.92	
		4	49.55±5.58	43.63±4.77	46.31±5.63	38.54±4.71	21.13±3.96	28.67±6.98	31.98±5.23	
		10	42.63±5.59	38.09±5.17	39.81±4.88	30.79±6.12	15.15±4.01	21.64±6.16	21.93±4.75	
10	1.0	1	79.17±6.51	77.46±5.78	74.71±6.35	77.49±5.60	61.28±8.27	36.59±8.98	64.96±7.30	
		4	74.60±6.69	70.41±6.83	65.61±7.13	69.97±6.42	50.59±7.94	18.31±10.57	63.75±7.23	
		10	66.64±6.84	63.51±7.38	59.71±7.35	61.50±7.28	42.13±7.53	11.54±8.87	52.89±7.32	61.52±7.22
	0.1	1	76.02±6.29	71.24±7.82	69.36±6.77	51.75±9.32	60.13±7.72	31.21±11.66	30.76±14.80	
		4	71.00±6.63	67.14±6.72	62.62±7.63	35.80±10.55	45.91±7.68	14.34±9.51	24.19±16.15	
		10	66.32±7.02	62.67±6.52	59.50±7.33	25.04±12.02	34.30±7.84	9.17±6.95	16.05±14.44	

We compare FedBABU with existing methods from the perspective of personalization. Appendix A presents details of the evaluation procedure and implementations of each algorithm. Table 5 describes the personalized accuracy of various algorithms. Notably, FedAvg is a remarkably strong baseline, overwhelming other recent personalized FL algorithms on CIFAR100 in most cases.[7] These results are similar to recent trends in the field of meta-learning, where fine-tuning based on well-trained representations overwhelms advanced few-shot classification algorithms for heterogeneous tasks (Chen et al., 2019a; 2020a; Dhillon et al., 2019; Tian et al., 2020). FedBABU (ours) further outshines FedAvg; it is believed that enhancing representations by freezing the head improves the performance.

In detail, when $\tau=1$, the performance gap between FedBABU and FedRep demonstrates the importance of fixing the head across clients. Note that when $\tau=1$, if there is no training process on the head in FedRep, FedRep is reduced to FedBABU. Moreover, we attribute the performance degradation of FedRep to the low epochs of training on the body. In addition, the efficiency of personalized FL algorithms increases when all clients participate; therefore, FedPer (Arivazhagan et al., 2019) assumes the activation of all clients during every communication round. The Per-FedAvg algorithm might suffer from dividing the test set into a support set and query set when there are many classes and from small fine-tuning iterations. In summary, FedAvg are comparable and better than even recent personalized FL algorithms such as Per-FedAvg and Ditto, and FedBABU (ours) achieves the higher performance than FedAvg and other decoupling algorithms.

---

[7]Similar results were reported in the recent paper (Collins et al., 2021), showing that FedAvg beats recent personalized algorithms (Smith et al., 2017; Fallah et al., 2020; Liang et al., 2020; Hanzely & Richtárik, 2020; Deng et al., 2020; Li et al., 2021; Arivazhagan et al., 2019) in many cases. Appendix N further discusses the effectiveness of FedAvg.

5.2.4 PERSONALIZATION SPEED OF FEDAVG AND FEDBABU

Table 6: Performance according to the fine-tune epochs (FL setting: f=0.1, and τ=10).

s	Algorithm	Fine-tune epochs (τ_f)								
		0 (Initial)	1	2	3	4	5	10	15	20
50	FedAvg	27.34±4.96	29.17±5.01	32.39±4.77	34.97±5.13	36.78±5.13	38.09±5.17	40.56±5.43	41.20±5.51	40.86±5.13
	FedBABU	27.91±5.27	35.20±5.58	40.60±5.47	42.12±5.61	42.74±5.60	42.63±5.59	41.94±5.68	41.19±5.52	40.61±5.28
10	FedAvg	14.40±5.64	27.43±6.46	48.63±7.30	58.08±6.11	61.27±6.15	62.67±6.52	63.91±6.49	64.56±6.45	64.89±6.53
	FedBABU	18.50±7.82	63.29±7.55	66.05±6.93	66.10±6.54	66.40±7.24	66.32±7.02	66.07±7.57	66.24±7.67	66.32±7.71

We investigate the personalization speed of FedAvg and FedBABU by controlling the fine-tuning epochs τ_f in the evaluation process. Table 6 describes the initial (when τ_f is 0) and personalized (otherwise) accuracy of FedAvg and FedBABU. Here, one epoch is equal to 10 updates in our case because each client has 500 training samples and the batch size is 50. It has been shown that FedAvg requires sufficient epochs for fine-tuning, as reported in Jiang et al. (2019). Notably, FedBABU achieves better accuracy with a small number of epochs, which means that FedBABU can personalize accurately and rapidly, especially when fine-tuning is either costly or restricted. This characteristic is explained further based on cosine similarity in Appendix K.

5.2.5 BODY AGGREGATION AND BODY UPDATE ON THE FEDPROX

Table 7: Initial and personalized accuracy of FedProx and FedProx+BABU with μ=0.01 on CIFAR100 with 100 clients and f=0.1.

FL settings		s=100 (heterogeneity ↓)		s=50		s=10 (heterogeneity ↑)	
Algorithm	τ	Initial	Personalized	Initial	Personalized	Initial	Personalized
FedProx	1	46.52±4.56	50.95±4.65	42.20±4.90	51.29±5.20	28.16±9.00	66.39±7.79
	4	36.54±4.74	39.83±4.71	33.59±4.80	40.17±5.11	18.20±7.62	41.56±9.34
	10	28.63±4.40	31.90±4.16	26.88±4.59	32.92±5.00	13.62±7.73	43.48±9.32
FedProx +BABU	1	48.53±5.15	57.44±4.72	46.25±5.31	63.12±5.25	33.13±8.11	78.86±5.70
	4	37.17±4.41	45.26±4.76	33.86±5.44	50.18±5.14	22.94±9.90	75.71±5.33
	10	27.79±3.95	35.68±4.34	27.48±5.22	42.37±6.10	15.66±8.29	67.15±7.10

FedProx (Li et al., 2018) regularizes the distance between a global model and local models to prevent local models from deviating. The degree of regularization is controlled by μ. Note that when μ is 0.0, FedProx is reduced to FedAvg. Table 7 describes the initial and personalized accuracy of FedProx and FedProx+BABU with μ=0.01 when f=0.1, and Appendix M reports the results when f=1.0. The global models trained by FedProx reduce the personalization capabilities compared to FedAvg (refer to Table 1 when f=0.1), particularly under realistic FL settings. We adapt the body aggregation and body update idea to the FedProx algorithm, referred to as FedProx+BABU, which performs better than the personalization of FedAvg. Furthermore, FedProx+BABU improves personalized performance compared to FedBABU (refer to Table 5 when f=0.1). This means that the regularization of the body is still meaningful. Our algorithm and various experiments suggest future directions of federated learning: *Which parts should be federated and enhanced? Representation!*

6 CONCLUSION

In this study, we focused on how to train a good federated global model for the purpose of personalization. We showed that existing methods to improve a global model (e.g., data sharing or regularization) could reduce ability to personalize. To mitigate this personalization performance degradation problem, we decoupled the entire network into the body, related to generality, and the head, related to personalization. Then, we demonstrated that training the head creates this problem. Furthermore, we proposed the FedBABU algorithm, which learns a shared global model that can rapidly adapt to heterogeneous data on each client. FedBABU only updates the body in the local update stage and only aggregates the body in the aggregation stage, thus developing a single global model with a strong representation. This global model can be efficiently personalized by fine-tuning each client's model using its own data set. Extensive experimental results showed that FedBABU overwhelmed various personalized FL algorithms. Our improvement emphasizes the importance of federating and enhancing the representation for FL.

REPRODUCIBILITY STATEMENT

We submitted our source code as an anonymous link in the abstract and will open it through GitHub. For convenience reproducibility, shell files of each algorithm are also included.

REFERENCES

Durmus Alp Emre Acar, Yue Zhao, Ramon Matas Navarro, Matthew Mattina, Paul N Whatmough, and Venkatesh Saligrama. Federated learning based on dynamic regularization. In *International Conference on Learning Representations*, 2021.

Manoj Ghuhan Arivazhagan, Vinay Aggarwal, Aaditya Kumar Singh, and Sunav Choudhary. Federated learning with personalization layers. *arXiv preprint arXiv:1912.00818*, 2019.

Christopher Briggs, Zhong Fan, and Peter Andras. Federated learning with hierarchical clustering of local updates to improve training on non-iid data. In *2020 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–9. IEEE, 2020.

Fei Chen, Mi Luo, Zhenhua Dong, Zhenguo Li, and Xiuqiang He. Federated meta-learning with fast convergence and efficient communication. *arXiv preprint arXiv:1802.07876*, 2018.

Wei-Yu Chen, Yen-Cheng Liu, Zsolt Kira, Yu-Chiang Frank Wang, and Jia-Bin Huang. A closer look at few-shot classification. In *International Conference on Learning Representations*, 2019a.

Yinbo Chen, Xiaolong Wang, Zhuang Liu, Huijuan Xu, and Trevor Darrell. A new meta-baseline for few-shot learning. *arXiv preprint arXiv:2003.04390*, 2020a.

Yiqiang Chen, Xin Qin, Jindong Wang, Chaohui Yu, and Wen Gao. Fedhealth: A federated transfer learning framework for wearable healthcare. *IEEE Intelligent Systems*, 35(4):83–93, 2020b.

Yutian Chen, Abram L Friesen, Feryal Behbahani, Arnaud Doucet, David Budden, Matthew W Hoffman, and Nando de Freitas. Modular meta-learning with shrinkage. *arXiv preprint arXiv:1909.05557*, 2019b.

Gary Cheng, Karan Chadha, and John Duchi. Fine-tuning is fine in federated learning. *arXiv preprint arXiv:2108.07313*, 2021.

Gregory Cohen, Saeed Afshar, Jonathan Tapson, and Andre Van Schaik. Emnist: Extending mnist to handwritten letters. In *2017 International Joint Conference on Neural Networks (IJCNN)*, pp. 2921–2926. IEEE, 2017.

Liam Collins, Hamed Hassani, Aryan Mokhtari, and Sanjay Shakkottai. Exploiting shared representations for personalized federated learning. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 2089–2099. PMLR, 2021. URL http://proceedings.mlr.press/v139/collins21a.html.

Yuyang Deng, Mohammad Mahdi Kamani, and Mehrdad Mahdavi. Adaptive personalized federated learning. *arXiv preprint arXiv:2003.13461*, 2020.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, 2019.

Guneet S Dhillon, Pratik Chaudhari, Avinash Ravichandran, and Stefano Soatto. A baseline for few-shot image classification. *arXiv preprint arXiv:1909.02729*, 2019.

Canh T Dinh, Tung T Vu, Nguyen H Tran, Minh N Dao, and Hongyu Zhang. Fedu: A unified framework for federated multi-task learning with laplacian regularization. *arXiv preprint arXiv:2102.07148*, 2021.

Moming Duan, Duo Liu, Xianzhang Chen, Yujuan Tan, Jinting Ren, Lei Qiao, and Liang Liang. Astraea: Self-balancing federated learning for improving classification accuracy of mobile deep learning applications. In *2019 IEEE 37th International Conference on Computer Design (ICCD)*, pp. 246–254. IEEE, 2019.

Alireza Fallah, Aryan Mokhtari, and Asuman Ozdaglar. Personalized federated learning: A meta-learning approach. *arXiv preprint arXiv:2002.07948*, 2020.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, pp. 1126–1135. PMLR, 2017.

Sebastian Flennerhag, Andrei A Rusu, Razvan Pascanu, Francesco Visin, Hujun Yin, and Raia Hadsell. Meta-learning with warped gradient descent. *arXiv preprint arXiv:1909.00025*, 2019.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256. JMLR Workshop and Conference Proceedings, 2010.

Filip Hanzely and Peter Richtárik. Federated learning of a mixture of global and local models. *arXiv preprint arXiv:2002.05516*, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9729–9738, 2020.

Andrew G Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.

Shaoxiong Ji, Teemu Saravirta, Shirui Pan, Guodong Long, and Anwar Walid. Emerging trends in federated learning: From model fusion to federated x learning, 2021.

Yihan Jiang, Jakub Konečnỳ, Keith Rush, and Sreeram Kannan. Improving federated learning personalization via model agnostic meta learning. *arXiv preprint arXiv:1909.12488*, 2019.

Bingyi Kang, Saining Xie, Marcus Rohrbach, Zhicheng Yan, Albert Gordo, Jiashi Feng, and Yannis Kalantidis. Decoupling representation and classifier for long-tailed recognition. In *International Conference on Learning Representations*, 2019.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Viraj Kulkarni, Milind Kulkarni, and Aniruddha Pant. Survey of personalization techniques for federated learning. In *2020 Fourth World Conference on Smart Trends in Systems, Security and Sustainability (WorldS4)*, pp. 794–797. IEEE, 2020.

Yoonho Lee and Seungjin Choi. Gradient-based meta-learning with learned layerwise metric and subspace. In *International Conference on Machine Learning*, pp. 2927–2936. PMLR, 2018.

José Lezama, Qiang Qiu, Pablo Musé, and Guillermo Sapiro. Ole: Orthogonal low-rank embedding-a plug and play geometric loss for deep learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8109–8118, 2018.

Tian Li, Anit Kumar Sahu, Manzil Zaheer, Maziar Sanjabi, Ameet Talwalkar, and Virginia Smith. Federated optimization in heterogeneous networks. *arXiv preprint arXiv:1812.06127*, 2018.

Tian Li, Shengyuan Hu, Ahmad Beirami, and Virginia Smith. Ditto: Fair and robust federated learning through personalization. In *International Conference on Machine Learning*, pp. 6357–6368. PMLR, 2021.

Paul Pu Liang, Terrance Liu, Liu Ziyin, Nicholas B Allen, Randy P Auerbach, David Brent, Ruslan Salakhutdinov, and Louis-Philippe Morency. Think locally, act globally: Federated learning with local and global representations. *arXiv preprint arXiv:2001.01523*, 2020.

Yishay Mansour, Mehryar Mohri, Jae Ro, and Ananda Theertha Suresh. Three approaches for personalization with applications to federated learning. *arXiv preprint arXiv:2002.10619*, 2020.

H Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, et al. Communication-efficient learning of deep networks from decentralized data. In *Proc. 20th Int'l Conf. Artificial Intelligence and Statistics (AISTATS)*, pp. 1273–1282, 2017.

Jaehoon Oh, Hyungjun Yoo, ChangHwan Kim, and Se-Young Yun. Boil: Towards representation change for few-shot learning. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=umIdUL8rMH.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in Neural Information Processing Systems*, 32: 8026–8037, 2019.

Aniruddh Raghu, Maithra Raghu, Samy Bengio, and Oriol Vinyals. Rapid learning or feature reuse? towards understanding the effectiveness of maml. In *International Conference on Learning Representations*, 2019.

Andrei A Rusu, Dushyant Rao, Jakub Sygnowski, Oriol Vinyals, Razvan Pascanu, Simon Osindero, and Raia Hadsell. Meta-learning with latent embedding optimization. *arXiv preprint arXiv:1807.05960*, 2018.

Andrew M Saxe, James L McClelland, and Surya Ganguli. Exact solutions to the nonlinear dynamics of learning in deep linear neural networks. *arXiv preprint arXiv:1312.6120*, 2013.

Aviv Shamsian, Aviv Navon, Ethan Fetaya, and Gal Chechik. Personalized federated learning using hypernetworks. *arXiv preprint arXiv:2103.04628*, 2021.

Virginia Smith, Chao-Kai Chiang, Maziar Sanjabi, and Ameet Talwalkar. Federated multi-task learning. *arXiv preprint arXiv:1705.10467*, 2017.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pp. 4080–4090, 2017.

Canh T Dinh, Nguyen Tran, and Tuan Dung Nguyen. Personalized federated learning with moreau envelopes. *Advances in Neural Information Processing Systems*, 33, 2020.

Alysa Ziying Tan, Han Yu, Lizhen Cui, and Qiang Yang. Towards personalized federated learning. *arXiv preprint arXiv:2103.00710*, 2021.

Yonglong Tian, Yue Wang, Dilip Krishnan, Joshua B Tenenbaum, and Phillip Isola. Rethinking few-shot image classification: a good embedding is all you need? *arXiv preprint arXiv:2003.11539*, 2020.

Kangkang Wang, Rajiv Mathews, Chloé Kiddon, Hubert Eichner, Françoise Beaufays, and Daniel Ramage. Federated evaluation of on-device personalization. *arXiv preprint arXiv:1910.10252*, 2019.

Hongwei Yang, Hui He, Weizhe Zhang, and Xiaochun Cao. Fedsteg: A federated transfer learning framework for secure image steganalysis. *IEEE Transactions on Network Science and Engineering*, 2020.

Jason Yosinski, Jeff Clune, Yoshua Bengio, and Hod Lipson. How transferable are features in deep neural networks? *arXiv preprint arXiv:1411.1792*, 2014.

Haiyang Yu, Ningyu Zhang, Shumin Deng, Zonggang Yuan, Yantao Jia, and Huajun Chen. The devil is the classifier: Investigating long tail relation classification with decoupling analysis. *arXiv preprint arXiv:2009.07022*, 2020.

Hui Zhang and Quanming Yao. Decoupling representation and classifier for noisy label learning. *arXiv preprint arXiv:2011.08145*, 2020.

Michael Zhang, Karan Sapra, Sanja Fidler, Serena Yeung, and Jose M Alvarez. Personalized federated learning with first order model optimization. *arXiv preprint arXiv:2012.08565*, 2020.

Yue Zhao, Meng Li, Liangzhen Lai, Naveen Suda, Damon Civin, and Vikas Chandra. Federated learning with non-iid data. *arXiv preprint arXiv:1806.00582*, 2018.

A   IMPLEMENTATION DETAIL

Our implementations are based on the code presented by (Liang et al., 2020).[8] All the reported results are based on the last model. For computation costs, we used a single TITAN RTX and the entire training time of FedBABU on CIFAR100 using MobileNet takes $\sim$2 hours when f=1.0 and τ=1. Therefore, as f decreases and τ increases, it takes less time.

A.1   ARCHITECTURES

In our experiments, we employ the 3convNet for EMNIST, 4convNet for CIFAR10, MobileNet for CIFAR100, and ResNet for CIFAR100. 3convNet and 4convNet are described below. MobileNet (Howard et al., 2017) includes depthwise convolution and pointwise convolution, and ResNet (He et al., 2016) includes skip connection.[9] Please refer to each paper in detail.

```
3convNet(
  (features): Sequential(
    (0): Sequential(
      (0): Conv2d(1, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
      (1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=False)
      (2): ReLU()
      (3): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
    )
    (1): Sequential(
      (0): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
      (1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=False)
      (2): ReLU()
      (3): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
    )
    (2): Sequential(
      (0): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
      (1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=False)
      (2): ReLU()
      (3): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
    )
  )
  (linear): Linear(in_features=576, out_features=62, bias=True)
)

4convNet(
  (features): Sequential(
    (0): Sequential(
      (0): Conv2d(3, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
      (1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=False)
      (2): ReLU()
      (3): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
    )
    (1): Sequential(
      (0): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
      (1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=False)
      (2): ReLU()
      (3): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
    )
    (2): Sequential(
      (0): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
      (1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=False)
      (2): ReLU()
      (3): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
    )
    (3): Sequential(
      (0): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
      (1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=False)
      (2): ReLU()
      (3): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
    )
  )
  (linear): Linear(in_features=256, out_features=10, bias=True)
)
```

---

[8]https://github.com/pliang279/LG-FedAvg

[9]We use two architectures from https://github.com/kuangliu/pytorch-cifar

A.2 DATASETS

We used two public datasets, the CIFAR (Krizhevsky et al., 2009)[10] and EMNIST (Cohen et al., 2017) [11], for performance evaluation. The composition of each dataset is summarized in Table 8. We applied linear transformations such as horizontal flipping and random cropping.

Table 8: Composition of CIFAR and EMNIST.

	# of Training	# of Validation	# of Classes
CIFAR-10	50,000	10,000	10
CIFAR-100	50,000	10,000	100
EMNIST	731,668	82,587	62

A.3 HYPERPARAMETERS

For **LG-FedAvg**, FedAvg models corresponding to the FL settings in Table 3 are used as an initialization. It is then trained about a quarter of FedAvg training with a learning rate of 0.001. For **FedRep**, the number of local epochs for head and body updates were set to τ and 1, respectively. For **Per-FedAvg**, we used the first-order (FO) version, and the β value was set as the learning rate value corresponding to the communication round. For **Ditto**, the λ used to control the regularization term was set to 0.75.

A.4 EVALUATION OF FL ALGORITHMS

In FL algorithms, because the parts that need to be shared over all clients after federated training may not be shared due to client fraction, we evaluate these algorithms as follows:

Algorithm 2 Evaluation procedure of FedAvg, FedBABU, FedPer, LG-FedAvg, and FedRep.

1: initlist = [ ]   (If alg is FedAvg or FedBABU)
2: perlist = [ ]
3: **for** each client $i \in [1, N]$ in parallel **do**
4:     $\theta_{i,s}(0) \leftarrow \theta_{G,s}^K$
5:     $Acc_{init} \leftarrow$ **Eval**$(\theta_i(0); D_i^{ts})$ (If alg is FedAvg or FedBABU)
6:     initlist.append(Acc_{init})   (If alg is FedAvg or FedBABU)
7:     $\theta_i(\tau_f I_i) \leftarrow$ **Fine-tune**$(alg, \theta_i(0), \tau_f; D_i^{tr})$
8:     $Acc_{per} \leftarrow$ **Eval**$(\theta_i(\tau_f I_i); D_i^{ts})$
9:     perlist.append(Acc_{per})
10: **end for**
11: **return** initlist, perlist

12: **function** FINE-TUNE(alg, θ_i, τ_f)
13:     $I_i \leftarrow \lceil \frac{nC_i}{B} \rceil$
14:     **for** each fine-tune epoch $1, \cdots, \tau_f$ **do**
15:         **for** each iteration $1, \cdots, I_i$ **do**
16:             $\theta_i \leftarrow SGD(\theta_i)$ (If alg is FedAvg or FedBABU or FedPer or LG-FedAvg)
17:             $\theta_{i,cls} \leftarrow SGD(\theta_i)$ (If alg is FedRep)
18:         **end for**
19:     **end for**
20:     **for** each iteration $1, \cdots, I_i$ **do**   (If alg is FedRep)
21:         $\theta_{i,ext} \leftarrow SGD(\theta_i)$
22:     **end for**
23:     **return** θ_i
24: **end function**

---

where $\theta_{G,s}^K$ indicates the shared parts after federated training (i.e., full in the cases of FedAvg and FedBABU, body in the cases of FedPer and FedRep, and head in the case of LG-FedAvg). All notations are explained in the evaluation paragraph in Section 3. Because communication round k is not related to evaluation, it is emitted. For FedAvg and FedBABU, *initial accuracy* is also calculated. Although all clients have different personalized models because some parts are not shared after broadcasting except for FedAvg and FedBABU, it is not completely personalized because there is a common part $\theta_{G,s}^K$. Therefore, we fine-tune all algorithms. FedRep trains models sequentially (Line 17 and 21), while others jointly (Line 16). Finally, the mean and standard deviation of initlist and perlist are reported as *initial accuracy* and *personalized accuracy* in our paper.

---

[10]https://www.cs.toronto.edu/ kriz/cifar.html
[11]https://www.nist.gov/itl/products-and-services/emnist-dataset

B ORTHOGONALITY OF RANDOM INITIALIZATION

We hypothesize that the orthogonal initialization (Saxe et al., 2013) on the head, through which the row vectors of the classifier parameters θ_{cls} are orthogonal, is the best for the body-only update rule. At each update, the output of the extractor is pulled toward its label's row of θ_{cls} and pushed apart from the other rows of θ_{cls} through backpropagation. Therefore, orthogonal weight initialization can separate the outputs of the extractor well based on their class labels. Note that distribution-based random initializations, such as Xaiver (Glorot & Bengio, 2010) and He (He et al., 2015), have almost orthogonal rows because the orthogonality of two random vectors is observed in high dimensions with high probability (Lezama et al., 2018).

Figure 3: Test accuracy curves according to the initialization method when the body is only trained in the centralized setting. The values in parentheses indicate the average of cosine similarities between row vectors.

Figure 3 shows test accuracy curves for many different initialization methods when only the body is trained in the centralized setting.[12] When the row vectors are initialized similarly, a convergence gap appears (green and red lines in Figure 3), as expected. More experiments in the centralized setting are reported in subsection F.1 and Appendix G. Based on these empirical and theoretical results, we used He (uniform) initialization, the default setting in PyTorch (Paszke et al., 2019), in our paper.

This characteristic can be proved. Xavier (Glorot & Bengio, 2010) and He (He et al., 2015) are representative distribution-based random initialization methods, controlling the variance of parameters using network size to avoid the exploding/vanishing gradient problem. Two initialization methods use uniform and normal distribution. In detail, each element follows $\mathcal{U}(-a, a)$ or $\mathcal{N}(0, \sigma^2)$ independently, where a and σ are defined by non-linearity (such as ReLU and Tanh) and layer input-output size. Because we used the ReLU non-linear function in our implementations, we calculate a and σ by multiplying $\sqrt{2}$, for scaling of ReLU non-linearity.

Because we focus on initialization on the head, we specify $\theta_{cls} \in \mathbb{R}^{C \times d}$, where C is the number of classes (i.e., layer output size) and d is the dimension of the last representation (i.e., layer input size). Namely, each element random variable $\{w_{i,j}\}_{i \in [1,C], j \in [1,d]}$ follows $\mathcal{U}(-a, a)$ or $\mathcal{N}(0, \sigma^2)$ independently.

When $w_{i,j} \sim \mathcal{U}(-a, a)$, in Xavier initialization, a is defined as $\sqrt{2} \times \sqrt{\frac{6}{d+C}}$. Similarly, in He initialization, a is defined as $\sqrt{2} \times \sqrt{\frac{3}{d}}$ or $\sqrt{2} \times \sqrt{\frac{3}{C}}$ depending on which to be preserved, forward pass or backward pass. When $w_{i,j} \sim \mathcal{N}(0, \sigma^2)$, in Xavier initialization, σ is defined as $\sqrt{2} \times \sqrt{\frac{2}{d+C}}$. Similarly, in He initialization, σ is defined as $\sqrt{2} \times \sqrt{\frac{1}{d}}$ or $\sqrt{2} \times \sqrt{\frac{1}{C}}$ depending on which to be preserved, forward pass or backward pass. However, It is noted that a in the uniform distribution and σ in the normal distribution do not affect proof on orthogonality, therefore we keep the form of $\mathcal{U}(-a, a)$ and $\mathcal{N}(0, \sigma^2)$ for simplicity.

We first consider $2d$ independent random variables $\{w_{i,j}\}_{i \in \{p,q\}, j \in [1,d]}$ for any $p \neq q \in [1, C]$. Then, we can define d independent random variables $\{w_{p,j} w_{q,j}\}_{j \in [1,d]}$ from the above $2d$ independent random variables. Then, for all $j \in [1, d]$, $\mathbb{E}[w_{p,j} w_{q,j}] = \mathbb{E}[w_{p,j}]\mathbb{E}[w_{q,j}] = 0$ and $\mathbb{V}[w_{p,j} w_{q,j}] = \mathbb{V}[w_{p,j}]\mathbb{E}[w_{q,j}]^2 + \mathbb{V}[w_{p,j}]\mathbb{V}[w_{q,j}] + \mathbb{E}[w_{p,j}]^2\mathbb{V}[w_{q,j}] = \mathbb{V}[w_{p,j}]\mathbb{V}[w_{q,j}]$ because each element in θ_{cls} follows $\mathcal{U}(-a, a)$ or $\mathcal{N}(0, \sigma^2)$ independently. Let $S_d = \frac{1}{d} \sum_{j=1}^{d} w_{p,j} w_{q,j}$. Then, by the Weak Law of Large Numbers, $\lim_{d \to \infty} P(|S_d - \mathbb{E}[S_d]| > \epsilon) = \lim_{d \to \infty} P(|S_d| > \epsilon) = 0$ for all $\epsilon > 0$ because $\{w_{p,j} w_{q,j}\}_{j \in [1,d]}$ are independent random variables and there is V such that $\mathbb{V}[w_{p,j} w_{q,j}] < V$ for all j.

---

[12]All initialization methods except for 'similar' are provided by PyTorch (Paszke et al., 2019). Here, 'similar' initialization is implemented using a uniform distribution on [0.45, 0.55], and then each row vector is unitized by dividing the norm corresponding to the row vector.

C PERSONALIZATION OF THE CENTRALIZED MODEL

In (Jiang et al., 2019), they showed that localizing centralized initial models is harder. Similarly, we investigate the personalization of the centralized model under different heterogeneity. First, we train two models with 10 epochs, one is entirely updated (F in Table 9), and another is body-partially updated (B in Table 9) using all training data set. Then, the trained model is broadcast to each client and then evaluated. Table 9 describes the results of this experiment. It is demonstrated that if models are updated body-partially, then personalization ability does not hurt even under centralized training.

Table 9: Personalization of the centralized models. F is trained entirely, and B is trained body-partially in the centralized setting.

s	Model	Fine-tune epochs (τ_f)					
		0 (Initial)	1	2	3	4	5
100	F	40.25±4.75	40.77±4.72	41.80±4.86	42.43±4.78	43.32±4.72	44.15±4.61
	B	39.64±4.96	43.37±5.41	47.66±5.08	50.16±5.24	51.09±5.00	52.15±5.04
50	F	37.92±5.48	38.93±5.52	40.68±5.48	42.40±5.33	43.86±5.39	45.27±5.43
	B	37.18±5.21	43.66±5.34	51.14±5.49	54.67±5.06	56.34±4.82	57.36±5.21
10	F	25.46±6.23	28.04±6.88	33.43±7.32	39.56±7.66	44.74±7.43	50.32±7.05
	B	23.86±5.08	48.63±5.39	69.14±5.78	74.32±5.35	75.90±5.49	76.47±5.48

D EFFECT OF MOMENTUM DURING LOCAL UPDATES ON PERFORMANCE

We investigate the effect of momentum during local updates on the performance of FedAvg and FedBABU. Table 10 describes the initial and personalized accuracy according to the momentum during local updates. The momentum for personalization fine-tuning is the same as the momentum in federated training. In both cases of FedAvg and FedBABU, appropriate momentum improves the performance, especially personalized accuracy. However, when the extreme momentum (m=0.99) is used, FedAvg completely loses the ability to train models, while FedBABU has robust performance.

Table 10: Initial and personalized accuracy according to momentum (m) during local updates under a realistic FL setting (N=100, f=0.1, and τ=10).

	Initial accuracy					
m	$s = 100$		$s = 50$		$s = 10$	
	FedAvg	FedBABU	FedAvg	FedBABU	FedAvg	FedBABU
0.0	26.07±3.83	26.38±3.98	24.71±4.15	24.72±4.67	15.44±7.16	13.66±6.15
0.5	26.63±4.61	27.01±4.62	26.27±4.87	27.58±4.75	16.60±6.14	17.98±6.55
0.9	28.18±4.83	29.38±4.74	27.34±4.96	27.91±5.27	14.40±5.64	18.50±7.82
0.99	19.84±4.12	30.62±4.60	1.00±1.40	30.01±5.19	1.00±3.32	15.68±7.11
	Personalized accuracy					
m	$s = 100$		$s = 50$		$s = 10$	
	FedAvg	FedBABU	FedAvg	FedBABU	FedAvg	FedBABU
0.0	28.46±4.05	30.24±4.39	30.02±4.65	33.43±5.26	40.80±9.00	59.85±7.41
0.5	30.44±4.37	32.70±4.65	33.64±4.78	38.65±5.14	54.32±8.33	67.34±6.32
0.9	33.13±5.22	35.94±5.06	38.09±5.17	42.63±5.59	62.67±6.52	66.32±7.02
0.99	23.88±4.34	34.17±4.75	1.12±1.48	42.17±5.32	1.00±3.32	61.02±7.84

E EFFECT OF MASSIVENESS ON PERFORMANCE

We increase the number of clients from 100 to 500, and then each client has 100 training data and 20 test data. Table 11 describes the initial and personalized accuracy of FedAvg and FedBABU on CIFAR100 under various FL settings with 500 clients. The performance of FedAvg is slightly better than that of FedBABU in many cases; however, FedBABU overwhelms FedBABU in the case of extreme FL setting (s=10, f=0.1, and τ=10). More interestingly, if each client has a few data samples, then local epochs τ should be more than 1. It is thought that massiveness makes data size insufficient on each client (when the total number of data is fixed) and brings out other problems.

Table 11: Initial and personalized accuracy of FedAvg and FedBABU on CIFAR100 under various settings with 500 clients. The used network is MobileNet.

Hyperparameter			Initial accuracy		Personalized accuracy	
s	f	τ	FedAvg	FedBABU	FedAvg	FedBABU
100	1.0	1	13.71±7.58	11.85±7.13	16.12±7.99	15.00±7.54
		4	18.98±8.57	16.79±8.38	21.17±9.05	19.94±8.64
		10	15.70±8.18	15.66±8.23	17.54±8.91	18.47±8.61
	0.1	1	14.59±7.72	10.53±7.25	16.46±8.27	13.90±7.96
		4	18.90±8.33	17.36±8.85	20.88±8.85	20.30±9.27
		10	16.79±7.90	14.38±8.14	18.22±8.37	16.76±8.33
50	1.0	1	13.67±8.05	11.04±7.01	19.29±9.31	17.39±8.11
		4	18.36±8.60	16.60±8.43	22.76±9.05	23.15±9.51
		10	15.95±8.57	14.81±8.24	19.57±9.28	21.38±9.78
	0.1	1	14.58±8.33	10.72±6.81	19.65±9.14	16.05±8.11
		4	18.28±8.79	16.79±9.04	22.39±9.78	23.57±9.79
		10	15.79±8.21	15.07±7.97	18.52±8.69	20.83±8.90
10	1.0	1	9.91±7.14	7.41±6.55	37.62±11.76	35.02±10.71
		4	15.34±8.49	12.67±7.58	39.91±12.43	49.07±11.13
		10	12.99±7.98	12.93±8.15	35.47±11.29	48.07±12.25
	0.1	1	10.96±7.22	8.42±6.58	38.95±11.63	35.13±10.85
		4	15.03±8.27	13.99±7.82	37.92±11.64	49.96±11.94
		10	12.39±7.65	13.29±7.40	32.41±10.91	49.83±11.74

F RESULTS OF 4CONVNET ON CIFAR10

F.1 ACCURACY CURVES IN THE CENTRALIZED SETTING

When 4convNet is used on CIFAR10, a similar tendency appears. Comparing Figure 2 and Figure 4, the importance of learning representation is emphasized more when tasks are difficult. In addition, Figure 5 shows the necessity of orthogonality when the body is only trained and approximation of random initialization to the orthogonal initialization using 4convNet on CIFAR10.

Figure 4: Test accuracy curves of 4convNet on CIFAR10 according to the update part in the centralized setting.

Figure 5: Test accuracy curves of 4convNet on CIFAR10 according to the initialization method when the body is only trained.

F.2 EXPERIMENTAL RESULTS

We also evaluate algorithms on CIFAR10 using 4convNet. Table 12 and Table 13 are the experiment results corresponding to the Table 3 and Table 5 in the main paper, respectively. The tendency of performance comparison and the superiority of our algorithm appears similarly when using 4convNet on CIFAR10.

Table 12: Initial accuracy of FedAvg and FedBABU according to the existence of classifier on CIFAR10 under various settings with 100 clients. The used network is 4convNet.

Hyperparameter			FedAvg		FedBABU	
s	f	τ	w/ classifier	w/o classifier	w/ classifier	w/o classifier
10	1.0	1	68.89±6.35	74.41±6.25	71.50±7.35	75.00±7.46
		4	61.56±6.84	66.17±7.44	68.40±6.67	71.77±7.29
		10	60.06±5.68	65.21±7.94	64.66±6.00	69.04±6.68
	0.1	1	63.79±7.59	69.48±6.72	69.36±5.61	71.21±6.87
		4	59.65±8.03	66.11±7.37	66.80±7.43	69.27±8.05
		10	57.32±6.76	63.19±6.81	62.68±7.06	67.58±6.42
5	1.0	1	66.56±9.39	80.73±8.27	68.54±8.45	80.53±7.99
		4	52.60±7.79	70.53±9.15	63.79±9.12	78.34±8.30
		10	51.55±8.23	71.03±8.77	61.10±9.80	77.13±7.10
	0.1	1	55.13±8.57	71.27±10.03	63.44±9.82	77.64±8.26
		4	48.77±8.54	68.64±11.36	59.93±8.32	74.61±8.81
		10	46.32±10.52	67.07±8.77	55.55±9.90	73.29±9.25
2	1.0	1	59.47±15.16	88.60±6.96	63.51±14.63	88.34±7.05
		4	41.08±13.42	83.87±10.92	55.43±15.76	88.80±8.57
		10	39.47±13.44	82.41±10.79	48.52±13.47	86.33±8.93
	0.1	1	40.48±14.59	81.43±12.74	57.22±14.05	86.81±8.31
		4	26.72±14.54	78.56±12.58	44.39±16.49	83.12±9.68
		10	22.29±16.39	73.54±10.97	36.57±17.23	84.37±10.52

Table 13: Personalized accuracy comparison on CIFAR10 under various settings with 100 clients. The used network is 4convNet.

Hyperparameter			Personalized accuracy							
s	f	τ	FedBABU (Ours)	FedAvg	FedPer	LG-FedAvg	FedRep	Per-FedAvg	Ditto	Local-Only
10	1.0	1	80.52±5.51	79.72±5.24	78.51±5.66	80.37±5.32	71.96±6.62	79.89±5.84	79.10±6.31	
		4	79.30±5.67	73.35±6.15	71.04±7.50	74.75±5.87	63.71±7.01	72.10±6.57	79.08±5.82	
		10	76.86±5.08	71.03±5.86	69.25±7.07	71.91±5.72	60.27±7.13	66.52±7.64	74.22±7.03	
	0.1	1	78.80±5.51	73.05±5.94	77.22±5.57	67.95±7.00	78.21±5.38	77.23±5.48	75.26±7.63	55.40±11.78
		4	77.45±6.23	71.06±6.19	71.13±6.78	64.17±7.29	68.78±6.91	67.32±7.99	71.18±6.60	
		10	76.25±6.16	69.11±5.70	66.43±6.59	61.15±7.32	60.70±8.76	61.22±8.14	65.44±7.42	
5	1.0	1	85.17±6.43	83.82±6.75	84.50±5.70	85.04±6.35	78.98±8.29	74.96±7.36	83.89±7.10	
		4	83.65±5.99	77.47±8.32	76.96±8.65	77.54±8.14	73.05±9.11	65.17±10.71	84.18±6.83	
		10	83.48±6.13	77.01±7.80	76.17±8.11	77.28±7.52	70.62±7.36	53.31±12.12	79.55±7.50	68.79±13.38
	0.1	1	82.76±6.47	75.08±9.34	80.69±7.63	63.30±10.62	83.71±7.05	72.15±10.22	72.63±10.11	
		4	81.31±7.17	74.87±9.64	74.74±8.04	59.17±10.18	77.64±7.51	58.32±11.28	67.04±9.23	
		10	80.99±7.64	74.29±8.29	74.92±8.32	55.19±13.91	68.71±10.47	47.48±13.76	59.16±11.34	
2	1.0	1	91.41±6.50	91.40±6.12	91.75±6.90	92.35±5.44	91.11±8.21	72.02±14.48	91.15±7.26	
		4	91.24±7.33	88.91±9.06	89.14±8.44	88.67±9.03	87.74±8.08	43.41±23.51	91.24±7.88	
		10	90.53±7.20	88.48±8.44	88.15±9.20	87.38±8.56	86.19±9.50	36.42±18.35	89.87±7.42	90.85±9.10
	0.1	1	90.98±6.22	86.36±10.57	90.33±7.52	68.63±14.34	91.88±7.37	63.28±13.77	62.47±15.22	
		4	87.85±8.57	85.94±10.72	86.84±10.2	47.00±24.75	86.68±10.13	32.19±19.63	54.98±18.83	
		10	88.93±9.33	85.14±10.73	86.69±8.04	33.30±22.29	83.85±11.20	26.61±19.52	44.76±21.63	

F.3 ABLATION STUDY ACCORDING TO THE LOCAL UPDATE PARTS

We decouple the entire network in more detail during local updates to investigate whether the body should be totally trained. For this ablation study, we used 4convNet on CIFAR10. Table 14 and Table 15 show the initial and personalized accuracy according to the local update parts, respectively. For consistency, all cases are personalized by fine-tuning the entire network in this experiment. In all cases, FedBABU has the best performance, which implies that the body must be totally trained at least when using 4convNet. It is believed that the same (body-totally) or similar (body except for a few top layers) trends appear when large networks are used.

Table 14: Initial accuracy comparison on CIFAR10 under various settings with 100 clients. The used network is 4convNet.

Hyperparameter			Local update parts				
s	f	τ	Conv1	Conv12	Conv123	Conv1234 (FedBABU)	Conv1234+Linear (FedAvg)
10	1.0	1	25.22±8.34	47.23±6.91	68.44±6.65	71.50±7.35	68.89±6.35
		4	23.02±9.57	45.73±7.55	60.25±7.69	68.40±6.67	61.56±6.84
		10	17.80±8.15	42.51±7.03	60.48±6.96	64.66±6.00	60.06±5.68
	0.1	1	19.33±7.71	42.84±8.15	62.71±7.67	69.36±5.61	63.79±7.59
		4	19.85±8.96	41.58±8.37	55.26±6.65	66.80±7.43	59.65±8.03
		10	18.99±9.10	44.38±7.49	54.61±6.66	62.68±7.06	57.32±6.76
5	1.0	1	23.42±8.35	44.35±9.59	64.27±10.48	68.54±8.45	66.56±9.39
		4	22.34±9.48	40.07±8.83	54.50±9.21	63.79±9.12	52.60±7.79
		10	18.94±10.38	39.59±9.03	51.25±9.22	61.10±9.80	51.55±8.23
	0.1	1	20.78±7.96	38.90±10.02	52.14±8.95	63.44±9.82	55.13±8.57
		4	19.33±10.59	40.71±9.19	47.66±11.17	59.93±8.32	48.77±8.54
		10	23.71±8.86	36.74±9.72	46.97±9.81	55.55±9.90	46.32±10.52
2	1.0	1	18.72±16.35	45.01±13.57	58.86±15.93	63.51±14.63	59.47±15.16
		4	20.08±10.09	34.58±11.84	40.56±12.73	55.43±15.76	41.08±13.42
		10	18.81±14.56	29.74±10.94	37.75±12.08	48.52±13.47	39.47±13.44
	0.1	1	16.17±18.73	37.08±12.45	45.57±13.36	57.22±14.05	40.48±14.59
		4	14.09±18.82	28.75±14.13	25.12±15.63	44.39±16.49	26.72±14.54
		10	17.40±10.53	23.73±17.87	23.16±19.27	36.57±17.23	22.29±16.39

Table 15: Personalized accuracy comparison on CIFAR10 under various settings with 100 clients. The used network is 4convNet.

Hyperparameter			Local update parts				
s	f	τ	Conv1	Conv12	Conv123	Conv1234 (FedBABU)	Conv1234+Linear (FedAvg)
10	1.0	1	55.94±7.28	64.88±8.34	78.74±5.24	80.52±5.51	79.72±5.24
		4	53.06±7.17	62.84±6.57	71.85±6.11	79.30±5.67	73.35±6.15
		10	52.89±7.14	62.02±6.48	71.16±6.24	76.86±5.08	71.03±5.86
	0.1	1	53.85±8.04	64.40±6.47	72.79±6.46	78.80±5.51	73.05±5.94
		4	50.75±8.21	61.79±6.84	66.45±7.31	77.45±6.23	71.06±6.19
		10	51.95±7.45	62.72±7.64	67.41±6.31	76.25±6.16	69.11±5.70
5	1.0	1	67.49±9.74	74.39±7.74	82.55±6.50	85.17±6.43	83.82±6.75
		4	66.12±10.02	71.77±8.48	79.68±6.77	83.65±5.99	77.47±8.32
		10	64.87±8.21	69.73±9.10	76.25±8.51	83.48±6.13	77.01±7.80
	0.1	1	65.50±9.00	74.50±8.77	74.50±8.77	82.76±6.47	75.08±9.34
		4	65.05±8.56	70.80±9.29	75.44±8.06	81.31±7.17	74.87±9.64
		10	65.61±8.73	69.66±8.68	74.79±7.85	80.99±7.64	74.29±8.29
2	1.0	1	85.44±9.20	88.20±8.86	90.61±6.48	91.41±6.50	91.40±6.12
		4	84.46±9.30	83.94±10.18	88.86±8.62	91.24±7.33	88.91±9.06
		10	81.62±9.66	86.20±10.72	88.58±9.01	90.53±7.20	88.48±8.44
	0.1	1	85.46±9.68	85.78±9.73	88.18±8.41	90.98±6.22	86.36±10.57
		4	82.74±10.45	85.13±9.77	85.91±10.87	87.85±8.57	85.94±10.72
		10	82.52±10.02	84.98±9.25	85.46±9.74	88.93±9.33	85.14±10.73

G   RESULTS OF RESNET18 AND RESNET50 ON CIFAR100

G.1   ACCURACY CURVES IN THE CENTRALIZED SETTING

We experiment with ResNet18 and ResNet50. In the centralized setting, test accuracy curves according to the update part (Figure 6 and Figure 8) and according to the initialization method (Figure 7 and Figure 9) have the same trend as we have seen before.

Figure 6: Test accuracy curves of ResNet18 on CIFAR100 according to the update part in the centralized setting.

Figure 7: Test accuracy curves of ResNet18 on CIFAR100 according to the initialization method when the body is only trained.

Figure 8: Test accuracy curves of ResNet50 on CIFAR100 according to the update part in the centralized setting.

Figure 9: Test accuracy curves of ResNet50 on CIFAR100 according to the initialization method when the body is only trained.

G.2 EXPERIMENTAL RESULTS

Table 16 and Table 17 are the results of ResNet18 and ResNet50, respectively. It is shown that the performance gap between FedAvg and FedBABU increases when ResNet is used rather than when MobileNet (in the main paper) is used. Furthermore, it is observed that as the complexity of the model increases (ResNet18 $\rightarrow$ ResNet50), the performance of FedAvg decreases, while that of FedBABU does not.

Table 16: Initial and personalized accuracy of FedAvg and FedBABU on CIFAR100 under various settings with 100 clients. The used network is ResNet18. f is 0.1.

Hyperparameter		Initial accuracy		Personalized accuracy	
s	τ	FedAvg	FedBABU	FedAvg	FedBABU
100	1	57.26±4.71	59.87±4.27	60.39±5.16	66.48±4.43
	4	44.79±4.70	49.02±5.01	49.32±4.90	55.65±4.81
	10	34.52±4.73	40.60±5.62	39.04±4.77	47.42±5.66
50	1	53.73±4.97	59.23±5.10	63.21±5.33	71.16±4.75
	4	42.47±5.21	49.03±4.56	52.76±5.99	62.54±4.92
	10	37.09±4.20	40.71±4.98	47.13±4.47	54.99±5.37
10	1	42.88±8.08	53.65±7.53	76.84±7.08	83.83±5.22
	4	29.15±8.18	39.76±8.23	67.29±6.42	77.40±6.45
	10	26.54±7.66	30.96±8.09	66.18±7.29	72.49±6.19

Table 17: Initial and personalized accuracy of FedAvg and FedBABU on CIFAR100 under various settings with 100 clients. The used network is ResNet50. f is 0.1.

Hyperparameter		Initial accuracy		Personalized accuracy	
s	τ	FedAvg	FedBABU	FedAvg	FedBABU
100	1	42.89±5.34	60.78±4.74	47.59±5.16	65.74±4.72
	4	33.59±4.35	50.71±4.37	39.56±4.43	56.35±4.43
	10	32.88±4.23	40.59±4.65	37.32±4.47	45.52±5.29
50	1	42.14±5.27	59.51±4.69	53.04±5.28	70.58±5.06
	4	30.97±4.43	48.65±4.94	42.76±4.95	59.64±5.74
	10	30.90±4.76	41.14±5.47	43.28±5.49	52.13±5.14
10	1	28.18±7.99	51.17±6.97	65.50±6.92	81.43±6.20
	4	19.31±7.56	38.45±9.50	58.92±7.40	73.86±6.96
	10	18.41±7.42	30.22±8.26	59.50±7.30	68.42±8.04

H RESULTS OF RESNET10 ON DIRICHLET DISTRIBUTION-BASED CIFAR100

We evaluate ours and existing algorithms under unbalanced and non-IID settings derived from the Dirichlet distribution. Figure 10 and 11 describe the distributions of train and test data points and non-IID depending on β, which is the hyperparameter of the Dirichlet distribution. Table 18 describes the results on Dirichlet distribution-based non-IID CIFAR100 in the realistic FL setting (f=0.1 and τ=10). The lower β implies the larger heterogeneity.

Figure 10: Data distribution ($\beta = 1.0$).

Figure 11: Data distribution ($\beta = 0.5$).

Table 18: Personalized accuracy comparison on Dirichlet distribution-based non-IID CIFAR100 with 100 clients (FL setting: f=0.1, and τ=10). The used network is MobileNet.

	Personalized accuracy						
β	FedBABU (Ours)	FedAvg	FedPer	LG-FedAvg	FedRep	Per-FedAvg	Ditto	Local-only
1.0	34.92±6.22	32.10±6.15	34.21±5.68	25.00±6.12	12.68±5.27	18.85±4.97	14.77±3.92	23.73±5.71
0.5	44.67±5.80	40.21±5.68	35.62±6.17	27.24±6.73	12.52±4.32	18.36±5.01	17.18±4.31	31.24±5.49

I RESULTS OF 3CONVNET ON EMNIST

Table 19 describes the results on EMNIST using a network that consists of three convolution layers and a linear classifier. We set the number of users to 1488, and the number of data points per user was approximately 450. We fixed the fraction ratio at 0.1 and local epochs at 10 (which is the realistic setting used in our paper). The results demonstrate that FedBABU also has the best performance on EMNIST.

Table 19: Personalized accuracy comparison on EMNIST with 1488 clients (FL setting: f=0.1, and τ=10). The used network is 3convNet.

	Personalized accuracy						
s	FedBABU (Ours)	FedAvg	FedPer	LG-FedAvg	FedRep	Per-FedAvg	Ditto	Local-Only
60	85.27±5.33	84.52±4.62	54.68±6.77	82.75±4.78	75.28±5.21	78.45±5.22	83.38±5.46	72.50±5.91
30	89.30±5.03	85.46±5.16	58.72±8.04	81.64±5.80	82.03±5.34	80.61±6.02	83.23±6.06	81.63±5.73
6	95.96±5.00	89.83±7.72	64.86±15.09	73.50±13.02	94.61±5.11	62.94±14.86	76.27±12.72	96.06±3.89

J RESULTS ON IN-DISTRIBUTION (ID) AND OUT-OF-DISTRIBUTION (OOD) CLASSES

To investigate the accuracy of in-distribution (ID) and out-of-distribution (OOD) classes, we scatter IID-like test set (s=100) to all clients. Namely, some classes are in test data set (s=100), but not in training data set (s=50 or s=10). Table 20 describes the results of FedAvg and FedBABU on this experiment. Here, in-distribution accuracy is the test accuracy of the classes present in the training data set; otherwise, out-of-distribution accuracy. Before personalization (Before in tables), FedBABU beats FedAvg from both ID and OOD. After personalization (After in tables), FedBABU becomes fit only for the ID classes than OOD classes. The OOD accuracy of FedBABU decreases more than that of FedAvg, but the accuracy of FedAvg similarly drops after personalization. These results indicate that no personalization is the best strategy for both FedBABU and FedAvg. Therefore, because the OOD accuracy of FedBABU is higher than that of FedAvg before personalization, it is concluded that FedBABU has better performance than FedAvg when the optimal strategy for OOD is used.

Table 20: In-distribution (ID) and out-of-distribution (OOD) accuracy of FedAvg and FedBABU before/after personalization under various settings with 100 clients. The used network is MobileNet.

Algorithm			FedAvg				FedBABU			
Hyperparameter			ID accuracy		OOD accuracy		ID accuracy		OOD accuracy	
s	f	τ	Before	After	Before	After	Before	After	Before	After
50	1.0	1	47.30±7.05	55.14±7.57	46.46±6.74	32.85±6.67	48.30±7.75	57.92±7.98	47.81±6.56	24.06±5.27
		4	37.30±8.56	45.30±8.61	37.24±6.29	27.05±5.71	38.99±7.73	49.70±8.00	37.76±5.71	13.88±4.78
		10	30.98±7.57	38.46±9.04	30.54±5.98	20.14±5.18	27.63±7.41	37.40±8.06	29.69±6.24	5.72±3.32
	0.1	1	39.90±7.55	47.06±7.96	39.06±6.17	28.32±5.76	42.98±8.20	53.35±7.73	42.14±7.49	16.04±5.08
		4	33.23±7.88	41.25±8.19	35.70±6.15	27.38±5.63	37.07±8.02	47.04±9.18	36.34±6.10	11.67±4.32
		10	28.70±7.77	36.32±7.41	27.15±6.00	18.05±5.44	28.26±8.44	38.74±9.08	29.06±5.61	6.70±2.94
10	1.0	1	42.16±18.36	78.14±16.62	41.51±5.12	14.25±3.37	45.76±16.41	79.60±11.35	44.93±5.13	3.93±2.24
		4	30.60±15.77	68.38±16.14	31.43±5.02	7.13±3.10	38.43±17.27	71.59±15.29	37.05±5.19	0.13±0.36
		10	26.30±16.40	61.21±17.16	23.70±4.50	2.27±1.48	27.20±15.12	64.21±16.24	25.49±4.42	0.00±0.00
	0.1	1	34.47±18.00	69.23±14.87	34.10±4.87	9.74±2.95	42.57±19.11	75.18±16.46	39.64±5.04	3.32±1.89
		4	26.86±16.09	64.24±16.45	27.09±4.55	6.03±2.73	31.31±17.27	68.38±15.55	30.75±5.23	0.06±0.24
		10	18.42±12.83	56.21±17.46	19.67±3.89	2.95±1.92	22.30±14.65	64.73±17.16	22.46±4.71	0.00±0.00

K SIMILARITY BETWEEN CLIENTS DURING FINE-TUNING

We investigate the cosine similarity between different clients during 20 fine-tuning epochs, described in Figure 12. During fine-tuning for personalization evaluation, the entire network is updated in the cases of both FedAvg and FedBABU. From the results, it is found that classifier (black line in Figure 12) is closely related to personalization. In other words, all clients have similar extractors during fine-tuning (i.e., large cosine similarity), while make different classifiers based on their own data. Furthermore, it is observed that the cosine similarity on the head between different clients

Figure 12: Layer-wise cosine similarity of FedAvg and FedBABU trained under the realistic FL setting (f=0.1 and τ=10) during fine-tuning. The blue-, green-, and red-like lines represent low-, middle-, and high-level convolution layers, respectively. The black line represents the last linear layer (i.e., head).

decreases more rapidly in the case of FedBABU than FedAvg. It is believed that this is because the classifier of FedAvg starts personalization from the federated convergent classifier, while that of FedBABU starts personalization from the initialized orthogonal classifier. This characteristic explains rapid personalization, introduced in Section 5.2.4.

L FEDBABU WITH BODY UPDATE ON THE SERVER

Table 21: Initial and personalized accuracy of FedBABU on CIFAR100 under realistic FL settings (N=100, f=0.1, and τ=10) according to the p, which is the percentage of all client data that the server also has. Here, the body is updated only on the server using available data.

	s=100 (heterogeneity $\downarrow$)		s=50		s=10 (heterogeneity $\uparrow$)	
p	Initial	Personalized	Initial	Personalized	Initial	Personalized
0.00	29.38±4.74	35.94±5.06	27.91±5.27	42.63±5.59	18.50±7.82	66.32±7.02
0.05	28.68±4.65	36.25±4.77	26.94±4.98	41.01±5.34	21.32±5.85	66.56±7.24
0.10	32.49±4.52	39.93±4.76	31.39±4.84	47.02±5.54	24.34±5.32	68.95±6.92

Let us repeat the experiment in Section 4 again, where the server has a small portion p of the non-privacy data of the clients. Table 21 describes the initial and personalized accuracy of FedBABU when the global model is body-partially updated on the server using available data (such as experiments (B) in Table 2). FedBABU with body updates on the server improves personalization compared to FedAvg with body updates on the server, maintaining the initial accuracy (refer to (B) in Table 2). This result demonstrates that training the head negatively affects personalization even when trained locally. In addition, the performance of FedBABU improves as p increases. This implies that there is room for enhancing the representation beyond that of FedBABU.

M BODY AGGREGATION AND BODY UPDATE ON THE FEDPROX

Even when all clients are active every communication round (i.e., f=1.0), the personalized performance of FedProx+BABU beats not only that of FedAvg but also that of FedBABU.

Table 22: Initial and personalized accuracy of FedProx and FedProx+BABU with μ of 0.01 on CIFAR100 with 100 clients and f of 1.0.

FL settings		s=100 (heterogeneity $\downarrow$)		s=50		s=10 (heterogeneity $\uparrow$)	
Algorithm	τ	Initial	Personalized	Initial	Personalized	Initial	Personalized
	1	42.25±4.58	56.22±4.54	52.08±4.92	59.95±4.99	44.39±7.53	78.96±6.16
FedProx	4	40.32±4.70	43.17±4.62	40.11±5.80	45.99±6.05	29.73±6.74	67.66±7.67
	10	30.75±4.53	33.43±4.48	29.44±4.24	35.65±4.60	19.63±5.73	57.83±7.13
FedProx +BABU	1	55.02±4.42	61.48±4.83	54.13±4.86	66.54±4.68	50.42±9.63	83.75±5.97
	4	39.01±4.97	46.31±4.98	38.79±5.15	52.96±5.46	34.09±7.28	77.28±5.96
	10	28.69±4.64	36.29±4.45	30.39±5.39	44.46±5.49	25.16±5.84	69.77±6.26

N DISCUSSION ON THE EFFECTIVENESS OF FEDAVG

MOCHA (Smith et al., 2017) is a representative personalized FL paper using regularization based on relationships between tasks. pFedMe (T Dinh et al., 2020) and Ditto (Li et al., 2021) train local models with a regularization based on the divergence between a global model and local models. If the weight on regularization is set to zero, these regularized personalized FL algorithms reduce to the local-only algorithm; on the other extreme, these reduce to the FedAvg algorithm (i.e., $\theta_1 = \cdots = \theta_N$). The personalized FL algorithms such as FedPer (Collins et al., 2021), in which each client has parts that are not aggregated (i.e., personalized parts), can be explained similarly. If there is no personalized part, these personalized FL algorithms reduce to the FedAvg; on the other extreme, i.e., if the entire network is not aggregated, these personalized FL algorithms reduce to the local-only algorithm. In summary, personalized FL algorithms are in-between local-only and FedAvg algorithms and have better personalized performance than both local-only and FedAvg in general.

In the same vein, FedAvg+Fine-tuning is also in-between local-only and FedAvg because this algorithm uses two extreme algorithms sequentially (i.e., FedAvg followed by local-only). However, intuitively, FedAvg+Fine-tuning is a bit more FedAvg-based, whereas personalized FL algorithms are a bit more local-only-based. This is because FedAvg+Fine-tuning is the same as FedAvg before personalization, whereas personalized FL algorithms develop different clients' models from scratch

like local-only. Therefore, we believe that *FedAvg+Fine-tuning earns more benefits (particularly for representation) from federation* than personalized FL algorithms from this difference (FedAvg-based v.s. local-only-based). An additional difference between FedAvg+Fine-tuning and regularized personalized FL algorithms is that FedAvg+Fine-tuning optimizes clients *separately* using their own data set based on the well-federated extractor, whereas regularized personalized FL algorithms optimize clients *jointly* from scratch. In other words, FedAvg+Fine-tuning can easily optimize all clients' models based on their own data sets. However, it is too difficult to optimize all clients' models simultaneously. Therefore, FedAvg+Fine-tuning can achieve better personalized performance than regularized personalized FL algorithms.

Furthermore, very recent work (Cheng et al., 2021) has addressed the effectiveness of FedAvg+Fine-tuning theoretically. In Cheng et al. (2021), they compared local-only (zero collaboration), FedAvg (zero personalization) (McMahan et al., 2017), FedAvg+Fine-tuning, Per-FedAvg (Fallah et al., 2020), and pFedMe (T Dinh et al., 2020) in the high-dimensional asymptotic limit by analyzing bias-variance. They demonstrated that the asymptotic test loss of FedAvg+Fine-tuning (FTFA in Cheng et al. (2021)) matches that of Per-FedAvg and that the asymptotic test loss of FedAvg+Fine-tuning with a ridge regularizer (RTFA in Cheng et al. (2021)) matches that of pFedMe on their stylized linear regression model.

Although Cheng et al. (2021) thoroughly addressed this problem on their stylized linear regression model, there are few results on real data sets except for test accuracies. It is believed that "why FedAvg+Fine-tuning is effective" itself needs to be studied more using real data sets, as "why MAML (Finn et al., 2017) is effective" has been addressed in (Raghu et al., 2019).

O   FEDAVG WITH DIFFERENT LEARNING RATES

Table 23: FedAvg with different learning rates under realistic FL setting (f=0.1 and τ=10). We set the body's initial learning rate (α_b) as 0.1.

s	FedAvg ($\alpha_h=\alpha_b$)	FedAvg ($\alpha_h=0.1 \times \alpha_b$)	FedAvg ($\alpha_h=0.01 \times \alpha_b$)	FedBABU ($\alpha_h=0$)
100	24.34±4.58	27.10±4.43	28.37±4.60	29.36±4.46
50	33.10±5.08	35.97±5.17	36.21±5.08	36.49±5.37
10	50.25±6.27	52.96±7.52	54.04±7.60	54.93±7.85

What we want to emphasize is the importance of making all clients have the same class boundary by freezing the head. We argue that this shared classifier enhances the representation power of the federated model, which is an important factor for personalization. From this perspective, if the head moves even a little bit client by client, the different class boundaries to train feature extractor are used during local updates. Therefore, the federated model's feature extractor might hurt.

To verify this hypothesis, we experiment using different learning rates depending on the parts. The above table describes the federated model's accuracy without a classifier (i.e., w/o classifier accuracy in Table 3) to investigate representation power of models. We set the body's initial learning rate as 0.1, the fraction ratio as 0.1, and local epochs as 10. α_h and α_b are the head's learning rate and the body's learning rate, respectively.

From this result, we believe that the federated model's representation power increases as the head's learning rate decreases, i.e., as a learning signal for the body is larger. In this trend, we highlight that the best performance is due to the same classifier on all clients.

P   CLASS-WISE ANALYSIS DURING FEDERATED TRAINING

To explain why FedBABU has better performance than FedAvg after federated training (i.e., before fine-tuning), we analyze the federated training procedure of FedAvg and FedBABU class-wisely under the realistic federated settings (f=0.1 and τ=10). For this analysis, we assume that each client has 500 training data and 10,000 test data (i.e., the whole test data) of CIFAR-100. Test data set is divided into two groups for each client; in-class test data and out-of-class test data. In-class test data indicates test data whose class is in the classes in training data, whereas out-of-class test data indicates test data whose class is not in the classes in training data. For instance, if client A has

Figure 13: In-class and out-of-class test accuracy curves according to the heterogeneity. The models are trained under the realistic federated settings (f=0.1 and τ=10).

classes 0-9 as training data, then in-class test data indicates test data whose class is one of 0-9 and out-of-class test data indicates test data whose class is one of 10-99.

Figure 13 describes the in-class ((a)-(c)) and out-of-class ((d)-(f)) test accuracy curves according to the heterogeneity. Client sampling, broadcasting, local updates, and aggregation stages are repeated during federated training. The accuracies per epoch are averaged right after broadcasting the aggregated model to the selected clients and during local updates on them. It is observed that in-class accuracy of the aggregated model is significantly low and increases dramatically during local updates, whereas out-of-class accuracy of the aggregated model is significantly high and decreases dramatically during local updates, as heterogeneity is larger. In all cases, FedBABU has higher out-of-class accuracy than FedAvg after local updates. It implies that *freezing the head makes less damage to out-of-class during local updates and can lead to better aggregation*. Furthermore, when heterogeneity is large (s=10), FedBABU has higher in-class accuracy than FedAvg after local updates.