CONTRASTIVE HIERARCHICAL CLUSTERING

ABSTRACT

Deep clustering has been dominated by flat clustering models, which split a dataset into a predefined number of groups. Although recent methods achieve extremely high similarity with the ground truth on popular benchmarks, the information contained in the flat partition is limited. In this paper, we introduce CoHiClust, a Contrastive Hierarchical Clustering model based on deep neural networks, which can be applied to large-scale image data. By employing a self-supervised learning approach, CoHiClust distills the base network into a binary tree without access to any labeled data. The hierarchical clustering structure can be used to analyze the relationship between clusters as well as to measure the similarity between data points. Experiments performed on typical image benchmarks demonstrate that CoHiClust generates a reasonable structure of clusters, which is consistent with our intuition and image semantics. Moreover, by applying the proposed pruning strategy, we can restrict the hierarchy to the requested number of clusters (leaf nodes) and obtain the clustering accuracy comparable to the state-of-the-art flat clustering baselines.

1 INTRODUCTION

Clustering, a fundamental branch of unsupervised learning, is often one of the first steps in data analysis, which finds applications in anomaly detection Barai & Dey (2017), personalized recommendations Zhang et al. (2014) or bioinformatics Lakhani et al. (2015). Since it does not use any information about class labels, representation learning becomes an integral part of deep clustering methods. Initial approaches use representations taken from pre-trained models Guérin et al. (2017); Naumov et al. (2021) or employ auto-encoders in joint training of the representation and the clustering model Guo et al. (2017a); Mautz et al. (2019). More recent works designed to image data frequently follow the self-supervised learning principle, where representation is trained on pairs of similar images automatically generated by data augmentations Li et al. (2021b); Dang et al. (2021). Since augmentations used for image data are class invariant, the latter techniques often obtain very high similarity with the ground truth classes. However, we should be careful when comparing clustering techniques only by inspecting their accuracy with ground truth classes because the primary goal of clustering is to deliver information about data and not to perform classification.

Most works in the area of deep clustering focus on producing flat partitions with a predefined number of groups. Although hierarchical clustering gains notable attention in classical machine learning and has been frequently applied in real-life problems Zou et al. (2020); Śmieja et al. (2014), its role has been drastically marginalized in the era of deep learning. In the case of hierarchical clustering, the exact number of clusters does not have to be specified because we can inspect the partition at various tree levels. Moreover, we can analyze the clusters' relationships, e.g. by finding super-clusters or measuring the distance between groups in the hierarchy. The above advantages make hierarchical clustering an excellent tool for analyzing complex data. To the best of our knowledge, DeepECT Mautz et al. (2019; 2020) is the only hierarchical clustering model trained jointly with the neural network, which however has not been examined to large-scale image datasets.

To fill this gap, we introduce CoHiClust (**Co**ntrastive **Hi**erarchical **Clust**ering), which creates a hierarchy of clusters and can be applied to large-scale data. CoHiClust uses a neural network to generate a high-level representation of data, which is next distilled into the tree hierarchy by applying the projection head, see Figure 2. The whole framework is trained jointly in an end-to-end manner without labels using our novel contrastive loss and automatically generated data augmentations following the self-supervised learning principle.

Figure 1: **A tree hierarchy generated by CoHiClust for F-MNIST** (images in the nodes denote mean images in each sub-tree). The right sub-tree contains clothes while the other items (shoes and bags) are placed in the left branch. Looking at the lowest hierarchy level, we have clothes with long sleeves grouped in the neighboring leaves. The same holds for clothes with designs. Observe that CoHiClust assigned white-colored t-shirts and dresses to the same cluster, while trousers are in the separate one. Small shoes such as sneakers or sandals are considered similar (neighboring leaves) and distinct from ankle shoes. Concluding, CoHiClust is able to retrieve meaningful information about image semantics, which is complementary to the ground truth classification.

The constructed hierarchy uses the structure of a binary tree, where the sequence of decisions made by internal nodes determines the final assignment to clusters (leaf nodes). In consequence, similar examples are processed longer by the same path than dissimilar ones. By inspecting the number of edges needed to connect two clusters (leaves), we obtain a natural similarity measure between data points. Although CoHiClust assumes a pre-defined tree structure with a fixed height, we introduce a pruning mechanism, which removes the least informative leaf nodes until the requested number of leaves is obtained. In contrast to typical pruning strategies or tree cuts, where neighboring leaves are only merged to ancestor node, we allow for reassigning data points between clusters by finetuning the whole model, which further improves topology of the tree.

The proposed model has been examined on various image datasets and compared with both hierarchical and flat clustering baselines. By analyzing the constructed hierarchies, we show that CoHiClust generates a structure of clusters that is consistent with our intuition and image semantics, see Figures 1. Our analysis is supported by a quantitative study, which shows that CoHiClust gives higher similarity with ground truth partition than available hierarchical baselines, see Tables 1 and 2. Moreover, it is among the three best-performing methods when compared to the flat clustering models, see Table 3.

Our main contributions are summarized as follows:

- We introduce a hierarchical clustering model CoHiClust, which converts the base neural network into a binary tree. The model is trained effectively with no supervision using our novel hierarchical contrastive loss applied to self-generated data augmentations.
- We implement a pruning strategy, which not only leads to creating a fixed number of leaves but also improves the constructed hierarchy.

- Our experimental analysis shows that CoHiClust builds hierarchies based on the well-defined and intuitive patterns retrieved from data.
- Since CoHiClust is the first deep hierarchical clustering model applied to large-scale image datasets, we also deliver a new benchmark, which can be used to compare hierarchical clustering methods.

2 RELATED WORK

In this section, we briefly introduce some recent developments in three related topics, i.e., contrastive learning, deep clustering, and hierarchical methods.

Contrastive Learning The basic idea of contrastive learning is to learn such a feature space, in which similar pairs stay close to each other while dissimilar ones are far apart Chopra et al. (2005). In early works, training was performed in a supervised way on pairs or triplets labeled manually Hadsell et al. (2006); Schroff et al. (2015). It was later observed that in selected domains, such as computer vision, positive pairs can be generated automatically using adversarial perturbations Miyato et al. (2018) or data augmentation He et al. (2020), giving the rise of a new field called self-supervised learning Chen et al. (2020). Fine-tuning a simple classifier using a small amount of labeled data on the representation created in a self-supervised way allows for obtaining the accuracy comparable to a fully supervised setting with a large labeled dataset. SimCLR He et al. (2020) applies NT-Xent loss to maximize the agreement between differently augmented views of the same sample. Barlow Twins Zbontar et al. (2021) learns to make the cross-correlation matrix between two distorted versions of the same samples close to the identity. BYOL Grill et al. (2020) claims to achieve new state-of-the-art results without using negative samples. Other works use memory banks to reduce the cost of computing the embeddings of negative samples in every batch Wu et al. (2018); He et al. (2020).

Deep clustering A primary focus in deep embedded clustering has merely been on flat clustering objectives with the actual number of clusters known a priori. DEC Xie et al. (2016) is one of the first works, which combines the auto-encoder loss with a clustering objective to jointly learn the representation and perform clustering. This idea was further explored with some improvements in IDEC Guo et al. (2017a), JULE Yang et al. (2016) and DCEC Guo et al. (2017b). IMSAT Hu et al. (2017) and IIC Ji et al. (2019) use perturbations to generate pairs of similar examples and apply information-theoretic objectives for training. PICA Huang et al. (2020) maximizes the global partition confidence of the clustering solution to find the most semantically plausible data separation. Following the progress in self-supervised learning, CC Li et al. (2021b) and DCSC Zhang et al. (2022) perform contrastive learning by generating pairs of positive and negative instances through data augmentations.

Hierarchical methods Hierarchical clustering algorithms are a well-established area within classical data mining Murtagh & Contreras (2012), but they were rarely studied in deep learning. Deep-ECT Mautz et al. (2019; 2020) is the only method, which jointly learns the deep representation using auto-encoder architecture and performs hierarchical clustering in a top-down manner. Unfortunately, there is not comparative study conducted on large image data. The experimental study of objective-based hierarchical clustering methods performed on the embedding vectors from pre-trained deep learning models is presented in Naumov et al. (2021).

In the case of classification, there is a growing interest in deep hierarchical methods, which in our opinion should also be reflected in the area of unsupervised learning. SDT Frosst & Hinton (2017) is one of the first models that distills the base neural networks into a soft decision tree. More advanced methods automatically generate deep networks with a tree structure in a multi-step or an end-to-end manner Tanno et al. (2019); Alaniz et al. (2021); Wan et al. (2020).

3 COHICLUST MODEL

The proposed CoHiClust builds a hierarchy of clusters based on the output of the base neural network. There are four key components of CoHiClust:

Figure 2: **Illustration of CoHiClust.** The output neurons of the projection head π (appended to the base network g) model decisions made by the internal tree nodes. The final assignment of the input example to the cluster (leaf node) is performed by aggregating edge probabilities located on the path from the root to this leaf.

- The base neural network, which generates representation used by the tree.
- The tree model, which assigns data points to clusters by a sequence of decisions.
- The regularized contrastive loss, which allows for training the whole framework.
- The pruning strategy, which restricts the tree to the requested number of leaves.

We discuss the above components in detail in the following parts.

Tree hierarchy   We use a soft binary decision tree to create a hierarchical structure, where leaves play the role of clusters (similar to Frosst & Hinton (2017)). In contrast to hard decision trees, every internal node defines the probability of taking a left/right branch. The final assignment of the input examples to clusters involves partial decisions made by the internal nodes. Aggregating these decisions induces the posterior probability over leaves.

Let us consider a complete binary tree with T levels, where the root is located at the level 0 and the leaves are represented at the level T. This gives us 2^t nodes at the level t denoted by tuples (t, i), for $i = 0, 1, \ldots, 2^t - 1$, see Figure 2. The path going from the root to the node (t, i) is given by the sequence of binary decisions $y = (y_1, \ldots, y_t) \in \{0, 1\}^t$ made by the internal nodes, where $y_s = 0$ ($y_s = 1$) means that we take the left (right) branch being in the node at the level s. Observe that we can retrieve the index j of the node at the level s from y by taking $j = b_s(y) = \sum_{m=1}^{s} y_m 2^{s-m}$. In other words, the first s bits of y are a binary representation of the number j.

We consider the path induced by the sequence of decisions $y = (y_1, \ldots, y_t) \in \{0, 1\}^t$, which goes from the root to the node (t, i), where $i = b_t(y)$. We want to calculate the probability $P_t^i(x)$ that the input example $x \in \mathbb{R}^D$ reaches node (t, i). If $p_s^{b_s(y)}(x)$ is the probability of going from the parent node $(s - 1, b_{s-1}(y))$ to its descendant $(s, b_s(y))$, then

$$P_t^i(x) = p_1^{b_1(y)}(x) \cdot p_2^{b_2(y)}(x) \cdot \ldots p_t^{b_t(y)}(x).$$

Observe that $P_t(x) = [P_t^0(x), P_t^1(x), \ldots, P_t^{2^t-1}(x)]$ defines a proper probability distribution, i.e. $\sum_{j=0}^{2^t-1} P_t^j(x) = 1$. In consequence, the probability distribution over clusters (leaves) equals $P_T(x)$, see Figure 2.

Tree generation   To generate our tree model, we need to parameterize the probabilities $p_t^i(x)$ of taking the left/right branch in every internal node. To this end, we employ a neural network $g : \mathbb{R}^D \to \mathbb{R}^N$ with an additional projection head $\pi : \mathbb{R}^N \to \mathbb{R}^K$, where $K = 2^T - 1$ and T is the height of the tree. The number K of the output neurons equals the number of internal tree nodes.

The neural network g is responsible for extracting high-level information from data. It can be instantiated by a typical architecture, such as ResNet, and is used to generate embeddings $z = g(x)$ of the input data. We do not use pre-trained networks but train the whole model end-to-end using the proposed hierarchical contrastive loss. This allows for generating the representation, which is suited to the underlying clustering task.

The projection head π operates on the embeddings z and parameterizes decisions made by the internal tree nodes. In our case, π is a single-layer network with the output dimension equal to the number of internal nodes. To model binary decisions of the internal nodes, we apply the sigmoid function σ. In consequence, the projection head is given by

$$\pi(z) = [\sigma(w_1^T z + b_1), \ldots, \sigma(w_K^T z + b_K)],$$

where $w_n \in \mathbb{R}^N$ and $b_n \in \mathbb{R}$ are trainable parameters of π. By interpreting the output neurons of π as the internal nodes of the decision tree, we get the probabilities of left edges in the nodes:

$$p_{t+1}^{2i}(x) = \sigma(w_n^T z + b_n) \text{, for } n = 2^t + i.$$

Note that $p_{t+1}^{2i-1}(x) = 1 - p_{t+1}^{2i}(x)$ always corresponds to the probability of right edge.

Contrastive hierarchical loss To train CoHiClust, we introduce the hierarchical contrastive loss function designed for trees. Our idea relies on maximizing the likelihood that similar data points will follow the same path. The more similar data points, the longer they should be routed through the same nodes. Since we work in the unsupervised setting, we use a self-supervised approach and generate similar images by data augmentations.

Let us consider two data points x_1, x_2 and their posterior probabilities $P_t(x_1), P_t(x_2)$ at the level t. The probability that x_1 and x_2 reach the same node at this level is given by the scalar product $P_t(x_1) \cdot P_t(x_2) = \sum_{i=0}^{2^t-1} P_t^i(x_1) P_t^i(x_2)$. This term is maximal if both probabilities are identical one-hot vectors. In a training phase, we do not want to force hard splits in the nodes (binary probabilities) because in this way the model quickly finds a local minimum by assigning data points to fixed leaves with high confidence. Instead of sticking to hard assignments in a few training epochs, we want to let the model explore possible solutions. To this end, we take the square root before applying the scalar product, which corresponds to the Bhattacharyya coefficient Bhattacharyya (1946):

$$s_t(x_1, x_2) = \sqrt{P_t(x_1) \cdot P_t(x_2)} = \sum_{i=0}^{2^t-1} \sqrt{P_t^i(x_1) P_t^i(x_2)}.$$

Observe that $s_t(x_1, x_2) = 1$, if only $P_t(x_1) = P_t(x_2)$ (probabilities do not have to binarize), which leads to the exploration of possible paths. By aggregating the similarity scores over all tree levels, we arrive at our final similarity function $s(x_1, x_2) = \sum_{t=0}^{T-1} s_t(x_1, x_2)$.

In a training phase, we take a minibatch $\{x_j\}_{j=1}^N$ of N examples and generate its augmented view $\{\tilde{x}_j\}_{j=1}^N$. Every pair $(x_j, \tilde{x}_j)$ is considered positive, which means that we will maximize their similarity score. In consequence, we encourage the model to assign them to the same leaf node. To avoid degenerate solutions, where all points end up in the same leaf, we treat all other pairs negative and minimize the similarity scores for them. Finally, the proposed hierarchical contrastive loss is given by:

$$\text{CoHiLoss} = \frac{1}{N(N-1)} \sum_{j=1}^N \sum_{i \neq j} s(x_j, \tilde{x}_i) - \frac{1}{N} \sum_{j=1}^N s(x_j, \tilde{x}_j).$$

By minimizing the above loss, we maximize the likelihood that similar data points follow the same path (second term) and minimize the likelihood that dissimilar ones are grouped together.

Regularization Final cluster assignments are induced by aggregating several binary decisions made by the internal tree nodes. In practice, the base neural network may not train all nodes and, in consequence, use only a few leaves for clustering. While selecting the number of clusters in flat clustering is desirable, here we would like to create a hierarchy, which is not restricted to a given number of leaves. To enable end-to-end training of the base neural network with the arbitrary number of leaves, we consider two regularization strategies.

The first regularization explicitly encourages the model to use both left and right sub-trees equally Frosst & Hinton (2017). We realize this postulate by minimizing the cross-entropy between the desired distribution $[0.5, 0.5]$ and the actual distribution for choosing the left or right path in a given node.

Table 1: Dendrogram purity (DP) of clustering hierarchies (higher is better).

Method	MNIST	F-MNIST
DeepECT	0.82	0.47
DeepECT + Aug	0.94	0.44
IDEC + Single	0.39	0.34
IDEC + Complete	0.40	0.35
AE + Bisecting	0.53	0.38
AE + Single	0.11	0.10
AE + Complete	0.25	0.26
CoHiClust	0.97	0.52

Table 2: Clustering metrics of partitions generated from the tree hierarchies on MNIST and F-MNIST (higher is better).

Method	MNIST		F-MNIST	
	NMI	ACC	NMI	ACC
DeepECT	0.83	0.85	0.60	0.52
DeepECT + Aug	0.93	0.95	0.59	0.50
IDEC	0.86	0.85	0.58	0.53
AE + k-means	0.70	0.77	0.52	0.48
CoHiClust	0.97	0.99	0.62	0.65

The second regularization does not directly influence the routing in the tree but focuses on improving the output representation of the base network g. For this purpose, we use NT-Xent loss Chen et al. (2020) on the embedding space $z = g(x)$. With the NT-Xent loss, we maximize the cosine similarity on the embedding space for all positive pairs and minimize the cosine similarity on the embedding space for all negative pairs.

Taking together the contrastive loss CoHiLoss with two regularization functions R_1 (for entropy) and R_2 (for NT-Xent), we arrive at our final loss:

$$\text{Loss} = \text{CoHiLoss} + \beta_1 R_1 + \beta_2 R_2, \tag{1}$$

where β_1, β_2 are the user-defined hyperparameters. Instead of selecting their values in the validation procedure (which can be problematic in unsupervised learning), we set β_1 proportional to the depth of the tree $\beta_1 = 2^{-T}$ and $\beta_2 = 1$.

Pruning The proposed model builds a complete tree with 2^T leaves. Although such a structure is useful for analyzing the hierarchy of clusters, in some cases we are interested in creating a tree with the requested number of groups, which is not equal to the power of 2. For this purpose, we introduce a pruning strategy that reduces the least significant leaf nodes. In contrast to typical pruning approaches, which focus solely on deleting nodes, we further improve the hierarchy by training CoHiClust in the pruning phase.

We start with calculating the probability of leaves $P_T^i = \frac{1}{|X|} \sum_{x \in X} P_T^i(x)$, which describes the expected fraction of data points assigned to a given leaf. Assuming that the importance of the cluster is related to the average number of assigned examples, we reduce a leaf with the lowest probability. After removing the leaf, we finetune the whole model using CoHiClust loss (1). If we want to reduce more leaves, we perform leaf pruning and model retraining iteratively until the requested number of leaves is obtained. The resulting tree is binary, but can have an arbitrary structure and does not have to be complete. Consequently, pruning is also a way of improving the topology of the tree model.

4 EXPERIMENTS

We evaluate our method with several datasets of increasing difficulty. We show that CoHiClust outperforms hierarchical clustering models and is among the three best-performing flat clustering methods in terms of similarity with the ground truth classes.In addition, we analyze the constructed hierarchies, which in our opinion are equally important in practical use-cases. Our experiments demonstrate that CoHiClust reveals novel patterns and relations between data points beyond those contained in ground truth classes.

Comparison with hierarchical clustering methods First, we compare CoHiClust with hierarchical baselines. To the best of our knowledge, DeepECT Mautz et al. (2019) is the only hierarchical clustering method based on deep neural networks. Following their experimental setup, we also consider classical hierarchical algorithms evaluated on the latent representation created by the autoencoder and IDEC Guo et al. (2017a). We report the results on two popular image datasets[1]: MNIST and F-MNIST.

---

[1]We intentionally do not use two remaining datasets: USPS which is analogous to MNIST and Reuters which is not an image database.

(a) F-MNIST   (b) ImageNet-10

Figure 3: Distance matrices retrieved from the constructed hierarchies for ground truth classes, see text in the paper for the interpretation.

We run CoHiClust with 16 leaves (4 tree levels) using ResNet18 as a base neural network. The initial model is trained for 50 epochs on MNIST and 100 epochs on F-MNIST using a minibatch size of 256. Next, we perform pruning with an additional 50 and 100 epochs of fine-tuning on MNIST and F-MNIST, respectively, to end up with 10 clusters, which equals the true number of classes for considered datasets. To evaluate the cluster hierarchies against ground truth flat partition, we use dendrogram purity (DP) Kobren et al. (2017); Yang et al. (2019),which attains its maximum value of 1 if and only if all data points from the same class are assigned to some pure sub-tree.

The results summarized in Table 1 demonstrate that CoHiClust outperforms all baselines on both MNIST and F-MNIST datasets. Interestingly, DeepECT benefits from data augmentation in the case of MNIST, while on F-MNIST it deteriorates its performance. All methods except CoHiClust and DeepECT failed completely to create a hierarchy recovering true classes, which confirms that there is a lack of powerful hierarchical clustering methods based on neural networks.

To further evaluate the performance on MNIST and F-MNIST, we measure the normalized mutual information (NMI) and the clustering accuracy (ACC) between the ground truth partition and the flat clustering generated from the tree hierarchy. We exclude the combinations of hierarchical and embedding methods from the comparison due to their poor performance. Instead, we consider two flat clustering methods: IDEC and k-means evaluated on the latent representation generated by the autoencoder. It can be seen from Table 2 that CoHiClust outperforms baseline methods across all datasets and metrics. The disproportion between the results obtained on MNIST and F-MNIST demonstrates that recovering true classes of clothes is a significantly more challenging task than recognizing the hand-written digits.

Analyzing the clustering hierarchies Although comparing constructed clustering with the ground truth partition is a widely-used evaluation measure in the literature, it is even more important from a practical point of view to visualize the results and perform their qualitative assessment. Figure 1 presents the clustering tree constructed for F-MNIST (see appendix for the hierarchy of MNIST). Images in nodes show the means calculated over data points assigned to the respective nodes. For every leaf, we also present sample images classified to this cluster and the percentage of images from dominant classes in the group (with a fraction higher than 15%). Visual inspection shows that neighboring leaves contain images with similar patterns, see description in Figure 1 for detailed findings.

The hierarchy also allows us to define the distance $d(a, b)$ between two examples a, b using the number of edges that connect them. We use the average of this score to calculate the similarity

Figure 4: **A tree hierarchy generated by CoHiClust for ImageNet-10.** The left sub-tree contains examples related to the means of transport with neighboring leaves occupied by visually similar classes such as sports cars and trailer trucks (first two leaves from the left) as well as airliners, airships, and container ships (next three leaves). Interestingly, airliners and airships photographed in the sky are assigned to a different cluster than analogical objects located on the ground. In the right sub-tree, CoHiClust almost perfectly clustered examples of two classes: Maltese dog and snow leopard. Surprisingly, images with a ball in the foreground (without people) are grouped together with oranges because of their circular shape. Soccer balls accompanied by the player are considered more similar to the images with penguins (their shapes are also similar). Nevertheless, all images of penguins are assigned to the neighboring leaves.

between ground truth classes A and B:

$$d(A, B) = \frac{1}{Z} \sum_{a \in A} \sum_{b \in B} d(a, b),$$

where Z is the number of all pairs. The above distance is small if examples from classes A and B are located in the nearby leaf nodes (on average).

The obtained distance matrix presented in Figure 3 (left) confirms that clusters discovered by Co-HiClust reveal many different patterns than the information encoded in the ground truth classes. While clothes are well separated from other items (number of edges greater than 6), we cannot distinguish particular clothes items from each other (distance between 3 and 4). As can be seen in Figure 1, CoHiClust generated the hierarchy based on the sleeve length or the presence of designs. From this point of view, we can say that the results obtained by CoHiClust are complementary to the ground truth classification. However, we can also observe some similarities with ground truth classification: it is evident that the elements of the following 5 classes have not been spread between clusters: "trousers", "sandals", "sneakers", "bags" and "ankle boots" (we have $d(A, A) < 0$ for these classes).

Evaluation on large-scale datasets   In addition to comparing CoHiClust with hierarchical baselines on gray images, we perform the evaluation on large-scale datasets of color images: CIFAR-10, STL-10, ImageNet-Dogs, and ImageNet-10. Since none of the previous hierarchical methods have been examined on these datasets, we use the benchmark including flat clustering methods reported in Li et al. (2021a). It is expected that flat clustering methods will perform better because they directly

Table 3: Comparison with flat clustering methods on large-scale image benchmarks (higher is better).

Dataset	CIFAR-10			STL-10			ImageNet-10			ImageNet-Dogs		
Metrics	NMI	ACC	ARI	NMI	ACC	ARI	NMI	ACC	ARI	NMI	ACC	ARI
K-means Mac	0.087	0.229	0.049	0.125	0.192	0.061	0.119	0.241	0.057	0.055	0.105	0.020
SC Zelnik-Manor & Perona	0.103	0.247	0.085	0.098	0.159	0.048	0.151	0.274	0.076	0.038	0.111	0.013
AC Gowda & Krishna (1978)	0.105	0.228	0.065	0.239	0.332	0.140	0.138	0.242	0.067	0.037	0.139	0.021
NMF Cai	0.081	0.190	0.034	0.096	0.180	0.046	0.132	0.230	0.065	0.044	0.118	0.016
AE Bengio et al.	0.239	0.314	0.169	0.250	0.303	0.161	0.210	0.317	0.152	0.104	0.185	0.073
DAE Vincent et al. (2010)	0.251	0.297	0.163	0.224	0.302	0.152	0.206	0.304	0.138	0.104	0.190	0.078
DCGAN Radford et al. (2015)	0.265	0.315	0.176	0.210	0.298	0.139	0.225	0.346	0.157	0.121	0.174	0.078
DeCNN Zeiler et al. (2010)	0.240	0.282	0.174	0.227	0.299	0.162	0.186	0.313	0.142	0.098	0.175	0.073
VAE Kingma & Welling (2013)	0.245	0.291	0.167	0.200	0.282	0.146	0.193	0.334	0.168	0.107	0.179	0.079
JULE Yang et al. (2016)	0.192	0.272	0.138	0.182	0.277	0.164	0.175	0.300	0.138	0.054	0.138	0.028
DEC Xie et al. (2016)	0.257	0.301	0.161	0.276	0.359	0.186	0.282	0.381	0.203	0.122	0.195	0.079
DAC Chang et al. (2017)	0.396	0.522	0.306	0.366	0.470	0.257	0.394	0.527	0.302	0.219	0.275	0.111
DDC Chang et al. (2019)	0.424	0.524	0.329	0.371	0.489	0.267	0.433	0.577	0.345	0.239	0.306	0.128
DCCM Wu et al. (2019)	0.496	0.623	0.408	0.376	0.482	0.262	0.608	0.710	0.555	0.321	0.383	0.182
PICA Huang et al. (2020)	0.591	0.696	0.512	0.611	0.713	0.531	0.802	0.870	0.761	0.352	0.352	0.201
CC Li et al. (2021a)	0.705	0.790	0.637	0.764	0.850	0.726	0.859	0.893	0.822	0.445	0.429	0.274
CoHiClust	0.490	0.591	0.392	0.503	0.529	0.386	0.742	0.744	0.622	0.407	0.350	0.193

focus on partitioning data into a given number of groups. Hierarchical models, such as CoHiClust, build a hierarchy with the number of leaves exceeding the number of classes, which makes it difficult to obtain so high a resemblance with the ground truth as flat models. Moreover, the optimization of hierarchy is a more difficult and challenging process because final assignments rely on aggregating several binary decisions made by the internal nodes.

Our model uses ResNet34 as a base network, which better suits the complexity of the current images and coincides with the architecture used in Li et al. (2021a). We consider a tree with 16 leaves (4 levels), which is next pruned to obtain the number of clusters equal to the number of ground truth classes. We train the initial complete tree with the batch size of 256 for 1000 epochs and use 100 epochs after pruning every leaf. To measure the similarity of the constructed partition with the ground truth, we apply three widely-used clustering metrics: normalized mutual information (NMI), clustering accuracy (ACC), and adjusted rand index (ARI). In the appendix, we also show DP of the hierarchies generated by CoHiClust.

The results presented in Table 3 show that CoHiClust usually is among the three best-performing methods. It gives very good results, compared to the baselines, on the subset of the ImageNet dataset achieving 0.742 of NMI. Nevertheless, one should keep in mind that CoHiClust is the only hierarchical method in this comparison, which makes it more challenging to construct flat partition, which resembles the ground truth classes.

To better analyze the results returned by CoHiClust, we plot the constructed clustering hierarchies and distance matrices calculated for ground truth classes. Figure 4 presents and discusses the tree hierarchy constructed for ImageNet-10 (remaining hierarchies together with distance matrices are presented in the appendix). Supporting the analysis with the use of a distance matrix, we can observe that examples of 5 out of 10 classes have not been spread across different clusters (we have $d(A, A) \leq 1$). Airliner and airship classes are the most semantically similar. The class king penguin is the most distinct from the classes representing the means of transport with an average distance greater than 7. Overall, we can see a very high similarity between classes related to the means of transport. The distance between other classes is not as small, which suggests that there are no evident patterns that connect e.g. king penguin, Maltese dog, or orange.

5 CONCLUSION

We proposed a contrastive hierarchical clustering model CoHiClust, which suits well to clustering of large-scale image databases. The hierarchical structure constructed by CoHiClust delivers significantly more information about data than typical flat clustering models. In particular, we can inspect the similarity between selected groups by measuring their distance in the hierarchy tree and, in consequence, find super-clusters. Experimental analysis performed on typical clustering benchmarks confirms that the produced partitions have high similarity with ground truth classes. At the same time CoHiClust allows for discovering important patterns which have not been encoded in the class labels.

REFERENCES

Stephan Alaniz, Diego Marcos, Bernt Schiele, and Zeynep Akata. Learning decision trees recurrently through communication. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 13518–13527, 2021.

Anwesha Barai and Lopamudra Dey. Outlier detection and removal algorithm in k-means and hierarchical clustering. World Journal of Computer Application and Technology, 5(2):24–29, 2017.

Yoshua Bengio, Pascal Lamblin, Dan Popovici, and Hugo Larochelle. Greedy layer-wise training of deep networks. In B. Schölkopf, J. Platt, and T. Hoffman (eds.), Advances in Neural Information Processing Systems. MIT Press.

Anil Bhattacharyya. On a measure of divergence between two multinomial populations. Sankhyā: the indian journal of statistics, pp. 401–406, 1946.

J. Chang, Y. Guo, L. Wang, G. Meng, S. Xiang, and C. Pan. Deep discriminative clustering analysis. arXiv preprint arXiv:1905.01681, 2019.

Jianlong Chang, Lingfeng Wang, Gaofeng Meng, Shiming Xiang, and Chunhong Pan. Deep adaptive image clustering. In Proceedings of the IEEE International Conference on Computer Vision (ICCV), Oct 2017.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In Hal Daumé III and Aarti Singh (eds.), Proceedings of the 37th International Conference on Machine Learning, volume 119 of Proceedings of Machine Learning Research, pp. 1597–1607. PMLR, 13–18 Jul 2020. URL https://proceedings.mlr.press/v119/chen20j.html.

Sumit Chopra, Raia Hadsell, and Yann LeCun. Learning a similarity metric discriminatively, with application to face verification. In 2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05), volume 1, pp. 539–546. IEEE, 2005.

Zhiyuan Dang, Cheng Deng, Xu Yang, Kun Wei, and Heng Huang. Nearest neighbor matching for deep clustering. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 13693–13702, 2021.

Nicholas Frosst and Geoffrey Hinton. Distilling a neural network into a soft decision tree. arXiv preprint arXiv:1711.09784, 2017.

K. Chidananda Gowda and G. Krishna. Agglomerative clustering using the concept of mutual nearest neighbourhood. Pattern Recognition, 10:105–112, 1978.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent-a new approach to self-supervised learning. Advances in neural information processing systems, 33:21271–21284, 2020.

Joris Guérin, Olivier Gibaru, Stéphane Thiery, and Eric Nyiri. Cnn features are also great at unsupervised classification. arXiv preprint arXiv:1707.01700, 2017.

Xifeng Guo, Long Gao, Xinwang Liu, and Jianping Yin. Improved deep embedded clustering with local structure preservation. In Ijcai, pp. 1753–1759, 2017a.

Xifeng Guo, Xinwang Liu, En Zhu, and Jianping Yin. Deep clustering with convolutional autoencoders. In International conference on neural information processing, pp. 373–382. Springer, 2017b.

R. Hadsell, S. Chopra, and Y. LeCun. Dimensionality reduction by learning an invariant mapping. In 2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06), volume 2, pp. 1735–1742, 2006. doi: 10.1109/CVPR.2006.100.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In 2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp. 9726–9735, 2020. doi: 10.1109/CVPR42600.2020.00975.

Weihua Hu, Takeru Miyato, Seiya Tokui, Eiichi Matsumoto, and Masashi Sugiyama. Learning discrete representations via information maximizing self-augmented training. In International conference on machine learning, pp. 1558–1567. PMLR, 2017.

Jiabo Huang, Shaogang Gong, and Xiatian Zhu. Deep semantic clustering by partition confidence maximisation. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pp. 8849–8858, 2020.

Xu Ji, João F Henriques, and Andrea Vedaldi. Invariant information clustering for unsupervised image classification and segmentation. In Proceedings of the IEEE International Conference on Computer Vision, pp. 9865–9874, 2019.

D. P. Kingma and M. Welling. Auto-encoding variational bayes. arXiv preprint arXiv:1312.6114, 2013.

Ari Kobren, Nicholas Monath, Akshay Krishnamurthy, and Andrew McCallum. A hierarchical algorithm for extreme clustering. In Proceedings of the 23rd ACM SIGKDD international conference on knowledge discovery and data mining, pp. 255–264, 2017.

Jyoti Lakhani, Anupama Chowdhary, and Dharmesh Harwani. Clustering techniques for biological sequence analysis: A review. Journal of Applied Information Scienc, 3(1):14–32, 2015.

Yunfan Li, Peng Hu, Zitao Liu, Dezhong Peng, Joey Tianyi Zhou, and Xi Peng. Contrastive clustering. Proceedings of the AAAI Conference on Artificial Intelligence, 35(10):8547–8555, May 2021a. URL https://ojs.aaai.org/index.php/AAAI/article/view/17037.

Yunfan Li, Peng Hu, Zitao Liu, Dezhong Peng, Joey Tianyi Zhou, and Xi Peng. Contrastive clustering. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 35, pp. 8547–8555, 2021b.

Dominik Mautz, Claudia Plant, and Christian Böhm. Deep embedded cluster tree. In 2019 IEEE International Conference on Data Mining (ICDM), pp. 1258–1263. IEEE, 2019.

Dominik Mautz, Claudia Plant, and Christian Böhm. Deepect: The deep embedded cluster tree. Data Science and Engineering, 5(4):419–432, 2020.

Takeru Miyato, Shin-ichi Maeda, Masanori Koyama, and Shin Ishii. Virtual adversarial training: a regularization method for supervised and semi-supervised learning. IEEE transactions on pattern analysis and machine intelligence, 41(8):1979–1993, 2018.

F. Murtagh and P. Contreras. Algorithms for hierarchical clustering: an overview. Wiley Interdiscip Rev Data Min Knowl Discov, 2(1):86–97, 2012.

Stanislav Naumov, Grigory Yaroslavtsev, and Dmitrii Avdiukhin. Objective-based hierarchical clustering of deep embedding vectors. In AAAI, pp. 9055–9063, 2021.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. arXiv preprint arXiv:1511.06434, 11 2015.

Florian Schroff, Dmitry Kalenichenko, and James Philbin. Facenet: A unified embedding for face recognition and clustering. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 815–823, 2015.

Marek Śmieja, Dawid Warszycki, Jacek Tabor, and Andrzej J Bojarski. Asymmetric clustering index in a case study of 5-ht1a receptor ligands. PloS one, 9(7):e102069, 2014.

Ryutaro Tanno, Kai Arulkumaran, Daniel Alexander, Antonio Criminisi, and Aditya Nori. Adaptive neural trees. In International Conference on Machine Learning, pp. 6166–6175. PMLR, 2019.

Pascal Vincent, Hugo Larochelle, Isabelle Lajoie, Yoshua Bengio, and Pierre-Antoine Manzagol. Stacked denoising autoencoders: Learning useful representations in a deep network with a local denoising criterion. Journal of Machine Learning Research, 11(110):3371–3408, 2010.

Alvin Wan, Lisa Dunlap, Daniel Ho, Jihan Yin, Scott Lee, Henry Jin, Suzanne Petryk, Sarah Adel Bargal, and Joseph E Gonzalez. Nbdt: neural-backed decision trees. arXiv preprint arXiv:2004.00221, 2020.

Jianlong Wu, Keyu Long, Fei Wang, Chen Qian, Cheng Li, Zhouchen Lin, and Hongbin Zha. Deep comprehensive correlation mining for image clustering. In Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), October 2019.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via non-parametric instance discrimination. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 3733–3742, 2018.

Junyuan Xie, Ross Girshick, and Ali Farhadi. Unsupervised deep embedding for clustering analysis. In International conference on machine learning, pp. 478–487. PMLR, 2016.

Jianwei Yang, Devi Parikh, and Dhruv Batra. Joint unsupervised learning of deep representations and image clusters. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 5147–5156, 2016.

Ruipeng Yang, Dan Qu, Yekui Qian, Yusheng Dai, and Shaowei Zhu. An online log template extraction method based on hierarchical clustering. EURASIP Journal on Wireless Communications and Networking, 2019(1):1–12, 2019.

Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow twins: Self-supervised learning via redundancy reduction. In International Conference on Machine Learning, pp. 12310–12320. PMLR, 2021.

Matthew D. Zeiler, Dilip Krishnan, Graham W. Taylor, and Rob Fergus. Deconvolutional networks. In 2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, pp. 2528–2535, 2010.

Lihi Zelnik-Manor and Pietro Perona. Self-tuning spectral clustering. In Advances in Neural Information Processing Systems.

Feng Zhang, Lin Li, Qiang Hua, Chun-Ru Dong, and Boon-Han Lim. Improved deep clustering model based on semantic consistency for image clustering. Knowledge-Based Systems, 253:109507, 2022. ISSN 0950-7051. doi: https://doi.org/10.1016/j.knosys.2022.109507. URL https://www.sciencedirect.com/science/article/pii/S0950705122007560.

Yuchen Zhang, Amr Ahmed, Vanja Josifovski, and Alexander Smola. Taxonomy discovery for personalized recommendation. In Proceedings of the 7th ACM international conference on Web search and data mining, pp. 243–252, 2014.

Quan Zou, Gang Lin, Xingpeng Jiang, Xiangrong Liu, and Xiangxiang Zeng. Sequence clustering in bioinformatics: an empirical study. Briefings in bioinformatics, 21(1):1–10, 2020.

A SUPPLEMENTARY EXPERIMENTAL RESULTS

In Figures 5, 6, 7 and 8 we illustrate the tree hierarchies constructed by CoHiClust for the remaining datasets. Distance matrices for ground true classes generated from these hierarchies are shown in Figure 9.

Figure 5: Tree hierarchy constructed for MNIST.

Figure 6: Tree hierarchy constructed for CIFAR-10.

Figure 7: Tree hierarchy constructed for STL-10.

Figure 8: Tree hierarchy constructed for ImageNet-Dogs.

B ABLATION STUDY

In Table 4, we show how the selection of the architecture for the base network g influences the performance of CoHiClust. As can be seen, the difference in the results is marginal.

Table 4: Comparison of ResNet architectures.

Dataset	CIFAR-10			STL-10		
Metrics	NMI	ACC	ARI	NMI	ACC	ARI
ResNet18	0.48	0.51	0.36	0.5034	0.5294	0.3861
ResNet34	0.4903	0.5916	0.3922	0.498	0.467	0.366

Next, we analyze whether end-to-end training is crucial for the performance of CoHiClust. For this purpose, we first pretrain the base network g using NT-Xent loss, which corresponds to the typical SimCLR model Chen et al. (2020). Next, we add the projection head π to g and train CoHiClust using CoHiLoss $+ R_2$ loss. As can be seen in Table 5 the model trained in an end-to-end manner obtains significantly better scores.

Figure 9: Distance matrices retrieved from the constructed hierarchies for ground truth classes.

Table 5: Training CoHiClust end-to-end vs. training CoHiClust on representation taken from pre-trained SimCLR.

	NMI	ACC	ARI
end-to-end training	0.498	0.467	0.386
pretrained representation	0.434	0.480	0.297

C DENDROGRAM PURITY FOR DATASETS OF COLOR IMAGES

In Table 6, we present dendrogram purity obtained by CoHiClust for datasets of color images. This benchmark can be used to compare other hierarchical clustering models.

Table 6: Dendrogram purity on color images.

	DP
CIFAR-10	0.396
STL-10	0.345
ImageNet-10	0.613
ImageNet-Dogs	0.198