PUMPOUT: A META APPROACH FOR ROBUSTLY TRAINING DEEP NEURAL NETWORKS WITH NOISY LABELS

ABSTRACT

It is challenging to train deep neural networks robustly on the industrial-level data, since labels of such data are heavily noisy, and their label generation processes are normally agnostic. To handle these issues, by using the memorization effects of deep neural networks, we may train deep neural networks on the whole dataset only the first few iterations. Then, we may employ early stopping or the small-loss trick to train them on selected instances. However, in such training procedures, deep neural networks inevitably memorize some noisy labels, which will degrade their generalization. In this paper, we propose a meta algorithm called *Pumpout* to overcome the problem of memorizing noisy labels. By using *scaled stochastic gradient ascent*, Pumpout actively squeezes out the negative effects of noisy labels from the training model, instead of passively forgetting these effects. We leverage Pumpout to upgrade two representative methods: MentorNet and Backward Correction. Empirical results on benchmark datasets demonstrate that Pumpout can significantly improve the robustness of representative methods.

1   INTRODUCTION

Learning from the industrial-level data is quite demanding, since labels of such data are heavily noisy, and their label generation processes are usually agnostic (Xiao et al., 2015; Jiang et al., 2018). Essentially, noisy labels of such data are corrupted from ground-truth labels without any prior assumptions (i.e., class-conditional noise (Natarajan et al., 2013)), which degrades the robustness of learning models. It is noted that industrial-level data is frequently emerging in our daily life, such as social-network data (Cha & Cho, 2012), E-commerce data (Xiao et al., 2015) and crowdsourcing data (Welinder et al., 2010; Han et al., 2018a).

Due to the large data volume, industrial-level data can be well handled by deep neural networks (Xiao et al., 2015). Thus, the key issue is how to train deep neural networks robustly on noisy labels of such data, since deep neural networks have the high capacity to fit noisy labels eventually (Zhang et al., 2017). To handle noisy labels, one common direction focuses on estimating the noise transition matrix (Goldberger & Ben-Reuven, 2017; Han et al., 2018b). For instance, Patrini et al. (2017) first leveraged a two-step solution to estimate the noise transition matrix. Based on this estimated matrix, they conducted backward loss correction, which is used for training deep neural networks robustly. However, the noise transition matrix is not easy to be estimated accurately, especially when the noise ratio is high and the number of classes is large.

Motivated by the memorization effects of deep neural networks (Arpit et al., 2017), one emerging direction focuses on training only on selected instances (Jiang et al., 2018; Ren et al., 2018; Han et al., 2018c), which does not require any prior assumptions on noisy labels. Specifically, deep learning models are known to learn easy instances first, then gradually adapt to hard instances when training epochs become large (Arpit et al., 2017). Therefore, in the first few iterations, we may train deep neural networks on the whole dataset, and let them sufficiently learn clean instances in the noisy dataset. Then we may later conduct early stopping (Goodfellow et al., 2016), which tries to stop the training on noisy instances; or we may employ the small-loss trick (Jiang et al., 2018; Han et al., 2018c), which tries to perform the training selectively on clean (small-loss) instances.

However, when noisy labels indeed exist, no matter using early stopping or small-loss trick, deep learning models inevitably memorize some noisy labels (Zhang et al., 2017), which will lead to the poor generalization performance. In this paper, we design a meta algorithm called *Pumpout*,

which allows us to overcome the issue of memorizing noisy labels. The main idea of Pumpout is to actively squeeze out the negative effects of noisy labels from the training model, instead of passively forgetting these effects by further training. Specifically, on clean labels, Pumpout conducts stochastic gradient descent typically; while on noisy labels, Pumpout conducts *scaled stochastic gradient ascent*, instead of stopping gradient computation as usual. This aggressive policy can erase the negative effects of noisy labels actively and effectively.

We leverage Pumpout to upgrade two representative but orthogonal approaches in the area of "deep learning with noisy labels": MentorNet (Jiang et al., 2018) and Backward Correction (Patrini et al., 2017; van Rooyen & Williamson, 2018). We conducted experiments on simulated noisy *MNIST* and *CIFAR10* datasets. Empirical results demonstrated that, under both extremely noisy labels (i.e., 45% and 50% of noisy labels) and low-level noisy labels (i.e., 20% of noisy labels), the robustness of two upgraded approaches (by Pumpout) is obviously superior than that of original approaches.

2 PUMPOUT MEETS NOISY SUPERVISION

Meta algorithm. The original idea of Pumpout is to actively squeeze out the negative effects of noisy labels from the training model, instead of passively forgetting these effects. However, in the design of meta algorithm, we should consider how our meta algorithm can simultaneously benefit multiple orthogonal approaches, such as training on selected instances (Jiang et al., 2018), estimating the noise transition matrix (Patrini et al., 2017) and designing regularization (Miyato et al., 2016).

For this purpose, we generalize noisy labels into "not-fitting" labels, and generalize clean labels into "fitting" labels (details of the fitting condition will be discussed in Q1 below). In the high level, the meta algorithm Pumpout is to train deep neural networks by stochastic gradient descent on "fitting" labels, and train deep neural networks by *scaled stochastic gradient ascent* on "not-fitting" labels.

In the low level, the proposed Algorithm 1 is named Pumpout. Specifically, we maintain deep neural network f (with parameter w_f). When a single point $\{\mathbf{x}_i, y_i\}$ is sequentially selected from noisy set $\mathcal{D}$ (step 3), we first check whether $\{\mathbf{x}_i, y_i\}$ is fitting the discriminative condition or not. If yes, we conduct stochastic gradient descent typically (step 4); otherwise, we conduct scaled (γ) stochastic gradient ascent (step 5), which erases the negative effects of "not-fitting" labels. The abstract algorithm arises three important questions naturally.

Algorithm 1 Meta Algorithm Pumpout.

1: **Input** network parameter w_f, learning rate η, maximum epoch $T_{\max}$, hyper parameter $0 \leq \gamma \leq 1$;
for $t = 1, 2, \ldots, T_{\max}$ **do**
   2: **Shuffle** training set $\mathcal{D}$;   //noisy dataset
   for $i = 1, \ldots, |\mathcal{D}|$ **do**
      3: **Select** $\{\mathbf{x}_i, y_i\}$ from $\mathcal{D}$ sequentially;
      if $\{\mathbf{x}_i, y_i\}$ *is fitting* **then**
        4: **Update** $w_f = w_f - \eta\nabla f(\mathbf{x}_i, y_i)$;   //stochastic gradient descent
      end
      else
        5: **Update** $w_f = w_f + \gamma\eta\nabla f(\mathbf{x}_i, y_i)$;   //scaled stochastic gradient ascent
      end
   end
end
6: **Output** w_f.

Three important questions.

    Q1. What is the fitting condition?

    Q2. Why do we need gradient ascent on non-fitting data, in addition to gradient descent on fitting data?

    Q3. Why do we need to scale the stochastic gradient ascent on non-fitting data?

To answer the *first question*, we need to emphasize a view that orthogonal approaches require different fitting conditions. Intuitively, if a single point $\{\mathbf{x}_i, y_i\}$ satisfies a discriminative fitting condition,

it means that our training model will regard this data point as a useful knowledge, and fitting on this point will benefit training the robust model. Conversely, if a single point $\{\mathbf{x}_i, y_i\}$ does not satisfy the discriminative fitting condition, it means that, our training model will regard this data point as useless knowledge, and want to erase the negative effects of this point actively. To instantiate the fitting condition, we provide two concrete cases in Algorithm 2 and Algorithm 3, respectively.

The above answer motivates our *second question*: why cannot we only conduct stochastic gradient descent on fitting data points (step 4). In other words, can we remove scaled stochastic gradient ascent (step 5) in Algorithm 1? In this case (removing step 5), our algorithm degenerates to training only on selected instances. However, once some of the selected instances are found to be false positives, our training model will fit on them, and thus the negative effects will inevitably occur (i.e., degrading the generalization). Instead of passively forgetting these negative effects, we hope to actively squeeze out the negative effects from the training model by using scaled stochastic gradient ascent (step 5).

Lastly, the *third question* closely connects with the second one. Namely, why do we need *scaled* instead of *ordinary* stochastic gradient ascent? The answer can be intuitively explained. Assume that we view stochastic gradient ascent as correction to "not-fitting" labels, and view $0 \leq \gamma \leq 1$ as a scale parameter. When $\gamma = 1$, our Pumpout will squeeze out the negative effects with full fast rate; while when $\gamma = 0$, our Pumpout will not squeeze out any negative effects. Both cases are not optimal. For the first case, the fast squeezing rate will negatively affect the convergence of our algorithm. For the second case, no squeezing rate will inevitably let deep neural networks memorize some "not-fitting" labels, which degrades their generalization.

3 PUMPOUT BENEFITS STATE-OF-THE-ART ALGORITHMS

In this section, we apply the idea of Pumpout to MentorNet and Backward Correction as follows.

3.1 UPGRADED MENTORNET

Algorithm 2 represents the upgraded MentorNet using Pumpout approach (denoted as $\text{Pumpout}_{\text{SL}}$), where MentorNet uses the small-loss trick. Specifically, we maintain deep neural network f (with parameter w_f). When a mini-batch $\bar{\mathcal{D}}$ is formed (step 3), we first let f select a small proportion of instances in this mini-batch $\bar{\mathcal{D}}_s$ that have *small* training losses (step 4). The number of instances is controlled by $R(T)$, and f only samples $R(T)$ percentage of instances out of the mini-batch. More importantly, we let f select a proportion of instances in this mini-batch $\bar{\mathcal{D}}_b$ that have *big* training losses (step 5). The number of instances is controlled by $1 - R(T)$, and f only samples $1 - R(T)$ percentage of instances out of the mini-batch. Then, we conduct stochastic gradient descent on small-loss instances $\bar{\mathcal{D}}_s$ (step 6); while we conduct scaled stochastic gradient ascent on big-loss instances $\bar{\mathcal{D}}_b$ (step 7), which actively erases the negative effects of big-loss instances. The update of $R(T)$ (step 8) follows Han et al. (2018c), in which extensive discussion has been conducted.

Algorithm 2 $\text{Pumpout}_{\text{SL}}$. The fitting condition is whether a point belongs to small-loss instances.

1: **Input** network parameter w_f, learning rate $\eta > 0$, estimated noise rate τ, maximum epoch $T_{\max}$, maximum iteration $N_{\max}$, hyper parameter $0 \leq \gamma \leq 1$;
for $T = 1, 2, \ldots, T_{\max}$ **do**
    2: **Shuffle** training set $\mathcal{D}$;   //noisy dataset
    for $N = 1, \ldots, N_{\max}$ **do**
        3: **Draw** mini-batch $\bar{\mathcal{D}}$ from $\mathcal{D}$;
        4: **Sample** $\bar{\mathcal{D}}_s = \arg\min_{\bar{\mathcal{D}}} \ell(f, \bar{\mathcal{D}}, R(T))$;   //sample $R(T)\%$ small-loss instances
        5: **Sample** $\bar{\mathcal{D}}_b = \arg\max_{\bar{\mathcal{D}}} \ell(f, \bar{\mathcal{D}}, 1 - R(T))$;   //sample $1 - R(T)\%$ big-loss instances
        6: **Update** $w_f = w_f - \eta \nabla f(\bar{\mathcal{D}}_s)$;   //update w_f by stochastic gradient descent on $\bar{\mathcal{D}}_s$;
        7: **Update** $w_f = w_f + \gamma\eta \nabla f(\bar{\mathcal{D}}_b)$; //update w_f by scaled stochastic gradient ascent on $\bar{\mathcal{D}}_b$;
    end
    8: **Update** $R(T) = 1 - \min\left\{\frac{T}{T_k}\tau, \tau\right\}$;
end
9: **Output** w_f.

Relations to MentorNet. To handle noisy labels, an emerging direction focuses on training only on selected instances (Jiang et al., 2018; Ren et al., 2018; Han et al., 2018c), which is free of estimating the noise transition matrix, and also free of the class-conditional noise assumption. These works try to select clean instances out of the noisy ones, and then use them to update the network. Among those works, a representative method is MentorNet (Jiang et al., 2018), which employs the small-loss trick. Specifically, MentorNet pre-trains an extra network, and then uses the extra network for selecting small-loss instances as clean instances to guide the training. However, the idea of MentorNet is similar to the self-training approach (Chapelle et al., 2009), thus MentorNet inherits the same drawback of accumulated error caused by the sample-selection bias.

Note that, if we remove step 5 and step 7 in Algorithm 2, $\text{Pumpout}_{\text{SL}}$ algorithm will be reduced to the core version of MentorNet. It means that $\text{Pumpout}_{\text{SL}}$ algorithm is more aggressive than MentorNet in essence. Namely, $\text{Pumpout}_{\text{SL}}$ conducts not only stochastic gradient descent on small-loss instances (like MentorNet), but also scaled stochastic gradient ascent on big-loss instances.

3.2 UPGRADED BACKWARD CORRECTION

Algorithm 3 represents the upgraded Backward Correction using the Pumpout approach (denoted as $\text{Pumpout}_{\text{BC}}$), where Backward Correction is defined in Theorem 1. If the model being trained is flexible (i.e., a deep neural network), Backward Correction will lead to negative risks (Patrini et al., 2017), which subsequently yields an over-fit issue. To mitigate this issue, we maintain deep neural network f (with parameter w_f). When a single point $\{\mathbf{x}_i, y_i\}$ is sequentially selected from the j-th mini-batch $\bar{\mathcal{D}}$ (step 5), we first compute the temporary gradient g_t at this point (step 6). If Backward Correction produces a positive risk at this point, namely $\mathbf{1}^\top \mathbf{T}^{-1} \ell(\mathbf{x}_i, y_i; w_f) \geq \beta \geq 0$ (definitions of $\mathbf{T}$ and ℓ are in Theorem 1), we accumulate gradient G_a by the gradient descent (step 7); otherwise, we accumulate gradient G_a by the scaled gradient ascent (step 8), and this step erases the negative effects of negative-risk instances. Lastly, we average the accumulated gradient (step 9) and update parameter w_f by stochastic optimization (step 10).

Algorithm 3 $\text{Pumpout}_{\text{BC}}$. The fitting condition is whether a point satisfies $\mathbf{1}^\top \mathbf{T}^{-1} \ell(\mathbf{x}_i, y_i; w_f) \geq \beta$.

---
1. **Input** network parameter w_f, learning rate $\eta > 0$, maximum epoch $T_{\max}$, hyper parameter $\beta \geq 0$ and $0 \leq \gamma \leq 1$;
for $T = 1, 2, \ldots, T_{\max}$ **do**
  2. **Shuffle** training set $\mathcal{D}$ into n-mini batches with batch size k;   //noisy dataset
  for $j = 1, \ldots, n$ **do**
    3. **Reset** $G_a = 0$;   //gradient accumulator
    4: **Draw** j-th mini-batch $\bar{\mathcal{D}}$ from $\mathcal{D}$;
    for $i = 1, \ldots, k$ **do**
      5. **Select** $\{\mathbf{x}_i, y_i\}$ from $\bar{\mathcal{D}}$ as i-th data point;
      6. **Set** $g_t = \nabla_{w_f} \{\mathbf{1}^\top \mathbf{T}^{-1} \ell(\mathbf{x}_i, y_i; w_f)\}$;   //temp gradient
      if $\mathbf{1}^\top \mathbf{T}^{-1} \ell(\mathbf{x}_i, y_i; w_f) \geq \beta$ **then**
        | 7. **Update** $G_a = G_a + g_t$;   //gradient descent
      end
      else
        | 8. **Update** $G_a = G_a - \gamma g_t$;   //scaled gradient ascent
      end
    end
    9. **Average** $g_a = G_a / k$;
    10. **Update** $w_f = w_f - \eta g_a$;   //stochastic optimization
  end
end
11. **Output** w_f.

Relations to Backward Correction and its non-negative version. To handle noisy labels, the other popular direction focuses on estimating the noise transition matrix (Goldberger & Ben-Reuven, 2017; Patrini et al., 2017; Han et al., 2018b). Among those works, a representative method is Backward Correction. Specifically, Patrini et al. (2017) leveraged a two-step solution to estimate the noise

transition matrix heuristically. Then they employed the estimated matrix to correct the original loss, and robustly train a deep neural network based on the new loss function.

Theorem 1 *(Backward Correction, Theorem 1 in (Patrini et al., 2017)) Suppose that the noise transition matrix $\mathbf{T}$ is non-singular, where $\mathbf{T}_{ij} = \Pr(\tilde{y} = j | y = i)$ given that noisy label $\tilde{y} = j$ is flipped from clean label $y = i$. Given loss ℓ and network parameter w_f, Backward Correction is defined as*

$$\ell^{\leftarrow}(\mathbf{x}, y; w_f) = \mathbf{T}^{-1}\ell(\mathbf{x}, y; w_f). \tag{1}$$

Then, corrected loss is unbiased, namely,

$$\mathbb{E}_{\tilde{y}|\mathbf{x}}\ell^{\leftarrow}(\mathbf{x}, y; w_f) = \mathbb{E}_{y|\mathbf{x}}\ell(\mathbf{x}, y; w_f), \forall \mathbf{x}. \tag{2}$$

Remark 1 *Backward Correction operates on the loss vector directly. It is unbiased. LHS of Eq. (2) draws from noisy labels, and RHS of Eq. (2) draws from clean labels. Note that the corrected loss is differentiable, but not always non-negative (van Rooyen & Williamson, 2018).*

If the model being trained is flexible, such as a deep neural network, the backward loss correction will lead to negative risks, and the hazardous aspect is to yield an over-fit issue. Motivated by Kiryo et al. (2017), we should conduct a non-negative correction again based on the backward-corrected loss. The reason is that the risk should always be greater than 0 or equal to.

Theorem 2 *(Non-negative Backward Correction) Suppose that the noise transition matrix $\mathbf{T}$ is non-singular, where $\mathbf{T}_{ij} = \Pr(\tilde{y} = j | y = i)$ given that noisy label $\tilde{y} = j$ is flipped from clean label $y = i$. Given loss ℓ and network parameter w_f, Non-negative Backward Correction is defined as*

$$\ell_m^{\leftarrow}(\mathbf{x}, y; w_f) = \max\{0, \mathbf{1}^{\top}\mathbf{T}^{-1}\ell(\mathbf{x}, y; w_f)\}, \tag{3}$$

where $\mathbf{1}_{k \times 1}$. Then, the corrected loss is non-negative, namely,

$$\ell_m^{\leftarrow}(\mathbf{x}, y; w_f) \geq 0. \tag{4}$$

Remark 2 *$\ell_m^{\leftarrow}(\mathbf{x}, y; w_f)$ is a non-negative scalar. Our key claim is to overcome the over-fit issue by non-negative correction.*

However, the above non-negative correction is passive, since $\max$ operator means stopping gradient computation on negative-risk instances. This correction may not achieve the optimal performance. Namely, when $\mathbf{1}^{\top}\mathbf{T}^{-1}\ell(\mathbf{x}, y; w_f) > 0$, we conduct stochastic gradient descent; otherwise, we do not perform the stochastic gradient. To propose an aggressive non-negative correction, we reverse the gradient computation at negative-risk instances. Specifically, we use the Pumpout approach to improve Non-negative Backward Correction. Namely, when $\mathbf{1}^{\top}\mathbf{T}^{-1}\ell(\mathbf{x}, y; w_f) > 0$, we conduct stochastic gradient descent; when $\mathbf{1}^{\top}\mathbf{T}^{-1}\ell(\mathbf{x}, y; w_f) < 0$, we conduct scaled stochastic gradient ascent. This brings our Algorithm 3.

Note that, if we remove line 8 in Algorithm 3, Pumpout$_{\text{BC}}$ algorithm will be reduced to Non-negative Backward Correction. It means Pumpout$_{\text{BC}}$ algorithm is an aggressive version of Non-negative Backward Correction. Namely, Pumpout$_{\text{BC}}$ conducts not only stochastic gradient descent on nonnegative-risk instances, but also scaled stochastic gradient ascent on negative-risk instances.

4 EXPERIMENTS

Datasets. We verify the effectiveness of our Pumpout approach on two benchmark datasets preliminarily. *MNIST* and *CIFAR10* are used here (Table 1), as these data sets are popularly used for evaluation of noisy labels in the literature (Reed et al., 2015; Goldberger & Ben-Reuven, 2017; Patrini et al., 2017; Han et al., 2018c).

Since all datasets are clean, following (Reed et al., 2015; Patrini et al., 2017), we need to corrupt these datasets manually by the noise transition matrix $\mathbf{T}$, where $\mathbf{T}_{ij} = \Pr(\tilde{y} = j | y = i)$ given

Table 1: Summary of data sets used in the experiments.

	# of training	# of testing	# of class	image size
MNIST	60,000	10,000	10	28×28
CIFAR10	50,000	10,000	10	32×32

that noisy $\tilde{y}$ is flipped from clean y. Assume that the matrix $\mathbf{T}$ has two representative structures (Figure 1): (1) Pair flipping (Han et al., 2018b): a real-world application is the fine-grained classification, where you may make mistake only within very similar classes in the adjunct positions; (2) Symmetry flipping (Van Rooyen et al., 2015). Their precise definition is in Appendix A.

(a) Pair ($\epsilon = 45\%$). (b) Symmetry ($\epsilon = 50\%$).

Figure 1: Transition matrices of different noise types (using 5 classes as an example).

This paper first verifies whether Pumpout can significantly improve the robustness of representative methods on *extremely* noisy supervision, the noise rate ϵ is chosen from $\{0.45, 0.5\}$. Intuitively, this means almost half of the instances have noisy labels. Note that, the noise rate $> 50\%$ for pair flipping means over half of the training data have wrong labels that cannot be learned without additional assumptions. In addition to extremely noisy settings, we also verify whether Pumpout can significantly improve the robustness of representative methods on *low-level* noisy supervision, where ϵ is set to 0.2. Note that pair case is much harder than symmetry case. In Figure 1(a), the true class only has 10% more correct instances over wrong ones. However, the true has 37.5% more correct instances in Figure 1(b). Meanwhile, similarly to (Reed et al., 2015; Goldberger & Ben-Reuven, 2017; Jiang et al., 2018), we did not make any implicit assumption behind Pumpout.

Baselines. To verify the efficacy of Pumpout, we compare two orthogonal approaches in deep learning with noisy labels. The first set (SET1) comparison is to check whether Pumpout can improve the robustness of MentorNet. (i) MentorNet (Jiang et al., 2018). (ii) Pumpout$_{\text{SL}}$ (Algorithm 2). The second set (SET2) comparison is to check whether Pumpout can improve the robustness of Backward Correction. (i) Backward Correction (Patrini et al., 2017) (denoted as "BC", Theorem 1). (ii). Non-negative backward correction (denoted as "nnBC", Theorem 2). (iii) Pumpout$_{\text{BC}}$ (Algorithm 3). As a simple baseline, we also compare with the normal deep neural network that directly learns on the noisy training set (denoted as "Normal").

For the fair comparison, we implement all methods with default parameters by PyTorch, and conduct all the experiments on a NIVIDIA K80 GPU. Standard CNN is used with LReLU active function, and the detailed architecture is in Appendix B. Namely, we used the 9-layer CNN (Miyato et al., 2016; Laine & Aila, 2017) for *MNIST* and ResNet-32 (He et al., 2016) for *CIFAR10*, since the network structures we used here are standard test bed for weakly-supervised learning. For all datasets, Adam optimizer (momentum=0.9) with an initial learning rate of 0.001, the batch size is set to 128 and runs for 200 epoch. Besides, dropout and batch-normalization are also used.

Experimental setup. For *SET1*, the most important parameter of our Pumpout$_{\text{SL}}$ and MentorNet is $R(T)$. Here, we assume the noise level ϵ is known and set $R(T) = 1 - \tau \cdot \min\left(T/T_k, 1\right)$ with $T_k = 10$ and $\tau = \epsilon$. If ϵ is not known in advanced, ϵ can be inferred using validation sets (Liu & Tao, 2016). The choices of $R(T)$ and τ follows Han et al. (2018c). Note that $R(T)$ only depends on the memorization effect of deep networks but not any specific datasets. For *SET2*, the most important parameters of our Pumpout$_{\text{BC}}$ and nnBC are β and γ respectively. Specifically, the degree of tolerance is controlled by β ($\beta \geq 0$), and the scale of gradient ascent is controlled by γ ($0 \leq \gamma \leq 1$). The choices of β and γ follows Kiryo et al. (2017).

This paper provides two upgraded approaches to train deep neural networks robustly under noisy labels. Thus, our goal is to classify the clean instances as accurately as possible, and the measurement for both *SET1* and *SET2* is the test accuracy, i.e., *test accuracy = (# of correct predictions) / (# of test*

dataset). Besides, for *SET1*, we also use the label precision in each mini-batch, i.e., *label precision = (# of clean labels) / (# of all selected labels).* Specifically, we sample $R(T)$ of small-loss instances in each mini-batch, and then calculate the ratio of clean labels in the small-loss instances. Intuitively, higher label precision means less noisy instances in the mini-batch after sample selection; and the algorithm with higher label precision is also more robust to the label noise. All experiments are repeated five times. In each figure, the error bar for standard deviation is highlighted as a shade.

4.1 RESULTS OF PUMPOUT$_{SL}$ AND MENTORNET

MNIST.   In Figure 2, we show test accuracy (top) and label precision (bottom) vs number of epochs on *MINIST* dataset. In all three plots, we can clearly see the memorization effects of networks, i.e., test accuracy of Normal first reaches a very high level and then gradually decreases. Thus, a good robust training method should stop or alleviate the decreasing process. On this point, our Pumpout$_{SL}$ almost stops the decreasing process in the easier Symmetric-50% and Symmetric-20% cases. Meanwhile, compared to MentorNet, our Pumpout$_{SL}$ alleviates the decreasing process in the hardest Pair-45% case. Thus, Pumpout$_{SL}$ consistently achieves the higher accuracy over MentorNet.

To explain such good performance, we plot label precision (bottom). Compared to Normal, we can clearly see that both Pumpout$_{SL}$ and MentorNet can successfully pick clean instances out. However, our Pumpout$_{SL}$ achieves the higher label precision on not only the easier Symmetric-50% and Symmetric-20% cases, but also the hardest Pair-45% case. This shows our approach is better at finding clean instances due to the usage of scaled stochastic gradient ascent.

(a) Pair-45%.   (b) Symmetry-50%.   (c) Symmetry-20%.

Figure 2: Results of Pumpout$_{SL}$ and MentorNet on *MNIST* dataset. Top: test accuracy vs number of epochs; bottom: label precision vs number of epochs.

CIFAR10.   Figure 3 shows test accuracy and label precision vs number of epochs on *CIFAR10* dataset. Again, on test accuracy, we can see Pumpout$_{SL}$ strongly stops the memorization effects of networks. More importantly, on the easier Symmetric-50% and Symmetric-20% cases, it works better and better along with the training epochs. On label precision, while Normal fails to find clean instances, both Pumpout$_{SL}$ and MentorNet can do this. However, due to the usage of scaled stochastic gradient ascent, Pumpout$_{SL}$ is stronger and find more clean instances.

4.2 RESULTS OF PUMPOUT$_{BC}$ AND NNBC

MNIST.   Figure 4 shows test accuracy vs number of epochs on *MNIST* dataset. In all three plots, we can see the memorization effects of networks, i.e., test accuracy of Normal first reaches a very high level and then gradually decreases. However, our Pumpout$_{BC}$ fully stops the decreasing process in the hardest Pair-45% case. Meanwhile, in the easier Symmetric-50% and Symmetric-20%

Figure 3: Results of Pumpout$_{SL}$ and MentorNet on *CIFAR10* dataset. Top: test accuracy vs number of epochs; bottom: label precision vs number of epochs.

cases, our Pumpout$_{BC}$ works better and better along with the training epochs though it fluctuates. Moreover, our Pumpout$_{BC}$ finally achieves the higher accuracy over both BC and nnBC.

Figure 4: Results of Pumpout$_{BC}$ and nnBC on *MNIST* dataset. Test accuracy vs number of epochs.

5 CONCLUSION

This paper presents a meta algorithm called Pumpout, which significantly improves the robustness of state-of-the-art methods under noisy labels. Our key idea is to squeeze out the negative effects of noisy labels actively from the training model, instead of passively forgetting these effects. The realization of Pumpout is to train deep neural networks by stochastic gradient descent on "fitting" labels; while train deep neural networks by scaled stochastic gradient ascent on "not-fitting" labels. To demonstrate the efficacy of Pumpout, based on MentorNet and Backward Correction, we design two upgraded versions called Pumpout$_{SL}$ and Pumpout$_{BC}$, respectively. The experimental results show that, both updated approaches can train deep models more robustly over previous ones. In future, we can extend our work in the following aspects. First, we can leverage Pumpout approach to train deep models under another weak supervision, e.g., complementary labels (Ishida et al., 2017). Second, we should investigate the theoretical guarantees for Pumpout approach.

REFERENCES

D. Arpit, S. Jastrzebski, N. Ballas, D. Krueger, E. Bengio, M. Kanwal, T. Maharaj, A. Fischer, A. Courville, and Y. Bengio. A closer look at memorization in deep networks. In *International Conference on Machine Learning*, 2017.

Y. Cha and J. Cho. Social-network analysis using topic models. In *International ACM SIGIR conference on Research and Development in Information Retrieval*, pp. 565–574, 2012.

O. Chapelle, B. Scholkopf, and A. Zien. Semi-supervised learning. *IEEE Transactions on Neural Networks*, 20(3):542–542, 2009.

J. Goldberger and E. Ben-Reuven. Training deep neural-networks using a noise adaptation layer. In *International Conference on Learning Representations*, 2017.

I. Goodfellow, Y. Bengio, and A. Courville. *Deep learning*, volume 1. MIT press Cambridge, 2016.

B. Han, Y. Pan, and I. Tsang. Robust Plackett–Luce model for k-ary crowdsourced preferences. *Machine Learning*, 107(4):675–702, 2018a.

B. Han, J. Yao, G. Niu, M. Zhou, I. Tsang, Y. Zhang, and M. Sugiyama. Masking: A new perspective of noisy supervision. In *Advances in Neural Information Processing Systems*, 2018b.

B. Han, Q. Yao, X. Yu, G. Niu, M. Xu, W. Hu, I. Tsang, and M. Sugiyama. Co-teaching: Robust training of deep neural networks with extremely noisy labels. In *Advances in Neural Information Processing Systems*, 2018c.

K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 770–778, 2016.

T. Ishida, G. Niu, W. Hu, and M. Sugiyama. Learning from complementary labels. In *Advances in Neural Information Processing Systems*, pp. 5639–5649, 2017.

L. Jiang, Z. Zhou, T. Leung, L. Li, and L. Fei-Fei. Mentornet: Learning data-driven curriculum for very deep neural networks on corrupted labels. In *International Conference on Machine Learning*, pp. 2309–2318, 2018.

R. Kiryo, G. Niu, M. Du Plessis, and M. Sugiyama. Positive-unlabeled learning with non-negative risk estimator. In *Advances in Neural Information Processing Systems*, pp. 1675–1685, 2017.

S. Laine and T. Aila. Temporal ensembling for semi-supervised learning. In *International Conference on Learning Representations*, 2017.

T. Liu and D. Tao. Classification with noisy labels by importance reweighting. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 38(3):447–461, 2016.

T. Miyato, A. Dai, and I. Goodfellow. Virtual adversarial training for semi-supervised text classification. In *International Conference on Learning Representations*, 2016.

N. Natarajan, I. Dhillon, P. Ravikumar, and A. Tewari. Learning with noisy labels. In *Advances in Neural Information Processing Systems*, pp. 1196–1204, 2013.

G. Patrini, A. Rozza, A. Menon, R. Nock, and L. Qu. Making deep neural networks robust to label noise: a loss correction approach. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2233–2241, 2017.

S. Reed, H. Lee, D. Anguelov, C. Szegedy, D. Erhan, and A. Rabinovich. Training deep neural networks on noisy labels with bootstrapping. In *International Conference on Learning Representations Workshop*, 2015.

M. Ren, W. Zeng, B. Yang, and R. Urtasun. Learning to reweight examples for robust deep learning. In *International Conference on Machine Learning*, 2018.

B. van Rooyen and B. Williamson. A theory of learning with corrupted labels. *Journal of Machine Learning Research*, 18(228):1–50, 2018.

B. Van Rooyen, A. Menon, and B. Williamson. Learning with symmetric label noise: The importance of being unhinged. In *Advances in Neural Information Processing Systems*, pp. 10–18, 2015.

P. Welinder, S. Branson, P. Perona, and S. Belongie. The multidimensional wisdom of crowds. In *Advances in Neural Information Processing Systems*, pp. 2424–2432, 2010.

T. Xiao, T. Xia, Y. Yang, C. Huang, and X. Wang. Learning from massive noisy labeled data for image classification. In *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2691–2699, 2015.

C. Zhang, S. Bengio, M. Hardt, B. Recht, and O. Vinyals. Understanding deep learning requires rethinking generalization. In *International Conference on Learning Representations*, 2017.

A   DEFINITION OF NOISE

The definition of transition matrix $\mathbf{T}$ is as follow, where ϵ is the noise rate and n is the number of the classes.

$$
\text{Pair flipping:} \quad \mathbf{T} =
\begin{bmatrix}
1-\epsilon & \epsilon & 0 & \ldots & 0 \\
0 & 1-\epsilon & \epsilon & & 0 \\
\vdots & & \ddots & \ddots & \vdots \\
0 & & & 1-\epsilon & \epsilon \\
\epsilon & 0 & \ldots & 0 & 1-\epsilon
\end{bmatrix},
$$

$$
\text{Symmetry flipping:} \quad \mathbf{T} =
\begin{bmatrix}
1-\epsilon & \frac{\epsilon}{n-1} & \ldots & \frac{\epsilon}{n-1} & \frac{\epsilon}{n-1} \\
\frac{\epsilon}{n-1} & 1-\epsilon & \frac{\epsilon}{n-1} & \ldots & \frac{\epsilon}{n-1} \\
\vdots & & \ddots & & \vdots \\
\frac{\epsilon}{n-1} & \ldots & \frac{\epsilon}{n-1} & 1-\epsilon & \frac{\epsilon}{n-1} \\
\frac{\epsilon}{n-1} & \frac{\epsilon}{n-1} & \ldots & \frac{\epsilon}{n-1} & 1-\epsilon
\end{bmatrix}.
$$

B   NETWORK STRUCTURES

For MNIST, 32×32 gray image, the structure is as follows. We also summarize it into Table 2.

(1*28*28)-[C(3*3,128)]*2-maxpool(2*2,2)-dropout(0.25)-[C(3*3,256)]*3-maxpool(2*2,2)-dropout(0.25)-C(3*3,512)-C(3*3,256)-C(3*3,128)-avgpool(1*1)-128-10, where the input is a 28*28 image, C(3*3,128) means 128 channels of 3*3 convolutions followed by LReLU (negative slop=0.01), maxpool(2*2,2) means max pooling (kernel size=2, stride=2), avgpool(2*2) means average pooling (kernel size=2), [.]*n means n such layers, etc. Batch normalization was applied before LReLU activations.

Table 2: 9-layer CNN used in our experiments on *MNIST*.

CNN on MNIST
28×28 Gray Image
3×3 conv, 128 LReLU
3×3 conv, 128 LReLU
3×3 conv, 128 LReLU
2×2 max-pool, stride 2
dropout, $p = 0.25$
3×3 conv, 256 LReLU
3×3 conv, 256 LReLU
3×3 conv, 256 LReLU
2×2 max-pool, stride 2
dropout, $p = 0.25$
3×3 conv, 512 LReLU
3×3 conv, 256 LReLU
3×3 conv, 128 LReLU
avg-pool
dense $128 \rightarrow 10$

For CIFAR10, 32×32 RGB image, the structure is ResNet-32.