Transferring Knowledge across Learning Processes

Abstract

In complex transfer learning scenarios new tasks might not be tightly linked to previous tasks. Approaches that transfer information contained only in the final parameters of a source model will therefore struggle. Instead, transfer learning at a higher level of abstraction is needed. We propose Leap, a framework that achieves this by transferring knowledge across learning processes. We associate each task with a manifold on which the training process travels from initialization to final parameters and construct a meta learning objective that minimizes the expected length of this path. Our framework leverages only information obtained during training and can be computed on the fly at negligible cost. We demonstrate that our framework outperforms competing methods, both in meta learning and transfer learning, on a set of computer vision tasks. Finally, we demonstrate that Leap can transfer knowledge across learning processes in demanding Reinforcement learning environments (Atari) that involve millions of gradient steps.

1 Introduction

Transfer learning is the process of transferring knowledge encoded in one model trained on one set of tasks to another model that is applied to a new task. Since a trained model encodes information in its learned parameters, transfer learning typically transfers knowledge by encouraging the target model's parameters to resemble those of a previous (set of) model(s) (Pan & Yang, 2009). This approach limits transfer learning to settings where good parameters for a new task can be found in the neighborhood of parameters that were learned from a previous task. For this to be a viable assumption, the two tasks must have a high degree of structural affinity, such as when a new task can be learned by extracting features from a pre-trained model (Girshick et al., 2014; He et al., 2017; Mahajan et al., 2018). If not, this approach has been observed to limit knowledge transfer since the training process on one task will discard information that was irrelevant for the task at hand, but that would be relevant for another task (Higgins et al., 2017; Achille et al., 2018).

In this paper we argue that such information can be harnessed, even when the downstream task is unknown, by transferring knowledge of the learning process itself. In particular, we propose a meta learning framework for aggregating information across task geometries as they are observed during training. These geometries, formalized as the loss surface over the training data, encode all information seen during training and therefore avoid catastrophic loss of information. Moreover, by transferring knowledge across learning processes, information from previous tasks is distilled to explicitly facilitate the learning of a new task.

Meta learning frames the learning of a new task as a learning problem itself, typically in the few-shot learning paradigm (Lake et al., 2011; Santoro et al., 2016; Vinyals et al., 2016). In this environment, learning is a problem of rapid adaptation and can be solved by training a meta learner by backpropagating through the entire training process (Ravi & Larochelle, 2016; Andrychowicz et al., 2016; Finn et al., 2017). For more demanding tasks, formulating the meta learning in this manner is challenging; backpropagating through thousands of gradient steps is both impractical and susceptible to instability. We argue that as the training process grows longer in terms of the distance traversed on the loss landscape, the geometry of this landscape grows increasingly important. When adapting to a new task through a single or a handful of gradient steps, the geometry can largely be ignored. In contrast, with more gradient steps, it is the dominant feature of the training process.

Figure 1: Example of gradient paths on a manifold described by the loss surface. Leap learns an initialization with shorter expected gradient path that improves performance.

To scale meta learning beyond few-shot learning, we propose *Leap*, a light-weight framework for meta learning over task manifolds that does not need any forward- or backward-passes beyond those already performed by the underlying training process. We demonstrate empirically that Leap is a superior method to similar meta and transfer learning methods when learning a task requires more than a handful of training steps. Finally, we evaluate Leap in a Reinforcement Learning environment (Atari 2600; Bellemare et al., 2013), demonstrating that it can transfer knowledge across learning processes that require millions of gradient steps to converge.

2 TRANSFERRING KNOWLEDGE OVER LEARNING PROCESSES

We start in section 2.1 by introducing the gradient descent algorithm from a geometric perspective. Section 2.2 builds a framework for transfer learning and explains how we can leverage geometrical quantities to transfer knowledge across learning processes by guiding gradient descent. We focus on the point of initialization for simplicity, but our framework can readily be extended. Section 2.3 presents Leap, our lightweight algorithm for transfer learning across learning processes.

2.1 GRADIENT PATHS ON TASK MANIFOLDS

Central to our framework is the notion of a learning process; the harder a task is to learn, the harder it is for the learning process to navigate on the loss surface (fig. 1). Our framework is based on the idea that transfer learning can be achieved by leveraging information contained in similar learning processes. Exploiting that this information is encoded in the geometry of the loss surface, we leverage geometrical quantities to facilitate the learning process with respect to new tasks. We focus on the supervised learning setting for simplicity, though our framework applies more generally. Given a learning objective f that consumes an input $x \in \mathbb{R}^m$ and a target $y \in \mathbb{R}^c$ and maps a parameterization $\theta \in \mathbb{R}^n$ to a scalar loss value, we have the gradient descent update as

$$\theta^{i+1} = \theta^i - \alpha^i S^i \nabla f(\theta^i), \tag{1}$$

where $\nabla f(\theta^i) = \mathbb{E}_{x,y \sim p(x,y)}\big[\nabla f(\theta^i, x, y)\big]$. We take the learning rate schedule $\{\alpha^i\}_i$ and preconditioning matrices $\{S^i\}_i$ as given, but our framework can be extend to learn these jointly with the initialization. Differences schemes represent different optimizers; for instance, $\alpha^i = \alpha$, $S^i = I_n$ yields gradient descent, while defining S^i as the inverse Fisher matrix results in natural gradient descent (Amari, 1998). We assume this process converges to a stationary point after K gradient steps.

To distinguish different learning processes originating from the same initialization, we need a notion of their length. The longer the process, the worse the initialization is (conditional on reaching equivalent performance, discussed further below). Measuring the Euclidean distance between initialization and final parameters is misleading as it ignores the actual path taken. This becomes crucial when we compare paths from different tasks, as gradient paths from different tasks can originate from the same initialization and converge to similar final parameters, but take very different paths. Therefore, to capture the length of a learning process we must associate it with the loss surface it traversed.

The process of learning a task can be seen as a curve on a specific task manifold M. While this manifold can be constructed in a variety of ways, here we exploit that, by definition, any learning process traverses the loss surface of f. As such, to accurately describe the length of a gradient-based learning process, it is sufficient to define the task manifold as the loss surface. In particular, because the learning process in eq. 1 follows the gradient trajectory, it constantly provides information about the geometry of the loss surface. Gradients that largely point in the same direction indicate a well-behaved loss surface, whereas gradients with frequently opposing directions indicate an ill-conditioned loss surface, something we would like to avoid. Leveraging this insight, we propose a framework for transfer learning that exploits the accumulation of geometric information by constructing a meta objective that minimizes the expected length of the gradient descent path *across tasks*. In doing so, the meta objective intrinsically balances local geometries across tasks and encourages an initialization that makes the learning process as short as possible.

To formalize the notion of the distance of a learning process, we define a task manifold M as a submanifold of $\mathbb{R}^{n+1}$ given by the graph of f. Every point $p = (\theta, f(\theta)) \in M$ is locally homeomorphic to a Euclidean subspace, described by the tangent space $T_p M$. Taking $\mathbb{R}^{n+1}$ to be Euclidean, it is a Riemann manifold. By virtue of being a submanifold of $\mathbb{R}^{n+1}$, M is also a Riemann manifold. This is important because a Riemann manifold comes equipped with an smoothly varying inner product $g_p : T_p M \times T_p M \mapsto \mathbb{R}$ on tangent spaces, allowing us to measure the length of a path on M. In particular, the length (or energy) of any *curve* $\gamma : [0, 1] \mapsto M$ is defined by accumulating infinitesimal changes along the trajectory,

$$\text{Length}(\gamma) = \int_0^1 \sqrt{g_{\gamma(t)}(\dot{\gamma}(t), \dot{\gamma}(t))} \, dt, \qquad \text{Energy}(\gamma) = \int_0^1 g_{\gamma(t)}(\dot{\gamma}(t), \dot{\gamma}(t)) \, dt, \qquad (2)$$

where $\dot{\gamma}(t) = \frac{d}{dt}\gamma(t) \in T_{\gamma(t)}M$ is a tangent vector of $\gamma(t) = (\theta(t), f(\theta(t))) \in M$. We use parenthesis (i.e. $\gamma(t)$) to differentiate discrete and continuous domains. With M being a submanifold of $\mathbb{R}^{n+1}$, it inherits its metric via pullback, with induced metric $g_{\gamma(t)}(\dot{\gamma}(t), \dot{\gamma}(t)) = \langle \dot{\gamma}(t), \dot{\gamma}(t) \rangle$. Different Riemann metrics yield different manifold structures. In particular, if the model underlying f admits a predictive probability distribution $P(y \mid x)$, the task manifold can be given an information geometric interpretation by choosing the Fisher matrix as Riemann metric, in which case the task manifold is defined over the space of probability distributions (Amari & Nagaoka, 2007). If eq. 1 is defined as natural gradient descent, the learning process corresponds to gradient descent on this manifold (Amari, 1998; Martens, 2010; Pascanu & Bengio, 2014; Luk & Grosse, 2018).

Having a complete description of a task manifold, we can measure the length of a learning process by noting gradient descent can be seen as a discrete approximation to the scaled gradient flow $\dot{\theta}(t) = -S(t)\nabla f(\theta(t))$. This flow describes a curve that originates in $\gamma(0) = (\theta^0, f(\theta^0))$ and follows the gradient at each point. Going forward, we define γ to be this unique curve and refer to it as the *gradient path* from θ^0 on M. The gradient path length or energy can be computed exactly, but in practice we observe a discrete learning process. Analogously to how the gradient update rule approximates the gradient flow, the gradient path length or energy can be approximated by the cumulative chordal distance (Ahlberg et al., 1967),

$$d_p(\theta^0) = \sum_{i=0}^{K-1} \|\gamma^{i+1} - \gamma^i\|_2^p, \qquad p \in \{1, 2\}. \qquad (3)$$

We write d when the distinction between the length or energy metric is immaterial. Using the energy yields a slightly simpler objective, but the length normalizes each length segment and as such protects against differences in scale between task objectives. In appendix C, we carry out an ablation study and find that they perform similarly, though using the length leads to faster convergence. Importantly, d involves only terms seen during task training. We exploit this later when we construct the meta gradient, enabling us to perform gradient descent on the meta objective at negligible cost (eq. 8).

We now turn to the transfer learning setting, where we face a set of tasks, each with a distinct task manifold. Our framework is built on the idea that we can transfer knowledge across learning processes via the local geometry by aggregating information obtained along observed gradient paths. As such, Leap finds an initialization from which learning converges as rapidly as possible in expectation.

Figure 2: *Left:* illustration of Leap (algorithm 1) for two tasks, τ and τ'. From an initialization θ^0, the learning process of each task generates gradient paths, Ψ_τ and $\Psi_{\tau'}$, which Leap uses to minimize the expected path length. Iterating the process, Leap converges on an locally Pareto optimal initialization. *Right:* the pull-forward objective (eq. 6) used to minimize the expected gradient path length. Any gradient path $\Psi_\tau = \{\psi_\tau^i\}_{i=1}^{K_\tau}$ acts on θ^0 by pulling each θ_τ^i towards ψ_τ^{i+1}.

2.2 META LEARNING ACROSS TASK MANIFOLDS

Formally, we define a task $\tau = (f_\tau, p_\tau, u_\tau)$ as the process of learning to approximate the relationship $x \mapsto y$ through samples from the data distribution $p_\tau(x, y)$. This process is defined by the gradient update rule u_τ (as defined in eq. 1), applied K_τ times to minimize the task objective f_τ. Thus, a learning process starts at $\theta_\tau^0 = \theta^0$ and progress via $\theta_\tau^{i+1} = u_\tau(\theta_\tau^i)$ until $\theta_\tau^{K_\tau}$ is obtained. The sequence $\{\theta_\tau^i\}_{i=0}^{K_\tau}$ defines an approximate gradient path on the task manifold M_τ with distance $d(\theta^0; M_\tau)$.

To understand how d transfers knowledge across learning processes, consider two distinct tasks. We can transfer knowledge across these tasks' learning processes by measuring how good a shared initialization is. Assuming two candidate initializations converge to limit points with equivalent performance on each task, the initialization with shortest distance encodes more knowledge sharing. In particular, if both tasks have convex loss surfaces there is a unique optimal initialization that achieves Pareto optimality in terms of total path distance. This can be crucial for tasks with limited data: rapid convergence may be the difference between learning a task and failing due to overfitting (Finn et al., 2017).

Given a distribution of tasks $p(\tau)$, each candidate initialization θ^0 is associated with a measure of its expected gradient path distance, $\mathbb{E}_{\tau \sim p(\tau)}\big[d(\theta^0; M_\tau)\big]$, that summarizes the suitability of the initialization to the task distribution. The initialization (or a set thereof) with shortest expected gradient path distance maximally transfers knowledge across learning processes and is Pareto optimal in this regard. Above, we have assumed that all candidate initializations converge to limit points of equal performance. If the task objective f_τ is non-convex this is not a trivial assumption and the gradient path distance itself does not differentiate between different levels of final performance.

As such, it is necessary to introduce a feasibility constraint to ensure only initializations with some minimum level of performance are considered. We leverage that transfer learning never happens in a vacuum; we always have a second-best option, such as starting from a random initialization or a pre-trained model. Starting from this "second-best" initialization, ψ^0, gives us the level of performance we would obtain on each task in the absence of transferring knowledge across learning processes. As such, performance obtained by initializing from ψ^0 provides us with an upper bound for each task: a candidate solution θ^0 has to yield at least as good performance on any task in $p(\tau)$ to be a viable solution. Formally, this implies the task-specific requirement that a candidate θ^0 must satisfy $f_\tau(\theta_\tau^{K_\tau}) \leq f_\tau(\psi_\tau^{K_\tau})$. As this must hold for every task, we obtain the canonical meta objective

$$
\begin{aligned}
\min_{\theta^0} \quad & F(\theta^0) = \mathbb{E}_{\tau \sim p(\tau)}\big[d(\theta^0; M_\tau)\big] \\
\text{s.t.} \quad & \theta_\tau^{i+1} = u_\tau(\theta_\tau^i), \quad \theta_\tau^0 = \theta^0, \\
& \theta^0 \in \Theta = \cap_\tau \big\{\theta^0 \,\big|\, f_\tau(\theta_\tau^{K_\tau}) \leq f_\tau(\psi_\tau^{K_\tau})\big\}.
\end{aligned}
\tag{4}
$$

Algorithm 1 Leap: Transferring Knowledge over Learning Processes

---

Require: $p(\tau)$, $\tau = (f_\tau, u_\tau, p_\tau)$: distribution over tasks
Require: β: step size
 1: randomly initialize θ^0
 2: **while** not done **do**
 3:    $\nabla \bar{F} \leftarrow 0$: initialize meta gradient
 4:    sample task batch $\mathcal{B}$ from $p(\tau)$
 5:    **for all** $\tau \in \mathcal{B}$ **do**
 6:       $\psi_\tau^0 \leftarrow \theta^0$: initialize task baseline
 7:       **for all** $i \in \{0, \ldots, K_\tau - 1\}$ **do**
 8:          $\psi_\tau^{i+1} \leftarrow u_\tau(\psi_\tau^i)$: update baseline
 9:          $\theta_\tau^i \leftarrow \psi_\tau^i$: follow baseline (recall $\psi_\tau^0 = \theta^0$)
10:          increment $\nabla \bar{F}$ using the pull-forward gradient (eq. 8)
11:       **end for**
12:    **end for**
13:    $\theta^0 \leftarrow \theta^0 - \frac{\beta}{|\mathcal{B}|} \nabla \bar{F}$: update initialization
14: **end while**

This meta objective is robust to variations in the geometry of loss surfaces, as it balances complementary and competing learning processes (fig. 2). For instance, there may be an initialization that can solve a small subset of tasks in a handful of gradient steps, but would be catastrophic for other related tasks. When transferring knowledge via the initialization, we must trade off commonalities and differences between gradient paths. In eq. 4 these trade-offs arise naturally. For instance, as the number of tasks whose gradient paths move in the same direction increases, so does their pull on the initialization. Conversely, as the updates to the initialization renders some gradient paths longer, these act as springs that exert increasingly strong pressure on the initialization. The solution to eq. 4 thus achieves an equilibrium between these competing forces.

Solving eq. 4 naively requires training to convergence on each task to determine whether an initialization satisfies the feasibility constraint, which can be very costly. Fortunately, because we have access to a second-best initialization, we can solve eq. 4 more efficiently by obtaining gradient paths from ψ^0 and use these as baselines that we incrementally improve upon. This improved initialization converges to the same limit points, but with shorter expected gradient path distances (theorem 1). As such, it becomes the new second-best option; Leap (algorithm 1) repeats this process of improving upon increasingly demanding baselines, ultimately finding a solution to the canonical meta objective.

2.3 LEAP

Leap starts from a given second-best initialization ψ^0, shared across all tasks, and construct baseline gradient paths $\Psi_\tau = \{\psi_\tau^i\}_{i=0}^{K_\tau}$ for each task τ in a batch $\mathcal{B}$. These provide a set of baselines $\Psi = \{\Psi_\tau\}_{\tau \in \mathcal{B}}$; recall that all tasks share the same initialization, $\psi_\tau^0 = \psi^0 \in \Theta$. We use these baselines, corresponding to task-specific learning processes, to modify the gradient path distance metric in eq. 3 by freezing the forward point γ_τ^{i+1} in all norms,

$$\bar{d}_p(\theta^0; M_\tau, \Psi_\tau) = \sum_{i=0}^{K_\tau - 1} \|\bar{\gamma}_\tau^{i+1} - \gamma^i\|_2^p, \tag{5}$$

where $\bar{\gamma}_\tau^i = (\psi_\tau^i, f(\psi_\tau^i))$ represents the frozen forward point from the baseline and $\gamma_\tau^i = (\theta_\tau^i, f(\theta_\tau^i))$ the point on the gradient path originating from θ^0. This surrogate distance metric directly encodes the feasibility constraint; optimizing θ^0 with respect to Ψ therefore pulls the initialization forward along each task-specific gradient path in an unconstrained variant of eq. 4 that replaces Θ with Ψ,

$$\min_{\theta^0} \quad \bar{F}(\theta^0; \Psi) = \mathbb{E}_{\tau \sim p(\tau)}\left[\bar{d}(\theta^0; M_\tau, \Psi_\tau)\right], \tag{6}$$
$$\text{s.t.} \qquad \theta_\tau^{i+1} = u_\tau(\theta_\tau^i), \quad \theta_\tau^0 = \theta^0.$$

We refer to eq. 6 as the *pull-forward* objective. Incrementally improving θ^0 over ψ^0 leads to a new second-best option that Leap uses to generate a new set of more demanding baselines, to further improve the initialization. Iterating this process, Leap produces a sequence of candidate solutions to eq. 4, all in Θ, with incrementally shorter gradient paths. In theorem 1, we show that the limit point of this sequence lies in Θ, and as such is equivalent to performing gradient descent directly on the canonical meta objective (eq. 4). In principle, $\bar{F}$ can be evaluated for any θ^0, but a more efficient strategy is to evaluate θ^0 at ψ^0. In this case, $\bar{d} = d$, so that $\bar{F} = F$, and gradient descent on $\bar{F}$ is equivalent to gradient descent on F.

Theorem 1 (Pull-forward). *Define a sequence of initializations $\{\psi_s^0\}_{s \in \mathbb{N}}$ by*

$$\psi_{s+1}^0 = \psi_s^0 - \beta_s \nabla \bar{F}(\psi_s^0; \Psi_s), \qquad \psi_0^0 \in \Theta. \tag{7}$$

For $\beta_s > 0$ sufficiently small, there exist learning rates schedules $\{\alpha_\tau^i\}_{i=1}^{K_\tau}$ for all tasks such that $\psi_{k \to \infty}^0$ is a limit point in Θ.

Proof; see appendix A. While the pull-forward objective can be solved with any optimization algorithm, we consider gradient-based methods. Because the meta gradient requires differentiating the learning process, we must adopt an approximation. In doing so, we obtain a meta-gradient that can be computed analytically on the fly during task training. Differentiating $\bar{F}$, we have

$$\nabla \bar{F}(\theta^0, \Psi) = 2 \, \mathbb{E}_{\tau \sim p(\tau)} \left[\sum_{i=0}^{K_\tau - 1} J_\tau^i(\theta_\tau^0)^T \left(|\Delta f_\tau^i| \, \nabla f_\tau(\theta_\tau^i) - \Delta \theta_\tau^i \right) \left(\|\bar{\gamma}_\tau^i - \gamma_\tau^i\|_2^p \right)^{p-2} \right] \tag{8}$$

where J_τ^i denotes the Jacobian of θ_τ^i with respect to the initialization, $\Delta f_\tau^i = f_\tau(\psi_\tau^{i+1}) - f_\tau(\theta_\tau^i)$ and $\Delta \theta_\tau^i = \psi_\tau^{i+1} - \theta_\tau^i$. To render the meta gradient tractable, we need to approximate the Jacobians, as these are extremely costly to compute. Empirical evidence suggest that they are largely redundant (Finn et al., 2017; Nichol et al., 2018). Nichol et al. (2018) further shows that the resulting meta-gradient remains faithful to the original meta objective. We provide some further support for this approximation (see appendix B). First, we note that the learning rate directly controls the quality of the approximation; for any K_τ, the identity approximation can be made arbitrarily accurate by choosing a sufficiently small learning rate scheme. We conduct an ablation study to ascertain how severe this limitation is and find that it is relatively loose. For the best-performing learning rate, the identity approximation is accurate to four decimal places and shows no signs of significant deterioration as the number of training steps increases. As such, we assume $J^i \approx I_n$ throughout. Finally, by evaluating $\nabla \bar{F}$ at $\theta^0 = \psi^0$, the meta gradient contains only terms seen during standard training and can be computed on asynchronously on the fly at negligible cost.

In practice we use stochastic gradient descent during task training. This injects noise in f as well as in its gradient, resulting in a noisy gradient path. Noise in the gradient path does not prevent Leap from converging, as long as the gradient path converges. However, noise reduces the rate of convergence, in particular when a noisy gradient step results in $f_\tau(\psi_\tau^{s+1}) - f_\tau(\theta_\tau^i) > 0$. This can either be the result of a poor estimate of the true gradient, or because of too large a step size. In either case, we found that de-prioritizing such line segments significantly speeds up convergence, as well as allows the use of larger learning rates. In this paper, we augment $\bar{F}$ with a stabilizer of the form

$$\mu\left(f_\tau(\psi_\tau^{i+1}), f_\tau(\theta_\tau^i)\right) = \begin{cases} 0 & \text{if} \quad f_\tau(\psi_\tau^{i+1}) \leq f_\tau(\theta_\tau^i), \\ -2(f_\tau(\psi_\tau^{i+1}) - f_\tau(\theta_\tau^i))^2 & \text{else.} \end{cases}$$

The stabilizer points in the opposite direction of the gradient, and as such reduces the weight placed on the gradient of $f_\tau(\theta_\tau^i)$. This counteracts both poor estimates and overly large step sizes. In appendix C we perform an ablation study and find that the stabilizer is not necessary for Leap to converge, but it does speed up convergence significantly.

3   RELATED WORK

Transfer learning has been explored in a variety of settings, the most typical approach attempting to infuse knowledge in a target model's parameters by encouraging them to lie close to those of a pretrained source model (Pan & Yang, 2009). Because such approaches can limit knowledge transfer (Higgins et al., 2017; Achille et al., 2018), applying standard transfer learning techniques leads to *catastrophic forgetting*, by which the model is rendered unable to perform a previously mastered task (McCloskey & Cohen, 1989; Goodfellow et al., 2013). These problems are further accentuated when there is a larger degree of diversity among tasks that push optimal parameterizations further apart. In these cases, transfer learning can in fact be worse than training from scratch.

Recent approaches extend standard finetuning by adding regularizing terms to the training objective that encourage the model to learn parameters that both solve a new task and retain high performance on previous tasks. These regularizers operate by protecting the parameters that affect the loss function the most (Miconi et al., 2018; Zenke et al., 2017; Kirkpatrick et al., 2017; Lee et al., 2017; Serrà et al., 2018). Because these approaches use a single model to encode both global task-general information and local task-specific information, they can over-regularize, preventing the model from learning further tasks. More importantly, Schwarz et al. (2018) found that while these approaches mitigate catastrophic forgetting, they are unable to facilitate knowledge transfer on the benchmark they considered. Ultimately, if a single model must encode both task-generic and task-specific information, it must either saturate or grow in size (Rusu et al., 2016).

In contrast, meta learning aims to learn the learning process itself (Schmidhuber, 1987; Bengio et al., 1991; Santoro et al., 2016; Ravi & Larochelle, 2016; Andrychowicz et al., 2016; Vinyals et al., 2016; Finn et al., 2017). Most of the literature focuses on the few-shot learning setting, where a task is some variation on a common theme, such as subsets of classes from a larger pool of data (Lake et al., 2015; Vinyals et al., 2016). The meta learning algorithm adapts a model to a new task given a handful of samples. Recent attention has been devoted to three main approaches. One trains the meta learner to adapt to a new task by comparing an input to samples from previous tasks (Vinyals et al., 2016; Mishra et al., 2018; Snell et al., 2017). More relevant to our framework are approaches that parameterize the training process through a recurrent neural network that takes the gradient as input and produces a new set of parameters (Ravi & Larochelle, 2016; Santoro et al., 2016; Andrychowicz et al., 2016; Hochreiter et al., 2001). The approach most closely related to us learns an initialization such that the model can adapt to a new task through one or a few gradient updates (Finn et al., 2017; Nichol et al., 2018; Al-Shedivat et al., 2017; Lee & Choi, 2018). In contrast to our work, these methods focus exclusively on few-shot learning, where the gradient path is trivial as only a single or a handful of training steps are allowed, limiting them to settings where the current task is closely related to previous ones.

It is worth noting that the Model Agnostic Meta Learner (MAML: Finn et al., 2017) can be written as $\mathbb{E}_{\tau \sim p(\tau)}\big[f_\tau(\theta_\tau^K)\big]$.[1] As such it arises as a special case of Leap where only the final parameterization is evaluated in terms of its final performance. Similarly, the Reptile algorithm (Nichol et al., 2018), which proposes to update rule $\theta^0 \leftarrow \theta^0 + \epsilon\left(\mathbb{E}_{\tau \sim p(\tau)}\big[\theta_\tau^K\big] - \theta^0\right)$, can be seen as a naive version of Leap that assumes all task geometries are Euclidean. In particular, Leap reduces to Reptile if f_τ is removed from the task manifold and the energy metric without stabilizer is used. We find this configuration to perform significantly worse than any other (section 4.1, appendix C).

Related work studying models from a geometric perspective have explored how to interpolate in a generative model's learned latent space Tosi et al. (2014); Shao et al. (2017); Arvanitidis et al. (2018); Chen et al. (2018); Kumar et al. (2017). Riemann manifolds have also garnered attention in the context of optimization, as a preconditioning matrix can be understood as the instantiation of some Riemann metric (Amari & Nagaoka, 2007; Abbati et al., 2018; Luk & Grosse, 2018).

4   EMPIRICAL RESULTS

We consider three experiments designed to provide increasingly complex transfer learning environments. We measure transfer learning in terms of final test error and *area under the error curve*, defined as the error score on the training set during training. We compare Leap to competing meta

---

[1]MAML differs from Leap in that it evaluates the meta objective on a held-out test set.

Figure 3: Transfer learning on Omniglot. *Left:* Evolution of training curves during meta training of Leap. Blue signifies beginning of training, red end of training. *Right:* AUC under error curve across number of pretraining tasks. Shading: two standard deviations across 10 seeds. *Author's suggested first-order approximation; †multi-headed finetuning.

learning methods on the Omniglot dataset by tasking the meta learning with transferring knowledge across alphabets (section 4.1). Further, we study Leap's ability to transfer knowledge over more complex and diverse tasks in the Multi-CV experiment (section 4.2). Finally, we evaluate Leap on a more demanding reinforcement learning problem, demonstrating its ability to scale (section 4.3).

4.1 OMNIGLOT

The Omniglot (Lake et al., 2015) dataset consists of 50 alphabets, which we define to be a distinct task. We hold 10 out for validation during meta training, and 10 for final evaluation. We use a subset of the remaining 30 for pretraining. We compare final performance and the rate of convergence on held-out tasks as we vary the number of pretraining tasks from 1 to 30. As baselines, we compare against no pretraining, finetuning in multi-headed mode, the first-order approximation version of MAML (FOMAML; Finn et al., 2017), and Reptile. We find that the length metric (d_2) performs marginally better, and as such we report scores for Leap under the length metric. We perform an ablation study across configurations in appendix C. For further details, appendix D.

Leap consistently outperforms both multi-headed finetuning, FOMAML and Reptile (fig. 3). The gap between Leap and other meta learning frameworks is large and Leap is in fact the only meta learner to outperform finetuning. That Leap does better than Reptile, which in turn does better than FOMAML, underscores the importance of leveraging the task geometry in meta learning. Multi-task finetuning is a tough benchmark to beat as tasks are very similar. It is striking that Leap can outperform it even with a single pretraining task, and perhaps more so that the performance margin grows with the number of pretraining tasks.

4.2 MULTI-CV

Inspired by Serrà et al. (2018), we consider a set of computer vision datasets as distinct tasks. We pretrain on all but one task, which is held out for final evaluation. For details, see appendix E. To reduce the computational burden during meta training, we pretrain on each task in the meta batch for ten epochs using the energy metric (d_1). We found this to reach equivalent performance to training on longer gradient paths or using the length metric. This indicates that it is sufficient for Leap to see a partial trajectory to correctly infer shared structures across task geometries.

We compare Leap against a random initialization, multi-headed finetuning, a non-sequential version of HAT (Serrà et al., 2018) (i.e. allowing revisits) and a non-sequential version of Progressive Nets (Rusu et al., 2016), where we allow lateral connection between every task. Note that this makes Progressive Nets over 8 times larger in terms of learnable parameters.

The Multi-CV experiment is more challenging both due to greater task diversity and greater complexity among tasks. We report results on held-out tasks in table 1. Leap outperforms all baselines on all but one transfer learning tasks (Facescrub), where Progressive Nets does marginally better than a random initialization owing to its increased parameter count. Notably, while Leap does marginally worse than a random initialization, finetuning and HAT leads to a substantial drop in performance. On all other tasks, Leap converges faster to optimal performance and achieves superior final performance.

Table 1: Results on Multi-CV benchmark. All methods are trained until convergence on held-out tasks. Fine-tuning is multiheaded. [†] Area under training error curve; scaled to 0–100.[‡]Our implementation. MNIST results omitted; see appendix E, table 3.

Held-out task	Method	Test (%)	Train (%)	AUC[†]
Facescrub	Leap	19.9	0.0	11.6
	Fine-tuning	32.7	0.0	13.2
	Progressive Nets[‡]	**18.0**	0.0	8.9
	HAT[‡]	25.6	0.1	14.6
	No pre-training	18.2	0.0	**10.5**
Cifar10	Leap	**21.2**	**10.8**	**17.5**
	Fine-tuning	27.4	13.3	20.7
	Progressive Nets[‡]	24.2	15.2	24.0
	HAT[‡]	27.7	21.2	27.3
	No pre-training	26.2	13.1	23.0
SVHN	Leap	**8.4**	**5.6**	**7.5**
	Fine-tuning	10.9	6.1	10.5
	Progressive Nets[‡]	10.1	6.3	13.8
	HAT[‡]	10.5	5.7	8.5
	No pre-training	10.3	6.9	11.5
Cifar100	Leap	**52.0**	**30.5**	**43.4**
	Fine-tuning	59.2	31.5	44.1
	Progressive Nets[‡]	55.7	42.1	54.6
	HAT[‡]	62.0	49.8	58.4
	No pre-training	54.8	33.1	50.1
Traffic Signs	Leap	**2.9**	0.0	**1.2**
	Fine-tuning	5.7	0.0	1.7
	Progressive Nets[‡]	3.6	0.0	4.0
	HAT[‡]	5.4	0.0	2.3
	No pre-training	3.6	0.0	2.4

4.3 ATARI

To demonstrate that Leap can scale to large problems, both in computational terms but also in the complexity of tasks, we apply it in a reinforcement learning domain, specifically Atari 2600 games (Bellemare et al., 2013). We use a variant of the actor-critic architecture for all experiments (Sutton et al., 1998). We learn both the policy π and the value function V from raw pixels, with π and V sharing a convolutional encoder (Schwarz et al., 2018). We apply Leap with respect to this convolutional encoder, using the energy metric (d_1). During meta training, we sample mini-batches from 27 games that has an action space dimensionality of at most 10, holding out two games with similar action space dimensionality for evaluation, as well as games with larger action spaces (table 4). During meta training, we train on each task in the mini-batch for five million training steps, accumulating the meta gradient as in algorithm 1. See appendix F for details.

We train for 100 meta training steps, which is sufficient to see a distinct improvement with respect to the initialization; we expect a longer meta-training phase to yield further gains. We find that Leap generally outperforms a random initialization, and in all but one case at least performs on par with it. This performance gain is primarily driven by less volatile exploration, as seen by the confidence intervals in fig. 4 (see also fig. 8). Leap finds a useful exploration space faster and more consistently, demonstrating that Leap can find shared structures across learning processes on as diverse and complex tasks as training a deep actor-critic model on Atari games. However, we also note that this regularity may not cater equally to all tasks, as the result on WizardOfWor (part of the pre-training set) shows. In this outlying case, Leap exhibits two modes: in one it performs on par

Figure 4: Mean normalized episode returns on Atari games across training steps. Scores are reported as moving average over 500 episodes. Shaded regions depict two standard deviations across ten seeds. Leap (orange) generally outperforms a random initialization (blue), even when the action space is twice as large as during pretraining (table 4, appendix F).

with a random initialization while exhibiting less variance across runs; it takes considerably longer to find a useful exploration space (fig. 8). This outlier stems from the fact that in deep Reinforcement Learning, starting from the same initialization can yield very different gradient paths under different random seeds. As such, it can be mitigated by increasing Leap's exposure to the task; that is, by training for a greater number of steps.

That Leap can outperform a random initialization on the pretraining set (AirRaid, UpNDown) is perhaps not surprising. More striking is that it exhibits the same patters on out-of-distribution tasks. In particular, Alien, Gravitar and RoadRunner all have at least 50% larger state space than anything encountered during pretraining, yet Leap outperforms a random initialization. This suggests that transferring knowledge at a higher level of abstraction, such as in the space of gradient paths, generalizes to unseen task variations provided the underlying learning dynamics are similar.

5   CONCLUSIONS

Transfer learning typically ignores the process of learning a task, restricting it to scenarios where target tasks are very similar to source tasks. In this paper, we present Leap, a framework that facilitates transfer learning at a higher level of abstraction. By formalizing transfer learning as minimizing the expected gradient path over task-specific loss surfaces, we propose a method for meta learning that scales to highly demanding problems. We find empirically that Leap has superior generalizing properties to finetuning and competing methods. Moreover, by virtue of transferring knowledge across learning processes, it is robust to non-trivial diversity in task distributions.

REFERENCES

Gabriele Abbati, Alessandra Tosi, Michael Osborne, and Seth Flaxman. Adageo: Adaptive geometric learning for optimization and sampling. In *International Conference on Artificial Intelligence and Statistics*, pp. 226–234, 2018.

Alessandro Achille, Tom Eccles, Loic Matthey, Christopher P. Burgess, Nick Watters, Alexander Lerchner, and Irina Higgins. Life-long disentangled representation learning with cross-domain latent homologies. *arXiv preprint arXiv:1808.06508*, 2018.

J Harold Ahlberg, Edwin Norman Nilson, and Joseph Leonard Walsh. *The Theory of Splines and Their Applications*. Academic Press, 1967. p. 51.

Maruan Al-Shedivat, Trapit Bansal, Yuri Burda, Ilya Sutskever, Igor Mordatch, and Pieter Abbeel. Continuous Adaptation via Meta-Learning in Nonstationary and Competitive Environments. In *International Conference on Learning Representations*, 2017.

Shun-Ichi Amari. Natural gradient works efficiently in learning. *Neural computation*, 10(2):251–276, 1998.

Shun-ichi Amari and Hiroshi Nagaoka. *Methods of information geometry*, volume 191. American Mathematical Society, 2007.

Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. In *Advances in Neural Information Processing Systems*, 2016.

Georgios Arvanitidis, Lars Kai Hansen, and Søren Hauberg. Latent Space Oddity: on the Curvature of Deep Generative Models. In *International Conference on Learning Representations*, 2018.

M. G. Bellemare, Y. Naddaf, J. Veness, and M. Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, 2013.

Yoshua Bengio, Samy Bengio, and Jocelyn Cloutier. *Learning a synaptic learning rule*. Université de Montréal, Département d'informatique et de recherche opérationnelle, 1991.

Nutan Chen, Alexej Klushyn, Richard Kurle, Xueyan Jiang, Justin Bayer, and Patrick van der Smagt. Metrics for Deep Generative Models. In *International Conference on Artificial Intelligence and Statistics*, 2018.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-Agnostic Meta-Learning for Fast Adaptation of Deep Networks. In *International Conference on Machine Learning*, 2017.

Ross Girshick, Jeff Donahue, Trevor Darrell, and Jitendra Malik. Rich feature hierarchies for accurate object detection and semantic segmentation. In *International Conference on Computer Vision and Pattern Recognition*, pp. 580–587, 2014.

Ian J Goodfellow, Mehdi Mirza, Da Xiao, Aaron Courville, and Yoshua Bengio. An empirical investigation of catastrophic forgetting in gradient-based neural networks. *arXiv preprint arXiv:1312.6211*, 2013.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *International Conference on Computer Vision*, pp. 2980–2988, 2017.

Irina Higgins, Arka Pal, Andrei A Rusu, Loic Matthey, Christopher P Burgess, Alexander Pritzel, Matthew Botvinick, Charles Blundell, and Alexander Lerchner. Darla: Improving zero-shot transfer in reinforcement learning. *arXiv preprint arXiv:1707.08475*, 2017.

Sepp Hochreiter, A Steven Younger, and Peter R Conwell. Learning to learn using gradient descent. In *International Conference on Artificial Neural Networks*, 2001.

Diederik P. Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. In *International Conference on Learning Representations*, 2015.

James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, Demis Hassabis, Claudia Clopath, Dharshan Kumaran, and Raia Hadsell. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 2017.

Abhishek Kumar, Prasanna Sattigeri, and P Thomas Fletcher. Improved Semi-supervised Learning with GANs using Manifold Invariances. In *Advances in Neural Information Processing Systems*, 2017.

Brenden Lake, Ruslan Salakhutdinov, Jason Gross, and Joshua Tenenbaum. One shot learning of simple visual concepts. In *Proceedings of the Annual Meeting of the Cognitive Science Society*, 2011.

Brenden M. Lake, Ruslan Salakhutdinov, and Joshua B. Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 350(6266):1332–1338, 2015.

Sang-Woo Lee, Jin-Hwa Kim, JungWoo Ha, and Byoung-Tak Zhang. Overcoming Catastrophic Forgetting by Incremental Moment Matching. In *Advances in Neural Information Processing Systems*, 2017.

Yoonho Lee and Seungjin Choi. Meta-Learning with Adaptive Layerwise Metric and Subspace. In *International Conference on Machine Learning*, 2018.

Kevin Luk and Roger Grosse. A coordinate-free construction of scalable natural gradient. *arXiv preprint arXiv:1808.10340*, 2018.

Dhruv Mahajan, Ross B. Girshick, Vignesh Ramanathan, Kaiming He, Manohar Paluri, Yixuan Li, Ashwin Bharambe, and Laurens van der Maaten. Exploring the limits of weakly supervised pretraining. *arXiv preprint Arxiv:1805.00932*, 2018.

James Martens. Deep learning via hessian-free optimization. In *International Conference on Machine Learning*, 2010.

Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of Learning and Motivation*, volume 24, pp. 109–165. Elsevier, 1989.

Thomas Miconi, Jeff Clune, and Kenneth O. Stanley. Differentiable plasticity: training plastic neural networks with backpropagation. *International Conference on Machine Learning*, 2018.

Nikhil Mishra, Mostafa Rohaninejad, Xi Chen, and Pieter Abbeel. A Simple Neural Attentive Meta-Learner. In *International Conference on Learning Representations*, 2018.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning. *arXiv preprint arXiv:1312.5602*, 2013.

Alex Nichol, Joshua Achiam, and John Schulman. On First-Order Meta-Learning Algorithms. *arXiv preprint ArXiv:1803.02999*, 2018.

Sinno Jialin Pan and Qiang Yang. A survey on transfer learning. *IEEE Transactions on Knowledge & Data Engineering*, (10):1345–1359, 2009.

Razvan Pascanu and Yoshua Bengio. Revisiting natural gradient for deep networks. In *International Conference on Learning Representations*, 2014.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *International Conference on Learning Representations*, 2016.

Andrei A Rusu, Neil C Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks. *arXiv preprint arXiv:1606.04671*, 2016.

Adam Santoro, Sergey Bartunov, Matthew Botvinick, Daan Wierstra, and Timothy Lillicrap. Meta-learning with memory-augmented neural networks. In *International Conference on Machine Learning*, 2016.

Jürgen Schmidhuber. *Evolutionary principles in self-referential learning*. PhD thesis, Technische Universität München, 1987.

Jonathan Schwarz, Jelena Luketina, Wojciech M Czarnecki, Agnieszka Grabska-Barwinska, Yee Whye Teh, Razvan Pascanu, and Raia Hadsell. Progress & compress: A scalable framework for continual learning. In *International Conference on Machine Learning*, 2018.

Joan Serrà, Dídac Surís, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task. In *International Conference on Machine Learning*, 2018.

Hang Shao, Abhishek Kumar, and P Thomas Fletcher. The Riemannian Geometry of Deep Generative Models. *arXiv preprint ArXiv:1711.08014*, 2017.

Jake Snell, Kevin Swersky, and Richard S Zemel. Prototypical Networks for Few-shot Learning. In *Advances in Neural Information Processing Systems*, 2017.

Richard S Sutton, Andrew G Barto, et al. *Reinforcement learning: An introduction*. MIT Press, Cambridge, 1998.

Alessandra Tosi, Søren Hauberg, Alfredo Vellido, and Neil D Lawrence. Metrics for Probabilistic Geometries. *Conference on Uncertainty in Artificial Intelligence*, 2014.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. Matching Networks for One Shot Learning. In *Advances in Neural Information Processing Systems*, 2016.

Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual Learning Through Synaptic Intelligence. In *International Conference on Machine Learning*, 2017.

APPENDIX

A   PROOF OF THEOREM 1

Proof. We first establish that, for all s, $d(\psi^0_{s+1}) = F(\psi^0_{s+1}; \Psi_{s+1}) \leq F(\psi^0_s; \Psi_s) = d(\psi^0_s)$, with strict inequality for at least some s. Because $\{\beta_s\}^\infty_{s=1}$ satisfies the gradient descent criteria, it follows that the sequence $\{\psi^0_s\}^\infty_{s=1}$ is convergent, and that, for all s, $\lim_{i \to \infty} \psi^i_{s+1} = \lim_{i \to \infty} \psi^i_s$. That is, each initialization incrementally reduces the expected gradient path length while converging to the same limit point as ψ^0_0, and since $\psi^0_0 \in \Theta$ by assumption, we obtain $\psi^0_s \in \Theta$ for all s as an immediate consequence. To establish $d(\psi^0_{s+1}) \leq d(\psi^0_s)$, with strict inequality for some s, let

$$z^i_\tau = (\psi^{s,i}_\tau, f_\tau(\psi^{s,i}_\tau)) \qquad\qquad x^i_\tau = (\psi^{s+1,i}_\tau, f_\tau(\psi^{s+1,i}_\tau))$$
$$h^i_\tau = (\psi^{s,i+1}_\tau, f_\tau(\psi^{s,i+1}_\tau)) \qquad\qquad y^i_\tau = (\psi^{s+1,i+1}_\tau, f_\tau(\psi^{s+1,i+1}_\tau))$$

and denote by $\mathbb{E}_{\tau,i}$ the expectation over gradient paths, $\mathbb{E}_{\tau \sim p(\tau)} \sum^{K_\tau}_{i=1}$. Note that

$$F(\psi^0_s, \Psi_s) = \mathbb{E}_{\tau,i} \|h^i_\tau - z^i_\tau\|^p_2 \qquad\qquad F(\psi^0_s, \Psi_{s+1}) = \mathbb{E}_{\tau,i} \|y^i_\tau - z^i_\tau\|^p_2$$
$$F(\psi^0_{s,+1}\Psi_s) = \mathbb{E}_{\tau,i} \|h^i_\tau - x^i_\tau\|^p_2 \qquad\qquad F(\psi^0_{s+1}, \Psi_{s+1}) = \mathbb{E}_{\tau,i} \|y^i_\tau - x^i_\tau\|^p_2$$

with $p = 2$ defining the meta objective in terms of the gradient path energy and $p = 1$ in terms of the gradient path length. As we are exclusively concerned with the Euclidean norm, we drop the subscript going forward. By assumption, every β_s is sufficiently small to satisfy the gradient descent criteria $F(\psi^0_s; \Psi_s) \geq F(\psi^0_{s+1}; \Psi_s)$. Adding and subtracting $d(\psi^0_{s+1}) = F(\psi^0_{s+1}, \Psi_{s+1})$ to the RHS, we have

$$\mathbb{E}_{\tau,i} \|h^i_\tau - z^i_\tau\|^p \geq \mathbb{E}_{\tau,i} \|h^i_\tau - x^i_\tau\|^p$$
$$= \mathbb{E}_{\tau,i} \|y^i_\tau - x^i_\tau\|^p + \|h^i_\tau - x^i_\tau\|^p - \|y^i_\tau - x^i_\tau\|^p.$$

Consequently, it follows that $d(\psi^0_{s+1}) \leq d(\psi^0_s)$ if $\mathbb{E}_{\tau,i} \|h^i_\tau - x^i_\tau\|^p \geq \mathbb{E}_{\tau,i} \|y^i_\tau - x^i_\tau\|^p$. As our main concern is existence, we will show something stronger, namely that there exists α^i_τ such that

$$\|h^i_\tau - x^i_\tau\|^p \geq \|y^i_\tau - x^i_\tau\|^p \qquad \forall i, \tau, p$$

with at least one such inequality is strict, in which case $d(\psi^0_{s+1}) < d(\psi^0_s)$. We proceed by establishing the inequality for $p = 2$ and obtain $p = 1$ as an immediate consequence of monotonicity of the square root. Expanding the left hand side, $\|h^i_\tau - x^i_\tau\|^2$, we have

$$\|h^i_\tau - x^i_\tau\|^2 - \|y^i_\tau - x^i_\tau\|^2 = \|(h^i_\tau - z^i_\tau) + (z^i_\tau - x^i_\tau)\|^2 - \|y^i_\tau - x^i_\tau\|^2$$
$$= \|h^i_\tau - z^i_\tau\|^2 + 2\langle h^i_\tau - z^i_\tau, z^i_\tau - x^i_\tau \rangle + \|z^i_\tau - x^i_\tau\|^2 - \|y^i_\tau - x^i_\tau\|^2.$$

Every term except $\|z^i_\tau - x^i_\tau\|^2$ can be minimized by choosing α^i_τ small, whereas $\|z^i_\tau - x^i_\tau\|^2$ is controlled by β_s. Thus, our strategy is to make all terms except $\|z^i_\tau - x^i_\tau\|^2$ small, for a given β_s, by placing an upper bound on α^i_τ. We first show that $\|h^i_\tau - z^i_\tau\|^2 - \|y^i_\tau - x^i_\tau\|^2 = O\left({\alpha^i_\tau}^2\right)$. Some care is needed as the $(n + 1)$th dimension is the loss value associated with the other n dimensions. To be consistent in our notation, define $\hat{z}^i_\tau = \psi^{s,i}_\tau$, so that $z^i_\tau = (\hat{z}^i_\tau, f_\tau(\hat{z}^i_\tau))$. Similarly define $\hat{x}^i_\tau, \hat{h}^i_\tau$, and $\hat{y}^i_\tau$ to obtain

$$\|h_\tau^i - z_\tau^i\|^2 = \|\hat{h}_\tau^i - \hat{z}_\tau^i\|^2 + (f_\tau(\hat{h}_\tau^i) - f_\tau(\hat{z}_\tau^i))^2$$
$$\|y_\tau^i - x_\tau^i\|^2 = \|\hat{y}_\tau^i - \hat{x}_\tau^i\|^2 + (f_\tau(\hat{y}_\tau^i) - f_\tau(\hat{x}_\tau^i))^2$$
$$2\langle h_\tau^i - z_\tau^i, z_\tau^i - x_\tau^i \rangle = 2\langle \hat{h}_\tau^i - \hat{z}_\tau^i, \hat{z}_\tau^i - \hat{x}_\tau^i \rangle + (f_\tau(\hat{h}_\tau^i) - f_\tau(\hat{z}_\tau^i))(f_\tau(\hat{z}_\tau^i) - f_\tau(\hat{x}_\tau^i)).$$

Consider $\|\hat{h}_\tau^i - \hat{z}_\tau^i\|^2 - \|\hat{y}_\tau^i - \hat{x}_\tau^i\|^2$. Note that $\hat{h}_\tau^i = \hat{z}_\tau^i - \alpha_\tau^i g(\hat{z}_\tau^i)$, where $g(\hat{z}_\tau^i) = S_\tau^{s,i} \nabla f(\hat{z}_\tau^i)$, and similarly $\hat{y}_\tau^i = \hat{x}_\tau^i - \alpha_\tau^i g(\hat{x}_\tau^i)$ with $g(\hat{x}_\tau^i) = S_\tau^{s+1,i} \nabla f(\hat{x}_\tau^i)$. Thus, $\|\hat{h}_\tau^i - \hat{z}_\tau^i\|^2 = {\alpha_\tau^i}^2 \|g(\hat{z}_\tau^i)\|^2$ and similarly for $\|\hat{y}_\tau^i - \hat{x}_\tau^i\|^2$, so

$$\|\hat{h}_\tau^i - \hat{z}_\tau^i\|^2 - \|\hat{y}_\tau^i - \hat{x}_\tau^i\|^2 = {\alpha_\tau^i}^2 \left(\|g(\hat{z}_\tau^i)\|^2 - \|g(\hat{x}_\tau^i)\|^2 \right) = O\left({\alpha_\tau^i}^2\right).$$

Now consider $(f_\tau(\hat{h}_\tau^i) - f_\tau(\hat{z}_\tau^i))^2 - (f_\tau(\hat{y}_\tau^i) - f_\tau(\hat{x}_\tau^i))^2$. Using the above identities and first-order Taylor series expansion, we have

$$(f_\tau(\hat{h}_\tau^i) - f_\tau(\hat{z}_\tau^i))^2 = \left(\nabla f_\tau(\hat{z}_\tau^i)^T (\hat{h}_\tau^i - \hat{z}_\tau^i) + O\left(\alpha_\tau^i\right) \right)^2$$
$$= \left(-\alpha_\tau^i \nabla f_\tau(\hat{z}_\tau^i)^T g(\hat{z}_\tau^i) + O\left(\alpha_\tau^i\right) \right)^2 = O\left({\alpha_\tau^i}^2\right),$$

and similarly for $(f_\tau(\hat{y}_\tau^i) - f_\tau(\hat{x}_\tau^i))^2$. As such, $\|h_\tau^i - z_\tau^i\|^2 - \|y_\tau^i - x_\tau^i\|^2 = O\left({\alpha_\tau^i}^2\right)$.

Returning to $\|h_\tau^i - x_\tau^i\|^2 \geq \|y_\tau^i - x_\tau^i\|^2$, substituting in the above results, we have

$$\|h_\tau^i - x_\tau^i\|^2 - \|y_\tau^i - x_\tau^i\|^2 = \|z_\tau^i - x_\tau^i\|^2 + 2\langle h_\tau^i - z_\tau^i, z_\tau^i - x_\tau^i \rangle + O\left({\alpha_\tau^i}^2\right)$$
$$= \|z_\tau^i - x_\tau^i\|^2 - 2\alpha_\tau^i \langle g(z_\tau^i), z_\tau^i - x_\tau^i \rangle + O\left({\alpha_\tau^i}^2\right).$$

The first term is non-negative, and importantly, always non-zero whenever $\beta_s \neq 0$. Furthermore, α_τ^i can always be made sufficiently small for $\|z_\tau^i - x_\tau^i\|^2$ to dominate the residual, so we can focus on the inner product $\langle g(z_\tau^i), z_\tau^i - x_\tau^i \rangle$. If it is negative, all terms are positive and we have $\|h_\tau^i - x_\tau^i\|^2 - \|y_\tau^i - x_\tau^i\|^2 > 0$ as desired. If not, $\|z_\tau^i - x_\tau^i\|^2$ dominates if

$$\alpha_\tau^i \leq \frac{\|z_\tau^i - x_\tau^i\|^2}{2\langle g(z_\tau^i), z_\tau^i - x_\tau^i \rangle} \in (0, \infty).$$

Thus, for α_τ^i sufficiently small, we have $\|h_\tau^i - x_\tau^i\|^2 \geq \|y_\tau^i - x_\tau^i\|^2$, with strict inequality whenever $\langle g(z_\tau^i), z_\tau^i - x_\tau^i \rangle < 0$ or the bound on α_τ^i holds strictly. This establishes $d_2(\psi_{s+1}^0) \leq d_2(\psi_s^0)$, with strict inequality for some at least some s. To also establish it for the gradient path length, taking square roots on both sides of $\|h_\tau^i - x_\tau^i\|^2 \geq \|y_\tau^i - x_\tau^i\|^2$ yields the desired results, and so $\mathbb{E}_{\tau,i} \|h_\tau^i - x_\tau^i\|^p \geq \mathbb{E}_{\tau,i} \|y_\tau^i - x_\tau^i\|^p$ for $p \in \{1, 2\}$, establishing

$$d(\psi_{s+1}^0) = F(\psi_{s+1}^0; \Psi_{s+1}) \leq F(\psi_s^0; \Psi_s) = d(\psi_s^0),$$

with strict inequality whenever $\beta_s \neq 0$ and α_τ^i is sufficiently small.

Then, to see that the limit point of Ψ_{s+1} is the same as that of Ψ_s for β_s sufficiently small, note that $x_\tau^i = y_\tau^{i-1}$. As before, by the gradient descent criteria, β_s is such that

$$\mathbb{E}_{\tau,i} \|h_\tau^i - x_\tau^i\|^p = \mathbb{E}_{\tau,i} \|h_\tau^i - y_\tau^{i-1}\|^p \leq \mathbb{E}_{\tau,i} \|h_\tau^i - z_\tau^i\|^p = \mathbb{E}_{\tau,i} {\alpha_\tau^i}^p \|g(\hat{z}_\tau^i)\|^p.$$

Define ϵ_τ^i as the noise residual from the expectation; each y_τ^{i-1} is bounded by $\|h_\tau^i - y_\tau^{i-1}\|^p \leq {\alpha_\tau^i}^p \|g(\hat{z}_\tau^i)\|^p + \epsilon_\tau^i$. For β_s small this noise component vanishes, and since $\{\alpha_\tau^i\}_i$ is a converging sequence, the bound on y_τ^{i-1} grows increasingly tight. It follows then that $\{\psi_{s+1}^i\}_{i=1}^\infty$ converges to the same limit point as $\{\psi_s^i\}_{i=1}^\infty$, yielding $\psi_{s+1}^0 \in \Theta$ for all s, as desired. ∎

B   ABLATION STUDY: APPROXIMATING JACOBIANS $J^i(\theta^0)$

To understand the role of the Jacobians, note that (we drop task subscripts for simplicity)

$$J^{i+1}(\theta^0) = \left(I_n - \alpha^i S^i H_f(\theta^i)\right) J^i(\theta^0) = \prod_{j=0}^i \left(I_n - \alpha^j S^j H_f(\theta^j)\right)$$

$$= I_n - \sum_{j=0}^i \alpha^i S^i H_f(\theta^i) + O\left({\alpha^i}^2\right),$$

where $H_f(\theta^j)$ denotes the Hessian of f at θ^j. Thus, changes to θ^{i+1} are translated into θ^0 via all intermediary Hessians. This makes the Jacobians memoryless up to second-order curvature. Importantly, the effect of curvature can directly be controlled via α^i, and by choosing α^i small we can ensure $J^i(\theta^0) \approx I_n$ to be a reasonable assumption. In practice, this approximation works well (c.f. Finn et al., 2017; Nichol et al., 2018). Moreover, as a practical matter, if the alternative is some other approximation to the Hessians, the amount of noise injected grows exponentially with every iteration, making it an extremely challenging problem beyond the scope of this paper.

To understand how this approximation limits our choice of learning rates α^i we conduct an ablation study in the Omniglot experiment setting. We are interested in the relative precision of the identity approximation under different learning rates and across time steps, which we define as

$$\rho\left(i, \{\alpha^j\}_{j=0}^i\right) = \frac{\|I_n - J^i(\theta^0)\|_1}{\|J^i(\theta^0)\|_1}.$$

We use the same four-layer convolutional neural network as in the Omniglot experiment (appendix D). For each choice of learning rate, we train a model from a random initialization for 20 steps and compute ρ every 5 steps. Due to exponential growth of memory consumption, we were unable to compute ρ for more than 20 gradient steps. We report the relative precision of the first convolutional layer, as computing the Jacobian with respect to the other layers, all being considerably larger, was too costly. We computed ρ for all layers on the first five gradient steps and found no significant variation in precision across layers. Consequently, we prioritize reporting how precision varies with the number of gradient steps. As in the main experiments, we use stochastic gradient descent. We evaluate $\alpha^i = \alpha \in \{0.01, 0.1, 0.5\}$ across 5 different tasks. Figure 5 summarizes our results.

Reassuringly, we find the identity approximation to be accurate to at least the fourth decimal for learning rates we use in practice, and to the third decimal for the largest learning rate (0.5) we were able to converge with. Importantly, except for the smallest learning rate, the quality of the approximation is constant in the number of gradient steps. The smallest learning exhibit some deterioration on the fourth decimal, however larger learning rates provide an upper bound that is constant on the third decimal, indicating that this is of minor concern. Finally, we note that while these results suggest the identity approximation to be a reasonable approach on the class of problems we consider, other settings may put stricter limits on the effective size of learning rates.

C   ABLATION STUDY: LEAP HYPER-PARAMETERS

As Leap is a general framework, we have several degrees of freedom to specify a particular meta learner. In particular, the choice of task manifold, gradient path distance (i.e. d_p), and whether to incorporate stabilizers. These are non-trivial choices and to ascertain the importance of each, we conduct an ablation study. We vary the task manifold, between the full loss surface and only parameter space, the use of path energy or length as distance measure (i.e. d_p), and the importance of the

Figure 5: Relative absolute precision of Jacobian approximation. Precision is calculated for the Jacobian of the first layer, across different learning rates (colors) and gradient steps.

Figure 6: Average task training loss over meta-training steps. p denotes which d_p is used in the meta-objective, $\mu = 1$ indicates the use of the regularizer and $f_\tau = 1$ the inclusion of the loss in the task manifold.

stabilizer μ. We stay as close as possible to the set-up used in the Omniglot experiment (section 4.1), but fix the number of pre-training tasks to 30 and use fewer training steps in the inner and outer loop during meta-training; we perform 500 meta-gradient updates, which is sufficient to converge, and use a maximum of 100 gradient steps on each task during meta-training (i.e. $K_\tau \leq 100$; c.f.fig. 3). All other hyper-parameters are the same.

Our ablation study indicates that the richer the task manifold and the more accurate the gradient path length is approximated, the better Leap performs (fig. 6). Further, adding a stabilizer has the intended effect and leads to significantly faster convergence. The simplest configuration, defined in terms of the gradient path energy and with the task manifold equal equal to parameter space, yields a meta-gradient equivalent to the update rule used in Reptile. We find this configuration to be least efficient in terms of convergence and observe a significant deterioration in performance. Extending the task manifold to the loss surface does not improve meta-training convergence speed, but does cut prediction error in half. Adding the stabilizer significantly speeds up convergence, as intended. These

conclusions also hold under the gradient path length as distance measure, and in general using the gradient path length does better than using the gradient path energy as the distance measure.

D EXPERIMENT DETAILS: OMNIGLOT

Omniglot contains 50 alphabets, each consisting of a set of characters that in turn have 20 unique samples. We pretrain on up to 30 tasks, holding 10 tasks out for validation and 10 tasks for final evaluation. We use the same convolutional neural network architecture as in previous works (Vinyals et al., 2016; Finn et al., 2017; Schwarz et al., 2018) and train using stochastic gradient descent. For each alphabet, we define a task as a 20-class classification problem. For alphabets with more than 20 characters, we pick 20 characters at random, while alphabets with fewer characters (4) are dropped from the validation set. The validation set is used to for early stopping of the meta training process. On each task, we train the model using stochastic gradient descent with a batch size of 20, and a learning rate of 0.1, except for fine-tuning where we find 0.01 to perform better than 0.1 or 0.001. The initialization is trained using stochastic gradient descent with a learning rate of 0.1, except for in the case of Reptile where a lower learning rate of 0.01 performed best. We use a task batch size of 20, sampled with replacement. We train on a given task until we observe no more improvement on a set of held-out images. Following Schwarz et al. (2018), we augment the dataset with 36 random rotations.

Table 2: Mean test error on held out tasks.*Author's suggested first-order approximation; †multi-headed finetuning.

| Method
No. Pretraining tasks	Leap	Finetune[†]	Reptile	MAML[*]	No pretraining
1	7.5	7.5	8.4	8.8	17.0
2	6.4	6.3	8.0	8.8	16.8
4	4.0	4.7	7.2	8.6	17.9
6	3.1	4.4	6.3	8.4	16.1
8	2.7	4.2	6.1	8.7	15.9
10	2.1	4.0	5.7	9.2	16.1
12	2.0	3.6	5.4	8.6	16.2
14	1.9	3.8	5.2	8.6	16.6
16	1.7	3.9	5.1	9.1	16.7
18	1.8	3.7	5.1	8.7	15.9
20	1.7	3.9	4.7	9.4	16.6
22	1.6	3.7	4.9	8.6	16.2
24	1.8	3.5	5.0	8.7	15.9
26	1.6	3.3	4.5	9.2	16.9
28	1.7	3.8	4.8	9.3	17.0
30	1.6	3.6	4.6	8.7	16.1

E EXPERIMENT DETAILS: MULTI-CV

In this experiment, we allow different architectures between tasks by using a distinct final linear layers for each task. We use the same neural network architecture as in the Omniglot experiment and compare Leap against (a) a baseline with no pretraining, (b) multitask finetuning, (c) HAT (Serrà et al., 2018), and (d) Progressive Nets (Rusu et al., 2016). For HAT, we use the original formulation, but allow multiple revisits (until convergenve). For Progressive Nets, we allow lateral connections between all tasks and allow multiple revisits (until convergence). Note that Progressive Nets is over 8 times larger in terms of learnable parameters than the other models.

On a given task, we train the model using stochastic gradient descent with a learning rate of 0.1 and a batch size of 32. Training is stopped once the validation accuracy does not improve or once a preset

number of epochs is reached. For pretraining, we cap the number of training epochs to 10, and for the held-out task we cap the number of epochs to 100. We train Leap using Adam (Kingma & Ba, 2015) with a learning rate of 0.01 and a task batch size of 10. Once meta training is complete, we train on a held-out dataset until the validation error stops improving, or the training process reaches 100 epochs. We use no dataset augmentation; MNIST images are zero padded to have 32×32 images; we use the same normalizations as in Serrà et al. (2018).

Table 3: Transfer learning results on Multi-CV benchmark. All methods are trained until convergence on held-out tasks. [†]Area under training error curve; scaled to 0–100. [‡]Our implementation.

Held-out task	Method	Test (%)	Train (%)	AUC[†]
Facescrub	Leap	19.9	0.0	11.6
	Fine-tuning	32.7	0.0	13.2
	Progressive Nets[‡]	**18.0**	0.0	8.9
	HAT[‡]	25.6	0.1	14.6
	No pre-training	18.2	0.0	**10.5**
NotMNIST	Leap	**5.3**	**0.6**	**2.9**
	Fine-tuning	5.4	2.0	4.4
	Progressive Nets[‡]	5.4	3.1	3.7
	HAT[‡]	6.0	2.8	5.4
	No pre-training	5.4	2.6	5.1
MNIST	Leap	**0.7**	0.1	**0.6**
	Fine-tuning	0.9	0.1	0.8
	Progressive Nets[‡]	0.8	**0.0**	0.7
	HAT[‡]	0.8	0.3	1.2
	No pre-training	0.9	0.2	1.0
Fashion MNIST	Leap	**8.0**	4.2	**6.8**
	Fine-tuning	8.9	**3.8**	7.0
	Progressive Nets[‡]	8.7	5.4	9.2
	HAT[‡]	9.5	5.5	8.1
	No pre-training	8.4	4.7	7.8
Cifar10	Leap	**21.2**	**10.8**	**17.5**
	Fine-tuning	27.4	13.3	20.7
	Progressive Nets[‡]	24.2	15.2	24.0
	HAT[‡]	27.7	21.2	27.3
	No pre-training	26.2	13.1	23.0
SVHN	Leap	**8.4**	**5.6**	**7.5**
	Fine-tuning	10.9	6.1	10.5
	Progressive Nets[‡]	10.1	6.3	13.8
	HAT[‡]	10.5	5.7	8.5
	No pre-training	10.3	6.9	11.5
Cifar100	Leap	**52.0**	**30.5**	**43.4**
	Fine-tuning	59.2	31.5	44.1
	Progressive Nets[‡]	55.7	42.1	54.6
	HAT[‡]	62.0	49.8	58.4
	No pre-training	54.8	33.1	50.1
Traffic Signs	Leap	**2.9**	0.0	**1.2**
	Fine-tuning	5.7	0.0	1.7
	Progressive Nets[‡]	3.6	0.0	4.0
	HAT[‡]	5.4	0.0	2.3
	No pre-training	3.6	0.0	2.4

F   EXPERIMENT DETAILS: ATARI

We use the same network as in Mnih et al. (2013), adopting it to actor-critic algorithms by estimating both value function and policy through linear layers connected to the final output of a shared convolutional network. As is standard, we use downsampled $84 \times 84 \times 3$ RGB images as input. On each task, we use a batch size of 32, an unroll length of 5 and update the model parameters with RMSProp (using $\epsilon = 10^{-4}, \alpha = 0.99$) with a learning rate of 10^{-4}. We set the entropy cost to 0.01 and clip the absolute value of the rewards to maximum 5.0. The discounting factor was set to 0.99.

Table 4: Evaluation environment characteristics. †Calculated on baseline (no pretraining) data.

Environment	Action Space	Mean Reward†	Standard Deviation†	Pretraining Env
AirRaid	6	2538	624	Y
UpNDown	6	52417	2797	Y
WizardOfWor	10	2531	182	Y
Breakout	4	338	13	N
SpaceInvaders	6	1065	103	N
Asteroids	14	1760	139	N
Alien	18	1280	182	N
Gravitar	18	329	15	N
RoadRunner	18	29593	2890	N

Figure 7: Mean episode returns on Atari games across training steps. Scores are reported as moving average over 500 episodes. Shaded regions depict two standard deviations across ten seeds. KungFuMaster, RoadRunner and Krull have action state spaces that are twice as large as the largest action state encountered during pretraining. Leap (orange) generally outperforms a random initialization; in one case a random initialization does better on average due to outlying runs with Leap.

Figure 8: Mean normalized episode returns on Atari games across training steps for different runs. Scores are reported as moving average over 500 episodes. Leap (orange) outperforms a random initialization by being less volatile.