ARE GENERATIVE CLASSIFIERS MORE ROBUST TO ADVERSARIAL ATTACKS?

ABSTRACT

There is a rising interest in studying the robustness of deep neural network classifiers against adversaries, with both advanced attack and defence techniques being actively developed. However, most recent work focuses on *discriminative* classifiers, which only model the conditional distribution of the labels given the inputs. In this paper, we propose and investigate the *deep Bayes* classifier, which improves classical naive Bayes with conditional deep generative models. We further develop detection methods for adversarial examples, which reject inputs with low likelihood under the generative model. Experimental results suggest that deep Bayes classifiers are more robust than deep discriminative classifiers, and that the proposed detection methods are effective against many recently proposed attacks.

1 INTRODUCTION

Deep neural networks have been shown to be vulnerable to adversarial examples (Szegedy et al., 2013; Goodfellow et al., 2014). The latest attack techniques can easily fool a deep neural network with imperceptible perturbations (Goodfellow et al., 2014; Papernot et al., 2016b; Carlini & Wagner, 2017a; Kurakin et al., 2016; Madry et al., 2018; Chen et al., 2017a), even in the black-box case, where the attacker does not have access to the network's weights (Papernot et al., 2017b; Chen et al., 2017b; Alzantot et al., 2018a). Adversarial attacks are serious security threats to machine learning systems, threatening applications beyond image classification (Carlini & Wagner, 2018; Alzantot et al., 2018b).

To address this outstanding security issue, researchers have proposed defence mechanisms against adversarial attacks. Adversarial training, which augments the training data with adversarially perturbed inputs, has shown moderate success at defending against recently proposed attack techniques (Szegedy et al., 2013; Goodfellow et al., 2014; Tramèr et al., 2017; Madry et al., 2018). In addition, recent advances in Bayesian neural networks have demonstrated that uncertainty estimates can be used to detect adversarial attacks (Li & Gal, 2017; Feinman et al., 2017; Louizos & Welling, 2017; Smith & Gal, 2018). Another notable category of defence techniques involves the usage of generative models. For example, Gu & Rigazio (2014) used an auto-encoder to denoise the inputs before feeding them to the classifier. This denoising approach has been extensively investigated, and the "denoisers" in usage include generative adversarial networks (Samangouei et al., 2018), PixelCNNs (Song et al., 2018) and denoising auto-encoders (Kurakin et al., 2018). These developments rely on the *"off-manifold"* conjecture, that is, that adversarial examples are far away from the data manifold, although Gilmer et al. (2018) has challenged this observation with a synthetic example.

Surprisingly, much less recent work has investigated the robustness of *generative classifiers* (Ng & Jordan, 2002) against adversarial attacks for multi-class classification, where such classifiers explicitly model the conditional distribution of the inputs given labels. Typically, a generative classifier produces predictions by comparing between the likelihood of the labels for a given input, which is closely related to the "distance" of the input to the data manifold associated with a class. Therefore, generative classifiers should be robust to many recently proposed adversarial attacks if the "off-manifold" conjecture holds for many real-world applications. Unfortunately, many generative classifiers in popular use, including naive Bayes and linear discriminant analysis (Fisher, 1936), perform poorly on natural image classification tasks, making it difficult to verify the "off-manifold" conjecture and the robustness of generative classifiers with these tools. In recent work, k-nearest neighbors (Cover & Hart, 1967), a method which shares many similarities with generative classi-

fiers, has been significantly improved in handling natural images by leveraging deep feature representations (Papernot & McDaniel, 2018). To the best of our knowledge, an approach which targets a similar contribution has not yet been proposed for generative classifiers.

Are generative classifiers more robust to recently proposed adversarial attack techniques? To answer this, we improve the naive Bayes algorithm by using conditional deep generative models, and evaluate the conjecture on the proposed generative classifier. In summary, our contributions include:

- We propose *deep Bayes* as an extension of naive Bayes, in which the conditional distribution of an input, given a label, is parameterised by a deep latent variable model (LVM). We learn the LVM with the variational auto-encoder algorithm (Kingma & Welling, 2013; Rezende et al., 2014), and approximate Bayes' rule using importance sampling.
- We propose three detection methods for adversarial perturbations. The first two use the learned generative model as a proxy of the data manifold, and reject inputs that are far away from it. The third computes statistics for the classifier's output probability vector on training data, and rejects inputs that lead to under-confident predictions.
- We evaluate the robustness of the proposed generative classifier on the MNIST multi-class and CIFAR binary classification tasks. We also improve the robustness of deep neural networks on CIFAR-10 multi-class classification, by fusing discriminatively learned visual feature representations with the proposed generative classifiers. We further compare the generative classifiers with a number of discriminative classifiers, including Bayesian neural networks and *discriminative* latent variable models.

2 DEEP BAYES: CONDITIONAL DEEP LVM AS A GENERATIVE CLASSIFIER

Denote $p_{\mathcal{D}}(\boldsymbol{x}, \boldsymbol{y})$ the data distribution for the input $\boldsymbol{x} \in \mathbb{R}^D$ and label $\boldsymbol{y} \in \{\boldsymbol{y}_c | c = 1, ..., C\}$, where $\boldsymbol{y}_c$ denotes the one-hot encoding vector for class c. For a given $\boldsymbol{x} \in \mathbb{R}^D$ we can define the ground-truth label by

$$\boldsymbol{y} \sim p_{\mathcal{D}}(\boldsymbol{y}|\boldsymbol{x}) \quad \text{if } \boldsymbol{x} \in \text{supp}(p_{\mathcal{D}}(\boldsymbol{x})). \tag{1}$$

We assume the data distribution $p_{\mathcal{D}}(\boldsymbol{x}, \boldsymbol{y})$ follows the *manifold assumption*: for every class c, the conditional distribution $p_{\mathcal{D}}(\boldsymbol{x}|\boldsymbol{y}_c)$ has a low-dimensional manifold support $\mathcal{M}_c = \text{supp}(p_{\mathcal{D}}(\boldsymbol{x}|\boldsymbol{y}_c))$. Therefore the training dataset $\mathcal{D} = \{(\boldsymbol{x}^{(n)}, \boldsymbol{y}^{(n)})\}_{n=1}^N$ is generated as the following:

$$(\boldsymbol{x}^{(n)}, \boldsymbol{y}^{(n)}) \sim p_{\mathcal{D}}(\boldsymbol{x}, \boldsymbol{y}) \Leftrightarrow \boldsymbol{y}^{(n)} \sim p_{\mathcal{D}}(\boldsymbol{y}), \boldsymbol{x}^{(n)} \sim p_{\mathcal{D}}(\boldsymbol{x}|\boldsymbol{y}).$$

A (Bayesian) generative classifier first builds a *generative model* $p(\boldsymbol{x}, \boldsymbol{y}) = p(\boldsymbol{x}|\boldsymbol{y})p(\boldsymbol{y})$, and then, in prediction time, predicts the label $\boldsymbol{y}^*$ of a test input $\boldsymbol{x}^*$ using Bayes' rule,

$$p(\boldsymbol{y}^*|\boldsymbol{x}^*) = \frac{p(\boldsymbol{x}^*|\boldsymbol{y}^*)p(\boldsymbol{y}^*)}{p(\boldsymbol{x}^*)} = \text{softmax}_{c=1}^C \left[\log p(\boldsymbol{x}^*, \boldsymbol{y}_c) \right],$$

where $\text{softmax}_{c=1}^C$ denotes the softmax operator over the c axis. Therefore, the output probability vector is computed analogously to many deep discriminative classifiers which use softmax activation in the output layer, so many existing attacks can be tested directly. However, unlike discriminative classifiers, the "logit" values prior to softmax activation have a clear meaning here, which is the (approximated) log joint distribution $\log p(\boldsymbol{x}^*, \boldsymbol{y}_c)$ of input $\boldsymbol{x}^*$ conditioned on a given label $\boldsymbol{y}_c$. Therefore, one can also analyse the logit values to determine whether the unseen pair $(\boldsymbol{x}^*, \boldsymbol{y}^*)$ is legitimate, a utility which will be discussed further in later sections.

Naive Bayes is perhaps the most well-known generative classifier; it assumes a factorised distribution for the conditional generator, i.e. $p(\boldsymbol{x}|\boldsymbol{y}) = \prod_{d=1}^D p(x_d|\boldsymbol{y})$. However, this factorisation assumption is inappropriate for e.g. image and speech data. Fortunately, we can leverage the recent advances in generative modelling and apply a deep generative model for the joint distribution $p(\boldsymbol{x}, \boldsymbol{y})$. We refer to such generative classifiers that use deep generative models as *deep Bayes* classifiers.

In this paper, we consider a deep latent variable model (LVM) $p(\boldsymbol{x}, \boldsymbol{z}, \boldsymbol{y})$, which will be used for classification. In this case, the conditional distribution is $p(\boldsymbol{x}|\boldsymbol{y}) = \frac{\int p(\boldsymbol{x}, \boldsymbol{z}, \boldsymbol{y}) d\boldsymbol{z}}{\int p(\boldsymbol{x}, \boldsymbol{z}, \boldsymbol{y}) d\boldsymbol{z} d\boldsymbol{x}}$. Importantly, this leads to a conditional distribution $p(\boldsymbol{x}|\boldsymbol{y})$ that is *not* factorised (even when $p(\boldsymbol{x}|\boldsymbol{z}, \boldsymbol{y})$ is), which is much more powerful than naive Bayes. Since maximum likelihood is intractable, we follow

Figure 1: A visualisation of the graphical models, including both **G**enerative and **D**iscriminative ones, as well as **F**ully connected and **B**ottleneck ones. The last character indicates the first node in the topological order of the graph.

Kingma & Welling (2013) and Rezende et al. (2014) to introduce an amortised approximate posterior $q(z|x, y)$, and train both p and q by maximising the variational lower-bound:

$$\mathbb{E}_{\mathcal{D}}[\mathcal{L}_{\text{VI}}(x, y)] = \frac{1}{N} \sum_{n=1}^{N} \mathbb{E}_q \left[\log \frac{p(x_n, z_n, y_n)}{q(z_n|x_n, y_n)} \right]. \tag{2}$$

After training, the predicted class probability vector y^* for a future input x^* is computed by an approximation to Bayes' rule with importance sampling:

$$p(y^*|x^*) \approx \text{softmax}_{c=1}^{C} \left[\log \frac{1}{K} \sum_{k=1}^{K} \frac{p(x^*, z_c^k, y_c)}{q(z_c^k|x^*, y_c)} \right], \quad z_c^k \sim q(z|x^*, y_c). \tag{3}$$

We evaluate the effect of the following factorisation structures on the robustness of the induced classifier from the generative model $p(x, z, y)$ (see Figure 1).

$$p(x, z, y) = p(z)p(y|z)p(x|z, y) \quad \text{(GFZ)}$$
$$p(x, z, y) = p_{\mathcal{D}}(y)p(z|y)p(x|z, y) \quad \text{(GFY)}$$
$$p(x, z, y) = p(z)p(y|z)p(x|z) \quad \text{(GBZ)}$$
$$p(x, z, y) = p_{\mathcal{D}}(y)p(z|y)p(x|z) \quad \text{(GBY)}$$

$$p(x, z, y) = p_{\mathcal{D}}(x)p(z|x)p(y|z, x) \quad \text{(DFX)}$$
$$p(x, z, y) = p(z)p(x|z)p(y|z, x) \quad \text{(DFZ)}$$
$$p(x, z, y) = p_{\mathcal{D}}(x)p(z|x)p(y|z) \quad \text{(DBX)}$$

We use the initial character "G" to denote generative classifiers and "D" to denote discriminative classifiers. Models with the second character as "F" have a *fully connected* graph, while "B" models enforce the usage of the latent code z as a *bottleneck*. The last character of the model name indicates the first node in topological order. Model DFZ is somewhat intermediate, as it builds a generative model for the inputs x but also directly parameterises the conditional distribution $p(y|x, z)$. We do not test other architectures under this nomenclature, as either the graph contains directed cycles (e.g. $x \to y \to z \to x$), or z is the last node in topological order (e.g. $x \to y, (x, y) \to z$) so that the marginalisation of z does not affect classification.

3 DETECTING ADVERSARIAL ATTACKS WITH GENERATIVE CLASSIFIERS

We propose detection methods for adversarial examples using deep generative models. As an illustrating example, consider a labelled dataset of "cat" and "dog" images. If an adversarial image of a cat x_{adv} is incorrectly labelled as "dog", then either this image is ambiguous, or, under a *perfect* generative model, the logit $\log p(x_{\text{adv}}, \text{"dog"})$ will be significantly lower than normal. This means we can detect attacks using the logits $\log p(x^*, y_c), c = 1, ..., C$ computed on a test input x^*, by comparing them with the logits computed on legitimate training inputs.

Concretely, the proposed detection algorithms are as follows. We aim to reject both unlabelled input x that have low probability under $p_{\mathcal{D}}(x)$, and labelled data (x, y) that have low $p_{\mathcal{D}}(x, y)$ values.

- **Marginal detection**: rejecting inputs that are far away from the manifold.
  One can select a threshold δ and reject an input x if $-\log p(x) > \delta$. To determine the threshold δ, we can compute $\bar{d}_{\mathcal{D}} = \mathbb{E}_{x \sim \mathcal{D}}[-\log p(x)]$ and $\sigma_{\mathcal{D}} = \sqrt{\mathbb{V}_{x \sim \mathcal{D}}[\log p(x)]}$, then set $\delta = \bar{d}_{\mathcal{D}} + \alpha \sigma_{\mathcal{D}}$. It is also possible to compute the statistics $\bar{d}_p, \sigma_p$ on the images generated by the generative model accordingly.
- **Logit detection**: rejecting inputs using joint density.
  Given a victim model $y = F(x)$, one can reject x if $-\log p(x, F(x)) > \delta_y$. We can use the mean and variance statistics $\bar{d}_c, \sigma_c$ computed on $\log p(x, y_c)$ and select $\delta_{y_c} = \bar{d}_c + \alpha \sigma_c$.

Figure 2: Visualising detection mechanisms. The scattered dots are training data points, with different classes shown in different colours (red for $c = 0$ and blue for $c = 1$). Same labels are manually assigned for inputs when the detection method requires $\boldsymbol{y}$. Decision regions are shown in the corresponding colours. Input points in the shaded area are rejected by detection.

- **Divergence detection**: rejecting inputs with over- and/or under-confident predictions. Denote $\boldsymbol{p}(\boldsymbol{x})$ as a C-dimensional probability vector outputted by the classifier. For each class c, we first collect the *mean classification probability vector* $\boldsymbol{p}_c = \mathbb{E}_{(\boldsymbol{x}, \boldsymbol{y}_c) \in \mathcal{D}}[\boldsymbol{p}(\boldsymbol{x})]$, then compute the mean $\bar{d}_c$ and standard deviation σ_c on a selected divergence/distance measure $\mathrm{D}[\boldsymbol{p}_c || \boldsymbol{p}(\boldsymbol{x})]$ for all $(\boldsymbol{x}, \boldsymbol{y}_c) \in \mathcal{D}$. A test input $\boldsymbol{x}^*$ with prediction label $c^* = \arg\max \boldsymbol{p}(\boldsymbol{x}^*)$ is rejected if $\mathrm{D}[\boldsymbol{p}_{c^*} || \boldsymbol{p}(\boldsymbol{x}^*)] > \bar{d}_{c^*} + \alpha \sigma_{c^*}$. Therefore, an example $\boldsymbol{x}^*$ will be rejected if the classifier is over-confident or under-confident (ambiguous inputs).

  When D is selected as the KL-divergence, we call this detection method *KL detection*. Other divergence/distance measures such as total variation (TV) can also be used.

For better intuition, we visualise the detection mechanisms in Figure 2 with a synthetic "two rings" binary classification example. In this case we sample 2×1000 training data points as:

$$(\boldsymbol{x}, \boldsymbol{y}) \sim p_\mathcal{D} \Leftrightarrow \boldsymbol{y} \sim \mathrm{Bern}(0.5), \theta \sim \mathrm{Uniform}(0, 2\pi), \boldsymbol{x}|\boldsymbol{y} \sim \mathcal{N}(\boldsymbol{x}; \boldsymbol{c}_y + r_y[cos(\theta), sin(\theta)]^\mathrm{T}, \sigma^2 \mathbf{I}).$$

We consider a generative classifier $p(\boldsymbol{x}, \boldsymbol{y}) = p(\boldsymbol{x}|\boldsymbol{y}) p_\mathcal{D}(\boldsymbol{y}) = \mathcal{N}(\boldsymbol{x}; \boldsymbol{\mu}_y, \sigma^2 \mathbf{I}) \mathrm{Bern}(0.5)$ with $\boldsymbol{\mu}_y = \mathrm{proj}(\boldsymbol{x}, \mathrm{ring}_y) = \arg\min_{\hat{\boldsymbol{x}} \in \mathbb{R}^2, ||\hat{\boldsymbol{x}} - \boldsymbol{c}_y||_2 = r_y} ||\boldsymbol{x} - \hat{\boldsymbol{x}}||_2$. The δ thresholds are selected to achieve 10% false positive rates on training data. From the visualisations we see that inputs that are far away from the model manifold are rejected by marginal/logit detection. At the same time, logit detection rejects data points that are not on the manifold of the given class. KL/TV detection does not construct manifold-aware acceptance regions, which is as expected since the proposed divergence detection method does not require the classifier to be generative. However, both detection methods have some success in rejecting uncertain predictions, especially for TV, which also rejects ambiguous inputs (see the ring-cross regions in the last two plots). Combining all three methods, we see that the rejected inputs are either far away from the manifold, or are ambiguous.

We emphasise that in practice a suitable generative model is required for this detection task since the data distribution $p_\mathcal{D}(\boldsymbol{x}, \boldsymbol{y})$ is approximated by $p(\boldsymbol{x}, \boldsymbol{y})$. Otherwise, a poor generative model paired with the above detection methods can reject many legitimate inputs. Note that detection methods based on modelling logit values and/or denoising methods have also been considered in the literature (e.g. Li & Gal, 2017; Feinman et al., 2017; Song et al., 2018). But, as the logit values in deep Bayes represent the probability of generating the input $\boldsymbol{x}$ given the class label $\boldsymbol{y} = \boldsymbol{y}_c$, we can use the marginal and logit detection methods to directly verify the "off-manifold" adversarial example conjecture. Also, in principle, we can also add a lower-bounding threshold to marginal/logit detection so that an input-output pair $(\boldsymbol{x}, \boldsymbol{y})$ will be rejected if $-\log p(\boldsymbol{x}, F(\boldsymbol{x})) < \zeta_{\boldsymbol{y}}$. Again, for similar reasons of verifying the "off-manifold" conjecture, we do not test this idea in the experiments.

4 EXPERIMENTS

We carry out a number of tests on the proposed deep Bayes classifiers (3), where $q(\boldsymbol{z}|\cdot)$ and $p(\boldsymbol{z}|\cdot)$ are factorised Gaussians, and the conditional probability $p(\boldsymbol{x}|\cdot)$, if required, is parameterised by an ℓ_2 loss. Besides the LVM-based classifiers, we further train a Bayesian neural network (BNN) with Bernoulli dropout (dropout rate 0.3), as it has been shown in Li & Gal (2017) and Feinman et al. (2017) that BNNs are more robust than their deterministic counterparts. The constructed BNN has 2x more channels than LVM-based classifiers, making the comparison slightly "unfair", as the BNN layers have more capacity. We use $K = 10$ Monte Carlo samples for all the classifiers.

The adversarial attacks in test include both ℓ_∞ and ℓ_2 untargeted attacks: fast gradient sign method (FGSM, Goodfellow et al., 2014), projected gradient descent (PGD, Madry et al., 2018), momentum

Figure 3: Accuracies (column 1) and detection rates (columns 2-4) against **white-box zero-knowledge** ℓ_∞ attacks on MNIST. The higher the better. The right most column visualises crafted adversarial examples on an image of digit "7", with ℓ_∞ distortion ϵ growing from 0.1 to 0.5.

iterative attack (MIM, Dong et al., 2017) and Carlini & Wagner ℓ_2 (CW, Carlini & Wagner, 2017a). All the attacks are taken from the CleverHans 2.0 library (Papernot et al., 2017a). Two metrics are reported: *accuracy* of the classifier on crafted adversarial examples, and *detection rate* of the classifier on adversarial examples that have successfully fooled the classifier to predict wrong labels. This detection rate is defined as the true positive (TP) rate of finding an adversarial example, and the detection threshold is selected to achieve a 5% false positive rate on clean training data.

The experiments presented are performed under various threat model settings. We further evaluate the transferability of crafted adversarial examples across different classifiers in the same way as done in Papernot et al. (2016a). We only provide visualisations in the main text; full table results can be found in the appendix. Readers are also referred to the appendix for further experiments, including a quantitative analysis of the bottleneck effect on robustness and detection.

4.1 MNIST

The first set of experiments evaluate the robustness of generative classifiers on MNIST. Here the image pixel values are normalised to $[0, 1]$, and the LVM-based classifiers have $\dim(\boldsymbol{z}) = 64$. We first perform white-box *zero-knowledge* attacks, i.e. the attacker can differentiate through the classifier to craft adversarial examples, but he/she is not aware of the existence of the detector. Then we perform white-box *perfect-knowledge* attacks, where the attacker can differentiate through both the classifier and the detector, and he/she knows the usage of random $\boldsymbol{z}$ samples by the VAE-based classifiers (Biggio et al., 2013; Carlini & Wagner, 2017b). Lastly we consider grey-box and black-box attacks, and evaluate the robustness of generative classifiers against transferred attacks.

White-box attacks (zero-knowledge, ℓ_∞)   Results for ℓ_∞ attacks are reported in Figure 3, where the true-positive (TP) detection rate is computed on the attacks that have successfully caused the classifier to misclassify. Although FGSM is a weak attack, DFX & DFZ are not robust to it even when $\epsilon = 0.2$ (where the adversarial examples are still visually close to the original digit "7"). Other classifiers perform better. PGD & MIM, as stronger attacks, achieve better success rates on all classifiers, but the generative classifiers with bottleneck perform generally better than the discriminative ones. Interestingly, DBX is the most robust against FGSM & MIM, which agrees with the preliminary tests in Alemi et al. (2017). But DBX is less robust to PGD, and here GBZ is a clear winner. Overall the usage of bottleneck is beneficial for better robustness of MNIST classifiers.

For detection, generative classifiers have successfully detected the adversarial examples with $\epsilon \geq 0.3$, which is reasonable as the visual distortion is already significant. Importantly, for the generative classifiers, we observe that robustness decreases as the ℓ_∞ distortion ϵ increases, but at the same time the TP rates for marginal and logit detection also increase. This clearly demonstrates that these three ℓ_∞ attacks are ineffective for generative classifiers, as they fail to find near-manifold adversarial examples that fool both the classifier and the detection methods. DFZ, as an interme-

Table 1: **White-box zero-knowledge** CW-ℓ_2 attack results. Here, accuracy (adv) measures classifying the adversarial inputs to the original classes.

	acc. (clean)	acc. (adv)	ℓ_2 dist.	TP KL
BNN	99.12%	24.40%	2.129	95.31
GFZ	98.55%	28.58%	2.663	95.37
GBZ	97.45%	81.51%	2.446	91.01
GFY	99.15%	28.64%	2.732	96.03
GBY	98.72%	32.72%	2.735	94.46
DFX	99.10%	20.31%	2.095	99.96
DBX	98.87%	30.19%	1.806	96.76
DFZ	99.10%	13.60%	2.188	99.57

(a) clean inputs   (b) CW adv. inputs

Figure 4: Visualising the clean inputs and the CW adversarial examples crafted on GFZ, digits in red rectangles show significant ambiguity.

diate between generative and discriminative classifiers, has worse robustness results, but has good detection performance for the marginal and logit metrics. This is because with softmax activation, the marginal distribution $p(\boldsymbol{x})$ is dropped, but in marginal/logit detection $p(\boldsymbol{x})$ is still in use.

White-box attack (zero-knowledge, ℓ_2) For the CW ℓ_2 attack, we performed a hyper-parameter search for the loss-balancing parameter c (ℓ_2 distortion increases with larger c) in $\{0.1, 1, 10, 100, 1000\}$ on the first 100 test images, and we found $c = 10$ returns the highest success rate. Victim accuracy and detection rates are reported in Table 1, and we see that CW, though successful in terms of fooling many classifiers to predict wrongly, failed on attacking GBZ. Also, the ℓ_2 distortions of the successful attacks on generative classifiers are significantly larger. Furthermore, we found the success of the attack on GFZ & GFY is mainly due to the ambiguity of the crafted adversarial images. As visualised in Figure 4, the induced distortion from CW leads to ambiguous digits, significant ambiguity is denoted by the red rectangles. In the appendix, we visualize the adversarial examples generated on all classifiers, showing that the CW adversarial examples crafted on generative classifiers are more ambiguous than those crafted on discriminative ones. With the KL detection method, all classifiers achieve $> 95\%$ detection rates, which is as expected as the default CW attack configuration, by construction, generates adversarial examples that lead to minimal difference between the logit values of the most and the second most probable classes.

White-box attack (perfect-knowledge, ℓ_∞) The PGD-based perfect-knowledge ℓ_∞ attack is designed following (Carlini & Wagner, 2017b), where we construct an (approximate) Bayes classifier $p_k(\boldsymbol{y}|\boldsymbol{x})$ using (3) for each set of samples $\{\boldsymbol{z}_c^k\}_{c=1}^C$ (effectively $K = 1$ in eq. (3)), and minimize the following loss on clean datum $(\boldsymbol{x}, \boldsymbol{y})$ with PGD:

$$\mathcal{L}(\boldsymbol{\eta}) = \sum_{k=1}^{K} \log p_k(\boldsymbol{y}|\boldsymbol{x} + \boldsymbol{\eta}) + \lambda_{\text{detect}} \max(0, \Phi(\boldsymbol{x} + \boldsymbol{\eta}, \boldsymbol{y}) - \delta). \qquad (4)$$

The detection statistic $\Phi(\boldsymbol{x} + \boldsymbol{\eta}, \boldsymbol{y})$ is $-\log p(\boldsymbol{x} + \boldsymbol{\eta})$ for marginal detection, and δ is the corresponding threshold computed on training data. For logit/KL detection, the detection statistics and thresholds are constructed accordingly. We label the three attacks against the marginal, logit and KL based detection schemes '-PKM', '-PKL' and '-PKK' respectively. When we only have knowledge of the K samples and not the detection method we call this attack '-PK0' (ie λ_{detect}=0 in Eq. 4).

Results are visualised in Figure 5. We see that although the attacker can reduce detection levels, this comes with the trade-off of increasing accuracy, suggesting that a perfect-knowledge adversary cannot break both the classifier and detector working in tandem.

Grey-box attacks Athalye et al. (2018) claimed that if a successful defence against white-box attacks is due to gradient masking, then this defence is likely to be less effective against grey-box/black-box attacks, as they do not differentiate through the victim classifier and the defence mechanism (Papernot et al., 2017b). Therefore, we consider a grey-box setting where the attacker has access to the output probability vectors of the classifiers on the training data. We distill a victim classifier using a "student" CNN to achieve $> 99\%$ agreement on test data. Then, the adversarial examples are crafted on the substitute model. We report three metrics: the accuracy of the substitute CNN on the crafted examples (to ensure they fool the substitute), the accuracy of the victim classifier on the crafted examples (to test transferability), and the detection rate defined as before.

Figure 5: Accuracy and detection rates of DBX, GBY, and GBZ against PGD-based **perfect-knowledge** attack ($\epsilon = 0.2$) on MNIST. The solid area denotes accuracy and the hatched area denotes detection rate with each considered detector. Zero knowledge attacks are labelled '-ZK', other attack labels are described in the main text.

Figure 6: Accuracy and detection rates against **grey-box (left)** and **black-box (right)** attacks on MNIST. The higher the better.

We visualise the metrics in Figure 6. For PGD and MIM, the substitute models' accuracies are on par with the white-box victim accuracies for $\epsilon = 0.1$, but eventually the adversary fools the substitutes with increased ϵ. However, analyzing the victim accuracies, we see that grey-box attacks do not transfer very well, especially for the generative classifiers, where the victim accuracies are still around $50\% \sim 60\%$ when $\epsilon = 0.3$ (c.f. white-box victim accuracy $< 10\%$ for PGD). Also, the detection rates are near 100% for $\epsilon = 0.3$, meaning that most of the the grey-box adversarial images are also off the data manifold. The CW attack with a decently large c value is very effective on the substitute models, but still the generated adversarial examples fail to transfer, and classifier GFY achieves the best accuracy against them. Interestingly, the bottleneck classifiers are generally less robust to the grey-box CW attack when compared to their fully-connected counterparts.

Black-box attacks We additionally evaluate a black-box attack that only assumes access to queried labels. In other words, the attacker has no knowledge about the training data nor the victim model, they can only query the victim classifier for the labels on given inputs. We follow Papernot et al. (2017b) to train a substitute CNN using Jacobian-based dataset augmentation. Assume $\boldsymbol{y} = F(\boldsymbol{x})$ is the output one-hot vector of the victim, and $\boldsymbol{p}(\boldsymbol{x})$ is the probability vector output of the substitute model, then at the t^{th} outer-loop, we train the substitute CNN on dataset $\mathcal{D}_t = \{(\boldsymbol{x}_n, \boldsymbol{y}_n)\}$ with queried $\boldsymbol{y}_n$ for 10 epochs, and augment the dataset by

$$\mathcal{D}_{t+1} = \mathcal{D}_t \cup \{(\hat{\boldsymbol{x}}, F(\hat{\boldsymbol{x}})) \mid \hat{\boldsymbol{x}} = \boldsymbol{x} + \lambda \nabla_{\boldsymbol{x}} \boldsymbol{p}(\boldsymbol{x})^{\text{T}} \boldsymbol{y}, \ (\boldsymbol{x}, \boldsymbol{y}) \in \mathcal{D}_t\}. \quad (5)$$

We initialise $\mathcal{D}_1$ with 200×10 datapoints from the MNIST test set, select $\lambda = 0.1$, and run the algorithm for 6 outer-loops. This results in $64,000$ queried inputs and $\sim 96\%$ accuracy of the substitute model on test data. The results are visualised in Figure 6, similarly we see that the black-box attack

Figure 7: Results on **cross-model transfer** attacks on MNIST. The horizontal axis corresponds to the source victim that the adversarial examples are crafted on, and the vertical axis corresponds to the target victim that the attacks are transferred to. The higher (i.e. the lighter) the better.

of Papernot et al. (2017b) is ineffective on generative classifiers. Interestingly, the generative bottle-neck classifiers GBZ and GBY seem to be slightly more robust to black-box PGD & MIM attacks, and for the discriminative classifiers, the robustness results against CW are slightly improved when compared to the grey-box cases.

Cross-model attack transferability   Finally, we report in Figure 7 the transferability results of the crafted adversarial examples between different models (Papernot et al., 2016a). Here we take adversarial examples crafted in the white-box setting with PGD and MIM ($\epsilon = 0.3$), and transfer *successful* attacks to other classifiers. The transfer is effective between generative classifiers but not from generative to discriminative (and vice versa). The attacks crafted on DBX do not transfer in general, while at the same time, DBX is the least robust model in this case. Furthermore, the generative classifiers obtain very high detection rates on all transferred attacks ($> 95\%$). In summary, generative classifiers are more robust against the tested transfer attacks across different models.

4.2   CIFAR PLANE-VS-FROG BINARY CLASSIFICATION

In this section, we consider the same set of evaluations on CIFAR-10 data containing natural images. Unfortunately, we failed to train *fully* generative classifiers with comparable test accuracies to discriminative CNNs: the clean accuracies for GFZ & GFY are all $< 50\%$. Even when using the conditional PixelCNN++ (Salimans et al., 2017) (which uses much deeper networks), the clean accuracy on the test data is 72.4%, while a discriminative CNN can easily get $> 80\%$ test accuracy. Therefore, we consider a simpler binary classification problem and construct a dataset containing CIFAR images from the "airplane" and "frog" categories. The images in this dataset are scaled to $[0, 1]$. On this dataset, the generative classifiers use $\dim(\mathbf{z}) = 128$ and obtain $> 90\%$ clean test accuracy, with the exact numbers reported in the appendix. The attacks are performed on the test images that all models initially correctly classify, leading to a test set of 1577 instances. Due to the page limit, we only present white-box zero-knowledge attacks in the main text, and discuss further attacks in the appendix.

White-box attacks (zero-knowledge, ℓ_∞)   We present the white-box ℓ_∞ attack results in Figure 8, where the distortion strengths are selected as $\epsilon \in \{0.01, 0.02, 0.05, 0.1, 0.2\}$. Again, generative classifiers are more robust than the discriminative ones, but GBZ is the most robust, much better than the others when $\epsilon \geq 0.05$. BNN is significantly better than other discriminative VAE-based classifiers, presumably due to higher randomness. However, the detection rates with marginal probability and logit values are less satisfactory, as the methods fail to detect attacks with $\epsilon = 0.1$ (which attain both high success rate and induce visually perceptible distortion). KL detection performs much better, and interestingly, discriminative classifiers dominate in this metric. These detection results suggest that the ℓ_2 likelihood might not be best suited for modelling natural images, which has also been suggested in prior work (e.g. see Larsen et al., 2016; van den Oord et al., 2016). But, on the other hand, for generative classifiers, the visual distortion of the PGD attacks is less significant than that of FGSM & MIM (especially when $\epsilon = 0.2$), which also explains the lower TP rates for maginal and logit detection on PGD attacks.

White-box attack (zero-knowledge, ℓ_2)   As the test set is relatively small, we directly perform CW attacks on the test data with $c \in \{0.1, 1, 10, 100, 1000\}$. Results are visualised in Figure 9. The

Figure 8: Accuracy and detection rates against **white-box zero-knowledge** ℓ_∞ attacks on the CIFAR plane-vs-frog dataset. The higher the better. The right most column visualises crafted adversarial examples on an image of a plane, with ℓ_∞ distortion $\epsilon \in \{0.01, 0.02, 0.05, 0.1, 0.2\}$.

Figure 9: Accuracy and detection rates against **white-box zero-knowledge** CW attacks on the CIFAR plane-vs-frog dataset. The higher the better.

generative classifiers are significantly more robust than the others (with the best being GBZ), and the ℓ_2 distortions computed on successful attacks are also significantly higher. The TP rates are low for marginal and logit detection, which is reasonable as the crafted images are visually similar to the clean ones. Note that the distortion for the attacks on generative classifiers is perceptible. These results indicate that this CW attack is ineffective when attacking generative classifiers.

4.3 CIFAR-10: COMBINING DEEP BAYES AND DISCRIMINATIVE FEATURES

The final experiment examines the robustness of CIFAR10 multi-class classifiers, with the generative classifiers trained on *discriminative* visual features. To do this, we download a pretrained deep convolutional net[1] with VGG16-like architecture (Simonyan & Zisserman, 2014), and use its feature representation $\phi(x)$ as the input to the VAE-based classifiers: $p(y|x) = p(y|\phi(x))$. The classifiers in test include GBZ, GBY and DBX. We use fully-connected neural networks for these classifiers, and select from VGG16 the 9[th] convolution layer (CONV9) and the first fully connected layer after convolution (FC1) as the feature layers to ensure $\sim 90\%$ test accuracy (see appendix).

Results on **white-box zero-knowledge** ℓ_∞ **attacks** are visualised in Figure 10. Compared with the VGG16 baseline, we see clear improvements in robustness and detection for all VAE-based classifiers. In particular, the generative classifiers GBZ and GBY are overall better than DBX. More importantly, generative classifiers based on CONV9 features are significantly more robust than those based on FC1 features. In contrast, for DBX, which is *discriminative*, the robustness results are very similar, indicating that the level of feature representation has little effect. These results suggest that one can achieve both high clean accuracy and better robustness against adversaries by combining discriminatively learned visual features and generative classifiers.

---

[1] https://github.com/geifman/cifar-vgg, 93.59% test accuracy

Figure 10: Accuracy and detection rates against **white-box zero-knowledge** ℓ_∞ attacks on CIFAR-10. The higher the better. Note that results for the DBX classifiers are almost identical.

5 DISCUSSION

We have proposed *deep Bayes* as a generative classifier that uses deep latent variable models to model the joint distribution of input-output pairs. We have given evidence, on multiple classification tasks, that generative classifiers are more robust to adversarial attacks than discriminative classifiers. Furthermore, the logit in generative classifiers has a well defined meaning and can be used to detect attacks, even when the classifier is fooled.

Our results corroborate with the Bayesian neural network literature, in particular (Li & Gal, 2017; Feinman et al., 2017; Carlini & Wagner, 2017b), in showing that modelling unobserved variables are effective for defending against adversarial attacks[2]. In addition, we have also shown that the structure of the graphical model has a significant impact on robustness: deep LVM-based generative classifiers generally outperform the (randomised) discriminative ones.

While we have given strong evidence to suggest that generative classifiers are more robust to current adversarial attacks, we do not wish to claim that these models will be robust to *all* possible attacks. Aside from many recent attacks being designed specifically for discriminative neural networks, there is also evidence for the fragility of generative models; e.g. naive Bayes as a standard approach for spam filtering is well-known to be fragile (Dalvi et al., 2004; Huang et al., 2011), and very recently Tabacof et al. (2016); Kos et al. (2017); Creswell et al. (2017) also designed attacks for (unconditional) VAE-type models. However, generative classifiers can be made more robust too, to counter these weaknesses. Dalvi et al. (2004) have shown that generative classifiers can be made more secure if aware of the attack strategy, and Biggio et al. (2011; 2014) further improved naive Bayes' robustness by modelling the conditional distribution of the adversarial inputs. These approaches are similar to the adversarial training of discriminative classifiers, and efficient ways for doing so with generative classifiers can be an interesting research direction.

But even with this note of caution, we believe this work offers exciting avenues for future work. Using generative classifiers offers an interesting way to evaluate generative models and can drive improvements in their ability to tackle high-dimensional datasets, where traditionally generative classifiers have been less accurate than discriminative classifiers (Efron, 1975; Ng & Jordan, 2002). In addition, the combination of generative and discriminative models investigated in this paper is a compelling direction for future research. Overall, we believe that progress on generative classifiers can inspire better designs of attack, defence and detection techniques.

REFERENCES

Alexander A Alemi, Ian Fischer, Joshua V Dillon, and Kevin Murphy. Deep variational information bottleneck. In *International Conference on Learning Representations*, 2017.

---

[2]In Bayesian neural networks, the network weights are treated as unobserved/latent variables.

Moustafa Alzantot, Yash Sharma, Supriyo Chakraborty, and Mani Srivastava. Genattack: Practical black-box attacks with gradient-free optimization. *arXiv preprint arXiv:1805.11090*, 2018a.

Moustafa Alzantot, Yash Sharma, Ahmed Elgohary, Bo-Jhang Ho, Mani Srivastava, and Kai-Wei Chang. Generating natural language adversarial examples. *arXiv preprint arXiv:1804.07998*, 2018b.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. *arXiv preprint arXiv:1802.00420*, 2018.

Battista Biggio, Giorgio Fumera, and Fabio Roli. Design of robust classifiers for adversarial environments. In *Systems, Man, and Cybernetics (SMC), 2011 IEEE International Conference on*, pp. 977–982. IEEE, 2011.

Battista Biggio, Igino Corona, Davide Maiorca, Blaine Nelson, Nedim Šrndić, Pavel Laskov, Giorgio Giacinto, and Fabio Roli. Evasion attacks against machine learning at test time. In *Joint European conference on machine learning and knowledge discovery in databases*, pp. 387–402. Springer, 2013.

Battista Biggio, Giorgio Fumera, and Fabio Roli. Security evaluation of pattern classifiers under attack. *IEEE transactions on knowledge and data engineering*, 26(4):984–996, 2014.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *Security and Privacy (SP), 2017 IEEE Symposium on*, pp. 39–57. IEEE, 2017a.

Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, pp. 3–14. ACM, 2017b.

Nicholas Carlini and David Wagner. Audio adversarial examples: Targeted attacks on speech-to-text. *arXiv preprint arXiv:1801.01944*, 2018.

P. Y. Chen, Y. Sharma, H. Zhang, J. Yi, and C. Hsieh. Ead: Elastic-net attacks to deep neural networks via adversarial examples. *arXiv preprint arXiv:1709.0414*, 2017a.

P. Y. Chen, H. Zhang, Y. Sharma, J. Yi, and C. Hsieh. Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models. In *Proceedings of the 10th ACM Workshop on Artificial Intelligence and Security*, pp. 15–26. ACM, 2017b.

Thomas Cover and Peter Hart. Nearest neighbor pattern classification. *IEEE transactions on information theory*, 13(1):21–27, 1967.

Antonia Creswell, Anil A Bharath, and Biswa Sengupta. Latentpoison-adversarial attacks on the latent space. *arXiv preprint arXiv:1711.02879*, 2017.

Nilesh Dalvi, Pedro Domingos, Sumit Sanghai, Deepak Verma, et al. Adversarial classification. In *Proceedings of the tenth ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 99–108. ACM, 2004.

Yinpeng Dong, Fangzhou Liao, Tianyu Pang, Xiaolin Hu, and Jun Zhu. Discovering adversarial examples with momentum. *arXiv preprint arXiv:1710.06081*, 2017.

Bradley Efron. The efficiency of logistic regression compared to normal discriminant analysis. *Journal of the American Statistical Association*, 70(352):892–898, 1975.

Reuben Feinman, Ryan R Curtin, Saurabh Shintre, and Andrew B Gardner. Detecting adversarial samples from artifacts. *arXiv preprint arXiv:1703.00410*, 2017.

Ronald A Fisher. The use of multiple measurements in taxonomic problems. *Annals of human genetics*, 7(2):179–188, 1936.

Justin Gilmer, Luke Metz, Fartash Faghri, Samuel S Schoenholz, Maithra Raghu, Martin Wattenberg, and Ian Goodfellow. Adversarial spheres. *arXiv preprint arXiv:1801.02774*, 2018.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014.

Shixiang Gu and Luca Rigazio. Towards deep neural network architectures robust to adversarial examples. *arXiv preprint arXiv:1412.5068*, 2014.

Ling Huang, Anthony D Joseph, Blaine Nelson, Benjamin IP Rubinstein, and JD Tygar. Adversarial machine learning. In *Proceedings of the 4th ACM workshop on Security and artificial intelligence*, pp. 43–58. ACM, 2011.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Jernej Kos, Ian Fischer, and Dawn Song. Adversarial examples for generative models. *arXiv preprint arXiv:1702.06832*, 2017.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. *arXiv preprint arXiv:1607.02533*, 2016.

Alexey Kurakin, Ian Goodfellow, Samy Bengio, Yinpeng Dong, Fangzhou Liao, Ming Liang, Tianyu Pang, Jun Zhu, Xiaolin Hu, Cihang Xie, et al. Adversarial attacks and defences competition. *arXiv preprint arXiv:1804.00097*, 2018.

Anders Boesen Lindbo Larsen, Søren Kaae Sønderby, Hugo Larochelle, and Ole Winther. Autoencoding beyond pixels using a learned similarity metric. In *International Conference on Machine Learning*, pp. 1558–1566, 2016.

Yingzhen Li and Yarin Gal. Dropout inference in bayesian neural networks with alpha-divergences. In *International Conference on Machine Learning*, pp. 2052–2061, 2017.

Christos Louizos and Max Welling. Multiplicative normalizing flows for variational bayesian neural networks. *arXiv preprint arXiv:1703.01961*, 2017.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=rJzIBfZAb.

Andrew Y Ng and Michael I Jordan. On discriminative vs. generative classifiers: A comparison of logistic regression and naive bayes. In *Advances in neural information processing systems*, pp. 841–848, 2002.

Nicolas Papernot and Patrick McDaniel. Deep k-nearest neighbors: Towards confident, interpretable and robust deep learning. *arXiv preprint arXiv:1803.04765*, 2018.

Nicolas Papernot, Patrick McDaniel, and Ian Goodfellow. Transferability in machine learning: from phenomena to black-box attacks using adversarial samples. *arXiv preprint arXiv:1605.07277*, 2016a.

Nicolas Papernot, Patrick McDaniel, Somesh Jha, Matt Fredrikson, Z Berkay Celik, and Ananthram Swami. The limitations of deep learning in adversarial settings. In *Security and Privacy (EuroS&P), 2016 IEEE European Symposium on*, pp. 372–387. IEEE, 2016b.

Nicolas Papernot, Nicholas Carlini, Ian Goodfellow, Reuben Feinman, Fartash Faghri, Alexander Matyasko, Karen Hambardzumyan, Yi-Lin Juang, Alexey Kurakin, Ryan Sheatsley, Abhibhav Garg, and Yen-Chen Lin. cleverhans v2.0.0: an adversarial machine learning library. *arXiv preprint arXiv:1610.00768*, 2017a.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia Conference on Computer and Communications Security*, pp. 506–519. ACM, 2017b.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *International Conference on Machine Learning*, pp. 1278–1286, 2014.

Tim Salimans, Andrej Karpathy, Xi Chen, and Diederik P Kingma. Pixelcnn++: Improving the pixelcnn with discretized logistic mixture likelihood and other modifications. *arXiv preprint arXiv:1701.05517*, 2017.

Pouya Samangouei, Maya Kabkab, and Rama Chellappa. Defense-GAN: Protecting classifiers against adversarial attacks using generative models. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=BkJ3ibb0-.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*, 2014.

Lewis Smith and Yarin Gal. Understanding measures of uncertainty for adversarial example detection. In *Uncertainty in Artificial Intelligence*, 2018.

Yang Song, Taesup Kim, Sebastian Nowozin, Stefano Ermon, and Nate Kushman. Pixeldefend: Leveraging generative models to understand and defend against adversarial examples. *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=rJUYGxbCW.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Pedro Tabacof, Julia Tavares, and Eduardo Valle. Adversarial images for variational autoencoders. *arXiv preprint arXiv:1612.00155*, 2016.

Florian Tramèr, Alexey Kurakin, Nicolas Papernot, Ian Goodfellow, Dan Boneh, and Patrick McDaniel. Ensemble adversarial training: Attacks and defenses. *arXiv preprint arXiv:1705.07204*, 2017.

Aaron van den Oord, Nal Kalchbrenner, and Koray Kavukcuoglu. Pixel recurrent neural networks. In *International Conference on Machine Learning*, pp. 1747–1756, 2016.

A   MODEL ARCHITECTURES

MNIST experiments   The VAEs are constructed with convolutional encoders and deconvolutional generators. More specifically, the encoder network for $q(z|x, y)$ is the same across all VAE-based classifiers. It starts with a 3-layer convolutional neural network with 5×5 filters and 64 channels, with a max-pooling operation after each convolution. Then, the convolutional network is followed by a MLP with 2 hidden layers, each with 500 units, to produce the mean and variance parameters of q. The label y is injected into the MLP at the first hidden layer, as a one hot encoding (i.e. for MNIST, the first hidden layer has 500+10 units). The latent dimension is $\dim(z) = 64$.

The p models' architectures are the following:

  GFZ: For $p(y|z)$ we use a MLP with 1 hidden layer composed of 500 units. For $p(x|y, z)$ we used an MLP with 2 hidden layers, each with 500 units, and $4 \times 4 \times 64$ dimension output, followed by a 3-layer deconvolutional network with 5×5 kernel size, stride 2 and [64, 64, 1] channels.

  GFY: We use an MLP with 1 hidden layer composed of 500 units for $p(z|y)$, and the same architecture as GFZ for $p(x|y, z)$.

  DFZ: We use almost the same deconvolutional network architecture for $p(x|z)$ as GFZ's $p(x|y, z)$ network, except that the input is z only. For $p(y|x, z)$ we use almost the same architecture as $q(z|x, y)$ except that the injected input to the MLP is z and the MLP output is the set of logit values for y.

  DFX: We use the same architecture as G3 for $p(y|x, z)$. The network for $p(z|x)$ is almost identical except that there is no injected input to the MLP, and the network returns the mean and variance parameters for $q(z|x)$.

  DBX: We use GFZ's architecture for $p(y|z)$ and DFX's architecture for $p(z|x)$.

  GBY: We use GFY's architecture for $p(z|y)$ and DFZ's architecture for $p(x|z)$.

  GBZ: We use GFZ's architecture for $p(y|z)$ and DFZ's architecture for $p(x|z)$.

The BNN has almost the same architecture as the encoder network q, except that it uses 2x the hidden units/channels, and the last layer is 10 dimensions. Note that here we used dropout as it is convenient to implement, and we expect better approximate inference methods (such as stochastic gradient MCMC) to return better results for robustness and detection.

CIFAR plane-vs-frog experiments   The model architectures are almost the same as used in MNIST experiments, except that the hidden layer dimensions for the MLP layers are increased to 1000. For the encoder q, the channels are increased to [64, 128, 256]. For the p models, the deconvolutional networks have different channel values, [128, 64, 3], and the MLP before the deconvolution outputs a $4 \times 4 \times 256$ vector (before reshaping). The BNN has 2x the channels but still uses 1000 hidden units.

CIFAR-10 experiments   The pre-trained VGG16 network is downloaded from `https://github.com/geifmany/cifar-vgg`, where the CONV9 and FC1 layers correspond to:

CONV9: `https://github.com/geifmany/cifar-vgg/blob/master/cifar10vgg.py#L82`

  FC1: `https://github.com/geifmany/cifar-vgg/blob/master/cifar10vgg.py#L109`

The VAE-based classifiers build fully connected networks on top of the extracted features, and use $\dim(z) = 128$ for bottleneck. The encoder $q(z|\phi(x), y)$ has the network architectures $[\dim(\phi(x)) + \dim(y), 1000, 1000, \dim(z) \times 2]$, and we use the same encoder architecture across all classifiers. The decoder architectures are as follows:

  DBX: We use an MLP of layers $[\dim(z), 1000, \dim(y)]$ for $p(y|z)$ and an MLP of layers $[\dim(\phi(x)), 1000, 1000, \dim(z) \times 2]$ for $p(z|\phi(x))$.

Figure C.1: Accuracy and detection rates of DBX, GBY, and GBZ against PGD-based **perfect-knowledge** attack ($\epsilon = 0.1$) on CIFAR binary task. The solid area denotes accuracy and the hatched area denotes detection rate with each considered detector. Zero knowledge attacks are labelled '-ZK', other attack labels are the same as for the MNIST plot (Figure 5).

GBZ: We use an MLP of layers [dim($\boldsymbol{z}$), 1000, 1000, dim($\boldsymbol{y}$)] for $p(\boldsymbol{y}|\boldsymbol{z})$ and an MLP of layers [dim($\boldsymbol{z}$), 1000, 1000, dim($\boldsymbol{\phi}(\boldsymbol{x})$)] for $p(\boldsymbol{\phi}(\boldsymbol{x})|\boldsymbol{z})$.

GBY: We use an MLP of layers [dim($\boldsymbol{y}$), 1000, dim($\boldsymbol{z}$) $\times$ 2] for $p(\boldsymbol{z}|\boldsymbol{y})$ and GBZ's architecture for $p(\boldsymbol{\phi}(\boldsymbol{x})|\boldsymbol{z})$.

B ATTACK PARAMETERS

We use the Cleverhans package to perform attacks. We use the default hyper-parameters, if not specifically stated.

PGD: We perform the attack for 40 iterations with step-size 0.01.

MIM: We perform the attack for 40 iterations with step-size 0.01 and decay factor 1.0.

CW-ℓ_2: We use learning rate 0.01 and confidence 0, and we optimise the loss for 1000 iterations.

C FURTHER EXPERIMENTS

C.1 FURTHER EXPERIMENTS ON CIFAR BINARY CLASSIFICATION

White-box attack (perfect-knowledge, ℓ_∞) Figure C.1 shows the perfect knowledge attack on the CIFAR binary task. Again we see that although the attack is effective for the detection schemes, it comes with the price of decreased mis-classification rates. Interestingly GBY seems to be robust to this attack, where the accuracies on the crafted adversarial examples increase.

Grey-box attack We perform our grey-box experiments with exactly the same setting as done with MNIST. Figure C.2 shows that all the victim classifiers in test are robust to transferred attacks, with GBZ performing the best. Surprisingly, DBX is on par with other generative classifiers against PGD & MIM, and the discriminative classifiers are a bit most robust against grey-box CW. DFX performs the worst against the grey-box CW attack, although the difference is not significant. Again, the detection rates are low when the victim accuracies are high, indicating that grey-box attacks fail to generate near-manifold adversarial examples.

Black-box attack The setting is almost the same as done with MNIST, with the exception being that the initial query set $\mathcal{D}_1$ contains 200×2 datapoints ($12,800$ queries in total). The black-box substitutes achieve almost the same accuracy as their corresponding victim models on clean test datapoints. Figure C.2 shows that the victim classifiers are robust to the PGD/MIM transferred attacks. Interestingly, DBX is slightly less robust to the black-box CW attack compared to in the grey-box case, but again the difference is not significant. In general, black-box CW attacks return high victim accuracies and low detection rates, meaning that the crafted examples are close to the data manifold.

Figure C.2: Accuracy and detection rates against **grey-box (left)** and **black-box (right)** attacks on CIFAR plane-vs-frog. The higher the better.

Figure C.3: Results on **cross-model transfer** attacks on the CIFAR plane-vs-frog dataset. The horizontal axis corresponds to the source victim, and the vertical axis corresponds to the target victim. The higher (lighter) the better.

Cross-model attack transferability   Finally, we present the CIFAR cross-model attack transferability results in Figure C.3, and here we select $\epsilon = 0.1$ instead. Again, transferred attacks are less effective across the victim models. However, the TP rates for logit detection are significantly lower than in the MNIST case (also see Figure 8). Nevertheless, the detection rates for the "discriminative to generative" transfer are considerably higher. Combined with the accuracy results, we see that discriminative models as substitutes are ineffective in the transferred attack setting.

C.2   QUANTIFYING THE EFFECT OF THE BOTTLENECK LAYER

We see from the main text that classifiers with bottleneck structure may be preferred for resisting adversarial examples. To quantify this bottleneck effect, we train on MNIST models DBX, GBZ and GBY with z dimensions in $\{16, 32, 64, 128\}$ (the main text experiments use $\dim(z) = 64$).The clean test accuracy is shown in Table C.1, showing that all models in test perform reasonably well.

Table C.1: Clean test accuracy on MNIST classification (with varied bottleneck layer sizes).

	$\dim(z) = 16$	$\dim(z) = 32$	$\dim(z) = 64$	$\dim(z) = 128$
DBX	99.11%	99.01%	98.98%	98.91%
GBZ	97.11%	97.08%	97.45%	96.62%
GBY	98.82%	98.95%	98.72%	98.75%

We repeat the same **white-box zero-knowledge** ℓ_∞ attack experiments as done in the main text, where results are presented in Figure C.4 and Tables E.25, E.26 and E.27. It is clear that for discriminative classifiers, DBX, the models become less robust as the bottleneck dimension $\dim(z)$ increases. Interestingly DBX classifiers seem to be very robust against FGSM attacks, which agrees

Figure C.4: Accuracy and detection rates against **white-box zero-knowledge** ℓ_∞ attacks on MNIST, with varied bottleneck layer sizes.

Table D.1: Clean test accuracy on CIFAR plane-vs-frog classification.

BNN	GFZ	GFY	DFZ	DFX	DBX	GBZ	GBY
97.00%	91.60%	91.20%	94.85%	95.65%	96.00%	89.35%	90.65

with the results in Alemi et al. (2017). For the generative ones, we also observe similar trends (although much less significant) of decreased robustness for GBY classifiers, and for GBZ the trend is unclear, presumably due to local optimum issues in optimisation. In summary, GBZ classifiers are generally more robust compared to GBY classifiers. More importantly, when the accuracy of generative classifiers on adversarial images decreases to zero, the detection rates with marginal/logit detection increases to 100%. This clearly shows that the three attacks tested here cannot fool the generative classifiers without being detected.

D   ADDITIONAL RESULTS

We visualise in Figure D.1 the crafted adversarial images using white-box CW attack.

We present in Table D.1 the clean accuracy on CIFAR plane-vs-frog test images (2000 in total).

We present in Table D.2 the clean accuracy on CIFAR-10 test images.

Table D.2: Clean test accuracy on CIFAR-10 classification.

VGG16	GBZ-FC1	GBY-FC1	DBX-FC1	GBZ-CONV9	GBY-CONV9	DBX-CONV9
93.59%	92.55%	93.21%	93.49%	91.76%	88.33%	93.21%

(a) clean inputs   (b) adv. inputs (BNN)   (c) adv. inputs (GFZ)

(d) adv. inputs (GFY)   (e) adv. inputs (DFZ)   (f) adv. inputs (DFX)

(g) adv. inputs (DBX)   (h) adv. inputs (GBZ)   (i) adv. inputs (GBY)

Figure D.1: Visualising the clean inputs of MNIST and the CW adversarial examples crafted on all the classifiers.

E   RESULTS IN TABLES

We present in tables the full results of the experiments.

See Tables E.1 to E.9 for the white-box attacks.

See Tables E.10 to E.15 for the grey-box attacks.

See Tables E.16 to E.21 for the black-box attacks.

See Tables E.22 to E.24 for CIFAR-10 results with VGG-based classifiers.

See Tables E.25 to E.27 for bottleneck effect quantification results.

Table E.1: FGSM white-box zero-knowledge attack results on MNIST.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
BNN	92.4	67.8	40.5	26.2	20.4	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	93.0	94.2	95.4	95.5	96.5
GFZ	94.2	74.5	38.9	12.9	5.7	43.6	79.8	100.0	100.0	100.0	56.4	89.6	99.9	100.0	100.0	89.2	91.7	92.2	92.5	92.2
GBZ	92.5	80.3	62.0	42.4	27.2	37.0	81.7	100.0	100.0	100.0	57.6	93.5	100.0	100.0	100.0	91.6	90.9	90.3	91.1	91.5
GFY	94.3	74.8	46.5	21.7	10.5	53.1	92.6	100.0	100.0	100.0	66.2	97.9	100.0	100.0	100.0	90.8	93.1	93.8	94.2	94.2
GBY	93.6	76.4	47.5	22.3	10.7	41.9	84.5	100.0	100.0	100.0	57.7	92.5	100.0	100.0	100.0	89.3	92.7	92.8	92.9	92.9
DFX	70.1	14.8	1.0	0.4	0.6	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	93.6	93.8	93.8	93.5	94.3
DBX	91.6	77.8	58.1	44.5	36.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.6	93.6	95.2	96.3	97.0
DFZ	75.2	19.0	2.4	1.1	1.0	12.6	50.6	100.0	100.0	100.0	26.9	65.7	100.0	100.0	100.0	93.1	95.1	94.5	94.9	94.8

Table E.2: PGD white-box zero-knowledge attack results on MNIST.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
BNN	83.2	12.0	0.5	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.1	92.1	88.7	20.4	0.2
GFZ	86.7	37.7	7.7	1.2	0.3	43.2	71.8	91.4	99.4	100.0	55.8	77.1	94.8	99.6	100.0	90.3	92.1	90.9	90.4	89.7
GBZ	85.1	57.4	32.5	19.3	11.6	33.7	50.3	84.4	99.7	100.0	52.2	66.3	91.5	99.8	100.0	90.0	91.5	91.5	91.7	91.8
GFY	79.7	27.4	5.6	1.2	0.3	58.1	87.9	98.0	100.0	100.0	68.7	92.2	99.3	100.0	100.0	92.6	92.5	90.7	90.7	85.4
GBY	86.7	35.9	9.0	1.7	0.4	45.3	76.1	94.6	99.7	100.0	56.9	79.3	95.6	99.9	100.0	90.1	92.1	91.6	91.7	91.4
DFX	47.6	0.7	0.0	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.8	89.8	13.3	31.4	42.8
DBX	58.0	18.3	6.0	1.3	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.7	94.0	94.1	93.7	84.8
DFZ	49.6	1.0	0.0	0.0	0.0	11.8	44.3	94.1	100.0	100.0	25.9	57.6	94.5	99.9	100.0	93.9	89.8	12.1	22.9	28.0

Table E.3: MIM white-box zero-knowledge attack results on MNIST.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
BNN	82.0	7.2	0.1	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.2	91.1	72.0	64.5	7.1
GFZ	87.0	40.4	9.0	1.2	1.2	43.5	83.8	98.4	99.4	99.4	57.6	89.3	98.6	99.2	99.2	91.5	92.3	92.0	90.6	90.6
GBZ	79.6	27.4	5.6	1.5	0.5	36.1	86.3	100.0	100.0	100.0	53.5	93.1	99.9	100.0	100.0	91.3	91.4	91.9	92.2	92.7
GFY	80.8	30.1	6.8	1.4	1.4	56.0	93.7	99.8	100.0	100.0	68.1	96.6	99.9	100.0	100.0	90.9	92.4	92.0	91.6	91.6
GBY	84.9	22.9	1.5	0.1	0.0	47.4	91.2	99.9	100.0	100.0	59.8	92.8	99.9	100.0	100.0	91.4	92.1	91.2	86.8	29.0
DFX	48.4	0.8	0.0	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	93.2	89.6	9.2	17.5	17.5
DBX	66.7	28.7	19.7	17.2	17.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	93.5	94.3	94.6	94.7	94.7
DFZ	50.5	1.2	0.0	0.0	0.0	11.9	50.7	99.4	100.0	100.0	26.4	63.2	99.0	100.0	100.0	94.3	89.8	11.5	17.3	17.3

Table E.4: Perfect knowledge attacks on MNIST. This is done using the PGD attack with $\epsilon = 0.2$. 'ZK' stands for zero knowledge, 'PK0' where you have knowledge of the K samples but not of the detection system. 'PKM', 'PKL', and 'PKK' are attacks where you have knowledge of the K samples and of the marginal, logit and KL detection mechanisms respectively.

	ZK				PK0				PKM				PKL				PKK			
	acc.	TP marg.	TP logit	TP KL	acc.	TP marg.	TP logit	TP KL	acc.	TP marg.	TP logit	TP KL	acc.	TP marg.	TP logit	TP KL	acc.	TP marg.	TP logit	TP KL
DBX	18.3	N/A	N/A	94	17	N/A	N/A	93.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	35.9	N/A	N/A	93.9
GBZ	57.4	50.3	66.3	91.5	35.5	82.2	90.7	91.4	47.9	36.5	67.4	91.3	44.6	50.5	69.9	91.0	45	73.0	84.8	91.5
GBY	35.9	76.1	79.3	92.1	22	90.8	91.9	92.1	43.8	47.0	61.9	91.1	52.0	56.4	66.9	90.6	32.8	89.2	91.8	93.3

Table E.5: FGSM white-box zero-knowledge attack results on CIFAR plane-vs-frog binary classification.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
BNN	98.2	93.2	58.5	14.5	6.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	58.6	55.1	65.5	54.0	58.5
GFZ	97.1	94.7	81.8	56.4	31.4	11.4	10.1	5.9	17.4	99.3	11.4	10.4	6.8	17.2	99.3	58.6	40.1	35.9	41.0	50.6
GBZ	95.1	93.5	87.1	74.9	62.0	26.0	18.6	15.5	38.6	99.6	26.3	20.3	19.1	41.9	99.6	35.5	41.5	47.0	43.7	45.6
GFY	96.5	94.2	80.7	56.7	32.0	9.6	9.2	6.9	18.8	99.0	17.6	13.1	8.1	20.8	99.1	46.6	43.7	36.1	39.5	49.3
GBY	96.1	92.9	82.0	60.5	36.3	17.2	15.1	8.1	28.5	99.2	20.2	18.1	10.0	31.1	99.2	49.7	48.0	39.2	38.7	47.3
DFX	83.8	42.2	0.7	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	63.3	66.6	48.4	97.7	100.0
DBX	90.9	78.6	50.7	31.7	18.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	50.7	58.7	56.8	59.7	57.2
DFZ	83.9	52.1	2.9	0.0	0.0	6.6	3.8	2.2	3.9	60.6	6.9	4.2	2.4	3.3	60.4	57.5	62.3	54.8	66.7	99.8

Table E.6: PGD white-box zero-knowledge attack results on CIFAR plane-vs-frog binary classification.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
BNN	97.9	86.7	19.7	1.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	41.7	59.4	55.7	68.4	98.9
GFZ	98.0	93.9	67.7	21.7	3.5	3.3	6.6	5.6	7.8	32.9	5.0	9.5	6.0	8.2	33.0	37.5	45.1	34.5	44.0	57.7
GBZ	94.6	93.7	83.9	67.4	52.8	19.8	17.9	12.8	14.3	43.1	22.8	19.5	17.4	17.0	44.3	32.1	39.3	40.2	37.1	33.2
GFY	98.4	95.0	67.9	25.8	4.1	4.2	6.7	6.4	7.8	35.7	3.1	8.2	7.6	7.8	33.8	31.2	43.6	32.9	39.6	53.3
GBY	96.4	92.9	67.3	25.7	6.9	11.1	8.4	7.9	11.6	41.4	13.1	11.5	9.2	12.2	40.3	43.0	43.0	33.6	39.1	52.2
DFX	82.7	35.7	0.3	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	64.1	64.7	69.6	100.0	100.0
DBX	83.3	34.6	4.2	0.7	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	59.8	59.5	65.1	78.7	93.4
DFZ	82.4	36.9	0.4	0.0	0.0	4.9	3.8	5.1	12.3	91.1	6.5	4.1	5.5	12.3	91.3	56.3	60.3	54.7	99.7	100.0

Table E.7: MIM white-box zero-knowledge attack results on CIFAR plane-vs-frog binary classification.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
BNN	96.9	84.6	18.7	0.9	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	35.9	54.7	56.3	62.4	78.8
GFZ	96.9	91.5	58.1	15.2	1.9	6.5	6.2	6.4	10.6	86.1	10.0	8.3	6.6	11.3	84.5	31.0	39.0	32.1	47.2	77.1
GBZ	92.5	89.4	71.5	40.4	17.9	15.0	13.2	11.0	24.0	95.9	16.4	14.8	12.8	25.1	96.0	42.5	37.5	31.0	37.4	55.0
GFY	97.6	92.3	59.5	16.5	2.3	5.6	6.9	6.3	13.3	88.1	5.7	6.2	6.8	13.8	87.6	23.8	41.4	33.8	43.9	74.6
GBY	95.1	88.8	56.5	14.6	1.3	15.1	9.5	8.6	19.2	97.3	15.3	10.7	9.9	18.5	97.0	51.1	43.2	31.7	46.7	87.6
DFX	82.5	35.2	0.3	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	65.5	67.1	69.6	100.0	100.0
DBX	82.5	38.8	6.1	1.2	0.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	54.6	60.0	61.5	78.8	88.5
DFZ	81.5	36.1	0.4	0.0	0.0	5.4	3.9	5.0	13.4	96.9	6.2	4.1	5.5	13.8	96.8	61.1	58.5	55.3	99.9	100.0

Table E.8: CW white-box zero-knowledge attack results on CIFAR plane-vs-frog binary classification.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00
BNN	93.7	66.2	37.3	32.3	47.6	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	60.9	80.3	82.2	72.0	80.0
GFZ	99.5	95.6	76.5	77.9	78.3	0.0	4.5	2.6	3.0	3.4	0.0	4.6	3.0	3.6	4.2	29.2	30.4	25.6	27.1	29.0
GBZ	96.0	93.6	88.9	88.7	89.0	16.7	11.5	7.8	7.7	7.9	18.9	13.7	9.3	9.1	9.4	41.1	51.4	40.4	34.7	32.0
GFY	99.8	95.9	78.8	80.0	80.5	0.0	6.6	4.1	4.7	5.1	0.0	6.6	4.8	4.9	5.4	75.0	37.3	26.0	26.4	31.1
GBY	97.5	93.1	76.7	77.3	78.0	15.8	14.6	6.0	7.1	7.3	18.9	13.9	6.0	7.0	7.9	42.6	34.3	27.2	31.6	29.0
DFX	82.6	44.2	34.3	6.1	0.6	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	100.0	100.0	100.0	82.5	95.0
DBX	96.5	72.2	26.3	6.3	16.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	61.6	79.4	85.2	62.2	67.9
DFZ	94.5	72.3	29.9	6.3	17.9	7.3	5.8	4.3	4.1	4.2	14.1	6.9	5.0	4.4	4.4	82.6	97.3	97.1	83.0	80.2

Table E.9: Perfect knowledge attacks on CIFAR binary task. This is done using the PGD attack with $\epsilon = 0.1$. 'ZK' stands for zero knowledge, 'PK0' where you have knowledge of the K samples but not of the detection system. 'PKM', 'PKL', and 'PKK' are attacks where you have knowledge of the K samples and of the marginal, logit and KL detection mechanisms respectively.

	ZK				PK0				PKM				PKL				PKK			
	acc.	TP marg.	TP logit	TP KL	acc.	TP marg.	TP logit	TP KL	acc.	TP marg.	TP logit	TP KL	acc.	TP marg.	TP logit	TP KL	acc.	TP marg.	TP logit	TP KL
DBX	0.7	N/A	N/A	78.7	0.7	N/A	N/A	82.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	0.6	N/A	N/A	82.6
GBZ	67.4	14.3	17.0	37.1	57	40.6	45.1	49	58.4	9.6	18.5	46.9	58.5	1.8	7.8	47.8	59.9	25.5	27.6	42.4
GBY	25.7	11.6	12.2	39.1	28.5	22.0	22.6	49	29.5	5.6	7.6	45.9	29.2	0.8	1.8	45.4	27.9	15.6	15.9	45

Table E.10: Grey-box PGD attack results on MNIST.

	substitute acc					victim acc					TP logit				
ϵ	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
GFZ	86.7	14.3	0.0	0.0	0.0	96.6	83.3	51.3	26.8	17.2	49.5	73.8	99.7	100.0	100.0
GBZ	81.2	9.1	0.0	0.0	0.0	93.5	80.1	55.3	35.0	25.2	46.7	73.3	99.6	100.0	100.0
GFY	84.8	6.4	0.0	0.0	0.0	96.7	82.3	55.2	33.5	24.0	58.7	88.8	100.0	100.0	100.0
GBY	86.7	15.0	0.0	0.0	0.0	95.8	81.6	51.0	27.5	18.1	50.1	78.5	99.9	100.0	100.0
DFX	74.2	5.2	0.5	0.0	0.0	91.7	57.7	19.6	4.3	1.4	N/A	N/A	N/A	N/A	N/A
DBX	80.6	5.1	0.0	0.0	0.0	93.2	59.2	22.5	10.9	8.2	N/A	N/A	N/A	N/A	N/A
DFZ	69.6	3.4	0.3	0.0	0.0	91.9	57.2	21.4	6.3	2.6	33.6	55.1	91.7	100.0	100.0

Table E.11: Grey-box MIM attack results on MNIST.

	substitute acc					victim acc					TP logit				
ϵ	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
GFZ	87.2	16.1	0.0	0.0	0.0	96.5	82.4	42.8	14.2	3.7	50.6	82.5	100.0	100.0	100.0
GBZ	81.8	9.1	0.0	0.0	0.0	93.3	78.6	45.3	17.0	5.2	46.2	81.7	100.0	100.0	100.0
GFY	85.2	6.9	0.0	0.0	0.0	96.6	80.8	48.0	18.9	7.4	59.8	96.0	100.0	100.0	100.0
GBY	87.0	15.9	0.0	0.0	0.0	95.7	79.9	41.8	13.0	4.0	51.4	87.1	100.0	100.0	100.0
DFX	76.5	12.3	3.6	2.1	2.1	91.5	56.1	22.2	9.9	9.9	N/A	N/A	N/A	N/A	N/A
DBX	85.1	19.9	0.6	0.1	0.1	93.4	57.0	14.1	6.3	6.3	N/A	N/A	N/A	N/A	N/A
DFZ	70.9	3.2	0.0	0.0	0.0	91.8	54.6	16.4	2.7	0.3	34.5	63.8	98.9	100.0	100.0

Table E.12: Grey-box CW attack results on MNIST.

	substitute acc					victim acc					TP logit				
ϵ	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00
GFZ	98.4	4.6	0.0	0.0	0.0	98.8	96.9	96.0	93.4	90.2	53.4	44.2	41.6	40.6	43.7
GBZ	98.4	63.2	0.0	0.0	0.0	97.4	95.4	92.9	88.6	84.5	45.9	39.7	33.0	31.2	38.6
GFY	98.1	0.9	0.0	0.0	0.0	99.0	97.6	97.0	95.7	94.0	61.0	55.2	49.2	49.5	52.7
GBY	98.3	5.3	0.0	0.0	0.0	98.7	96.8	96.0	93.8	91.2	54.2	41.5	37.6	38.7	43.6
DFX	85.1	0.0	0.0	0.0	0.0	97.6	93.3	91.2	90.4	89.8	N/A	N/A	N/A	N/A	N/A
DBX	97.3	46.0	0.4	0.0	0.0	98.7	93.9	88.4	85.5	76.3	N/A	N/A	N/A	N/A	N/A
DFZ	80.5	0.0	0.0	0.0	0.0	97.2	94.6	92.3	91.5	91.2	32.9	28.6	28.1	36.5	44.5

Table E.13: Grey-box PGD attack results on CIFAR plane-vs-frog binary classification.

ϵ	substitute acc					victim acc					TP logit				
	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
GFZ	96.7	88.1	41.7	4.5	0.1	97.0	94.9	84.0	48.3	8.3	8.4	11.2	6.1	7.5	49.8
GBZ	92.9	83.1	37.8	5.5	0.0	95.3	94.8	91.8	83.1	65.6	15.5	12.8	10.9	19.9	79.8
GFY	96.9	88.1	33.7	3.3	0.1	96.9	95.9	85.3	54.2	12.7	2.6	2.0	5.0	8.5	61.2
GBY	95.2	85.6	32.4	2.8	0.1	96.8	95.3	86.4	59.8	18.5	21.8	14.3	10.5	12.5	75.2
DFX	95.7	80.8	10.1	0.2	0.0	99.1	96.7	79.4	28.3	0.9	N/A	N/A	N/A	N/A	N/A
DBX	95.7	80.5	30.5	1.7	0.0	99.5	98.2	91.1	65.1	21.8	N/A	N/A	N/A	N/A	N/A
DFZ	96.5	81.9	10.5	0.3	0.0	99.1	96.9	76.9	26.2	1.3	4.5	16.5	6.1	8.5	59.6

Table E.14: Grey-box MIM attack results on CIFAR plane-vs-frog binary classification.

ϵ	substitute acc					victim acc					TP logit				
	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
GFZ	96.3	87.9	42.1	4.7	0.1	97.1	94.8	83.0	44.8	4.9	8.7	11.1	5.8	8.5	75.1
GBZ	92.9	82.5	36.9	4.9	0.0	95.5	94.7	91.4	81.7	49.5	14.8	12.6	13.9	21.9	97.8
GFY	96.8	87.9	34.1	3.5	0.1	96.9	95.6	84.6	49.1	6.9	2.6	2.0	6.7	10.3	81.1
GBY	95.1	85.5	32.0	2.6	0.1	96.8	95.5	85.7	56.2	10.9	21.8	14.8	9.2	13.4	97.6
DFX	95.5	80.5	10.5	0.2	0.0	99.1	96.5	77.3	24.0	0.2	N/A	N/A	N/A	N/A	N/A
DBX	95.6	81.1	34.5	2.2	0.0	99.5	98.3	89.3	58.9	9.9	N/A	N/A	N/A	N/A	N/A
DFZ	96.3	81.5	10.7	0.5	0.0	99.1	96.9	74.9	21.9	0.3	4.5	16.6	6.4	9.9	80.2

Table E.15: Grey-box CW attack results on CIFAR plane-vs-frog binary classification.

ϵ	substitute acc					victim acc					TP logit				
	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00
GFZ	98.7	61.9	0.0	0.0	0.0	98.6	95.8	94.3	93.8	93.2	11.7	10.2	10.9	9.9	8.5
GBZ	96.3	69.8	3.3	0.0	0.0	95.9	95.7	94.7	94.7	94.5	13.5	12.7	12.3	13.7	14.4
GFY	98.4	54.4	0.0	0.0	0.0	98.1	96.1	95.3	95.1	94.3	0.0	2.2	3.7	4.6	7.6
GBY	97.6	52.9	2.2	0.0	0.0	97.7	95.6	94.5	94.3	93.7	25.8	15.7	14.2	13.7	18.0
DFX	64.4	0.0	0.0	0.0	0.0	98.5	97.2	97.1	96.7	95.5	N/A	N/A	N/A	N/A	N/A
DBX	91.3	56.2	0.3	0.0	0.0	99.7	99.0	99.0	98.9	98.1	N/A	N/A	N/A	N/A	N/A
DFZ	80.3	0.0	0.0	0.0	0.0	99.2	97.9	97.5	97.3	95.4	0.0	15.7	14.6	8.8	6.1

Table E.16: Black-box PGD attack results on MNIST.

ϵ	substitute acc					victim acc					TP logit				
	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
GFZ	44.2	0.7	0.0	0.0	0.0	97.3	88.4	62.7	33.8	21.8	48.7	61.0	92.3	99.8	100.0
GBZ	7.4	0.0	0.0	0.0	0.0	94.8	87.1	70.7	52.9	41.3	51.0	68.6	97.7	100.0	100.0
GFY	49.4	0.8	0.0	0.0	0.0	97.4	86.5	58.1	31.9	21.0	52.5	70.8	97.4	99.8	100.0
GBY	21.7	0.0	0.0	0.0	0.0	96.9	89.3	70.0	49.7	37.8	51.2	70.8	98.2	100.0	100.0
DFX	49.2	1.3	0.0	0.0	0.0	91.4	52.1	13.9	2.2	0.7	N/A	N/A	N/A	N/A	N/A
DBX	43.1	0.7	0.0	0.0	0.0	95.0	67.0	26.2	9.7	6.5	N/A	N/A	N/A	N/A	N/A
DFZ	53.8	1.7	0.0	0.0	0.0	92.9	56.3	15.2	3.4	1.5	34.7	52.8	94.0	99.9	100.0

Table E.17: Black-box MIM attack results on MNIST.

ϵ	substitute acc					victim acc					TP logit				
	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
GFZ	45.5	2.8	0.0	0.0	0.0	97.2	86.6	50.3	17.0	17.0	51.1	68.0	97.5	99.5	99.5
GBZ	8.4	0.0	0.0	0.0	0.0	94.7	85.9	63.5	35.2	17.1	51.2	74.4	99.0	100.0	100.0
GFY	53.1	2.5	0.3	0.1	0.1	97.2	83.7	49.2	20.1	20.1	55.1	80.6	99.0	99.9	99.9
GBY	24.5	0.0	0.0	0.0	0.0	96.8	88.3	62.8	31.7	13.3	49.3	77.6	99.9	100.0	100.0
DFX	51.3	2.3	0.1	0.0	0.0	91.4	51.7	13.3	1.9	1.9	N/A	N/A	N/A	N/A	N/A
DBX	47.8	1.6	0.1	0.0	0.0	94.8	67.0	23.2	7.6	7.6	N/A	N/A	N/A	N/A	N/A
DFZ	56.1	2.9	0.1	0.0	0.0	92.7	56.0	13.1	2.8	2.8	35.2	59.9	97.6	100.0	100.0

Table E.18: Black-box CW attack results on MNIST.

ϵ	substitute acc					victim acc					TP logit				
	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00
GFZ	65.2	0.3	0.0	0.0	0.0	98.8	98.7	97.4	94.3	92.0	52.3	50.8	39.6	44.7	55.3
GBZ	76.6	0.4	0.0	0.0	0.0	97.3	97.2	95.9	92.7	90.4	45.7	46.1	41.5	40.3	45.7
GFY	88.4	3.8	0.0	0.0	0.0	99.0	98.9	98.0	94.8	92.0	60.0	59.2	51.9	47.6	57.2
GBY	76.0	1.3	0.0	0.0	0.0	98.7	98.6	97.3	95.1	93.5	53.4	52.2	41.8	39.7	46.7
DFX	82.4	0.0	0.0	0.0	0.0	98.8	96.8	92.4	86.2	84.9	N/A	N/A	N/A	N/A	N/A
DBX	82.5	0.6	0.0	0.0	0.0	98.9	98.4	95.5	85.2	83.1	N/A	N/A	N/A	N/A	N/A
DFZ	86.5	0.2	0.0	0.0	0.0	98.8	94.5	89.3	81.5	79.3	42.9	25.5	22.3	27.7	38.2

Table E.19: Black-box PGD attack results on CIFAR plane-vs-frog binary classification.

ϵ	substitute acc					victim acc					TP logit				
	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
GFZ	95.5	89.9	45.5	6.8	0.1	97.6	95.6	88.7	68.8	29.7	6.2	6.7	6.0	10.8	71.8
GBZ	92.0	84.1	33.8	3.5	0.0	95.6	94.9	92.7	85.0	65.9	16.7	14.6	12.8	17.9	76.8
GFY	95.3	89.1	38.7	2.5	0.0	97.3	96.6	90.0	72.9	35.5	0.0	2.3	6.8	10.4	72.3
GBY	91.8	80.5	29.7	6.1	0.2	97.2	95.9	90.2	70.8	30.3	21.8	16.4	9.6	13.6	77.3
DFX	89.1	74.5	19.1	0.9	0.0	99.7	98.7	92.6	64.8	9.9	N/A	N/A	N/A	N/A	N/A
DBX	85.5	76.4	42.5	4.5	0.0	99.6	99.0	94.8	77.5	24.5	N/A	N/A	N/A	N/A	N/A
DFZ	85.5	73.5	21.1	1.5	0.0	99.5	99.2	93.8	70.1	15.1	0.0	5.0	8.9	15.9	85.1

Table E.20: Black-box MIM attack results on CIFAR plane-vs-frog binary classification.

ϵ	substitute acc					victim acc					TP logit				
	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
GFZ	95.5	89.7	46.4	7.7	0.2	97.5	95.7	88.5	66.5	20.5	6.2	6.7	5.9	12.7	82.7
GBZ	91.8	84.0	33.1	3.4	0.0	95.6	94.9	92.3	85.1	60.7	16.7	15.5	14.2	21.6	97.9
GFY	95.3	88.9	40.5	3.1	0.0	97.3	96.7	89.5	70.6	31.9	0.0	2.4	7.6	12.5	88.0
GBY	91.7	80.2	29.5	5.9	0.1	97.3	95.9	89.6	69.0	26.1	22.2	16.1	9.7	14.0	95.9
DFX	89.0	74.5	19.4	0.9	0.0	99.6	98.7	92.1	63.0	10.9	N/A	N/A	N/A	N/A	N/A
DBX	85.5	76.3	42.7	4.5	0.0	99.6	99.0	95.1	76.5	27.2	N/A	N/A	N/A	N/A	N/A
DFZ	85.3	73.4	21.4	1.6	0.0	99.6	99.1	92.9	67.7	14.9	0.0	4.5	7.5	14.2	91.9

Table E.21: Black-box CW attack results on CIFAR plane-vs-frog binary classification.

ϵ	substitute acc					victim acc					TP logit				
	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00	0.10	1.00	10.00	100.00	1000.00
GFZ	96.3	41.5	0.5	0.0	0.0	98.7	94.7	93.4	93.3	92.3	13.3	8.6	7.7	7.7	8.9
GBZ	94.9	73.3	1.4	0.0	0.0	95.9	95.3	94.6	94.5	94.5	13.5	11.8	11.8	13.2	13.1
GFY	96.4	62.0	1.3	0.0	0.0	98.1	96.7	94.8	94.7	94.1	0.0	2.8	6.5	6.1	6.8
GBY	93.5	33.6	1.7	0.0	0.0	97.7	95.9	95.4	95.4	95.0	25.8	16.4	15.9	18.6	19.8
DFX	90.3	10.9	0.0	0.0	0.0	99.9	98.8	98.5	98.5	97.9	N/A	N/A	N/A	N/A	N/A
DBX	87.2	31.8	0.0	0.0	0.0	99.9	97.1	94.5	93.9	94.7	N/A	N/A	N/A	N/A	N/A
DFZ	84.9	22.7	0.0	0.0	0.0	99.9	99.0	98.3	98.3	97.8	0.0	3.8	2.3	2.3	11.0

Table E.22: FGSM white-box zero-knowledge attack results on CIFAR-10.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
VGG16	44.5	25.8	16.6	11.9	10.1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	95.1	95.7	97.0	97.5	97.1
GBZ-FC1	63.7	49.7	34.3	18.9	12.7	60.0	62.4	80.6	90.9	94.1	63.7	65.0	80.6	95.0	98.4	90.1	90.8	92.3	92.6	92.6
GBY-FC1	64.9	50.0	36.1	19.5	11.3	52.2	59.0	80.4	90.1	92.5	54.6	61.9	80.3	95.6	98.4	90.7	91.3	92.1	92.4	90.3
DBX-FC1	57.3	45.7	31.8	16.3	10.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.8	93.2	94.0	94.3	92.8
GBZ-CONV9	81.6	74.1	58.5	48.9	45.8	13.7	17.0	28.4	76.0	90.2	18.3	20.6	31.7	64.3	71.6	91.7	91.5	91.7	93.3	86.4
GBY-CONV9	75.8	66.0	39.7	22.5	17.5	14.0	18.2	29.4	74.4	88.9	17.7	20.8	25.8	55.2	68.9	89.6	89.9	90.0	89.1	89.2
DBX-CONV9	59.0	45.7	31.8	17.8	11.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	93.7	94.1	94.9	95.2	93.7

Table E.23: PGD white-box zero-knowledge attack results on CIFAR-10.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
VGG16	18.8	0.6	0.0	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	93.9	91.8	67.4	69.9	66.4
GBZ-FC1	37.7	6.1	0.1	0.0	0.0	30.7	22.2	76.0	92.0	94.1	33.5	24.9	77.0	91.7	90.2	90.8	93.7	97.3	98.5	95.9
GBY-FC1	31.2	8.5	2.6	1.5	0.6	32.0	20.3	82.3	95.1	97.6	36.6	29.5	84.1	93.7	90.4	90.3	94.1	97.7	97.3	96.9
DBX-FC1	23.4	1.7	0.0	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	91.9	91.0	5.6	7.4	5.9
GBZ-CONV9	61.1	38.3	24.2	10.2	2.3	19.2	60.3	96.7	98.9	99.6	20.1	60.3	96.8	98.3	98.7	90.3	93.1	97.7	98.7	99.6
GBY-CONV9	66.5	26.6	3.2	0.4	0.0	17.0	55.6	95.7	99.2	99.6	17.8	52.7	95.3	98.6	97.6	89.6	91.8	98.7	99.4	96.9
DBX-CONV9	24.0	3.0	0.3	0.1	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	91.3	93.1	99.3	99.6	99.2

Table E.24: MIM white-box zero-knowledge attack results on CIFAR-10.

	acc. (adv)					TP marginal					TP logit					TP KL				
ϵ	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20	0.01	0.02	0.05	0.10	0.20
VGG16	13.1	0.4	0.0	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.2	92.4	72.3	77.1	79.0
GBZ-FC1	24.5	2.7	0.1	0.0	0.0	34.8	40.9	88.5	95.8	96.0	38.8	44.0	90.4	96.4	96.6	91.3	95.0	95.7	97.9	96.8
GBY-FC1	33.0	19.6	11.8	7.2	4.9	29.1	38.7	95.7	99.1	99.3	38.4	49.2	96.3	99.3	99.4	90.7	95.0	97.8	97.9	97.9
DBX-FC1	17.3	0.9	0.0	0.0	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	91.1	89.6	9.6	14.5	16.0
GBZ-CONV9	57.6	43.5	29.1	24.1	22.6	27.4	78.5	99.4	99.6	99.7	29.1	78.3	99.6	99.7	99.8	90.2	94.4	97.5	98.0	98.2
GBY-CONV9	39.1	18.1	4.3	1.9	1.5	25.6	70.4	98.6	99.6	99.8	28.2	71.1	98.6	99.7	99.8	89.6	94.5	99.4	99.8	99.7
DBX-CONV9	19.2	3.2	0.5	0.4	0.4	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.1	96.7	99.9	100.0	100.0

Table E.25: FGSM white-box zero-knowledge attack results on MNIST (with varied bottleneck layer sizes).

ϵ	acc. (adv)					TP marginal					TP logit					TP KL				
	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
DBX-16	92.6	85.6	76.4	64.7	52.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	90.3	92.4	92.3	92.7	94.2
DBX-32	92.6	84.4	71.1	57.2	46.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.2	92.3	92.8	94.9	95.0
DBX-64	91.6	77.8	58.1	44.5	36.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.6	93.6	95.2	96.3	97.0
DBX-128	87.8	47.6	20.1	12.7	10.3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	94.4	97.6	97.8	97.1	96.4
GBZ-16	92.0	75.8	52.5	34.0	21.7	28.7	71.5	99.9	100.0	100.0	49.2	86.3	99.9	100.0	100.0	90.8	90.6	92.0	91.9	90.9
GBZ-32	91.1	74.4	52.4	33.4	21.6	26.5	73.5	99.7	100.0	100.0	49.4	87.2	99.9	100.0	100.0	91.0	90.6	91.8	91.4	91.6
GBZ-64	92.5	80.3	62.0	42.4	27.2	37.0	81.7	100.0	100.0	100.0	57.6	93.5	100.0	100.0	100.0	91.6	90.9	90.3	91.1	91.5
GBZ-128	90.8	76.8	57.5	38.9	24.8	26.6	63.0	99.6	100.0	100.0	44.9	78.7	99.8	100.0	100.0	87.9	90.1	90.7	91.1	90.6
GBY-16	94.2	77.7	49.4	23.9	12.1	41.9	84.1	100.0	100.0	100.0	52.9	91.9	100.0	100.0	100.0	86.6	92.0	93.0	93.1	92.6
GBY-32	94.5	76.9	45.4	20.0	9.6	41.4	83.3	100.0	100.0	100.0	56.3	92.8	100.0	100.0	100.0	89.0	91.6	93.3	93.2	93.0
GBY-64	93.6	76.4	47.5	22.3	10.7	41.9	84.5	100.0	100.0	100.0	57.7	92.5	100.0	100.0	100.0	89.3	92.7	92.8	92.9	92.9
GBY-128	93.0	72.9	42.2	18.5	9.0	37.4	71.6	100.0	100.0	100.0	50.1	81.9	99.9	100.0	100.0	90.7	91.4	91.8	91.4	92.0

Table E.26: PGD white-box zero-knowledge attack results on MNIST (with varied bottleneck layer sizes).

ϵ	acc. (adv)					TP marginal					TP logit					TP KL				
	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
DBX-16	69.8	36.6	16.0	5.9	1.8	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	91.2	91.9	92.8	93.3	93.7
DBX-32	63.5	26.8	12.5	6.2	2.7	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	91.5	92.1	92.7	92.9	93.5
DBX-64	58.0	18.3	6.0	1.3	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	92.7	94.0	94.1	93.7	84.8
DBX-128	42.3	3.0	1.1	0.3	0.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	97.1	97.1	98.4	98.4	98.6
GBZ-16	88.3	62.8	37.4	23.1	15.5	27.1	35.8	71.9	98.9	100.0	46.3	53.0	82.3	99.3	100.0	89.6	91.7	92.3	91.4	91.8
GBZ-32	87.1	61.9	40.2	28.0	20.4	24.0	39.1	76.7	98.9	100.0	41.5	56.4	85.4	99.7	100.0	91.3	91.0	91.1	91.3	91.1
GBZ-64	85.1	57.4	32.5	19.3	11.6	33.7	50.3	84.4	99.7	100.0	52.2	66.3	91.5	99.8	100.0	90.0	91.5	91.5	91.7	91.8
GBZ-128	84.4	57.5	36.8	25.2	16.8	25.4	35.4	66.1	96.6	100.0	41.5	50.5	76.4	97.7	100.0	88.6	90.4	90.4	90.0	90.6
GBY-16	90.4	49.7	15.0	4.2	1.6	42.6	64.7	89.9	99.3	100.0	51.1	70.8	92.8	99.5	100.0	91.9	93.1	91.9	90.7	91.0
GBY-32	88.4	39.8	9.5	1.8	0.6	45.6	74.3	92.8	99.5	100.0	56.8	78.2	94.8	99.8	100.0	90.8	92.2	91.7	91.0	90.6
GBY-64	86.7	35.9	9.0	1.7	0.4	45.3	76.1	94.6	99.7	100.0	56.9	79.3	95.6	99.9	100.0	90.1	92.1	91.6	91.7	91.4
GBY-128	83.3	35.1	8.7	2.3	0.8	39.1	63.9	86.7	98.3	100.0	51.7	69.1	89.2	98.9	100.0	89.8	90.7	90.4	89.7	89.5

Table E.27: MIM white-box zero-knowledge attack results on MNIST (with varied bottleneck layer sizes).

ϵ	acc. (adv)					TP marginal					TP logit					TP KL				
	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50	0.10	0.20	0.30	0.40	0.50
DBX-16	72.2	37.1	20.7	14.7	11.7	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	91.8	92.3	92.8	93.4	93.9
DBX-32	66.7	27.6	16.8	12.5	10.6	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	91.8	92.5	92.4	93.2	93.5
DBX-64	66.7	28.7	19.7	17.2	17.2	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	93.5	94.3	94.6	94.7	94.7
DBX-128	42.3	1.3	0.2	0.1	0.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	97.2	97.6	98.6	98.9	99.1
GBZ-16	83.8	36.4	8.9	2.3	0.9	26.9	79.8	99.7	100.0	100.0	43.3	88.0	99.8	100.0	100.0	91.6	92.1	91.2	91.6	92.6
GBZ-32	82.7	35.5	9.5	3.0	1.1	26.6	83.2	99.7	100.0	100.0	45.8	90.0	99.8	100.0	100.0	90.3	91.7	91.4	92.5	92.6
GBZ-64	79.6	27.4	5.6	1.5	0.5	36.1	86.3	100.0	100.0	100.0	53.5	93.1	99.9	100.0	100.0	91.3	91.4	91.9	92.2	92.7
GBZ-128	79.2	32.1	8.7	2.6	1.2	26.1	68.5	99.2	100.0	100.0	41.2	79.1	99.4	100.0	100.0	89.7	91.5	91.4	91.4	92.5
GBY-16	89.2	34.6	3.5	0.2	0.0	44.8	88.1	99.8	100.0	100.0	55.9	91.7	99.7	100.0	100.0	89.4	92.5	91.0	90.6	36.9
GBY-32	86.7	25.8	1.6	0.1	0.0	45.1	91.2	100.0	100.0	100.0	58.6	94.0	100.0	100.0	100.0	90.9	91.8	91.1	68.6	31.1
GBY-64	84.9	22.9	1.5	0.1	0.0	47.4	91.2	99.9	100.0	100.0	59.8	92.8	99.9	100.0	100.0	91.4	92.1	91.2	86.8	29.0
GBY-128	82.1	23.7	1.9	0.0	0.0	40.4	83.0	99.7	100.0	100.0	51.7	87.5	99.6	100.0	100.0	91.2	91.2	89.8	82.8	44.4