META-LEARNING WITH DIFFERENTIABLE CLOSED-FORM SOLVERS

ABSTRACT

Adapting deep networks to new concepts from few examples is challenging, due to the high computational and data requirements of standard fine-tuning procedures. Most work on few-shot learning has thus focused on simple learning techniques for adaptation, such as nearest neighbours or gradient descent. Nonetheless, the machine learning literature contains a wealth of methods that learn non-deep models very efficiently. In this work we propose to use these fast convergent methods as the main adaptation mechanism for few-shot learning. The main idea is to teach a deep network to use standard machine learning tools, such as logistic regression, as part of its own internal model, enabling it to quickly adapt to novel tasks. This requires back-propagating errors through the solver steps. While normally the cost of the matrix operations involved in such process would be significant, by using the Woodbury identity we can make the small number of examples work to our advantage. We propose both closed-form and iterative solvers, based on ridge regression and logistic regression components. Our methods constitute a simple and novel approach to the problem of few-shot learning and achieve performance competitive with or superior to the state of the art on three benchmarks.

1 INTRODUCTION

While modern machine learning techniques thrive on big data, applying them to low-data regimes should certainly be possible. For example, humans can easily perform *fast mapping* (Carey, 1978; Carey & Bartlett, 1978), i.e. learning a new concept after only a single exposure. By contrast, supervised learning algorithms — and neural networks in particular — typically need to be trained using a vast amount of data in order to generalize well. This is problematic, as the availability of large labelled datasets cannot always be taken for granted. Labels can be costly to acquire: in drug discovery, for instance, researchers are often limited to characterizing only a handful of compounds (Altae-Tran et al., 2017). In other circumstances, data itself can be scarce. This can happen for example with the task of classifying rare animal species, whose exemplars are not easy to observe. Such a scenario, in which just one or a handful of training examples is provided, is referred to as *few-shot learning* (Fei-Fei et al., 2006; Lake et al., 2015; Hariharan & Girshick, 2017) and has recently seen a tremendous surge in interest within the machine learning community (e.g. Vinyals et al. (2016); Bertinetto et al. (2016); Ravi & Larochelle (2017); Finn et al. (2017)).

Currently, most methods tackling few-shot learning operate within the general paradigm of *meta-learning*, which allows us to develop algorithms in which the process of learning can improve with the number of tasks (Thrun, 1998; Vilalta & Drissi, 2002). This can be achieved by distilling knowledge about learning (i.e. meta-knowledge) and transferring this knowledge across tasks. In practice, for the problem of few-shot classification, meta-learning is often implemented using two "nested training loops". The *base learner* works at the level of individual *episodes*, which correspond to learning problems characterised by having only a small set of labelled training images available. The *meta learner*, by contrast, learns from a collection of such episodes, with the goal of improving the performance of the base learner across tasks.

Clearly, in any meta-learning algorithm it is of paramount importance to choose the base learner carefully. On one side of the spectrum, methods related to nearest-neighbours, such as learning similarity functions (Koch et al., 2015; Vinyals et al., 2016; Snell et al., 2017) and learning how to access a memory module (Santoro et al., 2016; Kaiser et al., 2017; Munkhdalai & Yu, 2017), are fast

Figure 1: Diagram of the proposed method for one episode (task), of which several are seen during meta-training. The task is to learn *new* classes given just few sample images per class. In this illustrative example, there are 3 classes and 2 samples per class, making each task a 3-way, 2-shot classification problem. At the base learning level, learning is accomplished by a differentiable ridge regression layer (R.R.), which computes task-specific weights (referred to as $w_{\mathcal{T}}$ in Section 3.1 and as W in Section 3.2). At the meta-training level, by back-propagating errors through many of these small learning tasks, we train a network whose weights are shared across episodes, together with the hyper-parameters of the R.R. layer. In this way, the R.R. base learner can improve its learning capabilities as the number of experienced tasks increases.

but rely solely on the quality of the similarity metric, with no additional data-dependent adaptation at test-time. On the other side of the spectrum, methods that optimize standard iterative learning algorithms, such as backpropagating through gradient descent (Finn et al., 2017; Nichol et al., 2018) or explicitly learning the learner's update rule (Hochreiter et al., 2001; Andrychowicz et al., 2016; Ravi & Larochelle, 2017), are accurate but slow.

In this paper, we take a different perspective. As base learners, we propose to adopt simple learning algorithms that admit a closed-form solution such as Ridge Regression. Crucially, the simplicity and differentiability of these solutions allow us to backpropagate through learning problems, achieving meta-learning. Moreover, these algorithms are particularly suitable for use within a meta-learning framework for few-shot classification for two main reasons. First, differently from iterative base learners, their closed-form solution allows tasks to be solved efficiently. Second, in a data regime characterized by few examples of high dimensionality, the Woodbury's identity (Petersen et al., 2008, Chapter 3.2) can be used to obtain a very significant gain in terms of computation speed.

We demonstrate the strength of our approach by performing extensive experiments on Omniglot (Lake et al., 2015), CIFAR-100 (Krizhevsky & Hinton, 2009) (adapted to the few-shot task) and mini-ImageNet (Vinyals et al., 2016). Our base learners are fast, simple to implement, and can achieve performance that is competitive with or superior to the state of the art in terms of accuracy.

2   RELATED WORK

The concept of meta-learning (i.e. learning to learn) has been of great importance in the machine learning community for several decades, with first examples appearing already in the eighties (Utgoff, 1986; Schmidhuber, 1987). Perhaps the simplest approach to meta-learning is to train a similarity function by exposing it to many "matching" tasks (Bromley et al., 1993; Chopra et al., 2005; Koch et al., 2015). Despite its simplicity, this general strategy is particularly effective and it is at the core of several state of the art few-shot classification algorithms (Vinyals et al., 2016; Snell et al., 2017; Sung et al., 2018). Interestingly, Garcia & Bruna (2018) interpret learning as information propagation from support (training) to query (test) images and propose a graph neural network that can generalize matching-based approaches. Since this line of work relies on learning a similarity

metric, one distinctive characteristic is that parameter updates only occur within the long time horizon of the meta-learning loop. While this can clearly spare costly computations, it also prevents these methods from performing adaptation at test time. A possible way to overcome the lack of adaptability is to train a neural network capable of predicting (some of) its own parameters. This technique has been first introduced in Schmidhuber (1992; 1993) and recently revamped by Bertinetto et al. (2016) and Munkhdalai & Yu (2017), with application to object tracking and few-shot classification. Rebuffi et al. (2017) show that a similar approach can be used to adapt a neural network, on the fly, to completely different visual domains.

Another popular approach to meta-learning is to interpret the gradient update of SGD as a parametric and learnable function (Bengio et al., 1992) rather than a fixed ad-hoc routine. Younger et al. (2001) and Hochreiter et al. (2001) observe that, because of the sequential nature of a learning algorithm, a recurrent neural network can be considered as a meta-learning system. They identify LSTMs as particularly apt for the task because of their ability to span long-term dependencies, which are important in order to meta-learn. A modern take on this idea has been presented by Andrychowicz et al. (2016) and Ravi & Larochelle (2017), showing benefits on classification and style transfer.

A recent and promising research direction is the one set by Maclaurin et al. (2015) and by the MAML algorithm (Finn et al., 2017; Finn & Levine, 2018). Instead of explicitly designing a meta-learner module to learn the update rule, they backpropagate through the very operation of gradient descent to optimize for the hyperparameters or the initial parameters of the learner. However, back-propagation through gradient descent steps is costly in terms of memory, and thus the total number of steps must be kept small.

In order to alleviate the drawback of catastrophic forgetting typical of deep neural networks (Mc-Closkey & Cohen, 1989), several recent methods (Santoro et al., 2016; Kaiser et al., 2017; Munkhdalai & Yu, 2017; Sprechmann et al., 2018) make use of memory-augmented models, which can first retain and then access important and previously unseen information associated with newly encountered tasks. While such memory modules store and retrieve information in the long time range, approaches based on attention like the one of Vinyals et al. (2016) are useful to specify the most relevant pieces of knowledge within a task. Mishra et al. (2018) complement soft attention with temporal convolutions, thus allowing the attention mechanism to access information related to past episodes.

In this paper, we take a different path compared to previous work and instead argue for simple, fast and differentiable base learners such as ridge regression. Compared to nearest-neighbour methods, they allow more flexibility because they produce a different set of parameters for different tasks (W_i in Figure 1). Compared to methods that adapt SGD, they exhibit an inherently fast rate of convergence, particularly in cases where a closed form solution exists. In similar spirit, Valmadre et al. (2017) propose a method to backpropagate through the solution of a closed-form problem. However, they resort to the Correlation Filter algorithm (Kumar et al., 2005), whose application is limited to scenarios in which the data matrix is circulant, such as object detection and tracking.

Our work is also related to multi-task learning (Caruana, 1998). Examples of this paradigm focused on kernel methods (e.g. Argyriou et al. (2007); Evgeniou & Pontil (2004)) and recently on deep neural networks (Ruder, 2017). A crucial difference between the multi-task and meta-learning paradigms is that, while the former is used to train methods on different tasks simultaneously, the latter allows us to deal with previously unseen tasks. In other words, multi-task learning operates in a closed-set world (where all tasks are known), and meta-learning in an open-set world (with unknown tasks).

3 METHOD

3.1 META-LEARNING

The goal of meta-learning is to enable a base learning algorithm to adapt to new tasks efficiently by generalizing from a set of training tasks $\mathcal{T} \in \mathbb{T}$. Each task (or episode) typically consists of a probability distribution of example inputs $x \in \mathbb{R}^m$ and outputs $y \in \mathbb{R}^o$, $(x, y) \sim \mathcal{T}$. In the case of few-shot classification, the inputs are represented by few images belonging to different unseen classes, while the outputs are the (task-specific) class labels. It is important not to confuse the small sets that are used in an episode/task $\mathcal{T}$ with the super-set $\mathbb{T}$ (such as Omniglot or miniImageNet, Section 4.1) from which they are drawn.

Consider a generic feature extractor, such as commonly used pre-trained networks $\phi(x) : \mathbb{R}^m \to \mathbb{R}^e$ (note that in practice we do not use pre-trained networks, but are able to train them from scratch). Then, a much simpler task-specific predictor $f(x \,|\, w_\mathcal{T}) : \mathbb{R}^e \times \mathbb{R}^p \to \mathbb{R}^o$ can be trained to map input embeddings to outputs. The predictor is parameterized by a set of parameters $w_\mathcal{T} \in \mathbb{R}^p$, which are specific to the task $\mathcal{T}$. For example, the predictor might be trained for the task of character recognition in the Roman alphabet, as opposed to the Greek one, which would represent another task.

To train and assess the predictor on a task, we are given access to training samples $Z_\mathcal{T} = \{(x_i, y_i)\} \sim \mathcal{T}$ and test samples $Z'_\mathcal{T} = \{(x'_i, y'_i)\} \sim \mathcal{T}$, sampled independently from the distribution $\mathcal{T}$. We can then use a learning algorithm Λ to obtain the parameters $w_\mathcal{T} = \Lambda(\phi(Z_\mathcal{T}))$. With slight abuse of notation, the learning algorithm thus applies ϕ to the sample inputs in $Z_\mathcal{T}$. The expected quality of the trained predictor is then computed by a standard loss or error function $L : \mathbb{R}^o \times \mathbb{R}^o \to \mathbb{R}$, which is evaluated on the test samples $Z'_\mathcal{T}$:

$$q(\mathcal{T}) = \frac{1}{|Z'_\mathcal{T}|} \sum_{(x,y) \in Z'_\mathcal{T}} L\left(f\left(\phi\left(x\right) \,|\, w_\mathcal{T}\right), y\right), \quad \text{with } w_\mathcal{T} = \Lambda(\phi(Z_\mathcal{T})). \tag{1}$$

Other than abstracting away the complexities of the learning algorithm as Λ, eq. (1) corresponds to the standard train-test protocol commonly employed in machine learning, here applied to a single task $\mathcal{T}$. However, simply re-training a predictor for each task ignores potentially useful knowledge that can be transferred between them. For this reason, we now take the step of parameterizing ϕ and Λ with two sets of *meta-parameters*, respectively ω and ρ, which can aid the training procedure. In particular, ω affects the representation of the input of the base learner algorithm Λ, while ρ corresponds to its hyper-parameters, which here can be learnt by the meta-learner loop instead of being manually set as it usually happens in a standard training scenario. These meta-parameters will affect the generalization properties of the learned predictors. This motivates evaluating the result of training on a held-out test set $Z'_\mathcal{T}$ (eq. (1)). In order to learn ω and ρ, we minimize the expected loss on held-out test sets over all tasks $\mathcal{T} \in \mathbb{T}$:

$$\min_{\omega, \rho} \frac{1}{|\mathbb{T}| \cdot |Z'_\mathcal{T}|} \sum_{\mathcal{T} \in \mathbb{T}} \sum_{(x,y) \in Z'_\mathcal{T}} L\left(f\left(\phi\left(x \,|\, \omega\right) \,|\, w_\mathcal{T}\right), y\right), \quad \text{with } w_\mathcal{T} = \Lambda(\phi(Z_\mathcal{T} \,|\, \omega) \,|\, \rho). \tag{2}$$

Since eq. (2) consists of a composition of non-linear functions, we can leverage the same tools used successfully in deep learning, namely back-propagation and stochastic gradient descent (SGD), to optimize it. The main obstacle is to choose a learning algorithm Λ that is amenable to optimization with such tools. This means that, in practice, Λ must be quite simple.

Examples of meta-learning algorithms. Note that, according to widely accepted definitions of learning (Mitchell, 1980) and meta-learning (Vilalta & Drissi, 2002; Vinyals et al., 2016), an algorithm is "learning to learn" if it can improve its learning skills with the number of experienced tasks (by modifying its bias, or prior).

Using eq. 2, it is possible to describe several of the meta-learning methods in the literature, which mostly differ for the choice of Λ. The feature extractor ϕ is typically a standard CNN, whose intermediate layers are trained jointly as ω (and thus are not task-specific). The last layer represents the linear predictor f, with task-specific parameters $w_\mathcal{T}$. In Siamese networks (Bromley et al., 1993; Chopra et al., 2005; Koch et al., 2015), f is a nearest neighbour classifier, generalized to k-nearest neighbours in Ren et al. (2018) The Learnet (Bertinetto et al., 2016) uses a factorized CNN or MLP to implement Λ, while MAML (Finn et al., 2017) implements it using SGD (and furthermore adapts all parameters of the CNN). In addition to learning ω, some works (Andrychowicz et al., 2016; Ravi & Larochelle, 2017) also learn the hyper-parameters of the base learner ρ.

We propose a different strategy and use closed-form optimization methods as base learner Λ, namely least-squares based solutions for ridge regression and logistic regression. In the outer loop, we allow SGD to learn both the parameters ω of the feature representation of Λ and its hyper-parameters ρ.

3.2 EFFICIENT RIDGE REGRESSION BASE LEARNERS

Similarly to the methods discussed in Section 3.1, over the course of a *single* episode/task we adapt a linear predictor f, which can be considered as the final layer of a CNN. The remaining layers ϕ are trained from scratch to generalize between tasks by the outer loop of meta-learning (eq. 2), but

for the purposes of one task they are considered fixed. In this section we assume that the inputs were pre-processed by the CNN ϕ, and that we are dealing only with the final linear predictor $f(x) = xW \in \mathbb{R}^o$, where the parameters $w_\mathcal{T}$ are reorganized into a matrix $W \in \mathbb{R}^{e \times o}$.

The motivation for our work is that, while not quite as simple as nearest neighbours, least-squares regressors admit closed-form solutions. Although simple least-squares is prone to overfitting, it is easy to augment it with L^2 regularization (controlled by a positive hyper-parameter λ), in what is known as ridge regression:

$$\Lambda(Z) = \arg\min_W \|XW - Y\|^2 + \lambda \|W\|^2 \tag{3}$$

$$= (X^T X + \lambda I)^{-1} X^T Y, \tag{4}$$

where $X \in \mathbb{R}^{n \times e}$ and $Y \in \mathbb{R}^{n \times o}$ contain the n sample pairs of input embeddings and outputs from Z, stacked as rows.

Because ridge regression admits a closed form solution (eq. (4)), it is relatively easy to integrate into meta-learning (eq. (2)) using standard automatic differentiation packages. The only element that may have to be treated more carefully is the matrix inversion. When the matrix to invert is close to singular (which we do not expect when $\lambda > 0$), it is possible to achieve more numerically accurate results by replacing the matrix inverse and vector product with a linear system solver (Murphy, 2012, 7.5.2). In our experiments, the matrices were not close to singular and we did not find this necessary.

Another concern about eq. (4) is that the intermediate matrix $X^T X \in \mathbb{R}^{e \times e}$ grows *quadratically* with the embedding size e. Given the high dimensionality of features typically used in deep networks, the inversion could come at a very expensive cost. To alleviate this, we rely on the Woodbury formula (Petersen et al., 2008, Chapter 3.2), obtaining:

$$W = \Lambda(Z) = X^T (XX^T + \lambda I)^{-1} Y. \tag{5}$$

The main difference between eq. (4) and eq. (5) is that the intermediate matrix $XX^T \in \mathbb{R}^{n \times n}$ only grows quadratically with the number of samples in the task, n. As we are interested in one or few-shot learning, this is typically very small. The overall cost of eq. (5) is only linear in the embedding size e.

Although this method was originally designed for regression, we found that it works well also in a (few-shot) classification scenario, where the target outputs are one-hot vectors representing classes. However, since eq. 4 does not directly produce classification labels, it is important to calibrate its output for the cross-entropy loss, which is used to evaluate the task's test samples (L in eq. 2). This can be done by simply adjusting our prediction $X'W$ with a scale and a bias $\alpha, \beta \in \mathbb{R}$:

$$\widehat{Y} = \alpha X'W + \beta. \tag{6}$$

Note that λ, α and β are hyper-parameters of the base learner Λ and can be learnt by the outer learning loop represented by the meta-learner, together with the CNN parameters ω.

3.3 ITERATIVE BASE LEARNERS AND LOGISTIC REGRESSION

It is natural to ask whether other learning algorithms can be integrated as efficiently as ridge regression within our meta-learning framework. In general, a similar derivation is possible for iterative solvers, as long as the operations are differentiable. For linear models with convex loss functions, a better choice than gradient descent is Newton's method, which uses curvature (second-order) information to reach the solution in very few steps. One learning objective of particular interest is logistic regression, which unlike ridge regression directly produces classification labels, and thus does not require the use of calibration before the (binary) cross-entropy loss.

When one applies Newton's method to logistic regression, the resulting algorithm takes a familiar form — it consists of a series of weighted least squares (or ridge regression) problems, giving it the name Iteratively Reweighted Least Squares (IRLS) (Murphy, 2012, Chapter 8.3.4). Given inputs $X \in \mathbb{R}^{n \times e}$ and binary outputs $y \in \{-1, 1\}^n$, the i-th iteration updates the parameters $w_i \in \mathbb{R}^e$ as:

$$w_i = \left(X^T \mathrm{diag}(d) X + \lambda I\right)^{-1} X^T \mathrm{diag}(d) \bar{y}, \tag{7}$$

where I is an identity matrix, $d = p(1 - p)$, $\bar{y} = p + (y - p)/d$, and $p = \sigma(w_{i-1}^T X)$ applies a sigmoid function σ to the predictions using the previous parameters w_{i-1}.

Since eq. (7) takes a similar form to ridge regression, we can use it for meta-learning in the same way as in section 3.2, with the difference that a small number of steps (eq. (7)) must be performed in order to obtain the final parameters $w_\mathcal{T}$. Similarly, we obtain a solution with a cost which is linear rather than quadratic in the embedding size by employing the Woodbury formula:

$$w_i = X^T \Big(X X^T + \lambda \mathrm{diag}(d)^{-1} \Big)^{-1} \bar{y},$$

where the inner inverse has negligible cost since it is a diagonal matrix. Note that a similar strategy could be followed for other learning algorithms based on IRLS, such as L^1 minimization and LASSO. We take logistic regression to be a sufficiently illustrative example, of particular interest for binary classification in one/few-shot learning, leaving the exploration of other variants for future work.

3.4 TRAINING POLICY

Figure 1 illustrates our overall framework. Like most meta-learning techniques, we organize our training procedure into *episodes*, each of which corresponds to a few-shot classification task. In standard classification, training requires sampling from a distribution of images and labels. Instead, in our case we sample from a distribution of tasks, each containing its own training set and test set, with just few samples per image. Each episode also contains two sets of labels: Y and Y'. The former is used to train the base learner, while the latter to compute the error of the just-trained base learner, enabling back-propagation in order to learn ω, λ, α and β.

In our implementation, one episode corresponds to a SGD mini-batch of size $S = N(K + Q)$, where N is the number of different classes ("ways"), K the number of samples per classes ("shots") and Q the number of query (or test) images per class.

4 EXPERIMENTS

In this section, we provide practical details for the two novel methods introduced in Section 3.2 and 3.3, which we dub R2-D2 (*Ridge Regression Differentiable Discriminator*) and LR-D2 (*Logistic Regression Differentiable Discriminator*). We analyze their performance against the recent literature on multinomial and binary classification problems using three few-shot learning benchmarks: Omniglot (Lake et al., 2015), miniImageNet (Vinyals et al., 2016) and CIFAR-FS, which we introduce in this paper. The code for both our methods and the splits of CIFAR-FS will be made available online.

4.1 FEW-SHOT LEARNING BENCHMARKS

Let $I_\star$ and $C_\star$ be respectively the set of images and the set of classes belonging to a certain data split $\star$. In standard classification datasets, $I_{\text{train}} \cap I_{\text{test}} = \varnothing$ and $C_{\text{train}} = C_{\text{test}}$. Instead, the few-shot setup requires both $I_{\text{meta-train}} \cap I_{\text{meta-test}} = \varnothing$ and $C_{\text{meta-train}} \cap C_{\text{meta-test}} = \varnothing$, while within a task we have $C_{\text{task-train}} = C_{\text{task-test}}$.

Omniglot (Lake et al., 2015) is a dataset of handwritten characters that has been referred to as the "MNIST transpose" for its high number of classes and small number of instances per class. It contains 20 examples of 1623 characters, grouped in 50 different alphabets. In order to be able to compare against the state of the art, we adopt the same setup used in Vinyals et al. (2016). Hence, we resize images to 28×28, we sample character classes independently from the alphabet and we augment the dataset using four rotated versions of the each instance ($0°, 90°, 180°, 270°$). Including rotations, we use 4800 classes for meta-training and meta-validation and 1692 for meta-testing.

miniImageNet (Vinyals et al., 2016) aims at representing a challenging dataset without demanding large computational resources. It is randomly sampled from ImageNet (Russakovsky et al., 2015) and it is constituted by a total of 60,000 images from 100 different classes, each with 600 instances. All images are RGB and have been downsampled to 84×84. As all recent work, we adopt the same splits of Ravi & Larochelle (2017), who employ 64 classes for meta-training, 16 for meta-validation and 20 for meta-testing.

CIFAR-FS. On the one hand, despite being lightweight, Omniglot is becoming too simple for modern few-shot learning methods, especially with the splits of Vinyals et al. (2016). On the other, miniImageNet is more challenging, but it might still require a model to train for several hours before

convergence. Thus, we propose CIFAR-FS (CIFAR100 few-shots), which is randomly sampled from CIFAR-100 (Krizhevsky & Hinton, 2009) and exhibits exactly the same settings of miniImageNet. We observed that the average inter-class similarity is sufficiently high to represent a challenge for the current state of the art. Moreover, the limited original resolution of 32×32 makes the task harder and at the same time allows fast prototyping. The classes contained in each split are detailed in Appendix C.

4.2 EXPERIMENTAL RESULTS

In order to produce the features X for the base learners (eq. 4 and 7), as many recent methods we use a shallow network of four convolutional "blocks", each consisting of the following sequence: a 3×3 convolution, batch-normalization, 2×2 max-pooling, and a leaky-ReLU with a factor of 0.1.

The four convolutional layers have $[96, 192, 384, 512]$ filters. Dropout is applied to the last two blocks for the experiments on miniImageNet and CIFAR-FS, respectively with probabilities 0.1 and 0.4. We do not use any fully connected layer. Instead, we flatten and concatenate the output of the third *and* fourth convolutional blocks and feed it to the base learner. Doing so, we obtain high-dimensional features of size 3584, 72576 and 8064 for Omniglot, miniImageNet and CIFAR-FS respectively. It is important to mention that the use of the Woodbury formula (section 3.2) allows us to make use of high-dimensional features without incurring burdensome computations. In fact, in few-shot problems the data matrix X is particulary "fat and short". As an example, with a 5-way/1-shot problem from miniImageNet we have $X \in \mathbb{R}^{5\times72576}$. Applying the Woodbury identity, we obtain significant gains in computation, as in eq. 5 we invert a matrix that is only 5×5 instead of 72576×72576.

As Snell et al. (2017), we observe that using a higher number of classes during training is important. Hence, despite the few-shot tasks at test time being 5 or 20-way, in our multinomial classification experiments we train using 60 classes for Omniglot, 16 for miniImageNet and 20 for CIFAR-FS. Moreover, in order not to train a different model for every single configuration (two for miniImageNet and CIFAR-FS, four for Omniglot), similarly to (Mishra et al., 2018) and differently from previous work, we train our models with a random number of shots, which does not deteriorate the performance and allow us to simply train one model per dataset. We then choose Q (the size of the query or test set) accordingly, so that the batch size S remains constant throughout the episodes. We set S to 660 for Omniglot, 240 for miniImageNet and 160 for CIFAR-FS.

At the meta-learning level, we train our methods with Adam (Kingma & Ba, 2015) with an initial learning rate of 0.005, dampened by 0.5 every 2,000 episodes. Training is stopped when the error on the meta-validation set does not decrease meaningfully for 20,000 episodes.

As for the base learner, we let SGD learn the parameters ω of the CNN, as well as the regularization factor λ and the scale α and bias β of the calibration layer of R2-D2 (end of Section 3.2). In practice, we observed that it is important to use SGD to adapt α and β, while it is indifferent whether λ is learnt or not. A more detailed analysis can be found in Appendix B.

Multinomial classification. Tables 1 and 2 show the performance of our closed-form base learner R2-D2 against the current state of the art for shallow architectures of four convolutional layers. Values represent average classification accuracies obtained by sampling 10,000 episodes from the meta test-set and are presented with 95% confidence intervals. For each column, the best performance is outlined in bold. If more than one value is outlined, it means their intervals overlap. For prototypical networks, we report the results reproduced by the code provided by the authors. For our comparison, we report the results of methods which train their models from scratch for few-shot classification, omitting very recent work of Qiao et al. (2018) and Gidaris & Komodakis (2018), which instead make use of pre-trained embeddings.

In terms of feature embeddings, Vinyals et al. (2016); Finn et al. (2017); Snell et al. (2017); Ravi & Larochelle (2017) use 64 filters per layer (which become 32 for miniImageNet in (Ravi & Larochelle, 2017; Finn et al., 2017) to limit overfitting). On top of this, Sung et al. (2018) also uses a *relation module* of two convolutional and two fully connected layers. GNN (Garcia & Bruna, 2018) employs an embedding with $[64, 96, 128, 256]$ filters, a fully connected layer and a graph neural network (with its own extra parameters). In order to ensure a fair comparison, we increased the capacity of the architectures of three representative methods (MAML, prototypical networks and GNN) to match ours. The results of these experiments are reported with a $*$ on Table 1. We make use of dropout on

Table 1: Few-shot multinomial classification accuracies on miniImageNet and CIFAR-FS.

Method	miniImageNet, 5-way		CIFAR-FS, 5-way	
	1-shot	5-shot	1-shot	5-shot
MATCHING NET (Vinyals et al., 2016)	44.2%	57%	—	—
MAML (Finn et al., 2017)	48.7±1.8%	63.1±0.9%	58.9±1.9%	71.5±1.0%
MAML ∗	40.9±1.5%	58.9±0.9%	53.8±1.8%	67.6±1.0%
META-LSTM (Ravi & Larochelle, 2017)	43.4±0.8%	60.6±0.7%	—	—
PROTO NET (Snell et al., 2017)	47.4±0.6%	65.4±0.5%	55.5±0.7%	72.0±0.6%
PROTO NET ∗	42.9±0.6%	65.9±0.6%	57.9±0.8%	76.7±0.6%
RELATION NET (Sung et al., 2018)	50.4±0.8%	65.3±0.7%	55.0±1.0%	69.3±0.8%
SNAIL (with *ResNet*) (Mishra et al., 2018)	55.7±*1.0%*	68.9±*0.9%*	—	—
SNAIL (with 32C) (Mishra et al., 2018)	45.1%	55.2%	—	—
GNN (Garcia & Bruna, 2018)	50.3%	66.4%	61.9%	75.3%
GNN∗	50.3%	68.2%	56.0%	72.5%
OURS/R2-D2 (with 64C)	48.9±0.6%	66.1±0.6%	61.5±0.7%	76.7±0.6%
OURS/R2-D2	**51.5**±0.2%	**68.8**±0.1%	**65.3**±0.2%	**79.4**±0.1%

Table 2: Few-shot multinomial classification accuracies on Omniglot.

Method	Omniglot, 5-way		Omniglot, 20-way	
	1-shot	5-shot	1-shot	5-shot
SIAMESE NET (Koch et al., 2015)	96.7%	98.4%	88%	96.5%
MATCHING NET (Vinyals et al., 2016)	98.1%	98.9%	93.8%	98.5%
MAML (Finn et al., 2017)	**98.7**±0.4%	**99.9**±0.1%	95.8±0.3%	98.9±0.2%
PROTO NET (Snell et al., 2017)	98.5±0.2%	99.5±0.1%	95.3±0.2%	98.7±0.1%
SNAIL (Mishra et al., 2018)	**99.07**±0.16%	**99.77**±0.09%	**97.64**±0.30%	**99.36**±0.18%
GNN (Garcia & Bruna, 2018)	**99.2%**	**99.7%**	**97.4%**	99.0%
OURS/R2-D2 (with 64C)	98.58±0.05%	99.67±0.02%	94.91±0.05%	98.94±0.02%
OURS/R2-D2	**98.96**±0.05%	**99.71**±0.02%	96.24±0.05%	**99.20**±0.02%

the last two layers for all the experiments on baselines with ∗, as we verified it is helpful to reduce overfitting. Moreover, we report results for experiments on our R2-D2 in which we use the 64 channels embedding of Vinyals et al. (2016); Snell et al. (2017); Ravi & Larochelle (2017).

Despite its simplicity, our proposed method achieves an average accuracy that, on miniImageNet and CIFAR-FS, is superior to the state of the art with shallow architectures. For example, on the four tasks of Table 1, R2-D2 improves on average of a relative 4.2% w.r.t. GNN (the second best method). R2-D2 shows competitive results also on Omniglot (Table 2), achieving among the best performance for all tasks. Furthermore, when we use the "lighter" embedding, we can still observe a performance which is in line with the state of the art. Interestingly, increasing the capacity of the other method it is not particularly helpful. It is beneficial only for GNN on miniImageNet and prototypical networks on CIFAR-FS, while being detrimental in all the other cases.

Our R2-D2 is also competitive against SNAIL, which uses a much deeper architecture (a ResNet with a total of 14 convolutional layers). Despite being outperformed for the 1-shot case, we can match its results on the 5-shot one. Moreover, it is paramount for SNAIL to make use of such deep embedding, as its performance drops significantly with a shallow one.

Binary classification. Finally, in Table 3 we report the performance of both our ridge regression and logistic regression base learners, together with four other methods representative of the state of the art. Since LR-D2 is limited to operate in a binary classification setup, we run our R2-D2 and prototypical network without oversampling the number of ways. For both methods and prototypical networks, we report the performance obtained annealing the learning rate by a factor of 0.99, which within this binary setup works significantly better than originally described in Snell et al. (2017). Moreover, motivated by the small size of the mini-batches, we replace Batch Normalization with Group Normalization (Wu & He, 2018). For this table, we use the default setup found in the code of MAML, which uses 5 SGD iterations during training and 10 during testing. Table 3 confirms the

Table 3: Few-shot binary classification accuracies on miniImageNet and CIFAR-FS.

Method	miniImageNet, 2-way		CIFAR-FS, 2-way	
	1-shot	5-shot	1-shot	5-shot
MAML (Finn et al., 2017)	74.9±3.0%	84.4±1.2%	**82.8**±2.7%	88.3±1.1%
PROTO NETS (Snell et al., 2017)	71.7±1.0%	84.8±0.7%	76.4±0.9%	88.5±0.6%
RELATION NET (Sung et al., 2018)	76.2±1.2%	**86.8**±1.0%	75.0±1.5%	86.7±0.9%
GNN (Garcia & Bruna, 2018)	**78.4%**	**87.1%**	79.3%	89.1%
OURS/R2-D2	76.7±0.3%	**86.8**±0.2%	**83.4**±**0.3%**	**91.1**±0.2%
OURS/LR-D2	76.7±0.3%	**87.2**±0.2%	83.3±0.2%	**91.2**±0.2%

validity of both our approaches on the binary classification problem.

Although different in nature, both MAML and our LR-D2 make use of iterative base learners: the former is based on SGD, while the latter on Newton's method (under the form of Iteratively Reweighted Least Squares). The use of second-order optimization might suggest that LR-D2 is characterized by computationally demanding steps. However, we can apply the Woodbury identity at every iteration and obtain a significant speedup. In Figure 2 we compare the performance of LR-D2 vs the one of MAML for a different number of steps of the base learner (kept constant between training and testing). On both datasets, the two methods are comparable for the 1-shot case, but with a higher number of shots our logistic regression approach outperforms MAML, especially for higher number of steps.

Figure 2: Accuracy on two datasets and two setups at different number of steps of the base learner for MAML, R2-D2 and LR-D2.

5 CONCLUSIONS

In this paper, we explored the feasibility of incorporating fast solvers with closed-form solutions as the base learning component of a meta-learning system. Importantly, the use of the Woodbury identity allows significant computational gains in a scenario presenting few samples with a high dimensionality, like the one of few-shot learning. We showed that these differentiable learning blocks work remarkably well, with excellent results on few-shot learning benchmarks, generalizing to new tasks that were not seen during training. We believe that our findings point in an exciting direction of more sophisticated online adaptation methods, able to leverage the potential of prior knowledge distilled in an offline training phase. In future work, we would like to explore Newton's methods with more complicated second-order structure than ridge regression, and experiment with cross-modal task learning.

REFERENCES

Han Altae-Tran, Bharath Ramsundar, Aneesh S Pappu, and Vijay Pande. Low data drug discovery with one-shot learning. *ACS central science*, 2017.

Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, and Nando de Freitas. Learning to learn by gradient descent by gradient descent. In *Advances in Neural Information Processing Systems*, 2016.

Andreas Argyriou, Theodoros Evgeniou, and Massimiliano Pontil. Multi-task feature learning. In *Advances in Neural Information Processing Systems*, 2007.

Samy Bengio, Yoshua Bengio, Jocelyn Cloutier, and Jan Gecsei. On the optimization of a synaptic learning rule. In *Preprints Conf. Optimality in Artificial and Biological Neural Networks*, pp. 6–8. Univ. of Texas, 1992.

Luca Bertinetto, João F Henriques, Jack Valmadre, Philip Torr, and Andrea Vedaldi. Learning feed-forward one-shot learners. In *Advances in Neural Information Processing Systems*, 2016.

Jane Bromley, James W Bentz, Léon Bottou, Isabelle Guyon, Yann LeCun, Cliff Moore, Eduard Säckinger, and Roopak Shah. Signature verification using a "Siamese" time delay neural network. *International Journal of Pattern Recognition and Artificial Intelligence*, 1993.

Susan Carey. Less may never mean more. *Recent advances in the psychology of language*, 1978.

Susan Carey and Elsa Bartlett. Acquiring a single new word. 1978.

Rich Caruana. Multitask learning. In *Learning to learn*. Springer, 1998.

Sumit Chopra, Raia Hadsell, and Yann LeCun. Learning a similarity metric discriminatively, with application to face verification. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2005.

Theodoros Evgeniou and Massimiliano Pontil. Regularized multi–task learning. In *Proceedings of the tenth ACM SIGKDD international conference on Knowledge discovery and data mining*, 2004.

Li Fei-Fei, Rob Fergus, and Pietro Perona. One-shot learning of object categories. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2006.

Chelsea Finn and Sergey Levine. Meta-learning and universality: Deep representations and gradient descent can approximate any learning algorithm. 2018.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, 2017.

Victor Garcia and Joan Bruna. Few-shot learning with graph neural networks. In *International Conference on Learning Representations*, 2018.

Spyros Gidaris and Nikos Komodakis. Dynamic few-shot visual learning without forgetting. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2018.

Bharath Hariharan and Ross B Girshick. Low-shot visual recognition by shrinking and hallucinating features. In *IEEE International Conference on Computer Vision*, 2017.

Sepp Hochreiter, A Steven Younger, and Peter R Conwell. Learning to learn using gradient descent. In *International Conference on Artificial Neural Networks*, pp. 87–94. Springer, 2001.

Łukasz Kaiser, Ofir Nachum, Aurko Roy, and Samy Bengio. Learning to remember rare events. In *International Conference on Learning Representations*, 2017.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. 2015.

Gregory Koch, Richard Zemel, and Ruslan Salakhutdinov. Siamese neural networks for one-shot image recognition. In *International Conference on Machine Learning workshops*, 2015.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. 2009.

BVK Vijaya Kumar, Abhijit Mahalanobis, and Richard D Juday. *Correlation pattern recognition*. Cambridge University Press, 2005.

Brenden M Lake, Ruslan Salakhutdinov, and Joshua B Tenenbaum. Human-level concept learning through probabilistic program induction. *Science*, 2015.

Dougal Maclaurin, David Duvenaud, and Ryan Adams. Gradient-based hyperparameter optimization through reversible learning. In *International Conference on Machine Learning*, pp. 2113–2122, 2015.

Michael McCloskey and Neal J Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of learning and motivation*. 1989.

Nikhil Mishra, Mostafa Rohaninejad, Xi Chen, and Pieter Abbeel. A simple neural attentive meta-learner. In *International Conference on Learning Representations*, 2018.

Tom M Mitchell. *The need for biases in learning generalizations*. Department of Computer Science, Laboratory for Computer Science Research, Rutgers Univ. New Jersey, 1980.

Tsendsuren Munkhdalai and Hong Yu. Meta networks. In *International Conference on Machine Learning*, 2017.

Kevin P. Murphy. *Machine Learning: A Probabilistic Perspective*. The MIT Press, 2012.

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms. *CoRR*, 2018. URL http://arxiv.org/abs/1803.02999.

Kaare Brandt Petersen, Michael Syskind Pedersen, et al. The matrix cookbook. *Technical University of Denmark*, 2008.

Siyuan Qiao, Chenxi Liu, Wei Shen, and Alan L. Yuille. Few-shot image recognition by predicting parameters from activations. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2018.

Sachin Ravi and Hugo Larochelle. Optimization as a model for few-shot learning. In *International Conference on Learning Representations*, 2017.

Sylvestre-Alvise Rebuffi, Hakan Bilen, and Andrea Vedaldi. Learning multiple visual domains with residual adapters. In *Advances in Neural Information Processing Systems*, 2017.

Mengye Ren, Eleni Triantafillou, Sachin Ravi, Jake Snell, Kevin Swersky, Joshua B Tenenbaum, Hugo Larochelle, and Richard S Zemel. Meta-learning for semi-supervised few-shot classification. In *International Conference on Learning Representations*, 2018.

Sebastian Ruder. An overview of multi-task learning in deep neural networks. *arXiv preprint arXiv:1706.05098*, 2017.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. 2015.

Adam Santoro, Sergey Bartunov, Matthew Botvinick, Daan Wierstra, and Timothy Lillicrap. Meta-learning with memory-augmented neural networks. In *International Conference on Machine Learning*, 2016.

Jürgen Schmidhuber. *Evolutionary principles in self-referential learning, or on learning how to learn: the meta-meta-... hook*. PhD thesis, Technische Universität München, 1987.

Jürgen Schmidhuber. Learning to control fast-weight memories: An alternative to dynamic recurrent networks. *Neural Computation*, 1992.

Jürgen Schmidhuber. A neural network that embeds its own meta-levels. In *Neural Networks, 1993., IEEE International Conference on*. IEEE, 1993.

Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for few-shot learning. In *Advances in Neural Information Processing Systems*, 2017.

Pablo Sprechmann, Siddhant M Jayakumar, Jack W Rae, Alexander Pritzel, Adrià Puigdomènech Badia, Benigno Uria, Oriol Vinyals, Demis Hassabis, Razvan Pascanu, and Charles Blundell. Memory-based parameter adaptation. 2018.

Flood Sung, Yongxin Yang, Li Zhang, Tao Xiang, Philip HS Torr, and Timothy M Hospedales. Learning to compare: Relation network for few-shot learning. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2018.

Albert Tarantola. *Inverse problem theory and methods for model parameter estimation*, volume 89. siam, 2005.

Sebastian Thrun. Lifelong learning algorithms. In *Learning to learn*. Springer, 1998.

Paul E Utgoff. Shift of bias for inductive concept learning. *Machine learning: An artificial intelligence approach*, 1986.

Jack Valmadre, Luca Bertinetto, João Henriques, Andrea Vedaldi, and Philip HS Torr. End-to-end representation learning for correlation filter based tracking. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2017.

Ricardo Vilalta and Youssef Drissi. A perspective view and survey of meta-learning. *Artificial Intelligence Review*, 2002.

Oriol Vinyals, Charles Blundell, Tim Lillicrap, Daan Wierstra, et al. Matching networks for one shot learning. In *Advances in Neural Information Processing Systems*, 2016.

Yuxin Wu and Kaiming He. Group normalization. *CoRR*, 2018. URL http://arxiv.org/abs/1803.08494.

A Steven Younger, Sepp Hochreiter, and Peter R Conwell. Meta-learning with backpropagation. In *Neural Networks, 2001. Proceedings. IJCNN'01. International Joint Conference on*. IEEE, 2001.

A   DIFFERENT GAUSSIAN PRIORS FOR REGULARIZATION

The regularization term can be seen as a prior gaussian distribution of the parameters in a Bayesian interpretation, or more simply Tikhonov regularization (Tarantola, 2005). In the most common case of λI, it corresponds to an isotropic gaussian prior on the parameters.

In addition to the case in which λ is a scalar, we also experiment with the variant $\text{diag}(\boldsymbol{\lambda})$, corresponding to an axis-aligned gaussian prior with an independent variance for each parameter, which can potentially exploit the fact that the parameters have different scales. Replacing λI with $\text{diag}(\boldsymbol{\lambda})$ in 4, the final expression for W after having applied the Woodbury identity becomes:

$$W = \Lambda(Z) = \text{diag}(\boldsymbol{\lambda})^{-1} X^T (X^T \text{diag}(\boldsymbol{\lambda})^{-1} X^T + I)^{-1} Y. \tag{8}$$

B   BASE LEARNER HYPER-PARAMETERS

Figure 3 illustrates the effect of using SGD to learn, together with the parameters ω of the CNN, also the hyper-parameters (ρ in 2) of the base learner Λ. We find that it is very important to learn the scalar α (right) used to calibrate the output of R2-D2 in 6, while it is indifferent whether or not to learn λ. Note that, by using SGD to update α, it is possible (e.g. in the range $[10^{-3}, 10^0]$) to recover from poor initial values and suffer just a little performance loss w.r.t. the optimal value of $\alpha = 10$.

The left plot of Figure 3 also shows the performance of R2-D2with the variant $\text{diag}(\lambda)$ introduced in Appendix A. Unfortunately, despite this formulation allows us to make use of a more expressive prior, it does not improve the results compared to using a simple scalar λ. Moreover, performance abruptly deteriorate for $\lambda > 0.01$.

Figure 3: Shaded areas represent 95% confidence intervals.

C   CIFAR-FS SPLITS

Meta-training classes: train, skyscraper, turtle, raccoon, spider, orange, castle, keyboard, clock, pear, girl, seal, elephant, apple, aquarium fish, bus, mushroom, possum, squirrel, chair, tank, plate, wolf, road, mouse, boy, shrew, couch, sunflower, tiger, caterpillar, lion, streetcar, lawn mower, tulip, forest, dolphin, cockroach, bear, porcupine, bee, hamster, lobster, bowl, can, bottle, trout, snake, bridge, pine tree, skunk, lizard, cup, kangaroo, oak tree, dinosaur, rabbit, orchid, willow tree, ray, palm tree, mountain, house, cloud.

Meta-validation classes: otter, motorcycle, television, lamp, crocodile, shark, butterfly, beaver, beetle, tractor, flatfish, maple tree, camel, crab, sea, cattle.

Meta-test classes: baby, bed, bicycle, chimpanzee, fox, leopard, man, pickup truck, plain, poppy, rocket, rose, snail, sweet pepper, table, telephone, wardrobe, whale, woman, worm.