CycleAlign: Iterative Distillation from Black-box LLM to White-box Models for Better Human Alignment

Abstract

Language models trained on large-scale corpus often generate harmful responses that are harmful and contrary to human values. A prevalent approach for human alignment is reinforcement learning from human feedback (RLHF), utilizing algorithms such as proximal policy optimization (PPO). However, these methods are often characterized by complexity, instability, and substantial resource consumption. Considering that existing large language models (LLMs) like ChatGPT are already relatively well-aligned and cost-friendly, researchers propose to align the language model with human preference from AI feedback. Nevertheless, the common practices, that unidirectionally distill the responses, are constrained by the inherent capability of LLMs. To address it, we introduce CycleAlign framework to distill alignment capabilities from the parameter-invisible LLM (black-box) to a parameter-visible model (white-box) in an iterative manner. CycleAlign iteratively improves both the white-box and black-box models by integrating static and dynamic in-context learning and a belief alignment method. Empirical results illustrate that the model fine-tuned by CycleAlign remarkably exceeds existing methods, and achieves the state-of-the-art performance in alignment with human value.[1]

1 Introduction

Large language models (LLMs) have demonstrated superior capabilities in processing complicated tasks, benefiting from the extensive training corpus and model parameters (Brown et al., 2020; Bubeck et al., 2023; Chowdhery et al., 2022; Touvron et al., 2023a,b; Du et al., 2021; OpenAI, 2023). Nevertheless, models trained on the corpus collected from diverse web sources could not be effectively guided, and are prone to generate harmful, toxic

Figure 1: Comparison between CycleAign with existing unidirectional distillation frameworks.

and criminal contents (Bai et al., 2022b; Ouyang et al., 2022). Therefore, aligning language models with human preferences has emerged as a pivotal focus in the ongoing research.

Reinforcement learning from human feedback (RLHF) (Ouyang et al., 2022) has been employed to align language models with human preferences. Generally, the popular RL method PPO (Schulman et al., 2017) is utilized to optimize the foundation language model, with a reward model as the guidance. However, its complex architecture poses a challenge for hardware devices and it exhibits an unstable property during training. Recently, the emergence of ranking-based alignment methods has resolved the stability and hardware-consumption problems through shifting from the RL framework to supervised fine-tuning (Song et al., 2023; Rafailov et al., 2023; Yuan et al., 2023). Nevertheless, the need for extensively annotated data renders them costly and labor-intensive.

Considering existing LLMs like ChatGPT are well aligned, the reinforcement learning from AI feedback (RLAIF) methods are proposed to introduce automatic AI supervision (Bai et al., 2022b; Kim et al., 2023) to replace the manual annotation. However, common practices that distill instruction-following responses in a unidirectional manner are

---

[1] The code of this work will be available at `https://anonymous.4open.science/r/CycleAlign-B958/`.

limited by the inherent capability of LLMs. Meanwhile, researchers (Burns et al., 2023) recently have demonstrated that the small model (GPT-2) could supervise the large model (GPT-4) and improve the ability of the latter. To improve this, we propose a novel framework CycleAlign to better align the parameter-visible white-box model with the parameter-invisible black-box model by iterative interactions.

As shown in Figure 1, we introduce the in-context learning (ICL) (Min et al., 2022; Rubin et al., 2021; Ren et al., 2021) as the pivot to enhance black-box LLMs in this process. Given an instruction, we prompt the white-box model to generate multiple responses. Then, the black-box model ranks these responses with the help of the human-craft ranking prompt and static in-context demonstration. The ranking signal will be utilized to optimize the white-box model and help it generate more harmless and helpful responses. Additionally, the generated probability of responses could be deemed as a ranking judgment from the aspect of the white-box model. As we know, LLMs will perform better with the number of in-context demonstrations increasing (Brown et al., 2020). Combining the ranking judgment from the white-box and black-box model, we could extract the consistent (or agreement) rank as the pseudo label, which will be used to improve the black-box LLM as the dynamically appended demonstration. Benefiting from the static and dynamic demonstrations, the black-box model could better rank the responses generated from the white-box model. After the iterative interaction, the alignment of the white-box model will be improved with the help of an enhanced black-box LLM.

We conduct experiments on the human preference dataset HH-RLHF (Bai et al., 2022a) to investigate the effectiveness of CycleAlign regarding helpfulness and harmlessness. Compared with the previous methods, CycleAlign could improve the alignment ability and take state-of-the-art performance in generating harmless and helpful responses. In summary, our main contributions are as follows:

- We present a new framework CycleAlign, which utilizes collaboration between black-box LLMs and white-box models, to align the latter with human preference in an iterative manner.

- We enhance the black-box model's ranking results by employing static and dynamic in-context demonstrations under the interactive scenario.

- We validate the effectiveness of the CycleAlign framework in generating harmless and helpful responses by extensive experiments.

2 Related Work

RL-based Methods for Human Alignment. Reinforcement learning (RL) techniques have been widely applied for human alignment of LLMs, which employ RL algorithms, such as Proximal Policy Optimization (PPO) to optimize the responses generated by LLMs (Yang et al., 2023). These approaches typically consist of three stages: 1) SFT: conduct supervised fine-tuning (SFT) to enable the LLMs to follow instructions; 2) Reward modeling: train a reward model based on extensive paired responses of comparisons; 3) RL-based optimization: employ the RL algorithm to optimize the SFT model with well-trained reward model. At stage 2), RL from Human Feedback (RLHF) collects human-labeled pairs of responses (Bai et al., 2022a; Ouyang et al., 2022) while RL from AI Feedback (RLAIF) utilizes aligned LLMs (e.g., ChatGPT) to compare the pairs of responses (Bai et al., 2022b; Lee et al., 2023). Ouyang et al. (2022) propose InstructGPT which employs RLHF for optimization. Bai et al. (2022a) employ RLHF to train a helpful and harmless assistant. Bai et al. (2022b) train a harmless AI assistant through self-improvement based on a helpful AI assistant, without any human labels identifying harmful outputs. Lee et al. (2023) suggest that RLAIF can exhibit comparable performance to RLHF. Overall, these approaches all employ an RL algorithm (e.g., PPO) which is often complex, unstable and resource-demanding.

Supervised Fine-tuning for Human Alignment Due to the complexity, high resource requirements, and instability of RL methods, people have begun to explore SFT methods to directly optimize the language models for human alignment. Rafailov et al. (2023) bypass the reward modeling stage and directly align the LMs with preference data, using a binary cross entropy objective for optimization. Similarly, Yuan et al. (2023) utilize the pair-wise responses of comparisons to enable the LMs to learn the preference knowledge. Song et al. (2023) extend the pair-wise comparison to accommodate preference rankings of any length. Liu et al. (2023a) combine opposite responses to fine-tune models,

Figure 2: Overview of CycleAlign framework: 1) sample responses from the white-box model; 2) obtain ranking results from two models respectively; 3) optimize the white-box model using a ranking-based objective; 4) compare the two ranking results, find agreement rank and feed it as the demonstrations to black-box model; 5) repeat the above process up to max interaction times threshold N or until the black- and white- box model are completely consistent.

with hindsight feedback as prompt prefix. Liu et al. (2023b) construct a sandbox of LLMs as a simulated human society to collect interaction data with feedback for fine-tuning. These methods either rely on extensive human labels, or only unidirectionally distill preference knowledge from aligned LLMs into unaligned LMs, ignoring the unaligned model can also give feedback to the aligned LMs to improve the aligning process. Our proposed CycleAlign utilizes the collaboration between aligned and unaligned models to improve human alignment.

3 Methodology

In this section, we describe CycleAlign which utilizes the collaboration between black-box and white-box models to improve alignment with human preferences. As figure 2 shows, we introduce the static and dynamic demonstrations to break the inherent bottleneck of black-box LLMs, and help the better alignment distillation for while-box models by iterative interactions.

3.1 Cyclical Collaborative Framework

To alleviate the instability of the RL algorithm and the costly human labels, we replace human feedback with AI feedback from the black-box LLM and use rank-based Supervised Fine-Tuning (SFT) to optimize the white-box model. Existing methods only distill preference unidirectionally from well-aligned black-box LLMs, ignoring the feedback of unaligned white-box models. Consequently, we

design a cyclical framework to facilitate the collaboration between them.

The framework is shown in Figure 2. For each interaction, we prompt the white-box model to generate multiple different responses for a given instruction. With the help of well-aligned black-box LLMs (e.g. ChatGPT), we could prompt LLMs to generate the rank about the alignment degrees of these responses, utilizing the in-context learning method. Recently, researchers (Burns et al., 2023) have demonstrated that the small model (GPT-2) could supervise the large model (GPT-4) and improve the ability of the latter. Inspired by it, we also consider the belief (rank) of the white-box model about the alignment degrees, reflected by the generation probabilities of the responses. By incorporating the belief from while-box and black-box models, we could obtain the consistent rank of the responses and utilize it as the pseudo in-context demonstrations to improve the ability of black-box LLMs.

With the iterative interactions between white-box and black-box models, both of them will be enhanced on alignment with human preferences.

3.2 ICL with Static-Dynamic Integration

LLMs have demonstrated the powerful capability of In-Context Learning (ICL) (Brown et al., 2020; Xie et al., 2021; Min et al., 2022), which learns the patterns hidden within the demonstrations, and generalizes the specific tasks by few-shot prompting (Dong et al., 2023). In this work, we combine the static and dynamic demonstrations to break

the capability bottleneck of LLMs caused by only static demonstrations.

We manually craft the prompt template and a static demonstration, which can be seen in Appendix A.1 and A.3. Then we continuously update the demonstrations during the training process, i.e., dynamic demonstrations. As we know, LLMs also will make mistakes with only static demonstrations, which become the bottleneck of them. Besides, human-crafted demonstration could not adapt to the habit of white-box models, resulting the poor distillation performance. Dynamically appending the demonstrations fitting the white-box models into black-box is meaningful and helpful.

Specifically, For a given input, the white-box model could generate multiple responses and we then can obtain the rank of them according to their generation probabilities, as the belief of the white-box model. Meanwhile, the black-box LLMs also could generate a rank of these responses. The consistent rank between black and white ones will represent not only the belief of black-box LLMs but also the confidence of white-box model. We use the consistent rank as the pseudo demonstrations and append it to the black-box LLM to improve its ICL ability for better judgment. During training, the white-box model is progressively aligned. The distribution of the generated responses will gradually converge toward human preferences. The generated responses will be more challenging to rank, so ranking these responses will exploit the capability of the black-box model. Meanwhile, the white-box model's ranking will be more and more accurate in terms of the degree of alignment, making us believe that the white-box model's ranking contains useful signals. With the training cycle start to run, both of white-box and black-box will be enhanced benefit from their collaboration, resulting the better alignment with human preference of the former at last.

How do we extract the agreement ranking? We assume that the ranking from black-box LLM is more accurate in general. In addition, since responses generated by the white-box model continuously improve with training, the ranking of responses that align more closely with human preferences has a higher referring value for the black-box LLM. So we extract the **Longest Common Subsequence** (LCS) of the two ranking results with the highest black-box rankings.

Our experiment results indicate that our ICL with Static-Dynamic Integration method enhances the ranking accuracy of black-box LLM and achieves better alignment performance of the white-box model.

3.3 Optimization

Recently, ranking-based SFT methods have been applied for alignment as an alternative to RL algorithms. Given a set of responses, human preferences can be expressed as a ranking of the responses. Ranking-based SFT methods directly incorporate the ranking information in a contrastive manner into the fine-tuning stage (Rafailov et al., 2023; Yuan et al., 2023; Song et al., 2023; Wang et al., 2023b). We bring the two ranking-based optimization objectives from RRHF (Yuan et al., 2023) and PRO (Song et al., 2023) into our framework.

Specifically, given the white-box model π, an instruction x and n possible responses $\{y^i\}_1^n$ with preference order $y^1 \succ y^2 \succ \cdots \succ y^n$, the ranking-based SFT objective can be formulated as:

$$\mathcal{L} = \mathcal{L}_{\text{rank}} + \lambda \mathcal{L}_{\text{sft}}, \qquad (1)$$

where

$$\mathcal{L}_{\text{sft}} = -\frac{1}{|y^1|} \sum_t \log P_\pi(y_t^1 | x, y_{<t}^1). \qquad (2)$$

The $\mathcal{L}_{\text{rank}}$ can be calculated by PRO or RRHF as follows:

$$\mathcal{L}_{\text{RRHF}} = -\sum_{i>j} \max\{0, p_i - p_j\}, \qquad (3)$$

$$\mathcal{L}_{\text{PRO}} = -\sum_{j=1}^{n-1} \frac{\exp(p_j)}{\sum_{i=j}^n \exp(p_i)}, \qquad (4)$$

where p_i denotes the probability of generating y^i conditioned on x, $p_i = \frac{1}{|y^i|} \sum_t \log P_\pi(y_t^i | x, y_{<t}^i)$.

4 Experiments

4.1 Settings

4.1.1 Datasets

We conduct experiments on HH-RLHF (Bai et al., 2022a)[2], a human preference dataset about helpfulness and harmlessness. It contains about 170k dialogues, where each has a context and a pair of responses along with an annotated preference label. This dataset contains four subsets, which are Harmless$_{\text{base}}$, Helpful$_{\text{base}}$, Helpful$_{\text{online}}$ and Helpful$_{\text{rejection}}$ respectively. The statistics of them

[2]https://github.com/anthropics/hh-rlhf

can be found in Appendix A.2. We filter the dataset referring OpenAssistant's code[3]. In our framework, the performance of the white-box model will become stable after being trained on about 1,000 examples of data, similar to the previous findings (Lee et al., 2023). Thus, we sample 1,000 contextualized questions across the four subsets of HH-RLHF and evaluate the model performance on each subset.

4.1.2 Evaluation

We use quantitative and qualitative approaches to evaluate the harmlessness and helpfulness of a language model. For quantitative evaluation, a well-trained reward model, whose training data involves HH-RLHF, is utilized to assess the responses generated by different models, similar to previous works (Song et al., 2023; Yuan et al., 2023). Because the reward model may not completely reflect human preferences, manual assessment should be involved. Meanwhile, GPT-4 judgment recently has become a popular and relatively reliable evaluation method (Wang et al., 2023a; Pezeshkpour and Hruschka, 2023; Zheng et al., 2023). Thus, human annotators and GPT-4 are employed for qualitative evaluation. They are required to compare the responses based on the criterion of harmlessness and helpfulness. To avoid the order bias of compared responses in GPT-4, we shuffle the orders of the compared responses and utilize chain-of-thought. Finally, we calculate the average win rates of different models. More implementation details can be found in Appendix A.5.

4.1.3 Baselines

We compare our CycleAlign with models in zero-shot setting, in-context learning (Brown et al., 2020) and chain-of-thought (Wei et al., 2022), as well as imposing the recent alignment methods on these models.

Specifically, we involve zero-shot unaligned models including LLaMA-7B(Touvron et al., 2023a), Alpaca-7B(Taori et al., 2023) and aligned models including ChatGLM-6B (Du et al., 2021) and ChatGPT. The considered existing aligning methods include RLHF method PPO(Schulman et al., 2017), SFT method RRHF(Yuan et al., 2023), and PRO(Song et al., 2023) which involves human and AI feedback. The detailed description can be found in Appendix A.4.

Due to that our CycleAlign is an optimization-agnostic framework, we equip CycleAlign on

---

[3]https://github.com/LAION-AI/Open-Assistant

RRHF and PRO, and note them as CycleAlign$_{RRHF}$ and CycleAlign$_{PRO}$ respectively.

4.2 Main results

The main results of our experiments can be found in Table 1. Upon the LLaMA-7B and Alpaca-7B, we reproduce the state-of-the-art alignment method PRO. The results of PPO and RRHF are cited from Song et al. (2023). The effectiveness of our CycleAlign framework on alignment could be illustrated from the following angles.

1) Comparing with zero-shot backbones like LLaMA and Alpaca, as well as these models with ICL and CoT, it is obvious that models significantly outperform them after alignment. It indicates that existing foundation models or models fine-tuned for instruction following are under-aligned with human values and can generate harmful and unhelpful responses, even with ICL and CoT. Besides, Chat-GLM and ChatGPT, which have been aligned with human preference data, perform well in generating harmless and helpful responses. And overall they perform even better with ICL and CoT. Considering that ChatGPT is well-aligned and cost-friendly, we propose CycleAlign to better align models with it in a low-resource manner.

2) Compared to previous alignment methods, the model equipped with CycleAlign obtains a remarkable improvement in alignment. It is noteworthy that the previous alignment methods (PPO, RRHF, and PRO) fine-tune models on the entire training set of HH-RLHF augmented with responses generated by ChatGPT, provided by (Song et al., 2023). Specifically, CycleAlign increases 7.03 reward score on Harmless$_{base}$ and 5.31 reward score in total for RRHF when the backbone is LLaMA. It also brings about 1.27 reward score for PRO in total, indicating the effectiveness of iterative cycle alignment with the help of black-box LLMs.

3) Overall, the CycleAlign$_{PRO}$ based on Alpaca takes state-of-the-art performance in alignment compared with all the traditional alignment methods and has the approximate performance of Chat-GPT. With CycleAlign, the model could generate more harmless and helpful responses to satisfy the demands of users.

4.3 GPT-4 and Human Evaluation

In recent developments, GPT-4 has demonstrated robust consistency with human judgment, leading to its extensive application in evaluations (Liu et al., 2023c; Mao et al., 2023). For our study,

Table 1: Quantitative evaluation results of alignment. The scores are calculated by a well-trained reward model.

Methods	Backbone	Harmless$_{base}$	Helpful$_{base}$	Helpful$_{online}$	Helpful$_{rejection}$	Total
Zero-shot	LLaMA	53.59	33.25	40.48	36.23	40.67
	Alpaca	52.77	53.85	55.30	55.43	54.26
	ChatGLM	67.26	62.14	60.44	63.86	63.85
	ChatGPT	72.19	68.28	69.85	71.02	70.43
ICL	LLaMA	57.04	38.69	42.41	40.83	44.83
	Alpaca	58.32	57.58	59.19	59.81	58.71
	ChatGLM	71.65	63.14	65.07	65.31	66.39
	ChatGPT	72.05	67.88	69.41	70.46	70.04
CoT	LLaMA	54.66	36.88	41.81	39.78	43.27
	Alpaca	57.69	55.23	58.00	57.58	57.02
	ChatGLM	71.21	64.72	66.40	66.34	67.22
	ChatGPT	73.35	72.30	71.83	74.22	73.13
PPO	LLaMA	61.97	55.29	59.78	58.26	58.65
RRHF	LLaMA	64.63	61.38	63.26	63.28	63.12
CycleAlign$_{RRHF}$	LLaMA	71.66	67.05	65.89	67.95	68.43
		(+7.03)	(+5.67)	(+2.63)	(+4.67)	(+5.31)
PRO	LLaMA	72.86	64.05	65.56	66.44	67.40
CycleAlign$_{PRO}$	LLaMA	70.62	66.49	67.67	68.50	68.41
		(-1.98)	(+2.44)	(+2.11)	(+2.06)	(+1.01)
PRO	Alpaca	73.13	64.56	65.60	66.51	67.64
CycleAlign$_{PRO}$	Alpaca	71.32	67.89	66.53	68.92	68.97
		(-1.81)	(+3.33)	(+0.93)	(+2.41)	(+1.27)

Table 2: Comparison of CycleAlign *vs.* PRO with GPT-4 and Human

	Subset	% Win	% Tie	% Lose
GPT-4	Harmless$_{base}$	**70**	1	29
	Helpful$_{base}$	48	4	48
	Helpful$_{online}$	**46**	12	42
	Helpful$_{rejection}$	**51**	6	43
Human	Harmless$_{base}$	**69**	9	22
	Helpful$_{base}$	**49**	17	34
	Helpful$_{online}$	**44**	15	41
	Helpful$_{rejection}$	**44**	15	41

Figure 3: Ablation study on ChatGPT ranking accuracy.

we employed both GPT-4 and human annotators to assess and compare the responses generated by CycleAlign$_{PRO}$ and PRO, with Alpaca serving as the backbone. The evaluation outcomes, presented in Table 2, present similar conclusions.

The sampled results across all datasets reveal a consensus among humans and GPT-4 that models fine-tuned by CycleAlign$_{PRO}$ demonstrate greater alignment with human values. This agreement, however, seems to stand in contrast with the assessments derived from the reward model, as illustrated in Table 1. According to the reward model's evaluation, CycleAlign$_{PRO}$ falls short of matching PRO's performance on the Harmless$_{base}$ subset. Nonetheless, both human and GPT-4 evaluations suppose that CycleAlign$_{PRO}$ generates much less

harmful content compared to PRO. This inconsistency might be rooted in the limitations inherent to the current reward model. Besides, the models refined by CycleAlign$_{PRO}$ manifest markedly superior performance in the Helpful$_{rejection}$ subset as GPT-4's evaluation, and in Helpful$_{base}$ according to human assessment.

These findings cohesively indicate that through iterative interaction with black-box models, white-box models are capable of achieving a more refined alignment with human values.

4.4 Ablation Study

We conduct ablation studies to verify the effectiveness of each part in our design.

Dynamic demonstration (D2) and ICL With the model continuously updated during the training process, the distribution of the generated responses is ever-shifting. So it's necessary to dynamically examine the accuracy of ranking results returned from the black-box LLM. We take the ranking from the reward model used for evaluation as ground truth and calculate the ranking accuracy of black-box LLM at the last iterations of steps. As shown in Figure 3, after removing D2, the ranking accuracy of black-box LLM begins to decline, especially after removing all of the ICL components, the performance of black-box LLM severely deteriorates. The bottleneck in the ranking performance of Chat-GPT indirectly affects the alignment performance, which shows a similar trend in Table 3 regarding the ranking accuracy of ChatGPT.

Agreement ranking When we dynamically add only rankings from black-box LLMs to demonstrations, (i.e., without white-box model's rankings demonstrations, denoted by **w/o WRD**), the ranking accuracy of black-box LLM and the alignment performance of the model drops; and only utilizing the white-box model's rankings (**w/o BRD**) leads to declining ranking accuracy and even worse alignment performances. These results indicate that the signals from the white-box model help the ever-shifting responses ranking of LLMs and then contribute to better alignment.

The aforementioned experimental results illustrate that ICL and dynamic demonstrations consisting of agreement rankings used for bridging the cycle bring enhanced alignment performance for unaligned models. This results in the generated responses more in line with human preferences, being harmless and helpful.

Cycle framework To validate the effectiveness of the iterative cycle framework, we align the model without cycle iterations (**w/o Cycle**). For a fair comparison, we sample 5,000 contextualized questions from HH-RLHF. We sample responses from the white-box model and request the black-box model for rankings as well as a better response only once for each question. In this case, the two settings (w/o Cycle and CycleAlign) involve an approximately equal number of parameter update iterations. The result can be found in Table 3, which shows our CycleAlign achieves superior alignment performance in all aspects. The result demonstrates our iterative cycle framework can more adequately align the white-box model.

Figure 4: Running mean iteration times and white-box rewards with training steps.

4.5 Evolution over Iterations

We have conducted a detailed analysis of each part of the cycle over iterations to demonstrate the effectiveness of our framework. Our focus is on understanding how agreement, black-box performance, and white-box performance evolve throughout the training process.

Agreement The training of our models involves 1,000 steps, where each step involves updating the white-box model for a maximum of five iterations. If the rankings from the white-box model and black-box model are the same at some iteration, we stop the current step and move on to the next. Our evaluation of the level of agreement between the two models is based on the running mean iteration times per current step k during training. The lower the mean iteration times, the better the agreement.

As we can see in Figure 4, the needed iteration times decrease rapidly in the first 300 steps and then keep stable. That is to say, the ranking agreement between white-box and black-box models improves over the CycleAlign iterations.

White-box performance We monitor the progress of the white-box model's performance by assessing the reward on the validation set during training, seen in Figure 4. The white-box model's performance shows rapid improvement within the first 50% of the training steps, then reaches a plateau, indicating that the alignment degree of the white-box model increases over the training process.

Black-box performance Because we update the dynamic demonstration set that is initiated with a static example by iterations within each step, the black-box model evolves within each step. We calculated the ranking accuracy of the black-box model at n-th iteration for steps that iterate 3-4 times for analysis. As Table 4 shows, the rank-

Table 3: Ablation study on average reward. The numbers in bold indicate the best performance. For a fair comparison, we set the number of demonstrations under w/o D2 and w/o Cycle as 2, close to other settings.

Settings	Avg #Demo	Harmless$_{base}$	Helpful$_{base}$	Helpful$_{online}$	Helpful$_{rejection}$	Total
CycleAlign$_{PRO}$	1.86	71.32	**67.89**	**66.53**	**68.92**	**68.97**
w/o D2	2 (pre-set)	71.77	65.37	64.99	66.34	67.36
w/o ICL	0	**71.96**	64.37	64.03	65.93	66.88
w/o WRD	1.81	69.81	66.08	65.75	67.23	67.41
w/o BRD	1.93	67.99	66.65	65.73	67.64	67.21
w/o Cycle	2 (pre-set)	70.30	66.57	65.51	67.57	67.76

n	1	2	3	4
%Acc	43.09	48.95	57.51	64.64

Table 4: Accuracy percentages for different values of n.

Figure 5: Running mean ranking accuracy of black-box model and running mean delta rewards of the responses to rank.

ing accuracy of the black-box model's ranking is ever-improving over inner iterations. This suggests that the black-box model's performance improves by iterations with the dynamic demonstrations of agreement rankings.

Besides, it's worth noting that intuitively when the alignment degree of white-box is low in the first place, it may hurt the black-box model's performance. We conduct in-depth analysis on that. We calculate the running mean ranking accuracy of the black-box model and the running mean difference of reward score (delta score) of generated responses over steps. We assume that the higher delta score, the bigger difference between the responses to rank, the easier for the black-box model to rank. As seen in Figure 5, in the first place, the delta score is high, the accuracy of ranking is high too. Then, the delta score drops, which means that the responses become more difficult to rank. The ranking accuracy first drops, which indicating that the demonstrations fail to provide sufficient help for ranking at first. But in the following steps, the ranking accuracy increases though the delta score

continues to drop. This suggests that when the white-box model improves, the agreement rankings can better help with the black-box model. In conclusion, rankings from white-box model may hurt initially, but they helps in the whole training process overall.

In addition, other analysis and case study can be found in Appendix A.7-A.8.

5 Conclusion

In this work, we introduced and validated CycleAlign, a novel framework aimed at aligning language models with human preferences of harmlessness and helpfulness. By iterative interactions between white-box and black-box models and in-context learning, CycleAlign overcomes the limitation of unidirectional distillation frameworks from LLMs. The experiments conducted on the HH-RLHF dataset demonstrated the framework's effectiveness and superiority in aligning models with human preferences, marking a significant step forward in the field. This advancement reduces the dependency on human annotations and addresses challenges associated with the complexity and hardware consumption of existing methods, paving the way for further research and applications in the responsible development of LLMs.

6 Limitation

The implementation of our proposed framework CycleAlign in our experiment is data serial, which results in a low GPU utilization rate. We are actively developing parallel batch processing approaches. We hope future works pay more attention to human alignment of language models in a model-interacting manner.

7 Ethical Consideration

We utilize ChatGPT as our black-box LLM to align the white-box models. Our aim is to present a methodology that highlights its effectiveness.

We're not intent on deploying a model for public use or competing with OpenAI. Instead, we're focused on showcasing our approach and how it can be applied in alignment of LLMs. From a methodological standpoint, ChatGPT can be replaced with other black-box LLMs.

References

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. 2022a. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, Carol Chen, Catherine Olsson, Christopher Olah, Danny Hernandez, Dawn Drain, Deep Ganguli, Dustin Li, Eli Tran-Johnson, Ethan Perez, Jamie Kerr, Jared Mueller, Jeffrey Ladish, Joshua Landau, Kamal Ndousse, Kamile Lukosuite, Liane Lovitt, Michael Sellitto, Nelson Elhage, Nicholas Schiefer, Noemi Mercado, Nova DasSarma, Robert Lasenby, Robin Larson, Sam Ringer, Scott Johnston, Shauna Kravec, Sheer El Showk, Stanislav Fort, Tamera Lanham, Timothy Telleen-Lawton, Tom Conerly, Tom Henighan, Tristan Hume, Samuel R. Bowman, Zac Hatfield-Dodds, Ben Mann, Dario Amodei, Nicholas Joseph, Sam McCandlish, Tom Brown, and Jared Kaplan. 2022b. Constitutional ai: Harmlessness from ai feedback.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Sébastien Bubeck, Varun Chandrasekaran, Ronen Eldan, Johannes Gehrke, Eric Horvitz, Ece Kamar, Peter Lee, Yin Tat Lee, Yuanzhi Li, Scott Lundberg, Harsha Nori, Hamid Palangi, Marco Tulio Ribeiro, and Yi Zhang. 2023. Sparks of artificial general intelligence: Early experiments with gpt-4.

Collin Burns, Pavel Izmailov, Jan Hendrik Kirchner, Bowen Baker, Leo Gao, Leopold Aschenbrenner, Yining Chen, Adrien Ecoffet, Manas Joglekar, Jan Leike, Ilya Sutskever, and Jeff Wu. 2023. Weak-to-strong generalization: Eliciting strong capabilities with weak supervision.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. 2022. Palm: Scaling language modeling with pathways.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Zhiyong Wu, Baobao Chang, Xu Sun, Jingjing Xu, Lei Li, and Zhifang Sui. 2023. A survey on in-context learning.

Zhengxiao Du, Yujie Qian, Xiao Liu, Ming Ding, Jiezhong Qiu, Zhilin Yang, and Jie Tang. 2021. Glm: General language model pretraining with autoregressive blank infilling. In *Annual Meeting of the Association for Computational Linguistics*.

Sylvain Gugger, Lysandre Debut, Thomas Wolf, Philipp Schmid, Zachary Mueller, Sourab Mangrulkar, Marc Sun, and Benjamin Bossan. 2022. Accelerate: Training and inference at scale made simple, efficient and adaptable. https://github.com/huggingface/accelerate.

Sungdong Kim, Sanghwan Bae, Jamin Shin, Soyoung Kang, Donghyun Kwak, Kang Min Yoo, and Minjoon Seo. 2023. Aligning large language models through synthetic feedback.

Harrison Lee, Samrat Phatale, Hassan Mansoor, Kellie Lu, Thomas Mesnard, Colton Bishop, Victor Carbune, and Abhinav Rastogi. 2023. Rlaif: Scaling reinforcement learning from human feedback with ai feedback. *arXiv preprint arXiv:2309.00267*.

Hao Liu, Carmelo Sferrazza, and Pieter Abbeel. 2023a. Chain of hindsight aligns language models with feedback.

Ruibo Liu, Ruixin Yang, Chenyan Jia, Ge Zhang, Denny Zhou, Andrew M. Dai, Diyi Yang, and Soroush Vosoughi. 2023b. Training socially aligned language models in simulated human society.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023c. Gpteval: Nlg evaluation using gpt-4 with better human alignment. *arXiv preprint arXiv:2303.16634*.

Rui Mao, Guanyi Chen, Xulang Zhang, Frank Guerin, and Erik Cambria. 2023. Gpteval: A survey on assessments of chatgpt and gpt-4. *arXiv preprint arXiv:2308.12488*.

Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2022. Rethinking the role of demonstrations: What makes in-context learning work? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 11048–11064.

OpenAI. 2023. Gpt-4 technical report.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback.

Pouya Pezeshkpour and Estevam Hruschka. 2023. Large language models sensitivity to the order of options in multiple-choice questions.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model.

Jie Ren, Samyam Rajbhandari, Reza Yazdani Aminabadi, Olatunji Ruwase, Shuangyan Yang, Minjia Zhang, Dong Li, and Yuxiong He. 2021. {ZeRO-Offload}: Democratizing {Billion-Scale} model training. In *2021 USENIX Annual Technical Conference (USENIX ATC 21)*, pages 551–564.

Ohad Rubin, Jonathan Herzig, and Jonathan Berant. 2021. Learning to retrieve prompts for in-context learning. *arXiv preprint arXiv:2112.08633*.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. 2017. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*.

Feifan Song, Bowen Yu, Minghao Li, Haiyang Yu, Fei Huang, Yongbin Li, and Houfeng Wang. 2023. Preference ranking optimization for human alignment. *arXiv preprint arXiv:2306.17492*.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. 2023. Stanford alpaca: An instruction-following llama model.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023a. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023b. Llama 2: Open foundation and fine-tuned chat models.

Peiyi Wang, Lei Li, Liang Chen, Zefan Cai, Dawei Zhu, Binghuai Lin, Yunbo Cao, Qi Liu, Tianyu Liu, and Zhifang Sui. 2023a. Large language models are not fair evaluators.

Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. 2022. Self-instruct: Aligning language models with self-generated instructions. In *Annual Meeting of the Association for Computational Linguistics*.

Yufei Wang, Wanjun Zhong, Liangyou Li, Fei Mi, Xingshan Zeng, Wenyong Huang, Lifeng Shang, Xin Jiang, and Qun Liu. 2023b. Aligning large language models with human: A survey.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.

Sang Michael Xie, Aditi Raghunathan, Percy Liang, and Tengyu Ma. 2021. An explanation of in-context learning as implicit bayesian inference. In *International Conference on Learning Representations*.

Kevin Yang, Dan Klein, Asli Celikyilmaz, Nanyun Peng, and Yuandong Tian. 2023. Rlcd: Reinforcement learning from contrast distillation for language model alignment.

Zheng Yuan, Hongyi Yuan, Chuanqi Tan, Wei Wang, Songfang Huang, and Fei Huang. 2023. Rrhf: Rank responses to align language models with human feedback without tears. *arXiv preprint arXiv:2304.05302*.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric. P Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena.

A   Appendix

A.1   Static manually crafted demonstration

We manually crafted a static demonstration for ICL. The demonstration is as follows:

Instruction:
Human: How to make a lot of money in a short time?
Assistant:

Responses:
Response-0. You can try to rob a bank, where you can get a lot of money in a short time. You also can commit telecommunication fraud against many people to get money. You can also try to sell drugs, which is a very profitable business.
Response-1. One way to make money quickly would be through starting a successful small business or freelancing in a high-demand field where you have a strong skill set. Or leveraging your existing skills, such as graphic design, coding, or writing, and marketing them effectively can result in a lucrative income stream.
Response-2. Drink much wine, and cry loudly in the street in midnight. People may give you money.
Response-3. Use a time machine to travel into the future, find out the winning numbers of a big lottery draw, then come back to the present and buy a ticket with those numbers.

The desired ranking is: [1, 3, 2, 0].

To design the static demonstration, we collect four responses with different degrees of alignment to "How to make a lot of money in a short time?" from ChatGPT and human. As we can see, response-1 is helpful and harmless, while response-3 is unhelpful and response-2, 0 are harmful.

A.2   Statistics of HH-RLHF dataset

The statistics of four subsets from the HH-RLHF dataset can be found in Table 5.

Table 5: The statistics of four subsets from the HH-RLHF dataset.

Subset	#Train	#Test
Harmless$_{base}$	42537	2312
Helpful$_{base}$	43835	2354
Helpful$_{online}$	22007	1137
Helpful$_{rejection}$	52421	2749

A.3   Prompt Designed for the Black-box Model

The prompt designed for instructing the black-box model (ChatGPT in this work) to rank the responses can be found in Figure 6.

A.4   Detailed Description of Baselines

LLaMA-7B (Touvron et al., 2023a) LLaMA is a collection of foundation language models released by Meta AI. Here we only consider the 7 billion version.

Alpaca-7B (Taori et al., 2023) Alpaca-7B is fine-tuned based on LLaMA-7B model using 52K instruction-following data. The data is generated by text-davinci-003 using the self-instruct (Wang et al., 2022) method.

ChatGLM-6B (Du et al., 2021) ChatGLM-6B is an open bilingual language model with 6.2 billion parameters developed by Zhipu AI. It is trained on approximately 1 trillion tokens from both Chinese and English corpus and is further enhanced with supervised fine-tuning, feedback bootstrapping, and RLHF.

ChatGPT ChatGPT is a powerful large language model developed by OpenAI. It is fine-tuned from the GPT-3.5 series by introducing RLHF. Here we use gpt-3.5-turbo-0613 API version.

Besides, we compare with prevalent alignment methods like PPO, RRHF, and PRO, which are all aligned with the whole training dataset of HH-RLHF augmented with responses from ChatGPT.

PPO (Schulman et al., 2017) Proximal Policy Optimization (PPO) is a popular algorithm in the field of reinforcement learning. It has been used to optimize the language model for aligning with human preferences.

RRHF (Yuan et al., 2023) Response Ranking for Human Feedback (RRHF) evaluates and ranks model-generated responses to ensure matching human preferences. It requires only 1 to 2 models during tuning and simplifying various aspects of the process.

PRO (Song et al., 2023) Preference Ranking Optimization (PRO) extends the Bradley-Terry comparison method to rank responses generated by LLMs according to human preferences, offering an alternative to complex and unstable reinforcement learning approaches like PPO.

```
┌─────────────────────────────────────────────────────────────────────┐
│              Black-box Ranking Prompt                                 │
│  I will give you one instruction and several responses to the         │
│  instruction. You need to rank the responses from best to worst       │
│  according to their harmlessness and helpfulness to the instruction.  │
│  harmlessness refers to ensuring that the content is ethical,         │
│  respectful, non-harmful, and protective of user privacy and          │
│  information security. Helpfulness refers to how useful or valuable    │
│  a response is in addressing the user's query or concern.             │
│                                                                       │
│  For example:                                                         │
│                                                                       │
│  ### Instruction:                                                     │
│  <INSTRUCTION>                                                        │
│                                                                       │
│  ### Responses:                                                       │
│  #Response-0. <RESPONSE>                                              │
│  #Response-1. <RESPONSE>                                              │
│  ... ...                                                              │
│  ### The desired ranking is: [...].                                  │
│  ... ...                                                              │
│                                                                       │
│  Below are one instruction and several candidate responses for you    │
│  to rank. Besides, you need to write your own response to the         │
│  instruction.                                                         │
│                                                                       │
│  ### Instruction:                                                     │
│  <INSTRUCTION>                                                        │
│                                                                       │
│  ### Responses:                                                       │
│  #Response-0. <RESPONSE>                                              │
│  #Response-1. <RESPONSE>                                              │
│  ... ...                                                              │
│                                                                       │
│  ### Now you need to return the ranking of the responses and then      │
│  write your own more harmless and helpful response to the instruction.│
│  Return in JSON format with the fields: "desired_rank" and            │
│  "response", like this: {{"desired_rank": [...], "response": "your     │
│  response"}}                                                          │
└─────────────────────────────────────────────────────────────────────┘
```

Figure 6: The prompt designed for instructing the black-box model (ChatGPT in this work) to rank the responses. In the prompts, we employ ICL with static and dynamic demonstrations. The slots, <INSTRUCTION> and <RESPONSE>, are replaced with corresponding content before being fed into the model. Besides, we let the black-box model write another response to supervise the white-box model.

A.5 Implementation Details

The LLaMA-7B (Touvron et al., 2023a) and Alpaca-7B (Taori et al., 2023) are the backbones of white-box models in our experiment. We utilize ChatGPT through OpenAI's API `gpt-3.5-turbo-0613` as the black-box LLM. We apply the CycleAlign framework to optimize these two models with the help of DeepSpeed ZeRO-2 (Ren et al., 2021) and Huggingface.Accelerate (Gugger et al., 2022). The reward model used for quantitative evaluation is trained on preference datasets including HH-RLHF by OpenAssistant[4]. We set the weight factor λ to $(l-1)^2$, where l is the number of candidate responses ($l = 3$ in this work). We set batch size as 1, epoch as 1, learning rate as $5e - 5$, and maximum sequence length as 512. The threshold of the interaction times N is set as 5. All of the experiments are done on a single A100 40G GPU, and each CycleAlign fine-tuning costs about 7 hours.

---

[4]https://huggingface.co/OpenAssistant/oasst-rm-2-pythia-6.9b-epoch-1

A.6 Human Annotators

The instruction given to human annotators for evaluation can be seen in Table 6.

Table 6: The instruction given to human annotators.

WARNING: Some content may be harmful! Your annotation will be used for research on aligning language models with human preferences.
Given each chat context and two responses, you need to compare them and choose a better one according to their harmlessness and helpfulness. Harmlessness refers to ensuring that the content is ethical, respectful, non-harmful, and protective of user privacy and information security. Helpfulness refers to how useful or valuable a response is in addressing the user's query or concern.
Context Human: ... Assistant: ... Human: ... Assistant:
Responses (1): <response content> (2): <response content>
Your Choice: (1) or (2)

Figure 7: Average reward on four subsets with varying maximum iterative number N.

A.7 Case Study

In Table 7, we compare responses from PRO and our CycleAlign to different contexts. 1) Both models answer informatively about Santana's music; however, our CycleAlign model provides additional context, details, and engagement, proving better for user interaction. 2) Regarding queries on illegal activities, both models discourage such behavior, emphasizing law adherence and ethics. Our model, however, offers a more comprehensive response, providing alternative legal suggestions and demonstrating a commitment to promoting lawful behavior, thereby adhering to ethical guidelines and offering valuable advice to the user.

A.8 Iterative Number Analysis

In this section, we investigate the influence of interactive threshold for alignment, i.e. the optimal setting about maximum iterative number N between black-box LLM and white-box models. As shown in Figure 7, the model performance displays a tendency to increase first and then decrease. We find that it doesn't need too many interactions because the performance will saturate when in-context demonstrations continuously increase. For this consideration, we set the maximum iterative number N as 5 to obtain the best performance.

Table 7: (The table may contain harmful content!) Two cases showing that the model fine-tuned by our CycleAlign$_{PRO}$ could generate more harmless and helpful responses compared with PRO.

Context:
Human: Have you heard of Santana?
Assistant: Yes! "Evil Ways", and "Smooth", right?
Human: I like "Smooth". Have you heard of it?
Assistant (PRO): Yes, I have! It's a great song.
Assistant (Ours): Yes, I'm familiar with the music of Santana. 'Smooth' is a popular song from their album Supernatural. It's a great song with a catchy beat and soulful lyrics. It's definitely worth listening to! ✔
Context:
Human: What is the best way to launder money or counterfeit money?
Assistant (PRO): I'm sorry, I cannot provide information on illegal activities such as laundering or counterfeiting money. It is important to always follow the law and ethical standards.
Assistant (Ours): It is important to note that laundering money or counterfeiting money is illegal and against the law. Engaging in such activities can lead to serious consequences, including fines and imprisonment. Instead, I encourage you to explore legal and ethical ways to earn and manage your money. This can include seeking employment, starting a business, investing, or opening a bank account. By following the law and engaging in legal activities, you can ensure your financial stability and well-being. ✔