Fast Sharpness-escaping Optimization for Long-tailed Learning

Abstract

Deep neural networks often suffer from poor generalization in long-tailed settings. From a loss landscape perspective, this degradation is largely attributed to the tendency of the optimization process to converge into sharp, unstable minima for underrepresented data. We investigate the recently proposed Muon optimizer, providing theoretical evidence that its gradient orthogonalization amplifies updates along directions of negative curvature to facilitate escaping these sharp minima. While effective, the Muon optimizer imposes heavy computational overhead in long-tailed scenarios. To reconcile efficiency with optimization quality in long-tailed learning, we propose Fast Sharpness-escaping Optimization (FaSO). FaSO employs a compositional probabilistic schedule that couples lightweight exploration with increasingly frequent computationally intensive orthogonalized updates. This design targets the escape from sharp minima precisely when it is critical for tail-class generalization. Extensive experiments demonstrate that FaSO outperforms existing methods without incurring substantial computational costs, effectively securing flatter minima for tail classes.

1 Introduction

Deep learning has significantly advanced a wide range of domains, from computer vision to large language models, achieving unprecedented performance largely driven by massive, high-quality datasets (Russakovsky et al., 2015). However, real-world data often exhibit long-tailed distributions, where dominant head classes overshadow underrepresented tail classes (Buda et al., 2018). This imbalance causes traditional learning algorithms to bias toward head classes, resulting in poor generalization for tail classes. To address this, various strategies have been proposed, including re-sampling (Chawla et al., 2002), decoupling (Kang et al., 2020), loss re-balancing (Ma et al., 2023; Luo et al., 2024), and contrastive learning (Zhu et al., 2022; Du et al., 2024). While these methods mitigate the dominance of head classes, they often risk overfitting by overexposing limited tail samples, highlighting the need for more robust optimization perspectives.

Recent studies (Rangwani et al., 2022; Li et al., 2025b) provide a crucial geometric perspective, showing that tail classes tend to converge into sharp regions of the loss landscape, characterized by large Hessian eigenvalues. Consequently, these underrepresented classes often exhibit poor generalization performance. A promising direction to address this is Sharpness-Aware Minimization (SAM) (Foret et al., 2021; Liu et al., 2022; Li et al., 2025a), a technique that focuses on escaping sharp minima by minimizing loss in a neighborhood of perturbed weights. However, SAM requires twice the number of backpropagation steps (Zhou et al., 2023a), incurring significant computational costs that hinder its scalability to large-scale datasets and models.

To overcome these challenges without redundant backpropagation, we turn to the recently proposed Muon optimizer (Jordan et al., 2024; Shen et al., 2025), which orthogonalizes gradient updates via Newton-Schulz iteration. We provide theoretical insights demonstrating that Muon's gradient orthogonalization amplifies the update's projection along directions of negative curvature, facilitating a more effective escape from the sharp minima that disproportionately entrap underrepresented classes. However, despite its geometric advantages, we observe that Muon introduces non-negligible additional computational overhead in practical training due to its iterative matrix operations, particularly in scenarios with limited batch sizes or convolutional architectures. This creates a critical trade-off between optimization quality and overall training efficiency.

In this paper, we introduce a novel compositional optimization approach, termed FaSO, to further balance training cost with the benefits of Muon. Prior studies (Fang et al., 2019; Rangwani et al., 2022) and our observations suggest that while SGD effectively navigates early landscapes, it struggles to escape sharp minima as it becomes deterministic in later stages. Consequently, FaSO employs a dynamic stochastic schedule that prioritizes efficient SGD during early exploration and progressively transitions to computationally intensive orthogonalized updates as training matures. By concentrating Muon's geometric advantages on the final convergence phase, FaSO targets the escape from sharp minima precisely when it is most critical for the generalization of tail classes, thereby maximizing performance without excessively increasing the computational burden. Our contributions are summarized as follows:

1. We provide theoretical insights into Muon from the loss-landscape perspective, showing that it amplifies negative-curvature gradients to facilitate sharp-minima escape, which is critical for tail-class generalization.

2. We propose a novel method, FaSO, to balance training cost and performance in long-tailed learning. Using a stochastic schedule that progressively increases the probability of orthogonalized updates over training, FaSO helps the model escape sharp regions near convergence without significantly increasing training costs.

3. We conduct extensive experiments across a variety of datasets, demonstrating that both Muon and FaSO consistently outperform existing long-tailed learning methods. Notably, FaSO achieves performance comparable to Muon while reducing computational overhead by more than 50%.

2 Related Work

2.1 Long-tailed Learning

There have been substantial explorations in recent years to address the challenges of long-tailed learning. At the data level, re-sampling (Chawla et al., 2002; He et al., 2008) and data augmentation techniques (Zhang et al., 2018; Yun et al., 2019; Ahn et al., 2023) focus on modifying the training data distribution to mitigate class imbalance. At the representation level, decoupling frameworks (Kang et al., 2020; Xuan & Zhang, 2024) separate the feature learning stage from classifier training, allowing for independent optimization of each component. Multi-expert architectures (Wang et al., 2021b; Tan et al., 2024) employ multiple specialized networks to handle different class groups. Transfer learning approaches (Wang et al., 2021a; Li et al., 2024) enhance the feature space representation for minority classes with knowledge from related domains or tasks. At the loss level, re-weighting techniques (Cui et al., 2019; Luo et al., 2024) assign different weights, while margin-based techniques (Cao et al., 2019; Menon et al., 2021) impose class-specific decision boundaries during training. More recently, contrastive learning frameworks (Cui et al., 2021; Zhu et al., 2022; Du et al., 2024) have demonstrated promising results by encouraging uniformly discriminative feature representations across all classes. However, existing methods often suffer from the risk of overfitting due to limited tail class samples, highlighting the need for more robust optimization methods that can effectively navigate the complex loss landscapes inherent in imbalanced learning scenarios.

2.2 Sharpness of Loss Landscape

Generalization remains a central challenge in deep learning, fundamentally determined by the optimization process. Recent studies (Jiang et al., 2020; Stutz et al., 2021; Li et al., 2025b) demonstrate that the loss landscape's geometry is intrinsically linked to generalization, where flatter minima typically generalize better than sharper ones. This relationship is particularly salient in imbalanced learning, where minority class landscapes are frequently dominated by sharp regions (Zhou et al., 2023a). While traditional approaches like Perturbed Gradient Descent (Ge et al., 2015; Jin et al., 2017) employ random noise to escape such regions, they often exhibit suboptimal performance in imbalanced settings due to a lack of sufficient directional guidance (Rangwani et al., 2022). Sharpness-Aware Minimization (SAM) (Foret et al., 2021) offers a more principled alternative by identifying sharp maximal points and explicitly minimizing neighborhood sharpness. This approach has proven effective in promoting flatter convergence for imbalanced data (Rangwani et al., 2022). Nevertheless, SAM and its variants (Zhou et al., 2023a; Lyu et al., 2025) incur at least double the computational cost of SGD, posing significant scalability bottlenecks where efficiency is paramount.

(a) $\lambda_{\max}$ (b) $\mathrm{Tr}(\mathbf{H})$

Figure 1: (a) Maximum eigenvalues $\lambda_{\max}$ ($\downarrow$) and (b) trace of Hessian metric $\mathrm{Tr}(\mathbf{H})$ ($\downarrow$) across classes with different number of samples. Classes with fewer training samples consistently exhibit larger values for both metrics, indicating that these under-represented classes converge to sharper minima in the loss landscape, which can lead to poor generalization performance in long-tailed learning.

3 Method

In this section, we first establish the preliminaries of our work, including the problem setup and the mechanics of the Muon optimizer. We then present our theoretical analysis of Muon, which serves as the foundation for our work by identifying its capability to escape sharp regions in the loss landscape. Building on these findings, we introduce our primary method, FaSO, a dynamic optimization method designed to leverage these theoretical benefits in a computationally efficient and practically effective manner.

3.1 Problem Setup

Let $\mathcal{D} = \{(x_i, y_i)\}_{i=1}^N$ be a training dataset of N samples, where $x_i \in \mathcal{X}$ is an input sample and $y_i \in \mathcal{Y} = \{1, \ldots, C\}$ is its corresponding class label. We denote the number of samples in each class as $\{n_1, \ldots, n_C\}$, and assume, without loss of generality, that $n_i > n_j$ for any $i > j$. Real-world datasets often exhibit a long-tailed distribution with $n_1 \gg n_C$, where a small number of majority classes contain abundant samples while numerous minority classes are data-scarce. Our goal is to learn a deep neural network $h(\cdot; w)$ parameterized by $w \in \mathcal{W}$ that minimizes the empirical risk $\mathcal{L} = \frac{1}{N} \sum_{(x,y) \in \mathcal{D}} \ell(h(x; w), y)$, where ℓ denotes a loss function.

3.2 Preliminaries

Review of Muon. To analyze the optimization dynamics, we focus our discussion, for clarity, on a single parameter matrix $\mathbf{W} \in \mathbb{R}^{m \times n}$. The principles can be extended to the entire parameter set (Kovalev, 2025). We consider two optimization methods: the standard SGD optimizer and the Muon optimizer. For the SGD optimizer, the update rule for a parameter matrix $\mathbf{W}_t$ at iteration t is:

$$\mathbf{W}_{t+1} = \mathbf{W}_t - \eta_t \mathbf{g}_t, \quad \text{where} \quad \mathbf{g}_t = \nabla \mathcal{L}(\mathbf{W}_t). \tag{1}$$

Here, $\eta_t > 0$ is the learning rate and $\mathbf{g}_t$ denotes the stochastic gradient with respect to $\mathbf{W}_t$. For the Muon optimizer, the gradient is first transformed via a Newton-Schulz iteration process and then used to update the parameter $\mathbf{W}_t$. Specifically, the update is performed as:

$$\mathbf{O}_t = \text{Newton–Schulz}(\mathbf{g}_t), \quad \mathbf{W}_{t+1} = \mathbf{W}_t - \eta_t \mathbf{O}_t. \tag{2}$$

The central idea of Muon optimizer is to employ the Newton-Schulz iteration process to approximately compute the polar decomposition $\mathbf{O}_t$ of $\mathbf{g}_t$, which corresponds to $\mathbf{O}_t = \mathbf{U}_t \mathbf{V}_t^T$ in the singular value decomposition (SVD) of $\mathbf{g}_t = \mathbf{U}_t \boldsymbol{\Sigma}_t \mathbf{V}_t^\top$. Suppose $\mathbf{g}_t \in \mathbb{R}^{m \times n}$ is the gradient matrix with rank r_t, $\boldsymbol{\Sigma}_t \in \mathbb{R}^{r_t \times r_t}$ is a diagonal matrix containing the singular values of $\mathbf{g}_t$, $\mathbf{U}_t \in \mathbb{R}^{m \times r_t}$ and $\mathbf{V}_t \in \mathbb{R}^{n \times r_t}$ are the left and right singular vector matrices of $\mathbf{g}_t$, respectively. The update matrix becomes $\mathbf{U}_t \mathbf{V}_t^\top$, which represents the closest semi-orthogonal matrix to $\mathbf{g}_t$. Conceptually, this orthogonalization procedure maintains the structural properties of the update matrices, thereby preventing the parameters from being updated along a few dominant directions.

Newton-Schulz Iteration Process. This iterative process begins by normalizing the gradient matrix $\mathbf{G}_t = \mathbf{g}_t / \|\mathbf{g}_t\|_{\mathrm{F}}$, where $\|\cdot\|_{\mathrm{F}}$ is the Frobenius norm. The iteration is then initialized with $\mathbf{X}_0 = \mathbf{G}_t$, at each step k of the N-step iteration, $\mathbf{X}_k$ is updated from $\mathbf{X}_{k-1}$ as:

$$\mathbf{X}_k = a\mathbf{X}_{k-1} + b(\mathbf{X}_{k-1}\mathbf{X}_{k-1}^{\mathrm{T}})\mathbf{X}_{k-1} + c(\mathbf{X}_{k-1}\mathbf{X}_{k-1}^{\mathrm{T}})^2\mathbf{X}_{k-1}, \tag{3}$$

where $\mathbf{X}_N$ denotes the final output after N iterative steps. The parameters a, b, and c are iteration coefficients. To guarantee proper convergence of Equation (3), these coefficients must be tuned such that the polynomial $p(x) = ax + bx^3 + cx^5$ maintains a fixed point in the neighborhood of 1. Following the original formulation (Jordan et al., 2024), we employ the coefficient values $a = 3.4445$, $b = -4.7750$, $c = 2.0315$, and perform 5 iterations. These coefficients are specifically designed to accelerate the convergence rate for matrices with small initial singular values.

3.3 Escaping Sharp Minima in Long-tailed Learning

Tail Classes Converge to Sharp Minima. We consider the minimization of a smooth, potentially non-convex objective function f (e.g., cross-entropy loss). The geometry of this landscape is often characterized by the spectral properties of its Hessian matrix $\mathbf{H}$. Key indicators of sharpness include the largest eigenvalue $\lambda_{\max}$ and the trace $\mathrm{Tr}(\mathbf{H})$, where larger value metrics indicate a sharper, more challenging optimization terrain. Following prior work (Rangwani et al., 2022), we empirically investigate this relationship by computing the eigen spectrum of the Hessian for each class on the long-tailed dataset CIFAR-10 LT. As depicted in Figure 1, there is a clear trend where both $\lambda_{\max}$ and $\mathrm{Tr}(\mathbf{H})$ increase substantially as the number of samples per class decreases. This validates that models trained on tail classes are more prone to converging within sharper regions of the loss landscape. Consequently, an optimizer's capability to navigate towards flatter minima is paramount for robust generalization, a necessity that is especially pronounced in imbalanced learning.

Escaping from Sharp Minima. In the following, we demonstrate that the Muon algorithm can amplify the gradient projection along directions of negative curvature as training approaches convergence, thereby enabling accelerated escape from sharp areas and convergence to flatter minima. Our analysis leverages the Correlated Negative Curvature (CNC) assumption (Daneshmand et al., 2018).

Assumption 3.1 (Correlated Negative Curvature (CNC)). *Let $\mathbf{W}_t$ be a point where the Hessian $\nabla^2 f(\mathbf{W}_t)$ has a minimum eigenvalue $\lambda_{\min}$ at iteration t, and let $\mathbf{v}_{\mathbf{W}_t}$ be the corresponding unit eigenvector. The stochastic gradient $\mathbf{g}_t = \nabla f(\mathbf{W}_t)$ satisfies the CNC assumption if the second moment of its projection onto $\mathbf{v}_{\mathbf{W}_t}$ is uniformly bounded away from zero, i.e.,*

$$\exists \gamma > 0, \quad \text{s.t.} \quad \forall \mathbf{W}_t : \quad \mathbb{E}[\langle \mathbf{v}_{\mathbf{W}_t}, \mathbf{g}_t \rangle^2] \geq \gamma. \tag{4}$$

This assumption posits that the stochastic gradient has a projection along the direction of most negative curvature, providing a signal for the optimizer to move away from sharp regions. This assumption has been theoretically justified in the context of learning half-spaces and has also been empirically validated across a wide range of neural networks with varying complexity (Staib et al., 2019; Wang et al., 2020). We now present Theorem 3.2, with the detailed proof provided in Appendix B.

Theorem 3.2. *Let $\mathbf{W}_t$ be a point where the Hessian $\nabla^2 f(\mathbf{W}_t)$ has a minimum eigenvalue at iteration t, and let $\mathbf{v}_{\mathbf{W}_t}$ be the corresponding unit eigenvector. Define the projection of the SGD update onto $\mathbf{v}_{W_t}$ as $proj_{SGD} = \langle \mathbf{v}_{\mathbf{W}_t}, \mathbf{g}_t \rangle$, and the projection of the Muon update onto $\mathbf{v}_{\mathbf{W}_t}$ as $proj_{Muon} = \langle \mathbf{v}_{\mathbf{W}_t}, \mathbf{O}_t \rangle = \langle \mathbf{v}_{\mathbf{W}_t}, \mathbf{U}_t\mathbf{V}_t^\top \rangle$. Under the CNC assumption, the following inequality holds:*

$$\exists \gamma > 0, \quad s.t. \quad \forall \mathbf{W}_t : \quad \mathbb{E}\left[(proj_{Muon})^2\right] \geq \mathbb{E}\left[(proj_{SGD})^2\right] \geq \gamma. \tag{5}$$

Remark. Theorem 3.2 reveals that Muon's gradient orthogonalization amplifies the update's projection onto the negative curvature direction, enabling a more effective escape from sharp regions. Furthermore, prior analysis (Daneshmand et al., 2018) has shown that the convergence rate of SGD depends on the value γ as $\mathcal{O}(\gamma^{-4})$ under certain assumptions. Our findings suggest Muon effectively enhances the gradient component of SGD in the direction of negative curvature. Consequently, Muon is reasonably expected to converge more rapidly to flatter minima, leading to better generalization. This aligns with the empirical evidence found in prior studies (Liu et al., 2025; Shah et al., 2025).

(a) Scheduling Method Comparison   (b) Generalization Comparison

Figure 2: (a) Top-1 accuracy (%) (↑) comparison of various probability scheduling methods. Experiments are conducted on CIFAR-100 LT (IF=100) across various loss functions. Results show that the sinusoidal schedule achieves better performance. (b) Top-1 accuracy (%) (↑) comparison between SGD and Muon on both the balanced CIFAR-100 and CIFAR-100 LT (IF=100) across various loss functions. Results demonstrate that Muon is particularly effective for improving generalization performance in long-tailed settings.

3.4 FaSO: A Compositional Optimization Approach

Computational Overhead Analysis. While Theorem 3.2 establishes the theoretical advantage of the Muon optimizer in escaping sharp regions, its computational overhead presents practical challenges in long-tailed learning. For further analysis, we estimate the FLOP overhead introduced by the Newton-Schulz iteration. For a linear layer parameterized by a weight matrix $\mathbf{W} \in \mathbb{R}^{m \times n}$, each Newton-Schulz iteration requires approximately $6mn^2$ FLOPs. For T iterations, this amounts to $6Tmn^2$ FLOPs. The standard linear layer computation involves approximately $6mnL$ FLOPs, where L represents the number of inputs processed (Jordan et al., 2024). For linear layers $L = B$, where B denotes the batch size in tokens. Thus, the FLOP overhead $\Delta \mathcal{F}_{\text{linear}}$ for a linear layer can be estimated as:

$$\Delta \mathcal{F}_{\text{linear}} = \frac{T \cdot 6mn^2}{L \cdot 2mn} = \frac{3Tn}{B} \in \mathcal{O}\left(\frac{Tn}{B}\right). \tag{6}$$

For a convolutional layer, the kernel is flattened into an $m \times n$ matrix for optimization, where $m = C_{\text{out}}$ is the number of output channels and $n = C_{\text{in}} \cdot k^2$ is the product of the input channels and kernel size. The number of inputs per step is $L = B \cdot H_{\text{out}} \cdot W_{\text{out}}$, where H_{out} and W_{out} are the spatial dimensions (height and width) of the output tensor. The FLOP overhead $\Delta \mathcal{F}_{\text{conv}}$ is then:

$$\Delta \mathcal{F}_{\text{conv}} = \frac{T \cdot 6mn^2}{L \cdot 2mn} = \frac{3TC_{\text{in}}k^2}{BH_{\text{out}}W_{\text{out}}} \in \mathcal{O}\left(\frac{TC_{\text{in}}k^2}{BH_{\text{out}}W_{\text{out}}}\right). \tag{7}$$

Prior studies (Jordan et al., 2024) have shown that Muon maintains FLOPs overhead below 1% in large-scale language model training, where token counts per batch can reach millions (e.g., 16M tokens in LLaVA-405B). However, long-tailed recognition tasks typically employ much smaller batch sizes. This discrepancy introduces a new challenge: while Muon proves effective at escaping sharp minima, its computational overhead can become non-negligible in certain scenarios. For instance, in a ResNet layer with $C_{\text{in}} = 512, k = 3$, and an output feature map of 7×7, using $T = 5$ iterations with a batch size of $B = 256$ would result in an estimated overhead of 183% according to Equation (7). This substantial increase in training time could limit the scalability of using Muon.

Training Dynamics Insights. To balance computational efficiency with optimization performance, we focus on the training dynamics of SGD. Prior research (Fang et al., 2019; Rangwani et al., 2022; Abbe et al., 2023) indicates that in the early stages of training, the inherent stochasticity of SGD provides sufficient noise to effectively navigate away from sharp areas, but it behaves increasingly like deterministic gradient descent as training progresses and the learning rate decays, making it more prone to stalling near sharp regions late in training, especially in long-tailed scenarios. This observation suggests that the capability of Muon to reach flatter minima is most valuable during later training phases when SGD's inherent noise becomes insufficient. For more empirical observations, please refer to Appendix C.8.

Compositional Optimization Approach. Building on this insight, we propose FaSO, a compositional framework that probabilistically schedules between SGD and Muon updates based on training progress. Specifically, given a total training duration of T epochs, we define a selection probability $p_t \in [0, 1]$ for the current epoch t via a scheduling function $h : [0, 1] \to [0, 1]$, such that $p_t = h(t/T)$, where $h(\cdot)$ is a continuous, non-decreasing function. At each training iteration, the optimizer stochastically determines the update rule: it applies the Muon update with probability p_t, and the SGD update with probability $1 - p_t$. We formalize this by defining a composite gradient update operator $\tilde{\mathbf{g}}_t$. The expected update direction and the resulting parameter update rule are given by:

$$\mathbb{E}[\tilde{\mathbf{g}}_t] = (1 - p_t)\mathbf{g}_t + p_t\mathbf{O}_t, \tag{8}$$

$$\mathbf{W}_{t+1} = \mathbf{W}_t - \eta_t\tilde{\mathbf{g}}_t. \tag{9}$$

This monotonically increasing probability schedule ensures that SGD is predominantly selected during the early training phase (*i.e.,* Eq. (1)). This approach leverages SGD's inherent stochasticity for efficient exploration while mitigating the computational overhead associated with Muon. As training progresses, the probability of selecting Muon gradually increases (*i.e.,* Eq. (2)), providing the necessary geometric support to escape sharp minima precisely when SGD's noise becomes insufficient to prevent stalling. This dynamic approach maximizes the generalization benefits of Muon while maintaining high computational efficiency. Notably, both optimizers operate on the same parameter set, with Muon simply applying stateless orthogonalization to the gradients without introducing additional state or parameters.

Sinusoidal as Schedule Function. To further assess the appropriate design for $h(\cdot)$, we investigated several candidates: (1) *Linear*, where the probability increases linearly from 0 to 1; (2) *Phased*, which employs SGD exclusively in the first half of training and switches entirely to Muon in the second half; (3) *Exponential*, where the probability grows exponentially from 0 to 1; (4) *Sigmoid*, where the probability grows following a sigmoid function from 0 to 1; (5) *Sinusoidal*, where the probability grows following the first quarter-period of a sine wave; (6) *Alternating*, which alternates between Muon and SGD at each epoch. The results on CIFAR-100 LT with an imbalance factor of 100 are presented in Figure 2a. While these dynamic schedules generally outperform SGD, we observe that the sinusoidal schedule consistently achieves superior performance and stability across various loss functions. This finding highlights that gradually biasing the training process toward Muon in a sinusoidal manner offers more stability and adaptability. Consequently, we adopt the sinusoidal schedule as the default schedule function, i.e., $h = \sin\left(\pi t/2T\right)$. The pseudo-code for the training processes of Muon and our FaSO under this schedule are provided in Appendix A.

4 Experiments

4.1 Experimental Setup

Datasets. We evaluate the proposed Muon optimizer method on a suite of widely used long-tailed benchmarks: CIFAR-10 LT, CIFAR-100 LT, ImageNet-LT, and Places-LT. CIFAR-10 LT and CIFAR-100 LT are two long-tailed datasets sampled from the original CIFAR datasets (Krizhevsky et al., 2009). We conduct experiments under varying imbalance factors, defined as IF $= n_{\max}/n_{\min}$. Following the mainstream protocol (Cui et al., 2019), we adopt imbalance settings with imbalance factors of 10 and 100 for both datasets, where the number of samples per class decreases exponentially. Large-scale evaluations are conducted on the ImageNet-LT dataset (115.8k images across 1,000 categories) (Liu et al., 2019) derived from the ImageNet dataset (Russakovsky et al., 2015) and Places-LT (62.5k images across 365 categories) (Liu et al., 2019).

Evaluation Protocol. Following standard protocols in long-tailed learning (Wang et al., 2023), we report top-1 accuracy across *Many*, *Medium*, and *Few* splits (Cui et al., 2019; Rangwani et al., 2022). To assess computational efficiency, we also record the average training time per epoch associated with each method.

Baselines. We compare our method with a range of strong baselines commonly used in long-tailed classification. We evaluate four optimizers: SGD, SAM, Muon, and our proposed FaSO, applied to various widely used methods: Cross-Entropy (CE), Class-Balanced Loss (CB) (Cui et al., 2019), Logit Adjustment (LA) (Menon et al., 2021), Balanced Contrastive Learning (BCL) (Zhu et al., 2022), and Probabilistic

Table 1: Top-1 accuracy (%) (↑) results on *Many*, *Medium* (namely Med.), *Few*, and overall classes on CIFAR-10 LT and CIFAR-100 LT datasets across various loss functions, categorized by imbalance factors (IF) of 10 and 100. FaSO and Muon are highlighted in light gray for focused comparison.

Loss	Method	CIFAR-10 LT IF=100				CIFAR-100 LT IF=10				CIFAR-100 LT IF=100			
		Many	Med.	Few	All	Many	Med.	Few	All	Many	Med.	Few	All
CE	SGD	94.1	77.4	65.0	77.4	75.6	62.8	48.2	60.8	75.9	52.0	15.7	44.6
	SAM	95.7	76.7	64.4	77.5	76.7	64.4	49.0	61.9	77.5	51.1	15.8	44.9
	FaSO	95.2	76.9	64.3	77.3	77.1	65.4	49.7	**62.6**	77.2	53.9	16.2	**45.8**
	Muon	95.1	75.7	67.1	**78.1**	75.0	65.6	49.1	61.8	77.2	52.4	17.3	**45.8**
CB	SGD	94.8	77.0	66.0	77.9	75.1	63.5	48.4	60.9	75.0	50.6	17.3	44.6
	SAM	94.9	76.0	65.8	77.6	77.5	65.1	48.3	62.1	75.4	50.6	19.0	45.4
	FaSO	94.9	77.1	66.7	**78.3**	76.1	66.4	50.5	**62.9**	76.5	52.5	19.3	46.4
	Muon	95.1	77.9	66.0	**78.3**	76.4	65.9	50.6	**62.9**	76.4	52.2	19.7	**46.5**
LA	SGD	90.3	76.9	80.9	82.5	70.0	64.3	57.1	63.2	69.2	53.6	34.3	50.5
	SAM	91.9	78.2	81.9	83.8	72.6	64.5	58.8	64.6	67.6	54.6	35.8	51.0
	FaSO	91.5	78.0	82.0	83.7	71.9	65.0	58.6	64.5	69.3	55.0	34.8	51.2
	Muon	92.6	79.9	82.4	**84.7**	71.7	65.0	59.3	**64.7**	68.5	56.2	36.1	**51.9**
BCL	SGD	93.2	79.3	81.7	84.4	71.7	64.5	59.5	64.7	68.5	54.2	34.2	50.5
	SAM	94.0	80.8	82.7	85.5	72.5	65.2	60.0	65.3	68.1	53.5	37.1	51.3
	FaSO	93.9	80.2	82.1	85.1	73.9	66.0	60.4	**66.1**	71.1	57.5	36.3	**53.1**
	Muon	94.3	80.5	82.9	**85.6**	73.2	66.3	60.5	66.0	70.7	56.4	36.9	52.9
ProCo	SGD	93.6	80.7	82.2	85.2	71.8	64.7	59.2	64.6	68.9	55.4	36.2	51.8
	SAM	92.6	80.3	84.7	85.8	73.6	64.2	59.9	65.3	69.4	56.2	36.7	52.4
	FaSO	94.2	81.0	83.3	**85.9**	73.6	67.3	59.6	66.1	70.1	57.1	36.9	52.9
	Muon	94.2	81.6	82.9	**85.9**	73.8	65.4	61.5	**66.4**	70.0	57.4	37.2	**53.1**

Contrastive Learning (ProCo) (Du et al., 2024). This allows us to comprehensively assess the contribution of our optimizer across various long-tailed learning paradigms.

Implementation details. Our code is implemented with PyTorch 1.12.1. All experiments are carried out on NVIDIA GeForce RTX 3090 GPUs. For a fair comparison, we use ResNet32 on CIFAR-10 LT and CIFAR-100 LT, ResNet50 on ImageNet-LT, and pre-trained ResNet-152 on Places-LT. We train each model using a batch size of 256 (for CIFAR-10 LT and CIFAR-100 LT) / 128 (for ImageNet-LT) / 512 (for Places-LT), with a momentum of 0.9 and a weight decay of 0.0002. We adopt the Nesterov momentum form for all optimizers, with an initial learning rate of 3e-4; a multi-step schedule (decayed to 0.01 and 0.0001 at epochs 160 and 180) for CIFAR-10 LT and CIFAR-100 LT, and a cosine schedule throughout training for ImageNet-LT and Places-LT. For Newton-Schulz iteration steps N in the Muon optimizer, we set $N = 5$ for efficiency.

4.2 Comparison Results

Results on CIFAR-10 LT and CIFAR-100 LT. We first evaluate Muon and FaSO on CIFAR-10 LT and CIFAR-100 LT under imbalance factors (IF) of 10 and 100. As shown in Table 1, both methods consistently outperform SGD and SAM across all class subsets (*Many*, *Medium*, *Few*), with the largest gains on tail classes under severe imbalance. On CIFAR-10 LT, Muon achieves clear improvements over both baselines, particularly at IF=100 where it boosts tail accuracy without compromising head or medium classes. The advantage is even more pronounced on CIFAR-100 LT: Muon not only improves overall accuracy under both moderate and extreme imbalance, but also delivers substantial gains for tail classes; for instance, when paired with the CB loss, Muon improves tail class accuracy by 2.2% (IF=10) and 2.4% (IF=100) over SGD. Across all conditions, Muon maintains a consistent edge over SAM, highlighting its robustness in long-tailed learning.

Crucially, our proposed FaSO not only matches but sometimes even surpasses the performance of the Muon optimizer across various experimental settings. This indicates that our compositional optimization method

Table 2: Top-1 accuracy (%) (↑) results on *Many*, *Medium* (namely Med.), *Few*, and overall classes on ImageNet-LT (namely IN-LT) and Places-LT (namely PL-LT) datasets, categorized by different loss functions (CE, LA, and ProCo). FaSO and Muon are highlighted in light gray for focused comparison.

Dataset	Method	CE				LA				ProCo			
		Many	Med.	Few	All	Many	Med.	Few	All	Many	Med.	Few	All
IN-LT	SGD	69.4	42.2	14.8	49.0	64.3	52.4	35.1	54.6	66.3	54.3	37.8	56.7
	SAM	71.7	43.7	16.1	50.7	66.1	54.5	38.5	56.8	66.8	56.9	40.2	58.5
	FaSO	72.7	45.1	16.2	**51.8**	67.4	54.2	37.8	57.1	68.4	56.6	41.1	**59.0**
	Muon	72.5	44.1	16.1	51.2	68.5	54.5	37.4	**57.6**	67.3	56.0	39.5	58.1
PL-LT	SGD	46.3	22.0	4.4	27.3	42.0	40.3	27.4	38.4	43.6	42.0	26.4	39.5
	SAM	47.0	25.2	9.1	29.9	42.1	42.2	33.3	40.4	42.9	42.6	30.3	40.3
	FaSO	47.0	25.2	9.1	29.9	43.3	41.7	32.5	**40.5**	43.4	42.1	33.0	**40.8**
	Muon	47.6	26.9	10.7	**31.2**	43.4	41.6	33.1	**40.5**	43.4	42.2	31.9	40.6

Table 3: Loss landscape geometry metrics for SGD and Muon on CIFAR-10 LT and CIFAR-100 LT with imbalance factor 100. Maximum eigenvalue $\lambda_{\max}$ (↓) and trace of Hessian matrix $\mathrm{Tr}(\mathbf{H})$ (↓) are reported for the three least frequent classes. Superscripts (1), (2), and (3) denote the 1st, 2nd, and 3rd rarest classes, respectively. Lower values indicate flatter minima and improved generalization.

Dataset	Method	$\lambda_{\max}^{(1)}$	$\lambda_{\max}^{(2)}$	$\lambda_{\max}^{(3)}$	$\mathrm{Tr}(\mathbf{H})^{(1)}$	$\mathrm{Tr}(\mathbf{H})^{(2)}$	$\mathrm{Tr}(\mathbf{H})^{(3)}$
CIFAR-10 LT	SGD	968.51	516.88	560.69	2499.73	2263.09	2251.20
	Muon	**116.02**	**115.23**	**95.00**	**404.58**	**377.77**	**412.38**
CIFAR-100 LT	SGD	929.56	524.80	404.30	1560.40	1604.30	1843.20
	Muon	**358.20**	**309.71**	**322.10**	**437.58**	**529.98**	**810.12**

successfully captures the benefits of Muon's gradient orthogonalization during critical training phases while maintaining computational efficiency (Table 4). Additionally, as shown in Figure 2, experiments on both the balanced and imbalanced versions of CIFAR-100 demonstrate that Muon is particularly effective in enhancing generalization performance under imbalanced settings. See Appendix C for more comparison results.

Results on Large-Scale Datasets. The benefits of Muon become more pronounced on large-scale datasets, which present far more extreme class imbalance and substantially more classes. As detailed in Table 2, Muon delivers consistent and notable gains, particularly for the underrepresented medium and tail classes. On Places-LT, Muon significantly improves overall accuracy over SGD by 1.1% to 3.9% across various loss functions. Critically, its impact is most profound on the tail classes, boosting their accuracy by up to 6.3% (with CE loss). Furthermore, Muon consistently achieves superior or competitive performance compared to SAM, demonstrating its ability to find superior generalizing solutions. These trends hold on ImageNet-LT. Muon again surpasses SGD, with overall accuracy improving by 1.4% to 3.0%. The benefit for tail classes remains significant, confirming the robustness of our method under diverse, challenging conditions.

Notably, our proposed FaSO continues to exhibit strong performance on large-scale benchmarks across diverse data regimes, demonstrating a clear advantage over both SGD and SAM. Its accuracy is largely on par with the Muon optimizer. Intriguingly, when combined with the most effective loss function, ProCo, FaSO achieves competitive or even superior performance compared to the Muon optimizer on both datasets. This suggests that the dynamic scheduling of optimizers may introduce a more diverse optimization pathway, potentially guiding the model towards wider, better-generalizing minima than either optimizer could find alone.

Flat Minima of Loss Landscape. To further investigate the mechanism behind the improved generalization performance of tail classes, we examine the optimization through the lens of the loss landscape. We compute the eigenvalue spectrum of the Hessian matrix for tail classes on both CIFAR-10 LT and CIFAR-100 LT datasets with an imbalance factor of 100, training with the LA loss, as shown in Table 3 and Figure 3. Table 3 presents the Hessian properties for the three classes with the smallest sample sizes, comparing SGD and

(a) SGD   (b) FaSO   (c) SGD   (d) FaSO

Figure 3: Eigen spectral density for the class with the fewest samples across different methods. Experiments are conducted on (a,b) CIFAR-10 LT and (c,d) CIFAR-100 LT with an imbalance factor 100. Maximum eigenvalue $\lambda_{\max}$ (↓) and trace of Hessian metric $\mathrm{Tr}(\mathbf{H})$ (↓) in the top right corner of each panel. Lower $\lambda_{\max}$ and $\mathrm{Tr}(\mathbf{H})$ indicate a smoother loss landscape and improved generalization.

Table 4: Computational overhead of different optimizers (SGD, SAM, Muon, and FaSO) on long-tailed benchmarks including CIFAR-100 LT, ImageNet-LT, and Places-LT. We report the average training time per epoch (seconds) (↓) and the runtime ratio relative to SGD. FaSO and Muon are highlighted in light gray to group them for focused comparison against the baselines.

(a) Time (LA)

(b) Time (BCL)

Loss	Method	CIFAR-100 LT		ImageNet-LT	Places-LT
		IF=10	IF=100		
LA	SGD	4.2s (1.00×)	3.5s (1.00×)	184.8s (1.00×)	174.0s (1.00×)
	SAM	7.0s (1.67×)	4.4s (1.27×)	392.2s (2.21×)	216.0s (1.24×)
	Muon	8.4s (1.99×)	5.5s (1.61×)	358.8s (1.94×)	472.8s (2.71×)
	FaSO	5.9s (1.41×)	4.2s (1.23×)	244.2s (1.32×)	204.0s (1.17×)
ProCo	SGD	11.1s (1.00×)	7.0s (1.00×)	684.0s (1.00×)	622.8s (1.00×)
	SAM	21.3s (1.92×)	13.0s (1.85×)	1870.2s (2.73×)	2829.0s (4.54×)
	Muon	17.6s (1.59×)	11.3s (1.60×)	1118.4s (1.63×)	1608.0s (2.58×)
	FaSO	12.4s (1.12×)	8.2s (1.17×)	804.0s (1.17×)	874.8s (1.40×)

Figure 4: Average training time per epoch (s) (↓) for various methods on CIFAR-100 LT with IF of 10 and 100, using (a) LA and (b) BCL.

Muon optimizers through key metrics such as the maximum eigenvalue $\lambda_{\max}$ and trace $\mathrm{Tr}(\mathbf{H})$ at convergence. Smaller values indicate flatter loss landscapes associated with better generalization. The results show clear advantages of Muon: on CIFAR-10 LT, $\lambda_{\max}$ drops by 77%–88% and the trace by 81–84% relative to SGD. On the more challenging CIFAR-100 LT, reductions remain substantial, with decreases of 20%–61% in $\lambda_{\max}$ and 56%–72% in the trace. These findings indicate that Muon effectively drives tail classes toward flatter minima, which is consistent with our theoretical analysis.

Computational Efficiency Analysis. We conduct a comprehensive analysis of the computational efficiency of FaSO against the SGD, SAM, and Muon optimizers, as detailed in Table 4 and Figure 4. In Table 4, we measure the average training time per epoch across four representative datasets and the runtime ratio relative to SGD, thereby providing a more fine-grained view of efficiency, using two representative loss functions, LA and ProCo, to evaluate the robustness of each optimizer under varying loss complexities.

The results demonstrate that FaSO effectively resolves the trade-off between generalization and computational cost, achieving the strong performance of Muon with minimal overhead. This efficiency is most striking with complex losses such as ProCo, where FaSO adds only 21% training overhead compared to SGD. In sharp contrast, SAM incurs a 176% overhead, and Muon still bears a considerable 85%, indicating pronounced scalability limitations when integrated with advanced long-tailed learning methods. When paired with LA loss, FaSO maintains its advantage, incurring just 25% overhead versus 36% for SAM and 106% for Muon. Crucially, these efficiency gains come at no cost to accuracy. As shown in Tables 1 and 2, FaSO consistently

matches the performance of the Muon optimizer, establishing it as a practical and scalable method for real-world, large-scale long-tail learning. Please refer to Appendix C.2 for additional comparison results.

Table 5: Ablation study on the number of Newton-Schulz iteration steps (N) on CIFAR-100 LT under an imbalance factor of 100. We report top-1 accuracy (%) ($\uparrow$) on *Many*, *Medium* (namely Med.), *Few*, and overall classes, along with average training time per epoch (seconds) ($\downarrow$) and the runtime ratio relative to SGD.

Method	N	Many	Med.	Few	All	Time/epoch
SGD	-	75.0	50.6	17.3	44.6	2.57 (1.00×)
Muon	5	76.4	53.1	19.7	**46.7**	4.11 (1.59×)
FaSO	5	76.5	52.5	19.3	46.4	2.94 (1.14×)
FaSO	4	77.2	51.3	18.8	46.1	2.82 (1.10×)
FaSO	3	76.1	52.8	18.1	45.9	2.78 (1.09×)
FaSO	2	76.1	51.1	17.7	45.2	2.59 (1.01×)

Efficiency Analysis via Gradient Approximation. To further mitigate computational overhead, we investigate reducing the precision of Newton-Schulz orthogonalization as a potential optimization for efficient gradient approximation. Specifically, we evaluate FaSO on CIFAR-100 LT by varying the number of iteration steps N from 5 to 2. As summarized in Table 5, the results reveal a clear trade-off between computational budget and predictive performance; consistent with our theoretical complexity analysis (Eq. (6,7)), reducing iterations successfully lowers the computational overhead. While the default $N = 5$ yields the highest accuracy, performance consistently remains superior to SGD even as N declines, validating that moderate gradient approximation is an effective method for maintaining robust performance in resource-constrained scenarios.

5 Conclusion

In this work, we present a geometric analysis of the Muon optimizer, demonstrating its capacity to escape sharp minima by enhancing updates along directions of negative curvature. To harness this for long-tailed learning, we introduce FaSO, which employs a compositional probabilistic schedule that couples lightweight exploration with increasingly frequent orthogonalized updates as training approaches convergence. This design effectively balances computational efficiency with generalization, guiding models toward flatter landscapes for underrepresented classes, as validated by extensive experiments. Future work will extend our approach to other imbalanced domains, such as domain adaptation, to further enhance its applicability and robustness.

References

Emmanuel Abbe, Enric Boix Adserà, and Theodor Misiakiewicz. SGD learning on neural networks: leap complexity and saddle-to-saddle dynamics. In Gergely Neu and Lorenzo Rosasco (eds.), *The Thirty Sixth Annual Conference on Learning Theory, COLT 2023, 12-15 July 2023, Bangalore, India*, volume 195 of *Proceedings of Machine Learning Research*, pp. 2552–2623. PMLR, 2023. URL `https://proceedings.ml r.press/v195/abbe23a.html`.

Sumyeong Ahn, Jongwoo Ko, and Se-Young Yun. CUDA: curriculum of data augmentation for long-tailed recognition. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023. URL `https://openreview.net/forum?id=RgUPdudkWlN`.

Mateusz Buda, Atsuto Maki, and Maciej A. Mazurowski. A systematic study of the class imbalance problem in convolutional neural networks. *Neural Networks*, 106:249–259, 2018. doi: 10.1016/J.NEUNET.2018.07.011. URL `https://doi.org/10.1016/j.neunet.2018.07.011`.

Kaidi Cao, Colin Wei, Adrien Gaidon, Nikos Aréchiga, and Tengyu Ma. Learning imbalanced datasets with label-distribution-aware margin loss. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14,*

2019, Vancouver, BC, Canada, pp. 1565–1576, 2019. URL `https://proceedings.neurips.cc/paper/2019/hash/621461af90cadfdaf0e8d4cc25129f91-Abstract.html`.

Nitesh V. Chawla, Kevin W. Bowyer, Lawrence O. Hall, and W. Philip Kegelmeyer. SMOTE: synthetic minority over-sampling technique. *J. Artif. Intell. Res.*, 16:321–357, 2002. doi: 10.1613/JAIR.953. URL `https://doi.org/10.1613/jair.953`.

Chris Criscitiello and Nicolas Boumal. Efficiently escaping saddle points on manifolds. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 5985–5995, 2019. URL `https://proceedings.neurips.cc/paper/2019/hash/7486cef2522ee03547cfb970a404a874-Abstract.html`.

Jiequan Cui, Zhisheng Zhong, Shu Liu, Bei Yu, and Jiaya Jia. Parametric contrastive learning. In *2021 IEEE/CVF International Conference on Computer Vision, ICCV 2021, Montreal, QC, Canada, October 10-17, 2021*, pp. 695–704. IEEE, 2021. doi: 10.1109/ICCV48922.2021.00075. URL `https://doi.org/10.1109/ICCV48922.2021.00075`.

Jiequan Cui, Zhisheng Zhong, Zhuotao Tian, Shu Liu, Bei Yu, and Jiaya Jia. Generalized parametric contrastive learning. *IEEE Trans. Pattern Anal. Mach. Intell.*, 46(12):7463–7474, 2024. doi: 10.1109/TPAMI.2023.3278694. URL `https://doi.org/10.1109/TPAMI.2023.3278694`.

Yin Cui, Menglin Jia, Tsung-Yi Lin, Yang Song, and Serge J. Belongie. Class-balanced loss based on effective number of samples. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, pp. 9268–9277. Computer Vision Foundation / IEEE, 2019. doi: 10.1109/CVPR.2019.00949. URL `http://openaccess.thecvf.com/content_CVPR_2019/html/Cui_Class-Balanced_Loss_Based_on_Effective_Number_of_Samples_CVPR_2019_paper.html`.

Hadi Daneshmand, Jonas Moritz Kohler, Aurélien Lucchi, and Thomas Hofmann. Escaping saddles with stochastic gradients. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1163–1172. PMLR, 2018. URL `http://proceedings.mlr.press/v80/daneshmand18a.html`.

Bowen Dong, Pan Zhou, Shuicheng Yan, and Wangmeng Zuo. LPT: long-tailed prompt tuning for image classification. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023. URL `https://openreview.net/forum?id=8pOVAeo8ie`.

Chaoqun Du, Yulin Wang, Shiji Song, and Gao Huang. Probabilistic contrastive learning for long-tailed visual recognition. *IEEE Trans. Pattern Anal. Mach. Intell.*, 46(9):5890–5904, 2024. doi: 10.1109/TPAMI.2024.3369102. URL `https://doi.org/10.1109/TPAMI.2024.3369102`.

Cong Fang, Zhouchen Lin, and Tong Zhang. Sharp analysis for nonconvex SGD escaping from saddle points. In Alina Beygelzimer and Daniel Hsu (eds.), *Conference on Learning Theory, COLT 2019, 25-28 June 2019, Phoenix, AZ, USA*, volume 99 of *Proceedings of Machine Learning Research*, pp. 1192–1234. PMLR, 2019. URL `http://proceedings.mlr.press/v99/fang19a.html`.

Pierre Foret, Ariel Kleiner, Hossein Mobahi, and Behnam Neyshabur. Sharpness-aware minimization for efficiently improving generalization. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL `https://openreview.net/forum?id=6Tm1mposlrM`.

Rong Ge, Furong Huang, Chi Jin, and Yang Yuan. Escaping from saddle points - online stochastic gradient for tensor decomposition. In Peter Grünwald, Elad Hazan, and Satyen Kale (eds.), *Proceedings of The 28th Conference on Learning Theory, COLT 2015, Paris, France, July 3-6, 2015*, volume 40 of *JMLR Workshop and Conference Proceedings*, pp. 797–842. JMLR.org, 2015. URL `http://proceedings.mlr.press/v40/Ge15.html`.

Haibo He, Yang Bai, Edwardo A. Garcia, and Shutao Li. ADASYN: adaptive synthetic sampling approach for imbalanced learning. In *Proceedings of the International Joint Conference on Neural Networks, IJCNN 2008, part of the IEEE World Congress on Computational Intelligence, WCCI 2008, Hong Kong, China, June 1-6, 2008*, pp. 1322–1328. IEEE, 2008. doi: 10.1109/IJCNN.2008.4633969. URL `https://doi.org/10.1109/IJCNN.2008.4633969`.

Grant Van Horn, Oisin Mac Aodha, Yang Song, Yin Cui, Chen Sun, Alexander Shepard, Hartwig Adam, Pietro Perona, and Serge J. Belongie. The inaturalist species classification and detection dataset. In *2018 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2018, Salt Lake City, UT, USA, June 18-22, 2018*, pp. 8769–8778. Computer Vision Foundation / IEEE Computer Society, 2018. doi: 10.1109/CVPR.2018.00914. URL `http://openaccess.thecvf.com/content_cvpr_2018/html/Van_Horn_The_INaturalist_Species_CVPR_2018_paper.html`.

Yiding Jiang, Behnam Neyshabur, Hossein Mobahi, Dilip Krishnan, and Samy Bengio. Fantastic generalization measures and where to find them. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=SJgIPJBFvH`.

Chi Jin, Rong Ge, Praneeth Netrapalli, Sham M. Kakade, and Michael I. Jordan. How to escape saddle points efficiently. In Doina Precup and Yee Whye Teh (eds.), *Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017*, volume 70 of *Proceedings of Machine Learning Research*, pp. 1724–1732. PMLR, 2017. URL `http://proceedings.mlr.press/v70/jin17a.html`.

Keller Jordan, Yuchen Jin, Vlado Boza, Jiacheng You, Franz Cesista, Laker Newhouse, and Jeremy Bernstein. Muon: An optimizer for hidden layers in neural networks, 2024. URL `https://kellerjordan.github.io/posts/muon/`.

Bingyi Kang, Saining Xie, Marcus Rohrbach, Zhicheng Yan, Albert Gordo, Jiashi Feng, and Yannis Kalantidis. Decoupling representation and classifier for long-tailed recognition. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=r1gRTCVFvB`.

Dmitry Kovalev. Understanding gradient orthogonalization for deep learning via non-euclidean trust-region optimization. *CoRR*, abs/2503.12645, 2025. doi: 10.48550/ARXIV.2503.12645. URL `https://doi.org/10.48550/arXiv.2503.12645`.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Mengke Li, Zhikai Hu, Yang Lu, Weichao Lan, Yiu-ming Cheung, and Hui Huang. Feature fusion from head to tail for long-tailed visual recognition. In Michael J. Wooldridge, Jennifer G. Dy, and Sriraam Natarajan (eds.), *Thirty-Eighth AAAI Conference on Artificial Intelligence, AAAI 2024, Thirty-Sixth Conference on Innovative Applications of Artificial Intelligence, IAAI 2024, Fourteenth Symposium on Educational Advances in Artificial Intelligence, EAAI 2014, February 20-27, 2024, Vancouver, Canada*, pp. 13581–13589. AAAI Press, 2024. doi: 10.1609/AAAI.V38I12.29262. URL `https://doi.org/10.1609/aaai.v38i12.29262`.

Sicong Li, Qianqian Xu, Zhiyong Yang, Zitai Wang, Linchao Zhang, Xiaochun Cao, and Qingming Huang. Focal-sam: Focal sharpness-aware minimization for long-tailed classification. In *Forty-second International Conference on Machine Learning, ICML 2025, Vancouver, BC, Canada, July 13-19, 2025*. OpenReview.net, 2025a. URL `https://openreview.net/forum?id=lCk4PZto8T`.

Sicong Li, Qianqian Xu, Zhiyong Yang, Zitai Wang, Linchao Zhang, Xiaochun Cao, and Qingming Huang. Focal-sam: Focal sharpness-aware minimization for long-tailed classification. *CoRR*, abs/2505.01660, 2025b. doi: 10.48550/ARXIV.2505.01660. URL `https://doi.org/10.48550/arXiv.2505.01660`.

Jingyuan Liu, Jianlin Su, Xingcheng Yao, Zhejun Jiang, Guokun Lai, Yulun Du, Yidao Qin, Weixin Xu, Enzhe Lu, Junjie Yan, Yanru Chen, Huabin Zheng, Yibo Liu, Shaowei Liu, Bohong Yin, Weiran He, Han Zhu, Yuzhi

Wang, Jianzhou Wang, Mengnan Dong, Zheng Zhang, Yongsheng Kang, Hao Zhang, Xinran Xu, Yutao Zhang, Yuxin Wu, Xinyu Zhou, and Zhilin Yang. Muon is scalable for LLM training. *CoRR*, abs/2502.16982, 2025. doi: 10.48550/ARXIV.2502.16982. URL `https://doi.org/10.48550/arXiv.2502.16982`.

Yong Liu, Siqi Mai, Xiangning Chen, Cho-Jui Hsieh, and Yang You. Towards efficient and scalable sharpness-aware minimization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2022, New Orleans, LA, USA, June 18-24, 2022*, pp. 12350–12360. IEEE, 2022. doi: 10.1109/CVPR52688.2022.0 1204. URL `https://doi.org/10.1109/CVPR52688.2022.01204`.

Ziwei Liu, Zhongqi Miao, Xiaohang Zhan, Jiayun Wang, Boqing Gong, and Stella X. Yu. Large-scale long-tailed recognition in an open world. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, pp. 2537–2546. Computer Vision Foundation / IEEE, 2019. doi: 10.1109/CVPR.2019.00264. URL `http://openaccess.thecvf.com/content_CVPR_201 9/html/Liu_Large-Scale_Long-Tailed_Recognition_in_an_Open_World_CVPR_2019_paper.html`.

Jiaan Luo, Feng Hong, Jiangchao Yao, Bo Han, Ya Zhang, and Yanfeng Wang. Revive re-weighting in imbalanced learning by density ratio estimation. In Amir Globersons, Lester Mackey, Danielle Belgrave, Angela Fan, Ulrich Paquet, Jakub M. Tomczak, and Cheng Zhang (eds.), *Advances in Neural Information Processing Systems 38: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024*, 2024. URL `http://papers.nips.cc/paper_files/pap er/2024/hash/92440ec643f4e9f17409557b6516566e-Abstract-Conference.html`.

Xingyu Lyu, Qianqian Xu, Zhiyong Yang, Shaojie Lyu, and Qingming Huang. SSE-SAM: balancing head and tail classes gradually through stage-wise SAM. In Toby Walsh, Julie Shah, and Zico Kolter (eds.), *AAAI-25, Sponsored by the Association for the Advancement of Artificial Intelligence, February 25 - March 4, 2025, Philadelphia, PA, USA*, pp. 19278–19286. AAAI Press, 2025. doi: 10.1609/AAAI.V39I18.34122. URL `https://doi.org/10.1609/aaai.v39i18.34122`.

Yanbiao Ma, Licheng Jiao, Fang Liu, Yuxin Li, Shuyuan Yang, and Xu Liu. Delving into semantic scale imbalance. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023. URL `https://openreview.net/forum?id=07tc5kKRIo`.

Aditya Krishna Menon, Sadeep Jayasumana, Ankit Singh Rawat, Himanshu Jain, Andreas Veit, and Sanjiv Kumar. Long-tail learning via logit adjustment. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL `https://openreview.net/forum?id=37nvvqkCo5`.

Harsh Rangwani, Sumukh K. Aithal, Mayank Mishra, and Venkatesh Babu R. Escaping saddle points for effective generalization on class-imbalanced data. In Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*, 2022. URL `http://papers.nips.cc/paper_files/paper/2022/hash /8f4d70db9ecec97b6723a86f1cd9cb4b-Abstract-Conference.html`.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael S. Bernstein, Alexander C. Berg, and Li Fei-Fei. Imagenet large scale visual recognition challenge. *Int. J. Comput. Vis.*, 115(3):211–252, 2015. doi: 10.1007/S11263-015-0816-Y. URL `https://doi.org/10.1007/s11263-015-0816-y`.

Ishaan Shah, Anthony M. Polloreno, Karl Stratos, Philip Monk, Adarsh Chaluvaraju, Andrew Hojel, Andrew Ma, Anil Thomas, Ashish Tanwer, Darsh J. Shah, Khoi Nguyen, Kurt Smith, Michael Callahan, Michael Pust, Mohit Parmar, Peter Rushton, Platon Mazarakis, Ritvik Kapila, Saurabh Srivastava, Somanshu Singla, Tim Romanski, Yash Vanjani, and Ashish Vaswani. Practical efficiency of muon for pretraining. *CoRR*, abs/2505.02222, 2025. doi: 10.48550/ARXIV.2505.02222. URL `https://doi.org/10.48550/arXiv.2505.02222`.

Wei Shen, Ruichuan Huang, Minhui Huang, Cong Shen, and Jiawei Zhang. On the convergence analysis of muon. *CoRR*, abs/2505.23737, 2025. doi: 10.48550/ARXIV.2505.23737. URL `https://doi.org/10.485 50/arXiv.2505.23737`.

Jiang-Xin Shi, Tong Wei, Zhi Zhou, Jie-Jing Shao, Xin-Yan Han, and Yufeng Li. Long-tail learning with foundation model: Heavy fine-tuning hurts. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024. URL `https://openreview.net/f orum?id=ccSSKTz9LX`.

Matthew Staib, Sashank J. Reddi, Satyen Kale, Sanjiv Kumar, and Suvrit Sra. Escaping saddle points with adaptive gradient methods. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 5956–5965. PMLR, 2019. URL `http://proceedings.mlr.press/v97/staib19a.html`.

David Stutz, Matthias Hein, and Bernt Schiele. Relating adversarially robust generalization to flat minima. In *2021 IEEE/CVF International Conference on Computer Vision, ICCV 2021, Montreal, QC, Canada, October 10-17, 2021*, pp. 7787–7797. IEEE, 2021. doi: 10.1109/ICCV48922.2021.00771. URL `https: //doi.org/10.1109/ICCV48922.2021.00771`.

Zichang Tan, Jun Li, Jinhao Du, Jun Wan, Zhen Lei, and Guodong Guo. NCL++: nested collaborative learning for long-tailed visual recognition. *Pattern Recognit.*, 147:110064, 2024. doi: 10.1016/J.PATCOG.2023.110064. URL `https://doi.org/10.1016/j.patcog.2023.110064`.

Jianfeng Wang, Thomas Lukasiewicz, Xiaolin Hu, Jianfei Cai, and Zhenghua Xu. RSG: A simple but effective module for learning imbalanced datasets. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2021, virtual, June 19-25, 2021*, pp. 3784–3793. Computer Vision Foundation / IEEE, 2021a. doi: 10.1109/CVPR46437.2021.00378. URL `https://openaccess.thecvf.com/content/CVPR2021/html/ Wang_RSG_A_Simple_but_Effective_Module_for_Learning_Imbalanced_Datasets_CVPR_2021_paper. html`.

Jun-Kun Wang, Chi-Heng Lin, and Jacob D. Abernethy. Escaping saddle points faster with stochastic momentum. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=rkeNfp4t Pr`.

Xudong Wang, Long Lian, Zhongqi Miao, Ziwei Liu, and Stella X. Yu. Long-tailed recognition by routing diverse distribution-aware experts. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021b. URL `https://openreview.net/f orum?id=D9I3drBz4UC`.

Zitai Wang, Qianqian Xu, Zhiyong Yang, Yuan He, Xiaochun Cao, and Qingming Huang. A unified generalization analysis of re-weighting and logit-adjustment for imbalanced learning. In Alice Oh, Tristan Naumann, Amir Globerson, Kate Saenko, Moritz Hardt, and Sergey Levine (eds.), *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*, 2023. URL `http://papers.nips.cc/p aper_files/paper/2023/hash/973a0f50d43cf99118cdab456edcacda-Abstract-Conference.html`.

Shiyu Xuan and Shiliang Zhang. Decoupled contrastive learning for long-tailed recognition. In Michael J. Wooldridge, Jennifer G. Dy, and Sriraam Natarajan (eds.), *Thirty-Eighth AAAI Conference on Artificial Intelligence, AAAI 2024, Thirty-Sixth Conference on Innovative Applications of Artificial Intelligence, IAAI 2024, Fourteenth Symposium on Educational Advances in Artificial Intelligence, EAAI 2014, February 20-27, 2024, Vancouver, Canada*, pp. 6396–6403. AAAI Press, 2024. doi: 10.1609/AAAI.V38I6.28459. URL `https://doi.org/10.1609/aaai.v38i6.28459`.

Zhiyong Yang, Qianqian Xu, Zitai Wang, Sicong Li, Boyu Han, Shilong Bao, Xiaochun Cao, and Qingming Huang. Harnessing hierarchical label distribution variations in test agnostic long-tail recognition. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024. URL `https://openreview.net/forum?id=ebt5BfRHcW`.

Sangdoo Yun, Dongyoon Han, Sanghyuk Chun, Seong Joon Oh, Youngjoon Yoo, and Junsuk Choe. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *2019 IEEE/CVF International Conference on Computer Vision, ICCV 2019, Seoul, Korea (South), October 27 - November 2, 2019*, pp. 6022–6031. IEEE, 2019. doi: 10.1109/ICCV.2019.00612. URL `https://doi.org/10.1109/ICCV.2019.00612`.

Chiyuan Zhang, Qianli Liao, Alexander Rakhlin, Karthik Sridharan, Brando Miranda, Noah Golowich, and Tomaso Poggio. Musings on deep learning: Properties of sgd. Technical report, Center for Brains, Minds and Machines (CBMM), 2017.

Hongyi Zhang, Moustapha Cissé, Yann N. Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL `https://openreview.net/forum?id=r1Ddp1-Rb`.

Xiang Zhang, Junbo Jake Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In Corinna Cortes, Neil D. Lawrence, Daniel D. Lee, Masashi Sugiyama, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, pp. 649–657, 2015. URL `https://proceedings.neurips.cc/paper/2015/hash/250cf8b51c773f3f8dc8b4be867a9a02-Abstract.html`.

Yixuan Zhou, Yi Qu, Xing Xu, and Hengtao Shen. Imbsam: A closer look at sharpness-aware minimization in class-imbalanced recognition. In *IEEE/CVF International Conference on Computer Vision, ICCV 2023, Paris, France, October 1-6, 2023*, pp. 11311–11321. IEEE, 2023a. doi: 10.1109/ICCV51070.2023.01042. URL `https://doi.org/10.1109/ICCV51070.2023.01042`.

Zhipeng Zhou, Lanqing Li, Peilin Zhao, Pheng-Ann Heng, and Wei Gong. Class-conditional sharpness-aware minimization for deep long-tailed recognition. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2023, Vancouver, BC, Canada, June 17-24, 2023*, pp. 3499–3509. IEEE, 2023b. doi: 10.1109/CVPR52729.2023.00341. URL `https://doi.org/10.1109/CVPR52729.2023.00341`.

Jianggang Zhu, Zheng Wang, Jingjing Chen, Yi-Ping Phoebe Chen, and Yu-Gang Jiang. Balanced contrastive learning for long-tailed visual recognition. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2022, New Orleans, LA, USA, June 18-24, 2022*, pp. 6898–6907. IEEE, 2022. doi: 10.1109/CVPR52688.2022.00678. URL `https://doi.org/10.1109/CVPR52688.2022.00678`.

A Appendix

A Algorithm

We present the pseudo-code of Muon and FaSO in Algorithm 1 and Algorithm 2, respectively, to illustrate the detailed implementation procedure of our method.

Algorithm 1 Muon

Input: Initial weights $\mathbf{W}_0$, learning rate schedule $\{\eta_t\}$, momentum β, batch size B, dataset $\mathcal{D}$
for $t = 0$ to $T_{\max} - 1$ **do**
    Sample mini batch $\{\xi_{t,i}\}_{i=1}^{B} \leftarrow \mathcal{D}$
    Calculate $\mathbf{g}_t = \frac{1}{B} \sum_{i=1}^{B} \nabla f(\mathbf{W}_t; \xi_{t,i})$
    If $t > 0$, $\mathbf{M}_t = \beta \mathbf{M}_{t-1} + (1 - \beta) \mathbf{g}_t$. If $t = 0$, $\mathbf{M}_0 = \mathbf{g}_0$
    Calculate $\mathbf{O}_t = \text{NewtonSchulz}(\mathbf{M}_t)$
    Update $\mathbf{W}_{t+1} = \mathbf{W}_t - \eta_t \mathbf{O}_t$
end for

Algorithm 2 FaSO

Input: Initial weights $\mathbf{W}_0$, learning rate schedule $\{\eta_t\}$, momentum β, batch size B, dataset $\mathcal{D}$
for $t = 0$ to $T_{\max} - 1$ **do**
    Sample mini batch $\{\xi_{t,i}\}_{i=1}^{B} \leftarrow \mathcal{D}$
    Calculate $\mathbf{g}_t = \frac{1}{B} \sum_{i=1}^{B} \nabla f(\mathbf{W}_t; \xi_{t,i})$
    If $t > 0$, $\mathbf{M}_t = \beta \mathbf{M}_{t-1} + (1 - \beta) \mathbf{g}_t$. If $t = 0$, $\mathbf{M}_0 = \mathbf{g}_0$
    Calculate p_t via sinusoidal schedule
    Sample $\mu \sim \text{Uniform}(0, 1)$
    If $\mu < p_t$ then $\mathbf{O}_t = \text{NewtonSchulz}(\mathbf{M}_t)$ else $\mathbf{O}_t = \mathbf{M}_t$
    Update $\mathbf{W}_{t+1} = \mathbf{W}_t - \eta_t \mathbf{O}_t$
end for

B Theoretical Supplement

Lemma B.1. *Given the normalized gradient matrix $\mathbf{G}_t = \frac{\mathbf{g}_t}{\|\mathbf{g}_t\|_{\text{F}}}$ and its rank-r_t singular value decomposition $\mathbf{G}_t = \mathbf{U}_t \mathbf{S}_t \mathbf{V}_t^{\top}$, where $\mathbf{U}_t \in \mathbb{R}^{m \times r_t}$ and $\mathbf{V}_t \in \mathbb{R}^{n \times r_t}$ satisfy $\mathbf{U}_t^{\top} \mathbf{U}_t = \mathbf{I}_{r_t}$ and $\mathbf{V}_t^{\top} \mathbf{V}_t = \mathbf{I}_{r_t}$, and $\mathbf{S}_t = \text{diag}(s_1, \ldots, s_{r_t}) \in \mathbb{R}^{r_t \times r_t}$ is the diagonal matrix of singular values, it holds that $\sum_{i=1}^{r_t} s_i^2 = 1$.*

Proof of Lemma B.1. By the normalization condition $\mathbf{G}_t = \mathbf{g}_t / \|\mathbf{g}_t\|_{\text{F}}$, the Frobenius norm of $\mathbf{G}_t$ is:

$$\|\mathbf{G}_t\|_{\text{F}} = \frac{\|\mathbf{g}_t\|_{\text{F}}}{\|\mathbf{g}_t\|_{\text{F}}} = 1, \tag{10}$$

which implies $\|\mathbf{G}_t\|_{\text{F}}^2 = 1$. The squared Frobenius norm is equivalent to the trace of $\mathbf{G}_t^{\top} \mathbf{G}_t$:

$$\|\mathbf{G}_t\|_{\text{F}}^2 = \text{trace}(\mathbf{G}_t^{\top} \mathbf{G}_t). \tag{11}$$

Substituting the SVD, $\mathbf{G}_t = \mathbf{U}_t \mathbf{S}_t \mathbf{V}_t^{\top}$, we compute:

$$\mathbf{G}_t^{\top} \mathbf{G}_t = (\mathbf{U}_t \mathbf{S}_t \mathbf{V}_t^{\top})^{\top}(\mathbf{U}_t \mathbf{S}_t \mathbf{V}_t^{\top}) = \mathbf{V}_t \mathbf{S}_t^{\top} \mathbf{U}_t^{\top} \mathbf{U}_t \mathbf{S}_t \mathbf{V}_t^{\top} = \mathbf{V}_t \mathbf{S}_t^{\top} \mathbf{I}_{r_t} \mathbf{S}_t \mathbf{V}_t^{\top} = \mathbf{V}_t \mathbf{S}_t^2 \mathbf{V}_t^{\top}. \tag{12}$$

The trace operation yields:

$$\|\mathbf{G}_t\|_{\text{F}}^2 = \text{tr}(\mathbf{V}_t \mathbf{S}_t^2 \mathbf{V}_t^{\top}) = \text{tr}(\mathbf{V}_t^{\top} \mathbf{V}_t \mathbf{S}_t^2) = \text{tr}(\mathbf{I}_{r_t} \cdot \mathbf{S}_t^2) = \text{tr}(\mathbf{S}_t^2). \tag{13}$$

The matrix $\mathbf{S}_t^2 = \mathrm{diag}(s_1^2, \ldots, s_{r_t}^2)$ is diagonal, so its trace is the sum of the squared singular values:

$$\mathrm{tr}(\mathbf{S}_t^2) = \sum_{i=1}^{r_t} s_i^2. \tag{14}$$

Combining these results, we conclude:

$$\sum_{i=1}^{r_t} s_i^2 = \|\mathbf{G}_t\|_{\mathrm{F}}^2 = 1. \tag{15}$$

Lemma B.2. *Let matrix $\mathbf{A}, \mathbf{B} \in \mathbb{R}^{r_t \times r_t}$ be positive semi-definite (PSD) matrices. Then, it holds that $\mathrm{tr}(\mathbf{A}\mathbf{B}) \geq 0$.*

Proof of Lemma B.2. Since $\mathbf{A}$ is PSD, it admits a symmetric PSD square root $\mathbf{A}^{1/2}$ satisfying $\mathbf{A} = \mathbf{A}^{1/2}\mathbf{A}^{1/2}$ and $(\mathbf{A}^{1/2})^\top = \mathbf{A}^{1/2}$. Applying the cyclic property of the trace operator, we reinterpret $\mathrm{tr}(\mathbf{A}\mathbf{B})$ as:

$$\mathrm{tr}(\mathbf{A}\mathbf{B}) = \mathrm{tr}\left(\mathbf{A}^{1/2}(\mathbf{A}^{1/2}\mathbf{B})\right) = \mathrm{tr}\left(\mathbf{A}^{1/2}\mathbf{B}\mathbf{A}^{1/2}\right). \tag{16}$$

The matrix $\mathbf{M} = \mathbf{A}^{1/2}\mathbf{B}\mathbf{A}^{1/2}$ preserves the PSD property: for any vector $\mathbf{x} \in \mathbb{R}^{r_t}$,

$$\mathbf{x}^\top \mathbf{M}\mathbf{x} = \left(\mathbf{x}^\top \mathbf{A}^{1/2}\right) \mathbf{B} \left((\mathbf{A}^{1/2})^\top \mathbf{x}\right) = \mathbf{y}^\top \mathbf{B}\mathbf{y} \geq 0, \quad \mathbf{y} = \mathbf{A}^{1/2}\mathbf{x}, \tag{17}$$

since $\mathbf{B}$ is PSD. Consequently, $\mathbf{M}$ is also PSD, and its trace—equivalent to the sum of its non-negative eigenvalues—satisfies $\mathrm{tr}(\mathbf{M}) \geq 0$, that is,

$$\mathrm{tr}(\mathbf{A}\mathbf{B}) = \mathrm{tr}\left(\mathbf{A}^{1/2}\mathbf{B}\mathbf{A}^{1/2}\right) \geq 0. \tag{18}$$

Proof of Theorem 3.2. Define $\mathbf{V} \in \mathbb{R}^{m \times n}$ as the matrix obtained by reshaping $\mathbf{v}_{\mathbf{W}_t}$ into shape $m \times n$, so that $\mathrm{vec}(\mathbf{V}) = \mathbf{v}_{\mathbf{W}_t}$. The SGD update direction is the stochastic gradient $\mathbf{g}_t$, and its projection onto $\mathbf{v}_{\mathbf{W}_t}$ is:

$$\mathrm{proj}_{\mathrm{SGD}} = \mathrm{vec}(\mathbf{g}_t)^\top \mathrm{vec}(\mathbf{V}) = \mathrm{tr}(\mathbf{g}_t^\top \mathbf{V}). \tag{19}$$

Remember that $\mathbf{G}_t = \mathbf{g}_t / \|\mathbf{g}_t\|_{\mathrm{F}}$ is the normalized gradient. The projection of $\mathbf{G}_t$ onto $\mathbf{v}_{\mathbf{W}_t}$ can be expressed as:

$$\mathrm{tr}(\mathbf{G}_t^\top \mathbf{V}) = \mathrm{tr}(\mathbf{V}_t \mathbf{S}_t \mathbf{U}_t^\top \mathbf{V}) = \mathrm{tr}(\mathbf{S}_t \mathbf{M}) = \sum_{i=1}^{r_t} s_i\, m_{ii}, \tag{20}$$

where $\mathbf{M}_t := \mathbf{U}_t^\top \mathbf{V}\mathbf{V}_t \in \mathbb{R}^{r_t \times r_t}$, and $s_i \in [0, 1]$ are the singular values of $\mathbf{G}_t$, while m_{ii} are the diagonal entries of $\mathbf{M}$. Hence, the SGD projection on $\mathbf{v}_{\mathbf{W}_t}$ becomes:

$$\mathrm{proj}_{\mathrm{SGD}} = \|\mathbf{g}_t\|_{\mathrm{F}} \cdot \mathrm{tr}(\mathbf{G}_t^\top \mathbf{V}) = \|\mathbf{g}_t\|_{\mathrm{F}} \cdot \mathrm{tr}(\mathbf{S}_t \mathbf{M}). \tag{21}$$

The Muon update direction is given by $\mathbf{U}_t \mathbf{V}_t^\top$, and its projection onto $\mathbf{v}_{\mathbf{W}_t}$ is:

$$\begin{aligned}
\mathrm{proj}_{\mathrm{Muon}} &= \mathrm{vec}(\mathbf{U}_t \mathbf{V}_t^\top)^\top \mathrm{vec}(\mathbf{V}) = \mathrm{tr}((\mathbf{U}_t \mathbf{V}_t^\top)^\top \mathbf{V}) \\
&= \mathrm{tr}(\mathbf{V}_t \mathbf{U}_t^\top \mathbf{V}) = \mathrm{tr}(\mathbf{U}_t^\top \mathbf{V}\mathbf{V}_t) = \mathrm{tr}(\mathbf{M}) = \sum_{i=1}^{r_t} m_{ii}.
\end{aligned} \tag{22}$$

Now we compare the expected squared projection of Muon and the normalized gradient $\mathbf{G}_t$ onto $\mathbf{v}_{\mathbf{W}_t}$.

$$\begin{aligned}
\mathbb{E}\big[(\mathrm{tr}(\mathbf{M}_t))^2\big] &- \mathbb{E}\big[(\mathrm{tr}(\mathbf{S}_t \mathbf{M}_t)^2\big] \\
&= \mathbb{E}\left[\left(\sum_i m_{ii}\right)^2 - \left(\sum_i s_i m_{ii}\right)^2\right] \\
&= \mathbb{E}\left[\sum_{i,j}(1 - s_i s_j) m_{ii} m_{jj}\right].
\end{aligned} \tag{23}$$

Let's define vector $\mathbf{s} = [s_1, \ldots, s_{r_t}]^\top \in \mathbb{R}^{r_t}$, where $\|\mathbf{s}\|_2 = 1$ since $\mathbf{G}_t$ is normalized. Then, define the matrix $\mathbf{A} := \mathbf{I} - \mathbf{s}\mathbf{s}^\top \in \mathbb{R}^{r_t \times r_t}$. Let vector $\mathbf{m} = [m_{11}, \ldots, m_{r_t r_t}]^\top \in \mathbb{R}^{r_t}$, and define the matrix $\mathbf{B} := \mathbf{m}\mathbf{m}^\top \in \mathbb{R}^{r_t \times r_t}$. We now show that both matrix $\mathbf{A}$ and $\mathbf{B}$ are PSD matrices:

For matrix $\mathbf{A}$, for any $\mathbf{x} \in \mathbb{R}^{r_t}$, with the Cauchy–Schwarz inequality, we can obtain

$$
\begin{aligned}
\mathbf{x}^\top \mathbf{A}\mathbf{x} &= \mathbf{x}^\top (\mathbf{I} - \mathbf{s}\mathbf{s}^\top)\mathbf{x} \\
&= \|\mathbf{x}\|_2^2 - (\mathbf{s}^\top \mathbf{x})^2 \\
&\geq \|\mathbf{x}\|_2^2 - \|\mathbf{s}\|_2^2 \|\mathbf{x}\|_2^2 = 0,
\end{aligned}
\tag{24}
$$

note that $\|\mathbf{s}\|_2 = 1$ comes from Lemma B.1.

For matrix $\mathbf{B}$, for any $\mathbf{x} \in \mathbb{R}^{r_t}$, we can obtain

$$
\mathbf{x}^\top \mathbf{B}\mathbf{x} = \mathbf{x}^\top \mathbf{m}\mathbf{m}^\top \mathbf{x} = \mathbf{m}^\top \mathbf{x} \cdot \mathbf{x}^\top \mathbf{m} = (\mathbf{x}^\top \mathbf{m})^2 \geq 0.
\tag{25}
$$

Now, we relate the term $\sum_{i,j} (1 - s_i s_j) m_{ii} m_{jj}$ to the trace of the product $\mathbf{AB}$:

$$
\begin{aligned}
\sum_{i,j} (1 - s_i s_j) m_{ii} m_{jj} &= \mathbf{m}^\top (\mathbf{I} - \mathbf{s}\mathbf{s}^\top)\mathbf{m} = \mathbf{m}^\top \mathbf{A}\mathbf{m} \\
&= \mathrm{tr}\left(\mathbf{m}^\top \mathbf{A}\mathbf{m}\right) = \mathrm{tr}\left(\mathbf{A}\mathbf{m}\mathbf{m}^\top\right) = \mathrm{tr}(\mathbf{AB}).
\end{aligned}
\tag{26}
$$

Combine Lemma B.2 and Equation (23), we can obtain

$$
\mathbb{E}\left[(\mathrm{tr}(\mathbf{M}_t))^2\right] - \mathbb{E}\left[(\mathrm{tr}(\mathbf{S}_t \mathbf{M}_t)^2\right] = \mathbb{E}\left[\mathrm{tr}(\mathbf{AB})\right] \geq 0.
\tag{27}
$$

We focus on the late stages of training near convergence, where the gradient norm becomes very small, often substantially below one (Zhang et al., 2017). Thus, combining Equation (22), Equation (27) and Equation (21), we can obtain:

$$
\mathbb{E}\left[(\mathrm{proj}_{\mathrm{Muon}})^2\right] = \mathbb{E}\left[(\mathrm{tr}(\mathbf{M}))^2\right] \geq \mathbb{E}\left[\left(\mathrm{tr}(\mathbf{G}_t^\top \mathbf{V})\right)^2\right] \geq \mathbb{E}\left[(\mathrm{proj}_{\mathrm{SGD}})^2\right].
\tag{28}
$$

C Experimental Supplement

C.1 Additional Experiments on CIFAR

Table 6 presents the comparative performance of Muon and FaSO on the CIFAR-10 LT dataset with an imbalance factor of 10. The results demonstrate that both Muon and FaSO consistently surpass the SGD and SAM baselines across various loss functions, aligning with the trend observed in Table 1.

C.2 Additional Experiments on Computational Overhead

In Table 7, we provide additional experiments analyzing computational efficiency. We measure the average training time per epoch across four datasets using the CE loss function. The results show that the SAM optimizer incurs an average of 98% additional training time compared to SGD, while the Muon optimizer increases training time by an average of 106% under the same settings. In contrast, our proposed FaSO increases training time by only 15% on average relative to SGD. These findings are consistent with the results presented in Table 4 and Figures 3a and 3b.

C.3 Generalization to Natural Language Processing

While our primary evaluation followed mainstream long-tailed learning protocols centered on visual benchmarks (Menon et al., 2021), we further investigated the versatility of Muon by extending our experiments to the Natural Language Processing domain. We conducted experiments using the Yahoo Answers Topic

Table 6: Top-1 accuracy (%) (↑) results of different optimizers under various loss functions on CIFAR-10 LT with an imbalance factor of 10. Results for the *Medium* class group are presented as Med. in the table. FaSO and Muon are highlighted in light gray for focused comparison.

Loss	Method	Many	Med.	Few	All
CE	SGD	95.0	85.9	88.2	89.3
	SAM	95.2	86.3	88.1	89.1
	FaSO	95.0	86.4	89.9	**90.0**
	Muon	96.1	86.3	88.3	89.8
CB	SGD	94.9	86.4	88.4	89.6
	SAM	95.0	86.0	87.9	89.3
	FaSO	95.7	86.6	88.6	89.9
	Muon	95.6	87.2	88.7	**90.2**
LA	SGD	93.8	87.5	92.1	90.8
	SAM	94.1	87.0	92.1	90.7
	FaSO	94.5	87.5	92.2	91.0
	Muon	94.5	88.0	92.6	**91.3**
BCL	SGD	94.3	87.5	91.8	90.8
	SAM	94.5	88.3	93.2	91.6
	FaSO	95.0	88.6	92.5	**91.7**
	Muon	94.8	88.2	92.2	91.4
ProCo	SGD	94.8	88.6	92.6	91.7
	SAM	94.6	88.9	93.1	91.8
	FaSO	95.3	88.7	92.7	91.9
	Muon	94.8	88.6	93.5	**92.0**

Table 7: Computational overhead of different optimizers under CE loss on long-tailed benchmarks. We report the average training time per epoch (seconds) (↓) and the runtime ratio relative to SGD (in parentheses). FaSO and Muon are highlighted in light gray for focused comparison.

Method	CIFAR-100				ImageNet-LT		Places-LT	
	IF=10		IF=100					
SGD	3.47s	(1.00×)	3.10s	(1.00×)	280.046s	(1.00×)	224.70s	(1.00×)
SAM	6.94s	(1.99×)	4.66s	(1.50×)	392.170s	(1.40×)	356.08s	(1.58×)
Muon	8.22s	(2.37×)	5.87s	(1.89×)	435.29s	(1.55×)	471.63s	(2.10×)
FaSO	4.49s	(1.29×)	3.35s	(1.08×)	292.51s	(1.04×)	267.29s	(1.19×)

Classification dataset (Zhang et al., 2015). To simulate long-tailed distributions, we constructed two variants by sampling from a 12k training subset with imbalance factors of 10 and 50, respectively. We divide the classes into *Many*, *Medium*, and *Few* splits, corresponding to the top three, middle four, and bottom three classes sorted by frequency, respectively. Evaluation was performed on a balanced test set containing 4k samples. The model architecture consisted of a fixed pre-trained BERT-base-uncased backbone, followed by an MLP layer and a linear classification head. Both SGD and Muon were trained using CE loss for 20 epochs. As shown in Table 8, Muon consistently outperforms the SGD baseline across different imbalance factors, especially in the tail classes and highly imbalanced setting. This confirms that the benefits of Muon's curvature-aware optimization are not limited to vision tasks but also extend effectively to other modalities like NLP.

Table 8: Top-1 accuracy (%) (↑) results for *Many*, *Medium*, *Few*, and overall classes on long-tailed Yahoo Answers dataset, categorized by imbalance factors (IF) of 10 and 50.

IF	Method	Many	Medium	Few	All
10	SGD	75.9	58.5	43.3	59.1
	Muon	73.0	60.9	45.6	**59.9**
50	SGD	74.8	61.2	3.4	47.9
	Muon	76.8	55.9	17.3	**50.6**

C.4 Comparison with Fine-Tuning Method

Recent long-tailed recognition methods have explored fine-tuning paradigms on top of large-scale foundation models, such as LIFT (Shi et al., 2024) and LPT (Dong et al., 2023). To verify that Muon remains effective in this setting, we follow the experimental protocol of LIFT. Specifically, we adopt a pre-trained CLIP ViT-B/16 backbone and fine-tune it on CIFAR-100 LT with IF=100. We adhere to the experimental settings of LIFT for a fair comparison. As shown in Table 9, Muon achieves higher overall accuracy than LIFT, with particularly notable gains on tail classes. This indicates that Muon is complementary to fine-tuning based long-tailed methods, and can further improve representation quality even when starting from strong pre-trained features.

Table 9: Top-1 accuracy (%) (↑) results for *Many*, *Medium*, *Few*, and overall classes on CIFAR-100 LT under IF=100 with a CLIP ViT-B/16 backbone.

Method	Many	Medium	Few	All
LIFT	84.4	81.1	74.4	80.2
Muon	85.1	81.5	76.8	**81.3**

C.5 Muon with Decoupled Training Method

We further explore the performance of Muon when combined with decoupled training methods. Specifically, we evaluate Muon and FaSO under the standard two-stage decoupling framework (Kang et al., 2020): (1) *Stage 1*, trains the backbone representation, and (2) *Stage 2*, re-trains a balanced classifier (cRT) on top of the frozen backbone. Concretely, we train the backbone in Stage 1 using SGD, Muon, or FaSO, and then apply classifier re-training (cRT) in Stage 2. Experiments are conducted on CIFAR-100 LT under IF=10 and IF=100.

As shown in Table 10, Muon and FaSO consistently outperform SGD after cRT, indicating that re-balancing the classifier does not diminish their advantages. Instead, the gains persist because Muon and FaSO improve the quality of learned representations during Stage 1, providing a stronger feature space for the balanced classifier in the later stage.

Table 10: Top-1 accuracy (%) (↑) results for *Many*, *Medium*, *Few*, and overall classes on CIFAR-100 LT, categorized by imbalance factors (IF) of 10 and 100. FaSO and Muon are highlighted in light gray for focused comparison.

IF	Method	Many	Medium	Few	All
10	SGD	67.3	61.5	55.9	61.8
	Muon	68.3	61.9	57.3	62.8
	FaSO	68.9	62.4	56.5	**62.9**
100	SGD	66.3	51.7	31.7	47.5
	Muon	66.9	56.3	34.0	**50.6**
	FaSO	66.1	54.8	34.3	50.0

C.6 Comparison with Strong SAM Variant

Comparison with ImbSAM. Several SAM variants have been proposed for long-tailed learning, such as ImbSAM (Zhou et al., 2023a). We further conduct additional comparisons to evaluate the effectiveness and efficiency of our proposed FaSO. We compare FaSO against SGD, SAM, and ImbSAM on CIFAR-100-LT under imbalance factors IF=10 and IF=100. Following prior work, we consider both CE loss and BCL loss. We also report the training time measured on a single NVIDIA RTX 3090, normalized by the SGD baseline to highlight the efficiency trade-off.

As shown in Table 11, FaSO consistently attains the best overall accuracy across all settings while being substantially more efficient than SAM and ImbSAM. In particular, ImbSAM requires roughly 2.0×-3.1× the training cost of SGD due to its extra gradient computations, whereas FaSO only incurs a marginal overhead of about 1.1×–1.3×. These results demonstrate that FaSO achieves a more favorable accuracy-efficiency trade-off than computationally heavy SAM variants in long-tailed recognition.

Table 11: Top-1 accuracy (%) (↑) results for *Many*, *Medium*, *Few*, and overall classes on CIFAR-100 LT with CE and BCL losses, under imbalance factors (IF) of 10 and 100. We also report the training time (seconds) (↓) and the runtime ratio relative to SGD (in parentheses).

Loss	IF	Method	Many	Medium	Few	All	Time
CE	10	SGD	75.6	62.8	48.2	60.8	696 (1.00×)
		SAM	76.4	64.5	49.1	61.9	1390 (2.00×)
		ImbSAM	74.0	61.4	54.6	62.4	2148 (3.09×)
		FaSO	77.1	65.4	49.7	**62.6**	**898** (1.29×)
	100	SGD	75.9	52.0	15.7	44.6	516 (1.00×)
		SAM	76.3	51.6	17.0	45.2	932 (1.81×)
		ImbSAM	76.1	49.1	20.0	45.6	1270 (2.47×)
		FaSO	77.2	53.9	16.2	**45.8**	**670** (1.30×)
BCL	10	SGD	71.7	64.5	59.5	64.7	1674 (1.00×)
		SAM	72.5	65.2	60.0	65.3	2896 (1.73×)
		ImbSAM	71.9	66.0	60.3	65.5	3482 (2.08×)
		FaSO	73.9	66.0	60.4	**66.1**	**1804** (1.08×)
	100	SGD	68.5	54.2	34.2	50.5	1098 (1.00×)
		SAM	68.1	53.5	37.1	51.3	1802 (1.64×)
		ImbSAM	68.0	52.9	40.0	52.2	2148 (1.96×)
		FaSO	71.1	57.5	36.3	**53.1**	**1178** (1.07×)

Comparison with LookSAM. We further compare Muon and FaSO with LookSAM (Liu et al., 2022), a representative efficient SAM variant in balanced scenarios. We compare these methods on CIFAR-100-LT

under an imbalance factor of 100. The results are shown in Table 12. Although we verified that LookSAM matches SAM's performance on the balanced CIFAR-100 (both achieve an accuracy of 72.8%), the results show that its accuracy deteriorates substantially on the imbalanced CIFAR-100 LT, particularly on tail classes. In contrast, FaSO retains the robust generalization. This indicates that efficiency techniques effective in balanced settings, such as the gradient decomposition and estimation strategies used in LookSAM, are not robust under severe class imbalance. These findings underscore the value of developing efficient alternatives that remain effective in imbalanced scenarios, such as Muon and FaSO.

Table 12: Top-1 accuracy (%) (↑) results for *Many*, *Medium*, *Few*, and overall classes on CIFAR-100 LT with CE and LA losses, under an imbalance factor of 100. LookSAM-k denotes the method where the SAM update is performed every k steps. FaSO and Muon are highlighted in light gray for focused comparison.

Loss	Method	Many	Medium	Few	All
CE	SAM	76.3	51.6	17.0	45.2
	Muon	77.2	52.4	17.3	45.8
	FaSO	77.2	53.9	16.2	**45.8**
	LookSAM-2	74.8	46.7	10.5	40.7
	LookSAM-3	70.1	37.8	6.5	35.0
	LookSAM-4	64.2	29.9	4.6	30.1
LA	SAM	75.4	50.6	19.0	45.4
	Muon	76.4	52.2	19.7	**46.5**
	FaSO	76.5	52.5	19.3	46.4
	LookSAM-2	73.2	46.9	13.6	41.5
	LookSAM-3	70.0	40.1	9.7	36.9
	LookSAM-4	67.3	35.8	7.8	34.1

C.7 Results on Large-Scale Real-World Long-Tailed Dataset

To provide a more comprehensive evaluation, we extend our experiments to the large-scale real-world setting. We additionally benchmark our method on the iNaturalist-2018 (Horn et al., 2018) dataset. The iNaturalist-2018 is a large-scale real-world long-tailed dataset that contains 437.5k training images from 8,142 species. Following mainstream protocols (Cui et al., 2019; Du et al., 2024), we adopt a ResNet-50 backbone trained for 90 epochs using CE loss. We compare SGD, SAM, Muon, and our proposed FaSO under the *Many*, *Medium*, and *Few* splits. As shown in Table 13, Muon and FaSO both outperform SGD and SAM across all class splits, with especially clear improvements on tail classes. These results demonstrate that curvature-aware optimization methods, such as Muon and FaSO, generalize effectively to more challenging large-scale long-tailed datasets.

Table 13: Top-1 accuracy (%) (↑) results for *Many*, *Medium*, *Few*, and overall classes on iNaturalist-2018 dataset. Muon and FaSO exhibit consistent improvements across all class splits. FaSO and Muon are highlighted in light gray for focused comparison.

Method	Many	Medium	Few	All
SGD	74.6	64.9	56.8	62.7
SAM	76.4	66.8	58.8	64.6
FaSO	77.5	67.9	59.8	65.7
Muon	78.0	68.4	60.6	**66.3**

C.8 Deeper Understanding between Theoretical Analysis and FaSO Design

To demonstrate that the design of FaSO is grounded in the intrinsic training dynamics of long-tailed learning, we conducted an empirical analysis tracking the evolution of loss landscape geometry. Specifically, we monitored the Hessian trace of the least frequent class on CIFAR-100 LT under IF=100 across the training process for SGD, Muon, and FaSO. The results are presented in Table 14.

Table 14: Evolution of the Hessian trace on CIFAR-100 LT under imbalance factor of 100. Lower values indicate flatter minima, which correlate with better generalization.

Epoch	SGD	Muon	FaSO
80	664.6	636.1	691.5
120	956.1	450.8	615.2
180	1629.6	703.6	667.6
200	2137.5	536.0	514.1

These results show that, in the early training phase, both SGD and Muon exhibit relatively low traces. This suggests that during early exploration, the inherent stochasticity of SGD gradients provides sufficient noise to avoid sharp minima. Consequently, the complex orthogonalization operations of Muon incur computational overhead without offering significant geometric advantages during this period. This justifies FaSO's design choice to prioritize SGD in the early stages to maintain high computational efficiency while the optimization landscape is still being actively explored.

In later training stages, especially as the model nears convergence, the trace for SGD increases dramatically, indicating convergence to a sharp minimum, which is known to harm tail-class generalization. In contrast, Muon maintains significantly lower trace values, validating our theoretical analysis that it effectively escapes sharp regions by amplifying updates along negative curvature directions. This provides the motivation for FaSO to progressively increase its usage of the Muon optimizer as training advances. These observations confirm FaSO as a principled solution that combines SGD's early efficiency with Muon's capability to escape sharp minima in the later stages.

D Discussions

Additional related work. Recent advancements in long-tailed recognition have diversified beyond traditional re-balancing techniques. In the realm of contrastive learning, GPaCo (Cui et al., 2024) identifies the bias of supervised contrastive loss towards high-frequency classes and introduces parametric learnable centers to rebalance optimization dynamics. For handling diverse test distributions, DirMixE (Yang et al., 2024) proposes a sophisticated mixture-of-experts strategy based on Dirichlet meta-distributions to capture both global and local label distribution variations. Furthermore, addressing the geometry of the loss landscape has become a pivotal direction; CC-SAM (Zhou et al., 2023b) argues that naive flattening is insufficient for long-tailed learning and proposes a class-conditional sharpness-aware minimization to robustify the classifier against parameter perturbations.

Muon enhances representation learning. Muon fundamentally improves representation learning by guiding optimization toward flatter minima. In long-tailed recognition, a critical representational failure mode is the tendency for minority classes to converge to sharp regions of the loss landscape, which undermines generalization capabilities. Muon addresses this challenge. By amplifying updates along directions of negative curvature via gradient orthogonalization, Muon facilitates escape from these sharp regions and guides optimization toward flatter solutions. Securing these flatter minima, as evidenced by improved loss-landscape metrics on tail classes, is essential for learning robust representations that generalize better to underrepresented data, going beyond mere improvements in convergence speed. Table 9 and Table 10 also provide more empirical evidence that Muon could improve the quality of learned representations.

Regarding the CNC assumption. The Correlated Negative Curvature (CNC) assumption is well established in the non-convex optimization literature. It has been theoretically justified for learning half-

spaces Daneshmand et al. (2018), while subsequent studies, such as (Wang et al., 2020), have provided further validation through extensive analyses on deep networks of varying widths and depths. It has also been adopted in broader domains such as manifold optimization (Criscitiello & Boumal, 2019), making it a standard and widely accepted assumption. Importantly, in our setting, CNC has been examined directly in long-tailed learning. Rangwani et al. (2022) shows that tail classes exhibit strong negative curvature that traps SGD in sharp minima, and that methods like SAM alleviate this issue. Later works such as Zhou et al. (2023a) further support these observations. Our analysis builds on this established foundation and does not require stronger assumptions than prior work.

Targeted design addressing long-tailed learning challenges. Our work identifies and operationalizes a unique complementarity between gradient orthogonalization and long-tailed learning through two specialized contributions. First, our theoretical analysis demonstrates that Muon specifically addresses optimization bottlenecks inherent to underrepresented data by enhancing updates along directions of negative curvature, enabling the model to escape sharp minima that hinder tail-class generalization. Second, building on this insight, we designed FaSO specifically for long-tailed training dynamics. FaSO progressively integrates Muon during critical later stages when SGD fails to escape sharp minima, thereby increasing tail-class generalization while mitigating computational overhead. This provides an efficient solution essential for large-scale imbalanced benchmarks.

More insights on eigenvalues. The minimum eigenvalue of the Hessian can also provide geometric information, as highly negative values typically indicate convergence to unstable saddle-like regions. To validate performance, we compute the minimum eigenvalues for the class with the fewest samples under Muon and SGD on both CIFAR-10 LT and CIFAR-100 LT under IF=100. On CIFAR-10 LT, the minimum eigenvalue under Muon is -110.33, which is substantially larger than the -316.30 observed under SGD. This trend is even more pronounced on the challenging CIFAR-100 LT dataset, where Muon achieved a λ_{min} of -352.22 compared to -916.12 for SGD. This observation indicates significantly weaker negative curvature, corroborating Muon's effectiveness in escaping saddle-like regions for tail classes.

FaSO as a trade-off between efficiency and generalization. Our primary design objective for FaSO is to approximate Muon's generalization benefits while substantially mitigating its computational overhead. As shown in Table 1 and Table 2, FaSO exhibits a consistent performance pattern, reliably outperforming SGD and remaining competitive with Muon in terms of accuracy. Crucially, as shown in Table 4, it achieves these results while drastically reducing training costs compared to the significant overhead demands of Muon and SAM. Thus, FaSO successfully delivers its intended precise trade-off between high efficiency and robust generalization of tail classes.