Point Transformer V2: Grouped Vector Attention and Improved Sampling

Abstract

As a pioneering work exploring transformer architecture for 3D point cloud understanding, Point Transformer achieves impressive results on multiple highly competitive benchmarks. In this work, we analyze the limitations of the Point Transformer and propose our powerful and efficient Point Transformer V2 model with novel designs that overcome the limitations of previous work. In particular, we first propose group vector attention, which is more parameter-efficient and effective than the previous version of vector attention. Inheriting the advantages of both learnable weight vector and multi-head attention, we present a highly effective implementation of grouped vector attention with a novel grouped weight encoding layer. We also strengthen the position information for attention by an additional position encoding multiplier. Furthermore, we design novel and lightweight grid-based sampling methods which enable better spatial alignment for down-sampling and upsampling and more efficient sampling. Extensive experiments show that our model achieves better performance than its predecessor and achieves state-of-the-art on several challenging 3D point cloud understanding benchmarks, including 3D point cloud segmentation on ScanNet v2 and S3DIS and 3D point cloud classification on ModelNet40. *Our code will be made publicly available.*

1 Introduction

Point Transformer (PTv1) [1] introduces the self-attention networks to 3D point cloud understanding. Combining the vector attention [2] with a U-Net style encoder-decoder framework, PTv1 achieves remarkable performance in several 3D point cloud recognition tasks, including shape classification, object part segmentation, and semantic scene segmentation.

In this work, we analyze the limitations of Point Transformer (PTv1) [1] and propose a new elegant and powerful backbone named Point Transformer V2 (PTv2). Our PTv2 improves upon PTv1 with several novel designs, including the grouped vector self-attention, the improved position embedding, and the new grid-based sampling schemes.

The vector attention layers in PTv1 utilize MLPs as the weight encoding to map the subtraction relation of query and key into an attention weight vector that can modulate the individual channels of the value vector. However, as the model goes deeper and the number of channels increases, the number of weight encoding parameters also increases drastically, leading to severe overfitting and limiting the model depth. To address this problem, we present grouped vector attention with a more parameter-efficient formulation, where the vector attention is divided into groups with shared vector attention weights. Meanwhile, we show that the well-known multi-head attention [3] and the vector attention [2, 1] are degenerate cases of our proposed grouped vector attention. Our proposed grouped vector attention inherits the merits of both vector attention and multi-head attention while being more efficient and powerful.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Furthermore, point positions provide important geometric information for 3D semantic understanding. Hence, the positional relationship among 3D points is more critical than 2D pixels. However, previous 3D position encoding schemes mostly follow the 2D ones and do not fully exploit the geometric knowledge in 3D coordinates. To this end, we strengthen the position encoding mechanism by applying an additional position encoding multiplier to the relation vector. Such a design strengthens the positional relationship information in the model, and we validate its effectiveness in our experiments.

Moreover, it is worth noting that the irregular, non-uniform spatial distributions of points are significant challenges to the upsampling and downsampling modules for point cloud processing. Previous FPS and kNN-based point cloud downsampling and upsampling approaches [4] are time-consuming and not spatially well-aligned. To overcome this problem, we propose a grid-based sampling approach, where the 3D space of the point cloud is divided into non-overlapping 3D grids. We fuse the point within the same grid cell during downsampling and map features back to these points within the same grid during upsampling.

In conclusion, we propose Point Transformer V2, which improves Point Transformer [1] from several perspectives:

- We propose an effective grouped vector attention (GVA) with a novel weight encoding layer that enables efficient information exchange within and among attention groups.
- We introduce an improved position encoding scheme to utilize point cloud coordinates better and further enhance the spatial reasoning ability of the model.
- We design the grid-based downsampling and upsampling strategies to enable more efficient and spatially better-aligned sampling than previous methods.

We conducted extensive analysis and controlled experiments to validate our designs. Our results indicate that PTv2 outperforms predecessor works and sets the new state-of-the-art on various 3D understanding tasks.

2 Related Works

Image transformers. With the great success of ViT [5], the absolute dominance of convolution in vision tasks is shaken by Vision Transformer, which becomes a trend in 2D image understanding [6, 7, 8, 9]. ViT introduces the far-reaching scaled dot-product self-attention and multi-head self-attention theory [3] in NLP into vision by considering image patches as tokens. However, operating global attention on the entire image consumes excessive memory. To solve the memory consumption problem, Swin Transformer [6] introduces the grid-based local attention mechanism to operate the transformer block in a sequence of shifted windows.

Point cloud understanding. Learning-based methods for processing 3D point clouds can be classified into the following types: projection-based, voxel-based, and point-based networks. An intuitive way to process irregular inputs like point clouds is to transform irregular representations into regular ones. Projection-based methods project 3D point clouds into various image planes and utilize 2D CNN-based backbones to extract feature representations [10, 11, 12, 13]. An alternative approach operates convolutions in 3D by transforming irregular point clouds into regular voxel representations [14, 15]. Those voxel-based methods suffer from inefficiency because of the sparsity of point clouds until the introduction and implementation of sparse convolution [16, 17]. Point-based methods extract features directly from the point cloud rather than projecting or quantizing irregular point clouds onto regular grids in 2D or 3D [18, 4, 19, 20]. The recently proposed transformer-based point cloud understanding approaches, introduced in the next paragraph, are also categorized into point-based methods.

Point cloud transformers. Transformer-based networks belong to the category of point-based networks for point cloud understanding. During the research upsurge of vision transformers, at almost the same period, Zhao et al. [1] and Guo et al. [21] published their explorations of applying attention to point cloud understanding, becoming pioneers in this direction. The PCT [21] proposed by Guo et al. performs global attention directly on the point cloud. Their work, similar to ViT, is limited by memory consumption and computational complexity. Meanwhile, based on the vector attention theory proposed in SAN [2], Point Transformer [1] proposed by Zhao et al. directly performs local attention between each point and its adjacent points, which alleviated the memory problem mentioned above. Point Transformer achieves remarkable results in multiple point cloud understanding tasks and

Figure 1: Comparison of the attention, position encoding, and sampling mechanisms between PTv1 and PTv2. Top-left: the vector attention (Sec. 3.1) with position encoding (Sec. 3.3) in PTv1 . Bottom-left: our grouped vector attention (Sec. 3.2, denoted by red) with improved position encoding (Sec. 3.3, denoted by blue) in PTv2. Top-right: the FPS-based downsampling and interpolation-based upsampling in PTv1. Bottom-right: our grid-based downsampling and upsampling in PTv2 (Sec. 3.4).

state-of-art results for several competitive challenges. FPT [22] follows the pace of Point Transformer and applies voxel hashing-based architecture to vector attention, achieving a better speed-accuracy trade-off. In this work, we analyze the limitations of the Point Transformer, and propose several novel architecture designs for the attention, position encoding, and sampling module, to improve the efficiency and effectiveness of the Point Transformer. Our proposed model, Point Transformer V2, performs better than the Point Transformer across a variety of 3D scene understating tasks.

3 Point Transformer V2

We analyze the limitations of Point Transformer V1 (PTv1) [1] and propose our Point Transformer V2 (PTv2), including several improved modules upon PTv1. We begin by introducing the mathematical formulations and revisiting the vector self-attention used in PTv1 in Sec. 3.1. Based on the observation that the parameters of PTv1 increases drastically with the increased model depth and channel size, we propose our efficient and powerful grouped vector attention in Sec. 3.2. Further, we introduce our improved weight encoding in Sec. 3.1 and the new sampling method in Sec. 3.4. We finally describe our network architecture in Sec. 3.5.

3.1 Problem Formulation and Background

Problem formulation. Let $\mathcal{M} = (\mathcal{P}, \mathcal{F})$ be a 3D point cloud scene containing a set of points $\boldsymbol{x}_i = (\boldsymbol{p}_i, \boldsymbol{f}_i) \in \mathcal{M}$, where $\boldsymbol{p}_i \in \mathbb{R}^3$ represents the point position, and $\boldsymbol{f}_i \in \mathbb{R}^c$ represents the point features. Point cloud semantic segmentation aims to predict a class label for each point $\boldsymbol{x}_i$, and the goal of scene classification is to predict a class label for each scene $\mathcal{M}$. $\mathcal{M}(\boldsymbol{p})$ denotes a mapping function that maps the point at position $\boldsymbol{p}$ to a subset of $\mathcal{M}$ denoted as "reference set". Next, we revisit the self-attention mechanism used in PTv1 [1].

Local attention. Conducting the global attention [5, 21] over all points in a scene is computationally heavy and infeasible for large-scale 3D scenes. Therefore, we apply local attention where the attention for each point $\boldsymbol{x}_i$ works within a subset of points, *i.e.*, reference point set, $\mathcal{M}(\boldsymbol{p}_i)$.

Shifted-grid attention [6], where attention is alternatively applied over two sets of non-overlapping image grids, has become is a common practice [23, 24, 25, 26] for image transformers. Similarly,

the 3D space can be split into uniform non-overlapping grid cells, and the reference set is defined as the points within the same grid, *i.e.*, $\mathcal{M}(\boldsymbol{p}_i) = \{(\boldsymbol{p}_j, \boldsymbol{f}_j) \mid \boldsymbol{p}_j$ in the same grid cell as $\boldsymbol{p}_i\}$. However, such attention relies on a cumbersome shift grid operation to achieve a global receptive field, and it does not work well on point clouds where the point densities within different grids are not consistent.

PTv1 adopted *neighborhood attention*, where the reference point set is a local neighborhood of the given point, *i.e.*, $\mathcal{M}(\boldsymbol{p}_i) = \{(\boldsymbol{p}_j, \boldsymbol{f}_j) \mid \boldsymbol{p}_j \in \text{Neighborhood}(\boldsymbol{p}_i)\}$. Specifically, the neighborhood point set $\mathcal{M}(\boldsymbol{p}_i)$ is defined as the k nearest neighboring (kNN) points of $\boldsymbol{p}_i$ in PTv1. Our experiments (Sec. 4.3) show that neighborhood attention is more effective than shifted-grid attention, so our approach adopts the neighborhood attention.

Scalar attention and vector attention. Given a point $\boldsymbol{x}_i = (\boldsymbol{p}_i, \boldsymbol{f}_i) \in \mathcal{M}$, we apply linear projections or MLPs to project the point features $\boldsymbol{f}_i$ to the feature vectors of query $\boldsymbol{q}_i$, key $\boldsymbol{k}_i$, and value $\boldsymbol{v}_i$, each with c_h channels. The standard *scalar attention (SA)* operated on the point x_i and its reference point set $\mathcal{M}(\boldsymbol{p}_i)$ can be represented as follows,

$$w_{ij} = \langle \boldsymbol{q}_i, \boldsymbol{k}_j \rangle / \sqrt{c_h}, \qquad \boldsymbol{f}_i^{\text{attn}} = \sum_{\boldsymbol{x}_j \in \mathcal{M}(\boldsymbol{p}_i)} \text{Softmax}(\boldsymbol{w}_i)_j \boldsymbol{v}_j, \tag{1}$$

The attention weights in the above formulation are scalars computed from the scaled dot-product [3] between the query and key vectors. Multi-head scalar attention (MSA) [3] is an extension of SA which runs several scalar attentions in parallel. MSA is widely applied in transformers, and we will show in Sec. 3.2 that MSA is a degenerate case of our proposed grouped vector attention.

Instead of the scalar attention weights, PTv1 applies *vector attention*, where the attention weights are vectors that can modulate the individual feature channels. In SA, the scalar attention is computed by the scaled dot-product between the query and key vectors. In vector attention, a weight encoding function encodes the relation between query and key to a vector. The vector attention[2] is formulated as follows,

$$\boldsymbol{w}_{ij} = \omega(\gamma(\boldsymbol{q}_i, \boldsymbol{k}_j)), \qquad f_i^{\text{attn}} = \sum_{\boldsymbol{x}_j \in \mathcal{M}(\boldsymbol{p}_i)} \text{Softmax}(\boldsymbol{W}_i)_j \odot \boldsymbol{v}_j, \tag{2}$$

where $\odot$ is the Hadamard product. γ is a relation function (*e.g.*, subtraction). $\omega : \mathbb{R}^c \to \mathbb{R}^c$ is a learnable weight encoding (*e.g.*, MLP) that computes the attention vectors to re-weight $\boldsymbol{v}_j$ by channels before aggregation. Fig. 2 (a) shows a method using vector attention with linear weight encoding.

3.2 Grouped Vector Attention

In vector attention, as the network goes deeper and there are more feature encoding channels, the number of parameters for the weight encoding layer increases drastically. The large parameter size restricts the efficiency and generalization ability of the model. In order to overcome the limitations of vector attention, we introduce the grouped vector attention, as illustrated in Fig. 1(left).

Attention groups. We divide channels of the value vector $\boldsymbol{v} \in \mathbb{R}^c$ evenly into g groups ($1 \le g \le c$). The weight encoding layer outputs a grouped attention vector with g channels instead of c channels. Channels of $\boldsymbol{v}$ within the same attention group share the same scalar attention weight from the grouped attention vector. Mathematically,

$$\boldsymbol{w}_{ij} = \omega(\gamma(\boldsymbol{q}_i, \boldsymbol{k}_j)), \qquad \boldsymbol{f}_i^{attn} = \sum_{\boldsymbol{x}_j}^{\mathcal{M}(\boldsymbol{p}_i)} \sum_{l=1}^{g} \sum_{m=1}^{c/g} \text{Softmax}(\boldsymbol{W}_i)_{jl} \boldsymbol{v}_j^{lc/g+m}, \tag{3}$$

where γ is the relation function and $\omega : \mathbb{R}^c \to \mathbb{R}^g$ is the learnable *grouped weight encoding* defined in the next paragraph. The second equation in Eq. 3 is the *grouped vector aggregation*. Fig. 2 (a) presents a vanilla GVA implemented by a fully connected weight encoding, the number of the grouped weight encoding function parameters reduced compared with the vector attention (Fig. 2 (b)), leading to a more efficient and powerful model.

GVA is a generalized formulation of VA and MSA. GVA is also a generalized form of multi-head scalar attention. In Eq. 3, if we define: Our GVA degenerates to vector attention (VA) when $g = c$,

Figure 2: Comparison of various weight encoding functions. Each square represents a scalar, and each row of them represents a vector. The three rows represent relation vector, weight vector, and value vector from top to bottom. The attention groups are separated by dash lines. For demonstration, we assume the feature dimension is 4 and the number of attention groups (applicable to b, c, d) is 2. Lines with different colors refer to different operations, blue lines represent learnable parameters act on input relation scalar, while red lines represent multiply by the input relation scalar. Orange lines identify which value feature is affected by the input scalar weight.

and it degenerates to multi-head self-attention (MSA) if ω in Eq. 3 is defined as follows,

$$\omega(\boldsymbol{r}) = \boldsymbol{r} \underbrace{\begin{bmatrix} \boldsymbol{1}_{1 \times c_g} & \boldsymbol{0}_{1 \times c_g} & \cdots & \boldsymbol{0}_{1 \times c_g} \\ \boldsymbol{0}_{1 \times c_g} & \boldsymbol{1}_{1 \times c_g} & \cdots & \boldsymbol{0}_{1 \times c_g} \\ \vdots & \vdots & \ddots & \vdots \\ \boldsymbol{0}_{1 \times c_g} & \boldsymbol{0}_{1 \times c_g} & \cdots & \boldsymbol{1}_{1 \times c_g} \end{bmatrix}}_{g \times c_g}^{T} \frac{1}{\sqrt{c_g}}, \tag{4}$$

where $c_g = c/g$ and $r \in \mathbb{R}^{1 \times c}$.

Grouped linear. Inspired by the weight encoding function of MSA, we design the grouped linear layer $\zeta(r) : \mathbb{R}^c \to \mathbb{R}^g$ where different groups of the input vector are projected with different parameters independently. Grouped linear further reduce the number of parameters in the weight encoding function. Our final adopted grouped weight encoding function is composed of the grouped linear layer, normalization layer, activation layer, and a fully connected layer to allow inter-group information exchange. Mathematically,

$$\zeta(\boldsymbol{r}) = \boldsymbol{r} \underbrace{\begin{bmatrix} \boldsymbol{p}_1 & \boldsymbol{0}_{1 \times c_g} & \cdots & \boldsymbol{0}_{1 \times c_g} \\ \boldsymbol{0}_{1 \times c_g} & \boldsymbol{p}_2 & \cdots & \boldsymbol{0}_{1 \times c_g} \\ \vdots & \vdots & \ddots & \vdots \\ \boldsymbol{0}_{1 \times c_g} & \boldsymbol{0}_{1 \times c_g} & \cdots & \boldsymbol{p}_g \end{bmatrix}}_{g \times c_g}^{T}, \tag{5}$$

$$\omega(\boldsymbol{r}) = \text{Linear} \circ \text{Act} \circ \text{Norm}(\zeta(\boldsymbol{r})), \tag{6}$$

where $c_g = c/g$, $\boldsymbol{p}_1, \ldots, \boldsymbol{p}_g \in \mathbb{R}^c_g$ are learnable parameters, and $\circ$ represents function composition.

3.3 Position Encoding Multipler

Different from the discrete, regular-grid pixels in 2D images, points in the 3D point cloud are unevenly distributed in a continuous Euclidean Metric space, making the spatial relationship in 3D point cloud much more complicated than 2D images. In transformers and attention modules, the spatial information is obtained with the position encoding $\delta_{bias}(\boldsymbol{p}_i - \boldsymbol{p}_j))$ added to the relation vector $\gamma(\boldsymbol{q}_i, \boldsymbol{k}_j)$ as a bias.

We strengthen the position encoding with an additional multiplier $\omega(\delta_{mul}(\boldsymbol{p}_i - \boldsymbol{p}_j)$ to the relation vector. As shown in Fig. 1 (left), our improved position encoding is as follows,

$$\boldsymbol{w}_{ij} = \omega(\delta_{mul}(\boldsymbol{p}_i - \boldsymbol{p}_j) \odot \gamma(\boldsymbol{q}_i, \boldsymbol{k}_j) + \delta_{bias}(\boldsymbol{p}_i - \boldsymbol{p}_j)), \tag{7}$$

where $\odot$ is the Hadamard product. $\delta_{mul}, \delta_{bias} : \mathbb{R}^d \mapsto \mathbb{R}^d$ are two MLP position encoding functions, which take relative positions as input.

3.4 Grid-based Sampling Methods

The farthest-point-sampling-based downsampling method and the interpolation-based upsampling method presented in PointNet++ [4] and used in PTv1 [1] are time-consuming, and the downsampling and upsampling are not spatially well-aligned. Therefore, we propose the more efficient and effective grid-based upsampling and downsampling approach, shown in Fig. 1.

Grid fusion downsampling. Given a point set $\mathcal{M} = (\mathcal{P}, \mathcal{F})$, we partition $\mathcal{M}$ into subsets $[\mathcal{M}_1, \mathcal{M}_2, ..., \mathcal{M}_{n'}]$ by partitioning the space into non-overlapping grid cells. The size of the grid cells is denoted as s. We downsample each subset of points $\mathcal{M}_i = (\mathcal{P}_i, \mathcal{F}_i)$ from a single grid cell as follows,

$$\boldsymbol{f}_i' = \text{MaxPool}(\{\boldsymbol{f}_j \boldsymbol{U} \mid \boldsymbol{f}_j \in \mathcal{F}_i\}), \qquad \boldsymbol{p}_i' = \text{MeanPool}(\{\boldsymbol{p}_j \mid \boldsymbol{p}_j \in \mathcal{P}_i\}), \tag{8}$$

where $(\boldsymbol{p}_i', \boldsymbol{f}_i')$ is the downsampled point position and features form subset $\mathcal{M}_i$, and $\boldsymbol{U} \in \mathbb{R}^{c \times c'}$ is the linear projection. Collecting the sampled points from n' subsets gives us the downsampled point set $\mathcal{M}' = \{p_i', f_i'\}_{i=1}^{n'}$.

Grid mapping upsampling. To upsample the downsampled point set $\mathcal{M}'$ back to $\mathcal{M}$, the point locations in $\mathcal{M}$ are known from the downsampling process, and we only need to obtain the upsampled features for each point in $\mathcal{M}$. With the help of the grid-based partitioning $[\mathcal{M}_1, \mathcal{M}_2, ..., \mathcal{M}_{n'}]$ during the downsampling stage, we can map a point feature to all points from the same subset,

$$\boldsymbol{f}_i^{up} = \boldsymbol{f}_j', \qquad \text{if } (\boldsymbol{p}_i, \boldsymbol{f}_i) \in \mathcal{M}_j. \tag{9}$$

3.5 Network Architecture

Backbone structure. Following previous works [17, 1], we adopt the U-net architecture with skip connections. There are four stages of encoders and decoders with block depths [2, 2, 6, 2] and [1, 1, 1, 1], respectively. The grid size multipliers for the four stages are [x3.0, x2.5, x2.5, x2.5], representing the expansion ratio over the previous sampling stage. The attention is conducted in a local neighborhood, described in "neighborhood attention" in Sec. 3.1. In Sec. 4.3 we compare the neighborhood attention with shift-grid attention.

The initial feature dimension is 48, and we first embed the input channels to this number with a basic block with attention groups of 6. Then, we double this feature dimension and attention groups each time entering the next encoding stage. The initial feature dimension is 48. For the four encoding stages, the feature dimensions are [96, 192, 384, 384], and the corresponding attention groups are [12, 24, 48, 48].

Output head. For point cloud semantic segmentation, we apply an MLP to map point features produced by the backbone to the final logic for each point in the input point set. For point cloud classification, we apply global average pooling over the point features produced by the encoding stages to obtain a global feature vector, followed by an MLP classifier for prediction.

4 Experiments

To validate the effectiveness of the proposed method, we conduct experimental evaluations on ScanNet v2 [45] and S3DIS [46] for semantic segmentation, and ModelNet40 [47] for shape classification. Implementation details are available in the supplementary materials.

4.1 Semantic Segmentation

Data and metric. For semantic segmentation, we experiment on ScanNet v2 [45] and S3DIS [46]. The ScanNet v2 dataset contains 1,513 room scans reconstructed from RGB-D frames. The dataset is divided into 1,201 scenes for training and 312 for validation. Point clouds for the model input are sampled from vertices of reconstructed meshes, and each sampled point is assigned a semantic label from 20 categories (wall, floor, table, etc.). The S3DIS dataset for semantic scene parsing consists of 271 rooms in six areas from three different buildings. Following a common protocol [37, 4, 1], area 5 is withheld during training and used for testing. Different from ScanNet v2, points of S3DIS are densely sampled on the mesh surfaces and annotated into 13 categories. Following a standard protocol [4], we use mean classwise intersection over union (mIoU) as the evaluation metric for

Table 1: Semantic segmentation on ScanNet v2.

Method	Input	Val	Test
PointNet++ [4]	point	53.5	55.7
3DMV [27]	point	-	48.4
PanopticFusion [28]	point	-	52.9
PointCNN [29]	point	-	45.8
PointConv [30]	point	61.0	66.6
JointPointBased [31]	point	69.2	63.4
PointASNL [32]	point	63.5	66.6
SegGCN [33]	point	-	58.9
RandLA-Net [34]	point	-	64.5
KPConv [20]	point	69.2	68.6
JSENet [35]	point	-	69.9
FusionNet [36]	point	-	68.8
SparseConvNet [16]	voxel	69.3	72.5
MinkUNet [17]	voxel	72.2	73.6
FastPT [22]	point	72.5	-
PTv1 [1]	point	70.6	-
PTv2 (ours)	point	**75.4**	**73.9**

Table 2: Semantic segmentation on S3DIS Area 5.

Method	Input	OA	mAcc	mIoU
PointNet [18]	point	-	49.0	41.1
SegCloud [37]	point	-	57.4	48.9
TanConv [38]	point	-	62.2	52.6
PointCNN [29]	point	85.9	63.9	57.3
PointWeb [19]	point	87.0	66.6	60.3
HPEIN [39]	point	87.2	68.3	61.9
GACNet [40]	point	87.8	-	62.9
PAT [41]	point	-	70.8	60.1
ParamConv [42]	point	-	67.0	58.3
SPGraph [43]	point	86.4	66.5	58.0
SegGCN [33]	point	88.2	70.4	63.6
MinkUNet [17]	voxel	-	71.7	65.4
PAConv [44]	point	-	-	66.6
KPConv [20]	point	-	72.8	67.1
FastPT [22]	point	-	77.6	71.0
PTv1 [1]	point	90.8	76.5	70.4
PTv2(ours)	point	**91.1**	**77.9**	**71.6**

validation and test set of ScanNet v2. And we use mean classwise intersection over union (mIoU), mean of classwise accuracy (mAcc), and overall point-wise accuracy (OA) for evaluating performance on S3DIS area5.

Performance comparison. Table 1 and Table 2 show the results of our PTv2 model compared with previous methods on ScanNet v2 and S3DIS, respectively. Our PTv2 model outperforms prior methods in all evaluation metrics. Notably, PTv2 significantly outperforms PTv1 [1] by 4.9% mIoU on the ScanNet v2 validation set.

Visualization. The qualitative results of point cloud semantic segmentation are shown in Fig. 3 and Fig. 4. Our PTv2 model is able to predict semantic segmentation results that are quite close the ground-truth. It is worth noting that our model can capture the detailed structure information and predict the correct semantics for challenging scenarios. For example, in the S3DIS scenes with chairs, PTv2 is able to cleanly predict the chairs' legs and armrests.

4.2 Shape Classification

Data and metric. We test our proposed PTv2 model for 3D point cloud classification on ModelNet40 dataset. The ModelNet40 [47] dataset consists of 12,311 CAD models belonging to 40 object categories. 9,843 models are split out for training, and the rest 2,468 models are reserved for testing. Following the common practice in the community, we report the class-average accuracy (mAcc) and overall accuracy (OA) on the test set.

Performance comparison. We test our PTv2 model and compare it with previous models on the ModelNet40 dataset for shape classification. Results are shown in Table 3, demonstrating that our proposed PTv2 model achieves state-of-the-art performance on ModelNet40 shape classification. The visualization results of shape classification are provided in the supplementary materials.

4.3 Ablation Study

We conduct ablation studies to examine the effectiveness of each module in our design. The ablation study results are reported on ScanNet v2 validation set.

Attention type. We first investigate the effects of different attention designs. We experiment with two types of local attention introduced in Sec. 3.1, namely shifted-grid attention and neighborhood attention [1]. Then, to validate the effectiveness of our proposed grouped vector attention (denoted as "GVA"), we compare it with the commonly-used multi-head self-attention (denoted as "MSA"). We use the vanilla position encoding in PTv1 [1] and our proposed grid-based sampling scheme in all of the experiments in Table 4. It shows neighborhood attention performs significantly better than shifted-grid attention, indicating that the neighborhood attention is better suited for point clouds which are non-uniformly distributed. Moreover, our proposed grouped vector attention consistently outperforms

Table 3: Shape classification on ModelNet40.

Method	mAcc (%)	OA (%)
PointNet [18]	86.0	89.2
PointNet++ [4]	-	91.9
PointCNN [29]	88.1	92.5
PointConv [30]	-	92.5
KPConv [20]	-	92.9
DGCNN [48]	90.2	92.9
RS-CNN [49]	-	92.9
PointASNL [32]	-	92.9
DensePoint [50]	-	93.2
PosPool [51]	-	93.2
GBNet [52]	91.0	93.8
PCT [21]	-	93.2
PA-DGC [44]	-	93.9
CurveNet [53]	-	**94.2**
PTv1 [1]	90.6	93.7
PTv2 (ours)	**91.6**	**94.2**

Table 4: Attention type ablation.

Local Type	Mechanism Type	mIoU (%)
Shifted-Grid	MSA	71.6
	GVA	72.5
Neighborhood	MSA	73.9
	GVA	**75.0**

Table 5: Sampling method ablation.

Sampling Method	Sampling Ratio	Grid Size Multipliers	mIoU (%)
FPS	1/4	-	74.4
	1/6	-	72.9
Grid	~1/4	[×3.0, ×2.0, ×2.0, ×2.0]	75.2
	~1/4	[×4.0, ×2.0, ×2.0, ×2.0]	75.0
	~1/6	[×3.0, ×2.5, ×2.5, ×2.5]	**75.4**
	~1/6	[×4.0, ×2.5, ×2.5, ×2.5]	74.7

Table 6: Weight encoding ablation.

Weight encoding	mIoU (%)
(1) MSA	73.9
(2) L	73.8
(3) GL	74.1
(4) L+N+A+L	74.7
(5) **GL+N+A+L (ours)**	**75.0**

Table 7: Module design ablation.

ID	GVA	PE mul	Grid down	Grid up	mIoU (%)
I					72.3
II	✓				73.8
III	✓	✓			74.4
IV	✓	✓	✓		74.9
V	✓	✓	✓	✓	**75.4**

the commonly-used multi-head self-attention with both shifted-grid attention and neighborhood attention. So our grouped vector attention is not only more efficient, but also more effective, than multi-head self-attention. The comparison between GVA and MSA indicates the effectiveness of the learnable parameters in the grouped linear layer of the grouped weight encoding in Sec. 3.2.

Weight encoding. We study the effects of different weight encoding functions ω in Table 6. The weight encoding functions are introduced in Sec. 3.1 and Sec. 3.2, and different attention mechanisms adopt different weight encoding functions. We use the vanilla position encoding in PTv1 [1] and our proposed grid-based sampling scheme in all of the experiments in Table 4. We experimented with the following weight encoding functions: (1) The weight encoding for MSA in Eq. 4, denoted as "MSA". (2) Weight encoding as a linear layer denoted as "L". (3) The grouped linear layer, which is ζ in Eq. 5, denoted as "GL". (4) The linear layer followed by batch normalization, activation, and another linear layer, denoted as "L+N+A+L". (5) The grouped linear layer, followed by batch normalization, activation, and a linear layer, denoted as "GL+N+A+L". (5) is also the grouped weight encoding function used for our grouped vector attention, introduced as ω in Eq. 5. Results in Table 6 demonstrate that our grouped weight encoding function outperforms other compared designs. Specifically, comparing (1), (3) and (5), GL slightly outperforms MSA but adding additional inter-group information exchange combined with proper normalization and activation can boost the performance to be better than MSA. Moreover, the comparison between (5) and (4) and the comparison between (3) and (2) both indicate that our grouped linear layer outperforms the naive linear layer, even though the grouped linear layer has g times fewer parameters and requires less computing than the linear layer.

Sampling method. In Sec. 3.4 we discuss potential limitations of the FPS-based sampling in PTv1 and propose a new grid-based upsampling and downsampling scheme. We experiment with different downsampling-upsampling schemes in Table 5. For our grid-based sampling, the base grid size is 0.02 meters, which is identical to the voxelization grid size during data pre-processing. The grid size multipliers are the grid size expansion ratio over the previous sampling stage. For example, [×4.0, ×2.0, ×2.0, ×2.0] means that the sampling grid sizes are: [0.08, 0.16, 0.32, 0.64] meters, respectively. We choose a relatively large value for initial grid sizes (×3.0 and ×4.0) to provide sufficiently large receptive fields, which is analogous to the common practice in image

Figure 3: Visualization of semantic segmentation results on ScanNet v2.

Figure 4: Visualization of semantic segmentation results on S3DIS.

transformers [5]. For subsequent subsampling stages, we observe that ×2.0 grid size increase results in an approximate downsample ratio of 4 for the point cloud, while ×2.5 grid size increase results in an approximate downsample ratio of 6. We choose the same sampling ratio of 4 and 6 in FPS-based sampling experiments to ensure a fair comparison. The results in Table 5 illustrate that our grid-based sampling achieves higher mIoU than the FPS-based method. For FPS-based sampling, the performance decreases significantly when the sampling ratio increases from 4 to 6. However, for our grid-based sampling, we observe that initial grid size and subsequent grid size multipliers do not significantly affect the overall performance, so we can use larger grid sizes to reduce the number of points in each stage to save memory.

Module design. We ablate different modules: grouped vector attention (VGA), position encoding multiplier (PE mul), grid fusion downsampling (Grid down), grid mapping upsampling (Grid up). The results are shown in Table 7. Experiment I is PTv1 [1] with structural parameter adjustments and better data processing, which are also shared with the rest of experiments. Experiment II to V add each of our proposed components in turns. The increasing mIOU indicates the effectiveness of each component.

5 Conclusion

We propose Point Transformer V2 (PTv2), a powerful and efficient transformer-based backbone for 3D point cloud understanding. Our work makes several non-trivial improvements upon Point Transformer V1 [1], including the grouped vector attention, improved position encoding, and grid-based sampling. Our PTv2 model achieves state-of-the-art performance on point cloud classification and semantic segmentation benchmarks.

Limitations. Our limitation is that we have not yet explored the effect of parameter initialization for our point transformer, which plays an essential role in the convergence of image transformers. More information is in the supplementary materials.

Potential negative social impact. When training the Point Transformer V2 model on large datasets, researchers should be aware of the potential negative social impact introduced by the dataset bias and improper usage of the model.

References

[1] Hengshuang Zhao, Li Jiang, Jiaya Jia, Philip Torr, and Vladlen Koltun. Point transformer. In *ICCV*, 2021. 1, 2, 3, 6, 7, 8, 9

[2] Hengshuang Zhao, Jiaya Jia, and Vladlen Koltun. Exploring self-attention for image recognition. In *CVPR*, 2020. 1, 2, 4

[3] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *NeurIPS*, 2017. 1, 2, 4

[4] Charles R Qi, Li Yi, Hao Su, and Leonidas J Guibas. Pointnet++: Deep hierarchical feature learning on point sets in a metric space. In *NeurIPS*, 2017. 2, 6, 7, 8

[5] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. *ICLR*, 2021. 2, 3, 9

[6] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. *ICCV*, 2021. 2, 3

[7] Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pyramid vision transformer: A versatile backbone for dense prediction without convolutions. In *ICCV*, 2021. 2

[8] Xiaoyi Dong, Jianmin Bao, Dongdong Chen, Weiming Zhang, Nenghai Yu, Lu Yuan, Dong Chen, and Baining Guo. Cswin transformer: A general vision transformer backbone with cross-shaped windows. *arXiv:2107.00652*, 2021. 2

[9] Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *ECCV*, 2020. 2

[10] Hang Su, Subhransu Maji, Evangelos Kalogerakis, and Erik G. Learned-Miller. Multi-view convolutional neural networks for 3d shape recognition. In *ICCV*, 2015. 2

[11] Bo Li, Tianlei Zhang, and Tian Xia. Vehicle detection from 3d lidar using fully convolutional network. In *RSS*, 2016. 2

[12] Xiaozhi Chen, Huimin Ma, Ji Wan, Bo Li, and Tian Xia. Multi-view 3d object detection network for autonomous driving. In *CVPR*, 2017. 2

[13] Alex H Lang, Sourabh Vora, Holger Caesar, Lubing Zhou, Jiong Yang, and Oscar Beijbom. Pointpillars: Fast encoders for object detection from point clouds. In *CVPR*, 2019. 2

[14] Daniel Maturana and Sebastian Scherer. Voxnet: A 3d convolutional neural network for real-time object recognition. In *IROS*, 2015. 2

[15] Shuran Song, Fisher Yu, Andy Zeng, Angel X Chang, Manolis Savva, and Thomas Funkhouser. Semantic scene completion from a single depth image. In *CVPR*, 2017. 2

[16] Benjamin Graham, Martin Engelcke, and Laurens van der Maaten. 3d semantic segmentation with submanifold sparse convolutional networks. In *CVPR*, 2018. 2, 7

[17] Christopher Choy, JunYoung Gwak, and Silvio Savarese. 4d spatio-temporal convnets: Minkowski convolutional neural networks. In *CVPR*, 2019. 2, 6, 7

[18] Charles R Qi, Hao Su, Kaichun Mo, and Leonidas J Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. In *CVPR*, 2017. 2, 7, 8

[19] Hengshuang Zhao, Li Jiang, Chi-Wing Fu, and Jiaya Jia. Pointweb: Enhancing local neighborhood features for point cloud processing. In *CVPR*, 2019. 2, 7

[20] Hugues Thomas, Charles R Qi, Jean-Emmanuel Deschaud, Beatriz Marcotegui, François Goulette, and Leonidas J Guibas. Kpconv: Flexible and deformable convolution for point clouds. In *ICCV*, 2019. 2, 7, 8

[21] Meng-Hao Guo, Jun-Xiong Cai, Zheng-Ning Liu, Tai-Jiang Mu, Ralph R Martin, and Shi-Min Hu. Pct: Point cloud transformer. *Computational Visual Media*, 2021. 2, 3, 8

[22] Chunghyun Park, Yoonwoo Jeong, Minsu Cho, and Jaesik Park. Fast point transformer. *CVPR*, 2022. 3, 7

[23] Bowen Cheng, Alexander G. Schwing, and Alexander Kirillov. Per-pixel classification is not all you need for semantic segmentation. In *NeurIPS*, 2021. 3

[24] Bowen Cheng, Ishan Misra, Alexander G. Schwing, Alexander Kirillov, and Rohit Girdhar. Masked-attention mask transformer for universal image segmentation. In *CVPR*, 2022. 3

[25] Zhenda Xie, Zheng Zhang, Yue Cao, Yutong Lin, Jianmin Bao, Zhuliang Yao, Qi Dai, and Han Hu. Simmim: A simple framework for masked image modeling. In *CVPR*, 2022. 3

[26] Hao Zhang, Feng Li, Shilong Liu, Lei Zhang, Hang Su, Jun Zhu, Lionel M. Ni, and Heung-Yeung Shum. Dino: Detr with improved denoising anchor boxes for end-to-end object detection. *arXiv preprint arXiv:2203.03605*, 2022. 3

[27] Angela Dai and Matthias Nießner. 3dmv: Joint 3d-multi-view prediction for 3d semantic scene segmentation. In *ECCV*, 2018. 7

[28] Gaku Narita, Takashi Seno, Tomoya Ishikawa, and Yohsuke Kaji. Panopticfusion: Online volumetric semantic mapping at the level of stuff and things. In *IROS*, 2019. 7

[29] Yangyan Li, Rui Bu, Mingchao Sun, Wei Wu, Xinhan Di, and Baoquan Chen. Pointcnn: Convolution on x-transformed points. *NeurIPS*, 2018. 7, 8

[30] Wenxuan Wu, Zhongang Qi, and Li Fuxin. Pointconv: Deep convolutional networks on 3d point clouds. In *CVPR*, 2019. 7, 8

[31] Hung-Yueh Chiang, Yen-Liang Lin, Yueh-Cheng Liu, and Winston H Hsu. A unified point-based framework for 3d segmentation. In *3DV*, 2019. 7

[32] Xu Yan, Chaoda Zheng, Zhen Li, Sheng Wang, and Shuguang Cui. Pointasnl: Robust point clouds processing using nonlocal neural networks with adaptive sampling. In *CVPR*, 2020. 7, 8

[33] Huan Lei, Naveed Akhtar, and Ajmal Mian. Seggcn: Efficient 3d point cloud segmentation with fuzzy spherical kernel. In *CVPR*, 2020. 7

[34] Qingyong Hu, Bo Yang, Linhai Xie, Stefano Rosa, Yulan Guo, Zhihua Wang, Niki Trigoni, and Andrew Markham. Randla-net: Efficient semantic segmentation of large-scale point clouds. In *CVPR*, 2020. 7

[35] Zeyu Hu, Mingmin Zhen, Xuyang Bai, Hongbo Fu, and Chiew-lan Tai. Jsenet: Joint semantic segmentation and edge detection network for 3d point clouds. In *ECCV*, 2020. 7

[36] Feihu Zhang, Jin Fang, Benjamin Wah, and Philip Torr. Deep fusionnet for point cloud semantic segmentation. In *ECCV*, 2020. 7

[37] Lyne Tchapmi, Christopher Choy, Iro Armeni, JunYoung Gwak, and Silvio Savarese. Segcloud: Semantic segmentation of 3d point clouds. In *3DV*, 2017. 6, 7

[38] Maxim Tatarchenko, Jaesik Park, Vladlen Koltun, and Qian-Yi Zhou. Tangent convolutions for dense prediction in 3d. In *CVPR*, 2018. 7

[39] Li Jiang, Hengshuang Zhao, Shu Liu, Xiaoyong Shen, Chi-Wing Fu, and Jiaya Jia. Hierarchical point-edge interaction network for point cloud semantic segmentation. In *ICCV*, 2019. 7

[40] Lei Wang, Yuchun Huang, Yaolin Hou, Shenman Zhang, and Jie Shan. Graph attention convolution for point cloud semantic segmentation. In *CVPR*, 2019. 7

[41] Jiancheng Yang, Qiang Zhang, Bingbing Ni, Linguo Li, Jinxian Liu, Mengdie Zhou, and Qi Tian. Modeling point clouds with self-attention and gumbel subset sampling. In *CVPR*, 2019. 7

[42] Shenlong Wang, Simon Suo, Wei-Chiu Ma, Andrei Pokrovsky, and Raquel Urtasun. Deep parametric continuous convolutional neural networks. In *CVPR*, 2018. 7

[43] Loic Landrieu and Martin Simonovsky. Large-scale point cloud semantic segmentation with superpoint graphs. In *CVPR*, 2018. 7

[44] Mutian Xu, Runyu Ding, Hengshuang Zhao, and Xiaojuan Qi. Paconv: Position adaptive convolution with dynamic kernel assembling on point clouds. In *CVPR*, 2021. 7, 8

[45] Angela Dai, Angel X. Chang, Manolis Savva, Maciej Halber, Thomas Funkhouser, and Matthias Nießner. Scannet: Richly-annotated 3d reconstructions of indoor scenes. In *CVPR*, 2017. 6

[46] Iro Armeni, Ozan Sener, Amir R. Zamir, Helen Jiang, Ioannis Brilakis, Martin Fischer, and Silvio Savarese. 3d semantic parsing of large-scale indoor spaces. In *CVPR*, 2016. 6

[47] Zhirong Wu, Shuran Song, Aditya Khosla, Fisher Yu, Linguang Zhang, Xiaoou Tang, and Jianxiong Xiao. 3d shapenets: A deep representation for volumetric shapes. In *CVPR*, 2015. 6, 7

[48] Yue Wang, Yongbin Sun, Ziwei Liu, Sanjay E Sarma, Michael M Bronstein, and Justin M Solomon. Dynamic graph cnn for learning on point clouds. *TOG*, 2019. 8

[49] Yongcheng Liu, Bin Fan, Shiming Xiang, and Chunhong Pan. Relation-shape convolutional neural network for point cloud analysis. In *CVPR*, 2019. 8

[50] Yongcheng Liu, Bin Fan, Gaofeng Meng, Jiwen Lu, Shiming Xiang, and Chunhong Pan. Densepoint: Learning densely contextual representation for efficient point cloud processing. In *ICCV*, 2019. 8

[51] Ze Liu, Han Hu, Yue Cao, Zheng Zhang, and Xin Tong. A closer look at local aggregation operators in point cloud analysis. In *ECCV*, 2020. 8

[52] Shi Qiu, Saeed Anwar, and Nick Barnes. Geometric back-projection network for point cloud classification. *TMM*, 2021. 8

[53] Tiange Xiang, Chaoyi Zhang, Yang Song, Jianhui Yu, and Weidong Cai. Walk in the cloud: Learning curves for point clouds shape analysis. In *ICCV*, 2021. 8