Adaptive Oracle-Efficient Online Learning

Abstract

The classical algorithms for online learning and decision-making have the benefit of achieving the optimal performance guarantees, but suffer from computational complexity limitations when implemented at scale. More recent sophisticated techniques, which we refer to as *oracle-efficient* methods, address this problem by dispatching to an *offline optimization oracle* that can search through an exponentially-large (or even infinite) space of decisions and select that which performed the best on any dataset. But despite the benefits of computational feasibility, most oracle-efficient algorithms exhibit one major limitation: while performing well in worst-case settings, they do not adapt well to friendly environments. In this paper we consider two such friendly scenarios, (a) "small-loss" problems and (b) IID data. We provide a new framework for designing follow-the-perturbed-leader algorithms that are oracle-efficient and adapt well to the small-loss environment, under a particular condition which we call *approximability* (which is spiritually related to sufficient conditions provided in (Dudík et al., 2020)). We identify a series of real-world settings, including online auctions and transductive online classification problems, for which approximability holds. We also extend the algorithm to an IID data setting and establish a "best-of-both-worlds" bound in the oracle-efficient setting.

1 Introduction

Online learning is a fundamental paradigm for modeling sequential decision making problems (Cesa-Bianchi & Lugosi, 2006; Shalev-Shwartz, 2011; Hazan, 2016). Online learning is usually formulated as a zero-sum game between a learner and an adversary. In each round $t = 1, \ldots, T$, the learner first picks an action x_t from a (finite) set $\mathcal{X} = \{x^{(1)}, \ldots, x^{(K)}\}$ with cardinality equal to K. In the meantime, an adversary reveals its action $y_t \in \mathcal{Y}$. As a consequence, the learner observes y_t, and suffers a loss $f(x_t, y_t)$, where $f : \mathcal{X} \times \mathcal{Y} \mapsto [0, 1]$. The goal is to minimize the *regret*, which is defined as the difference between the cumulative loss of the learner $\sum_{t=1}^{T} f(x_t, y_t)$, and the cumulative loss of the best action in hindsight $L_T^* = \min_{x \in \mathcal{X}} \sum_{t=1}^{T} f(x, y_t)$.

A wide variety of algorithms have been proposed for the goal of minimizing worst-case regret (without any consideration of computational complexity per iteration); see (Cesa-Bianchi & Lugosi, 2006; Shalev-Shwartz, 2011; Hazan, 2016) for representative surveys of this literature. These algorithms all obtain a worst-case regret bound of the order $O(\sqrt{T \log K})$, which is known to be minimax-optimal (Cesa-Bianchi & Lugosi, 2006). Over the last two decades, sophisticated adaptive algorithms have been designed that additionally enjoy *problem-dependent* performance guarantees, which can automatically lead to better results in friendly environments. One of the most important example for this kind of guarantees is the so-called "small-loss" bound (Hutter & Poland, 2005; Cesa-Bianchi & Lugosi, 2006; Van Erven et al., 2014). Such a bound depends on the best cumulative loss in hindsight (i.e. L_T^*) instead of the total number of rounds (T). Thus, this bound is much tighter than the worst-case bound, especially when the best decision performs well in the sense of

incurring a very small loss. Another example is the "best-of-both-worlds" bound (Van Erven et al., 2014), which results in an even tighter regret bound for independent and identically distributed (IID) loss functions.

However, all of these algorithms applied out-of-the-box suffer a *linear* dependence on the number of decisions K. This is prohibitively expensive, especially in problems such as network routing (Awerbuch & Kleinberg, 2008) and combinatorial market design (Cesa-Bianchi et al., 2014), where the cardinality of the decision set grows exponentially with the natural expression of the problem. Although several efficient algorithms do exist when the loss functions have certain special structure, such as linearity (Kalai & Vempala, 2005), or convexity (Zinkevich, 2003), these results can not be easily extended to the more general settings of interest.

Notice that the efficiency of the above specialized methods is usually made possible by assuming that the corresponding *offline* optimization problem (i.e., minimizing the (averaged) loss) can be solved efficiently. This observation motivates the *oracle-efficient online learning* problem (Hazan & Koren, 2016). In this setting, the learner has access to a black-box offline oracle, which, given a real-weighted dataset $\mathcal{S} = \{(w^{(j)}, y^{(j)})\}_{j=1}^n$, can efficiently return the solution to the following problem:

$$\operatorname*{argmin}_{x \in \mathcal{X}} \sum_{j=1}^n w^{(j)} f(x, y^{(j)}). \tag{1}$$

The goal is to design *oracle-efficient* algorithms which can query the offline-oracle $O(1)$ times each round. Concrete examples of such an oracle include algorithms for empirical risk minimization (Bishop, 2007), data-driven market design (Nisan & Ronen, 2007), and dynamic programming (Bertsekas, 2019).

As pointed out by Hazan & Koren (2016), the design of oracle-efficient algorithms is extremely challenging and such an algorithm does not exist in the worst case. Nevertheless, recent work (Daskalakis & Syrgkanis, 2016; Syrgkanis et al., 2016; Dudík et al., 2020) has introduced a series of algorithms which are oracle-efficient when certain sufficient conditions are met. Among them, the state-of-the-art method is the *generalized-follow-the-perturbed-leader* algorithm (GFTPL, Dudík et al., 2020), which is a variant of the classical follow-the-perturbed-leader (FTPL) algorithm (Kalai & Vempala, 2005). Similar to FTPL, GFTPL perturbs the cumulative loss of each decision by adding a random variable, and chooses the decision with the smallest perturbed loss as x_t. However, the vanilla FTPL perturbs each decision independently, which requires to generate K independent random variables in total. Moreover, the oracle in (1) can not be applied here since the oracle can not handle the perturbation term. To address these limitations, GFTPL only generates a low-dimensional noise vector in the beginning, and constructs K *dependent* perturbations based on the multiplication between the noise vector and a *perturbation translation matrix* (PTM). In this way, the computational complexity for the noise generation is largely reduced. On the other hand, oracle-efficiency can be achieved by setting the elements in the PTM as carefully designed synthetic losses. Dudík et al. (2020) show that a worst-case optimal regret bound can be obtained when the PTM is *admissible*, i.e., every two rows are significantly distinct. This serves as a *sufficient condition* for achieving oracle-efficiency.

While these results form a solid foundation for general *worst-case* oracle-efficient online learning, it remains unclear whether *problem-dependent*, or *data-adaptive* bounds are achievable in conjunction with oracle-efficiency. In other words, the design of a generally applicable oracle-efficient *and* adaptive online learning algorithm has remained open. In this paper, we provide an affirmative answer to this problem, and make the following contributions.

- We propose a variant of the GFTPL algorithm (Dudík et al., 2020), and derive a new sufficient condition for ensuring oracle-efficiency while achieving the *small-loss* bound. Our key observation is that while the admissibility condition of the PTM in GFTPL successfully stabilizes the algorithm (by ensuring that $\mathbb{P}[x_t \neq x_{t+1}]$ is small), it is too weak to adapt to a small loss. We address this challenge via a new condition for PTM, called approximability. Critically, this condition ensures a stronger stability measure, i.e., the ratio of $\mathbb{P}[x_t = x^{(i)}]$ and $\mathbb{P}[x_{t+1} = x^{(i)}]$ is upper-bounded by a universal constant for any $i \in [K]$. We obtain the small-loss bound by equipping GFTPL with an approximable PTM, a data-dependent step-size and Laplace distribution for the perturbation noise. Our new condition of *approximability* is simple and interpretable, and can be easily verified for an arbitrary

PTM. It shares both similarities and differences from the *admissibility* condition proposed in Dudík et al. (2020). We demonstrate this through several examples where one of the sufficient condition holds, but not the other.

- We identified a series of real-world applications where approximable PTMs exist, for example: (a) a series of online auctions problems (Dudík et al., 2020); (b) problems with a small adversary's action space $|\mathcal{Y}|$ (Daskalakis & Syrgkanis, 2016); and (c) transductive online classification (Syrgkanis et al., 2016; Dudík et al., 2020). This is the first-time that the small-loss bound is obtained in these applications. To achieve this, we introduce novel PTMs and analysis for showing the approximability condition on these PTMs.

- We achieve the "best-of-both-worlds" bound, which enjoys even tighter results when the data is IID or the number of leader changes is small. The main idea is to combine our proposed algorithm with vanilla FTL leveraging ideas from a meta-algorithm introduced in Van Erven et al. (2014).

2 Related Work

Our work contributes to two classes of problems: oracle-efficient online learning and adaptive online learning. In this section, we briefly review the related work in these areas.

2.1 Oracle-efficient online learning

For oracle-efficient online learning, the pioneer work of Hazan & Koren (2016) points out that oracle-efficient methods do not exist when dealing with general hostile adversaries, which implies that additional assumptions on the problem structure have to be made. Daskalakis & Syrgkanis (2016) consider the setting in which the cardinality of the adversary's action set $\mathcal{Y}$ is finite and small, and propose to add a series of "fake" losses to the learning history based on random samples from $\mathcal{Y}$. They prove that for this setting an $O(|\mathcal{Y}|\sqrt{T})$ bound can be obtained. Syrgkanis et al. (2016) study the contextual combinatorial online learning problem, where each action is associated with a binary vector. They also assume the loss function set contains all linear functions as a sub-class. For this problem, Syrgkanis et al. (2016) construct a set of synthetic losses for perturbation based on randomly-selected contexts, and achieve worst-case optimal bounds when all the contextual information can be obtained beforehand, or when there exists a small set of contexts that can tell each decision apart. Dudík et al. (2020) focus on the general non-contextual setting, and propose the generalized FTPL algorithm. This algorithm generates a small number of random variables at the beginning, and then perturbs the learning history via the linear combinations of these random variables. The algorithm can be implemented efficiently by setting the combination parameters as carefully designed loss values. Niazadeh et al. (2021) consider a more complicated combinatorial setting where the offline problem is NP-hard, but a robust *approximation* oracle exists. For this case, they propose an online algorithm based on the approximation oracle, and prove that it has low approximate regret, which is a measure weaker than regret. Note that the aforementioned methods suffer from the worst-case bounds, and cannot benefit from nice structures in data. Recently, several concurrent work (Block et al., 2022; Haghtalab et al., 2022a) investigate how to obtain tighter bounds oracle-efficiently when the distribution of data is close to the uniform distribution (Rakhlin et al., 2011; Haghtalab et al., 2022b). However, their results do not improve the dependence on T.

In this paper, we mainly focus on the so-called the learning with expert advice setting (Cesa-Bianchi & Lugosi, 2006), where the action set is discrete, and the loss can be highly non-convex. On the other hand, efficient algorithms can be obtained when the loss functions have certain properties, such as linearity (Kalai & Vempala, 2005; Hutter & Poland, 2005; Awerbuch & Kleinberg, 2008), convexity (Zinkevich, 2003; Hazan et al., 2007) or submodularity (Hazan & Kale, 2012). Finally, we note that, in this paper we mainly focus on the full-information setting, where the learner can observe the whole loss function after the action is submitted. On the other hand, online learning with oracle has also been widely studied in the bandit setting (Langford & Zhang, 2008; Dudik et al., 2011; Agarwal et al., 2014; Foster et al., 2018; Foster & Rakhlin, 2020).

2.2 Adaptive online learning

In this paper, we focus on designing oracle-efficient algorithms with *problem-dependent* regret guarantees. Note that this kind of bound can be achieved by many inefficient algorithms in general, such as Hedge and its variants (Cesa-Bianchi & Lugosi, 2006; De Rooij et al., 2014; Luo & Schapire, 2015), and follow-the-perturbed-leader (Van Erven et al., 2014) or follow-the-regularized-leader (Orabona, 2019) type of methods. Small-loss can also be obtained efficiently when the loss functions are simply linear (Hutter & Poland, 2005; Syrgkanis et al., 2016). On the other hand, in online convex optimization, i.e., when the decision set and the loss functions are convex, small-loss bound can be obtained when the loss functions are smooth (Srebro et al., 2010; Orabona et al., 2012; Wang et al., 2020). However, these algorithms heavily rely on the special structure of the loss functions. In this paper, we take the first step to extend these methods to support the complicated and non-convex problems which appear in real-world applications.

Apart from the small-loss, there exist other types of problem-dependent bounds, such as second-order bound (Cesa-Bianchi et al., 2005; Gaillard et al., 2014), or quantile bound (Chaudhuri et al., 2009; Koolen & Erven, 2015), but how to obtain these more refined theoretical guarantees in the oracle-efficient setting remains an open problem.

3 GFTPL with Small-Loss Bound

In this section, forgoing computational complexity, we provide a new FTPL type of algorithm that enjoys the small-loss bound. We then show that the proposed algorithm can be implemented efficiently by the offline oracle in Section 4. Before diving into the details, we first briefly recall the definition of online learning and regret.

Preliminaries. The online decision problem we consider can be described as follows. In each round t, a learner picks an action $x_t \in \mathcal{X} = [x^{(1)}, \ldots, x^{(K)}]$. After observing the adversary's decision $y_t \in \mathcal{Y}$, the learner suffers a loss $f(x_t, y_t)$ where the loss function $f : \mathcal{X} \times \mathcal{Y} \mapsto [0, 1]$ is known. The regret is defined as

$$R_T := \mathbb{E}\left[\sum_{t=1}^{T} f(x_t, y_t) - L_T^*\right],$$

where $L_T^* = \min_{k \in [K]} \sum_{j=1}^{T} f(x^{(k)}, y_j)$ is the cumulative loss of the best action in hindsight, and the expectation is taken with respect to the potentially randomized strategy of the learner.

Our proposed algorithm follows the framework of GFTPL (Dudík et al., 2020). To help understanding, we first give a brief introduction to the intuition behind this method. Specifically, in each round t, GFTPL picks x_t by solving the following optimization problem:

$$x_t = \operatorname*{argmin}_{k \in [K]} \sum_{j=1}^{t-1} f(x^{(k)}, y_j) + \left\langle \Gamma^{(k)}, \alpha \right\rangle,$$

where α is a N-dimensional noise vector ($N \ll K$) generated from a uniform distribution, and $\Gamma^{(k)}$ is the k-th row of a matrix $\Gamma \in [0, 1]^{K \times N}$, which is referred to as the *perturbation translation matrix* (PTM). Compared to vanilla FTPL, GFTPL only generates a small number (N) of random variables, and each expert is perturbed by a different linear combination of these random variables based on Γ. The results of Dudík et al. (2020) rely on the following assumption on Γ.

Definition 1. (δ-admissibility (Dudík et al., 2020)) *Let $\Gamma \in [0, 1]^{K \times N}$ be a matrix, and denote $\Gamma^{(k)}$ as the k-th row of Γ, and $\Gamma^{(k,i)}$ the i-th element of $\Gamma^{(k)}$. Then, Γ is δ-admissible if (a) $\forall k, k' \in [K]$, $\exists i \in [N]$, such that $\Gamma^{(k,i)} \neq \Gamma^{(k',i)}$; and (b) $\forall i \in [N], k, k' \in [K]$, such that $\Gamma^{(k,i)} \neq \Gamma^{(k',i)}$, then $|\Gamma^{(k,i)} - \Gamma^{(k',i)}| \geq \delta$.*

The δ-admissibility guarantees that every two rows in Γ are significantly distinct. As pointed out by Dudík et al. (2020), this is the essential property required by GFTPL, and is used to *stabilize* the algorithm in the analysis, i.e., ensuring that $\mathbb{P}[x_t \neq x_{t+1}]$ is small. However, motivated by adaptive FTPL in the inefficient setting (Hutter & Poland, 2005), we observe that the small-loss bound can not rest on this notion of stability, instead one needs to control the following $\forall t$ and $\forall i \in [K]$,

$$\frac{\mathbb{P}[x_t = x^{(i)}]}{\mathbb{P}[x_{t+1} = x^{(i)}]}, \tag{2}$$

the ratio of the probability of picking the i-th decision in two consecutive rounds. We note that δ-admissibility is not strong enough to ensure this quantity is bounded, as we establish in the following lemma. (See Appendix A.1 for proof).

Lemma 1. *There is an instance of a δ-admissible Γ, and a sequence $\{y_t : t = 1, 2, \ldots\}$, such that if we run GFTPL we can have $\frac{\mathbb{P}[x_t = x^{(i)}]}{\mathbb{P}[x_{t+1} = x^{(i)}]} = \infty$ for some $i \in [K]$ and some $t > 0$.*

To tackle this problem, we propose a new property for Γ. Let $B_\gamma^1 := \{s \in \mathbb{R}^N : \|s\|_1 \leq \gamma\}$.

Definition 2. (γ-approximability) *Let $\Gamma \in [0, 1]^{K \times N}$. We say that Γ is γ-approximable if*

$$\forall k \in [K], y \in \mathcal{Y} \; \exists s \in B_\gamma^1 \; \forall j \in [K] : \qquad \left\langle \Gamma^{(k)} - \Gamma^{(j)}, s \right\rangle \geq f(x^{(k)}, y) - f(x^{(j)}, y).$$

It may not be immediately obvious how we arrived at this condition, so let us provide some intuition. The goal of perturbation methods in sequential decision problems, going back to the early work of Hannan (1957), is to ensure that the algorithm is "hedging" across all available alternative decisions. A new observed data point y may make expert j suddenly look more attractive than expert k, as we have now introduced a new gap $f(x^{(k)}, y) - f(x^{(j)}, y)$ in their measured loss values. With this in mind, we say that Γ is a "good" (i.e. approximable) choice for the PTM, if this gap can be overcome (hedged) by some small (i.e. likely) perturbation s, so that $\left\langle \Gamma^{(k)} - \Gamma^{(j)}, s \right\rangle$ makes up the difference. Later, we will show that γ-approximability guarantees the required stability measure in (2), and thus is critical for the small-loss bound.

We want to emphasize two final points. First, the γ-approximability condition is *purely for analysis purposes* and we need not compute the s in response to y and k. Second, much of the computational and decision-theoretic challenges rest heavily on the careful design of Γ. The PTM allows the algorithm to perform the appropriate hedging across an exponentially-sized set of experts with only an $N \ll K$ dimensions of perturbation. As we demonstrate in the following example, we can always construct a γ-approximable Γ, with $N = O(\log K)$, but at the expense of computational efficiency. The proposed Γ will not generally be *compatible* with the given oracle.

Simple Example. For any online learning problem we may construct Γ as follows. Let $N := \lceil \log_2 K \rceil$, and define the kth row $\Gamma^{(k)}$ to be the *binary representation* of the index k, with $+1/-1$ values instead of $0/1$. We claim that this Γ is γ-approximable, for $\gamma = \lceil \log_2 K \rceil$. We can satisfy the condition of Definition 2, by setting $s = \Gamma^{(k)}$. It is easy to that for any $j \neq k$ we have $\left\langle \Gamma^{(k)} - \Gamma^{(j)}, s \right\rangle = \left\langle \Gamma^{(k)} - \Gamma^{(j)}, \Gamma^{(k)} \right\rangle \geq 2 \geq f(x^{(k)}, y) - f(x^{(j)}, y)$, where the last inequality holds because $|f(x^{(i)}, y)| \leq 1$ for any $i \in [K]$.

Comparison We note that, although γ-approximability leads to a much tighter bound, it is not stronger than δ-admissibility. Instead, they are incomparable conditions. Specifically:

- In Section 4.1 we demonstrate that when Γ is binary, admissibility leads to approximability. As shown by Dudík et al. (2020), a binary and admissible Γ exists in various online auctions problems, including VCG with bidder-specific reserves (Roughgarden & Wang, 2019), envy-free item pricing (Guruswami et al., 2005), online welfare maximization in multi-unit auction (Dobzinski & Nisan, 2010), and simultaneous second-price auctions (Daskalakis & Syrgkanis, 2016). We can directly obtain an approximable Γ in such cases.

- On the other hand, in problems such as level auction (Dudík et al., 2020), one can construct both admissible and approximable Γ, although in different ways; we discuss in Section 4.1.

- In section 4.2, we show that, when the adversary's action space is small, we can always construct a γ-approximable Γ, while δ-admissible Γ in general does not exist.

- In Appendix A.2, we show that in some cases a δ-admissible Γ can be obtained while γ-approximability cannot be achieved.

Equipped with the γ-approximable PTM, we develop a generalized follow-the-perturbed-leader algorithm with the Laplace distribution[1] and a time-variant step size, which is summarized in Algo-

---

[1]Note that the Laplace distribution is not the unique choice to get the small-loss bound. In Appendix A.5, we prove that the ℓ_p perturbation $p(\alpha) \propto \exp\left\{ -\left(\sum_i |\alpha^{(i)}|^p \right)^{\frac{1}{p}} \right\}$ indeed works for any $p \geq 1$.

Algorithm 1 Generalized follow-the-perturbed-leader with small-loss bound

---

1: **Init:** $\Gamma \in [0,1]^{K \times N}$
2: Draw IID vector $\alpha = [\alpha^{(1)}, \ldots, \alpha^{(N)}] \sim \text{Lap}(1)^N$; that is, $p(\alpha^{(i)}) = \frac{1}{2}\exp(-|\alpha^{(i)}|)$
3: **for** $t = 1, \ldots, T$ **do**
4:     Set $\alpha_t \leftarrow \frac{\alpha}{\eta_t}$, where $\eta_t > 0$ a parameter computed online
5:     Choose $x_t \leftarrow \underset{k \in [K]}{\operatorname{argmin}} \sum_{j=1}^{t-1} f(x^{(k)}, y_j) + \left\langle \Gamma^{(k)}, \alpha_t \right\rangle$
6:     Observe y_t
7: **end for**

---

223 rithm 1. For the proposed algorithm, we successfully obtain the following stronger stability property.
224

Lemma 2. *Assume Γ is γ-approximable. Let $x_t' = \operatorname{argmin}_{k \in [K]} \sum_{j=1}^{t} f(x^{(k)}, y_j) + \langle \Gamma^{(k)}, \alpha_t \rangle$. Then in each round t, we have $\forall i \in [K]$,*

$$\mathbb{P}[x_t = x^{(i)}] \leq \exp\left(\gamma \eta_t\right) \mathbb{P}[x_t' = x^{(i)}].$$

225 Note that we replace the term x_{t+1} in (2) with x_t', as a time-variant step-size is used. Based on
226 Lemma 2, we obtain the regret bound of Algorithm 1 as follows.

Theorem 1. *Assume Γ is γ-approximable, and let $L_T^* = \min_{k \in [K]} \sum_{j=1}^{T} f(x^{(k)}, y_j)$. Algorithm 1,*
228 *with $\eta_t = \min\left\{\frac{1}{\gamma}, \frac{c}{\sqrt{L_{t-1}^* + 1}}\right\}$ for any $c > 0$, achieves the following regret bound:*

$$
\begin{aligned}
R_T \leq &\left(\frac{4\sqrt{2}\max\{2\ln K, \sqrt{N \ln K}\}}{c} + 2\gamma\left(c + \frac{1}{c}\right) \right) \sqrt{L_T^* + 1} \\
&+ 8\gamma \ln\left(\frac{1}{c}\sqrt{L_T^* + 1} + \gamma\right) + 2\gamma^2 + 4\sqrt{2}\max\{2\ln K, \sqrt{N \ln K}\}\gamma.
\end{aligned}
\tag{3}
$$

229 The proof of Lemma 2 and Theorem 1 can be found in Appendix A.3. By setting $c = \Theta(1)$, Theorem
230 1 implies that our proposed algorithm achieves $O(\max\{\gamma, \ln K, \sqrt{N \ln K}\}\sqrt{L_T^*})$ regret bound.

Comparison to GFTPL (Dudík et al., 2020) The original GFTPL algorithm has an $O(\frac{N}{\delta}\sqrt{T})$
232 regret bound. For the dependence on T, our $O(\sqrt{L_T^*})$ bound reduces to $O(\sqrt{T})$ in the worst-case,
233 and automatically becomes tighter when L_T^* is small. On the other hand, for the dependence on other
234 terms, we note that both $\frac{N}{\delta}$ and $\max\{\gamma, \ln K, \sqrt{N \ln K}\}$ are lower bounded by $\Omega(\ln K)$, and their
235 exact relationship depends on the specific problem. In Section 4, we show that for many auction
236 applications, the two terms are on the same order. Moreover, in cases such as when $|\mathcal{Y}|$ is small,
237 Algorithm 1 with an appropriate c leads to $O\left(\sqrt{L_T^* \max\{\ln K, \sqrt{|\mathcal{Y}| \ln K}\}}\right)$ regret bound, while
238 the regret bound of GFTPL in Dudík et al. (2020) can blow up since δ can be infinitely small.

4 Oracle-efficiency and Applications

240 In this section, we discuss how to run Algorithm 1 in an oracle-efficient way. Following Dudík et al.
241 (2020), we introduce the following definition.

Definition 3 (Implementability). *A matrix Γ is implementable with complexity M if for each $j \in [N]$ there exists a dataset S_j, with $|S_j| \leq M$, such that $\forall k, k' \in [K]$,*

$$\Gamma^{(k,j)} - \Gamma^{(k',j)} = \sum_{(w,y) \in \mathcal{S}_j} w\left(f(x^{(k)}, y) - f(x^{(k')}, y)\right).$$

242 Based on Definition 3, it is easy to get the following theorem, which is similar to Theorem 2.10 of
243 Dudík et al. (2020).

Algorithm 2 Oracle-based GFTPL for the reward feedback

1: **Input:** Data set S_j, $j \in [N]$, that implement a matrix $\Gamma \in [0,1]^{K \times N}$, $\eta_1 = \min\{\frac{1}{\gamma}, 1\}$.

2: Draw IID vector $\alpha = [\alpha^{(1)}, \ldots, \alpha^{(N)}] \sim \text{Lap}(1)^N$

3: **for** $t = 1, \ldots, T$ **do**

4: $\quad$ Choose $x_t \leftarrow \underset{k \in [K]}{\text{argmin}} \sum_{j=1}^{t-1} f(x^{(k)}, y_j) + \sum_{i=1}^{N} \frac{\alpha^{(i)}}{\eta_t} \left[\sum_{(w,y) \in S_i} w \cdot r(x^{(k)}, y) \right]$

5: $\quad$ Observe y_t

6: $\quad$ Compute $\widehat{L}_t^* = \underset{k \in [K]}{\min} \sum_{j=1}^{t} f(x^{(k)}, y_j)$ by using the oracle

7: $\quad$ Set $\eta_{t+1} \leftarrow \min\left\{ \frac{1}{\gamma}, \frac{1}{\sqrt{\widehat{L}_t^* + 1}} \right\}$

8: **end for**

Theorem 2. *If Γ is implementable, then Algorithm 1 is oracle-efficient and has a a per-round complexity $O(T + NM)$.*

In the following, we discuss how to construct approximable and implementable Γ matrices in different applications.

4.1 Applications in online auctions

In this part, we apply Algorithm 1 to online auction problems, which is the main focus of Dudík et al. (2020). To deal with this sort of problems, we first transform Algorithm 1 to online learning with rewards setting, i.e., in each round t, after choosing x_t, instead of suffering a loss, the learner obtains a reward $r(x_t, y_t) \in [0,1]$. For this case, it is straightforward to see that running Algorithm 1 on a surrogate loss $f(x,y) = 1 - r(x,y)$ directly leads to the small-loss bound. To proceed, we slightly change this procedure and obtain Algorithm 2. The main difference is that, we implement Γ with the reward function $r(x,y)$, instead of the surrogate loss $f(x,y)$. This makes the construction of Γ *much easier*. We have the following regret bound for Algorithm 2.

Corollary 1. *Let $f(x,y) = 1 - r(x,y)$. Assume Γ is γ-approximable w.r.t. $f(x,y)$ and implementable with function $r(x,y)$. Then Algorithm 2 is oracle-efficient and achieves the following regret bound:*

$$R_T = \mathbb{E}\left[L_T^* - \sum_{t=1}^{T} r(x_t, y_t) \right] = O\left(\max\left\{ \frac{\gamma}{\epsilon}, \ln K, \sqrt{N \ln K} \right\} \sqrt{T - L_T^*} \right),$$

where $L_T^* = \max_{i \in [K]} \sum_{t=1}^{T} r(x^{(i)}, y_t)$ is the cumulative reward of the best expert.

Next, we discuss how to construct the PTM in several auction problems.

Auctions with binary and admissible Γ. As shown by Dudík et al. (2020), in many online auction problems, such as VCG with bidder-specific reserves (Roughgarden & Wang, 2019), envy-free item pricing (Guruswami et al., 2005), online welfare maximization in multi-unit auction (Dobzinski & Nisan, 2010) and simultaneous second-price auctions (Daskalakis & Syrgkanis, 2016), there exists a binary PTM which is 1-admissible and implementable with N rows where $N \ll K$. For these cases, we have the following lemma. The proof is deferred to Appendix B.1.

Lemma 3. *Let $\Gamma \in [0,1]^{K \times N}$ be a binary matrix and 1-admissible, then Γ is N-approximable.*

Combining Lemma 3 with Corollary 1, and noticing the fact the $N = \Omega(\ln K)$, we can obtain an $O(N\sqrt{T - L_T^*})$ bound for all of the above problems. Compared to the original GFTPL, our condition leads to a similar dependence on N and a tighter dependence on T. More details about the aforementioned auction problems and corresponding regret bounds can be found in Appendix B.2.

Level auction Level auction is firstly proposed by Morgenstern & Roughgarden (2015) and is capable to get a $(1 - \epsilon)$ approximation compared with Myerson's optimal auction when the distribution of each bidder's valuation is independent from others. For this problem, the PTM in Dudík et al.

(2020) does not lead to approximability. To address this problem, we propose a novel way of constructing an approximable and implementable PTM. *The key idea is to utilize a coordinate-wise threshold function to implement* Γ. Note that this kind of function can not be directly obtained. Instead, we create an augmented problem with a surrogate loss to deal with this issue. For level auction with single-item, n-bidders, s-level and m-discretization level, our method enjoys an $O(nsm\sqrt{T - L_T^*})$ regret bound, which is tighter than the $O(nm^2\sqrt{T})$ (note that $s \leq m$) of the original GFTPL. Due to the page limitation, we postpone the detailed problem description and proof to Appendix B.3.

4.2 Other applications

Oracle learning and finite parameter space   In many real-world applications, such as security game (Balcan et al., 2015) and online bidding with finite threshold vectors (Daskalakis & Syrgkanis, 2016), the decision set $\mathcal{X}$ is extremely large, while the adversary's action set $|\mathcal{Y}|$ is finite small. For these problems, we can construct an implementable PTM based the following Lemma, where the proof can be found in Appendix B.4.

Lemma 4. *Consider the setting with* $|\mathcal{Y}| = d$ *($d \ll K$), then there exists a 1-approximable and implementable* Γ *with d columns and complexity 1.*

Combining Lemma 4 and Theorem 1, and configuring $c = \sqrt{\max\{\ln K, \sqrt{d \ln K}\}}$, we observe that our algorithm achieves $O(\sqrt{\max\{\ln K, \sqrt{d \ln K}\}}\sqrt{L_T^*})$ small-loss bound. On the other hand, in this kind of problems, because of the continuity of the loss functions, a δ-admissible PTM in general does not exist (as δ may approach 0 without any discretization). Therefore, our proposed condition not only leads to a tighter bound, but can also solve problems that the original GFTPL (Dudík et al., 2020) can not handle.

Transductive online classification   Finally, we consider the transductive online classification problem (Syrgkanis et al., 2016; Dudík et al., 2020). In this setting, $\mathcal{X}$ contains K binary classifiers. In each round t, firstly the adversary picks a feature vector $w_t \in \mathcal{W}$, where $|\mathcal{W}| = m$. Then, the learner chooses a classifier $x_t(\cdot)$ from $\mathcal{X}$. After that, the adversary reveals the label $y_t \in \{0, 1\}$, and the learner suffers a loss $f(x_t, (w_t, y_t)) = \mathbb{I}[x_t(w_t) \neq y_t]$. We assume the problem is transductive, i.e., the learner has access to $\mathcal{W}$ at the beginning. For this setting, we achieve the following results (the proof is in Appendix B.5).

Lemma 5. *Consider transductive online classification with* $|\mathcal{W}| = m$. *Then there exists a 1-approximable and implementable PTM with m columns and complexity 1. Moreover, Algorithm 1 with such a PTM and appropriately chosen parameters achieves* $O(\sqrt{\max\{\ln K, \sqrt{m \ln K}\}}\sqrt{L_T^*})$ *regret.*

Negative implementability   In the this paper we assume that the offline oracle can solve the minimization problem in (1) given any real-weights. In some cases, the oracle can only accept positive weights. This problem can be solved by constructing negative implementable PTM (Dudík et al., 2020). Note that in most cases discussed above negative implementable and approximable PTM exist, which is shown in Appendix B.6.

5   Best-of-Both-Worlds Bound

By setting all step sizes η_t as ∞, Algorithm 1 reduces to the classical FTL algorithm, which suffers linear regret in the adversarial setting and enjoys much tighter bounds when the data is IID or number of leader changes is small. To be more specific, we introduce the following regret bound for FTL.

Lemma 6 (Lemma 9, De Rooij et al. (2014)). *Let* $x_t^{\mathsf{FTL}} = \operatorname{argmin}_{i \in [K]} \sum_{s=1}^{t-1} f(x^{(i)}, y_s)$ *be the output of the FTL algorithm at round t, C_T the set of rounds where the leader changes, and $\delta_t = f(x_t^{\mathsf{FTL}}, y_t) - (L_t^* - L_{t-1}^*)$ the "mixability gap" at round t. Then for any $T \geq 1$, the regret of FTL is bounded by* $R_T^{\mathsf{FTL}} \leq \sum_{t \in C_T} \delta_t \leq |C_T|$.

Note that since $f \in [0, 1]$ and $L_t^* - L_{t-1}^* \in [0, f(x_t^{\mathsf{FTL}}, y_t)]$, we know $\delta_t \in [0, 1]$. For the *i.i.d* case, if the mean loss of the best expert is smaller than that of other experts by a constant, then due to

---

Algorithm 3 Oracle-efficient Flipflop (OFF)

Initialization: $\mathsf{Alg}_1 = \mathsf{FTL}$

1: **for** $t = 1, \ldots, T$ **do**
2:     Get x_t by Alg_t, observe y_t
3:     Compute $\widehat{U}_t^{\mathsf{FTL}}$ and $\widehat{U}_t^{\mathsf{GFTPL}}$
4:     **if** $\mathsf{Alg}_t == \mathsf{FTL}$ and $\widehat{U}_t^{\mathsf{FTL}} > \alpha \widehat{U}_t^{\mathsf{GFTPL}}$ **then**
5:         $\mathsf{Alg}_{t+1} = \mathsf{GFTPL}$
6:     **else if** $\mathsf{Alg}_t == \mathsf{GFTPL}$ and $\widehat{U}_t^{\mathsf{GFTPL}} > \beta \widehat{U}_t^{\mathsf{FTL}}$ **then**
7:         $\mathsf{Alg}_{t+1} = \mathsf{FTL}$
8:     **end if**
9:     Feed y_t to Alg_{t+1}
10: **end for**

---

the law of large numbers, the number of leader changes would be small, which results in a constant regret bound (De Rooij et al., 2014).

Denote U_T^{GFTPL} as the attainable regret bound (as in Theorem 1) for running Algorithm 1 alone and $U_T^{FTL} = \sum_{t \in C_T} \delta_t$ to be that of FTL. In the following, we develop a new algorithm and prove that it is optimal in both worlds, that is, its regret is on the order of $O(\min\{U_T^{\mathsf{FTL}}, U_T^{\mathsf{GFTPL}}\})$.

The proposed algorithm, named as oracle-efficient flipflop (OFF) algorithm, is summarized in Algorithm 3. It is motivated by the Flipflop algorithm (De Rooij et al., 2014), and the core idea is to switch between FTL and GFTPL (Algorthm 1) based on the comparison of the estimated regret. We optimistically start from FTL. In each round t, we firstly pick x_t based on the current algorithm Alg_t, and then obtain the adversary's action y_t (line 2). Next, we compute the estimated bounds of regret of both algorithms until round t (line 3). Specifically, let $\mathcal{I}_t^{\mathsf{FTL}} = \{i | i \in [t], \mathsf{Alg}_i = \mathsf{FTL}\}$ and $\mathcal{I}_t^{\mathsf{GFTPL}} = \{i | i \in [t], \mathsf{Alg}_i = \mathsf{GFTPL}\}$ be the set of rounds up to t in which we run FTL and GFTPL. Then, the estimated regret of FTL in $\mathcal{I}_t^{\mathsf{FTL}}$ is given by $\widehat{U}_t^{\mathsf{FTL}} = \sum_{i \in \mathcal{I}_t^{\mathsf{FTL}}} \delta_i$, and the estimated regret of GFTPL in $\mathcal{I}_t^{\mathsf{GFTPL}}$ can be bounded via Theorem 1:

$$
\begin{aligned}
\widehat{U}_t^{\mathsf{GFTPL}} = {}& \left(4\sqrt{2} \max\{2 \ln K, \sqrt{N \ln K}\} + 4\gamma \right) \sqrt{\widehat{L}_t^* + 1} \\
& + 8\gamma \ln\left(\sqrt{\widehat{L}_t^* + 1} + \gamma \right) + 2\gamma^2 + 4\sqrt{2} \max\{2 \ln K, \sqrt{N \ln K}\}\gamma.
\end{aligned}
\tag{4}
$$

where $\widehat{L}_t^* = \min_{x \in \mathcal{X}} \sum_{i \in \mathcal{I}_t^{\mathsf{GFTPL}}} f(x, y_i)$ and we set $c = 1$. Note that, the two quantities defined above are the exact regret upper bounds of the two algorithms on their sub-time intervals up to round t, due to the fact that the regret bounds provided in Lemma 6 and Theorem 1 are *timeless*. Moreover, note that the two values can be computed by the oracle. We compare the estimated regret of both algorithms, and use the algorithm which performs better for the next round (lines 4-8).

For the proposed algorithm, we have the following theoretical guarantee (the proof can be found in Appendix C).

Theorem 3. *Assume we have a γ-approximable Γ, then Algorithm 3 is able to achieve the following bound:*
$$
R_T^{OFF} \leq \min\left\{ 3U_T^{\mathsf{GFTPL}} + 1, 3U_T^{FTL} + \tau \right\},
$$
where $\tau = 4\sqrt{2} \max\{2 \ln K, \sqrt{N \ln K}\} + 12\gamma$ and $\alpha = \beta = 1$.

6 Conclusion

In this paper, we propose a variant of the generalized follow-the-perturbed-leader algorithm and derive a sufficient condition under which the small-loss bound can be attained in the oracle-efficient setting. We also show the condition is satisfied in various applications. Finally, we extend the algorithm to adapt to IID losses and achieve a "best-of-both-worlds" bound. In the future, we would like to investigate how to achieve tighter results for oracle-efficient setting, such as the second-order bound (De Rooij et al., 2014).

References

Agarwal, A., Hsu, D., Kale, S., Langford, J., Li, L., and Schapire, R. Taming the monster: A fast and simple algorithm for contextual bandits. In *Proceedings of the 27th International Conference on Machine Learning*, pp. 1638–1646, 2014.

Awerbuch, B. and Kleinberg, R. Online linear optimization and adaptive routing. *Journal of Computer and System Sciences*, 74(1):97–114, 2008.

Balcan, M.-F., Blum, A., Haghtalab, N., and Procaccia, A. D. Commitment without regrets: Online learning in stackelberg security games. In *Proceedings of the 16th ACM conference on economics and computation*, pp. 61–78, 2015.

Bertsekas, D. *Reinforcement learning and optimal control*. Athena Scientific, 2019.

Bishop, C. M. *Pattern Recognition and Machine Learning*. Springer, 2007.

Block, A., Dagan, Y., Golowich, N., and Rakhlin, A. Smoothed online learning is as easy as statistical learning. *arXiv preprint arXiv:2202.04690*, 2022.

Cesa-Bianchi, N. and Lugosi, G. *Prediction, Learning, and Games*. Cambridge University Press, 2006.

Cesa-Bianchi, N., Mansour, Y., and Stoltz, G. Improved second-order bounds for prediction with expert advice. In *Proceedings of the 18th Annual Conference on Learning Theory*, pp. 217–232, 2005.

Cesa-Bianchi, N., Gentile, C., and Mansour, Y. Regret minimization for reserve prices in second-price auctions. *IEEE Transactions on Information Theory*, 61(1):549–564, 2014.

Chaudhuri, K., Freund, Y., and Hsu, D. J. A parameter-free hedging algorithm. 22, 2009.

Daskalakis, C. and Syrgkanis, V. Learning in auctions: Regret is hard, envy is easy. In *The 57th Annual Symposium on Foundations of Computer Science*, pp. 219–228, 2016.

De Rooij, S., Van Erven, T., Grünwald, P. D., and Koolen, W. M. Follow the leader if you can, hedge if you must. *The Journal of Machine Learning Research*, 15(1):1281–1316, 2014.

Dobzinski, S. and Nisan, N. Mechanisms for multi-unit auctions. *Journal of Artificial Intelligence Research*, 37:85–98, 2010.

Dudik, M., Hsu, D., Kale, S., Karampatziakis, N., Langford, J., Reyzin, L., and Zhang, T. Efficient optimal learning for contextual bandits. In *Proceedings of the Twenty-Seventh Conference on Uncertainty in Artificial Intelligence*, pp. 169–178, 2011.

Dudík, M., Haghtalab, N., Luo, H., Schapire, R. E., Syrgkanis, V., and Vaughan, J. W. Oracle-efficient online learning and auction design. *Journal of the ACM*, 67(5):1–57, 2020.

Foster, D. and Rakhlin, A. Beyond ucb: Optimal and efficient contextual bandits with regression oracles. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 3199–3210. PMLR, 2020.

Foster, D., Agarwal, A., Dudik, M., Luo, H., and Schapire, R. Practical contextual bandits with regression oracles. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 1539–1548, 2018.

Gaillard, P., Stoltz, G., and Van Erven, T. A second-order bound with excess losses. In *Proceedings of the 27th Annual Conference on Learning Theory*, pp. 176–196, 2014.

Guruswami, V., Hartline, J. D., Karlin, A. R., Kempe, D., Kenyon, C., and McSherry, F. On profit-maximizing envy-free pricing. In *16th Annual ACM-SIAM Symposium on Discrete Algorithms*, pp. 1164–1173, 2005.

Haghtalab, N., Han, Y., Shetty, A., and Yang, K. Oracle-efficient online learning for beyond worst-case adversaries. *arXiv preprint arXiv:2202.08549*, 2022a.

Haghtalab, N., Roughgarden, T., and Shetty, A. Smoothed analysis with adaptive adversaries. In *IEEE 62nd Annual Symposium on Foundations of Computer Science*, pp. 942–953, 2022b.

Hannan, J. Approximation to bayes risk in repeated play. *Contributions to the Theory of Games*, 3 (2):97–139, 1957.

Hazan, E. Introduction to online convex optimization. *Foundations and Trends in Optimization*, 2 (3-4):157–325, 2016.

Hazan, E. and Kale, S. Online submodular minimization. In *Journal of Machine Learning Research*, volume 13, pp. 2903–2922, 2012.

Hazan, E. and Koren, T. The computational power of optimization in online learning. In *Proceedings of the 48th annual ACM symposium on Theory of Computing*, pp. 128–141, 2016.

Hazan, E., Agarwal, A., and Kale, S. Logarithmic regret algorithms for online convex optimization. *Machine Learning*, 69(2-3):169–192, 2007.

Hutter, M. and Poland, J. Adaptive online prediction by following the perturbed leader. *Journal of Machine Learning Research*, 6(22):639–660, 2005.

Kalai, A. and Vempala, S. Efficient algorithms for online decision problems. *Journal of Computer and System Sciences*, 71(3):291–307, 2005.

Koolen, W. M. and Erven, T. V. Second-order quantile methods for experts and combinatorial games. In *Proceedings of the 28th Conference on Learning Theory*, pp. 1155–1175, 2015.

Langford, J. and Zhang, T. The epoch-greedy algorithm for multi-armed bandits with side information. In *Advances in Neural Information Processing Systems 20*, pp. 817–824, 2008.

Luo, H. and Schapire, R. E. Achieving all with no parameters: Adanormalhedge. In *Proceedings of the 28th Conference on Learning Theory*, pp. 1286–1304, 2015.

Morgenstern, J. H. and Roughgarden, T. On the pseudo-dimension of nearly optimal auctions. *Advances in Neural Information Processing Systems 28*, 2015.

Niazadeh, R., Golrezaei, N., Wang, J. R., Susan, F., and Badanidiyuru, A. Online learning via offline greedy algorithms: Applications in market design and optimization. In *Proceedings of the 22nd ACM Conference on Economics and Computation*, pp. 737–738, 2021.

Nisan, N. and Ronen, A. Computationally feasible vcg mechanisms. *Journal of Artificial Intelligence Research*, 29:19–47, 2007.

Orabona, F. A modern introduction to online learning. *arXiv preprint arXiv:1912.13213*, 2019.

Orabona, F., Cesa-Bianchi, N., and Gentile, C. Beyond logarithmic bounds in online learning. In *Proceedings of the 15th International Conference on Artificial Intelligence and Statistics*, pp. 823–831, 2012.

Rakhlin, A., Sridharan, K., and Tewari, A. Online learning: Stochastic, constrained, and smoothed adversaries. 24, 2011.

Roughgarden, T. and Wang, J. R. Minimizing regret with multiple reserves. *ACM Transactions on Economics and Computation*, 7(3):1–18, 2019.

Shalev-Shwartz, S. Online learning and online convex optimization. *Foundations and Trends in Machine Learning*, 4(2):107–194, 2011.

Srebro, N., Sridharan, K., and Tewari, A. Smoothness, low-noise and fast rates. In *Advances in Neural Information Processing Systems 23*, pp. 2199–2207, 2010.

Syrgkanis, V., Krishnamurthy, A., and Schapire, R. Efficient algorithms for adversarial contextual learning. In *Proceedings of the 33rd International Conference on Machine Learning*, pp. 2159–2168, 2016.

Van Erven, T., Kotlowski, W., and Warmuth, M. K. Follow the leader with dropout perturbations. In *Proceedings of The 27th Conference on Learning Theory*, pp. 949–974, 2014.

Wang, G., Lu, S., Hu, Y., and Zhang, L. Adapting to smoothness: A more universal algorithm for online convex optimization. In *Proceedings of the 34th AAAI Conference on Artificial Intelligence*, 2020.

Zinkevich, M. Online convex programming and generalized infinitesimal gradient ascent. In *Proceedings of the 20th International Conference on Machine Learning*, pp. 928–936, 2003.