Robust Reinforcement Learning using Adversarial Populations

Abstract

Reinforcement Learning (RL) is an effective tool for controller design but can struggle with issues of robustness, failing catastrophically when the underlying system dynamics are perturbed. The Robust RL formulation tackles this by adding worst-case adversarial noise to the dynamics and constructing the noise distribution as the solution to a zero-sum minimax game. However, existing work on learning solutions to the Robust RL formulation has primarily focused on training a single RL agent against a single adversary. In this work, we demonstrate that using a single adversary does not consistently yield robustness to dynamics variations under standard parametrizations of the adversary; the resulting policy is highly exploitable by new adversaries. We propose a population-based augmentation to the Robust RL formulation in which we randomly initialize a population of adversaries and sample from the population uniformly during training. We empirically validate across robotics benchmarks that the use of an adversarial population results in a less exploitable, more robust policy. Finally, we demonstrate that this approach provides comparable robustness and generalization as domain randomization on these benchmarks while avoiding a ubiquitous domain randomization failure mode.

1 Introduction

Developing controllers that work effectively across a wide range of potential deployment environments is one of the core challenges in engineering. The complexity of the physical world means that the models used to design controllers are often inaccurate. Optimization based control design approaches, such as reinforcement learning (RL), have no notion of model inaccuracy and can lead to controllers that fail catastrophically under mismatch. In this work, we aim to demonstrate an effective method for training reinforcement learning policies that are robust to model inaccuracy by designing controllers that are effective in the presence of worst-case adversarial noise in the dynamics.

An easily automated approach to inducing robustness is to formulate the problem as a zero-sum game and learn an adversary that perturbs the transition dynamics (Tessler et al., 2019; Kamalaruban et al., 2020; Pinto et al., 2017). If a global Nash equilibrium of this problem is found, then that equilibrium provides a lower bound on the performance of the policy under some bounded set of perturbations. Besides the benefit of removing user design once the perturbation mechanism is specified, this approach is maximally conservative, which is useful for safety critical applications.

However, the literature on learning an adversary predominantly uses a single, stochastic adversary. This raises a puzzling question: the zero-sum game does not necessarily have any pure Nash equilibria (see Appendix C in Tessler et al. (2019)) but the existing robust RL literature mostly appears to attempt to solve for pure Nash equilibria. That is, the most general form of the minimax problem searches over distributions of adversary and agent policies, however, this problem is approximated in the literature by a search for a single agent-adversary pair. We contend that this reduction to a single adversary approach can sometimes fail to result in improved robustness under standard parametrizations of the adversary policy.

The following example provides some intuition for why using a single adversary can decrease robustness. Consider a robot trying to learn to walk east-wards while an adversary outputs a force representing wind coming from the north or the south. For a fixed, deterministic adversary the agent knows that the wind will come from either south or north and can simply apply a counteracting force at each state. Once the adversary is removed, the robot will still apply the compensatory forces and

possibly become unstable. Stochastic Gaussian policies (ubiquitous in continuous control) offer little improvement: they cannot represent multi-modal perturbations. Under these standard policy parametrizations, we cannot use an adversary to endow the agent with a prior that a strong wind could persistently blow either north or south. This leaves the agent exploitable to this class of perturbations.

The use of a single adversary in the robustness literature is in contrast to the multi-player game literature. In multi-player games, large sets of adversaries are used to ensure that an agent cannot easily be exploited (Vinyals et al., 2019; Czarnecki et al., 2020; Brown & Sandholm, 2019). Drawing inspiration from this literature, we introduce **RAP** (Robustness via Adversary Populations): a randomly initialized population of adversaries that we sample from at each rollout and train alongside the agent. Returning to our example of a robot perturbed by wind, if the robot learns to cancel the north wind effectively, then that opens a niche for an adversary to exploit by applying forces in another direction. With a population, we can endow the robot with the prior that a strong wind could come from either direction and that it must walk carefully to avoid being toppled over.

Our contributions are as follows:

- Using a set of continuous robotics control tasks, we provide evidence that a single adversary does not have a consistent positive impact on the robustness of an RL policy while the use of an adversary population provides improved robustness across all considered examples.
- We investigate the source of the robustness and show that the single adversary policy is exploitable by new adversaries whereas policies trained with RAP are robust to new adversaries.
- We demonstrate that adversary populations provide comparable robustness to domain randomization while avoiding potential failure modes of domain randomization.

2   RELATED WORK

This work builds upon robust control (Zhou & Doyle, 1998), a branch of control theory focused on finding optimal controllers under worst-case perturbations of the system dynamics. The Robust Markov Decision Process (R-MDP) formulation extends this worst-case model uncertainty to uncertainty sets on the transition dynamics of an MDP and demonstrates that computationally tractable solutions exist for small, tabular MDPs (Nilim & El Ghaoui, 2005; Lim et al., 2013). For larger or continuous MDPs, one successful approach has been to use function approximation to compute approximate solutions to the R-MDP problem (Tamar et al., 2014).

One prominent variant of the R-MDP literature is to interpret the perturbations as an adversary and attempt to learn the distribution of the perturbation under a minimax objective. Two variants of this idea that tie in closely to our work are Robust Adversarial Reinforcement Learning (RARL)(Pinto et al., 2017) and Noisy Robust Markov Decision Processes (NR-MDP) (Tessler et al., 2019) which differ in how they parametrize the adversaries: RARL picks out specific robot joints that the adversary acts on while NR-MDP adds the adversary action to the agent action. Both of these works attempt to find an equilibrium of the minimax objective using a single adversary; in contrast our work uses a large set of adversaries and shows improved robustness relative to a single adversary.

A strong alternative to the minimax objective, domain randomization, asks a designer to explicitly define a distribution over environments that the agent should be robust to. For example, (Peng et al., 2018) varies simulator parameters to train a robot to robustly push a puck to a target location in the real world; (Antonova et al., 2017) adds noise to friction and actions to transfer an object pivoting policy directly from simulation to a Baxter robot. Additionally, domain randomization has been successfully used to build accurate object detectors solely from simulated data (Tobin et al., 2017) and to zero-shot transfer a quadcopter flight policy from simulation (Sadeghi & Levine, 2016).

The use of population based training is a standard technique in multi-agent settings. Alphastar, the grandmaster-level Starcraft bot, uses a population of "exploiter" agents that fine-tune against the bot to prevent it from developing exploitable strategies (Vinyals et al., 2019). (Czarnecki et al., 2020) establishes a set of sufficient geometric conditions on games under which the use of multiple adversaries will ensure gradual improvement in the strength of the agent policy. They empirically demonstrate that learning in games can often fail to converge without populations. Finally, Active Domain Randomization (Mehta et al., 2019) is a very close approach to ours, as they use a population

of adversaries to select domain randomization parameters whereas we use a population of adversaries to directly perturb the agent actions. However, they explicitly induce diversity using a repulsive term and use a discriminator to generate the reward.

3 BACKGROUND

In this work we use the framework of a multi-agent, finite-horizon, discounted, Markov Decision Process (MDP) (Puterman, 1990) defined by a tuple $\langle A_{\text{agent}} \times A_{\text{adversary}}, S, \mathcal{T}, \mathcal{R}, \gamma \rangle$. Here A_{agent} is the set of actions for the agent, $A_{\text{adversary}}$ is the set of actions for the adversary, S is a set of states, $\mathcal{T} : A_{\text{agent}} \times A_{\text{adversary}} \times S \to \Delta(S)$ is a transition function, $R : A_{\text{agent}} \times A_{\text{adversary}} \times S \to \mathbb{R}$ is a reward function and γ is a discount factor. S is shared between the adversaries as they share a state-space with the agent. The goal for a given MDP is to find a policy π_θ parametrized by θ that maximizes the expected cumulative discounted reward $J^\theta = \mathbb{E}\left[\sum_{t=0}^{T} \gamma^t r(s_t, a_t) | \pi_\theta\right]$. The conditional in this expression is a short-hand to indicate that the actions in the MDP are sampled via $a_t \sim \pi_\theta(s_t, a_{t-1})$. We denote the agent policy parametrized by weights θ as π_θ and the policy of adversary i as $\bar{\pi}_{\phi_i}$. Actions sampled from the adversary policy $\bar{\pi}_{\phi_i}$ will be written as $\bar{a}_t^i$. We use ξ to denote the parametrization of the system dynamics (e.g. different values of friction, mass, wind, etc.) and the system dynamics for a given state and action as $s_{t+1} \sim f_\xi(s_t, a_t)$.

3.1 BASELINES

Here we outline prior work and the approaches that will be compared with RAP. Our baselines consist of a single adversary and domain randomization.

3.1.1 SINGLE MINIMAX ADVERSARY

Our adversary formulation uses the *Noisy Action Robust MDP* (Tessler et al., 2019) in which the adversary adds its actions onto the agent actions. The objective is

$$\max_\theta \min_\phi \mathbb{E}\left[\sum_{t=0}^{T} \gamma^t r(s_t, a_t + \alpha \bar{a}_t) | \pi_\theta, \ \bar{\pi}_\phi\right] \tag{1}$$

where α is a hyperparameter controlling the adversary strength. We note an important restriction inherent to this adversarial model. Since the adversary is only able to attack the agent through the actions, there is a restricted class of dynamical systems that it can represent; this set of dynamical systems may not necessarily align with the set of dynamical systems that the agent may be tested in. This is a restriction caused by the choice of adversarial perturbation and could be alleviated by using different adversarial parametrizations e.g. perturbing the transition function directly.

3.1.2 DYNAMICS RANDOMIZATION

Domain randomization is the setting in which the user specifies a set of environments which the agent should be robust to. This allows the user to directly encode knowledge about the likely deviations between training and testing domains. For example, the user may believe that friction is hard to measure precisely and wants to ensure that their agent is robust to variations in friction; they then specify that the agent will be trained with a wide range of possible friction values. We use ξ to denote some vector that parametrizes the set of training environments (e.g. friction, masses, system dynamics, etc.). We denote the domain over which ξ is drawn from as Ξ and use $\mathcal{P}(\Xi)$ to denote some probability distribution over ξ. The domain randomization objective is

$$\max_\theta \mathbb{E}_{\xi \sim \mathcal{P}(\Xi)}\left[\mathbb{E}_{s_{t+1} \sim f_\xi(s_t, a_t)}\left[\sum_{t=0}^{T} \gamma^t r(s_t, a_t) | \pi_\theta\right]\right]$$
$$s_{t+1} \sim f_\xi(s_t, a_t) \tag{2}$$
$$a_t \sim \pi_\theta(s_t)$$

Here the goal is to find an agent that performs well on average across the distribution of training environment. Most commonly, and in this work, the parameters ξ are sampled uniformly over Ξ.

4 RAP: ROBUSTNESS VIA ADVERSARY POPULATIONS

RAP extends the minimax objective with a population based approach. Instead of a single adversary, at each rollout we will sample uniformly from a population of adversaries. By using a population, the agent is forced to be robust to a wide variety of potential perturbations rather than a single perturbation. If the agent begins to overfit to any one adversary, this opens up a potential niche for another adversary to exploit. For problems with only one failure mode, we expect the adversaries to all come out identical to the minimax adversary, but as the number of failure modes increases the adversaries should begin to diversify to exploit the agent. To induce this diversity, we will rely on randomness in the gradient estimates and randomness in the initializations of the adversary networks rather than any explicit term that induces diversity.

Denoting $\bar{\pi}_{\phi_i}$ as the i-th adversary and $i \sim U(1, n)$ as the discrete uniform distribution defined on 1 through n, the objective becomes

$$\max_{\theta} \min_{\phi_1} \ldots \min_{\phi_n} \ \mathbb{E}_{i \sim U(1,n)} \left[\sum_{t=0}^{T} \gamma^t r(s_t, a_t, \alpha \bar{a}_t^i) | \pi_\theta, \ \bar{\pi}_{\phi_i} \right] \tag{3}$$
$$s_{t+1} \sim f(s_t, a_t + \alpha \bar{a}_t)$$

For a single adversary, this is equivalent to the *minimax adversary* described in Sec. 3.1.1

We will optimize this objective by converting the problem into the equivalent zero-sum game. At the start of each rollout, we will sample an adversary index from the uniform distribution and collect a trajectory using the agent and the selected adversary. For notational simplicity, we assume the trajectory is of length M and that adversary i will participate in J_i total trajectories while, since the agent participates in every rollout, the agent will receive J total trajectories. We denote the j-th collected trajectory for the agent as $\tau_j = (s_0, a_0, r_0, s_1) \times \cdots \times (s_M, a_M, r_M, s_{M+1})$ and the associated trajectory for adversary i as $\tau_j^i = (s_0, a_0, -r_0, s_1) \times \cdots \times (s_M, a_M, -r_M, s_M)$. Note that the adversary reward is simply the negative of the agent reward. We will use Proximal Policy Optimization (Schulman et al., 2017) (PPO) to update our policies. We caution that we have overloaded notation slightly here and for adversary i, $\tau_{j=1:J_i}^i$ refers only to the trajectories in which the adversary was selected: adversaries will only be updated using trajectories where they were active. At the end of a training iteration, we update all our policies using gradient descent. The algorithm is summarized below:

Algorithm 1: Robustness via Adversary Populations

Initialize $\theta, \phi_1 \cdots \phi_n$ using Xavier initialization (Glorot & Bengio, 2010);
while *not converged* **do**
    for *rollout j=1...J* **do**
        sample adversary $i \sim U(1, n)$;
        run policies $\pi_\theta, \bar{\pi}_{\phi_i}$ in environment until termination;
        collect trajectories τ_j, τ_j^i
    end
    update $\theta, \phi_1 \cdots \phi_n$ using PPO (Schulman et al., 2017) and the collected trajectories;
end

---

5 EXPERIMENTS

In this section we present experiments on continuous control tasks from the OpenAI Gym Suite (Brockman et al., 2016; Todorov et al., 2012). We compare with the existing literature and evaluate the efficacy of a population of learned adversaries across a wide range of state and action space sizes. We investigate the following hypotheses:

H1. Agents are more likely to overfit to a single adversary than a population of adversaries, leaving them less robust on in-distribution tasks.

H2. Agents trained against a population of adversaries will generalize better, leading to improved performance on out-of-distribution tasks.

Figure 1: From left to right, the Hopper, Half-Cheetah, and Ant environments we use to test our algorithm.

H3. Naive parametrization of domain randomization can result in a brittle policy, even when evaluated on the same distribution it was trained on.

In-distribution tasks refer to the agent playing against perturbations that are in the training distribution: adversaries that add their actions onto the agent. However, the particular form of the adversary and their restricted perturbation magnitude means that there are many dynamical systems that they cannot represent (for example, significant variations of joint mass and friction). These tasks are denoted as out of distribution tasks. All of the tasks in the test set described in Sec. 5.1 are likely out-of-distribution tasks.

5.1 Experimental Setup and Hyperparameter Selection

While we provide exact details of the hyperparameters in the Appendix, adversarial settings require additional complexity in hyperparameter selection. In the standard RL procedure, optimal hyperparameters are selected on the basis of maximum expected cumulative reward. However, if an agent playing against an adversary achieves a large cumulative reward, it is possible that the agent was simply playing against a weak adversary. Conversely, a low score does not necessarily indicate a strong adversary nor robustness: it could simply mean that we trained a weak agent.

To address this, we adopt a version of the train-validate-test split from supervised learning. We use the mean policy performance on a suite of validation tasks to select the hyperparameters, then we train the policy across ten seeds and report the resultant mean and standard deviation over twenty trajectories. Finally, we evaluate the seeds on a holdout test set of eight additional model-mismatch tasks. These tasks vary significantly in difficulty; for visual clarity we report the average across tasks in this paper and report the full breakdown across tasks in the Appendix.

We experiment with the Hopper, Ant, and Half Cheetah continuous control environments shown in Fig. 1. To generate the validation model mismatch, we pre-define ranges of mass and friction coefficients as follows: for Hopper, mass $\in [0.7, 1.3]$ and friction $\in [0.7, 1.3]$; Half Cheetah and Ant, mass $\in [0.5, 1.5]$ and friction $\in [0.1, 0.9]$. We scale the friction of every Mujoco geom and the mass of the torso with the same (respective) coefficients. We compare the robustness of agents trained via RAP against: 1) agents trained against a single adversary in a zero-sum game, 2) agents trained using domain randomization, and 3) an agent trained only using PPO and no perturbation mechanism. To train the domain randomization oracle, at each rollout we uniformly sample a friction and mass coefficient from the validation set ranges. We then scale the friction of all geoms and the mass of the torso by their respective coefficients; this constitutes directly training on the validation set which creates a strong baseline. To generate the test set of model mismatch, we take both the highest and lowest friction coefficients from the validation range and apply them to different combinations of individual geoms. For the exact selected combinations, please refer to the Appendix.

6 Results

H1. Analysis of Overfitting
A globally minimax optimal adversary should be unexploitable and perform equally well against any adversary of equal strength. We investigate the optimality of our policy by asking whether the minimax agent is robust to swaps of adversaries from different training runs, i.e. different seeds. Fig. 2 shows the result of these swaps for the one adversary and three adversary case. The diagonal corresponds to playing against the adversaries the agent was trained with while every other square corresponds to playing against adversaries from a different seed. To simplify presentation, in the

three adversary case, each square is the average performance against all the adversaries from that seed. We observe that the agent trained against three adversaries is robust under swaps while the single adversary case is not. The agent trained against a single adversary is highly exploitable, as can be seen by its extremely sub-par performance against an adversary from any other seed. Since the adversaries off-diagonal are feasible adversaries, this suggests that we have found a poor local optimum of the objective.

In contrast, the three adversary case is generally robust regardless of which adversary it plays against, suggesting that the use of additional adversaries has made the agent more robust. Of course, it's possible that the adversaries are simply weaker, but as we discuss in Sec. H2., the improved performance on transfer tasks suggests that the robustness across seed swaps is indicative of a genuine improvement in robustness.

Figure 2: Average cumulative reward under swaps for one adversary training (left) and three-adversary training (right). Each square corresponds to 20 trials. In the three adversary case, each square is the average performance against the adversaries from that seed.

H2. Robustness and Generalization of Population Training
Here we present the results from the validation and holdout test sets described in Section 5.1. We compare the performance of training with adversary populations of size three and five against vanilla PPO, the domain randomization oracle, and the single minimax adversary.

Figure 3: Average reward for Ant, Hopper, and Cheetah environments across ten seeds and across the validation set (top row) and across the holdout test set (bottom row). We compare vanilla PPO, the domain randomization oracle, and the minimax adversary against RAP of size three and five. Bars represent the mean and the arms represent the std. deviation. Both are computed over 20 rollouts for each test-set sample. The std. deviation for the test set are not reported here for visual clarity due to the large variation in holdout test difficulty.

Fig.3 shows the average reward (the average of ten seeds across the validation or test sets respectively) for each environment. Table 1 gives the corresponding numerical values and the percent change of each policy from the baseline. Standard deviations are omitted on the test set due to wide variation

	Validation					Test				
Ant	0 Adv	DR	1 Adv	3 Adv	5 Adv	0 Adv	DR	1 Adv	3 Adv	5 Adv
Mean Rew.	6336	6743	6349	6432	**6438**	2908	3613	3206	**3272**	3203
% Change		6.4	0.2	1.5	**1.6**		24.3	10.2	**12.5**	10.2
	Validation					Test				
Hopper	0 Adv	DR	1 Adv	3 Adv	5 Adv	0 Adv	DR	1 Adv	3 Adv	5 Adv
Mean Rew.	1182	2662	1094	**2039**	2021	472	1636	913	**1598**	1565
% Change		125	-7.4	**72.6**	71		246	93.4	**238**	231
	Validation					Test				
Cheetah	0 Adv	DR	1 Adv	3 Adv	5 Adv	0 Adv	DR	1 Adv	3 Adv	5 Adv
Mean Rew.	5659	3864	5593	5912	**6323**	5592	3656	5664	6046	**6406**
% Change		-32	-1.2	4.5	**11.7**		-35	1.3	8.1	**14.6**

Table 1: Average reward and % change from vanilla PPO (0 Adv) for Ant, Hopper, and Cheetah environments across ten seeds and across the validation (left) or holdout test set (right). Across all environments, we see consistently higher robustness using RAP than the minimax adversary. Most robust adversarial approach is bolded.

in task difficulty; the individual tests that we aggregate here are reported in the Appendix with appropriate error bars. In all environments we achieve a higher reward across both the validation and holdout test set using RAP of size three and/or five when compared to the single minimax adversary case. These results from testing on new environments with altered dynamics supports hypothesis H1. that training with a population of adversaries leads to more robust policies than training with a single adversary. Furthermore, while the performance is only comparable with domain randomization, the adversarial approach does not require identifying appropriate randomizations.

For a more detailed comparison of robustness across the validation set, Fig. 4 shows heatmaps of the performance across all the mass, friction coefficient combinations. Here we highlight the heatmaps for Hopper and Half Cheetah for vanilla PPO, domain randomization, single adversary, and best adversary population size. Additional heatmaps for other adversary population sizes and the Ant environment can be found in the Appendix. Note that Fig. 4 is an example of a case where a single adversary has negligible effect on or slightly reduces the performance of the resultant policy on the validation set. This supports our hypothesis that a single adversary can actually lower the robustness of an agent.

Figure 4: Average reward across ten seeds on each validation set parametrization – friction coefficient on the x-axis and mass coefficient on the y-axis. DR refers to domain randomization and X Adv is an agent trained against X adversaries. Top row is Hopper and bottom row is Half Cheetah.

H3. Effect of Domain Randomization Parametrization

From Fig. 3, we see that in the Ant and Hopper domains, the DR oracle achieves the highest transfer reward in the validation set as expected since the DR oracle is trained directly on the validation set. Interestingly, we found that the domain randomization policy performed much worse on the Half Cheetah environment, despite having access to the mass and friction coefficients during training. Looking at the performance for each mass and friction combination in Fig. 5, we found that the DR

agent was able to perform much better at the low friction coefficients and learned to prioritize those values at the cost of significantly worse performance on average. This highlights a potential issue with domain randomization: while training across a wide variety of dynamics parameters can increase robustness, naive parametrizations can cause the policy to exploit subsets of the randomized domain and lead to a brittle policy.

Figure 5: Average reward for Half Cheetah environment across ten seeds. Top row shows the average reward when trained with a 'bad' friction parametrization which lead to DR not learning a robust agent policy, and bottom row shows the average reward when trained with a 'good' friction parametrization.

We hypothesize that this is due to the DR objective in Eq. 2 optimizing in expectation over the sampling range. To test this, we created a separate range of 'good' friction parameters $[0.5, 1.5]$ and compared the robustness of a DR policy trained with 'good' range against a DR policy trained with 'bad' range $[0.1, 0.9]$ in Fig. 5. Here we see that a 'good' parametrization leads to the expected result where domain randomization is the most robust. We observe that domain randomization underperforms adversarial training on the validation set despite the validation set literally constituting the training set for domain randomization. This suggests that underlying optimization difficulties caused by significant variations in reward scaling are partially to blame for the poor performance of domain randomization. Notably, the adversary-based methods are not susceptible to the same parametrization issues.

7   CONCLUSIONS AND FUTURE WORK

In this work we demonstrate that the use of a single adversary to approximate the solution to a minimax problem does not consistently lead to improved robustness. We propose a solution through the use of multiple adversaries (RAP), and demonstrate that this provides robustness across a variety of robotics benchmarks. We also compare RAP with domain randomization and demonstrate that while DR can lead to a more robust policy, it requires careful parametrization of the domain we sample from to ensure robustness. RAP does not require this tuning, allowing for use in domains where appropriate tuning requires extensive prior knowledge or expertise.

There are several open questions stemming from this work. While we empirically demonstrate the effects of RAP, we do not have a compelling theoretical understanding of why multiple adversaries are helping. Perhaps RAP helps approximate a mixed Nash equilibrium as discussed in Sec. 1 or perhaps population based training increases the likelihood that one of the adversaries is strong? Would the benefits of RAP disappear if a single adversary had the ability to represent mixed Nash?

There are some extensions of this work that we would like to pursue. We have looked at the robustness of our approach in simulated settings; future work will examine whether this robustness transfers to real-world settings. Additionally, our agents are currently memory-less and therefore cannot perform adversary identification; perhaps memory leads to a system-identification procedure that improves transfer performance. Our adversaries can also be viewed as forming a task distribution, allowing them to be used in continual learning approaches like MAML (Nagabandi et al., 2018) where domain randomization is frequently used to construct task distributions.

REFERENCES

Rika Antonova, Silvia Cruciani, Christian Smith, and Danica Kragic. Reinforcement learning for pivoting task. *arXiv preprint arXiv:1703.00472*, 2017.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

Noam Brown and Tuomas Sandholm. Superhuman ai for multiplayer poker. *Science*, 365(6456): 885–890, 2019.

Wojciech Marian Czarnecki, Gauthier Gidel, Brendan Tracey, Karl Tuyls, Shayegan Omidshafiei, David Balduzzi, and Max Jaderberg. Real world games look like spinning tops. *arXiv preprint arXiv:2004.09468*, 2020.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256, 2010.

Parameswaran Kamalaruban, Yu-Ting Huang, Ya-Ping Hsieh, Paul Rolland, Cheng Shi, and Volkan Cevher. Robust reinforcement learning via adversarial training with langevin dynamics. *arXiv preprint arXiv:2002.06063*, 2020.

Eric Liang, Richard Liaw, Philipp Moritz, Robert Nishihara, Roy Fox, Ken Goldberg, Joseph E Gonzalez, Michael I Jordan, and Ion Stoica. Rllib: Abstractions for distributed reinforcement learning. *arXiv preprint arXiv:1712.09381*, 2017.

Shiau Hong Lim, Huan Xu, and Shie Mannor. Reinforcement learning in robust markov decision processes. In *Advances in Neural Information Processing Systems*, pp. 701–709, 2013.

Bhairav Mehta, Manfred Diaz, Florian Golemo, Christopher J Pal, and Liam Paull. Active domain randomization. *arXiv preprint arXiv:1904.04762*, 2019.

Anusha Nagabandi, Chelsea Finn, and Sergey Levine. Deep online learning via meta-learning: Continual adaptation for model-based rl. *arXiv preprint arXiv:1812.07671*, 2018.

Arnab Nilim and Laurent El Ghaoui. Robust control of markov decision processes with uncertain transition matrices. *Operations Research*, 53(5):780–798, 2005.

Xue Bin Peng, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *2018 IEEE international conference on robotics and automation (ICRA)*, pp. 1–8. IEEE, 2018.

Lerrel Pinto, James Davidson, Rahul Sukthankar, and Abhinav Gupta. Robust adversarial reinforcement learning. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 2817–2826. JMLR. org, 2017.

Martin L Puterman. Markov decision processes. *Handbooks in operations research and management science*, 2:331–434, 1990.

Fereshteh Sadeghi and Sergey Levine. Cad2rl: Real single-image flight without a single real image. *arXiv preprint arXiv:1611.04201*, 2016.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Aviv Tamar, Shie Mannor, and Huan Xu. Scaling up robust mdps using function approximation. In *International Conference on Machine Learning*, pp. 181–189, 2014.

Chen Tessler, Yonathan Efroni, and Shie Mannor. Action robust reinforcement learning and applications in continuous control. *arXiv preprint arXiv:1901.09184*, 2019.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 23–30. IEEE, 2017.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033. IEEE, 2012.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

Kemin Zhou and John Comstock Doyle. *Essentials of robust control*, volume 104. Prentice hall Upper Saddle River, NJ, 1998.

A FULL DESCRIPTION OF THE MDPS

We use the Mujoco ant, cheetah, and hopper environments as a test of the efficacy of our strategy versus the 0 adversary, 1 adversary, and domain randomization baselines. We use the Noisy Action Robust MDP formulation Tessler et al. (2019) for our adversary parametrization. If the normal system dynamics are

$$s_{k+1} = s_k + f(s_k, a_k)\Delta t$$

the system dynamics under the adversary are

$$s_{k+1} = s_k + f(s_k, a_k + a_k^{\text{adv}})\Delta t$$

where a_k^{adv} is the adversary action at time k.

The notion here is that the adversary action is passed through the dynamics function and represents some additional set of dynamics. It is standard to clip actions within some boundary but for the above reason, we clip the agent and adversary actions separately. Otherwise, an agent would be able to limit the effect of the adversary by always taking actions at the bounds of its clipping range. The agent is clipped between $[-1, 1]$ in the Hopper environment and the adversary is clipped between $[-.25, .25]$.

The MDP through which we train the agent policy is characterized by the following states, actions, and rewards:

- $s_t^{\text{agent}} = [o_t, a_t]$ where o_t is an observation returned by the environment, and a_t is the action taken by the agent.

- We use the standard rewards provided by the OpenAI Gym Mujoco environments at `https://github.com/openai/gym/tree/master/gym/envs/mujoco`. For the exact functions, please refer to the code at **ANONYMIZED**.

- $a_t^{\text{agent}} \in [a_{\min}, a_{\max}]^n$.

The MDP for adversary i is the following:

- $s_t = s_t^{\text{agent}}$. The adversary sees the same states as the agent.

- The adversary reward is the negative of the agent reward.

- $a_t^{\text{adv}} \in [a_{\min}^{\text{adv}}, a_{\max}^{\text{adv}}]^n$.

For our domain randomization Hopper baseline, we use the following randomization: at each rollout, we scale the friction of all joints by a single value uniformly sampled from [0.7, 1.3]. We also randomly scale the mass of the 'torso' link by a single value sampled from [0.7, 1.3]. For Half-Cheetah and Ant the range for friction is [0.1, 0.9] and for mass the range is [0.5, 1.5].

B HOLDOUT TESTS

In this section we describe in detail all of the holdout tests used.

Figure 6: Labelled Body Segments of Hopper

Table 2: Hopper Holdout Test Descriptions

Test	Body with Friction Coeff 1.3	Body with Friction Coeff 0.7
A	Torso, Leg	Floor, Thigh, Foot
B	Floor, Thigh	Torso, Leg, Foot
C	Foot, Leg	Floor, Torso, Thigh
D	Torso, Thigh, Floor	Foot, Leg
E	Torso, Foot	Floor, Thigh, Leg
F	Floor, Thigh, Leg	Torso, Foot
G	Floor, Foot	Torso, Thigh, Leg
H	Thigh, Leg	Floor, Torso, Foot

B.1 HOPPER

The Mujoco geom properties that we modified are attached to a particular body and determine its appearance and collision properties. For the Mujoco holdout transfer tests we pick a subset of the hopper 'geom' elements and scale the contact friction values by maximum friction coefficient, 1.3. Likewise, for the rest of the 'geom' elements, we scale the contact friction by the minimum value of 0.7. The body geoms and their names are visible in Fig. 6.

The exact combinations and the corresponding test name are indicated in Table 2 for Hopper.

B.2 CHEETAH

The Mujoco geom properties that we modified are attached to a particular body and determine its appearance and collision properties. For the Mujoco holdout transfer tests we pick a subset of the

Figure 7: Labelled Body Segments of Cheetah

Table 3: Cheetah Holdout Test Descriptions. Joints in the table receive the maximum friction coefficient of 0.9. Joints not indicated have friction coefficient 0.1

Test	Geom with Friction Coeff 0.9
A	Torso, Head, Fthigh
B	Floor, Head, Fshin
C	Bthigh, Bshin, Bfoot
D	Floor, Torso, Head
E	Floor, Bshin, Ffoot
F	Bthigh, Bfoot, Ffoot
G	Bthigh, Fthigh, Fshin
H	Head, Fshin, Ffoot

Figure 8: Labelled Body Segments of Ant

cheetah 'geom' elements and scale the contact friction values by maximum friction coefficient, 0.9. Likewise, for the rest of the 'geom' elements, we scale the contact friction by the minimum value of 0.1. The body geoms and their names are visible in Fig. 7.

The exact combinations and the corresponding test name are indicated in Table 4 for Hopper.

B.3 ANT

We will use torso to indicate the head piece, leg to refer to one of the four legs that contact the ground, and 'aux' to indicate the geom that connects the leg to the torso. Since the ant is symmetric we adopt a convention that two of the legs are front-left and front-right and two legs are back-left and back-right. Fig. 8 depicts the convention. For the Mujoco holdout transfer tests we pick a subset of the ant 'geom' elements and scale the contact friction values by maximum friction coefficient, 0.9. Likewise, for the rest of the 'geom' elements, we scale the contact friction by the minimum value of 0.1.

Table 4: Ant Holdout Test Descriptions. Joints in the table receive the maximum friction coefficient of 0.9. Joints not indicated have friction coefficient 0.1

Test	Geom with Friction Coeff 0.9
A	Front-Leg-Left, Aux-Front-Left, Aux-Back-Left
B	Torso, Aux-Front-Left, Back-Leg-Right
C	Front-Leg-Right, Aux-Front-Right, Back-Leg-Left
D	Torso, Front-Leg-Left, Aux-Front-Left
E	Front-Leg-Left, Aux-Front-Right, Aux-Back-Right
F	Front-Leg-Right, Back-Leg-Left, Aux-Back-Right
G	Front-Leg-Left, Aux-Back-Left, Back-Leg-Right
H	Aux-Front-Left, Back-Leg-Right, Aux-Back-Right

Test Name	0 Adv	1 Adv	3 Adv	Five Adv	Domain Rand
Test A	410 ± 140	1170 ± 570	$\mathbf{2210 \pm 630}$	2090 ± 920	1610 ± 310
Test B	430 ± 150	1160 ± 540	$\mathbf{2240 \pm 730}$	2200 ± 880	1610 ± 290
Test C	560 ± 120	490 ± 150	610 ± 250	580 ± 120	$\mathbf{1660 \pm 260}$
Test D	420 ± 150	1140 ± 560	$\mathbf{2220 \pm 680}$	2130 ± 890	1612 ± 360
Test E	550 ± 120	500 ± 150	600 ± 240	590 ± 120	$\mathbf{1680 \pm 280}$
Test F	420 ± 150	1200 ± 620	2080 ± 750	$\mathbf{2160 \pm 890}$	1650 ± 360
Test H	560 ± 130	500 ± 140	600 ± 230	600 ± 140	$\mathbf{1710 \pm 370}$
Test G	420 ± 150	1160 ± 590	$\mathbf{2210 \pm 680}$	2160 ± 920	1560 ± 340

Table 5: Results on holdout tests for each of the tested approaches for Hopper. Bolded values have the highest mean

Test Name	0 Adv	1 Adv	3 Adv	Five Adv	Domain Rand
Test A	4400 ± 2160	5110 ± 730	4960 ± 1280	$\mathbf{5560 \pm 1060}$	2800 ± 1540
Test B	6020 ± 880	5980 ± 290	6440 ± 1620	$\mathbf{6880 \pm 1090}$	3340 ± 600
Test C	5880 ± 1030	5730 ± 640	$\mathbf{6740 \pm 1190}$	6410 ± 790	4280 ± 240
Test D	5990 ± 940	5960 ± 260	6430 ± 1610	$\mathbf{6880 \pm 1090}$	3360 ± 570
Test E	5570 ± 570	5670 ± 290	5800 ± 1316	$\mathbf{6530 \pm 1250}$	3720 ± 540
Test F	5870 ± 750	5800 ± 350	6500 ± 1100	$\mathbf{6770 \pm 1070}$	3810 ± 330
Test H	5310 ± 1060	5270 ± 700	5610 ± 720	$\mathbf{5660 \pm 980}$	4560 ± 560
Test G	5710 ± 650	5790 ± 300	5890 ± 1240	$\mathbf{6560 \pm 1240}$	3380 ± 720

Table 6: Results on holdout tests for each of the tested approaches for Half Cheetah. Bolded values have the highest mean

The exact combinations and the corresponding test name are indicated in Table 4 for Hopper.

C RESULTS

Here we recompute the values of all the results and display them with appropriate standard deviations in tabular form.

There was not space for the ant validation set results so they are reproduced here.

D COST AND HYPERPARAMETERS

Here we reproduce the hyperparameters we used in each experiment and compute the expected runtime and cost of each experiment. Numbers indicated in {} were each used for one run. Otherwise the parameter was kept fixed at the indicated value.

D.1 HYPERPARAMETERS

For Mujoco the hyperparameters are:

Test Name	0 Adv	1 Adv	3 Adv	Five Adv	Domain Rand
Test A	590 ± 650	730 ± 630	600 ± 440	560 ± 580	$\mathbf{900 \pm 580}$
Test B	5240 ± 280	5530 ± 200	5770 ± 100	5710 ± 180	$\mathbf{6150 \pm 180}$
Test C	750 ± 820	1090 ± 660	1160 ± 540	1040 ± 760	$\mathbf{1370 \pm 800}$
Test D	5220 ± 300	5560 ± 220	5770 ± 90	5660 ± 190	$\mathbf{6120 \pm 180}$
Test E	5270 ± 290	5570 ± 210	5770 ± 100	5660 ± 220	$\mathbf{6140 \pm 150}$
Test F	780 ± 860	1160 ± 570	1120 ± 580	1140 ± 870	$\mathbf{1390 \pm 750}$
Test H	130 ± 290	420 ± 300	210 ± 220	160 ± 270	$\mathbf{700 \pm 560}$
Test G	5290 ± 280	5560 ± 220	5770 ± 100	5700 ± 190	$\mathbf{6150 \pm 160}$

Table 7: Results on holdout tests for each of the tested approaches for Ant. Bolded values have the highest mean

Figure 9: Ant Heatmap: Average reward across 10 seeds on each validation set (mass, friction) parametrization.

- Learning rate:
  - $\{.0003, .0005\}$ for half cheetah
  - $\{.0005, .00005\}$ for hopper and ant
- Generalized Advantage Estimation λ
  - $\{0.9, 0.95, 1.0\}$ for half cheetah
  - $\{0.5, 0.9, 1.0\}$ for hopper and ant
- Discount factor $\gamma = 0.995$
- Training batch size: 100000
- SGD minibatch size: 640
- Number of SGD steps per iteration: 10
- Number of iterations: 700
- We set the seed to 0 for all hyperparameter runs.
- The maximum horizon is 1000 steps.

For the validation across seeds we used 10 seeds ranging from 0 to 9. All other hyperparameters are the default values in RLlib Liang et al. (2017) 0.8.0

D.2 COST

For all of our experiments we used AWS EC2 c4.8xlarge instances which come with 36 virtual CPUs. For the Mujoco experiments, we use 2 nodes and 11 CPUs per hyper-parameter, leading to one full hyper-parameter sweep fitting onto the 72 CPUs. We run the following set of experiments and ablations, each of which takes 8 hours.

- 0 adversaries
- 1 adversary
- 3 adversaries
- 5 adversaries
- Domain randomization

for a total of 5 experiments for each of Hopper, Cheetah, Ant. For the best hyperparameters and each experiment listed above we run a seed search with 6 CPUs used per-seed, a process which takes about 12 hours. This leads to a total of $2*8*5*3 + 2*12*3*5 = 600$ node hours and $36*600 \approx 22000$ CPU hours. At a cost of ≈ 0.3 dollars per node per hour for EC2 spot instances, this gives ≈ 180 dollars to fully reproduce our results for this experiment. If the chosen hyperparameters are used and only the seeds are sweep, this is ≈ 100 dollars.

D.3 CODE

Our code is available at **ANONYMIZED**. For our reinforcement learning code-base we used RLlib Liang et al. (2017) version 0.8.0 and did not make any custom modifications to the library.

E PURE NASH EQUILIBRIA DO NOT NECESSARILY EXIST

While there are canonical examples of games in which pure Nash equilibria do not exist such as rock-paper-scissors, we are not aware one for sequential games with continuous actions. Tessler et al. (2019) contains an example of a simple, horizon 1 MDP where duality is not satisfied. The pure minimax solution does not equal the value of the pure maximin solution and a greater value can be achieved by randomizing one of the policies showing that there is no pure equilibrium.