On Effective Entropy Regularization for Large Reasoning Models

Abstract

Reinforcement learning with verifiable rewards (RLVR) has shown great promise in enhancing the reasoning abilities of large reasoning models (LRMs). However, it remains prone to entropy collapse and premature convergence. While naive entropy regularization is a standard remedy for exploration in traditional RL, we find it ineffective for LRMs. Our analysis shows that the failure stems from gradient imbalance and accumulation inherent in vast action spaces and long reasoning trajectories, which easily trigger global entropy explosion when exploration is unconstrained. To address this, we propose *SIREN* (**S**elect**I**ve ent**R**opy r**E**gularizatio**N**), a method that confines exploration to a meaningful subset of actions and states. *SIREN* achieves this through a two-step entropy masking mechanism, consisting of a top-p mask and a peak-entropy mask. Additionally, regularization is reformulated into a self-anchored form to stabilize training. Experiments across five mathematical benchmarks show that SIREN outperforms previous entropy-aware RLVR approaches, achieving, for example, a +6.6 maj@k improvement on AIME24/25 with Qwen2.5-Math-7B. Further analysis confirm that SIREN promotes greater response diversity, maintains entropy at an effective level, and preserves validation pass@k throughout training. This effectively mitigates the premature convergence problem common in RLVR for LRMs.

1 Introduction

Reinforcement learning with verifier rewards (RLVR) has become a promising method for enhancing large reasoning models (LRMs) by integrating reward modeling with automated verification. This technique has been shown to substantially improve complex reasoning abilities in domains such as mathematics and code (DeepSeek-AI, 2025; Team et al., 2025; Yang et al., 2025). Despite its success, a critical limitation has emerged in practice: entropy collapse and premature convergence (Yu et al., 2025; Cui et al., 2025). This issue causes the policy to become deterministic at an early stage, leading responses to collapse into near-identical outputs, and ultimately reducing both training efficiency in later stages and overall performance.

A common and intuitive solution to mitigate this issue is to incorporate entropy regularization to encourage exploration (Ziebart, 2010; Haarnoja et al., 2018a,c). In the context of LRMs, naive entropy regularization exhibits strong hyperparameter sensitivity and limited efficiency: a small coefficient yields minimal performance gains, while a large coefficient triggers a rapid entropy explosion(Cui et al., 2025). To better understand this behavior, we conduct a preliminary experiment. By analyzing probability distributions and the generated tokens from both an original model and one that experienced an entropy explosion under strong entropy regularization, we observe two key phenomena: (1) In the entropy-exploded model, the probability distribution becomes nearly uniform over the whole vocabulary, whereas in the original model, probability mass concentrates on a small, semantically meaningful subset. (2) In the entropy-exploded model, entropy remains uniformly high across almost all token positions, whereas in the original model, only a small fraction of tokens exhibit high entropy. Taken together, these phenomena suggest that the vast action space of LRMs makes it easy to increase the entropy by diffusing the probability mass across many low-utility tokens. The autoregressive generation process then propagates this uncertainty forward, causing the accumulated entropy bonus to scale with sequence length and ultimately trigger an explosion.

Based on these findings, we propose **S**elect**I**ve ent**R**opy r**E**gularizatio**N** (*SIREN*), a novel method that restricts exploration to a more effective subset of actions and states. *SIREN* consists of a two-step

masking mechanism to identify exploration targets precisely: (1) a *top-p mask*, which limits exploration to semantically meaningful subsets within the large action space of LRMs; and (2) a *peak-entropy mask*, which limits exploration on several logically critical tokens along long trajectories. Furthermore, to calibrate the regularization strength and stabilize training, we reformulate the naive regularization as *self-anchored regularization*, which helps control the overall entropy level during training.

To evaluate *SIREN*'s performance, we conduct a comprehensive evaluation across multiple backbones and mathematical reasoning benchmarks. Our method achieves significantly improved performance on Qwen2.5-Math-7B, with a maj@k of **54.6** and an avg@k of **46.1**. Compared to other baselines that also incorporate entropy, *SIREN* improves the maj@k by **+4.2**. *SIREN* also attains higher maj@k and avg@k on the smaller model Qwen2.5-Math-1.5B and the comparatively weaker model LLaMa3.1-8B. Through an analysis of pass@k and perplexity, which are commonly used to estimate the upper bound of reasoning and the uncertainty of generation (Holtzman et al., 2019; Yue et al., 2025; Cheng et al., 2025), we observe that *SIREN* yields more diverse responses and explores a wider scope, pushing the boundary of reasoning. In addition, the joint dynamics of entropy and validation pass@k during training indicate that *SIREN* performs effective, progressive exploration: it maintains high entropy in early stages and gradually converges later, ensuring sustained exploration while preventing degradation in validation pass@k.

In summary, the key contributions of this work are as follows.

- We analyze the limitations of naive entropy regularization in RLVR, showing that *the vast action space and long trajectories* flatten probability distributions across most positions. This highlights the need to control the effective scope of regularization.(Sec. 2)
- We propose *SIREN*, a novel method that selects exploration scopes at both the action and the trajectory levels for effective entropy regularization, while transforming the naive regularization into a self-anchored form to stabilize training.(Sec. 3)
- We achieve competitive results on mathematical benchmarks, showing consistent improvements over other entropy-related baselines on maj@k and avg@k.(Sec. 4)

2 Preliminary Analysis

2.1 Inefficiency of Naive Entropy Regularization

To address the core challenge of effective exploration in traditional RL, entropy regularization is widely adopted to encourage policy diversity and promote broader state exploration (Haarnoja et al., 2018b,c; Liu et al., 2020). Formally, given a query q, the entropy of the current policy π_θ at each token position v_j is defined as:

$$\mathcal{H}_j = -\sum_{v \in \mathcal{V}} \pi_\theta(v \mid q, v_{<j}) \log \pi_\theta(v \mid q, v_{<j}). \tag{1}$$

where $\mathcal{V}$ denotes the vocabulary. The corresponding training objective is:

$$J = J_{PO} + \beta \frac{1}{|o|} \sum_{j=1}^{|o|} \mathcal{H}_j, \tag{2}$$

in which J_{PO} represents the policy optimization objective, β is the entropy coefficient that controls the regularization strength, and o denotes a trajectory.

However, such naive entropy regularization performs poorly in the RLVR for LRMs, being highly sensitive to the entropy coefficient and prone to entropy collapse (Cui et al., 2025).

An intuitive explanation stems from the gradient behavior of the entropy term. The gradient of the token-level entropy $\mathcal{H}_t$ with respect to the pre-softmax logit $z_t(v)$ is:

$$\frac{\partial \mathcal{H}_t}{\partial z_t(v)} = (-1 - \log p_t(v)) \frac{\partial p_t(v)}{\partial z_t(v)}. \tag{3}$$

For LRMs, the action space is defined over a vocabulary of hundreds of thousands of tokens, where a considerable fraction carries little semantic relevance and receives near-zero probability $p_t(v)$. Based on Eq. 3, these tokens produce significantly larger gradients than meaningful ones, thereby dominating the update direction and causing unstable training dynamics.

There exists a fundamental trade-off in applying naive entropy regularization to LRMs when selecting a proper β: A large β causes the entropy term to dominate the objective (Eq. 2), prompting the optimization to flatten the distribution across the vocabulary and often leading to entropy explosion. Conversely, a sufficiently small β reduces

the entropy gradients for high-probability tokens to negligible levels, making the regularization ineffective for encouraging meaningful exploration. Complete theoretical derivations are provided in Appendix B.

2.2 Observations on the Failure Modes

Based on the preceding gradient analysis, we empirically examine naive entropy regularization in RLVR for LRMs. We train Qwen2.5-Math-7B with an entropy coefficient of 0.005 (slightly above the stable value of 0.001), keeping all other settings consistent with Sec. 4.1. An entropy explosion occurs at step 40, and we use this checkpoint for analysis. By visualizing token distributions and generated outputs on a representative AIME24 question (Li et al., 2024) (Fig. 1), we illustrate the model's behavior in action space and across trajectories (see Appendix G for more cases).

Our experiments reveal two recurring failure modes stemming from the distinctive nature of LRMs: an extremely large discrete action space and long-horizon autoregressive trajectories.

Flattened Token Distributions in Large Action Spaces. We first examine how entropy regularization affects token-level action distributions in LRMs. Figure 1(a) compares the first-token distributions before and after RL. Before RL, semantically meaningful tokens concentrate most of the probability mass, while the majority of tokens remain near zero. After RL, the distribution becomes nearly uniform, with many meaningless tokens rising to the top ranks. This validates our analysis: low-probability tokens dominate the gradient, pushing Eq. 1 toward its maximum and biasing the model toward excessive entropy.

Policy Nucleus. Motivated by this observation, we introduce the concept of a policy nucleus to constrain exploration. The policy nucleus is defined as a subset of the vocabulary containing the most semantically important tokens—those likely to generate coherent and reasonable responses. Since these tokens consistently rank at the top of the original model's distribution, we adopt the terminology of Top-p sampling (Holtzman et al., 2019) and refer to this subset as the nucleus. Our key insight is that **exploration should be concentrated within the policy nucleus rather than uniformly across the entire vocabulary**, offering a principled solution to the challenges posed by the vast action space of LRMs.

Cascaded Uncertainty along Long Trajectories.

We next investigate how entropy regularization interacts with the long-horizon autoregressive generation in LRMs. As shown in Fig. 1(b), before RL the model produces coherent reasoning steps with relatively low average token-level entropy. After RL, however, the output degenerates into largely meaningless token sequences, accompanied by a sharp rise in average entropy. Token-level entropy heatmaps further reveal that after RL, nearly all positions show uniformly high entropy, reflecting indiscriminate exploration. This suggests that the autoregressive process can turn early entropy spikes into a "chain reaction": uncertainty begets uncertainty, and as sequence length grows, the likelihood of such cascades increases, making entropy explosions more probable.

In contrast, the original model shows varied entropy across positions. Consistent with prior studies (Cui et al., 2025; Cheng et al., 2025; Wang et al., 2025), we observe that a small fraction of high-entropy tokens serve logical roles in guiding the reasoning process, such as *To, Once, Then*, while most tokens, which primarily fill sentences, exhibit much lower entropy. This indicates that **token-level entropy can help identify critical tokens, enabling selective and targeted regularization**, which may prevent cascade-induced instability in long LRM trajectories.

3 Selective Entropy Regularization

Building on our preliminary analysis (Sec. 2), we present *SIREN* (SelectIve entRopy rEgularizatioN), a method designed to prevent entropy explosion in large action spaces and long reasoning trajectories through targeted regularization. *SIREN* operates via a two-stage masking strategy: a *top-p mask* that restricts exploration to the policy nucleus, while a *peak-entropy mask* restricts entropy application to critical tokens (Sec. 3.2). Furthermore, *SIREN* introduces a self-anchored regularization term that dynamically adjusts regularization strength, significantly improving training stability (Sec. 3.3). The overall framework is depicted in Figure 2.

3.1 Preliminary

RLVR assigns binary rewards by comparing the extracted final answer with ground truth. We build on Dr.GRPO (Liu et al., 2025), a variant of GRPO (Shao et al., 2024) for RLVR. Compared with GRPO, Dr.GRPO removes the standard-deviation normalization in the group-relative ad-

Questions: Let p be the least prime number for which there exists a positive integer n such that $n^4 + 1$ is divisible by p^2. Find the least positive integer m such that $m^4 + 1$ is divisible by p^2.

(a) Probability distribution

Before RL   Average Entropy: 0.22

To solve this problem , we need to find the smallest prime number \(p \) such that there exists a positive integer \(n \) for which \(n ^ 4 + 1 \) is divisible by \(p ^ 2 \). Once we find \(p \), we need to find

0.0   5.0

After RL   Average Entropy: 11.33

`s s hurd rte disg `s ` f a `s idious `s e \`\`\t `t `` s` a` \`\` o `` \ \\` = `` \\`\\```` \\`\\` \\`a \\`\`` -\`\`\`\`\`\`\` -`, \`\ \\` = \`\\=\`\`\` \\`-, \`\`\```` \`\` -\`\>\`\`\`\`\`\`. \`\`\`\`

10.9   11.7

(b) Generated tokens with corresponding entropy visualization

Figure 1: Comparison of the first token's probability distributions and generated tokens before and after RL with naive entropy regularization (entropy coefficient set to 0.005).

(a) Naive Entropy Regularization   (b) SIREN

Figure 2: The pipeline of *SIREN* compared to naive entropy regularization. (a) Naive entropy regularization computes entropy over the entire vocabulary and maximizes it uniformly across all tokens, which often leads to excessive exploration in LRMs. (b) *SIREN* introduces selective entropy regularization, including: (i) a *top-p mask* that restricts entropy computation to the policy nucleus, (ii) a *peak-entropy* token mask that identifies the most informative tokens, and (iii) a *self-anchored form of regularization* that maintains the entropy magnitude close to its initial level. Together, these components enable more targeted exploration and improved training stability.

vantage, which empirically yields stronger performance and shorter responses.

For each query q, Dr.GRPO samples a group of outputs $\{o_i\}_{i=1}^{G}$ and defines $\hat{A}_i^{\text{Dr}} = R(o_i) - \text{mean}(\{R(o_j)\}_{j=1}^{G})$. The training objective is

$$J_{\text{Dr}}(\theta) = \mathbb{E}_{q \sim \mathcal{P}(Q), \{o_i\}_{i=1}^{G} \sim \pi_{\theta_{\text{old}}}(O|q)} \left[\frac{1}{G} \sum_{i=1}^{G} \right.$$
$$\left. \text{CLIP}(r_i(\theta), \hat{A}_i^{Dr}) - \beta D_{\text{KL}}(\pi_\theta \| \pi_{\text{ref}}) \right], \quad (4)$$

We take Dr.GRPO as the optimization backbone and augment it with selective entropy regularization.

3.2 Selective Two-step Entropy Masking

We first apply top-p masking to recompute entropy within the policy nucleus for each token, and then apply peak-entropy token masking to identify critical tokens. For regularization, the entropy and

gradients are computed only on these selected candidates and tokens.

Top-p Mask within a Token. Since LRMs have an extremely large action space, exploration over the entire space often assigns high probability to meaningless tokens, leading to incoherent outputs. To address this, we introduce a *top-p mask* to constrain exploration within the policy nucleus, i.e., the subset of meaningful tokens that are worth exploring. A visualization is shown in the yellow region on the left side of Figure 2(b). Formally, the policy nucleus is defined as:

$$\mathcal{V}_j^{(p)} = \arg\min_{\mathcal{S} \subseteq \mathcal{V}} |\mathcal{S}| \; s.t. \sum_{v \in \mathcal{S}} P(v \mid v_{<j}) \geq p, \quad (5)$$

where $\mathcal{V}$ denotes the original vocabulary, and $P(v \mid v_{<j})$ is the probability of token v_j.

The top-p mask and the corresponding recomputed entropy are then defined as:

$$M_j^{\text{top-p}}(v) = \begin{cases} 1, & v \in \mathcal{V}_j^{(p)} \\ 0, & \text{otherwise,} \end{cases} \quad (6)$$

$$P'(v \mid v_{<j}) = \frac{M_j^{\text{top-p}}(v)\, P(v \mid v_{<j})}{\sum_{u \in \mathcal{V}} M_j^{\text{top-p}}(u)\, P(u \mid v_{<j})}, \quad (7)$$

$$\mathcal{H}'_j = -\sum_{v \in V} P'(v \mid v_{<j}) \log P'(v \mid v_{<j}). \quad (8)$$

Peak-Entropy Mask for a Trajectory. Similarly, as analyzed in Sec.2, for long trajectories in LRMs, uncertainty accumulates exponentially, eventually causing entropy to explode at every token position, as exemplified in the right part of Figure1(b). Only a small subset of tokens plays a disproportionately important role in exploration, typically corresponding to sentence heads or logical connectors that determine the reasoning direction, while most other tokens serve as semantic fillers. Consistent with prior observations (Cheng et al., 2025; Wang et al., 2025; Cui et al., 2025), we find that such critical tokens tend to exhibit relatively high entropy. To focus on regularization on these tokens, we introduce a *peak-entropy mask*, which selects tokens whose entropy lies in the top τ-quantile within a trajectory. Concretely, for the i-th trajectory o_i in a batch, we define the τ-quantile of the token-level entropy, computed from the recomputed entropy $\mathcal{H}'$ in Eq. 8, as:

$$q_\tau^{(i)} = \text{Quantile}_\tau \left\{ \mathcal{H}'(v_1^{(i)}), \ldots, \mathcal{H}'(v_{|o_i|}^{(i)}) \right\}, \quad (9)$$

and construct the peak-entropy mask $\mathbf{m}_j^{\text{peak}}$ by retaining tokens above the τ-quantile of entropy:

$$\mathbf{m}_j^{\text{peak}} = \begin{cases} 1, & \text{if } \mathcal{H}'(v_j) \geq q_\tau^{(i)}, \\ 0, & \text{otherwise.} \end{cases} \quad (10)$$

Finally, the entropy $\overline{\mathcal{H}}$ is aggregated over all trajectories within a batch as shown in Eq. 11, where G is the number of trajectories in the batch.

$$\overline{\mathcal{H}} = \frac{1}{\sum_{i=1}^{G} \sum_{j=1}^{|o_i|} \mathbf{m}_j^{peak}} \sum_{i=1}^{G} \sum_{j=1}^{|o_i|} \mathbf{m}_j^{\text{peak}} \cdot \mathcal{H}'(v_j^{(i)}). \quad (11)$$

3.3 Self-Anchored Regularization

The naive objective of entropy regularization, which generally aims to maximize entropy (Haarnoja et al., 2018b; Liu et al., 2020), can easily fall into two extremes in the context of LRMs: either excessively high, leading to global

explosion and incoherent outputs, or too low, failing to mitigate premature convergence of the policy. To address this issue and keep the policy's entropy at an appropriate level, we modify the objective into a self-anchored regularization. It is defined as the mean squared error (MSE) between the aggregated entropy $\overline{\mathcal{H}}$ (computed as in Eq. 11) and an entropy anchor $\mathcal{H}_a$:

$$L_{sa} = \left(\overline{\mathcal{H}} - \mathcal{H}_a \right)^2. \quad (12)$$

Accordingly, the new training objective is formulated as $J' = J_{PO} - \beta L_{sa}$. Instead of introducing an external hyperparameter for the entropy anchor $\mathcal{H}_a$, we initialize it using the aggregated entropy $\overline{\mathcal{H}}$ at the initial step (Eq. 11), which is why we term it *self-anchored*. This initialization is model- and dataset-specific, reflecting the inherent uncertainty of the pre-trained policy before accuracy-driven RL fine-tuning. At this stage, the model typically produces more diverse outputs with higher entropy, providing a natural and exploration-friendly starting point.

4 Experiment

4.1 Setup

Models. The main experiments and analysis are conducted on Qwen2.5-Math-7B (Yang et al., 2024). We further apply our method to the smaller Qwen2.5-Math-1.5B (Yang et al., 2024) and the comparatively weaker LLaMA3.1-8B (Dubey et al., 2024), with corresponding results discussed in Sec. 4.2.

Training. For Qwen models, we adopt the LUFFY (Yan et al., 2025) training configuration on OpenR1-Math-46k-8192 (Face). Following DAPO (Yu et al., 2025), we remove the KL loss and set the clip ratio to 0.28. For the weaker LLaMA3.1-8B, we use an easier training set constructed from OpenR1-Math-46k-8192, GSM8K (Cobbe et al., 2021), and MATH500 (Hendrycks et al., 2021). Full dataset construction, hyperparameters, rollout settings, and implementation details are provided in Appendix C.

Evaluation. We evaluate on five mathematical reasoning benchmarks: AIME24, AIME25, AMC (Li et al., 2024), OlympiadBench (He et al., 2024), and MATH500 (Hendrycks et al., 2021). Performance is measured by maj@k and avg@k, where maj@k uses majority voting over k samples Wang et al., 2022 and avg@k averages correctness across samples (Yu et al., 2025; Yan et al., 2025). We use

Table 1: Overall performance of Qwen2.5-Math-7B compared with Dr.GRPO, naive entropy regularization, and other RLVR methods that also incorporate entropy. All models are evaluated under a unified setting. Best results are denoted in **bold**, and the second-best results are underlined.

	AIME24		AIME25		AMC22		MATH500		Olympiad Bench		Average	
	Maj@32	*Avg@32*	*Maj@32*	*Avg@32*	*Maj@32*	*Avg@32*	*Maj@8*	*Avg@8*	*Maj@8*	*Avg@8*	*Maj.*	*Avg.*
Qwen2.5-Math-7B	30.0	11.0	13.3	3.8	60.2	29.8	70.8	46.4	25.3	15.4	39.9	21.3
Dr.GRPO	30.0	21.5	16.7	15.4	67.5	61.1	84.2	81.2	45.3	42.0	48.7	44.2
Naive Entropy Reg.	33.3	28.0	20.0	14.1	63.9	58.9	84.2	80.4	44.4	40.9	49.2	44.5
Dual Gradient Reg.	36.7	**30.2**	20.0	16.7	68.7	**63.7**	82.8	79.6	43.7	40.7	50.4	**46.2**
Clip-Cov	33.3	22.5	20.0	**18.1**	67.5	59.3	78.4	76.6	41.6	38.3	48.2	43.0
KL-Cov	36.7	26.7	16.7	15.1	66.3	60.2	84.0	79.6	44.0	40.9	49.5	44.5
Entropy Adv.	30.0	27.4	13.3	12.9	65.1	58.7	80.8	78.4	43.0	40.0	46.4	43.5
On Forking Tokens	36.7	24.0	20.0	13.9	62.7	57.2	84.6	81.1	45.0	40.9	49.8	43.3
SIREN (ours)	**43.3**	28.4	**26.7**	17.9	**71.1**	60.1	**85.0**	**81.9**	**46.8**	**42.5**	**54.6**	46.1

Figure 3: Average maj@k and avg@k across five mathematical benchmarks for *SIREN* on different backbones, including Qwen2.5-Math-1.5B and LLaMa3.1-8B (see Appendix E.1 for detailed results).

k=32 for AIME24, AIME25, and AMC, and k=8 for the remaining benchmarks. For each model, we report the checkpoint with the best validation accuracy; full evaluation details are given in Appendix C.

Baseline methods. We compare against *Dr.GRPO (Liu et al., 2025)*, *naive entropy regularization*, *Dual Gradient Regularization (Haarnoja et al., 2018c)*, *Clip-Cov / KL-Cov (Cui et al., 2025)*, *Entropy Advantage (Cheng et al., 2025)*, and *RL on forking tokens (Wang et al., 2025)*. Detailed baseline descriptions and implementation specifics are provided in Appendix C.2.

4.2 Main Results

SOTA performance on RLVR with Qwen2.5-Math-7B. Table 1 presents a comparative evaluation of the original Qwen2.5-Math-7B model, several baseline methods, and our proposed approach. *SIREN* yields substantial gains over the base model and achieves competitive or superior performance compared to strong RL baselines across benchmarks. Specifically, it achieves an average maj@k of **54.6**, outperforming the strongest baseline by **+4.2** points. In AIME24 and AIME25, the most challenging benchmarks, our method achieves a maj@32 score of **43.3** and **26.7**, re-

spectively, achieving consistent improvements of **+6.6** points over the best-performing baseline on both datasets. For the overall average avg@k, our method reaches **46.1**, surpassing previous approaches and setting a new record.

Extending to Other Models. To further verify the generalizability of our method, we extend *SIREN* to smaller and weaker models. The evaluation results are presented in Figure 3. On the smaller model Qwen2.5-math-1.5B and the weaker model LLaMA3.1-8B, *SIREN* consistently achieves the best maj@k and avg@k across five mathematical benchmarks, outperforming both Dr.GRPO and naive entropy regularization. *SIREN* improves maj@k by +2.4 on Qwen2.5-math-1.5B and +2.8 on LLaMA3.1-8B.

5 Analysis

We analyze how *SIREN* improves exploration in LRMs from both theoretical and empirical perspectives. Theoretically, its masking mechanism mitigates inefficiency and instability. Empirically, pass@k (Figure 4), perplexity (Figure 5), and training dynamics (Figure 6) show that *SIREN* expands the reasoning boundary, maintains higher diversity than naive baselines, and regulates exploration more effectively. We further conduct ablation and sensitivity studies to assess the contribution of each module and the impact of key hyperparameters.

5.1 Theoretical Grounding of *SIREN*

Naive entropy regularization in LRMs suffers from a fundamental trade-off: strong entropy bonuses lead to instability by amplifying noisy tail-token gradients, while weak bonuses provide little useful exploration. *SIREN* resolves this trade-off by restricting entropy regularization to the policy nucleus and high-uncertainty positions, yielding more localized and lower-variance gradients.

Figure 4: Pass@k performance of *SIREN* in comparison with various RLVR baselines, scaling with k.

Formal derivations and detailed analysis are provided in Appendix B.

5.2 *SIREN* Promotes Exploration

Pass@k Analysis. We adopt pass@k to examine the exploration boundaries of models trained with *SIREN*. Following prior work (Yue et al., 2025; Cheng et al., 2025; Wu et al., 2025), pass@k is widely recognized as an indicator of the upper bound of reasoning ability. We set k=256 for difficult yet small-scale benchmarks (AIME, AIME 2025), and k=128 for medium-level, larger benchmarks (AMC, OlympiadBench, MATH500). Results are shown in Figure 4. *SIREN* surpasses baseline methods across all benchmarks except AIME 2024, demonstrating its potential to expand the reasoning boundary. On AIME 2024, although pass@k is slightly lower than strong baselines, *SIREN* achieves higher maj@k and avg@k, as shown in Table 1. These results indicate that *SIREN* effectively balances exploration with exploitation, yielding higher-quality and more consistent answers across multiple trials.

Perplexity Analysis. Besides pass@k, the exploratory effects promoted by *SIREN* can also be verified using perplexity (PPL). Following Yue et al. (2025), PPL measures a model's ability to predict a response, with lower PPL indicating higher probability to generate response Y. Previous work (Yue et al., 2025) shows that RL reduces PPL, revealing a collapse in a smaller subset of responses and thus harming exploration. We quantitatively evaluated the original model's PPL of responses generated by the original model, Dr.GRPO, naive entropy regularization, and *SIREN*. For responses, we reused the outputs obtained during the evaluation phase. As shown in Fig. 5, *SIREN* consistently achieves higher PPL compared to baseline RL methods, suggesting that it effectively mitigates the convergence of responses and encourages exploration over a broader range of possible outputs.

5.3 *SIREN* Makes Exploration More Effective

We further study the training dynamics to understand why *SIREN* can promote exploration. We focus on two metrics closely related to exploration, namely entropy and validation pass@16, with the results shown in Figure 6. Dr.GRPO, Naive Reg (0.001), and *SIREN* (0.001) all exert little to no control over entropy, causing the policy to converge prematurely during the early stages of training. This lack of entropy regulation limits exploration of new states, leading to a decrease in validation pass@k. In contrast, Naive Reg (0.005) uses an excessively large entropy coefficient, resulting in rapid entropy explosion and poor performance. *SIREN* (0.005), however, maintains a substantial level of entropy during the early training stage, with a slight increase between steps 50–80, which encourages the generation of more diverse responses. As training progresses, the entropy gradually converges and eventually stabilizes at a higher level than the other baselines. By keeping entropy at an appropriate level throughout training, *SIREN* ensures continuous exploration, which is effectively converted into more correct responses and leads to improved validation pass@k. Comparison of *SIREN* with other baselines is provided in the Appendix F.2.

5.4 Ablation Study

Our method consists of three components: *the peak-entropy mask, the top-p mask,* and *the self-anchored regularization*. As shown in Table 2, removing any component degrades performance, with the largest drop caused by removing self-anchored regularization (-10.3 maj@k and -15.5 avg@k), indicating that it is critical for stabilizing entropy while preserving useful exploration. Using only self-anchored regularization still improves over naive entropy regularization but remains inferior to the full *SIREN* framework; detailed results are deferred to Appendix E.2.

Figure 5: Average perplexity of generated responses across all benchmarks, computed using the base model Qwen2.5-Math-7B.

Figure 6: Training dynamics of entropy (left) and pass@16 performance (right) under different regularization strategies.

Table 2: Abaltion results of *SIREN* on Qwen2.5-Math-7B.

	Maj.	*Avg.*
SIREN	**54.6**	**46.1**
w/o TopP Mask	49.2	43.1
w/o Peak-Entropy Mask	48.9	44.0
w/o Self-Anchored Reg.	44.3	30.6
w/ only Self-Anchored Reg.	52.3	43.6

Table 3: Sensitivity analysis of *SIREN* with respect to the top-p cutoff p and peak-entropy quantile τ.

	p = 0.8, τ=0.8	p = 0.7	p = 0.9	$\tau = 0.7$	$\tau = 0.75$	$\tau = 0.85$	$\tau = 0.9$
Avg.Maj	**54.6**	48.5	52.0	50.9	54.1	52.6	50.3
Avg.Avg	**46.1**	42.2	44.8	43.5	46.0	43.7	40.7

5.5 Sensitivity Analysis

Results (Table 3) show that raising the top-p cutoff only slightly harms performance, whereas lowering it to 0.7 causes a sharp drop. This occurs because an overly strict cutoff leaves too few tokens for effective entropy regularization. For τ, adjustments within ± 0.05 yield stable results; a decrease of 0.1 maintains acceptable avg@k, but an increase of 0.1 leads to a larger decline, likely because high quantiles filter out useful reasoning tokens. Overall, performance remains robust under reasonable hyperparameter variations, indicating that *SIREN* does not require precise tuning. The complete results are in Appendix E.3.

6 Related work

Reinforcement Learning for LLMs. Reinforcement learning has been a major technique for post-training large language models (LLMs) (Ouyang et al., 2022; Touvron et al., 2023; Rafailov et al., 2023). Recently, RLVR, which replaces the reward model with a verification function that compares the model's boxed answer against the ground truth, has demonstrated substantial potential for improving reasoning capabilities (Shao et al., 2024; DeepSeek-AI, 2025; Jaech et al., 2024; Team et al., 2025). This has attracted increasing attention from the research community, leading to a variety of subsequent improvements (Zeng et al., 2025; Hu et al., 2025; Yeo et al., 2025; Liu et al., 2025; Yu et al., 2025). Yet, despite its promise, RLVR still faces significant challenges such as entropy collapse and premature convergence, which severely restrict exploration and limit the performance.

Exploration in reinforcement learning. Effective exploration remains an important topic in reinforcement learning. One line of research incorporates intrinsic motivation or reward bonuses to construct auxiliary signals that incentivize agents to explore new states (Bellemare et al., 2016; Ostrovski et al., 2017; Pathak et al., 2017; Burda et al., 2018; Fortunato et al., 2019). Another line of work improves exploration by maximizing entropy, thereby introducing uncertainty into the policy to encourage more diverse behaviors (Ziebart, 2010; Haarnoja et al., 2017, 2018b,c). As an important signal for policy optimization, entropy has also been utilized in RLVR. Cui et al. (2025) investigates the empirical correlation between entropy and performance, and proposes clipping or KL-based mechanisms to indirectly control entropy. Meanwhile, Cheng et al. (2025); Zheng et al. (2025); Wang et al. (2025) treat entropy as a heuristic signal, using it for advantage shaping, enhancing the rollout phase, or loss masking. Unlike the aforementioned methods, which exploit entropy only indirectly or as an auxiliary signal, our method analyzes the failure of naive entropy regularization and directly extends it from traditional RL to RLVR for LRMs. This enables explicit and effective control of entropy, thereby directly promoting policy exploration.

7 Conclusion

This work revealed that entropy collapse in LRMs arises from uncontrolled exploration, amplified by vast action spaces and long trajectories. To address this, we introduced *SIREN*, which increases naive regularization with a two-step entropy mask and self-anchored regularization. Experiments and analysis demonstrated that *SIREN* not only stabilizes training but also drives richer reasoning, surpassing previous entropy-based methods. Our results underlined a central insight: LRMs require targeted and efficient exploration, providing a foundation for future advances in enhancing LRM exploration.

Limitations

We believe there is still room for improvement in our work. First, due to limited computational resources, we restrict our experiments to models with up to 8B parameters. Prior work (Wang et al., 2025) suggests that the benefits of enhanced exploration may be more pronounced in larger models, so evaluating *SIREN* at greater scales remains an important direction for future work. Second, the range of models considered in this study is relatively narrow. While we included both weaker and stronger baselines and extended our analysis to the Llama series, other categories are not covered, such as distilled models, instruction-tuned models. Finally, our evaluation is limited to the mathematical reasoning domain. We did not examine other RLVR scenarios, such as code generation or scientific reasoning, which may further highlight the generality of *SIREN*.

References

Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. 2016. Unifying count-based exploration and intrinsic motivation. *Advances in neural information processing systems*, 29.

Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. 2018. Exploration by random network distillation. *arXiv preprint arXiv:1810.12894*.

Daixuan Cheng, Shaohan Huang, Xuekai Zhu, Bo Dai, Wayne Xin Zhao, Zhenliang Zhang, and Furu Wei. 2025. Reasoning with exploration: An entropy perspective. *arXiv preprint arXiv:2506.14758*.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, and 1 others. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Ganqu Cui, Yuchen Zhang, Jiacheng Chen, Lifan Yuan, Zhi Wang, Yuxin Zuo, Haozhan Li, Yuchen Fan, Huayu Chen, Weize Chen, and 1 others. 2025. The entropy mechanism of reinforcement learning for reasoning language models. *arXiv preprint arXiv:2505.22617*.

DeepSeek-AI. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *Preprint*, arXiv:2501.12948.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The llama 3 herd of models. *arXiv e-prints*, pages arXiv–2407.

Hugging Face. Open r1: A fully open reproduction of deepseek-r1, january 2025. *URL https://github.com/huggingface/open-r1*, page 9.

Meire Fortunato, Mohammad Gheshlaghi Azar, Bilal Piot, Jacob Menick, Ian Osband, Alex Graves, Vlad Mnih, Remi Munos, Demis Hassabis, Olivier Pietquin, Charles Blundell, and Shane Legg. 2019. Noisy networks for exploration. *Preprint*, arXiv:1706.10295.

Tuomas Haarnoja, Haoran Tang, Pieter Abbeel, and Sergey Levine. 2017. Reinforcement learning with deep energy-based policies. In *International conference on machine learning*, pages 1352–1361. PMLR.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. 2018a. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pages 1861–1870. Pmlr.

Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. 2018b. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pages 1861–1870. Pmlr.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, and 1 others. 2018c. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*.

Chaoqun He, Renjie Luo, Yuzhuo Bai, Shengding Hu, Zhen Leng Thai, Junhao Shen, Jinyi Hu, Xu Han, Yujie Huang, Yuxiang Zhang, and 1 others. 2024. Olympiadbench: A challenging benchmark for promoting agi with olympiad-level bilingual multimodal scientific problems. *arXiv preprint arXiv:2402.14008*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*.

Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2019. The curious case of neural text degeneration. *arXiv preprint arXiv:1904.09751*.

Jingcheng Hu, Yinmin Zhang, Qi Han, Daxin Jiang, Xiangyu Zhang, and Heung-Yeung Shum. 2025. Open-reasoner-zero: An open source approach to scaling up reinforcement learning on the base model. *arXiv preprint arXiv:2503.24290*.

Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, and 1 others. 2024. Openai o1 system card. *arXiv preprint arXiv:2412.16720*.

Jia Li, Edward Beeching, Lewis Tunstall, Ben Lipkin, Roman Soletskyi, Shengyi Huang, Kashif Rasul, Longhui Yu, Albert Q Jiang, Ziju Shen, and 1 others. 2024. Numinamath: The largest public dataset in ai4maths with 860k pairs of competition math problems and solutions. *Hugging Face repository*, 13(9):9.

Zhuang Liu, Xuanlin Li, Bingyi Kang, and Trevor Darrell. 2020. Regularization matters in policy optimization-an empirical study on continuous control. In *International Conference on Learning Representations*.

Zichen Liu, Changyu Chen, Wenjun Li, Penghui Qi, Tianyu Pang, Chao Du, Wee Sun Lee, and Min Lin. 2025. Understanding r1-zero-like training: A critical perspective. *arXiv preprint arXiv:2503.20783*.

Georg Ostrovski, Marc G Bellemare, Aäron Oord, and Rémi Munos. 2017. Count-based exploration with neural density models. In *International conference on machine learning*, pages 2721–2730. PMLR.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. 2017. Curiosity-driven exploration by self-supervised prediction. In *International conference on machine learning*, pages 2778–2787. PMLR.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. 2025. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, pages 1279–1297.

Kimi Team, Angang Du, Bofei Gao, Bowei Xing, Changjiu Jiang, Cheng Chen, Cheng Li, Chenjun Xiao, Chenzhuang Du, Chonghua Liao, and 1 others. 2025. Kimi k1.5: Scaling reinforcement learning with llms. *arXiv preprint arXiv:2501.12599*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, and 1 others. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Shenzhi Wang, Le Yu, Chang Gao, Chujie Zheng, Shixuan Liu, Rui Lu, Kai Dang, Xionghui Chen, Jianxin Yang, Zhenru Zhang, and 1 others. 2025. Beyond the 80/20 rule: High-entropy minority tokens drive effective reinforcement learning for llm reasoning. *arXiv preprint arXiv:2506.01939*.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2022. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*.

Fang Wu, Weihao Xuan, Ximing Lu, Mingjie Liu, Yi Dong, Zaid Harchaoui, and Yejin Choi. 2025. The invisible leash: Why rlvr may or may not escape its origin. *arXiv preprint arXiv:2507.14843*.

Jianhao Yan, Yafu Li, Zican Hu, Zhi Wang, Ganqu Cui, Xiaoye Qu, Yu Cheng, and Yue Zhang. 2025. Learning to reason under off-policy guidance. *arXiv preprint arXiv:2504.14945*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

An Yang, Beichen Zhang, Binyuan Hui, Bofei Gao, Bowen Yu, Chengpeng Li, Dayiheng Liu, Jianhong Tu, Jingren Zhou, Junyang Lin, Keming Lu, Mingfeng Xue, Runji Lin, Tianyu Liu, Xingzhang Ren, and Zhenru Zhang. 2024. Qwen2.5-math technical report: Toward mathematical expert model via self-improvement. *arXiv preprint arXiv:2409.12122*.

Edward Yeo, Yuxuan Tong, Morry Niu, Graham Neubig, and Xiang Yue. 2025. Demystifying long chain-of-thought reasoning in llms. *arXiv preprint arXiv:2502.03373*.

Qiying Yu, Zheng Zhang, Ruofei Zhu, Yufeng Yuan, Xiaochen Zuo, Yu Yue, Weinan Dai, Tiantian Fan, Gaohong Liu, Lingjun Liu, and 1 others. 2025. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*.

Yang Yue, Zhiqi Chen, Rui Lu, Andrew Zhao, Zhaokai Wang, Shiji Song, and Gao Huang. 2025. Does reinforcement learning really incentivize reasoning capacity in llms beyond the base model? *arXiv preprint arXiv:2504.13837*.

Weihao Zeng, Yuzhen Huang, Qian Liu, Wei Liu, Keqing He, Zejun Ma, and Junxian He. 2025. Simplerl-zoo: Investigating and taming zero reinforcement learning for open base models in the wild. *arXiv preprint arXiv:2503.18892*.

Tianyu Zheng, Tianshun Xing, Qingshui Gu, Taoran Liang, Xingwei Qu, Xin Zhou, Yizhi Li, Zhoufutu Wen, Chenghua Lin, Wenhao Huang, and 1 others. 2025. First return, entropy-eliciting explore. *arXiv preprint arXiv:2507.07017*.

Brian D Ziebart. 2010. *Modeling purposeful adaptive behavior with the principle of maximum causal entropy*. Carnegie Mellon University.

A LLM Usage

During the preparation of this work, we used GPT-5 solely to improve the language. The LLMs served only as assistant tools and did not contribute to any intellectual or scientific aspect of the work. After using this tool, we carefully reviewed and edited all content and take full responsibility for the publication.

B Theoretical Analysis

In this section, we provide the theoretical grounding of *SIREN*'s masking mechanism. We first analyze why naive entropy regularization fails by examining its gradient structure and inherent instability, and how *SIREN* mitigates these issues. We then show that *SIREN* reduces entropy variance, leading to more stable and effective entropy optimization.

B.1 Gradient-Based Explanation

We analyze why naive entropy regularization is either **unstable** (entropy explosion) or **ineffective** (negligible exploration), and how *SIREN*'s two masks (a token-level top-p mask and a trajectory-level peak-entropy mask) simultaneously **bound entropy growth** and **concentrate exploration on meaningful actions and positions**.

B.1.1 Why Naive Entropy Regularization Fails in RLVR for LRM

Let $\mathcal{V}$ be the vocabulary with size $|\mathcal{V}| = V$, trajectory length T, and policy logits z_t at position t.

The naive entropy term at step t is

$$H_t(\theta) = -\sum_{v \in \mathcal{V}} p_t(v) \log p_t(v), \quad (13)$$

with gradient (up to the softmax Jacobian)

$$\frac{\partial H_t}{\partial z_t(v)} = -\big(1 + \log p_t(v)\big) \frac{\partial p_t(v)}{\partial z_t(v)}. \quad (14)$$

Head–Tail Decomposition For each step t, define:
- **Head (nucleus)** $\mathcal{V}_t^{\text{head}}$: smallest set of tokens with cumulative mass $\geq p$; size $K_t \leq K$.
- **Tail** $\mathcal{V}_t^{\text{tail}} = \mathcal{V} \setminus \mathcal{V}_t^{\text{head}}$.

Assumption 1 (matches behavior of pretrained LLMs). *There exist constants $c_{\text{head}}, c_{\text{tail}} > 0$ such that:*

$$\sum_{v \in \mathcal{V}_t^{\text{head}}} p_t(v) \geq c_{\text{head}}, \qquad p_t(v) \leq \frac{c_{\text{tail}}}{V - K_t} \quad \textit{for all } v \in \mathcal{V}_t^{\text{tail}}$$

Lemma 1 (Naive entropy gradient is dominated by tail coordinates). *Under Assumption 1, there exist constants $A_{\text{head}}, A_{\text{tail}} > 0$ such that:*

$$\sum_{v \in \mathcal{V}_t^{\text{head}}} \left\| \frac{\partial H_t}{\partial z_t(v)} \right\|^2 \leq A_{\text{head}} K_t, \quad (15)$$

$$\sum_{v \in \mathcal{V}_t^{\text{tail}}} \left\| \frac{\partial H_t}{\partial z_t(v)} \right\|^2 \geq A_{\text{tail}}(V - K_t) \log^2 V. \quad (16)$$

Thus, naive entropy focuses its gradient on *tail tokens*, which are semantically meaningless.

Explosion vs. Ineffectiveness Let reward be bounded by $|R(o)| \leq R_{\max}$. The naive objective is

$$J_{\text{naive}}(\theta) = \mathbb{E}[R(o)] + \beta \sum_{t=1}^{T} H_t(\theta). \quad (17)$$

- **Entropy explosion.** Entropy per step is at most $\log V$. Total entropy reward is at most $\beta T \log V$. If $\beta \log V \gg R_{\max}$, entropy dominates the reward and pushes the policy toward uniform, causing explosion, especially since T is large.
- **Ineffective exploration.** To avoid explosion, β must be small. But then the fraction of entropy-gradient energy on the head is at most $\frac{A_{\text{head}} K}{A_{\text{tail}}(V-K)\log^2 V}$, which becomes negligible for large V. Thus, *naive entropy barely changes head tokens* and yields almost no exploration.

B.1.2 Why *SIREN* Enables Stable and Effective Entropy Regularization

***SIREN*'s Token-Level Top-p Mask** *SIREN* replaces H_t with the **nucleus entropy**

$$H_t^{(p)} = -\sum_{v \in \mathcal{V}_t^{\text{head}}} p_t^{(p)}(v) \log p_t^{(p)}(v), \quad (18)$$

where $p_t^{(p)}$ renormalizes p_t over $\mathcal{V}_t^{\text{head}}$.

Then:

$$\frac{\partial H_t^{(p)}}{\partial z_t(v)} = \begin{cases} \text{entropy gradient}, & v \in \mathcal{V}_t^{\text{head}}, \\ 0, & v \in \mathcal{V}_t^{\text{tail}}. \end{cases}$$

Thus:

1. **Tail gets zero entropy gradient.** This removes the instability caused by pushing thousands of meaningless tail tokens.

2. **Entropy per step is bounded by $\log K$.**

$$H_t^{(p)} \leq \log K.$$

3. **Exploration on head tokens becomes strong and meaningful.** All entropy gradient is concentrated on $\leq K$ tokens. Therefore, for the same β, exploration on useful actions increases dramatically.

SIREN's Peak-Entropy Mask   Let

$$\mathcal{T}_{\text{peak}} = \{t : H_t^{(p)} \text{ in top-}\rho \text{ fraction}\}, \qquad |\mathcal{T}_{\text{peak}}| = \rho T.$$

SIREN applies entropy only at these steps:

$$J_{SIREN}^{\text{entropy}}(\theta) = \beta \sum_{t \in \mathcal{T}_{\text{peak}}} H_t^{(p)}(\theta). \qquad (19)$$

1. **Entropy cannot dominate reward.**

$$J_{SIREN}^{\text{entropy}} \leq \beta \rho T \log K.$$

2. **Stronger exploration at selected positions.** Naive entropy gives each step a scale $\sim \beta/T$; *SIREN* gives $\sim \beta/(\rho T)$ on selected steps. Local exploration signals are therefore amplified by $1/\rho$.

3. **Low-entropy positions contribute almost no useful exploration.**

   If entropy is small, say $H_t \leq H_{\text{low}}$, then most mass lies on a single token $v_t^\star$:

   $$p_t(v_t^\star) \geq 1 - \delta(H_{\text{low}}), \qquad \delta(H_{\text{low}}) \to 0.$$

   Then the naive entropy gradient satisfies

   $$\sum_{v \in \mathcal{V}} \left\| \beta \frac{\partial H_t}{\partial z_t(v)} \right\|^2 \leq C\beta^2 \delta(H_{\text{low}}),$$

   which is negligible for a safe small β.

Thus, naive entropy has almost no effect at low-entropy positions. *SIREN* simply removes them, losing nothing while reducing instability.

B.2   Variance Reduction Advantages of *SIREN*

In this section we show that *SIREN* yields *lower-variance* entropy gradients than naive entropy regularization for the same coefficient β, in the large-vocabulary regime.

Let $g_{\text{naive}}(\theta; o)$ and $g_{\text{SIREN}}(\theta; o)$ denote the entropy-gradient contributions to the policy gradient for a single rollout o, under naive entropy and *SIREN* respectively. We focus on their variance over trajectories $o \sim \pi_\theta$:

$$\text{Var}[g] := \mathbb{E}\big[\|g - \mathbb{E}g\|^2\big] = \mathbb{E}\big[\|g\|^2\big] - \|\mathbb{E}g\|^2.$$

B.2.1   Per-step squared norms

Recall from the previous lemmas that at each step t:

$$\|g_t^{\text{naive}}\|^2 = \beta^2 \sum_{v \in \mathcal{V}} \left\| \frac{\partial H_t}{\partial z_t(v)} \right\|^2 \qquad (20)$$

$$\geq \beta^2 A_{\text{tail}}(V - K_t) \log^2 V, \qquad (21)$$

$$\|g_t^{\text{SIREN}}\|^2 = \beta^2 \sum_{v \in \mathcal{V}_t^{\text{head}}} \left\| \frac{\partial H_t^{(p)}}{\partial z_t(v)} \right\|^2 \qquad (22)$$

$$\leq \beta^2 B_{\text{head}} K_t, \qquad (23)$$

for constants $A_{\text{tail}}, B_{\text{head}} > 0$ independent of V and T. In particular, $g_t^{\text{SIREN}}(v) = 0$ for all $v \in \mathcal{V}_t^{\text{tail}}$.

We write the trajectory-level entropy gradients approximately as

$$g_{\text{naive}}(\theta; o) \approx \sum_{t=1}^{T} g_t^{\text{naive}}(\theta; o),$$

$$g_{\text{SIREN}}(\theta; o) \approx \sum_{t \in \mathcal{T}_{\text{peak}}(o)} g_t^{\text{SIREN}}(\theta; o),$$

where $\mathcal{T}_{\text{peak}}(o)$ is the set of peak-entropy positions for trajectory o, with $|\mathcal{T}_{\text{peak}}(o)| = \rho T$.

We make a mild aggregation assumption that per-step entropy gradients are not perfectly canceling.

Assumption 2 (Weak temporal correlation). *There exist constants $c_1, c_2 > 0$ (independent of V, T) such that*

$$\mathbb{E}\big[\|g_{\text{naive}}\|^2\big] \geq c_1 \sum_{t=1}^{T} \mathbb{E}\big[\|g_t^{\text{naive}}\|^2\big], \qquad (24)$$

$$\mathbb{E}\big[\|g_{\text{SIREN}}\|^2\big] \leq c_2 \sum_{t \in \mathcal{T}_{\text{peak}}} \mathbb{E}\big[\|g_t^{\text{SIREN}}\|^2\big]. \qquad (25)$$

This simply requires that cross-terms in $\mathbb{E}\|\sum_t g_t\|^2$ do not systematically cancel the per-step squared norms.

Using (21)–(23) and Assumption 2, and noting that $K_t \leq K$ and $V - K_t \geq V - K$, we obtain

$$\mathbb{E}\big[\|g_{\text{naive}}\|^2\big] \geq c_1 \sum_{t=1}^{T} \beta^2 A_{\text{tail}}(V - K_t) \log^2 V \qquad (26)$$

$$\geq c_1 \beta^2 A_{\text{tail}} T (V - K) \log^2 V, \qquad (27)$$

$$\mathbb{E}\big[\|g_{\text{SIREN}}\|^2\big] \leq c_2 \sum_{t \in \mathcal{T}_{\text{peak}}} \beta^2 B_{\text{head}} K_t \qquad (28)$$

$$\leq c_2 \beta^2 B_{\text{head}} \rho T K. \qquad (29)$$

For large vocabulary V and modest nucleus size $K \ll V$, the ratio of second moments satisfies

$$\frac{\mathbb{E}\big[\|g_{\text{naive}}\|^2\big]}{\mathbb{E}\big[\|g_{\text{SIREN}}\|^2\big]} \geq \frac{c_1 A_{\text{tail}}}{c_2 B_{\text{head}}} \cdot \frac{V-K}{\rho K} \cdot \log^2 V, \tag{30}$$

which grows without bound as $V \to \infty$.

B.2.2 From second moment to variance

We now relate the second moments to the variances.

Assumption 3 (Bounded mean gradient). *There exists $M > 0$, independent of V and T, such that*

$$\big\|\mathbb{E}[g_{\text{naive}}]\big\| \leq M, \qquad \big\|\mathbb{E}[g_{\text{SIREN}}]\big\| \leq M.$$

This simply states that the expected entropy gradient (the bias term) does not grow with vocabulary size; it is controlled by the scale of the loss and clipping.

Using the identity $\text{Var}[g] = \mathbb{E}\big[\|g\|^2\big] - \|\mathbb{E}g\|^2$ and Assumption 3, we obtain

$$\text{Var}[g_{\text{naive}}] = \mathbb{E}\big[\|g_{\text{naive}}\|^2\big] - \big\|\mathbb{E}[g_{\text{naive}}]\big\|^2 \tag{31}$$

$$\geq \mathbb{E}\big[\|g_{\text{naive}}\|^2\big] - M^2, \tag{32}$$

$$\text{Var}[g_{\text{SIREN}}] = \mathbb{E}\big[\|g_{\text{SIREN}}\|^2\big] - \big\|\mathbb{E}[g_{\text{SIREN}}]\big\|^2 \tag{33}$$

$$\leq \mathbb{E}\big[\|g_{\text{SIREN}}\|^2\big]. \tag{34}$$

Combining with (27)–(29), for sufficiently large V we can choose a constant $C' > 1$ such that

$$\mathbb{E}\big[\|g_{\text{naive}}\|^2\big] - M^2 \geq C' \mathbb{E}\big[\|g_{\text{SIREN}}\|^2\big]. \tag{35}$$

Therefore,

$$\text{Var}[g_{\text{naive}}] \geq C' \mathbb{E}\big[\|g_{\text{SIREN}}\|^2\big] \geq C' \text{Var}[g_{\text{SIREN}}], \tag{36}$$

i.e., the variance of the entropy gradient under naive entropy regularization is asymptotically larger than under SIREN, by at least a constant factor that itself grows with vocabulary size.

Conclusion. In the large-vocabulary, long-horizon regime, naive entropy regularization yields an entropy-gradient estimator with substantially higher variance than SIREN: noisy tail-token contributions at all timesteps inflate $\mathbb{E}\|g_{\text{naive}}\|^2$, while SIREN's top-$p$ and peak-entropy masks remove most of these noise sources and keep the entropy gradient localized and low-variance.

C Experimental Details

C.1 Detailed Setup

Code Implementation Our implementation is based on verl (Sheng et al., 2025)[1], with modifications to the entropy calculation, entropy aggregation, and objective computation in the RL algorithm. We employ vLLM[2] as the rollout generator and math-verify[3] for answer extraction and verification. We gratefully acknowledge the contributions of these open-source projects. To ensure reproducibility, we provide the complete implementation in an anonymous repository: https://anonymous.4open.science/r/siren_anonymous-6888.

Construction Method of Dataset for Llama3.1-8B. We manually construct an easier dataset for LLaMA3.1-8B. Specifically, for prompts drawn from OpenR1-Math-46K-8192, the GSM8K training set, and the MATH500 training set, we employ LLaMA3.1-8B-Instruct, LLaMA3.1-72B, and LLaMA3.1-72B-Instruct to generate 8 responses per prompt. We assume that stronger models from the same series can reflect the potential performance of weaker ones. During sampling, the temperature is set to 0.6 and the maximum response length is set to 8192. We filter out prompts for which none of the models can produce a correct answer. The resulting dataset contains 35K examples. The system prompt is shown in Appendix D.

Training Qwen2.5-Series Models. For the Qwen2.5 series models, we sample 8 responses per prompt. The learning rate is fixed at 1e-6 with a warm-up of 5 steps. The rollout batch size is set to 128, and the mini-batch size for updates is 8 prompts, meaning that the policy is updated 16 times per rollout. The maximum response length is 3072 tokens, and the maximum prompt length is 1024 tokens; prompts exceeding this limit are filtered out before training. We train the models for 2 epochs, corresponding to a total of 714 steps.

Most experiments on Qwen2.5-Math-7B are conducted on 16 NVIDIA A800 GPUs across 2 nodes (8 GPUs per node), with two exceptions: (1) *SIREN* on Qwen2.5-Math-7B with an entropy coefficient of 0.001, and (2) the ablation experiment using only self-anchored regularization. Both are conducted on 8 NVIDIA H200 GPUs. For Qwen2.5-Math-1.5B, all experiments are conducted on 4 NVIDIA

---

[1] https://github.com/volcengine/verl
[2] https://github.com/vllm-project/vllm
[3] https://github.com/huggingface/Math-Verify

H200 GPUs.

Training LLaMA3.1-8B. For LLaMA3.1-8B, due to the relative weakness of the model, we sample 16 responses per prompt. The rollout batch size is set to 512, and the mini-batch size for updates is 32, resulting in 16 policy updates per rollout. The maximum response length is 2048 tokens and the maximum prompt length is 1024 tokens. We train the model for 2 epochs on a dataset of 35K examples, corresponding to a total of 136 steps. We directly adopt the chat template of LLaMA3.1-8B-instruct without any modification. All experiments are conducted on 8 NVIDIA H200 GPUs.

Validation. For validation, we use the full test sets of the five datasets. Validation is performed every 10 steps. For each question, 16 responses are generated, with the sampling temperature set to 0.6 and the maximum response length kept consistent with training.

Evaluation. For evaluation, we set the temperature to 0.6 and the maximum number of new tokens to 32,768 to avoid artificially truncating responses. We use vLLM to generate the responses and math-verify to evaluate them.

C.2 Details of Baseline Methods

Dual Gradient Regularization (Haarnoja et al., 2018c). SAC is sensitive to the choice of the temperature parameter(entropy coefficient) α. Adjusting α manually is challenging because the policy entropy can fluctuate unpredictably across tasks and during training as the policy improves. To address this, an improved SAC formulation treats the problem as a constrained optimization: while maximizing the expected return, the policy is required to satisfy a minimum entropy constraint:

$$\max_{\pi} \mathbb{E}_{\pi}[R] \quad \text{s.t.} \quad H(\pi(\cdot|s)) \geq H_{\min}, \ \forall s,$$

where $H_{\min}$ is a predefined minimum policy entropy threshold.

To enforce this constraint automatically, the temperature α is treated as a learnable parameter and optimized via gradient ascent on the dual objective:

$$J(\alpha) = \mathbb{E}[-\alpha(H(\pi(\cdot|s_t)) - H_{\min})],$$

This allows the policy to adaptively adjust α during training. In our implementation, we integrate this mechanism by synchronously updating α, with its learning rate set equal to that of the policy.

Clip-Cov / KL-Cov (Cui et al., 2025). This work observes that changes in policy entropy are primarily driven by the covariance between action probabilities and logit updates, which is proportional to the advantage when using policy-gradient–style updates. High-probability actions with large advantages tend to decrease entropy, whereas rare actions with large advantages increase it. This work mitigates excessive entropy decrease by suppressing updates on tokens with high covariance: Clip-Cov samples a subset of these tokens and zeros out their policy loss, while KL-Cov selects the top-k% covariance tokens and applies an additional KL penalty to constrain their update magnitude. Importantly, these methods do not compute entropy or perform entropy-based regularization; instead, they indirectly regulate entropy by controlling updates on a small set of influential tokens. As a result, they are not susceptible to entropy explosion.

Entropy Advantage (Cheng et al., 2025). This method applies an entropy-guided advantage shaping strategy to encourage exploratory reasoning. Concretely, it injects an entropy-dependent term $\psi(H_t) = \min(\alpha \cdot H_t^{\text{detach}}, |A_t|/\kappa$ into the advantage function, forming $A_t^{\text{shaped}} = A_t + \psi(H_t)$. Because entropy is detached, it does not introduce gradients that directly push entropy upward. Furthermore, the shaping term is strictly bounded by $|A_t|/\kappa$, preventing runaway growth. Thus, the method emphasizes high-entropy positions while avoiding the uncontrolled positive feedback loop responsible for entropy explosion.

RL on Forking Tokens (Wang et al., 2025). This work identifies that only a small fraction of tokens exhibit high entropy, and these "forking" tokens critically influence downstream reasoning paths. The method improves RLVR by restricting policy-gradient updates only to these high-entropy tokens, showing that using roughly 20% of the tokens is sufficient to match or exceed full-token optimization performance. Since the method does not apply entropy regularization at all and simply filters which tokens receive policy loss, it does not introduce any mechanism that would drive entropy to diverge.

D System Prompt

E Additional Results

E.1 Extending to Other Models

Table 4 reports detailed results on five mathematical benchmarks. On Qwen2.5-Math-1.5B, *SIREN* achieves an average maj@k of 45.1 and avg@k of 37.0, outperforming naive baselines by +2.4 on average maj@k, respectively. On LLaMA3.1-8B,

SIREN attains 10.5 maj@k and 8.7 avg@k, also surpassing all other baselines.

E.2 Ablation Study

Hyperparameters For the ablation experiment with the self-anchored regularization, we set the entropy coefficient to 0.005, consistent with the main experiment. For the experiment without self-anchored regularization, we set the entropy coefficient to 0.0001 to avoid entropy explosion as much as possible.

Results The detailed performance of the ablation study is reported in Table 5. As shown, removing each component (top-p mask, peak-entropy mask, or self-anchored regularization) leads to a performance drop, with the removal of the self-anchored regularization causing the most severe decline: -10.3 maj@k and -15.5 avg@k. This highlights the critical role of self-anchored regularization in maintaining training stability and enabling the effectiveness of other modules.

Since the performance degradation caused by removing the self-anchored regularization is too significant, we also conduct an ablation experiment using only this component. The results show that self-anchored regularization can also improve the performance of naive entropy regularization, yielding notable gains, especially on relatively easier benchmarks such as MATH500 and Olympiad-Bench. However, the overall average performance still lags behind *SIREN*, indicating that each component in *SIREN* contributes effectively.

E.3 Sensitivity Analysis

Table 6 presents the detailed experimental results of *SIREN* under different hyperparameter settings. We observe that when the top-p cutoff is increased or the quantile τ is increased or decreased, the performance only shows a slight decline. This indicates that *SIREN* is robust and does not rely heavily on fine-tuning these hyperparameters.

F Analysis

F.1 *SIREN* Selects Effective Tokens

To provide a more intuitive illustration of what tokens are selected by our method, we construct a word cloud. Specifically, we randomly sample 8 questions from MATH500 and use Qwen2.5-7B-Math to generate 16 responses for each question, with the hyperparameters kept consistent with those used in the evaluation. We then collect the selected

Table 4: Overall performance on five mathematical benchmarks, extending to Qwen2.5-Math-1.5B and LLaMa3.1-8B.

	AIME24		AIME25		AMC22		MATH500		Olympiad Bench		Average	
	Maj@32	*Avg.*	*Maj@32*	*Avg.*	*Maj@32*	*Avg.*	*Maj@8*	*Avg.*	*Maj@8*	*Avg.*	*Maj.*	*Avg.*
Qwen2.5-Math-1.5B												
Qwen2.5-Math-1.5B	23.3	8.2	13.3	4.2	51.8	27.5	59.4	35.3	31.0	21.6	35.8	19.4
Dr.GRPO	16.7	14.1	16.7	8.4	55.4	44.1	81.2	**77.3**	41.5	**37.5**	42.3	36.3
Naive Entropy Reg	**23.3**	**15.3**	20.0	9.8	57.8	**48.1**	75.4	70.8	36.9	32.1	42.7	35.2
SIREN	20.0	13.8	**23.3**	**12.0**	**60.2**	47.9	80.2	75.7	**41.6**	36.0	**45.1**	**37.0**
LLaMa3.1-8B												
LLaMa3.1-8B	3.3	0.1	0.0	0.0	2.4	1.5	8.8	5.1	1.5	1.4	2.5	1.6
Dr.GRPO	0.0	0.0	0.0	0.0	6.0	7.4	25.8	22.5	6.8	6.1	7.7	7.3
Naive Entropy Reg	**3.3**	**0.1**	3.3	0.5	8.4	7.6	20.6	19.5	5.6	5.2	7.6	6.6
SIREN	0.0	0.0	**3.3**	**1.4**	**13.3**	**9.7**	**28.4**	**25.1**	**7.7**	**7.1**	**10.5**	**8.7**

Table 5: Overall performance of Qwen2.5-Math-7B compared with Dr.GRPO, naïve entropy regularization, and other RLVR methods that also incorporate entropy. All models are evaluated under a unified setting. Bold indicates the best results.

	AIME24		AIME25		AMC22		MATH500		Olympiad Bench		Average	
	Maj@32	*Avg@32*	*Maj@32*	*Avg@32*	*Maj@32*	*Avg@32*	*Maj@8*	*Avg@32*	*Maj@8*	*Avg@32*	*Maj.*	*Avg.*
SIREN	**43.3**	28.4	**26.7**	**17.9**	**71.1**	60.1	85.0	**81.9**	46.8	42.5	**54.6**	**46.1**
w/o TopP Mask	40.0	26.4	16.7	14.4	68.7	**60.4**	81.6	77.9	39.3	36.7	49.2	43.1
w/o Peak-Entropy Mask	33.3	**29.0**	26.7	16.8	65.1	59.2	80.0	77.9	39.4	37.3	48.9	44.0
w/o Self-Anchored Reg.	23.3	15.7	13.3	6.1	60.2	43.9	81.8	59.9	43.0	27.6	44.3	30.6
w/ only Self-Anchored Reg.	30.0	22.3	26.7	13.5	67.5	58.2	**87.4**	80.7	**49.8**	**43.2**	52.3	43.6

Figure 7: Word cloud of tokens selected by *SIREN*.

Figure 8: Training dynamics of entropy and validation pass@16, comparing *SIREN* with other RLVR baselines.

tokens and draw a word cloud with a maximum of 200 words (see Fig. 7). As shown in the figure, the high-frequency words are concentrated on core terms closely related to mathematical problem statements and reasoning, such as Given, The, To, Answer, and Consider, along with typical mathematical concepts such as product, sum, value, and equation. This demonstrates that our method effectively captures the key information in problem descriptions and solution processes rather than being dominated by redundant or noisy tokens, thereby further validating the rationality and effectiveness of the proposed mask strategy.

F.2 *SIREN* Makes Exploration More Effective (Part 2)

We study the training dynamics of the RLVR baseline, with results shown in Figure 8. Consistent with the main text, *SIREN* maintains higher entropy and pass@k, indicating more sustained exploration. Interestingly, *Kl-Cov* also preserves entropy

Table 6: Detailed experimental results of *SIREN* under different hyperparameter settings.

	AIME24		AIME25		AMC22		MATH500		Olympiad Bench		Average	
	Maj@32	*Avg.*	*Maj@32*	*Avg.*	*Maj@32*	*Avg.*	*Maj@8*	*Avg.*	*Maj@8*	*Avg.*	*Maj.*	*Avg.*
top-p=0.8, τ=0.8	**43.3**	**28.4**	**26.7**	**17.9**	**71.1**	60.1	85.0	81.9	46.8	42.5	**54.6**	**46.1**
Varying top-p ($\tau = 0.8$)												
top-p=0.7	33.3	24.2	16.7	12.8	62.7	55.7	83.2	77.6	46.7	40.8	48.5	42.2
top-p=0.9	40.0	25.5	16.7	13.5	69.9	60.0	86.4	81.8	47.3	43.3	52.0	44.8
Varying τ (top-p = 0.8)												
τ=0.7	33.3	21.6	23.3	15.5	**71.1**	61.6	84.6	80.1	42.1	38.7	50.9	43.5
τ=0.75	**43.3**	28.1	16.7	13.2	73.5	62.3	**86.6**	**82.0**	**50.4**	**44.2**	54.1	46.0
τ=0.85	40.0	21.5	23.3	14.2	**71.1**	**61.7**	82.6	79.9	45.9	41.4	52.6	43.7
τ=0.9	26.7	16.0	23.3	13.1	69.9	54.9	84.4	78.3	47.1	41.1	50.3	40.7

and pass@k well; however, it introduces additional computational overhead during training due to the need to compute the KL divergence with the original model.

G Case Study

G.1 More cases of preliminary analysis

We provide additional cases comparing generated tokens from the original model and the entropy-exploded model, as shown in Fig. 9. The observations are consistent with the main text: (1) after RL training with entropy explosion, the generated content becomes meaningless; (2) in the original model, tokens with higher entropy tend to correspond to logically critical positions, such as initiating or bridging a line of reasoning and elaborating individual reasoning steps, and so on.

G.2 Comparison of responses generated by *SIREN* and RL baselines

To qualitatively demonstrate the improvement of the *SIREN* mechanism in structured exploration, we randomly selected two cases from the AIME24 (Li et al., 2024) task that were correctly solved by the *SIREN* model but failed by the baseline model for analysis. Compared with the baseline*Dr.GRPO*, *SIREN* produces more detailed solution steps, tends to break down the problem into finer-grained steps using more tokens, and includes a complete verification process, resulting in more accurate answers.

Example 1:

Question and Ground Truth

Question: Alice chooses a set A of positive integers. Then Bob lists all finite nonempty sets B of positive integers with the property that the maximum element of B belongs to A. Bob's list has 2024 sets. Find the sum of the elements of A.

Ground Truth: 55

Response from RL Baseline   **1043 Tokens**

[Problem Setup] To solve this problem, let's start by understanding the relationship between the set A and the sets B that Bob lists. The key point is that the maximum element of each set B must be an element of A.

[Strategy] If A has n elements, then the number of possible sets B is related to the number of ways we can choose a maximum element from A and then choose any subset of the elements less than the maximum element to be the remaining elements of B.

[Equation Transformation] If A has n elements, then for each element $a \in A$, we can form sets B where a is the maximum element. The number of such sets B is $2^{a-1} - 1$ (we subtract 1 to exclude the empty set). Summing this over all elements of A gives the total number of sets B. If $A = \{a_1, a_2, \ldots, a_n\}$, then the total number of sets B is:

$$\sum_{i=1}^{n}(2^{a_i-1} - 1) = \sum_{i=1}^{n} 2^{a_i-1} - n$$

We know that this sum is equal to 2024. So we

Questions: Rectangles *ABCD* and *EFGH* are drawn such that *D,E,C,F* are collinear. Also, *A,D,H,G* all lie on a circle. If *BC=16,AB=107,FG=17*, and *EF=184*, what is the length of *CE*?

Before RL	Average Entropy: 0.260

Let 's solve the problem step by step . 1 . ** Under stand the Problem : ** - We have two rectangles \(AB CD \) and \(E FG H \) such that \(D , E , C , F \) are coll inear . - The points \(A , D , H , G \) lie on a circle . - We are given the lengths \(BC = 1 6 \), \(AB = 1 0 7 \), \(FG = 1 7 \), and \(EF = 1 8 4 \). - We need to find the length of \(CE \). 2 . ** An alyze the Geometry : ** - Since \(A , D , H , G \) lie on a circle , and \(AB CD \) and \(E FG H \) are rectangles , we can use the properties of the circle and the rectangles to find the required length . - The length \(CE \) can be found by considering the distances along the line \(D , E

0.0   4.271

After RL	Average Entropy: 9.107

In □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□[$_ □□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□[$_□[$□□□□□□[$_□□[$_□□ [$_ [$_□($_□[$_[$□[$_[$_□[$_[$_[$_[$_[$_[$ [$□[$_[$_

6.822   11.326

Questions: Let △ *ABC* have circumcenter O and incenter I with $\overline{IA} \perp \overline{OI}$, circumradius 13, and inradius 6. Find $AB \cdot AC$.

Before RL	Average Entropy: 0.514

In $\ triangle ABC $, points $ D $ and $ E $ lie on $\ over line { BC }$ and $\ over line { AC }$, respectively . $ AB = 1 0 $, $ AE = 6 $, $ CE = 5 $, $\ over line { AD }\ per p \ over line { BC }$, and $\ over line { BE }\ per p \ over line { AC }$. Find $ BD $. 1 . ** Given Information : ** - $\ triangle ABC $ has circum center $ O $ and in center $ I $. - $\ over line { IA } \ per p \ over line { OI }$. - Circ um radius $ R = 1 3 $. - In radius $ r = 6 $. - We need to find $ AB \ cdot AC $. 2 . ** Using the Given Per pendicular ity : ** - Since $\ over line { IA } \ per p \ over line { OI }$, we can use the fact

0.0   8.806

After RL	Average Entropy: 10.975

`` `` `` `` `` `` `` `` `` `` `` `` `` ``(`` ""`` ``( `` ``(``` ``` `\[\[\ [`\`\-,\[\`-\[\`-[[-\,[,[]]\[]-, `\[-\[\\[\`` `` [-`\[\[\[[ `\`]],[[\,[[,`\-\`[[\[\[\`\`, \[[\]`\[\[\-\[[-\[[\[,[`\`\[,[[\[-[,-\]-[[\[[\-\[[\],[\[\]\-[[\[-,[,[,\[\,[,[[-[[\[\[[\[,[,[,[-\[\[-[,[[,[[\[[\[\]\,[[\[],[[\,[/[,[[[[\[\[-[[-[[,] `\-\[\[[[,[[[\[\,[-,[,[[-,[-[,[,[[,[[- [[-[[[\[[\[/[,[-\[[[\,[[- [[,[[\],,[[[

10.278   11.586

Figure 9: More comparison cases between the original model and the entropy-exploded model, with questions sampled from AIME25 (first 200 tokens).

need to find a set A such that:

$$\sum_{i=1}^{n} 2^{a_i - 1} - n = 2024$$

[Candidate Check] This can be rearranged to:

$$\sum_{i=1}^{n} 2^{a_i - 1} = 2024 + n$$

One way to approach this is to start by finding the smallest possible set A and then iterating to find the correct set. Let's start by assuming A has the smallest possible elements, i.e., $A = \{1, 2, 3, \ldots, n\}$. Then the sum becomes:

$$\sum_{i=1}^{n} 2^{i-1} = 2^0 + 2^1 + 2^2 + \cdots + 2^{n-1} = 2^n - 1$$

We need to find n such that:

$$2^n - 1 = 2024 + n$$

[Incorrect Assumption] We can solve this equation by trial and error. Let's start by checking small values of n. For $n = 11$:

$$2^{11} - 1 = 2047 \quad \text{and} \quad 2024 + 11 = 2035$$

This is close but not quite right. Let's try $n = 10$:

$$2^{10} - 1 = 1023 \quad \text{and} \quad 2024 + 10 = 2034$$

This is too small. So $n = 11$ is the correct value. Now we need to find the set A that satisfies the equation. The set A must be $\{1, 2, 3, \ldots, 11\}$, but we need to check if there is a smaller set that works.

[Incorrect Conclusion] The correct set A is $\{11, 10, 9, 8, 7, 6, 5, 4, 3, 2, 1\}$. The sum of the elements of A is:

$$11 + 10 + 9 + 8 + 7 + 6 + 5 + 4 + 3 + 2 + 1 = 66$$

[Incorrect Answer] So the final answer is:

$$\boxed{66}$$

[Problem Setup] Let's begin by understanding the problem. We are given that Bob lists all finite nonempty sets B of positive integers such that the maximum element of B belongs to a set A chosen by Alice. The number of such sets B is 2024, and we need to find the sum of the elements of A.

[Variable Definition] Let's denote the set A as $A = \{a_1, a_2, \ldots, a_n\}$ where $a_1 < a_2 < \ldots < a_n$. For each element a_i in A, the sets B that have a_i as their maximum element are all the nonempty subsets of $\{1, 2, \ldots, a_i - 1\}$. The number of nonempty subsets of a set with $a_i - 1$ elements is $2^{a_i-1} - 1$. Therefore, the total number of sets B is the sum of these for all a_i in A:

$$(2^{a_1-1}-1)+(2^{a_2-1}-1)+\cdots+(2^{a_n-1}-1) = 2024$$

[Equation Transformation] This simplifies to:

$$2^{a_1-1} + 2^{a_2-1} + \cdots + 2^{a_n-1} - n = 2024$$

$$2^{a_1-1} + 2^{a_2-1} + \cdots + 2^{a_n-1} = 2024 + n$$

[Strategy] We need to find a set of integers $\{a_1, a_2, \ldots, a_n\}$ such that the sum of powers of 2 is $2024+n$. To find the correct set, we first note that $2024+n$ must be expressible as a sum of distinct powers of 2. The largest power of 2 less than or equal to 2024 is $2^{10} = 1024$. We can start by expressing 2024 in binary:

$$2024_{10} = 11111101000_2 = 1024+512+256+128+$$
$$64 + 32 + 8$$

This means:

$$2024 = 2^{10} + 2^9 + 2^8 + 2^7 + 2^6 + 2^5 + 2^3$$

[Candidate Check] If we add n to 2024, we need to check if the resulting sum can be expressed as a sum of distinct powers of 2. To find the

correct n, we can check the next smallest values. If $n = 1$, then:

$$2024 + 1 = 2025$$

The binary representation of 2025 is:

$$2025_{10} = 11111101001_2 = 1024+512+256+128$$
$$+64 + 32 + 8 + 1$$

This means:

$$2025 = 2^{10} + 2^9 + 2^8 + 2^7 + 2^6 + 2^5 + 2^3 + 2^0$$

This is a sum of distinct powers of 2, so it is valid. Therefore, the set A could be $\{11, 10, 9, 8, 7, 6, 3, 1\}$. The sum of the elements of A is:

$$11 + 10 + 9 + 8 + 7 + 6 + 3 + 1 = 55$$

[Verification] To verify, the number of sets B is:

$$(2^{11-1}-1)+(2^{10-1}-1)+(2^{9-1}-1)+(2^{8-1}-1)+$$
$$(2^{7-1}-1)+(2^{6-1}-1)+(2^{3-1}-1)+(2^{1-1}-1)$$

$$= (2^{10}-1)+(2^9-1)+(2^8-1)+(2^7-1)+(2^6-1)$$
$$+(2^5 - 1) + (2^2 - 1) + (2^0 - 1)$$

$$= 1024-1+512-1+256-1+128-1+64-1+32-1$$
$$+4 - 1 + 1 - 1$$

$$= 1024+512+256+128+64+32+4+1-8$$

$$= 2025 - 8 = 2017$$

This is not 2024, so we need to check the next value. If $n = 2$, then:

$$2024 + 2 = 2026$$

The binary representation of 2026 is:

$2026_{10} = 11111101010_2 = 1024+512+256+128+$

$$+32 + 8 + 2$$

This means:

$$2026 = 2^{10} + 2^9 + 2^8 + 2^7 + 2^6 + 2^5 + 2^3 + 2^1$$

This is a sum of distinct powers of 2, so it is valid. Therefore, the set A could be $\{11, 10, 9, 8, 7, 6, 3, 1\}$ with an additional element, say 2. The sum of the elements of A is:

$$11 + 10 + 9 + 8 + 7 + 6 + 3 + 1 + 2 = 57$$

But, the number of sets B is:

$$(2^{11-1}-1)+(2^{10-1}-1)+(2^{9-1}-1)+(2^{8-1}-1)+$$
$$(2^{7-1}-1)+(2^{6-1}-1)+(2^{3-1}-1)+(2^{1-1}-1)+$$
$$(2^{2-1} - 1)$$

$$= (2^{10}-1)+(2^9-1)+(2^8-1)+(2^7-1)+(2^6-1)+$$
$$(2^5 - 1) + (2^2 - 1) + (2^0 - 1) + (2^1 - 1)$$

$$= 1024-1+512-1+256-1+128-1+64-1+32-1$$
$$+4 - 1 + 1 - 1 + 2 - 1$$

$$= 1024+512+256+128+64+32+4+1+2-9$$

$$= 2026 - 9 = 2017$$

This is not 2024, so the correct set A must be $\{11, 10, 9, 8, 7, 6, 3, 1\}$ with $n = 1$. The sum of the elements of A is 55. So, the final answer is:

[Conclusion]

$$\boxed{55}$$

Example 2:

Question and Ground Truth

Question: Let $\omega \neq 1$ be a 13th root of unity. Find the remainder when

$$\prod_{k=0}^{12}(2 - 2\omega^k + \omega^{2k})$$

is divided by 1000.
Ground Truth: 321

Response from RL Baseline
Total Length: 808 Tokens

[Problem Setup and Polynomial Definition]
To solve the problem, we need to evaluate the product $\prod_{k=0}^{12}(2 - 2\omega^k + \omega^{2k})$ where ω is a 13th root of unity, and then find the remainder when the result is divided by 1000.

First, let's understand the expression $2 - 2\omega^k + \omega^{2k}$. Since ω is a 13th root of unity, $\omega^{13} = 1$ and ω^k for $k = 0, 1, 2, \ldots, 12$ are all distinct 13th roots of unity. We need to evaluate the product for $k = 0, 1, 2, \ldots, 12$.

Let's denote the polynomial $P(x) = 2 - 2x + x^2$. We need to evaluate the product $P(\omega^0) \cdot P(\omega^1) \cdot P(\omega^2) \cdot \ldots \cdot P(\omega^{12})$.

First, we evaluate $P(\omega^k)$:

$$P(\omega^k) = 2 - 2\omega^k + (\omega^k)^2 = 2 - 2\omega^k + \omega^{2k}.$$

Now, we need to find the product of these values for $k = 0, 1, 2, \ldots, 12$.

[Flawed Mathematical Reasoning/Incorrect Formula Application]
To simplify the problem, we can use the fact that the polynomial $P(x) = 2 - 2x + x^2$ can be rewritten in a more convenient form. Notice that:
$$P(x) = x^2 - 2x + 2.$$

We need to evaluate the product:

$$\prod_{k=0}^{12}(2 - 2\omega^k + \omega^{2k}).$$

This product can be evaluated by considering the polynomial $P(x)$ evaluated at the 13th roots of unity. The polynomial $P(x)$ can be written as:
$$P(x) = x^2 - 2x + 2.$$

We need to find the value of the product of $P(\omega^k)$ for $k = 0, 1, 2, \ldots, 12$. This can be

---

done by considering the polynomial $P(x)$ and its roots.

The polynomial $P(x)$ can be evaluated at the roots of unity. The product of the values of a polynomial at the roots of unity can be found using the fact that the product of the values of a polynomial $P(x)$ at the roots of unity is given by the constant term of the polynomial $P(x)$ raised to the power of the number of roots, divided by the leading coefficient raised to the power of the number of roots minus one.

In this case, the polynomial $P(x) = x^2 - 2x + 2$ has a constant term of 2 and a leading coefficient of 1. The product of the values of $P(x)$ at the 13th roots of unity is given by $2^{13}/1^{12} = 2^{13} = 8192$.

[Modulo Operation and Incorrect Final Answer]
Finally, we need to find the remainder when 8192 is divided by 1000. This is given by:

$$8192 \mod 1000 = 192.$$

So the remainder when the product is divided by 1000 is $\boxed{192}$.

Response   from   _SIREN_
Total Length: 1417 Tokens

[Problem Setup and Initial Transformation]
To solve this problem, we need to consider the expression $\prod_{k=0}^{12}(2 - 2\omega^k + \omega^{2k})$, where ω is a 13th root of unity, i.e., $\omega^{13} = 1$ and $\omega \neq 1$. Let's first rewrite the expression inside the product:

$$2 - 2\omega^k + \omega^{2k} = 2(1 - \omega^k) + \omega^{2k}.$$

[Contextual Background - Roots of Unity]
Next, we will look at the polynomial whose roots are ω^k for $k = 0, 1, 2, \ldots, 12$. The polynomial is $x^{13} - 1 = 0$, which can be factored as:

$$x^{13} - 1 = (x-1)(x-\omega)(x-\omega^2)\cdots(x-\omega^{12}).$$

[Reframing the Problem as Polynomial Product]
We need to find the value of the product $\prod_{k=0}^{12}(2 - 2\omega^k + \omega^{2k})$. We can consider the polynomial $P(x) = 2 - 2x + x^2$, and we need to find the product $P(\omega^0) \cdot P(\omega^1) \cdot P(\omega^2) \cdots P(\omega^{12})$.

[Attempted Solution - First Approach (Incorrect Formula)]
To find this product, we can consider the polynomial whose roots are $P(\omega^k)$ for $k = 0, 1, 2, \ldots, 12$. Let's define a new polynomial $Q(y)$ such that the roots of $Q(y)$ are $P(\omega^k)$. We can find $Q(y)$ by considering the transformation $y = P(x) = 2 - 2x + x^2$. To find $Q(y)$, we need to express x in terms of y. We have:

$$x^2 - 2x + 2 - y = 0.$$

The roots of this quadratic equation are:

$$x = 1 \pm \sqrt{y - 1}.$$

Since ω^k are the 13th roots of unity, we need to find the polynomial whose roots are $P(\omega^k)$. The polynomial $Q(y)$ will be the resultant of the polynomial $x^{13} - 1$ and the transformation $y = 2 - 2x + x^2$. However, a simpler approach is to note that the product of the values of a polynomial at the roots of unity is given by the resultant of the polynomial and $x^n - 1$, where n is the degree of the polynomial. In this case, we can use the fact that the product of $P(\omega^k)$ for $k = 0, 1, 2, \ldots, 12$ is the value of the polynomial $P(x)$ raised to the power of the degree of the polynomial $x^{13} - 1$, evaluated at the roots of unity.

[Attempted Solution - Second Approach (Incorrect /Incomplete Formula)]
The polynomial $P(x) = 2 - 2x + x^2$ can be written as $P(x) = (x-1)^2 + 1$. The product of $P(\omega^k)$ for $k = 0, 1, 2, \ldots, 12$ is the value of the polynomial $P(x)$ evaluated at the roots of unity, which is the constant term of the polynomial $P(x)^{13}$ divided by the leading coefficient. This is given by:

$$\prod_{k=0}^{12} P(\omega^k) = P(1)^{13} = (2 - 2\cdot 1 + 1^2)^{13} = 1^{13} = 1.$$

[Self-Correction and Recognition of Complexity]
However, this is not the correct approach for this specific problem. We need to consider the polynomial whose roots are $2 - 2\omega^k + \omega^{2k}$. Let's define a new polynomial $R(x)$ such that the roots of $R(x)$ are $2 - 2\omega^k + \omega^{2k}$. We can find $R(x)$ by considering the transformation $x = 2 - 2\omega^k + \omega^{2k}$. To find $R(x)$, we need to

express ω^k in terms of x. However, a simpler approach is to note that the product of the values of a polynomial at the roots of unity is given by the resultant of the polynomial and $x^n - 1$, where n is the degree of the polynomial. In this case, we can use the fact that the product of $2 - 2\omega^k + \omega^{2k}$ for $k = 0, 1, 2, \ldots, 12$ is the value of the polynomial $P(x)$ raised to the power of the degree of the polynomial $x^{13} - 1$, evaluated at the roots of unity.

[Pragmatic Computational Approach]

Let's use Python to calculate the product $\prod_{k=0}^{12}(2 - 2\omega^k + \omega^{2k})$ and find the remainder when this product is divided by 1000.

```python
import numpy as np

# 13th roots of unity
omega = np.exp(2j * np.pi / 13)
roots_of_unity = [omega**k for k in

range(13)]

# Calculate the product
product = np.prod([2 - 2*omega**k
# + omega**(2*k) for k in
range(13)])

# Get the real part of the product
# (since the imaginary part
b should be very close to 0)
product_real = np.real(product)

# Find the remainder when the product
is divided by 1000 remainder =
int(round(product_real)) % 1000
print(remainder)

321
```

[Final Answer] The remainder when $\prod_{k=0}^{12}(2 - 2\omega^k + \omega^{2k})$ is divided by 1000 is $\boxed{321}$.