The Grounding Gap: How LLMs Anchor the Meaning of Abstract Concepts Differently from Humans

Odysseas S. Chlapanis
Department of Informatics
Athens University of Economics and Business
Archimedes, Athena Research Center
Greece

Orfeas Menis Mastromichalakis
Instituto de Telecomunicações
Portugal

Christos H. Papadimitriou
Department of Computer Science
Columbia University
United States

Abstract

Abstract concepts — justice, theory, availability — have no single perceivable referent; in the human brain, their meaning emerges from a web of experiences, affect, and social context. Do large language models (LLMs) ground abstract concepts in a similar way? We study this by replicating property-generation experiments from cognitive science on 21 frontier and open-weight LLMs. Across models and experiments, we find a consistent pattern: when compared to humans, models rely too heavily on word associations, and underproduce properties tied to emotion and internal states. This yields a large and consistent grounding gap: no model exceeds a Pearson correlation $r = 0.37$ with human responses, compared to a human-to-human ceiling above $r = 0.9$. To better interpret this gap, we also replicate a rating experiment on grounding categories and find that here LLMs align more closely with human judgment, and alignment improves as models get larger. We then use sparse autoencoders (SAEs) to inspect whether this information is also reflected in the models' internal features, and we do identify features connected to grounding dimensions such as "sensorimotor" and "social". These findings suggest that current LLMs can recover grounding dimensions when explicitly queried, but do not recruit them in a human-like way when words are generated freely.[1]

1 Introduction

Concrete concepts such as *cat* and *table* are anchored in shared experience through identifiable referents that can be perceived through the senses [Borghi et al., 2017]. In contrast, abstract concepts such as *art*, *adventure*, or *justice*, lack such referents. When humans process abstract words, they reconstruct their meaning from grounded experiences. Consider how a person makes sense of *art*: a colorful *painting*, a feeling of *awe*, a favorite *concert*, as well as more abstract ideas such as *creativity*. Grounded-cognition theories argue that such sensorimotor, emotional, and social anchors are not incidental but constitutive of meaning [Lakoff and Johnson, 2003, Barsalou, 1999, 2026]. Whether LLMs represent abstract concepts in a similarly grounded way, or rely primarily on patterns of linguistic association [Bender and Koller, 2020, Bender et al., 2021], remains an open question.

To measure how closely LLMs align with humans in the grounding of abstract concepts, we replicate on LLMs two property-generation experiments from cognitive science [Harpaintner et al., 2018,

---

[1]All data and code are publicly available at `https://github.com/odychlapanis/grounding-gap/`.

Kelly et al., 2024]. In these experiments, participants — in these references humans, in this paper models — are given a concept and asked to list the properties, situations, or associations that come to mind. Although individual responses vary, the coded distributions across human participants are highly consistent: people anchor abstract concepts along grounding dimensions such as sensorimotor experience, emotion, and social context in a similar and consistent way. We then compare the distributions produced by models with those produced by humans. Across 21 frontier and open models, we find a large and consistent grounding gap. In both experiments, no model reaches a human–model correlation above $r = 0.37$, while the human–human ceilings exceed $r = 0.9$. Models are also much closer to one another than to humans: model–model correlations are systematically higher than model–human correlations. Taken together, these results show that current LLMs exhibit a shared mode of grounding abstract concepts that is systematically different from the human one.

But does the gap arise because models lack an understanding of the categories that structure human grounding, or because this understanding is not recruited in a human-like way when concepts are generated freely? To answer, we turn to a rating experiment from cognitive science, in which words are evaluated directly along grounding-related dimensions [Troche et al., 2017]. There, recent LLMs align much more closely with human judgments, and this alignment improves with model scale, leaving a gap of only about .1 in Pearson correlation with humans. This contrast suggests that the relevant dimensions are at least partly available to the models when they are explicitly queried, but they are not spontaneously recruited in a human-like way during property generation.

This raises a mechanistic question: Can we find in LLMs internal representations that align with these grounding-related dimensions? To investigate this, we analyze models with sparse autoencoders (SAEs), a technique that helps identify interpretable internal features [Bricken et al., 2023, Huben et al., 2024, Templeton et al., 2024]. We search for features whose activations track grounding-related dimensions, and we do find evidence of such structure: some internal features correlate with human grounding dimensions or sub-dimensions. We then validate these features by showing that steering the model along them increases generation of properties from the corresponding target categories. Taken together, our findings suggest that current LLMs understand the basic grounding categories nearly–but not quite–as well as humans do, and yet they do not recruit them in a human-like way when generating freely.

Contributions.

- We replicate two property-generation experiments from cognitive science on 21 frontier and open LLMs, and show a large and consistent gap between humans and models in the grounding of abstract concepts.
- We replicate a rating experiment on grounding-related dimensions and show that LLMs align much more closely – but not fully – with human judgments there, indicating that the gap is not simply due to failure to recognize the relevant dimensions.
- We use sparse autoencoders to probe Gemma models for internal features related to grounding dimensions, and we do find evidence of such structure.

2 Related work

Grounded cognition and grounding norms. Traditional theories of *grounded cognition* in language posit that abstract categories are not represented as arbitrary symbols but are grounded in sensorimotor and affective experience [Barsalou, 1999, Barsalou and Wiemer-Hastings, 2005]. Neurocognitive evidence supports that action words engage motor and premotor cortex [Hauk et al., 2004, Pulvermüller, 2005], and emotional and social dimensions of abstract concepts have been linked to interoceptive processing [Critchley et al., 2004, Mancano and Papagno, 2026]. Behavioral norms operationalize these dimensions at scale: datasets in which human participants rate words on Likert scales for dimensions such as sensorimotor strength, arousal, valence, and socialness. Lynott et al. [2020] provide modality-specific strength ratings for 40,000 English words, while Scott et al. [2019] and Diveica et al. [2023] cover arousal, valence, and socialness dimensions. These corpora enable grounding research to move beyond binary concrete/abstract distinctions [Brysbaert et al., 2014]. The property-listing paradigm [McRae et al., 2005, Barsalou and Wiemer-Hastings, 2005] provides a richer signal: rather than scalar ratings, participants freely generate properties of concepts, yielding a distributional profile over experiential dimensions. Harpaintner et al. [2018]

applied this paradigm specifically to abstract nouns, showing that they elicit rich sensorimotor, social, and affective features. Kelly et al. [2024] extended the paradigm to test whether emotion concepts form a distinct subcategory, finding that they rely more strongly on interoceptive features than other abstract concepts. These two studies form the empirical basis of our behavioral experiments.

LLM cognitive experiments. Early work showed that language models often fail psycholinguistic diagnostics and do not reliably ground semantic properties [Ettinger, 2020]. Pezzelle et al. [2021] compared pre-trained transformer representations against human concept norms and found that visual co-training improves alignment for concrete word pairs, but offers little benefit for abstract ones. Recent work extends this question to frontier and open LLMs by prompting them for human-style ratings and comparing them to established norms. Xu et al. [2025] report strong alignment with Glasgow and Lancaster norms on non-sensorimotor dimensions, but weaker alignment on sensory and motor domains. Wang et al. [2025b] similarly find persistent gaps for abstract concepts, embodied modalities, and emotion or social dimensions across nine LLMs, with alignment improving with scale. Related studies also show that LLMs can approximate affective and sensorimotor ratings [Trott, 2024] and recover aspects of perceptual color structure from text alone [Abdou et al., 2021]. Closest to our setup, Suresh et al. [2023] use property listing rather than ratings, but focus on concrete concepts and feature-overlap similarity against existing norms. In contrast, we target abstract concepts and classify generated properties into experiential categories.

Mechanistic interpretability of semantic concepts. A prominent line of mechanistic interpretability work uses linear probes to localize non-linguistic latent structure in LLM residual streams, recovering concept axes for board game states, spatiotemporal coordinates, and sentiment [Li et al., 2023, Nanda et al., 2023, Gurnee and Tegmark, 2024, Tigges et al., 2024]. Some works extend this paradigm by using these latent vectors to steer models towards the detected concepts [Turner et al., 2024, Panickssery et al., 2024]. Recent studies have identified circuit-level emotion components to control emotional expression [Wang et al., 2025a] and recovered emotion directions in models like Claude Sonnet 4.5 [Sofroniew et al., 2026]. In this work, we analyze features learned by sparse autoencoders (SAEs) to probe whether grounding-related information is reflected in model representations. SAEs decompose polysemantic LLM representations into monosemantic, interpretable features [Bricken et al., 2023, Huben et al., 2024, Templeton et al., 2024]. Recently, SAE features have been applied for analyzing emotion [Wu et al., 2025]. In our work, we leverage the Gemma Scope 2 SAE models [McDougall et al., 2025], the successor to Gemma Scope [Lieberum et al., 2024], and we probe sensorimotor, internal-state, and social concepts.

3   The grounding gap

We study LLM grounding of abstract concepts through *property generation*, a behavioral paradigm from cognitive science in which participants are given a concept and asked to list the features, situations, or associations that come to mind for it. Unlike scalar rating tasks [Troche et al., 2017], which require participants to map conceptual content onto a fixed set of predefined dimensions, property generation captures the content that people spontaneously recruit when representing a concept. For this reason, it has been used as a richer and more faithful way to study grounding, especially for abstract concepts [Barsalou and Wiemer-Hastings, 2005, McRae et al., 2005].

To measure how closely LLMs align with humans on conceptual grounding, we replicate two human property-generation studies on abstract concepts: Harpaintner et al. [2018] and Kelly et al. [2024]. We selected these studies because both provide publicly available data and explicit coding taxonomies, enabling controlled human–model comparison under complementary experimental designs. Harpaintner et al. [2018] (*Experiment 1*) organizes properties of abstract concepts into *sensorimotor*, *internal-state*, *social*, and *verbal-association* content, reflecting dimensions of abstract-concept representation that are well established in the broader literature [Troche et al., 2017, Villani et al., 2019]. Kelly et al. [2024] (*Experiment 2*) provides a more specialized setting, with a different stimulus design and coding taxonomy with a particular focus on emotion concepts. Using both experiments allows us to test whether human–model grounding gaps persist across distinct property-generation paradigms rather than arising from a single dataset or coding scheme.

Figure 1: Per-word property-category frequency distributions for three frontier LLMs vs. the human baseline on the 293-abstract-noun benchmark [Harpaintner et al., 2018]. Each box spans the 25th–75th percentile of word-level frequencies; median annotated.

3.1 Experimental setup

We apply the same procedure in both experiments, following their original designs. For each stimulus word, we prompt the model to generate the properties, situations, or associations that come to mind (four properties for Experiment 1 and five for Experiment 2), using the original human instructions (prompts in Appendix G). We then map the generated properties to the taxonomy of the corresponding human study and compare the resulting per-word category generations against the human ones. All scores are averaged over 10 runs per model; see Appendix E for convergence analysis.

Stimulus sets. The stimulus set consists of the target words presented to participants—or, in our case, to the models—for property generation. For the first experiment [Harpaintner et al., 2018], we derive a 293-word English stimulus set from the original 296 German abstract concepts. Two items were excluded as translation duplicates (the original paper provided English translations for all words), and one additional item was excluded because it is used as a one-shot example in the original prompt. In the second experiment [Kelly et al., 2024], the stimulus set contains 357 words split into three subsets: 118 abstract emotion words, 118 abstract non-emotion words, and 119 concrete words. We use the 236 abstract words for our analysis; see Appendix C for findings for concrete words.

Property coding. The generated properties are open-ended, so they must be assigned to the grounding categories defined by each study. Following the original coding schemes, generated properties for Harpaintner et al. [2018] are assigned to: *Sensorimotor*, *Internal State & Emotion*, *Social*, and *Verbal Association*, while for Kelly et al. [2024] to *Taxonomic*, *Entity*, *Situation*, and *Introspective*. We use LLMs-as-coders, after validating candidate models on human-annotated word-to-category pairs. The selected coders achieve agreement with the ground truth that is comparable to, or higher than, human coders, while remaining practical to use at scale. We use *Gemini-2.5-Flash-Lite* as the primary coder for Experiment 1 and *Gemini-2.5-Flash* for Experiment 2. Detailed coder comparisons, annotation protocols, and reliability analyses are reported in Appendix A.

Alignment metric and human ceiling. After coding, each stimulus word is represented by the relative frequencies of its responses across the four target categories. We compare human and model frequency profiles using per-category Pearson r, and report *Mean r*, the average across the four categories, as our main alignment metric. The corresponding human ceiling is the Pearson r that two independent splits of raters would obtain on the same words: for Experiment 2 we compute it directly from Kelly et al. [2024]'s participant responses, and for Experiment 1 we estimate it analytically from Harpaintner et al. [2018]'s per-word aggregates using standard inter-rater reliability formulas; the two methods agree to within 0.01 on Experiment 2, validating our estimator (Appendix F).

Figure 2: Mean r for all LLMs vs. the human ceiling on Experiment 1 [Harpaintner et al., 2018]. Parameter count for closed models is based on estimations from Li [2026].

Models and settings. We evaluated a diverse set of 21 frontier and open-weight LLMs spanning several families; we refer to Appendix B.1 for the full list of models. We used the default temperature for all generations and to ensure coding reliability LLM-coders used a temperature of $T = 0.0$.

3.2 Results

Experiment 1. Figure 1 illustrates the per-word and per-category distributions for human responses and for three representative frontier models: Claude Opus 4.6, Gemini 3.1 Pro Preview, and GPT-5.4. Relative to humans, all three models generate substantially more *Verbal Association* properties and substantially fewer *Internal State & Emotion* properties. The same overall pattern holds across all models (see Appendix B for the full set of models). The similarity between the frequency of the different models also indicates that this is not a coincidental property of a single model family, but a consistent behavior across current architectures. By contrast, *Sensorimotor* frequencies remain closer to the human range in the aggregate, and *Social* frequencies are also broadly comparable, although this category is relatively sparse for both humans and models and is therefore less informative at the frequency level alone.

The frequency distributions indicate a systematic mismatch between human and model grounding, but aggregate frequency alone does not show whether models ground the *same* concepts in the *same* way as humans. For example, a model may produce a human-like number of *Sensorimotor* or *Social* properties overall, while assigning those properties to different words. We therefore measure alignment directly by computing Pearson correlations between human and model category-frequency generations across the stimulus set, as described in Section 3.1.

As shown in Figure 2, human-model alignment remains far below the estimated human–human ceiling across all 21 models. The best model reaches only a mean $r \approx 0.37$, compared with an estimated human ceiling of about 0.97, with the same pattern across individual categories as shown in Table 1. Thus, even when aggregate frequencies appear relatively human-like, models often associate grounding dimensions with different concepts than humans do. This gap is not explained by scale:

Table 1: Per-category Pearson correlations on Experiment 1 for three representative frontier models.

Model	Mean r	Sensorimotor	Internal	Social	Verbal
Estimated human ceiling	*0.974*	*0.966*	*0.964*	*0.971*	*0.992*
GPT-5.4	0.301 ± 0.005	0.329	0.256	0.413	0.206
Claude Opus 4.6	0.264 ± 0.004	0.203	0.201	0.375	0.279
Gemini 3.1 Pro Preview	0.257 ± 0.008	0.304	0.161	0.397	0.167

(a) Experiment 1 (Harpaintner et al. [2018])   (b) Experiment 2 (Kelly et al. [2024])

Figure 3: Pearson-r correlation heatmaps for three representative frontier models and humans.

larger models and stronger general-purpose systems do not show reliably higher human alignment, suggesting that the mismatch is not simply a capability bottleneck that shrinks with model size.

Inter-model correlations reveal a complementary pattern. As shown in Figure 3a, models correlate substantially more with one another than with humans, despite spanning different providers, data mixtures, and architectural choices. This suggests that current LLMs share a rather common mode of abstract-concept grounding, but one that is systematically distinct from the human pattern. The grounding gap is therefore not idiosyncratic to a single model family, but shared across current autoregressive LLMs.

Experiment 2. Experiment 2 confirms the findings of Experiment 1 under a different experimental setup. Human-model alignment remains low in the combined abstract condition, which pools the *abstract emotion* and *abstract non-emotion* items: even the strongest models reach only a mean $r \approx 0.33$, far below the human-to-human correlation of $r \approx 0.91$. Full results for all models are reported in Appendix B.

Inter-model correlations also follow the same pattern as in Experiment 1. As shown in Figure 3b, models correlate substantially more with one another than with humans. Together, the two experiments reveal a robust behavioral grounding gap: current LLMs share a common model-like pattern of abstract-concept representation, but one that remains systematically distinct from humans.

3.3 LLM-coder error margins

The Pearson correlations and category frequencies reported above are based on labels produced by Gemini 2.5 Flash-Lite. To estimate whether this affects our conclusions, we manually re-coded the outputs of three frontier models (Claude Opus 4.6, Gemini 3.1 Pro, and GPT-5.4) and compared the resulting metrics with those obtained from Flash-Lite labels on the same property pairs. The differences are minor: replacing Flash-Lite with human coders changes Mean r by only $\Delta = +0.014 \pm 0.019$ on average, with no consistent per-model shift (per-model 95% confidence intervals contain zero), and changes per-category mean frequencies by roughly $\pm 2\%$. These margins are far smaller than the human–model gap reported in Section 3.2, indicating that our main results are not driven by the use of LLMs as coders. Detailed analyses are reported in Appendix A.

4 Rating analysis of grounding dimensions

To better understand the grounding gap identified through the previous experiments, we study whether this gap arises because current LLMs do not properly recover the grounding dimensions that structure human concept representations, or because these dimensions are not recruited in a human-like way when concepts are generated freely. To distinguish between these possibilities, we replicate a rating experiment from cognitive science [Troche et al., 2017]. Unlike property generation, rating

Figure 4: Mean r for all LLMs vs. the human ceiling on the rating experiment [Troche et al., 2017]. Parameter count for closed models is based on estimations from Li [2026].

experiments do not test the spontaneous associations for a concept; instead, they test whether the model can score a word on semantic dimensions once these dimensions are explicitly specified.

Setup. We follow the setup of Troche et al. [2017], in which human participants rated 751 English nouns on 14 dimensions using a 1–7 Likert scale. The dimensions cover sensory content (*Color*, *Taste/Smell*, *Tactile*, *Visual Form*, *Auditory*), motor content (*Self-Motion*), internal and evaluative content (*Emotion*, *Polarity*, *Morality*, *Thought*), social content (*Social*), and magnitude-related content (*Space*, *Quantity*, *Time*). Using the original prompt "I relate this word to [*X*]," we evaluated the same 21 models from previous experiments over 10 shuffled runs each. Performance is reported as Mean r, the Pearson correlation between model and human ratings averaged across all 14 dimensions.

Results. The results differ sharply from those of property generation (compare Figures 2 and 4). On this task, recent frontier LLMs align much more closely with human judgments, with the strongest model reaching Mean $r \approx 0.76$ against an estimated human ceiling of about 0.89. Unlike property generation, alignment here improves substantially with model scale. This contrast suggests that the grounding gap is not due to an inability to recognize dimensions such as sensation, emotion, or sociality. Rather, current LLMs can recover these dimensions when they are made explicit in the task, but do not recruit them in a human-like way when asked to generate the content of abstract concepts freely. Extended experimental details and results are provided in Appendix D.

5 Mechanistic analysis

Having established that LLMs can predict grounding dimension ratings, we investigate whether they internally encode features tracking these dimensions by analyzing the 4B and 12B Gemma 3 instruction-tuned models using Gemma Scope 2 sparse autoencoders (SAEs) [McDougall et al., 2025]. We isolate latent features correlated with grounding dimensions, focusing on those that align strongly with human experiential categories. Remarkably, some of these internal features surpass the model's own behavioral baseline in human alignment. While steering these representations predictably increases the generation of target-category properties, we view this merely as a methodological sanity check; artificially amplifying feature activations does not close the grounding gap, as it overrides rather than reflects the model's natural internal structure.

5.1 Methodology

Feature identification. We ask whether the model contains SAE features that correspond to grounding categories or sub-groups beyond individual words. First, we collect a pool of 426 labeled nouns from four psycholinguistic norm databases [Lynott et al., 2020, Diveica et al., 2023, Scott et al., 2019, Brysbaert et al., 2014], each associated with one of the 4 grounding dimensions of interest (sensorimotor, internal-state, social, and abstract content). For each noun w, we generate 10 English sentences ending in w using Gemini-3.1-pro-preview, and then remove w, creating a

Figure 5: Percentage of mean r for all LLMs and SAE features vs. the estimated human ceiling mean r on the rating experiment dimensions.

form of cloze (fill-the-blank) questions to study model activations when generating w. We record the SAE activation at the final token of these cloze questions, i.e. the position where the model is about to generate w, and take the per-feature median across the ten sentences as the noun's activation signature. A feature enters category c's candidate pool if it has non-zero median activation on at least five distinct nouns from c. The approach is similar to the one used by [Sofroniew et al., 2026] for emotion vectors. Construction details are reported in Appendix H.1. This approach gives us a set of candidate features for all 4 grounding dimensions.

Tracking grounding dimension norms with SAE features. The previous stage is designed to select features that their activations are correlated with generation of nouns related to their category, but their activations are not necessarily aligned with humans. Our goal is to find features that not only respond to a grounding dimension, but do so in a way that is aligned with human norms in a grounding dimension. To achieve this we evaluate these candidate features on the same dataset we used in our rating experiment in Section 4. For the *feature* measurement, the original rating prompts are unsuitable: they target a specific dimension and elicit a numeric answer, whereas our candidate features were identified in the regime of free noun generation. We instead use two simple and generic property-generation prompts and the original complex property-generation prompt from Section 3 and average the results, record each candidate feature's activation at the final prompt position, and correlate it with the human ratings on each dimension. This measures how well the feature itself tracks the human grounding signal while simulating the property-generation task.

5.2 Results

Overall, both models show a rather strong behavioral alignment with human ratings across most grounding dimensions (Figure 5). Sensory dimensions are the main exception: model ratings remain far below the human ceiling, which is consistent with the findings of Xu et al. [2025]. Nevertheless, the SAE analysis identifies features that correlate with all evaluated dimensions, including the behaviorally weaker sensory ones. For most dimensions, the best-matching SAE features reach Pearson correlations in the range of $r = 0.6$ to 0.8, suggesting that these grounding-related dimensions are at least partially reflected in the models' internal representations. The main exception is the magnitude category, which includes space, quantity, and time and shows weaker feature alignment, possibly reflecting the more abstract nature of these dimensions. Overall, these results suggest that the models contain internal features that track several sub-dimensions of grounding, with these features being aligned with human judgments to some extent, and should not be interpreted as complete or fully human-like representations.

5.3 Feature steering

To interpret and validate these features, we conduct a steering experiment on Gemma 3 4B using the highest-correlation SAE feature for each dimension: sensory, motor, internal, social, and magnitude. We replicate Experiment 1 (Section 3.2) under feature steering, using feature clamping [Templeton et al., 2024] to a fixed high activation value. Steering increases target-category property generation in all cases: sensory (+5.3% *Sensorimotor*), motor (+4.7% *Sensorimotor*), internal (+9.4% *Internal*), social (+14.7% *Social*), and magnitude (+1.7% *Verbal*). These effects support the feature–category associations identified in the correlation analysis. We further inspect the highest-activating examples for each feature using Neuronpedia,[2] and find that the features generally activate on words related to their grounding dimensions. However, they are not perfectly category-specific: some also activate on words outside the narrow target dimension, suggesting that they capture broader semantic patterns rather than clean, isolated grounding categories or sub-dimensions. For details, see Appendix H.2.

6 Discussion

Grounding is important for humans because it connects language to lived experience and the physical world. As LLMs take roles originally meant for humans and move closer to agentic autonomy, their apparent differences from humans in grounding acquire some significance. The grounding gap we identified is unlikely to go away through scaling and text-based training alone, since (a) our experiments show that scaling [Hoffmann et al., 2022, Wei et al., 2022] does not appear to help, with state-of-the-art models remaining remarkably far from human ceilings, and (b) the excessive reliance on verbal associations we observe is a natural result of training that is focused on prediction from linguistic context, a core characteristic of autoregressive LLMs. Genuine progress on this front may require fundamental shifts, such as novel training techniques or alternative architectures [Fung et al., 2025, Brooks, 1991].

Our interpretability analysis reveals that LLMs possess latent grounding structures that sometimes exhibit stronger human alignment than the model's overall behavioral output. However, these features do not exclusively encode sensory, internal, or social experiences (see Appendix H.2 for details). According to one mainstream theory of grounded cognition [Barsalou, 1999], true conceptual understanding requires the capacity to internally simulate physical experiences. Whether LLMs possess, or can acquire through training, internal circuits capable of such simulation remains an open challenge for future research.

Limitations. Our behavioral analysis is limited by the generality of the property-generation experiments we replicate, although both are well established in the literature. To our knowledge, these are the only extant property-generation studies on abstract-concept grounding with both openly available stimulus sets and coding taxonomies suitable for direct replication and comparison. The fact that we observe highly consistent results across these two independently designed experiments, with different stimuli, taxonomies, and participant samples, suggests that the observed gap is not specific to a single experimental setup.

A second limitation is the use of LLMs as coders, which could introduce model-specific biases into the estimated category frequencies and correlations. We mitigate this by validating candidate coders against human-annotated word-to-category pairs and selecting models with human-level or stronger agreement. We also show in Section 3.3 that replacing the LLM coder with human coders changes the main metrics only marginally, with differences far smaller than the human–model gaps reported above. This makes it highly unlikely that our conclusions are driven by the coding procedure.

Finally, our SAE analysis is limited to Gemma models due to the limited availability of high-quality SAEs for recent LLMs and the cost of scaling the analysis. More generally, SAE features are interpretable approximations of model representations, not complete decompositions. The absence of a feature in an SAE therefore does not guarantee that the corresponding information is absent from the underlying model. We therefore treat the SAE results as exploratory evidence that complements the behavioral findings, rather than as the basis for strong mechanistic claims.

---

[2] Neuronpedia is an open-source platform for SAE interpretability and visualization: `https://www.neuronpedia.org`.

7 Conclusion

We investigate how well frontier LLMs are cognitively aligned with humans in their grounding of abstract concepts. We replicate two property-generation experiments on 21 LLMs, and find strong evidence that **LLMs are not grounded in the same way humans are** — but of course they were not trained to be. In particular, LLMs exhibit systematic under-production of internal-state properties and over-production of abstract ones, and overall very poor Pearson correlation with humans, while they correlate well with each other. These failures are uniform across LLM families and do not improve with scale. In a replicated rating experiment, LLMs exhibit a reasonable understanding of concept categories, and in fact SAE features selective for such categories exist in Gemma-3-4B and Gemma-3-12B, in evidence that grounding structure is encoded internally in LLMs even though it may not behaviorally expressed. Going forward, our results suggest that grounding alignment with humans may be an interesting and novel quantity that is invisible to current testing benchmarks, and may be worth watching in the future. And finally, further scaling or better text-based training will probably not close the gap, so we may need to rethink the way we design and train LLMs.

References

M. Abdou, A. Kulmizev, D. Hershcovich, S. Frank, E. Pavlick, and A. Søgaard. Can language models encode perceptual structure without grounding? a case study in color. In *Proceedings of the 25th Conference on Computational Natural Language Learning (CoNLL)*, 2021. URL `https://aclanthology.org/2021.conll-1.9/`.

L. W. Barsalou. Perceptual symbol systems. *Behavioral and Brain Sciences*, 22(4):577–660, 1999. doi: 10.1017/S0140525X99002149.

L. W. Barsalou. Grounded cognition. In M. C. Frank and A. Majid, editors, *Open Encyclopedia of Cognitive Science*. MIT Press, 2026. URL `https://oecs.mit.edu/pub/9iq4376o`.

L. W. Barsalou and K. Wiemer-Hastings. Situating abstract concepts. In D. Pecher and R. A. Zwaan, editors, *Grounding Cognition: The Role of Perception and Action in Memory, Language, and Thought*, pages 129–163. Cambridge University Press, 2005. doi: 10.1017/CBO9780511499968.0 07.

E. M. Bender and A. Koller. Climbing towards NLU: On meaning, form, and understanding in the age of data. In D. Jurafsky, J. Chai, N. Schluter, and J. Tetreault, editors, *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5185–5198, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.463. URL `https://aclanthology.org/2020.acl-main.463/`.

E. M. Bender, T. Gebru, A. McMillan-Major, and S. Shmitchell. On the dangers of stochastic parrots: Can language models be too big? In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '21, page 610–623, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450383097. doi: 10.1145/3442188.3445922. URL `https://doi.org/10.1145/3442188.3445922`.

A. M. Borghi, F. Binkofski, C. Castelfranchi, F. Cimatti, C. Scorolli, and L. Tummolini. The challenge of abstract concepts. *Psychological Bulletin*, 143(3):263–292, 2017. doi: 10.1037/bul0000089.

T. Bricken, A. Templeton, J. Batson, B. Chen, A. Jermyn, T. Conerly, N. Turner, C. Anil, C. Denison, A. Askell, R. Lasenby, Y. Wu, S. Kravec, N. Schiefer, T. Maxwell, N. Joseph, Z. Hatfield-Dodds, A. Tamkin, K. Nguyen, B. McLean, J. E. Burke, T. Hume, S. Carter, T. Henighan, and C. Olah. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2023. https://transformer-circuits.pub/2023/monosemantic-features/index.html.

R. A. Brooks. Intelligence without representation. *Artificial Intelligence*, 47(1):139–159, 1991. ISSN 0004-3702. doi: https://doi.org/10.1016/0004-3702(91)90053-M. URL `https://www.sciencedirect.com/science/article/pii/000437029190053M`.

M. Brysbaert, A. B. Warriner, and V. Kuperman. Concreteness ratings for 40 thousand generally known English word lemmas. *Behavior Research Methods*, 46(3):904–911, 2014. doi: 10.3758/s1 3428-013-0403-5.

H. D. Critchley, S. Wiens, P. Rotshtein, A. Öhman, and R. J. Dolan. Neural systems supporting interoceptive awareness. *Nature Neuroscience*, 7(2):189–195, 2004. doi: 10.1038/nn1176.

V. Diveica, P. M. Pexman, and R. J. Binney. Quantifying social semantics: An inclusive definition of socialness and ratings for 8,388 English words. *Behavior Research Methods*, 55:461–473, 2023. doi: 10.3758/s13428-022-01810-x.

A. Ettinger. What BERT is not: Lessons from a new suite of psycholinguistic diagnostics for language models. *Transactions of the Association for Computational Linguistics*, 8:34–48, 2020. doi: 10.1162/tacl_a_00298.

P. Fung, Y. Bachrach, A. Celikyilmaz, K. Chaudhuri, D. Chen, W. Chung, E. Dupoux, H. Gong, H. Jégou, A. Lazaric, et al. Embodied ai agents: Modeling the world. *arXiv preprint arXiv:2506.22355*, 2025.

W. Gurnee and M. Tegmark. Language models represent space and time. In B. Kim, Y. Yue, S. Chaudhuri, K. Fragkiadaki, M. Khan, and Y. Sun, editors, *International Conference on Learning Representations*, volume 2024, pages 2483–2503, 2024. URL `https://proceedings.iclr.c c/paper_files/paper/2024/file/0a6059857ae5c82ea9726ee9282a7145-Paper-Con ference.pdf`.

M. Harpaintner, N. M. Trumpp, and M. Kiefer. The semantic content of abstract concepts: A property listing study of 296 abstract words. *Frontiers in Psychology*, 9:1748, 2018. doi: 10.3389/fpsyg.20 18.01748.

O. Hauk, I. Johnsrude, and F. Pulvermüller. Somatotopic representation of action words in human motor and premotor cortex. *Neuron*, 41(2):301–307, 2004. doi: 10.1016/S0896-6273(03)00838-9.

J. Hoffmann, S. Borgeaud, A. Mensch, E. Buchatskaya, T. Cai, E. Rutherford, D. de Las Casas, L. A. Hendricks, J. Welbl, A. Clark, T. Hennigan, E. Noland, K. Millican, G. van den Driessche, B. Damoc, A. Guy, S. Osindero, K. Simonyan, E. Elsen, O. Vinyals, J. W. Rae, and L. Sifre. Training compute-optimal large language models. In *Proceedings of the 36th International Conference on Neural Information Processing Systems*, NIPS '22, Red Hook, NY, USA, 2022. Curran Associates Inc. ISBN 9781713871088.

R. Huben, H. Cunningham, L. R. Smith, A. Ewart, and L. Sharkey. Sparse autoencoders find highly interpretable features in language models. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=F76bwRSLeK`.

A. E. Kelly, Y. N. Kenett, J. D. Medaglia, J. J. Reilly, P. Dudhat, and E. G. Chrysikou. Conceptual structure of emotions. *Emotion*, 24(6):1550–1561, 2024. doi: 10.1037/emo0001327.

G. Lakoff and M. Johnson. *Metaphors We Live By*. University of Chicago Press, 2003. ISBN 9780226470993. doi: 10.7208/chicago/9780226470993.001.0001. URL `http://dx.doi.org/1 0.7208/chicago/9780226470993.001.0001`.

B. Li. Incompressible knowledge probes: Estimating black-box llm parameter counts via factual capacity. *arXiv preprint arXiv:2604.24827*, 2026.

K. Li, A. K. Hopkins, D. Bau, F. Viégas, H. Pfister, and M. Wattenberg. Emergent world representations: Exploring a sequence model trained on a synthetic task. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id= DeG07_TcZvT`.

T. Lieberum, S. Rajamanoharan, A. Conmy, L. Smith, N. Sonnerat, V. Varma, J. Kramar, A. Dragan, R. Shah, and N. Nanda. Gemma scope: Open sparse autoencoders everywhere all at once on gemma 2. In Y. Belinkov, N. Kim, J. Jumelet, H. Mohebbi, A. Mueller, and H. Chen, editors, *Proceedings of the 7th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*, pages 278–300, Miami, Florida, US, Nov. 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.blackboxnlp-1.19. URL `https://aclanthology.org/2024.blackb oxnlp-1.19/`.

D. Lynott, L. Connell, M. Brysbaert, J. Brand, and J. Carney. The Lancaster sensorimotor norms: multidimensional measures of perceptual and action strength for 40,000 English words. *Behavior Research Methods*, 52:1271–1291, 2020. doi: 10.3758/s13428-019-01316-z.

M. Mancano and C. Papagno. Emotional and social dimension of abstract concepts meet with interoception in right anterior insula. *Journal of Neuroscience*, 46(2):e0238252025, 2026. doi: 10.1523/JNEUROSCI.0238-25.2025.

C. McDougall, A. Conmy, J. Kramár, T. Lieberum, S. Rajamanoharan, and N. Nanda. Gemma scope 2 - technical paper. Technical report, Google DeepMind, Sept. 2025. `https://storage.google apis.com/deepmind-media/DeepMind.com/Blog/gemma-scope-2-helping-the-ai-s afety-community-deepen-understanding-of-complex-language-model-behavior/ Gemma_Scope_2_Technical_Paper.pdf`.

K. McRae, G. S. Cree, M. S. Seidenberg, and C. McNorgan. Semantic feature production norms for a large set of living and nonliving things. *Behavior Research Methods*, 37(4):547–559, 2005. doi: 10.3758/BF03192726.

N. Nanda, A. Lee, and M. Wattenberg. Emergent linear representations in world models of self-supervised sequence models. In Y. Belinkov, S. Hao, J. Jumelet, N. Kim, A. McCarthy, and H. Mohebbi, editors, *Proceedings of the 6th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*, pages 16–30, Singapore, Dec. 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.blackboxnlp-1.2. URL `https://aclanthology.org/202 3.blackboxnlp-1.2/`.

N. Panickssery, N. Gabrieli, J. Schulz, M. Tong, E. Hubinger, and A. Turner. Steering LLaMA 2 via contrastive activation addition. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15504–15522. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.acl-long.828.

S. Pezzelle, E. Takmaz, and R. Fernández. Word representation learning in multimodal pre-trained transformers: An intrinsic evaluation. *Transactions of the Association for Computational Linguistics (TACL)*, 9:1563–1579, 2021. URL `https://aclanthology.org/2021.tacl-1.93/`.

F. Pulvermüller. Brain mechanisms linking language and action. *Nature Reviews Neuroscience*, 6(7): 576–582, 2005. doi: 10.1038/nrn1706.

G. G. Scott, A. Keitel, M. Becirspahic, B. Yao, and S. C. Sereno. The Glasgow norms: ratings of 5,500 words on nine scales. *Behavior Research Methods*, 51:1258–1270, 2019. doi: 10.3758/s134 28-018-1099-3.

N. Sofroniew, I. Kauvar, W. Saunders, R. Chen, T. Henighan, S. Hydrie, C. Citro, A. Pearce, J. Tarng, W. Gurnee, J. Batson, S. Zimmerman, K. Rivoire, K. Fish, C. Olah, and J. Lindsey. Emotion concepts and their function in a large language model, 2026. URL `https://arxiv.org/abs/ 2604.07729`.

S. Suresh, K. Mukherjee, X. Yu, W.-C. Huang, L. Padua, and T. T. Rogers. Conceptual structure coheres in human cognition but not in large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 722–738, 2023. URL `https://aclanthology.org/2023.emnlp-main.47/`.

A. Templeton, T. Conerly, J. Marcus, J. Lindsey, T. Bricken, B. Chen, A. Pearce, C. Citro, E. Ameisen, A. Jones, H. Cunningham, N. L. Turner, C. McDougall, M. MacDiarmid, C. D. Freeman, T. R. Sumers, E. Rees, J. Batson, A. Jermyn, S. Carter, C. Olah, and T. Henighan. Scaling monosemanticity: Extracting interpretable features from claude 3 sonnet. *Transformer Circuits Thread*, 2024. URL `https://transformer-circuits.pub/2024/scaling-monosemanticity/index.h tml`.

C. Tigges, O. J. Hollinsworth, A. Geiger, and N. Nanda. Language models linearly represent sentiment. In Y. Belinkov, N. Kim, J. Jumelet, H. Mohebbi, A. Mueller, and H. Chen, editors, *Proceedings of the 7th BlackboxNLP Workshop: Analyzing and Interpreting Neural Networks for NLP*, pages 58–87, Miami, Florida, US, Nov. 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.blackboxnlp-1.5. URL `https://aclanthology.org/2024.blackbox nlp-1.5/`.

J. Troche, S. J. Crutch, and J. Reilly. Defining a conceptual topography of word concreteness: Clustering properties of emotion, sensation, and magnitude among 750 English words. *Frontiers in Psychology*, 8:1787, 2017. doi: 10.3389/fpsyg.2017.01787.

S. Trott. Can large language models help augment english psycholinguistic datasets? *Behavior Research Methods*, 56(6):6082–6100, Jan. 2024. doi: 10.3758/s13428-024-02337-z. URL `http://dx.doi.org/10.3758/s13428-024-02337-z`.

A. M. Turner, L. Thiergart, G. Leech, D. Udell, J. J. Vazquez, U. Mini, and M. MacDiarmid. Steering language models with activation engineering, 2024. URL `https://arxiv.org/abs/2308.102 48`.

C. Villani, L. Lugli, M. T. Liuzza, and A. M. Borghi. Varieties of abstract concepts and their multiple dimensions. *Language and Cognition*, 11(3):403–430, 2019. doi: 10.1017/langcog.2019.23.

C. Wang, Y. Zhang, R. Yu, Y. Zheng, L. Gao, Z. Song, Z. Xu, G. Xia, H. Zhang, D. Zhao, and X. Chen. Do LLMs "feel"? emotion circuits discovery and control, Oct. 2025a. URL `https://arxiv.org/abs/2510.11328`.

Y. Wang, D. Liang, and Y. Zeng. Cognitive alignment between humans and llms across multimodal domains, Jan. 2025b. URL `https://www.researchsquare.com/article/rs-5736241/v1`. Research Square preprint.

J. Wei, Y. Tay, R. Bommasani, C. Raffel, B. Zoph, S. Borgeaud, D. Yogatama, M. Bosma, D. Zhou, D. Metzler, E. H. Chi, T. Hashimoto, O. Vinyals, P. Liang, J. Dean, and W. Fedus. Emergent abilities of large language models. *Transactions on Machine Learning Research*, 2022. ISSN 2835-8856. URL `https://openreview.net/forum?id=yzkSU5zdwD`. Survey Certification.

X. Wu, H. Wang, Z. Yan, X. Tang, P. Xu, W.-T. Siok, P. Li, J.-H. Gao, B. Lyu, and L. Qin. Ai shares emotion with humans across languages and cultures, 2025. URL `https://arxiv.org/abs/25 06.13978`.

Q. Xu, Y. Peng, S. A. Nastase, M. Chodorow, M. Wu, and P. Li. Large language models without grounding recover non-sensorimotor but not sensorimotor features of human concepts. *Nature Human Behaviour*, 9:1871–1886, 2025. doi: 10.1038/s41562-025-02203-8.

L. Zheng, W.-L. Chiang, Y. Sheng, S. Zhuang, Z. Wu, Y. Zhuang, Z. Lin, Z. Li, D. Li, E. Xing, H. Zhang, J. Gonzalez, and I. Stoica. Judging llm-as-a-judge with mt-bench and chatbot arena, 2023. URL `https://proceedings.neurips.cc/paper_files/paper/2023/file/91f18 a1287b398d378ef22505bf41832-Paper-Datasets_and_Benchmarks.pdf`.

A LLMs-as-coders for property-generation experiments

A.1 Benchmarking LLMs-as-coders

In this section, we evaluate the performance of LLMs on the downstream task of automated property coding. Our methodology builds upon the established "LLM-as-a-judge" paradigm [Zheng et al., 2023]. However, deploying LLMs as coders presents a more straightforward, and arguably more reliable, framework than using them as evaluative judges. A typical LLM-judge must typically surpass the candidate model in reasoning capabilities to accurately score its output, while a LLM-coder merely has to be able to classify the properties properly. This coding task is fundamentally a simplified variation of the rating task detailed in Section 4, a domain where we have already demonstrated robust LLM performance. Furthermore, because this task involves classification rather than quality evaluation, it avoids the self-enhancement bias typically observed in LLM-as-judge setups [Zheng et al., 2023]. This lack of self-bias makes it methodologically sound to use the same model to both generate and subsequently code its own responses.

Data collection and benchmark creation. To rigorously benchmark the models as coders, we needed a substantial dataset of coded properties. Fortunately, Kelly et al. [2024] provides a large-scale public dataset: the complete $49,942$ word-property pairs produced in their experiment. For experiment 1, no such word-property pairs were provided, so an expert annotator labeled 2,077 pairs, which were generated by the older versions of the three frontier LLMs at the time (Claude-Opus 4.6, GPT-5.1, Gemini-3.0-Pro). We utilized these two datasets as our primary benchmarks to identify the optimal LLM coder for each experiment.

Validation metrics and human reference. For each candidate coder we report percentage agreement with the ground-truth label and Cohen's κ. The human reference for Experiment 1 is the 76.8% two-coder joint agreement reported by Harpaintner et al. [2018] on their original validation subset; Harpaintner et al. [2018] do not report a κ ceiling, so we leave that cell blank. For Experiment 2, the human reference is the 64.25% two-coder agreement and $\kappa = 0.52$ reported by Kelly et al. [2024].

To ensure deterministic coding results, we use temperature $T = 0.0$ for all LLM-coders.

Table 2: Experiment 1 coder leaderboard. Six LLM coders predict the 4-category property label on the 2077-pair ground truth. % Agreement is overall percentage agreement, κ is Cohen's kappa. Per-category columns are recall, i.e. the percentage of pairs labeled by the human as that category that the LLM also labeled as that category. [†]Human ceiling is the 76.8% two-coder joint agreement reported by Harpaintner et al. [2018]. **Gemini-2.5-Flash-Lite** was selected as the coder for all experiments with this dataset, unless otherwise specified.

Coder	% Agreement	κ	Sensorimotor	Emotion	Social	Association
Human ceiling[†]	*76.8*	–	–	–	–	–
Gemini 3.1 Pro	68.6	0.510	69.6	62.6	55.5	72.1
Claude Sonnet 4.6	67.6	0.492	55.6	68.5	57.3	76.9
Gemini 2.5 Flash-Lite	67.2	0.505	66.2	75.9	62.1	67.1
Gemini 2.5 Flash	65.6	0.484	77.0	60.6	63.0	60.3
GPT-OSS 120B	64.4	0.477	76.0	66.5	68.6	55.9
GPT-5 mini	64.2	0.486	87.5	68.0	67.8	48.6

Error margins for Gemini-2.5-Flash-Lite as a coder. The Experiment 1 coder benchmark in Table 2 measures property-level agreement, but the Experiment 1 leaderboard actually consumes the per-word category-frequency vector and its Pearson r against the human norms. To estimate the error coder substitution introduces at that leaderboard level, we re-coded the single hand-coded run of three reference generation models (Claude Opus 4.6, Gemini 3.1 Pro, GPT-5.4) with both Flash-Lite and the human ground truth on the exact same (word, property) pairs and bootstrapped the difference over words (1000 paired iterations, same resampled words for both coders within an iteration so that $\Delta = (\text{Flash-Lite} - \text{Human})$ is a paired statistic). The Mean r a human coder would have produced has a cross-model average difference from the LLM-coder values of $\Delta = +0.014 \pm 0.019$, with every model 95% CI containing zero. On the same property pairs the cross-model average frequency

Table 3: Experiment 2 coder leaderboard. % Agreement and κ are computed against the $49,592$ gold human-coded labels. [†]Human ceiling is the 64.25% two-coder agreement and $\kappa = 0.52$ reported by Kelly et al. [2024]. **Gemini-2.5-Flash** was selected as the coder for all experiments with this dataset, unless otherwise specified.

Coder	% Agreement	κ
Human ceiling[†]	*64.25*	*0.52*
Gemini 2.5 Flash	69.3	0.579
GPT-OSS 120B	65.4	0.510
Gemma 3 12B	60.9	0.476
Gemini 2.5 Flash-Lite	60.2	0.484

Δ's are $+2.3\%$ Sensorimotor, -0.1% Internal, -0.5% Social, -1.7% Verbal Association, with every per-model 95% CI containing zero. So the per-category attribution rates a human coder would have produced are within roughly ±2 percentage points of the Flash-Lite values.

B Extended results for Experiment 1

Here we present extended quantitative results for the first experiment (Section 3.2) based on the Harpaintner et al. [2018] dataset.

B.1 Detailed model setup

We evaluate 21 LLMs spanning closed-weight frontier and open-weight families. All generations use each provider's default sampling temperature. Coding is performed at $T = 0.0$ for determinism (Section A.1).

The closed-weight models are accessed through their official APIs: **Anthropic** (Claude Opus 4.6, Claude Sonnet 4.6, Claude Haiku 4.5), **OpenAI** (GPT-5.4), and **Google** (Gemini 3.1 Pro, Gemini 3 Flash, Gemini 3.1 Flash-Lite, Gemini 2.5 Flash, Gemini 2.5 Flash-Lite). The open-weight models are run on 8x Quadro RTX 6000 GPUs, with model-parallel sharding for the 70B and 120B systems: **Meta** (Llama 3.1 70B Instruct, Llama 3.1 8B Instruct), **OpenAI open-weights** (GPT-OSS 120B, GPT-OSS 20B), **Google open-weights** (Gemma-3-27B-IT, Gemma-3-12B-IT, Gemma-3-4B-IT), and **Alibaba Qwen** (Qwen3 8B, Qwen3 4B, Qwen3-VL 30B, Qwen3-VL 8B, Qwen3-VL 4B).

Each model produces 10 independent runs over the full 293-word Harpaintner stimulus set. Per-word category-frequency vectors are averaged across runs before correlating with the human norms; $\pm$ values reported in the leaderboard are bootstrap standard deviations over 1000 resamples of the runs (Section E.2).

B.2 Detailed results for all 21 models

Figure 6 presents the frequency profiles for all models. Table 4 details the performance of all 21 models evaluated in our panel. Smaller models occasionally outperform substantially larger ones, suggesting that simply increasing parameter count does not organically close the grounding gap.

C Extended results for Experiment 2

Here we present extended quantitative results for the second experiment (Section 3.2) based on the Kelly et al. [2024] dataset. The Kelly stimulus set partitions the 357 target words into three matched conditions: 118 abstract emotion words, 118 abstract non-emotion words, and 119 concrete words. The main text reports alignment on the combined 236-word abstract subset (emotion plus non-emotion). For completeness, in this appendix we also report the leaderboard restricted to the 119-word concrete subset, which serves as a control condition: concrete nouns are the easy case for property generation, since they admit clearly perceptual properties that all candidate models recover well.

Figure 6: Property-frequency boxplots for all 21 LLMs, sorted by Mean r.

Table 4: Full experiment 1 leaderboard, all 21 models in the panel, sorted by Mean r. Ten generation runs per model (Claude Haiku 4.5: nine). Bold marks the column max.

Rank	Model	Mean r	Sensorimotor	Internal	Social	Verbal
	Estimated human ceiling	*0.974*	*0.966*	*0.964*	*0.971*	*0.992*
1	Llama 3.1 70B	**0.375**	0.344	**0.464**	0.424	0.267
2	Qwen3 8B	0.373	**0.351**	0.390	**0.462**	**0.288**
3	Gemini 2.5 Flash-Lite	0.348	0.276	0.382	0.456	0.278
4	Qwen3 4B	0.314	0.335	0.405	0.318	0.200
5	GPT-OSS 20B	0.302	0.326	0.255	0.429	0.196
6	GPT-5.4	0.301	0.332	0.258	0.400	0.213
7	Gemini 2.5 Flash	0.296	0.291	0.310	0.364	0.218
8	Qwen3-VL 4B	0.295	0.344	0.251	0.326	0.260
9	Gemma-3-12B	0.292	0.277	0.283	0.357	0.251
10	Qwen3-VL 30B	0.292	0.278	0.240	0.412	0.237
11	Llama 3.1 8B	0.283	0.186	0.356	0.406	0.185
12	Claude Sonnet 4.6	0.277	0.287	0.242	0.352	0.225
13	Qwen3-VL 8B	0.273	0.313	0.256	0.325	0.199
14	Gemma-3-4B	0.270	0.279	0.266	0.291	0.244
15	Claude Opus 4.6	0.264	0.203	0.205	0.362	0.284
16	Claude Haiku 4.5	0.257	0.251	0.191	0.310	0.276
17	Gemini 3.1 Pro	0.256	0.307	0.163	0.383	0.171
18	Gemini 3.1 Flash-Lite	0.223	0.264	0.134	0.279	0.216
19	Gemini 3 Flash	0.216	0.251	0.182	0.294	0.137
20	GPT-OSS 120B	0.199	0.210	0.238	0.230	0.116
21	Gemma-3-27B	0.196	0.262	0.115	0.262	0.144

Properties are classified by Gemini-2.5-Flash into the four superordinate Kelly categories: **Taxonomic**, **Entity**, **Situation**, and **Introspective**. Each model produces 10 runs over the full 357-word stimulus set; per-concept category-frequency vectors are averaged across runs before correlating with the human reference distribution. The primary metric is Pearson r between the per-concept distributions of the model and the human aggregate, computed separately on the abstract and concrete subsets.

Figure 7 replicates the scaling plot for the Experiment 2 setup: even the strongest models reach only Mean $r \approx 0.36$ on the abstract subset, far below the human-to-human ceiling of $r \approx 0.91$, and there is no monotonic trend in parameter count. Table 5 lists every model on both subsets sorted by abstract Pearson r. The pattern mirrors Experiment 1: the abstract-subset gap remains roughly flat across model sizes and providers, while the same models reach much higher alignment ($r \in [0.29, 0.53]$) on the concrete subset. This contrast is consistent with the central claim of the paper: the gap is specific to abstract concepts, not a general property-generation deficit. Figure 8 confirms this from a different angle: on the concrete subset the human-to-model and model-to-model correlations sit in similar ranges, whereas on the abstract subset (Fig. 3 in the main text) models are much more correlated with each other than with humans.

D   Rating experiment additional results

Task.   We replicate the rating study of Troche et al. [2017] using 751 English nouns rated on 14 Abstract Conceptual Grounding (ACG) dimensions under the uniform framing *"I relate this word to [X]"*, with responses on a 1 to 7 Likert scale (1 = Strongly Disagree, 7 = Strongly Agree). Each model produces ten rating seeds; per-word ratings are averaged across seeds before correlating with the human norms. The primary metric is the Pearson r averaged over the 14 dimensions. Following the original study, the 14 dimensions are organised into three components: **Sensory** (Color, Taste/Smell, Tactile, Visual Form, Auditory), **Internal** (Emotion, Polarity, Social, Morality, Thought, Self-Motion), and **Magnitude** (Space, Quantity, Time). Table 6 reports the per-component Pearson correlations alongside the overall Mean r for every model out of the 21.

Results.   Three patterns stand out in Table 6, and each one provides a different angle on the grounding gap reported in the main text.

Figure 7: Mean r for all LLMs vs. the human ceiling on Experiment 2 [Kelly et al., 2024]. Parameter count for closed models is based on estimations from Li [2026].

Table 5: Extended leaderboard on experiment 2 Kelly et al. [2024], for both the abstract and concrete subsets. Models are sorted by Pearson r on the abstract subset.

Model	Abstract	Concrete
Human ceiling	*0.909 ± 0.015*	*0.920 ± 0.008*
Gemini 2.5 Flash-Lite	**0.361 ± 0.009**	0.488 ± 0.014
Gemma 3 12B	0.348 ± 0.011	0.393 ± 0.010
Qwen 3 8B	0.317 ± 0.009	0.417 ± 0.016
Gemma 3 4B	0.309 ± 0.008	0.423 ± 0.015
GPT-5.4	0.281 ± 0.009	0.482 ± 0.012
Claude Haiku 4.5	0.271 ± 0.014	0.358 ± 0.025
Gemma 3 27B	0.259 ± 0.008	0.447 ± 0.016
Claude Opus 4.6	0.241 ± 0.007	0.467 ± 0.013
Gemini 3.1 Flash-Lite	0.241 ± 0.007	0.465 ± 0.012
Qwen 3-VL 30B	0.237 ± 0.012	0.452 ± 0.027
Llama 3.1 70B	0.232 ± 0.011	0.469 ± 0.017
Qwen 3-VL 8B	0.224 ± 0.014	0.420 ± 0.061
Qwen 3 4B	0.218 ± 0.012	0.316 ± 0.035
GPT-OSS 20B	0.212 ± 0.014	0.287 ± 0.020
Gemini 2.5 Flash	0.199 ± 0.012	**0.531 ± 0.018**
Qwen 3-VL 4B	0.186 ± 0.014	0.352 ± 0.023
GPT-OSS 120B	0.181 ± 0.012	0.401 ± 0.021
Llama 3.1 8B	0.178 ± 0.018	0.344 ± 0.034
Gemini 3.1 Pro	0.170 ± 0.012	0.526 ± 0.017
Claude Sonnet 4.6	0.169 ± 0.007	0.436 ± 0.013
Gemini 3 Flash	0.158 ± 0.013	0.463 ± 0.023

The first observation is that the strongest models are essentially at the human ceiling on this task. Claude Sonnet 4.6 reaches Mean $r = 0.760$ against a cross-dimension human ceiling of approximately 0.78 (Appendix F), and the next six models in Table 6 all sit within 0.04 of that mark. The same models top out at $r \approx 0.37$ on the property generation task of Experiment 1 against a ceiling of 0.97 (Table 4), an order-of-magnitude larger gap to the human reference. We take the contrast as direct evidence for the central claim of the paper: when a grounding dimension is named explicitly in the prompt, current LLMs can recover it; the gap is therefore specific to the spontaneous property generation setting and is not a general inability to register sensorimotor, internal, or social content.

The second observation is that scaling helps recognition, but only on a subset of the components. Within every open-weight family we tested, the Sensory component improves dramatically with model size: Gemma scales from -0.086 at 4B to 0.704 at 27B, Llama scales from -0.161 at 8B

Figure 8: Experiment 2 properties correlation heatmap for the concrete word subset. The correlation between LLMs–humans is closer to LLMs-LLMs in this case, compared to Fig. 3.

Table 6: Rating experiment results for all 21 models. Mean r is the average of the 14 per-dimension Pearson correlations against the human ratings.

Model	Mean r	Sensory	Motor	Internal	Social	Magnitude
Claude Sonnet 4.6	0.760	0.839	0.583	0.787	0.827	0.628
Claude Opus 4.6	0.755	0.868	0.393	0.779	0.812	0.637
Gemini 3 Flash	0.730	0.889	0.189	0.750	0.793	0.600
Gemini 2.5 Flash	0.720	0.872	0.229	0.740	0.813	0.574
Gemini 3.1 Pro	0.719	0.883	0.119	0.753	0.790	0.576
GPT-5.4	0.717	0.846	0.432	0.733	0.737	0.567
Llama 3.1 70B	0.707	0.729	0.495	0.754	0.832	0.637
Gemma 3 27B	0.706	0.704	0.614	0.775	0.829	0.606
Qwen 3 8B	0.703	0.807	0.375	0.717	0.828	0.580
GPT-OSS 20B	0.701	0.757	0.513	0.712	0.825	0.613
GPT-OSS 120B	0.695	0.709	0.512	0.745	0.837	0.617
Gemini 2.5 Flash-Lite	0.679	0.719	0.434	0.743	0.787	0.572
Gemini 3.1 Flash-Lite	0.677	0.829	-0.058	0.686	0.794	0.618
Claude Haiku 4.5	0.672	0.801	0.071	0.711	0.768	0.571
Qwen 3-VL 30B	0.665	0.641	0.604	0.712	0.827	0.607
Gemma 3 12B	0.559	0.326	0.693	0.758	0.811	0.554
Qwen 3-VL 8B	0.517	0.300	0.557	0.693	0.764	0.551
Qwen 3 4B-2507	0.507	0.321	0.540	0.687	0.703	0.499
Qwen 3-VL 4B	0.457	0.192	0.539	0.682	0.740	0.479
Llama 3.1 8B	0.341	-0.161	0.528	0.736	0.710	0.464
Gemma 3 4B	0.297	-0.086	0.491	0.588	0.580	0.391

to 0.729 at 70B, and Qwen3 scales from 0.321 at 4B to 0.807 at 8B (Table 6). The Magnitude component shifts up by a comparable margin within each family. The Internal and Social components, by contrast, are essentially flat across model sizes: every model in Table 6 sits in the range $[0.58, 0.84]$ on these two components, regardless of parameter count or provider. Recognition of affective and social content is therefore not a capability bottleneck at any scale we tested. Perceptual grounding, on the other hand, is recoverable only at sufficient scale, and once that scale is reached the model can rate perceptual content as well as humans do.

The third observation is that the Motor sub-dimension is a persistent weakness that scaling does not close. As shown in Table 6, the strongest closed-weight models all score weakly on Motor, with Gemini 3.1 Pro at 0.119, Gemini 3 Flash at 0.189, Claude Opus 4.6 at 0.393, and Gemini 3.1 Flash-Lite even falling below zero at -0.058. More importantly, the within-family scaling that lifts Sensory does not lift Motor: Gemma improves only modestly from 0.491 at 4B to 0.614 at 27B (with 12B sitting higher than 27B at 0.693), Llama actually drops from 0.528 at 8B to 0.495 at 70B, and Qwen3 drops from 0.540 at 4B to 0.375 at 8B.

Figure 9: Mean Pearson r vs. number of runs averaged, on Experiment 1, for GEMMA-3-4B-IT coded by Gemini-2.5-Flash-Lite. Solid line: mean over 50 random subsets at each subset size; band: ± 1 std across subsets; dashed: 100-run asymptote; dotted: the 10-run cadence used by the Experiment 1 leaderboard.

E   Variance and uncertainty in Experiment 1

The Experiment 1 leaderboard reports each model's Mean Pearson r as the point estimate from 10 independent generation runs, plus a bootstrap standard deviation. Two questions a reader is right to ask: (i) is a 10-run point estimate close to the asymptote that the same model would reach with infinitely many runs, and (ii) what does the bootstrap $\pm$ bar actually quantify? We answer both empirically by running GEMMA-3-4B-IT 100 times on the full 293-word Harpaintner pool, treating that aggregate as the ground truth, and comparing it to what we would have estimated from random 10-run subsets of the same data.

E.1   Convergence: how accurate is the 10-run estimate?

Figure 9 plots Mean r as a function of the number of runs averaged, with shaded ± 1 std bands over 50 random subsets at each subset size. The estimate climbs monotonically toward the 100-run asymptote of $r = +0.322$. At the Experiment 1 leaderboard cadence of 10 runs, the average estimate is $r = +0.309$, lower than the asymptote by $\Delta r = +0.013$.

The curve has two practical implications. *For absolute r values on a single model*, a 10-run point estimate sits about 0.01 below the asymptote it would converge to, so quoted r values are slightly conservative. *For ranking models against each other*, this bias is approximately constant across models, so the relative ordering on the 10-run Experiment 1 leaderboard is stable.

E.2   Bootstrap calibration

The Experiment 1 leaderboard's $\pm$ value next to each model's Mean r is a bootstrap standard deviation computed from $N_{\text{boot}} = 1000$ resamples of the 10 runs with replacement. For each resample we re-aggregate the per-word frequencies, recompute Mean r against the human norms, and take the standard deviation of the resulting distribution.

F   Estimation of human correlation ceilings

Each experiment reports a per-category Pearson r human ceiling, defined as the correlation between two independent panels of N raters scored on the same stimuli. This is the largest r a noiseless model could expect to reach against the published norms, which are themselves panel means. We obtain it in one of two ways depending on what each original study released. Kelly et al. [2024] provides participant-level responses, so we compute the ceiling by direct resampling. Harpaintner et al. [2018] and Troche et al. [2017] release only per-word means and SDs, so we estimate the ceiling from those

aggregates using the standard ICC+Spearman–Brown chain: ICC_1 recovers single-rater reliability from the ratio of between-word to total variance, and Spearman–Brown projects single-rater reliability up to the N-vs-N scale via $r_{full} = 2r_{split}/(1 + r_{split})$. We always report r_{full}, because the human norm against which models are correlated is a full-panel mean rather than a single rater.

F.1 Experiment 2: empirical split-half

We draw 1000 random half-splits of the participants per concept (median $N\approx30$ raters across 357 concepts), compute per-concept property-category percentages on each half, and average Pearson r across splits. Spearman–Brown then projects the half-panel correlation to $r_{full} = 0.909$ on the 236-word abstract subset used in the main text and $r_{full} = 0.968$ on the 119-word concrete subset used in the appendix.

F.2 Validation of the ceiling estimation

Experiment 2 is the only dataset where both methods are available on the same data, since the participant-level release also yields per-word means and SDs. Applying the ICC+SB chain we use for the other experiments to the Experiment 2 category-frequency matrix gives a within-dataset cross-check on the estimate.

Table 7: ICC+Spearman–Brown analytical estimate vs. 1000-split empirical ceiling on Experiment 2, both at r_{full} scale.

Slice	ICC+SB	Empirical	$|\Delta|$
Abstract (236 words)	0.916	0.909	0.007
Concrete (119 words)	0.969	0.968	0.001

The two methods agree to within 0.007 on both slices, with the analytical estimate sitting fractionally above the empirical ceiling. We therefore consider the ICC+SB ceilings reported below as accurate to within ~0.01.

Experiment 1 ceilings. Harpaintner et al. [2018] publish per-word frequencies in four aggregate categories. The resulting r_{full} ceilings are:

Sensorimotor: 0.966, Internal: 0.964, Social: 0.971, Verbal: 0.992 ($\overline{r}_{full} = 0.974$).

Rating-experiment ceilings. Troche et al. [2017] publish per-word means and SDs on each of the 14 grounding dimensions. We apply ICC+SB dimension-by-dimension with $\sigma^2_{between}$ from the cross-stimulus variance of per-word means, σ^2_{within} from the mean squared SD, and N from the median raters per word (≈ 24). The 14 r_{full} ceilings range from 0.62 on Polarity to 0.91 on Visual Form (cross-dimension mean 0.78).

G Prompting setup

This section presents verbatim every prompt used on the three experiments. The literal token {word} is substituted by each target concept on each call, and {properties} (in the coding prompts) by the comma-separated list of generated properties for that concept.

G.1 Property Generation Prompt (Experiment 1)

The generation prompt for Experiment 1 is shown below in Figure 10. It asks the model for exactly four spontaneous properties per noun, with one in-context example (*sympathy*). It follows the original property listing instructions of Harpaintner et al. [2018].

G.2 Property Generation Prompt (Experiment 2)

The generation prompt for Experiment 2 is shown below in Figure 11. It asks the model for exactly five spontaneous clues per noun, with two in-context examples (*dog* and *dejected*). It follows the human rater instructions in Appendix A of Kelly et al. [2024].

```
You will be performing a word generation task. For the given word '{word}', generate four
unique associations/situations/properties (referred to as 'properties') that come to mind as
spontaneously as possible. Avoid using synonyms. Your response should include only the word
and the four properties, formatted like this example:
word: sympathy
properties: hug, friends, joy, sun
```

Figure 10: Property generation prompt for Experiment 1 Harpaintner et al. [2018], reproduced verbatim. The placeholder `{word}` is replaced by each of the target nouns at inference time.

```
Your job is to define the word "{word}" so that another person, who will only be able to see
your definitions, is able to guess the word you were defining. You can think of this task as
a game in which you need to help your partner understand the meaning of a word that you know
but they don't by giving them clues.

List each clue on a separate numbered line. Clues can be single words or short phrases, but
each clue should contain as few words as possible. You should describe properties of the
idea the word refers to, including its physical features (such as how it looks, feels, or
sounds), where or when you might encounter or experience it, where or when it is used or
experienced, how it is used or experienced, or how it behaves. For example, for the two
words below you might give the following clues:

DOG: Pet, Animal, Has fur, Barks, 4 legs
DEJECTED: Slumped, Shoulders, After you've failed, Feel hopeless, No enthusiasm

A good response will, when all of the clues are combined, define or describe the idea the
word refers to as completely as possible. Keep in mind that your partner will need to guess
the exact word you defined, so try to give clues that will help them separate that word from
other, similar words. Although a word might be used multiple ways, list properties of the
most common usage (the one that you think of first when you read the word).

Remember that you should describe what the word means, and not the word itself — clues such
as "starts with a 't'" or "is a three-letter word" will not be used. Do not use similar
words, or synonyms, as clues. Also refrain from listing whatever comes to mind when you read
the word (e.g., "cat" for the word dog), as these associated things do not describe the
meaning of the word itself.

You must provide exactly 5 clues.

Word: {word}.
```

Figure 11: Property generation prompt used for Experiment 2 Kelly et al. [2024], reproduced verbatim. The placeholder `{word}` is replaced by each target concept at inference time.

G.3   Coding Prompt (Experiment 1)

Each generated property is assigned one of five mutually exclusive categories: **Sensorimotor feature** (a feature experienced by the senses); **Social constellation** (the coexistence or interaction of persons); **Internal state and emotion** (internal cognitive processes such as motivation, emotion, volition); **Association** (thematically or symbolically related but not descriptive); and **Other abstract concept** (an abstract feature that describes the concept). After coding, the two abstract categories: **Association** and **Other abstract concept** are merged to form the final abstract category **Verbal association**. The prompt provides a single in-context example (the *sympathy* properties from the generation prompt, one per category) and asks the coder to emit one labelled line per property. The full coding prompt is shown in Figure 12.

```
You are given an abstract word and four properties that refer to this word. You have to
classify each property into one of the following five categories.

Sensorimotor feature: A feature that can be experienced by our senses. It describes the
meaning of the abstract concept, or the abstract concept can be applied to this feature.
Social constellation: a feature or a situation that describes the coexistence of different
persons or which implies an interaction between at least two different persons.
Internal state and emotion: a feature or a situation that reflects internal, cognitive
processes (e.g., motivation, emotion, volition).
Association: a feature or a situation that does not describe the abstract concept, but which
is thematically or symbolically related to it.
Other abstract concept: an abstract feature that describes the abstract concept or to which
the abstract concept can be applied.

You must output each property and the category, formatted as in the following example
(Abstract word: sympathy, Properties: hug, friends, joy, sun).
hug: Sensorimotor feature
friends: Social constellation
joy: Internal state and emotion
sun: Association

Abstract word: {word}
Properties: {properties}
```

Figure 12: Coding prompt for Experiment 1. Categories are listed verbatim from Harpaintner et al. [2018]; {word} and {properties} are replaced at inference time by the concept and the comma-separated generated property list.

G.4 Rating Experiment Prompt

The rating experiment Troche et al. [2017] uses 14 affective conceptual grounding dimensions: *color, taste/smell, tactile, visual form, auditory, emotion, polarity, social, morality, thought, self-motion, space, quantity, time*. Every dimension uses the same instruction skeleton, with only the dimension specific statement substituted in. The full prompt for the *emotion* dimension is shown verbatim in Figure 13; the other thirteen dimensions are produced by replacing the sentence "I relate this word with human emotion." with the analogous sentence for the target dimension, taken verbatim from Troche et al. [2017]. The output is a list of (`'word', INT_SCORE`) tuples on a 1–7 Likert scale.

```
In this study we are selecting linguistic stimuli and we need evaluations on a series of
words. For each word, rate your level of agreement with the following statement:

"I relate this word with human emotion."

The scale ranges from 1 to 7, as follows:
Strongly Disagree <- 1      2      3      4      5      6      7 -> Strongly Agree

Keep in mind that the value of "1" corresponds to Strongly Disagree and value of "7"
to Strongly Agree. Please feel free to use the whole range of values provided. When
making your ratings, try to be as accurate as possible, but do not spend too much time
on any one word.

In each line of the output write only the word and its rating in a tuple like this:
('word', INT_SCORE).
```

Figure 13: Rating prompt for the Troche benchmark, shown for the *emotion* dimension. The same instruction skeleton is reused for all 14 dimensions; only the target sentence ("I relate this word with X.") changes between dimensions, with the wording for each dimension taken verbatim from Troche et al. [2017].

H   Extended mechanistic analysis results

H.1   Feature identification dataset construction

This appendix documents how we built the 426-noun balanced corpus used as the candidate pool for SAE feature identification (Section 5.1). Published norm sets cover individual dimensions of abstract-concept structure but no single resource gives us four balanced experiential categories on the same vocabulary, as well as Troche et al. [2017] does. But we did not want to use our test-set to discover features, so we had to look at other norms. Additionally, we wanted to use only the very highest words per category, and this meant that we neeeded a larger dataset to subsample only the highest ones. We therefore built our own noun corpus by combining four complementary datasets. Each category is anchored to one primary norm and a single thresholded metric as shown in Table 8 below, so that only the highest-scoring words per category are selected. A word that is not a noun or that satisfies thresholds for more than one grounded category is dropped from both. The final corpus comprises of 110 sensorimotor, 102 internal state, 102 social and 112 abstract nouns, for a total of 426 nouns.

Table 8: Norm sources and the metric extracted from each.

Norm	Source	Metric used
Lancaster Sensorimotor	Lynott et al. [2020]	Max across 6 modalities
Diveica Socialness	Diveica et al. [2023]	Socialness 1–7
Glasgow Norms	Scott et al. [2019]	$Arousal + |Valence-5|$
Brysbaert Concreteness	Brysbaert et al. [2014]	Concreteness 1–5

Table 9: Feature-identification corpus composition. Sensorimotor is further partitioned into 11 Lancaster sub-modalities at 10 words each (Visual, Auditory, Olfactory, Gustatory, Haptic, Interoception, Mouth, Head, Hand_arm, Foot_leg, Torso), enabling per-submodality stratification at the splitting stage.

Category	N	Primary source
Sensorimotor	110	Lancaster Norms (11 submodalities $\times$ 10)
Social	102	Diveica Socialness
Internal State	102	Glasgow
Abstract Baseline	112	Brysbaert (low concreteness)

Sentence generation   Each of the 426 nouns is paired with 10 context sentences that elicit the noun as the next token. Sentences are produced with Gemini-3.1-pro-preview at temperature 0. For example, for w=*surprise* one of the generated sentences is

> *"If you are feeling sad because you think everyone forgot your birthday, but then they jump out of the dark to make you smile, they have planned a ___".*

The blank is the position where the target noun was originally written.

The prompt instructs Gemini to write 10 numbered sentences ending with the target word, framed as a one-line riddle that makes the missing word easy to recover, and themed by the noun's category:

> *Write 10 numbered sentences about everyday life that end with the word '`<WORD>`'. Your goal in writing these sentences is to make sure that it is obvious that the sentence ends with this word, like a very simple and easy riddle to learn the word. You must also make sure that the sentence is aligned with the theme of '`<THEME>`'. Start your answer with '1. `<the first sentence>`'.*

The string for `<THEME>` is filled per subcategory (for Sensorimotor: Visual $\rightarrow$ "visual perception", Auditory $\rightarrow$ "auditory perception", etc.) or per category (Internal, Social). For Abstract nouns the theme clause is dropped: there is no grounded modality to anchor on, so we let Gemini choose any framing.

A regex post-processor then strips the target noun from the end of each generated line and verifies it is the same as the intended target. The final 3,521 successful rows generated for the 426 training nouns are released publicly.

Last-word-target probing: per-noun activation signatures Once the dataset is built, for each sentence in $S(w)$, we remove the target noun w and feed the resulting prefix to the model. The SAE activation is read at the last token of the prefix, i.e. the position where the model is about to emit w given everything before it. Per (layer, feature) we take the median across the 10 sentences. Any feature that has a non-zero median for five or more nouns from a single category is considered as a candidate for that category.

Why this construction. The setup ensures (i) The SAE sees a natural mid-sentence residual and therefore stays inside its training distribution, unlike isolated-token probes where many SAE features go silent. (ii) The residual at position $n-1$ is a read-out of the pre-next-token distribution conditioned on the preceding context, which is target-word-specific without requiring the model to actually emit the target. (iii) The aggregation is median over 10 diverse context sentences, which suppresses any single sentence's effect.

Identified features per layer. In Figure 14 we see the features that have at least one non-zero median noun activation in our dataset and the ones that have at least five activations from a single category: the candidates. The features that have only a single activation are of course substantially more: either they fired randomly, or they are very specific to that noun. We observe an interesting phenomenon: until layers 15-17 the model seems to be encoding mostly and understanding the context of the previous and current tokens, so it does not have many features that correspond to the next token content which is our interest. From layer 17 (where it has about 1500 features) and after we see that the number of specific features increases rapidly and at layer 24 it reaches 3500 features and stays constant, indicating that the model starts making decisions about the next word. On the other hand, the candidate features we selected exhibit a different behavior: they increase slightly but noticeably after layer 15 and then they remain constant, until a sudden step increase in the last layer. We hypothesize that this is because these features are mostly responsible for category-level decisions that have to do with the theme and context of the prefix, as intended by their selection process, and not so much for specific decisions dictated by linguistic or reasoning rules.

Figure 14: Number of SAE features per layer identified with our detection algorithm in Gemma-3-4B.

H.2 Feature validation

Feature interpretation. Determining the precise functionality of the features highly correlated with grounding dimensions remains challenging, as most lack an obvious semantic meaning. To facilitate interpretation and visualization, we provide links to Neuronpedia for representative features within each category. Additionally, we report automatic interpretations derived from our dataset activations using Claude-Opus-4.6. Note that the highest-correlated features discovered in our analysis are often not hosted on Neuronpedia, as the platform currently only supports a subset of layers (i.e., layers 9, 16, 22, and 29). Consequently, we present the best-performing features currently available.

Figure 15: Boxplot for steered model with sensory (top) and internal (bottom) features.

Importantly, while Neuronpedia typically displays the highest positive and negative logits for each feature, our analysis focuses on the highest positive *next-token* logits (i.e., the logits predicted for the token immediately following the active feature). This distinction stems from our dataset's construction and aligns more accurately with our primary task of property-generation.

Representative features from each category available on Neuronpedia:

- **Sensory** ($r = 0.575$)**:** Feature 193, Layer 22.[3]
  Auto-interpretation: Edible foods and gustatory/oral content.

- **Motion-Self** ($r = 0.426$)**:** Feature 132, Layer 29.[4]
  Auto-interpretation: Forceful or momentous events and qualities.

- **Internal** ($r = 0.647$)**:** Feature 472, Layer 29.[5]
  Auto-interpretation: Emotional and motivational states across positive and negative affect.

- **Social** ($r = 0.375$)**:** Feature 166, Layer 22.[6]
  Auto-interpretation: Family and kinship relations.

- **Time** ($r = 0.373$)**:** Feature 733, Layer 29[7].
  Auto-interpretation: Value-laden outcomes, advantages and setbacks.

Feature steering. For steering, we use clamping [Templeton et al., 2024] and we set the activation to double the median of the highest-activating noun from our identification dataset (Section 5.1). While this heuristic ensures a clear signal, it yields inconsistent intervention strengths. Specifically

---

[3]https://www.neuronpedia.org/gemma-3-4b-it/22-gemmascope-2-res-16k/193

[4]https://www.neuronpedia.org/gemma-3-4b-it/29-gemmascope-2-res-16k/132

[5]https://www.neuronpedia.org/gemma-3-4b-it/29-gemmascope-2-res-16k/472

[6]https://www.neuronpedia.org/gemma-3-4b-it/22-gemmascope-2-res-16k/166

[7]https://www.neuronpedia.org/gemma-3-4b-it/29-gemmascope-2-res-16k/733

for the internal-feature, we found it had unususally high max-activation and we kept it at 1x, because otherwise the model did not follow instructions properly.

In Figure 15 we present the boxplots for the Sensory and Internal features from above, compared against the baseline model. Both features lead to substantial shifts of the distribution of generated properties towards their target category, while the other categories decline or remain almost constant.