DEEP REPRESENTATIONS FOR TIME-VARYING BRAIN DATASETS

ABSTRACT

Finding an appropriate representation of dynamic activities in the brain is crucial for many downstream applications. Due to its highly dynamic nature, temporally averaged fMRI (functional magnetic resonance imaging) cannot capture the whole picture of underlying brain activities, and previous works lack the ability to learn and interpret the latent dynamics in brain architectures. In this paper, we build an efficient graph neural network model that incorporates both region-mapped fMRI sequences and structural connectivities obtained from DWI (diffusion-weighted imaging) as inputs. Through novel sample-level adaptive adjacency matrix learning and multi-resolution inner cluster smoothing, we find good representations of the latent brain dynamics. We also attribute inputs with integrated gradients, which enables us to infer (1) highly involved brain connections and subnetworks for each task (2) keyframes of imaging sequences along the temporal axis, and (3) subnetworks that discriminate between individual subjects. This ability to identify critical subnetworks that characterize brain states across heterogeneous tasks and individuals is of great importance to neuroscience research. Extensive experiments and ablation studies demonstrate our proposed method's superiority and efficiency in spatial-temporal graph signal modeling with insightful interpretations of brain dynamics.

1 INTRODUCTION

Neuroimaging techniques such as fMRI (functional magnetic resonance imaging) and DWI (diffusion-weighted imaging) provide a window into complex brain processes. Yet, modeling and understanding these signals has always been a challenge. Network neuroscience (Bassett & Sporns, 2017) views the brain as a multiscale networked system and models these signals in their graph representations: nodes represent brain ROIs (regions of interest), and edges represent either structural or functional connections between pairs of regions.

Recent works leverage variants of the Graph Neural Networks (Scarselli et al., 2009), making progress on identifying physiological characteristics and brain disorders. In Kim & Ye (2020), authors combine grad-CAM (Selvaraju et al., 2017) and GIN (Xu et al., 2018) to highlight brain regions that are responsible for gender classification with resting-state fMRI data. Li et al. (2020) utilizes the regularized pooling with GNN to identify fMRI biomarkers. Noman et al. (2021) embeds both topological structures and node signals of fMRI networks into low-dimensional latent representations for a better identification of depression. However, the first two works use time-averaged fMRI, losing rich dynamics in the temporal domain. The third combines nodes' temporal and feature dimensions instead of handling them separately, leading to a suboptimal representation (as discussed in section 3.2). To overcome these issues, we propose ReBraiD (Deep **Re**presentations for Time-varying **Brai**n **D**atasets), a graph neural network model that jointly models dynamic functional signals and structural connectivities, leading to a more comprehensive deep representation of brain dynamics. We use fMRI and DWI data for these two modalities.

To simultaneously encode signals along spatial and temporal dimensions, some notable works in traffic prediction and activity recognition domains such as Graph WaveNet (Wu et al., 2019b) alternate TCN (temporal convolution network) (Lea et al., 2016) and GCN (graph convolutional network) (Kipf & Welling, 2016). Others (Song et al., 2020; Liu et al., 2020) use localized spatial-temporal graph to embed both domains' information in this extended graph. There are also works incorporat-

Figure 1: The proposed ReBraiD model for integrating brain structure and dynamics (the architecture shown is for classification). For each batch with batch size B, input X has a dimension of $(B, 1, N, T)$[1], and A, A_{adp} both have the dimension (B, N, N). The encoder (green part) encodes temporal and spatial information alternatively, producing a latent representation in $(B, d_{\mathrm{latent}}, N, 1)$. These embeddings are followed by linear layers for pooling and classification. The final output has a dimension of (B, C).

ing gated recurrent networks for the temporal domain such as (Seo et al., 2016; Ruiz et al., 2020). We choose the first option for ReBraiD, as it is more memory and time efficient, and can support much longer inputs. We also explore the best option when alternating spatial and temporal layers for encoding brain activities with extensive ablation studies. Upon this structure, we propose novel sample-level adaptive adjacency matrix learning and multi-resolution inner cluster smoothing, both of which learn and refine latent dynamic structures. We also make the model more efficient while being effective with the choice of the temporal layer.

Equally important as finding a good representation of brain dynamics is interpreting them. We utilize integrated gradients (Sundararajan et al., 2017) to identify how brain ROIs participate in various processes. This can lead to better behavioral understanding, biomarker discoveries, and characterization of individuals or groups with their brain imagings. We also make the novel contribution of identifying temporally important frames with graph attribution techniques; this can enable more fine-grained temporal analysis around keyframes when combined with other imaging modalities such as EEG (electroencephalogram). In addition, our subject-level and group-level attribution studies unveil heterogeneities among ROIs, tasks, and individuals.

2 METHOD

2.1 PRELIMINARIES

We utilize two brain imaging modalities mapped onto a same coordinate: SC (structural connectivity) from DWI scans, and time-varying fMRI scans. We represent them as a set of L graphs $\mathcal{G}_i = (A_i, X_i)$ with $i \in [1, L]$, in which $A_i \in \mathbb{R}^{N \times N}$ represents normalized adjacency matrix with an added self-loop: $A_i = \tilde{D}_{\mathrm{SC}_i}^{-\frac{1}{2}} \tilde{\mathrm{SC}}_i \tilde{D}_{\mathrm{SC}_i}^{-\frac{1}{2}}$, $\tilde{\mathrm{SC}}_i = \mathrm{SC}_i + I_N$ and $\tilde{D}_{\mathrm{SC}_i} = \sum_w (\tilde{\mathrm{SC}}_i)_{vw}$. Graph signal matrix obtained from fMRI scans of the i^{th} sample is represented as $X_i \in \mathbb{R}^{N \times T}$. Here N is the number of nodes, and each node represents a brain region; T is the input signal length on each node. Our objective focuses on classifying brain signals $\mathcal{G}_i$ into one of C task classes through learning latent graph structures.

2.2 MODEL

ReBraiD takes (A, X) as inputs, and outputs task class predictions. The overall model structure is shown in fig. 1. For the i^{th} sample $X_i \in \mathbb{R}^{N \times 1 \times T}$, the initial 1×1 convolution layer increases its hidden feature dimension to d_{h1}, outputting (N, d_{h1}, T). The encoder then encodes temporal and spatial information alternately, reducing information to feature axis and generating a hidden

---

[1]Axis order follows PyTorch conventions. Dimension at the second index is the expanded feature dimension.

Figure 2: Comparison of strided non-causal TCN (left) and dilated causal TCN (right). The causal aspect is achieved through padding (kernel_size $- 1$) $\times$ dilation zeros to the layer's input. The resulting $\mathbf{y}$ always has the same length as input $\mathbf{x}$, in which $\mathbf{y}_\tau$ only depends on inputs $\mathbf{x}_{t \leq \tau}$. We can view strided non-causal TCN as the rightmost node of a dilated causal TCN.

representation of size $(N, d_{h2}, 1)$. The encoder is followed by two linear layers to perform node embedding pooling and two MLP layers for classification. Cross entropy is used as the loss function: $L_{CE}^{(i)} = - \sum_C y_i \log \hat{y}_i$, where $y_i \in \mathbb{R}^C$ is the one-hot vector of ground truth task label and $\hat{y}_i \in \mathbb{R}^C$ is model's predicted distribution. We now explain different components of the model.

Learning sample-level latent graph structures. Structural scans serve as our graph adjacency matrices. However, they are static not only across temporal frames but also across different tasks. In contrast, functional connectivities (FC) are highly dynamic, as shown in appendix A.1.1. To better capture dynamic graph structures, we assign an adaptive adjacency matrix to each input graph signal. Unlike other works such as Wu et al. (2019b) that use a universal latent graph structure, our model do not assume all samples share the same latent graph. Instead, in ReBraiD, each sample has a unique latent structure reflecting its signal status. This implies that the latent adjacency matrix cannot be treated as a learnable parameter as a part of the model. To solve this, we minimize the assumption down to a shared projection Θ_{adp} that projects each input sequence into an embedding space and use this embedding to generate the latent graph structure. Θ_{adp} can be learned in an end-to-end manner. The generated adaptive adjacency matrix for the i^{th} sample can be written as:

$$A_{i\_\text{adp}} = \text{Softmax}\left(\text{ReLU}\left((X_i\Theta_{\text{adp}})(X_i\Theta_{\text{adp}})^\top\right)\right), \Theta_{\text{adp}} \in \mathbb{R}^{T \times h_{\text{adp}}} \tag{1}$$

Gated TCN (Temporal Convolutional Network). We adopt the gating mechanism as in Oord et al. (2016b). However, different from TCNs generally used in sequence to sequence models that consist of dilated Conv1d and causal padding along the temporal dimension (Oord et al. (2016a)), we simply apply Conv1d with kernel 2 and stride 2 to embed temporal information. The reason is twofold: first, for a sequence to sequence model with a length-T output, y_τ should only depend on $x_{t \leq \tau}$ to avoid information leakage, and causal convolution can ensure this. In contrast, our model's task is classification, and the goal of our encoder along the temporal dimension is to embed signal information into the feature axis while reducing temporal dimension to 1. The receptive field of this single temporal point (with multiple feature channels) is meant to be the entire input sequence. Essentially, our TCN is the same as the last output node of a kernel 2 causal TCN whose dilation increases by 2 at each layer (fig. 2). Second, from a practical perspective, directly using strided non-causal TCN works the same as using dilated causal TCNs and taking the last node, while simplifies the model structure and reduces training time to less than a quarter.

Graph Network layer. In our model, every l temporal layers (section 3.1 studies the best l to choose) are followed by a spatial layer to encode signals with the graph structure. Building temporal and spatial layers alternatively helps spatial modules to learn embeddings at different temporal scales, and this generates better results than putting spatial layers after all temporal ones.

To encode spatial information, Kipf & Welling (2016) uses first-order approximation of spectral filters to form the layer-wise propagation rule of a GCN layer: $H^{(l+1)} = \text{GCN}(H^{(l)}) = f(AH^{(l)}W^{(l)})$. It can be understood as spatially aggregating information among neighboring nodes to form new node embeddings. In the original setting without temporal signals, $H^{(l)} \in \mathbb{R}^{N \times d}$ is the activation matrix of l^{th} layer, $A \in \mathbb{R}^{N \times N}$ denotes the normalized adjacency matrix with self-connections as discussed in section 2.1, $W^{(l)} \in \mathbb{R}^{d \times d'}$ is learnable model parameters, and f is a nonlinear activation function of choice. Parameters d and d' are the number of feature channels.

We view a GCN layer as a local smoothing operation followed by an MLP, and simplify stacking K layers to $A^K H$ as in Wu et al. (2019a). In ReBraiD, every graph network layer aggregates information from each node's K-hop neighborhoods based on both brain structural connectivity and the latent adaptive adjacency matrix: namely we have both $A_i^K H^{(l)} W_K$ and $A_{i\_\text{adp}}^K H^{(l)} W_{K\_\text{adp}}$ for input

$H^{(l)}$. We also gather different levels (from 0 to K) of neighbor information with concatenation. In other words, one graph convolution layer here corresponds to a small module that is equivalent to K simple GCN layers with residual connections. We can write our layer as:

$$H^{(l+1)} = \text{GNN}^{(l)}\left(H^{(l)}\right) = \text{MLP}\left[\text{Concat}_{k=1}^{K}\left(H^{(l)}, \text{ReLU}(A_i{}^k H^{(l)}), \text{ReLU}(A_{i\_\text{adp}}{}^k H^{(l)})\right)\right] \quad (2)$$

With the additional temporal dimension, $H^{(l)} \in \mathbb{R}^{N \times d \times t}$ in eq. (2), and $A_i \in \mathbb{R}^{N \times N}$ applies on $H^{(l)}$'s first two dimensions while multiplying. Outputs of different $\text{GNN}^{(l)}$ layers are parametrized and then skip connected with a summation. Since the temporal lengths of these outputs are different because of TCNs, max-pooling is used before each summation to make the lengths identical.

Multi-resolution inner cluster smoothing. We find using soft assignments as in DIFFPOOL (Ying et al. (2018)) to be beneficial for capturing long-range relationships among brain regions that neither appear in SC or learned by latent A_adp. To generate the soft assignment tensor assigning N nodes into c clusters (c chosen manually), we use $\text{GNN}^{(l)}_{pool}$ that obeys the same propagation rule as in eq. (2), followed by Softmax along c. This assignment is applied to the output of $\text{GNN}^{(l)}_{emb}$ which carries out the spatial embedding for the l^{th} layer input $H^{(l)}$:

$$S^{(l)} = \text{Softmax}\left(\text{GNN}^{(l)}_{pool}\left(H^{(\ell)}\right), 1\right) \in \mathbb{R}^{N \times c \times t}$$
$$Z^{(l)} = \text{GNN}^{(l)}_{emb}\left(H^{(l)}\right) \in \mathbb{R}^{N \times d \times t} \quad (3)$$
$$\tilde{H}^{(l)} = S^{(l)\top} Z^{(l)} \in \mathbb{R}^{c \times d \times t}$$

The extra temporal dimension allows nodes to be assigned to heterogeneous clusters at different frames. We find that using coarsened $A_i^{(l+1)} = S^{(l)\top} A_i^{(l)} S^{(l)} \in \mathbb{R}^{c \times c}$ as the graph adjacency matrix leads to worse performance compared to using SC-generated A_i and learned A_{i_adp} (comparison in section 3.1). In addition, if the number of nodes is changed, residual connections coming from the beginning of temporal-spatial blocks can not be used and this impacts overall performance. To continue use A_i and A_{i_adp} as graph adjacency matrices and allow residual connections, we reverse-assign $\tilde{H}^{(l)}$ with assignment tensor obtained from applying Softmax on $S^{(l)\top}$ along N, so that the number of nodes is kept unchanged:

$$\tilde{S}^{(l)} = \text{Softmax}\left(S^{(l)\top}, 1\right) \in \mathbb{R}^{c \times N \times t}$$
$$H^{(\ell+1)} = \tilde{S}^{(l)\top} \tilde{H}^{(l)} \in \mathbb{R}^{N \times d \times t} \quad (4)$$

In fact, eqs. (3) and (4) perform signal smoothing on nodes within each soft-assigned cluster (appendix A.1.2 shows a toy example). With the bottleneck $c < N$, the model is forced to pick up latent community structures. This inner-cluster smoothing is carried out at different spatial resolutions: as the spatial receptive field increases with more graph layers, we decrease cluster number c for the assignment operation.

Attribution with IG (Integrated Gradients). As one approach to model interpretability, *attribution* assigns credits to each part of the input, assessing how important they are to the final predictions. Wiltschko et al. (2020) gives an extensive comparison between different graph attribution approaches, in which IG (Sundararajan et al. (2017)) is top-performing and can be applied to trained models without extra alterations of the model structure. IG also has other desirable properties such as implementation invariance that other gradient methods are lacking. It is also more rigorous and accurate than obtaining explanations from attention weights or pooling matrices that span multiple feature channels. Intuitively, IG calculates how real inputs contribute differently compared to a selected baseline; it does so by aggregating model gradients at linearly interpolated inputs between the real and baseline inputs. For each sample, we calculate attributions at each point of both input $A \in \mathbb{R}^{N \times N}$ and $X \in \mathbb{R}^{N \times T}$:

$$\text{ATTR}_{A_{vw}} = \left(A_{vw} - A'_{vw}\right) \times \sum_{m=1}^{M} \frac{\partial F\left(A_{\text{Intrpl}}, X\right)}{\partial A_{\text{Intrpl}_{vw}}} \times \frac{1}{M}, \quad A_{\text{Intrpl}} = A' + \frac{m}{M} \times \left(A - A'\right)$$
$$ \quad (5)$$
$$\text{ATTR}_{X_{vt}} = \left(X_{vt} - X'_{vt}\right) \times \sum_{m=1}^{M} \frac{\partial F\left(A, X_{\text{Intrpl}}\right)}{\partial X_{\text{Intrpl}_{vt}}} \times \frac{1}{M}, \quad X_{\text{Intrpl}} = X' + \frac{m}{M} \times \left(X - X'\right)$$

$F(A, X)$ here represents our signal classification model, M is the step number when doing Riemann approximation of the path integral, and A', X' are baselines of A, X (see section 3.3 for more details). Note that eq. (5) calculates the attribution of one point on one sample. The process is repeated for every point of the input, so attributions have identical dimensions as inputs. To obtain brain region importance of a task, we aggregate attributions across multiple samples of that task.

Figure 3: 3a: Ablation studies on different input length (please see table 2 in appendix for numerical values of weighted F1 under each setting); 3b: Choosing number of GNN to TCN layer ratio.

3 EXPERIMENTS

We use fMRI signals from CRASH dataset (Lauharatanahirun et al. (2020)) for our experiments. The model classifies input fMRI into 6 tasks: resting state, visual working memory task (VWM), dynamic attention task (DYN), math task (MOD), dot probe task (DOT), and psychomotor vigilance task (PVT) (appendix A.2.1 has detailed task descriptions). We preprocess 4D voxel-level fMRI images into graph signals $\mathcal{G} = (A, X)$ by averaging voxel activities into regional signals with the 200-ROI cortical parcellation (voxel to region mapping) specified by Schaefer et al. (2018). We also standardize signals for each region and discard scan sessions with obvious abnormal spikes that may be caused by head movement, etc.. DWI scans are mapped into the same MNI152 coordinate and processed into adjacency matrices with the same parcellation as fMRI uses. Valid data contains 1940 scan sessions from 56 subjects, session length varies from 265 frames to 828 frames and TR (Repetition Time) is 0.91s. These 1940 scan sessions are separated into training, validation, and test sets with a ratio of 0.7-0.15-0.15. Hyperparameters including dropout rate, learning rate, and weight decay are chosen with grid search based on validation loss, and all results reported in this section are obtained from the test set. For each scan session, we use a sliding window to generate input sequences (in the following experiments $T \in \{8, 16, 32, 64, 128, 256\}$) and feed them to the model. Models are written in PyTorch, trained with Google Colab GPU runtimes, and 60 epochs are run for each experiment setting. Codes and data will be released upon acceptance.

3.1 MODEL COMPONENTS

Graph adjacency matrices. For each input sample $\mathcal{G}_i$, we test different options to provide graph adjacency matrices to the GNN layer. They include (i) our proposed method: using both adaptive adjacency matrix A_{i_adp} and SC-induced A_i; (ii) only using A_i; (iii) only using A_{i_adp}; (iv) replacing A_{i_adp} in setting i with A_{i_FC} derived from functional connectivity; (v) only using random graph adjacency matrices with the same level of sparsity as real As. We set h_{adp} to be 5 in eq. (1), which works better for our data than larger h_{adp} choices. K is set to 2 for eq. (2), meaning each GNN aggregates information from 2-hop neighbors based on the provided adjacency matrices. We evaluate our model with weighted F1 as the metric because of the imbalance among tasks. The results under different settings are reported in fig. 3a (and table 2 in appendix for numerical values).

From the results of setting (ii) plotted in fig. 3a, we see that removing the adaptive adjacency matrix impacts the performance differently at different input lengths: the gap peaks for signals of length 64 - 128, and becomes smaller for either shorter or longer sequences. This could suggest the existence of more distinct latent states of brain signals of this length that cannot be captured by structural connectivities. On the other hand, removing SC (setting (iii)) seems to have a more constant impact on the model performance, with shorter inputs more likely to see a slightly larger drop. In general, only using A_{adp} leads to smaller performance drop than only using SC, indicating the effectiveness of A_{adp} in capturing useful latent graph structures. More detailed studies in appendix A.2.2 shows A_{adp} learns distinct representations not captured by A.

As mentioned in section 2, our motivation behind creating sample-level adaptive adjacency matrices is FC's highly dynamic nature. Therefore, for setting (iv), we test directly using adjacency matrices A_{i_FC} obtained from FC instead of the learned A_{i_adp}. In particular, $A_{i\_FC} = \tilde{D}_{FC_i}^{-\frac{1}{2}} \tilde{FC}_i \tilde{D}_{FC_i}^{-\frac{1}{2}} \in \mathbb{R}^{200 \times 200}$, where $(FC_i)_{vw} = \mathrm{corr}((X_i)_v, (X_i)_w)$, $\tilde{FC}_i = FC_i + I_N$ and $\tilde{D}_{FC_i} = \sum_w (\tilde{FC}_i)_{vw}$. Fig. 3a shows A_{i_FC} constantly underperforms A_{i_adp}, except for being really close with length-8 inputs. Larger performance gaps are observed for longer inputs, where $\mathrm{Corr}((X_i)_v, (X_i)_w)$ struggles to capture the changing dynamics in the inputs. This demonstrates that our input-based latent A_{i_adp} has better representation power than input-based FC. We also notice batch correlation coefficients calculation for A_{i_FC} results in a slower training speed than computing A_{i_adp}.

An interesting result comes from setting (v), where we use randomly generated Erdős-Rényi graphs with the edge creation probability the same as averaged edge existence probability of As. Its performance is at a similar level or even better than settings (ii) and (iii). Our hypothesis is the model can learn the latent graph structure out of randomness, and we will verify this hypothesis in section 3.3.

Number of GNN layers. The total number of temporal layers depends on the input signal length since each strided TCN layer reduces the temporal length by a factor of 2: if the input length is 2^i, there need to be i temporal layers. But *is alternating every TCN with GNN the best strategy, or do we only need to follow one GNN after a few TCNs*? We study this question with different input lengths.

Model weighted F1 are plotted in fig. 3b for all possible GNN to total TCN ratios (e.g. length-256 inputs requires 8 TCN layers. The possible ratios are $\frac{1}{8}, \frac{1}{4}, \frac{1}{2}, 1$ since we can insert one GNN per 8, 4, 2, 1 TCN layers). The figure shows alternating every layer rarely yields the highest performance and the best ratio lines around one GNN per two TCN layers for our dataset. We repeat the experiment for $K = 1, 3$ (in eq. (2)) to rule out the possibility that this result is related to how many neighbors one GNN layer can reach; we find they have roughly the same pattern as the $K = 2$ case. Our hypothesis is that lower GNN to TCN ratio does not capture enough spatial context, while higher ones might be overfitting. We leave exploring the relationship between this ratio and nodes number N to a future study.

The best GNN to TCN ratio also depends on whether model incorporates latent adjacency matrices or not: without A_{adp}, length-128 signals achieves its relative best (among all ratios) when having one GNN per two TCNs, but it only needs one GNN per three TCNs if using A_{adp}. This shows learning latent structures A_{adp} not only improves overall model accuracy but can also reduce model parameters, thus complexity, in achieving the relative best results.

Multi-resolution inner cluster smoothing. To verify the capability of inner-cluster smoothing operation in capturing latent graph dynamics, we test the following settings: (vi) using our proposed model and inputs, except removing paralleled GNN_{pool} and inner-cluster smoothing module; (vii) previous setting (v) but remove GNN_{pool} and inner-cluster smoothing module; (viii) keep GNN_{pool}, but using coarsened graph instead of performing smoothing and increasing the node number back (essentially performing DIFFPOOL with an added temporal dimension). In this last setting, we hierarchically pool graph nodes until node number reaches 1, and we keep the total number of GNN layers the same as our other settings. Results are reported in fig. 3a (and table 2 in appendix). Apart from these three settings, we also test adding pooling regularization terms (described in appendix A.1.3) into the loss function but this does not lead to much of a difference.

The above results demonstrate that both setting (vi) and (vii) outperforms (viii) by a large margin, indicating the importance of keeping the original node number when representing brain signals. In addition, all three settings underperform our proposed method, and they are mostly worse than changing graph adjacency matrices as in settings (ii)-(v): this shows inner-cluster smoothing module has a large impact in learning latent graph dynamics. We also find using adaptive adjacency matrices and inner cluster smoothing can stabilize training, making the model less prone to over-fitting and achieving close-to-best performance over a larger range of hyperparameters.

3.2 MODEL COMPARISONS

In this section, we compare the vanilla GCN from Kipf & Welling (2016), Chebyshev Graph Convolutional Gated Recurrent Unit (GConvGRU) from Seo et al. (2016), GraphSAGE from Hamilton et al. (2018), GAT V2 from Brody et al. (2021) and Graph Transformer as in Shi et al. (2021). Their

Table 1: Model comparisons under the 256 input length setting.

Model	Accuracy (%)	Weighted F1	Training time (s / epoch)
GCN (Kipf & Welling (2017))	41.53	42.84	713
GAT V2 (Brody et al. (2021))	50.44	50.36	1142
GConvGRU (Seo et al. (2016))	52.26	56.05	9886
GraphSAGE (Hamilton et al. (2018))	61.84	61.87	1048
Graph Transformer (Shi et al. (2021))	66.51	66.11	1890
ReBraiD (proposed method)	**85.56**	**90.85**	**298**

original networks are built for different tasks such as traffic prediction and epidemiological forecasting, which work on a single shared graph adjacency matrix for all samples yet we have different A_i for each sample. To use them in our fMRI classificaiton problem, we directly take corresponding layers from PyTorch Geometric [2] and PyTorch Geometric Temporal [3] and use PyTorch Geometric graph-level classification network structures. We train baseline models with the same setting as our model: 256-frame inputs, Adam optimizer, cross entropy loss, and 60 epochs. Grid search is used to optimize the rest of hyperparameters. We compare accuracy, weighted F1 score, and training time per epoch in table 1; we also plot our model and Graph Transformer's confusion matrices in appendix fig. 11.

We observe that our proposed method significantly outperforms the baseline models by a margin of 20 to 40 percent. This demonstrates our proposed model's effectiveness in capturing latent brain dynamics. For these baseline models, temporal content is used as features; the comparison shows separating them into different axis is more advantageous. Besides, the training time of our model is significantly less. For one epoch under the same setting, our model takes roughly 298 seconds while the rest of the baselines take at least 713 seconds.

3.3 INTERPRETATIONS WITH IG

In this section, we study the contributions of different brain ROIs and subnetworks defined by their functionalities. For the subnetwork definition, we choose to use the 17 networks specified in Thomas Yeo et al. (2011)) which has a mapping from our previous 200-ROI parcellation. See table 3 in appendix for all subnetwork names. We compute IG of a model trained on length-256 input signals because the model has higher performance with longer inputs, leading to more accurate attributions. To select baseline inputs, we follow the general baseline selection principle for attribution methods: when the model takes in a baseline input, it should produce a near-zero prediction and $\mathrm{Softmax}(\text{outputs})$ should give each class about the same probability in a classification model. All-zero A' and X' can roughly achieve this for our model, so we choose them as our baseline inputs. For each task, the IG computation is done on 900 inputs to get an overall distribution.

Temporal importance. On the single input level, we can attribute which parts of the inputs in $\mathcal{G}_i$ are more important in predicting the target class by looking into $(\mathrm{ATTR}_X)_i$. This attribution map not only shows which brain regions contribute more but also reveals the important signal frames. One critical drawback of fMRI imaging is its low temporal resolution, but if we can know which part is more important, we can turn to more temporally fine-grained signals such as EEG to see if there are any special activities during that time. To confirm that the attributions we get are valid and consistent, we perform a sanity check of IG results on two overlapped inputs with an offset τ: the first input is obtained from window $[t_0, t_0 + T]$ and the second is obtained from window $[t_0 + \tau, t_0 + \tau + T]$. Offset aligned results are shown in fig. 4a, and we can see the attributions agree with each other quite well.

Spatial importance. We examine the connection importance between brain ROIs by looking at ATTR_A (task-averaged ATTR_A are plotted in fig. 13 in appendix). In particular, columns in ATTR_A with higher average values are sender ROIs of high-contributing connections, which is what matters in the GNN operation. We also explore why using random graph adjacency matrices (setting (v) in section 3.1) can produce a similar result for length-256 inputs compared to using both SC-induced A_i and A_{i_adp} (setting (i)). By examining ATTR_A under both settings (fig. 5), we see that the column

---
[2]https://pytorch-geometric.readthedocs.io/
[3]https://pytorch-geometric-temporal.readthedocs.io/

(a)   (b)

Figure 4: 4a: Temporal importance sanity check of IG results on two pieces of inputs with a large overlap period. Attribution maps are offset aligned; 4b: ATTR_X distributions across brain regions for VWM task, where the upper one separates left and right hemispheres and the lower one combines them (e.g. LH_VisCent and RH_VisCent are combined to region VisCent). Refer to table 3 in appendix to see brain region names that the x-axis numbers represent.

Figure 5: Column averages of task-averaged ATTR_A (mapped into 17-network subnetworks). Top row is obtained from real SC induced A, while bottom rows is obtained from random SC induced A_{rand}.

averages of ATTR_A under these two settings are similar for almost all tasks, meaning the model can learn where to pay attention to even using random adjacency matrix inputs. We credit this ability partially to multi-resolution inner cluster smoothing, as the performance would drop notably without it (setting (vii)). However, using ground truth SC not only gives us higher performance for shorter inputs but also provides the opportunity to better interpret brain region connections. We can directly use task-averaged ATTR_A as the weighted adjacency matrix to plot edges between brain ROIs, just as in fig. 6. Important brain regions obtained from ATTR_A mostly comply with the previous literature.

ATTR_X can also give us insights on spatial importance when the attribution maps are averaged or summed up along the temporal dimension. But it does so from another perspective: instead of showing important *structural connections* that support information passing, it reveals regions or subnetworks that are sources of the important *signals*. In fig. 4b, we plot the distribution of t-averaged and subnetwork-averaged (mapping 200 ROIs into 17 subnetworks) ATTR_X during VWM task. We can see the clear dominance of VisCent, DorsAttnA, and ContA subnetworks (numbered as 1, 5, 11). For the boxplots of other tasks and subnetwork rankings, please see fig. 14, table 4 and table 5 in appendix. More informative than the rankings is the distribution itself: even though VisCent, DorsAttnA, and ContA ranked top 3 for both resting state and VWM task for signal attributions, their relative importance and attribution distribution variances are totally different. In a sense, the distribution can act as a task fingerprint based on brain signal states.

We notice that signal-important ROIs are not necessarily the same as connection-important ROIs: top-ranked subnetworks for resting state are DefaultA and DefaultB by ATTR_A, and VisCent and DorsAttnA by ATTR_X; although they do coincide with each other for tasks like VMN. This disparity is reflected in fig. 6 as edge and node differences.

Group, session, and region heterogeneity. Average variances of attributions are very different across tasks, especially those of ATTR_X: VWM and DYN have much smaller attribution variances compared to other tasks. This can be caused by either task dynamics when certain tasks have more phase transitions and brain status changes, or/and group heterogeneity when individuals carry out certain tasks more differently than the others. We investigate the cause by looking into 3 subjects; each of them has multiple scan sessions for every task.

Figure 6: ROI attributions from ATTR_A and ATTR_X. Tasks are: Resting, VWM, DYN, DOT, MOD, PVT from left to right. Edge color and width are based on task-averaged $\text{ATTR}_A \in \mathbb{R}^{200 \times 200}$, and nodes color and size are based on task and temporal-averaged $\text{ATTR}_X \in \mathbb{R}^{200}$. For the visualization purpose, only edges with highest attributions are kept to ensure sparsity being 0.009 (down from around 0.196). For ROI attributions based only on ATTR_A where important sender ROIs are reflected by node sizes, please refer to fig. 12 in appendix.

Figure 7: ATTR_X distributions of 3 subjects doing VWM task (left) and MOD task (right). Outliers that go beyond $[Q1 - 1.5\,\text{IQR}, Q3 + 1.5\,\text{IQR}]$ are omitted. VWM has a much smaller average attribution variance than MOD.

We report the following findings: (1) Even only aggregating attributions over a single subject's sessions, attribution variances of the other four tasks are still larger than VWM and DYN. The variance values are comparable to that of aggregating over many subjects. This means the large variances are not mainly due to group heterogeneity, rather some tasks having more states than others. (2) Apart from different task dynamics, there is still group heterogeneity. For tasks with more dynamics (high attribution variances), the group heterogeneity is also more obvious. We can see from fig. 7 that attributions for VMM are much more concentrated and universal across subjects than that of MOD. (3) Flexibility of different subnetworks varies: subnetworks that have small distribution IQR (Interquartile Range) of the same subject's different sessions will also be more consistent across subjects. One example is subnetwork 18 during MOD task has both higher within-subject IQR and larger across-subject differences compared to subnetwork 19. This indicates for a certain task, some subnetworks are more individual and flexible (may activate differently across t), while others are more universal and fixed. In summary, we can reveal both critical regions that a particular task must rely on, and regions that can characterize individual differences during tasks.

4 CONCLUSIONS

In this paper, we propose ReBraiD, a high-performing and efficient graph neural network model that embeds both structural and dynamic functional brain signals for task classifications. To better capture latent dynamics, we propose input-dependent adjacency matrix learning and inner-cluster smoothing at multiple resolutions. Apart from quantitative results showing ReBraiD's superiority in representing brain activities, we also leverage integrated gradients to attribute and interpret the importance of both spatial brain regions and temporal keyframes, as well as presenting heterogeneities among subnetworks, tasks, and individuals. These findings can potentially reveal new neural basis or biomarkers of tasks and brain disorders when combined with behavioral metrics, and enable more fine-grained temporal analysis around keyframes when combined with other imaging techniques.

REFERENCES

Danielle S Bassett and Olaf Sporns. Network neuroscience. *Nature neuroscience*, 20(3):353–364, 2017.

Shaked Brody, Uri Alon, and Eran Yahav. How attentive are graph attention networks?, 2021.

William L. Hamilton, Rex Ying, and Jure Leskovec. Inductive representation learning on large graphs, 2018.

Byung-Hoon Kim and Jong Chul Ye. Understanding graph isomorphism network for rs-fmri functional connectivity analysis. *Frontiers in Neuroscience*, 14:630, 2020. ISSN 1662-453X. doi: 10.3389/fnins.2020.00630. URL https://www.frontiersin.org/article/10.3389/fnins.2020.00630.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks, 2017.

Nina Lauharatanahirun, Kanika Bansal, Steven M Thurman, Jean M Vettel, Barry Giesbrecht, Scott Grafton, James C Elliott, Erin Flynn-Evans, Emily Falk, and Javier O Garcia. Flexibility of brain regions during working memory curtails cognitive consequences to lack of sleep. *arXiv preprint arXiv:2009.07233*, 2020.

Colin Lea, René Vidal, Austin Reiter, and Gregory D. Hager. Temporal convolutional networks: A unified approach to action segmentation. In Gang Hua and Hervé Jégou (eds.), *Computer Vision – ECCV 2016 Workshops*, pp. 47–54, Cham, 2016. Springer International Publishing. ISBN 978-3-319-49409-8.

Xiaoxiao Li, Yuan Zhou, Nicha C. Dvornek, Muhan Zhang, Juntang Zhuang, Pamela Ventola, and James S. Duncan. Pooling regularized graph neural network for fmri biomarker analysis. *Medical image computing and computer-assisted intervention : MICCAI ... International Conference on Medical Image Computing and Computer-Assisted Intervention*, 12267:625–635, 2020.

Ziyu Liu, Hongwen Zhang, Zhenghao Chen, Zhiyong Wang, and Wanli Ouyang. Disentangling and unifying graph convolutions for skeleton-based action recognition. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 143–152, 2020.

Sylvia Loh, Nicole Lamond, Jill Dorrian, Gregory Roach, and Drew Dawson. The validity of psychomotor vigilance tasks of less than 10-minute duration. *Behavior Research Methods, Instruments, & Computers*, 36(2):339–346, 2004.

Steven J Luck and Edward K Vogel. The capacity of visual working memory for features and conjunctions. *Nature*, 390(6657):279–281, 1997.

Andrew Mattarella-Micke, Jill Mateo, Megan N Kozak, Katherine Foster, and Sian L Beilock. Choke or thrive? the relation between salivary cortisol and math performance depends on individual differences in working memory and math-anxiety. *Emotion*, 11(4):1000, 2011.

Fuad Noman, Chee-Ming Ting, Hakmook Kang, Raphael C. W. Phan, Brian D. Boyd, Warren D. Taylor, and Hernando Ombao. Graph autoencoders for embedding learning in brain networks and major depressive disorder identification, 2021.

Aaron van den Oord, Sander Dieleman, Heiga Zen, Karen Simonyan, Oriol Vinyals, Alex Graves, Nal Kalchbrenner, Andrew Senior, and Koray Kavukcuoglu. Wavenet: A generative model for raw audio. *arXiv preprint arXiv:1609.03499*, 2016a.

Aaron van den Oord, Nal Kalchbrenner, Oriol Vinyals, Lasse Espeholt, Alex Graves, and Koray Kavukcuoglu. Conditional image generation with pixelcnn decoders. *arXiv preprint arXiv:1606.05328*, 2016b.

Luana Ruiz, Fernando Gama, and Alejandro Ribeiro. Gated graph recurrent neural networks. *IEEE Transactions on Signal Processing*, 68:6303–6318, 2020.

Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE Transactions on Neural Networks*, 20(1):61–80, 2009. doi: 10.1109/TNN.2008.2005605.

Alexander Schaefer, Ru Kong, Evan M Gordon, Timothy O Laumann, Xi-Nian Zuo, Avram J Holmes, Simon B Eickhoff, and BT Thomas Yeo. Local-global parcellation of the human cerebral cortex from intrinsic functional connectivity mri. *Cerebral cortex*, 28(9):3095–3114, 2018.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

Youngjoo Seo, Michaël Defferrard, Pierre Vandergheynst, and Xavier Bresson. Structured sequence modeling with graph convolutional recurrent networks, 2016.

Yunsheng Shi, Zhengjie Huang, Shikun Feng, Hui Zhong, Wenjin Wang, and Yu Sun. Masked label prediction: Unified message passing model for semi-supervised classification, 2021.

Maurice L Sipos, Yair Bar-Haim, Rany Abend, Amy B Adler, and Paul D Bliese. Postdeployment threat-related attention bias interacts with combat exposure to account for ptsd and anxiety symptoms in soldiers. *Depression and Anxiety*, 31(2):124–129, 2014.

Chao Song, Youfang Lin, Shengnan Guo, and Huaiyu Wan. Spatial-temporal synchronous graph convolutional networks: A new framework for spatial-temporal network data forecasting. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 914–921, 2020.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning*, pp. 3319–3328. PMLR, 2017.

BT Thomas Yeo, Fenna M Krienen, Jorge Sepulcre, Mert R Sabuncu, Danial Lashkari, Marisa Hollinshead, Joshua L Roffman, Jordan W Smoller, Lilla Zöllei, Jonathan R Polimeni, et al. The organization of the human cerebral cortex estimated by intrinsic functional connectivity. *Journal of neurophysiology*, 106(3):1125–1165, 2011.

Alexander B Wiltschko, Benjamin Sanchez-Lengeling, Brian Lee, Emily Reif, Jennifer Wei, Kevin James McCloskey, Lucy Colwell, Wesley Qian, and Yiliu Wang. Evaluating attribution for graph neural networks. *Google Research*, 2020.

Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. Simplifying graph convolutional networks. In *International conference on machine learning*, pp. 6861–6871. PMLR, 2019a.

Zonghan Wu, Shirui Pan, Guodong Long, Jing Jiang, and Chengqi Zhang. Graph wavenet for deep spatial-temporal graph modeling. *arXiv preprint arXiv:1906.00121*, 2019b.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? *arXiv preprint arXiv:1810.00826*, 2018.

Steven Yantis, Jens Schwarzbach, John T Serences, Robert L Carlson, Michael A Steinmetz, James J Pekar, and Susan M Courtney. Transient neural activity in human parietal cortex during spatial attention shifts. *Nature neuroscience*, 5(10):995–1002, 2002.

Rex Ying, Jiaxuan You, Christopher Morris, Xiang Ren, William L Hamilton, and Jure Leskovec. Hierarchical graph representation learning with differentiable pooling. *arXiv preprint arXiv:1806.08804*, 2018.

A APPENDIX

A.1 MODELS

A.1.1 DYNAMIC FUNCTIONAL CONNECTIVITIES.

Fig. 8 shows functional connectivities (FCs) among N brain regions, where each FC $\in \mathbb{R}^{N \times N}$. The value at FC$_{ij}$ is calculated as the Pearson correlation coefficient between signals of brain region i and region j. The figure shows 6 FCs calculated from 6 consecutive sliding windows within a same fMRI session, with signal window length being 30 and sliding stride being 30. From the figure, we can clearly tell that FCs are highly dynamic.

Figure 8: Dynamic functional connectivities.

A.1.2 INNER-CLUSTER SMOOTHING TOY EXAMPLE.

Here we show a toy example demonstrating the inner-cluster smoothing module described in eqs. (3) and (4). Note that we will only show one time slice, and the same operation is done along every t: on a particular t, we have $Z \in \mathbb{R}^{N \times d}, S \in \mathbb{R}^{N \times c}$. We will use $N = 3, c = 2$ and node values $a, b, c \in \mathbb{R}^d$ for this toy example. In addition, this example is just to illustrate the concept behind the smoothing operation, and $\mathrm{Softmax}$ along the axis 1 is simplified as row normalization for a clearer presentation.

Figure 9: Inner-cluster smoothing toy example.

In this example, 1^{st} and 2^{nd} nodes are assigned to the first cluster, and 2^{nd} and 3^{rd} node are assigned to the second cluster. The final H_{new} after our smoothing module will mingle the first two nodes' values, and the last two nodes' values (based on assignment weights) while keeping their original node number unchanged.

A.1.3 REGULARIZATION TERMS FOR THE SOFT-ASSIGNMENT.

For each soft assignment matrix $S \in \mathbb{R}^{N \times c \times t}$ in eq. (3), we test three regularization terms:

- Similar to DIFFPOOL, for ensuring a more clearly defined node assignment, namely each node is only assigned to few clusters (the closer to one the better), we can minimize the entropy of single node assignments: $L_{E_1} = \frac{1}{c} \sum_{i=1}^{c} H(S_i)$, where S_i is along c.

- To ensure a representation separation among nodes, meaning the assignment shouldn't assign all the nodes a same way, we maximize the entropy of node assignment *patterns* across all nodes: $L_{E_2} = -\frac{1}{c} \sum_{i=1}^{c} H(\sum_{j=1}^{n} S_{ij})$, where j is along n and i is along c.

- To make assignment along temporal axis smoother, we penalize assignment variances within a small window $[\hat{t}, \hat{t} + \tau]$: $L_T = \frac{1}{t-\tau} \sum_{\hat{t}=0}^{t-\tau} \sigma(S_{[\hat{t}, \hat{t}+\tau]})$, where σ represents standard deviation.

Together with cross entropy classification loss L_{CE}, the final loss function of the model will be:

$$L_{reg} = \alpha_1 L_{CE} + \alpha_2 L_{E_1} + \alpha_3 L_{E_2} + \alpha_4 L_T, \quad \sum_i \alpha_i = 1 \tag{6}$$

A.2 EXPERIMENTS

A.2.1 TASK DESCRIPTIONS.

The following are task descriptions of CRASH (Cognitive Resilience and Sleep History) dataset:

Resting state: The subject simply lays in the scanner awake, with eyes open for 5 minutes.

Visual working memory task (VWM): The subject is presented with a pattern of colored squares on a computer screen for a very brief period (100ms). After 1000ms, they are presented with a single square and must determine if it is the same or different color as the previously presented square at that location. Responses are made with a button press (Luck & Vogel (1997)).

Dynamic Attention Task (DYN): Two streams of orientation gratings are presented to the left and right of fixation. Subjects monitor specified stream for a target (2 degree shift in orientation, clockwise or counter clockwise) that indicates whether the subject should continue to monitor the current stream (hold) or monitor the other stream (shift) and respond with a button press (Yantis et al. (2002)).

Dot Probe Task (Faces) (DOT): On each trial, two faces are presented, one neutral and the other happy or angry for 500ms. Then, either of two simple symbols is presented at the position of either of the faces. The subject must make a forced choice discrimination of the symbol. Reaction time differences as a function of the valance for the preceding facial expression are calculated. There is increased variability of the bias with PTSD and fatigue (Sipos et al. (2014)).

Math task (MOD): Subjects perform a modular math computation every 8 seconds and respond with a yes or no button press. The object of modular arithmetic is to judge the validity of problems such as 51=19(mod 4). One way to solve it is to subtract the middle number from the first number (i.e., 51–19) and then divide this difference is by the last number (32/4). If the dividend is a whole number, the answer is "true." Otherwise the answer is false (Mattarella-Micke et al. (2011)).

Psychomotor vigilance task (PVT): The subject monitors the outline of a red circle on a computer screen for 10 minutes, and whenever a counter clockwise red sweep begins, they press a button as fast as possible. Subjects are provided with response time feedback. The experimenter records response latencies (Loh et al. (2004)).

A.2.2 ABLATION STUDIES

Numerical values of fig. 3a are reported in table 2. Training time ranges from 51 seconds / epoch for length-8 inputs to 298 seconds / epoch for length-256 inputs. Although the model is trained for 60 epochs in all experiments, it converges to a relatively stable loss level within 20 epochs.

In addition, as we mentioned in section 3.1, latent A_{adp} can complement the task- and temporal-fixed A. We will now show that the learned A_{i_adp} is sparse for each sample, has evident task-based patterns, and differs from what A_i can provide: fig. 10 shows visualizations of latent A_{adp}, which we can tell is quite sparse as in fig. 10a: each input only gets few important columns (information providing nodes in GNN), and they vary from one sample to another, indicating A_{adp}'s ability to adapt to changing inputs within a same task. However, when we look into inputs (not shuffled) generated by consecutive sliding windows from a same scan session as in fig. 10b, we can see the latent structures appear to be in a smooth transition. In addition, when averaged across many samples for each task, undeniable task-based patterns emerge, as in figs. 10c to 10e. But the task-average patterns are also different from what we saw from Attr_A in fig. 5, suggesting A_{adp} is embedding dynamics that are not captured by A. One interesting phenomenon in fig. 10e is that across all

Table 2: Weighted F1 of ablation study settings.

Input length (frames)	8	16	32	64	128	256
(i): SC + adp	**66.19**	**70.18**	**75.87**	**76.14**	**82.91**	**90.85**
(ii): SC only	64.54	65.58	71.79	70.31	73.63	89.79
(iii): adp only	64.32	65.20	74.01	71.42	80.63	89.46
(iv): SC + FC	66.10	67.58	70.26	75.02	76.91	84.68
(v): random adj	62.17	66.25	72.30	73.72	76.58	89.22
(vi): (i) without smoothing	63.57	62.82	70.19	65.82	72.91	79.65
(vii): (v) without smoothing	56.88	64.08	72.27	62.72	75.16	83.75
(viii): coarsened graph	37.92	42.23	46.18	52.12	57.17	64.25

(a) A_{i_adp} of 6 randomly sampled inputs during DOT task.

(b) A_{i_adp} of 6 consecutive inputs from a same session during DOT task.

(c) Task-averaged A_{adp} for resting state, VWM, DYN, DOT, MOD, PVT.

(d) 200 ROIs' column sums of task-averaged A_{adp}. Task order is the same as (b).

(e) 34 (17 with LR) subnetworks' column sums of task-averaged A_{adp}. Task order is the same as (b).

Figure 10: Learned latent adaptive adjacency matrices A_{adp}.

tasks, LimbicB_OFC, Default_B, and LimbicA_TempPole are always among the most important subnetworks appeared in the latent A_{adp}. Further exploration is needed for explaining the case.

A.2.3 MODEL COMPARISONS.

We plot confusion matrices of our model, model from ablation study setting (viii), and the best performing baseline in fig. 11. Misclassification pairs clustered as the first three tasks (resting, VWM, DYN) and the latter three (DOT, MOD, PVT). However, we note that these pairs may be different for other input lengths.

(a)   (b)   (c)

Figure 11: Confusion matrices of: (11a) ReBraiD (our proposed model), (11b) model with coarsened graph (setting (viii)), (11c) Graph Transformer (best-performing baseline).

A.2.4 IG Attr_A

See fig. 12 for the visualization of important ROIs based on Attr_A, and fig. 13 for task-averaged Attr_A under real and random SC settings.

Figure 12: Important ROIs based on Attr_A. Tasks are: Resting, VWM, DYN, DOT, MOD, PVT from left to right. Node sizes are based on column sums of $\text{Attr}_A \in \mathbb{R}^{200 \times 200}$ and edge width are direcly based on Attr_A. For the visualization purpose, only edges with highest attributions are kept to ensure sparsity being 0.009 (down from around 0.196).

Figure 13: Task-averaged ATTR_A. The top row is obtained from real SC induced A, and the bottom row is obtained from random SC induced A_{rand}.

A.2.5 IG Attr_X

See fig. 14 for the complete attribution distributions for every task based on temporal-averaged Attr_X. Corresponding brain regions of a certain number are listed in table 3. For boxplots showing 17 regions, we combine LH and RH for their common network.

See table 4 for subnetwork rankings based on column-average Attr_A and table 5 for subnetwork rankings based on temporal-averaged Attr_X.

(a) Resting state.

(b) Visual working memory task.

(c) Dynamic Attention Task.

(d) Dot Probe Task.

(e) Math Task.

(f) Psychomotor vigilance task.

Figure 14: Brain subnetwork attribution distributions from Attr_X.

Table 3: Brain subnetworks in the 17-network definition.

1	LH_VisCent	18	RH_VisCent
2	LH_VisPeri	19	RH_VisPeri
3	LH_SomMotA	20	RH_SomMotA
4	LH_SomMotB	21	RH_SomMotB
5	LH_DorsAttnA	22	RH_DorsAttnA
6	LH_DorsAttnB	23	RH_DorsAttnB
7	LH_SalVentAttnA	24	RH_SalVentAttnA
8	LH_SalVentAttnB	25	RH_SalVentAttnB
9	LH_LimbicB_OFC	26	RH_LimbicB_OFC
10	LH_LimbicA_TempPole	27	RH_LimbicA_TempPole
11	LH_ContA	28	RH_ContA
12	LH_ContB	29	RH_ContB
13	LH_ContC	30	RH_ContC
14	LH_DefaultA	31	RH_DefaultA
15	LH_DefaultB	32	RH_DefaultB
16	LH_DefaultC	33	RH_DefaultC
17	LH_TempPar	34	RH_TempPar

Table 4: Attr_A: Top 10 brain subnetworks initiate important connections during different tasks (fig. 12 provides a ROI-based visualization).

	rest	VWM	DYN	DOT	MOD	PVT
1	RH_DefaultA	RH_VisPeri	LH_SomMotB	RH_VisPeri	RH_DefaultA	RH_ContA
2	LH_DefaultA	LH_VisPeri	RH_DefaultC	LH_VisPeri	LH_DefaultA	RH_SalVentAttnA
3	RH_DefaultB	LH_VisCent	LH_VisPeri	RH_ContC	LH_DefaultC	RH_ContC
4	RH_ContB	RH_VisCent	LH_SalVentAttnA	RH_DorsAttnA	RH_DefaultC	LH_SalVentAttnA
5	RH_LimbicB_OFC	LH_DefaultC	RH_ContC	RH_SalVentAttnA	RH_DefaultB	RH_DefaultA
6	RH_SalVentAttnB	RH_SomMotB	RH_ContA	LH_ContC	RH_LimbicB_OFC	LH_ContC
7	RH_SomMotB	RH_DefaultC	RH_DefaultA	RH_DefaultC	LH_SomMotB	RH_DorsAttnA
8	RH_TempPar	LH_SomMotB	RH_SalVentAttnA	LH_SomMotB	RH_LimbicA_TempPole	LH_LimbicB_OFC
9	LH_DefaultB	LH_LimbicA_TempPole	LH_DefaultC	RH_ContA	LH_DefaultB	LH_SomMotB
10	RH_SalVentAttnA	RH_LimbicA_TempPole	RH_VisPeri	RH_VisCent	RH_SomMotB	RH_DefaultC

Table 5: Attr_X: Top 10 brain subnetworks that are sources of the important signals during different tasks (fig. 6 provides a ROI-based visualization).

	rest	VWM	DYN	DOT	MOD	PVT
1	RH_VisCent	RH_VisCent	LH_TempPar	RH_LimbicB_OFC	LH_TempPar	RH_VisCent
2	LH_VisCent	LH_VisCent	LH_LimbicA_TempPole	LH_LimbicA_TempPole	LH_LimbicA_TempPole	LH_DorsAttnA
3	LH_DorsAttnA	LH_DorsAttnA	LH_VisPeri	RH_DefaultB	RH_SomMotB	LH_VisCent
4	RH_DorsAttnA	RH_DorsAttnA	LH_DefaultA	LH_TempPar	LH_DefaultB	RH_DorsAttnA
5	LH_ContA	LH_ContA	LH_DefaultC	RH_LimbicA_TempPole	RH_DefaultA	RH_LimbicB_OFC
6	LH_DorsAttnB	LH_DorsAttnB	RH_DefaultC	RH_TempPar	RH_LimbicA_TempPole	LH_ContA
7	LH_SomMotA	LH_SalVentAttnA	RH_SomMotA	LH_DefaultB	LH_LimbicB_OFC	RH_LimbicA_TempPole
8	LH_SalVentAttnA	LH_SomMotA	LH_ContB	LH_LimbicB_OFC	RH_DefaultB	LH_SomMotB
9	RH_ContA	RH_LimbicB_OFC	RH_SalVentAttnB	RH_SomMotB	LH_ContB	LH_LimbicB_OFC
10	LH_LimbicB_OFC	LH_LimbicB_OFC	LH_DefaultB	LH_DefaultA	LH_DefaultA	LH_DorsAttnB