# Interpretable visualization of single cell data using Janus autoencoders

## Abstract

The emergence of single-cell transcriptomics and proteomics approaches has resulted in a wealth of high-dimensional data that are challenging to interpret. Dimensionality reduction methods, such as UMAP and t-SNE, project data points onto a low-dimensional space that preserves cellular similarities from the high-dimensional measurement space. However, the projected dimensions typically have no interpretable biological meaning, and the relationships between measured biomolecular features are obscured completely. These limitations can be overcome by finding embeddings in which each dimension is a function of a distinct and biologically meaningful set of features. Here, we introduce Janus autoencoders, a novel neural network architecture capable of finding such low-dimensional embeddings by jointly optimizing multiple distinct one-dimensional embeddings of a dataset. We demonstrate the utility of Janus autoencoders for (1) visualizing multiomic data such that modality-specific contributions to cell type can be deconvolved and (2) visualizing mass cytometry data such that cell cycle effects can be distinguished from "true" cell state differences. Our initial demonstrations indicate that Janus autoencoders can uncover relationships between cellular states and their underlying cellular features in multiple biological contexts, with the potential to generally enable highly interpretable visualizations of single cell data.

## 1 Introduction

Single-cell sequencing technologies enable the profiling of whole genomes and/or transcriptomes of thousands of single cells in a single experiment [10, 6]. Single-cell proteomics technologies, such as mass cytometry (CyTOF), CITE-seq, and CODEX, use antibodies to detect proteins of interest, and allow for the simultaneous quantification of over 50 epitopes in thousands of single cells [2, 14, 8]. Such high-dimensional measurements yield information on regulatory mechanisms of cellular behaviors and enable investigations of cellular and tissue heterogeneity. However, precise interpretations of highly multiplexed data remain challenging.

Visualization is an essential step in the analysis of high dimensional single cell data. Dimensionality reduction techniques allow visualization of -omics data in two-dimensional space. Principal component analysis (PCA) is typically performed to linearly transform and project high-dimensional data to coordinates that preserve variation in cellular state. Recently popularized non-linear dimensionality reduction techniques, such as t-stochastic neighbour embedding (t-SNE) [11] and uniform manifold approximation and projection (UMAP) [1], aim to find a nonlinear mapping from a high-dimensional measurement space to a low-dimensional (typically 2D) space, in which similarities between data points are preserved.

Although UMAP and t-SNE are widely used in analyzing transcriptomics and proteomics data, a few inherent limitations of these type of methods prevent deep and precise biological interpretations.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

First, the low-dimensional embeddings identified by UMAP and t-SNE are determined by arbitrary nonlinear maps of the high-dimensional input space. As such, the dimensions of the low-dimensional embedding have no interpretable biological meaning. Second, while these methods preserve the similarity of single cells, the relationships between features are lost completely in the nonlinear mapping. Third, multi-omics analysis with UMAP or t-SNE involves intensive data normalization, preprocessing and integration [3, 9] which could potentially bias resulting visualizations.

One-SENSE, a related nonlinear dimensionality reduction approach, aims to find embeddings in which the dimensions have interpretable biological meaning and relationships between markers of interest are preserved [5]. This is done by splitting measured cellular features into biologically meaningful categories using prior knowledge, mapping each category of features to a single dimension using t-SNE or UMAP, and plotting the one dimensional embeddings together. This yields dimensions that each represent a distinct category of features, such that variation along an axis indicates the category of features responsible the variation.

However, one-SENSE visualizations typically lack well-defined clusters and clear distinctions of cell state [5, 12]. We hypothesize that this due to the lack of robustness of reduction to a single dimension using UMAP and t-SNE. It has been shown that there are often many appreciably different yet equally faithful low dimensional embeddings of single cell data [4]. As there are likely to be several equivalently faithful one-dimensional embeddings, different pairs of one-dimensional embeddings may have very different qualities when jointly visualized in two-dimensional space. In one-SENSE, the two one-dimensional embeddings are optimized completely separately, so an "optimal" pair of one-dimensional embeddings cannot be identified.

In this work, we seek to visualize single cell data using a nonlinear dimensionality reduction method in which each reduced dimension represents a distinct, biologically meaningful set of features. In contrast with previous methods, we preserve cell state information by jointly optimizing multiple one-dimensional embeddings in a context-aware fashion. To perform this optimization, we introduce Janus autoencoders, a novel neural network architecture. We demonstrate the utility of Janus autoencoders for two tasks: (1) visualizing multiomic data such that modality-specific contributions to cell state can be deconvolved, and (2) visualizing mass cytometry data such that cell cycle effects can be distinguished from "true" cell state differences.

## 2  Results

### 2.1  Network architecture

In order to jointly optimize multiple one dimensional embeddings of high dimensional data, we have developed a topologically modified autoencoder that we refer to as a Janus ("two-faced") autoencoder (Fig 1). While traditional autoencoders find low dimensional latent spaces in which each dimension is a function of all input dimensions, Janus autoencoders constrain the information used in each latent dimension by restricting the connectivity of the network. In particular, Janus autoencoders contain multiple disjoint encoder modules which map distinct sets of input dimensions to distinct latent dimensions, each of which can be used for a one-dimensional embedding. To ensure that these latent dimensions yield faithful joint embeddings as well as faithful one-dimensional embeddings, we use multiple decoder modules: one for each latent dimension which aims to reconstruct only the connected inputs, and one "joint" decoder which aims to reconstruct the full initial input based on all latent dimensions.

In the case of a Janus autoencoder with 2 latent dimensions, where the input $X$ is split into disjoint categories $X_1, X_2$, with reconstructions $\hat{X}, \hat{X_1}, \hat{X_2}$, we use a weighted mean-squared error loss function

$$\mathcal{L}(\hat{x_1}, \hat{x_2}, \hat{x}, x_1, x_2, x) = w_1 MSE(\hat{x_1}, x_1) + w_2 MSE(\hat{x_2}, x_2) + w_3 MSE(\hat{x}, x)$$

where the decoder weights $w_1, w_2, w_3$ are user-defined parameters which must be tuned for each specific application.

In initial demonstrations, we have used three hidden layers for each of the encoders and decoders, generally following the rule of thumb that each successive hidden encoding layer should decrease in size by a factor of 2 until enforced to be 1 in the latent dimension, and the inverse for decoding layers.

Figure 1: Workflow of single cell data visualization using Janus autoencoders. First, features in high dimensional single cell data are split into biologically meaningful categories. Then, a Janus autoencoder is trained on the dataset with categorized features. The Janus autoencoder architecture contains two encoder modules (shown with inputs $X_1, X_2$) and three decoder modules (shown with outputs $\hat{X}, \hat{X}_1, \hat{X}_2$). This architecture jointly optimizes two latent dimensions, each of which represents a different category of features. Finally, the optimized latent space (shown in dark red and dark blue) is used to visualize the dataset.

Anecdotally, we find that embeddings are not particularly sensitive to hidden layer sizes, and default selections are often sufficient.

## 2.2 Decoupling modal contributions to cell type in single cell CITE-seq data

Janus autoencoders are natural tools for analyzing multiomic datasets. With each measurement modality mapped to a different latent dimension, it is possible to infer modality-specific contributions to cell state based on visualization of the latent space. We demonstrate a proof-of-concept using a publically available CITE-seq [14] dataset quantifying the transcripts and surface proteins of 5,000 peripheral blood mononuclear cells (PBMCs) [7].

In line with prior analyses of multiomic PBMC datasets [3], we first determined putative coarse cell type clusters based on multiplexed Leiden clustering. As expected, visualization of the dataset using a traditional 2D UMAP preserves putative cell type clusters (Fig. 2a). However, in this visualization, it is not possible to deconvolve the contributions of the two modalities.

Such deconvolution is possible when each reduced dimension contains information from only one modality. A oneSENSE plot, where UMAP reductions to a single dimension are performed separately for RNA measurements and protein measurements, satisfies this criteria. However, we find that oneSENSE is unable to preserve putative cell type clusters (Fig. 2b), indicating inaccurate embeddings.

With visualization by Janus autoencoding, each axis is determined using only information from a single modality, and putative cell clusters are preserved, indicating accurate embeddings (Fig. 2c). Based on the Janus autoencoder visualization, we observe that the RNA measurements contain a large amount of cell type information, and that protein measurements can be used to resolve transcriptomically similar cell types. This is in line with observations made in a recent integrative analysis of other multiomic PBMC datasets [9].

Additionally, the Janus autoencoder shows distinct populations of PBMCs within coarse cell type clusters. The putative monocyte cluster (shown in blue) diverges into two populations in the Janus

(a) 2D UMAP        (b) oneSENSE        (c) Janus autoencoding

Figure 2: Visualizations of CITE-seq profiling of PBMCs, colored by putative cell type. **(a)** A conventional 2D UMAP plot. **(b)** A one-SENSE plot, where the X and Y dimensions are 1D UMAP reductions of RNA and protein measurements respectively. **(c)** A Janus autoencoding visualization, where the X and Y dimensions are neural network encodings of RNA and protein measurements respectively.

autoencoder visualization, separated only on the protein dimension, suggesting that cells with similar transcriptomic state may exhibit different surface marker profiles due to the exogenously induced cell surface protein remodeling or post-tranlational modifications. Similarly, the CD8+ memory T cell cluster (shown in green) diverges into two sub-clusters along the RNA axis in the Janus autoencoder visualization, indicating thatcells with similar surface marker signatures could have distinct transcriptomic states.

It has been demonstrated that mRNA levels in cells and tissues do not predict protein abundance [15]. In this initial demonstration, we show that Janus antoencoders could be used to decipher relationships between transcriptome and proteome in multi-omics data.

## 2.3 Regressing out cell cycle effects in mass cytometry data

It is known that experimentally meaningful single cell variation is often obscured by confounding factors such as cell cycle stage and cell size [13]. Using Janus autoencoders, it is possible to map potential confounding features to a different latent dimension than other markers of interest, allowing one to visualize the effects of and regress out confounding features in single cell datasets.

We demonstrate a proof of concept using a mass cytometry dataset which profiles 4 proteins with prominent cell cycle dependence in addition to 31 intracellular phosphorylation sites in a monocyte cell line (THP1) [13]. As observed in prior work, non-cell-cycle aware analyses, such as visualization with 2D UMAP, erroneously indicate the presence of multiple cell clusters due to the differential cell cycle states of analyzed cells (Fig 3a).

By analyzing cell-cycle dependent markers independently from the phosphorylation panel, it is possible to deconvolve cell cycle effects from experimentally meaningful differences in cell state. When applying oneSENSE with cell cycle markers mapped to one dimension and standard targets mapped to another dimension, we see that almost all single cell variation is attributable to cell cycle (Fig 3b). However, the oneSENSE plot contains cluster-like structures, rather than the ground-truth continuum expected based on prior work [13]. Additionally, the oneSENSE plot fails to recover an accurate pseudotime ordering of cells, as approximated by phospho-RB expression.

When visualized with Janus autoencoders, it is clear that cell state is relatively homogeneous when standard phosphorylation targets are decoupled from cell-cycle dependent targets, with the exception of cells in M-phase, in line with prior analyses [13]. Furthermore, the Janus autoencoder visualization faithfully reconstructs the pseudotime ordering of the cells in their cell cycle state (Fig. 3c). This analysis indicates that Janus autoencoders enable directly analyzing the effects of confounding factors in mass cytometry data without intensive data correction or normalization.

|              |              |                     |
|:------------:|:------------:|:-------------------:|
| (a) 2D UMAP  | (b) oneSENSE | (c) Janus autoencoding |

Figure 3: Visualization of mass cytometry profiling of THP1 cell line. **(a)** A conventional 2D UMAP plot, colored based on phospho-RB expression, a correlate of cell cycle pseudotime. **(b)** A one-SENSE plot, where the X and Y dimensions are 1D UMAP reductions of cell cycle markers and general protein measurements respectively. **(c)** A Janus autoencoding visualization, where the X and Y dimensions are neural network encodings of cell cycle markers and general protein measurements respectively.

## 3  Discussion

In this work, we have introduced Janus autoencoders, a novel neural network architecture for jointly learning multiple one dimensional embeddings of high dimensional data. Through initial demonstrations for modality-aware cell typing in multiomic data and cell cycle normalization in mass cytometry data, we have shown the potential general utility of Janus autoencoders for interpretable visualization of single cell data.

In both single-cell analysis problems, we observe that Janus autoencoders are able to capture the expected qualitative trends in cell state, while introducing meaning to the dimensions in visualizations. In the analysis of CITE-seq profiling of PBMCs, Janus autoencoders are able to capture cell type clusters while revealing the distinct contributions of the protein and RNA modalities. In the analysis of cell cycle effects in mass cytometry data, Janus autoencoders are able to reconstruct the pseudotime ordering of cells, while regressing out cell cycle dependent single cell variation.

Compared to oneSENSE, a similar approach utilizing 1D embeddings to profile the relationships between categorized sets of features, Janus autoencoders qualitatively demonstrate a greater capacity to capture cell type and pseudotime information in both initial demonstrations.

Cell typing, pseudotime inference, and confounding effect regression are common single cell data analysis tasks, each typically done using a distinct computational tool. In this work, we have shown that Janus autoencoders can perform each of these tasks, without explicit optimization for any specific task. This indicates that Janus autoencoders and similar approaches could potentially serve as general tools for nonlinear analyses of single cell data.

Janus autoencoders are subject to some of the same intrinsic shortcomings as other single cell data visualization techniques. In particular, for most high-dimensional datasets, it is highly unclear if reduction to a low dimensional space is mathematically justifiable. In future work, we plan to develop general metrics of embedding quality that can serve as a heuristic for the validity of visualizations produced by Janus autoencoders.

Janus autoencoders currently have not been formulated in a probabilistic setting. In future work, it would be compelling to create variational analogs of Janus autoencoders, such that identified latent spaces can be interpreted through the lens of Bayesian inference. Such formalization could enable quantitative exploration of embeddings, rather than qualitative assessments based on visualizations.

## 4  Acknowledgements

We thank Alan Amin and Tatiana Brailovskaya for fruitful discussions. We acknowledge the Caltech Summer Undergraduate Fellowship (SURF) Program and Wyss Institute Molecular Robotics Initiative (MRI) for funding. We thank the Jupyter Project for maintaining open-source computational tools.

# References

[1] Etienne Becht et al. "Dimensionality reduction for visualizing single-cell data using UMAP". en. In: *Nat. Biotechnol.* (Dec. 2018).

[2] Bernd Bodenmiller et al. "Multiplexed mass cytometry profiling of cellular states perturbed by small-molecule regulators". en. In: *Nat. Biotechnol.* 30.9 (Sept. 2012), pp. 858–867.

[3] Danila Bredikhin, Ilia Kats, and Oliver Stegle. "MUON: multimodal omics analysis framework". en. In: *Genome Biol.* 23.1 (Feb. 2022), p. 42.

[4] Tara Chari, Joeyta Banerjee, and Lior Pachter. "The Specious Art of Single-Cell Genomics". en. Aug. 2021.

[5] Yang Cheng et al. "Categorical Analysis of Human T Cell Heterogeneity with One-Dimensional Soli-Expression by Nonlinear Stochastic Embedding". en. In: *J. Immunol.* 196.2 (Jan. 2016), pp. 924–932.

[6] Charles Gawad, Winston Koh, and Stephen R Quake. "Single-cell genome sequencing: current state of the science". en. In: *Nat. Rev. Genet.* 17.3 (Mar. 2016), pp. 175–188.

[7] 10x Genomics. *PBMC 5k from 10x genomics*.

[8] Yury Goltsev et al. "Deep Profiling of Mouse Splenic Architecture with CODEX Multiplexed Imaging". en. In: *Cell* 174.4 (Aug. 2018), 968–981.e15.

[9] Yuhan Hao et al. "Integrated analysis of multimodal single-cell data". en. In: *Cell* 184.13 (June 2021), 3573–3587.e29.

[10] Allon M Klein et al. "Droplet barcoding for single-cell transcriptomics applied to embryonic stem cells". en. In: *Cell* 161.5 (May 2015), pp. 1187–1201.

[11] Dmitry Kobak and Philipp Berens. "The art of using t-SNE for single-cell transcriptomics". en. In: *Nat. Commun.* 10.1 (Nov. 2019), p. 5416.

[12] Florian Mair et al. "A Targeted Multi-omic Analysis Approach Measures Protein Expression and Low-Abundance Transcripts on the Single-Cell Level". en. In: *Cell Rep.* 31.1 (Apr. 2020), p. 107499.

[13] Maria Anna Rapsomaniki et al. "CellCycleTRACER accounts for cell cycle and volume in mass cytometry data". en. In: *Nat. Commun.* 9.1 (Feb. 2018), p. 632.

[14] Marlon Stoeckius et al. "Simultaneous epitope and transcriptome measurement in single cells". en. In: *Nat. Methods* 14.9 (July 2017), pp. 865–868.

[15] Bing Zhang et al. "Proteogenomic characterization of human colon and rectal cancer". en. In: *Nature* 513.7518 (Sept. 2014), pp. 382–387.