Exploiting Causal Graph Priors with Posterior Sampling for Reinforcement Learning

Abstract

Posterior sampling allows the exploitation of prior knowledge of the environment's transition dynamics to improve the sample efficiency of reinforcement learning. The prior is typically specified as a class of parametric distributions, a task that can be cumbersome in practice, often resulting in the choice of uninformative priors. In this work, we propose a novel posterior sampling approach in which the prior is given as a (partial) causal graph over the environment's variables. The latter is often more natural to design, such as listing known causal dependencies between biometric features in a medical treatment study. Specifically, we propose a hierarchical Bayesian procedure, called C-PSRL, simultaneously learning the full causal graph at the higher level and the parameters of the resulting factored dynamics at the lower level. For this procedure, we provide an analysis of its Bayesian regret, which explicitly connects the regret rate with the degree of prior knowledge. Our numerical evaluation conducted in illustrative domains confirms that C-PSRL strongly improves the efficiency of posterior sampling with an uninformative prior while performing close to posterior sampling with the full causal graph.

1 Introduction

Posterior sampling [51], also known as Thompson sampling, is a powerful alternative to classic optimistic methods for Reinforcement Learning (RL) [49], as it guarantees outstanding sample efficiency [35] through an explicit model of the epistemic uncertainty that allows exploiting prior knowledge over the environment's dynamics. Specifically, Posterior Sampling for Reinforcement Learning (PSRL) [48, 35] implements a Bayesian procedure (pseudocode is provided in Algorithm 1) in which, at every episode k, (1) a model of the environment's dynamics is sampled from a parametric prior distribution P_k, (2) an optimal policy π_k is computed (e.g., through value iteration [2]) according to the sampled model, (3) a posterior update is performed on the prior parameters to incorporate in P_{k+1} the evidence collected by running π_k in the true environment. Under the assumption that the true environment's dynamics are sampled with positive probability from the prior P_0, the latter procedure is guaranteed to converge to the true model and the optimal policy asymptotically while showcasing a Bayesian regret that scales with $O(\sqrt{K})$ being K the total number of episodes [37].

Although posterior sampling has been praised for its empirical prowess as well [6], specifying the prior as a class of parametric distributions, which is a crucial requirement of PSRL, can be cumbersome in practice. Let us take a Dynamic Treatment Regime (DTR) [33] as an illustrative application. In this setting, we aim to overcome a patient's disease by choosing treatment at each stage based on the patient's evolving conditions and previously administered treatments. The goal is to identify the best treatment for the specific patient quickly. Medicine provides plenty of prior knowledge to help solve the DTR problem efficiently. However, it is not easy to translate this knowledge into a parametric prior distribution that is general enough to include the model of any patient while being sufficiently

Submitted to 16th European Workshop on Reinforcement Learning (EWRL 2023). Do not distribute.

Algorithm 1 PSRL

---

    input: parametric prior P_0, episode horizon H
    for episode $k = 0, 2, \ldots, K - 1$ **do**
        Sample transition model $\mathcal{M}_k \sim P_k$
        Compute $\pi_k \leftarrow \arg\max_{\pi \in \Pi} V_{\mathcal{M}_k}(\pi)$
        Roll out policy π_k to collect data
        Update posterior P_{k+1} given P_k and new evidence
    end for

---

narrow to foster efficiency. Instead, it is remarkably easy to list some known causal relationships between patient's state variables, such as heart rate and blood pressure, or diabetes and glucose level. Those causal edges might come from experts' knowledge (e.g., physicians) or previous clinical studies. A prior in the form of a causal graph is clearly more natural to specify for practitioners, who might be unaware of the intricacies of Bayesian statistics. Posterior sampling does not currently support the specification of the prior through a causal graph, which limits its applicability.

This paper proposes a novel posterior sampling methodology that can exploit a prior specified through a partial causal graph over the environment's variables. Notably, a complete causal graph allows for a factorization of the environment's dynamics, which can be then expressed as a Factored Markov Decision Process (FMDP) [3]. PSRL can be applied to FMDPs, as demonstrated by previous work [36], where the authors assume to know the complete causal graph. However, this assumption is often unreasonable in practical applications.[1]

Instead, we consider having partial knowledge of the causal graph, which leads to considering a set of plausible FMDPs. Taking inspiration from [17, 26, 19, 18], we design a hierarchical Bayesian procedure that extends PSRL to the setting where the true model lies within a set of FMDPs (induced by the causal graph prior). We propose a novel algorithm, **C**ausal **PSRL** (C-PSRL), that considers two levels of prior knowledge. First, for every episode C-PSRL samples a factorization consistent with the causal graph prior. Then, it samples the model of the FMDP from a lower-level prior that is conditioned on the sampled factorization. After that, the algorithm proceeds similarly to PSRL.

Having introduced C-PSRL, we study the Bayesian regret it induces on the footsteps of previous analyses for PSRL in FMDPs [36] and hierarchical posterior sampling [19]. Our analysis shows that C-PSRL takes the best of both worlds by avoiding a direct dependence on the number of states in the regret (as in FMDPs) and without requiring a full causal graph prior (as in hierarchical posterior sampling). Moreover, we can analytically capture the dependency of the Bayesian regret on the number of causal edges known a priori and encoded in the (partial) causal graph prior. Finally, we empirically validate C-PSRL against two relevant baselines: PSRL with an uninformative prior, i.e., that does not model potential factorizations in the dynamics, and PSRL equipped with the full knowledge of the causal graph (an oracle prior). We carry out the comparison in simple yet illustrative domains, which show that exploiting a causal graph prior improves the efficiency over uninformative priors while being only slightly inferior to the oracle prior.

In summary, the main contributions of this paper include the following:

- A novel problem formulation that links PSRL with a prior expressed as a partial causal graph to the problem of learning an FMDP with unknown factorization (Section 2);
- A methodology (C-PSRL) that extends PSRL to exploit a partial causal graph prior (Section 3);
- The analysis of the Bayesian regret of C-PSRL, which is $\tilde{O}(\sqrt{K/2^\eta})$ where K is the total number of episodes and η is the degree of prior knowledge (Section 4);
- An ancillary result on causal identification that shows how a (sparse) super-graph of the true causal graph can be extracted from a run of C-PSRL as a byproduct (Section 5);
- An experimental evaluation of the performance of C-PSRL against PSRL with uninformative or oracle priors in illustrative domains (Section 6).

Finally, the aim of this work is to enable the use of posterior sampling for RL in relevant applications through a causal perspective on prior specification. We believe this contribution can help to close the gap between PSRL research and actual adoption of PSRL methods in real-world problems.

---

[1]DTR is an example, where several causal relations affecting patient's conditions remain a mystery.

2 Problem formulation

In this section, we first provide preliminary background on graphical causal models (Section 2.1) and Markov decision processes (Section 2.2). Then, we explain how a causal graph on the variables of a Markov decision process induces a factorization of its dynamics (Section 2.3). Finally, we formalize the reinforcement learning problem in the presence of a causal graph prior (Section 2.4).

Notation. With a few exceptions, we will denote a set or space with calligraphic letters $\mathcal{A}$, their elements with lowercase letters $a \in \mathcal{A}$, constants and random variables with uppercase letters A. A function f will also be lowercase. We denote $\Delta(\mathcal{A})$ the probability simplex over $\mathcal{A}$, and $[A]$ the set of integers $\{1, \ldots, A\}$. For a d-dimensional vector x, we define the *scope operator* $x[\mathcal{I}] := \bigotimes_{i \in \mathcal{I}} x_i$ for any set $\mathcal{I} \subseteq [d]$. When $\mathcal{I} = \{i\}$ is a singleton, we use $x[i]$ as a shortcut for $x[\{i\}]$.[2]

2.1 Causal graphs

Let $\mathcal{X} = \{X_j\}_{j=1}^{d_X}$ and $\mathcal{Y} = \{Y_j\}_{j=1}^{d_Y}$ be sets of random variables taking values $x_j, y_j \in [N]$ respectively, and let $p : \mathcal{X} \to \Delta(\mathcal{Y})$ a strictly positive probability density. Further, let $\mathcal{G} = (\mathcal{X}, \mathcal{Y}, z)$ be a bipartite Directed Acyclic Graph (DAG), or *bigraph*, having left variables $\mathcal{X}$, right variables $\mathcal{Y}$, and a set of edges $z \subseteq \mathcal{X} \times \mathcal{Y}$. We denote as z_j the parents of the variable $Y_j \in \mathcal{Y}$, such as $z_j = \{i \in [d_X] \mid (X_i, Y_j) \in z\}$ and $z = \bigcup_{j \in [d_Y]} \bigcup_{i \in z_j} \{(X_i, Y_j)\}$. We say that $\mathcal{G}$ is Z-sparse if $\max_{j \in [d_Y]} |z_j| \leq Z \leq d_X$, and we call Z the *degree of sparseness* of $\mathcal{G}$.

The tuple $(p, \mathcal{G})$ is called a *graphical causal model* [38] if p fulfills the Markov factorization property with respect to $\mathcal{G}$, that is $p(\mathcal{X}, \mathcal{Y}) = p(\mathcal{X})p(\mathcal{Y}|\mathcal{X}) = p(\mathcal{X}) \prod_{j \in [d_Y]} p_j(y[j]|x[z_j])$. Note that the causal model that we consider in this paper do not admit *confounding*, such as we can exclude "vertical" causal edges in $\mathcal{Y} \times \mathcal{Y}$ and directed edges $\mathcal{Y} \times \mathcal{X}$, which allows to write $p(\mathcal{X}, \mathcal{Y}) = p(\mathcal{X})p(\mathcal{Y}|\mathcal{X})$. Finally, we call *causal graph* the component $\mathcal{G}$ of a graphical causal model.

2.2 Markov decision processes

A finite episodic Markov Decision Process (MDP) [40] is defined as $\mathcal{M} := (\mathcal{S}, \mathcal{A}, p, r, \mu, H)$, where $\mathcal{S}$ is a state space of size S, $\mathcal{A}$ is an action space of size A, $p : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$ is a Markovian transition model such that $p(s'|s, a)$ denotes the conditional probability of the next state s' given the state s and action a, $r : \mathcal{S} \times \mathcal{A} \to \Delta([0, 1])$ is a reward function such that the reward collected performing action a in state s is distributed as $r(s, a)$ with mean $R(s, a) = \mathbb{E}[r(s, a)]$, $\mu \in \Delta(\mathcal{S})$ is the initial state distribution, $H < \infty$ is the episode horizon.

An agent interacts with the MDP as follows. First, the initial state is drawn $s_1 \sim \mu$. For each step $h < H$, the agent selects an action $a_h \in \mathcal{A}$. Then, they collect a reward $r_h \sim r(s_h, a_h)$ while the state transitions to $s_{h+1} \sim p(\cdot|s_h, a_h)$. The episode ends when s_H is reached.

The strategy from which the agent selects an action at each step is defined through a non-stationary, stochastic *policy* $\pi = \{\pi_h\}_{h \in [H]} \in \Pi$, where each $\pi_h : \mathcal{S} \to \Delta(\mathcal{A})$ is a function such that $\pi_h(a|s)$ denotes the conditional probability of selecting action a in state s at step h, and Π is the policy space. A policy $\pi \in \Pi$ can be evaluated through its value function $V_h^\pi : \mathcal{S} \to [0, H]$, which is the expected sum of rewards collected under π starting from state s at step h, i.e.,

$$V_h^\pi(s) := \mathbb{E}_\pi \left[\sum_{h'=h}^{H} R(s_{h'}, a_{h'}) \Big| s_h = s \right], \qquad \forall s \in \mathcal{S}, \ h \in [H].$$

We further define the expected value function under the initial state distribution of the MDP $\mathcal{M}$ as $V_\mathcal{M}(\pi) := \mathbb{E}_{s \sim \mu}[V_1^\pi(s)]$.

2.3 Causal structure induces factorization

In the previous Section 2.2, we formulated the MDP in the most general tabular representation, where each state (action) is identified by a unique symbol $s \in \mathcal{S}$ ($a \in \mathcal{A}$). However, in relevant real-world applications, the states and actions can be represented through a finite number of features. The DTR

---

[2]A recap of the notation, which is admittedly involved, can be found in Appendix A.

123 problem is an illustrative example, where state features can be, e.g., blood pressure and glucose level,
124 action features can be indicators on whether a particular medication is administered.

125 Let those state and action features be modeled by random variables in the interaction between an
126 agent and the MDP, we can consider additional structure in the process by considering the causal
127 graph of its variables, such that the value of a variable only depends on the values of its causal parents.
128 Looking back to DTR, we might know that the value of the blood pressure at step $h + 1$ only depends
129 on its value at step h and whether a particular medication has been administered.

130 Formally, we can show that combining an MDP $\mathcal{M} = (\mathcal{S}, \mathcal{A}, p, r, \mu, H)$ with a causal graph over its
131 variables, which we denote as $\mathcal{G}_\mathcal{M} = (\mathcal{X}, \mathcal{Y}, z)$, gives a Factored MDP (FMDP) [3]

$$\mathcal{F} = (\{\mathcal{X}_j\}_{j=1}^{d_X}, \{\mathcal{Y}_j, z_j, p_j, r_j,\}_{j=1}^{d_Y}, \mu, H, Z, N),$$

132 where $\mathcal{X} = \mathcal{S} \times \mathcal{A} = \mathcal{X}_1 \times \ldots \times \mathcal{X}_{d_X}$ is a factored state-action space with $d_X = d_S + d_A$ discrete
133 variables, $\mathcal{Y} = \mathcal{S} = \mathcal{Y}_1 \times \ldots \times \mathcal{Y}_{d_Y}$ is a factored state space with $d_Y = d_S$ variables, and z_j are
134 the causal parents of each state variable, which are obtained from the edges z of $\mathcal{G}_\mathcal{M}$. Then, p is
135 a *factored* transition model specified as $p(y|x) = \prod_{j=1}^{d_Y} p_j(y[j] \mid x[z_j]), \forall y \in \mathcal{Y}, x \in \mathcal{X}$, and r is
136 a *factored* reward function $r(x) = \sum_{j=1}^{d_Y} r(x[z_j])$, with mean $R(x) = \sum_{j=1}^{d_Y} R(x[z_j]), \forall x \in \mathcal{X}$.
137 Finally, $\mu \in \Delta(\mathcal{Y})$ and H are the initial state distribution and episode horizon as specified in $\mathcal{M}$, Z
138 is the degree of sparseness of $\mathcal{G}_\mathcal{M}$, N is a constant such that all the variables are supported in $[N]$.

139 The interaction between an agent and the FMDP can be described exactly as we did in Section 2.2 for
140 a tabular MDP, and the policies with their corresponding value functions are analogously defined.
141 With the latter formalization of the FMDP induced by a causal graph, we now have all the components
142 to introduce our learning problem in the next section.

2.4 Reinforcement learning with partial causal graph priors

144 In the previous Section 2.3, we show how the prior knowledge of a causal graph over the MDP
145 variables can be exploited to obtain an FMDP representation of the problem, which is well-known to
146 allow for more efficient reinforcement learning thanks to the factorization of the transition model
147 and reward function [36, 56, 50, 52, 7, 42]. However, in several applications is unreasonable to
148 assume prior knowledge of the full causal graph, and causal identification is costly in general [13, 44].
149 Nonetheless, *some* prior knowledge of the causal graph, i.e., a portion of the edges, may be easily
150 available. To name one application, in a DTR problem some edges of the causal graph on patient's
151 variables are commonly known, whereas several others are elusive.

152 In this paper, we study the reinforcement learning problem when a partial causal graph prior $\mathcal{G}_0 \subseteq \mathcal{G}_\mathcal{M}$
153 on the MDP $\mathcal{M}$ is available.[3] Especially, we formulate the learning problem in a Bayesian sense, in
154 which the instance is sampled from a prior distribution $P_0(\mathcal{G}_0)$ *consistent* with the causal graph prior
155 $\mathcal{G}_0$.[4] Then, analogously to previous works on Bayesian RL formulations, e.g., [35], we evaluate the
156 performance of a learning algorithm in terms of its induced Bayesian regret.

157 **Definition 1** (Bayesian Regret). *Let $\mathfrak{A}$ be a learning algorithm and let $P_0(\mathcal{G}_0)$ be a prior distribution
158 on FMDPs consistent with the partial causal graph prior $\mathcal{G}_0$. The K-episodes Bayesian regret of $\mathfrak{A}$
159 is given by*

$$\mathcal{BR}(K) := \mathop{\mathbb{E}}_{\mathcal{F}_* \sim P_0(\mathcal{G}_0)} \left[\sum_{k=1}^{K} V_*(\pi_*) - V_*(\pi_k) \right],$$

160 *where $V_*(\pi) = V_{\mathcal{F}_*}(\pi)$ is the value of the policy π in $\mathcal{F}_*$ under the initial state distribution,
161 $\pi_* \in \arg\max_{\pi \in \Pi} V_*(\pi)$ is the optimal policy in $\mathcal{F}_*$, and π_k is the policy played by algorithm $\mathfrak{A}$ at
162 step $k \in [K]$.*

163 Intuitively, the Bayesian regret allows to evaluate a learning algorithm on average over multiple
164 instances. This is particularly suitable in some domains, such as DTR, in which it is crucial to
165 achieve a good performance of the treatment policy on different patients. Having defined the learning
166 problem, in the next section we introduce an algorithm that achieves a Bayesian regret rate that is
167 sublinear in the number of episodes K.

---

[3]For two bigraphs $\mathcal{G}_\star = (\mathcal{X}, \mathcal{Y}, z_\star)$ and $\mathcal{G}_\bullet = (\mathcal{X}, \mathcal{Y}, z_\bullet)$, we let $\mathcal{G}_\star \subseteq \mathcal{G}_\bullet$ if $z_\star \subseteq z_\bullet$.
[4]We will specify in the next Section 3 how the prior $P_0(\mathcal{G}_0)$ can be constructed.

3 Causal PSRL

To face the learning problem described in the previous Section 2.4, we cannot naïvely apply the PSRL algorithm for FMDPs [36], since we cannot access the factorization z_* of the true instance $\mathcal{F}_*$, but only a causal graph prior $\mathcal{G}_0 = (\mathcal{X}, \mathcal{Y}, z_0)$ such that $z_0 \subseteq z_*$. Moreover, z_* is always *latent* in the interaction process, in which we can only observe state-action-reward realizations from $\mathcal{F}_*$. The observed realizations can be consistent with several factorizations of the transition dynamics of $\mathcal{F}_*$, which means we can neither extract z_* directly from data. This is the common setting of *hierarchical Bayesian methods* [17, 18, 26, 19], where a latent state is sampled from a latent hypothesis space on top of the hierarchy, which then conditions the sampling of the observed state down the hierarchy. In our setting, we can see the latent hypothesis space as the space of all the possible factorizations that are consistent with the prior $\mathcal{G}_0$, whereas the observed states are the model parameters of the FMDP, since we can observe realizations from those parameters. The algorithm that we propose, **C**ausal **PSRL** (C-PSRL), builds on this intuition to implement a principled hierarchical posterior sampling procedure to minimize the Bayesian regret exploiting the causal graph prior. In the following paragraph, we describe the details of the procedure, whereas we report its pseudocode in Algorithm 2.

Algorithm 2 Causal PSRL (C-PSRL)

1: **input**: causal graph prior $\mathcal{G}_0 \subseteq \mathcal{G}_{\mathcal{F}_*}$, degree of sparseness Z
2: Compute the set of consistent factorizations

$$\mathcal{Z} = \mathcal{Z}_1 \times \ldots \times \mathcal{Z}_{d_Y} = \left\{ z = \{z_j\}_{j \in [d_Y]} \quad \Big| \quad |z_j| < Z \text{ and } z_{0,j} \subseteq z_j \quad \forall j \in [d_Y] \right\}$$

3: Build the hyper-prior P_0 and the prior $P_0(\cdot|z)$ for each $z \in \mathcal{Z}$
4: **for** episode $k = 0, 1, \ldots, K - 1$ **do**
5:     Sample $z \sim P_k$ and $p \sim P_k(\cdot|z)$ to build the FMDP $\mathcal{F}_k$
6:     Compute the policy $\pi_k \leftarrow \arg\max_{\pi \in \Pi} V_{\mathcal{F}_k}(\pi)$
7:     Collect an episode with π_k in $\mathcal{F}_*$
8:     Compute the posteriors P_{k+1} and $P_{k+1}(\cdot|z)$ with the collected data
9: **end for**

First, C-PSRL computes the set $\mathcal{Z}$ of the factorizations consistent with the prior $\mathcal{G}_0$, i.e., which are both Z-sparse and include all of the edges in z_0 (line 2). Then, it specifies a parametric distribution P_0, which we call *hyper-prior*, over the latent hypothesis space $\mathcal{Z}$, and, for each $z \in \mathcal{Z}$, a further parametric distribution $P_0(\cdot|z)$, which is a *prior* on the model parameters, i.e., transition probabilities, conditioned on the latent state z (line 3). The former represents the agent's belief over the factorization of the true instance $\mathcal{F}_*$, whereas the latter is the belief on the factored transition model p_*.[5]

Having translated the causal graph prior $\mathcal{G}_0$ into proper parametric prior distributions, C-PSRL executes a hierarchical posterior sampling procedure (lines 4-9). For each episode k, the algorithm sample a factorization z from the current hyper-prior P_k, and a transition model p from the prior $P_k(\cdot|z)$, such that p is factored according to z (line 5). With these two objects, it builds the FMDP $\mathcal{F}_k$ (line 5), for which it computes the optimal policy π_k solving the corresponding planning problem (line 6). Finally, the policy π_k is deployed on the true instance $\mathcal{F}_*$ for an episode (line 7) to collect the evidence that serves to compute the posterior updates of the prior and hyper-prior (line 8).

As we shall see, the described Algorithm 2 has compelling statistical properties, as it suffers a sublinear regret in the number of episodes K (Section 4) while providing a notion of causal identification as a byproduct (Section 5), and showcases promising empirical performance (Section 6).

Informally, three key ingredients concur to make the algorithm successful. First and foremost, C-PSRL links the reinforcement learning of an FMDP $\mathcal{F}_*$ with unknown factorization to a hierarchical Bayesian learning problem, in which the factorization acts as a latent state on top of the hierarchy, and the transition probabilities are the observed state down the hierarchy. Secondly, C-PSRL exploits the causal graph prior $\mathcal{G}_0$ to reduce the size of the latent hypothesis space $\mathcal{Z}$, which is super-exponential in the number of features d_X, d_Y of $\mathcal{F}_*$ in general [41]. Finally, C-PSRL harnesses the specific causal structure of the problem to get a factorization z (line 5) through independent sampling of the parents $z_j \in \mathcal{Z}_j$ for each variable Y_j, which significantly reduces the number of hyper-prior parameters.

---

[5]A detailed description on the choice of parametric distributions P_0 and $P_0(\cdot|z)$, together with their corresponding posterior updates, is reported in Appendix B.

Crucially, this can be done as we do not admit "vertical" edges in $\mathcal{Y}$ and edges directed from $\mathcal{Y}$ to $\mathcal{X}$ in our hypothesis space, such that it is impossible to select parents' assignment that leads to a cycle. We report a couple of notes on C-PSRL below, before going through its analysis in the next sections.

Degree of sparseness. Notably, C-PSRL takes as input (line 1) the degree of sparseness Z of the true FMDP $\mathcal{F}_*$, which might be unknown in practice. In that case, Z can be seen as an hyper-parameter of the algorithm, which can be either implied through domain expertise or tuned independently.

Planning in FMDPs. C-PSRL requires exact planning in a FMDP (line 11), which is intractable in general [32, 29]. While we do not directly address computational issues in this paper, we note that efficient approximation schemes have been developed for this problem [14]. Moreover, under linear realizability assumptions for the transition model or value functions, i.e., they can be represented through a linear combination of known features, exact planning methods exist [57, 23, 8].

4 Regret analysis of C-PSRL

In this section, we study the Bayesian regret (see Definition 1) induced by C-PSRL taking as input a causal graph prior $\mathcal{G}_0 = (\mathcal{X}, \mathcal{Y}, z_0)$ with degree of sparseness Z. First, we further define the quantity

$$\eta \le \min_{j \in [d_Y]} |z_{0,j}|,$$

called *degree of prior knowledge*, which is a lower bound on the number of causal parents revealed by the prior $\mathcal{G}_0$ for each state variable Y_j of the true instance $\mathcal{F}_*$. With this definition, we provide an upper bound on the Bayesian regret incurred by C-PSRL, which we then discuss in Section 4.1.

Theorem 4.1. *Let $\mathcal{G}_0$ be a causal graph prior with degree of sparseness Z and degree of prior knowledge η. The K-episodes Bayesian regret incurred by* C-PSRL *is upper bounded as*[6]

$$\mathcal{BR}(K) \le \tilde{O}\left(\left(H^{5/2} N^{1+Z/2} d_Y + \sqrt{H 2^{d_X - \eta}}\right)\sqrt{K}\right).$$

While we defer the proof of the result to Appendix D, we report a sketch of its three main steps below.

Step 1. The first step of our proof bridges the previous analyses of a hierarchical version of PSRL, which is reported in [19], with the one of PSRL for factored MDPs [36]. In short, we can decompose the Bayesian regret (see Definition 1) as

$$\mathcal{BR}(K) = \mathbb{E}\left[\sum_{k=1}^{K} \mathbb{E}_k\left[V_*(\pi_*) - \overline{V}_k(\pi_*, Z_*)\right]\right] + \mathbb{E}\left[\sum_{k=1}^{K} \mathbb{E}_k\left[\overline{V}_k(\pi_k, Z_k) - V_*(\pi_k)\right]\right]$$

where we denote $\mathbb{E}_k[\cdot] := \mathbb{E}[\cdot \mid \mathcal{H}_k]$ the conditional expectation given the history of observations $\mathcal{H}_k = ((x_{h,l}, r_{h,l}))_{h \in [H], l \in [k-1]}$ collected until episode k, and $\overline{V}_k(\pi, z) = \mathbb{E}_{\mathcal{F} \sim P_k(\cdot|z)}[V_{\mathcal{F}}(\pi)]$ the value function of the policy π on average over the FMDPs $\mathcal{F}$ having factored transition model $p \sim P_k(\cdot|z)$ sampled from the posterior in episode k. Informally, the first term captures the regret due to the concentration of the *posterior* $P_k(\cdot|z_*)$ around the true transition model p_* having fixed the true factorization z_*. Instead, the second term captures the regret due to the concentration of the *hyper-posterior* P_k around the true factorization z_*. Each term can be bounded separately through a non-trivial adaptation of the analysis in [19] to the FMDP setting, which leads to the upper bound

$$\tilde{O}\left(\left(H^{5/2} N^{1+Z/2} d_Y + \sqrt{H|\mathcal{Z}|}\right)\sqrt{K}\right).$$

Step 2. The upper bound of the previous step is close to the final result up to a factor $\sqrt{|\mathcal{Z}|}$ related the size of the latent hypothesis space. Since C-PSRL performs local sampling from the product space $\mathcal{Z} = \mathcal{Z}_1 \times \ldots \times \mathcal{Z}_{d_Y}$, by combining independent samples $z_j \in \mathcal{Z}_j$ for each variable Y_j as we briefly explained in Section 3, we can refine the dependence in $|\mathcal{Z}|$ to $\max_{j \in [d_Y]} |\mathcal{Z}_j| \le |\mathcal{Z}|$.

Step 3. Finally, we aim to capture the dependency in the degree of prior knowledge η in the Bayesian regret. To do that, we have to express $\max_{j \in [d_Y]} |\mathcal{Z}_j|$ in terms of η. Formally, we can derive

$$\max_{j \in [d_Y]} |\mathcal{Z}_j| = \sum_{i=0}^{Z - \eta} \binom{d_X - \eta}{i} \le 2^{d_X - \eta}$$

which gives the final rate reported in Theorem 4.1.

---

[6]We report the regret rate with the common "Big-Oh" notation, in which $\tilde{O}$ hides logarithmic factors.

4.1 Discussion of the Bayesian regret

The regret bound in Theorem 4.1 contains two main terms, which informally capture the regret to learn the transition model having the true factorization (left), and to learn the true factorization (right).

The first term is typical in previous analyses of vanilla posterior sampling. Especially, the best known rate for the MDP setting is $\tilde{O}(H\sqrt{SAK})$ [37]. In a FMDP setting with known factorization, the direct dependencies with the size S, A of the state and action spaces can be refined to obtain $\tilde{O}(Hd_Y^{3/2}N^{Z/2}\sqrt{K})$ [36]. Our rate includes additional factors of H and N, but a better dependency on the number of state features d_Y.

The second term of the regret rate is instead unique to hierarchical Bayesian settings, which include an additional source of randomization in the sampling of the latent state from the hyper-prior. In Theorem 4.1 we are able to express this term in the degree of prior knowledge η, resulting in a rate $\tilde{O}(\sqrt{K/2^\eta})$. The latter naturally demonstrates that a richer causal graph prior $\mathcal{G}_0$ will benefit the efficiency of PSRL, bringing the regret rate closer to the one for an FMDP with known factorization.

Finally, we believe that the rate in Theorem 4.1 is shedding light on how prior causal knowledge, here expressed through a partial causal graph, impacts on the efficiency of posterior sampling for reinforcement learning.

5 C-PSRL embeds a notion of causal identification

In this section, we provide an ancillary result that links Bayesian regret minimization with C-PSRL to a notion of causal identification, which we call *weak*. Especially, we show that we can extract a Z-sparse super-graph of the causal graph $\mathcal{G}_{\mathcal{F}_*}$ of the true instance $\mathcal{F}_*$ as a byproduct.

A run of C-PSRL produces a sequence of policies $\{\pi_k\}_{k=0}^{K-1}$ that are optimal for the FMDPs $\{\mathcal{F}_k\}_{k=0}^{K-1}$ drawn from the posteriors. Every FMDP $\mathcal{F}_k$ is linked to a corresponding graph (or factorization) $\mathcal{G}_{\mathcal{F}_k} = (\mathcal{X}, \mathcal{Y}, z_k)$, where $z_k \sim P_k(\cdot|\mathcal{H}_k)$ is sampled from the hyper-posterior. Note that the algorithm does not enforce any causal meaning to the edges z_k of $\mathcal{G}_{\mathcal{F}_k}$. Nonetheless, we aim to show that we can extract a Z-sparse super-graph of $\mathcal{G}_{\mathcal{F}_*}$ from the sequence $\{\mathcal{F}_k\}_{k=0}^{K-1}$ with high probability.

First, we need to assume that any misspecification in the graph $\mathcal{G}_{\mathcal{F}_k}$ negatively affects the value function of the policy π_k. To this purpose, we extend the traditional notion of causal minimality [46] to value functions.

Definition 2 (ϵ-Value Minimality). *An FMDP $\mathcal{F}$ fulfills ϵ-value minimality, if for any FMDP $\mathcal{F}'$ encoding a proper subgraph of $\mathcal{G}_{\mathcal{F}}$, i.e., $\mathcal{G}_{\mathcal{F}'} \subset \mathcal{G}_{\mathcal{F}}$, it holds that $V_{\mathcal{F}}^* > V_{\mathcal{F}'}^* + \epsilon$, where $V_{\mathcal{F}}^*, V_{\mathcal{F}'}^*$ are the value functions of the optimal policies in $\mathcal{F}, \mathcal{F}'$ respectively.*

Then, as a corollary of Theorem 4.1, we can prove the following result.

Corollary 5.1 (Weak Causal Identification). *Let $\mathcal{F}_*$ be an FMDP in which the transition model p_* fulfill the causal minimality assumption with respect to $\mathcal{G}_{\mathcal{F}_*}$, and let $\mathcal{F}_*$ fulfill ϵ-value minimality. Then, $\mathcal{G}_{\mathcal{F}_*} \subseteq \mathcal{G}_{\mathcal{F}_K}$ holds with high probability, where $\mathcal{G}_{\mathcal{F}_K}$ is a Z-sparse graph randomly selected within the sequence $\{\mathcal{G}_{\mathcal{F}_k}\}_{k=0}^{K-1}$ produced by C-PSRL over $K \geq \tilde{O}(H^5 d_Y^2 2^{d_X - \eta}/\epsilon^2)$ episodes.*

The latter result shows that C-PSRL does identify the causal relationships between the FMDP variables, but cannot easily prune the non-causal edges, making $\mathcal{G}_{\mathcal{F}_K}$ a super-graph of $\mathcal{G}_{\mathcal{F}_*}$. In Appendix C, we report a detailed derivation of the previous result. Interestingly, Corollary 5.1 suggests a direct link between regret minimization in a FMDP with unknown factorization and a (weak) notion of causal identification, which might be further explored in future works.

6 Experiments

In this section, we provide experiments to both support the design of C-PSRL (Section 3) and validate its regret rate (Section 4). To this end, we consider two simple yet illustrative domains. The first, which we call *Random FMDP*, benchmarks the performance of C-PSRL on randomly generated FMDP instances, a setting akin to the Bayesian learning problem (see Section 2.4) that we considered in previous sections. The latter is instead a traditional RL environment, called *Taxi* [9], which is

Figure 1: **(a,b)** Regret and model error as a function of the episodes in the Random FMDP domain with $d_X = 9, d_Y = 6, Z = 5, N = 2, H = 100$. **(c,d)** Regret as a function of the episodes Taxi 3×3 with $d_X = 5, d_Y = 4, Z = 5, N = [3, 3, 2, 1, 6], H = 10$, Taxi 5×5 with $d_X = 5, d_Y = 4, Z = 5, N = [5, 5, 2, 1, 6], H = 15$. The plots report the mean and 95% c.i. over 20 runs.

naturally factored and hints at a potential application. In those domains, we compare C-PSRL against two natural baselines: PSRL for tabular MDPs [48], and Factored PSRL (F-PSRL), which extends PSRL to factored MDP settings [36]. Note that F-PSRL is equivalent to an instance of C-PSRL that receives the true causal graph prior as input, i.e., has an oracle prior.

Random FMDPs. In this domain, an FMDP (relevant parameters are reported in the caption of Figure 1) is sampled uniformly from the prior specified through a random causal graph, which is Z-sparse with at least two edges for every state variable ($\eta = 2$). Then, the regret is minimized by running PSRL, F-PSRL, and C-PSRL ($\eta = 2$) for 500 episodes. Figure 1a shows that C-PSRL achieves a regret that is significantly smaller than PSRL, thus outperforming the baseline with an uninformative prior, while being surprisingly close to F-PSRL, having the oracle prior. Indeed, C-PSRL resulted efficient in estimating the transition model of the sampled FMDP, as we can see from Figure 1b, which reports the ℓ_1 distance between the true model p_* and the p_k sampled by the algorithm at episode k.

Taxi. For the experiments in the Taxi domain, which was initially proposed by [9], we use the common Gym implementation [4]. In this environment, a taxi driver needs to pick up a passenger at a specific location, and then it has to bring the passenger to their destination. The environment is represented as a grid, with some special cells identifying the passenger location and destination. As reported in [45], this domain is inherently factored since the state space is represented by four independent features: The position of the taxi (row and column), the passenger's location and whether they are on the taxi, and the destination. We perform the experiment on two grids with varying size (3×3 and 5×5 respectively), for which we report the relevant parameters in Figure 1. Here we compare the proposed algorithm C-PSRL ($\eta = 2$) with PSRL. Both algorithms converge to a good policy eventually in the smaller grid (see the regret in Figure 1c). Instead, when the size of the grid increases, PSRL is still suffering a linear regret after 400 episodes, whereas C-PSRL succeeds in finding a good policy efficiently (see Figure 1d). Notably, this domain resembles the problem of learning optimal routing in a taxi service, and our results show that exploiting common knowledge (such as that the location of the taxi and passenger's destination) in the form of a causal graph prior can be a game changer for the resulting performance.

7 Related work

We revise here the most relevant related work in posterior sampling, factored MDPs, and causal RL.

Posterior sampling. Thompson sampling [51] is a well-known Bayesian algorithm that has been extensively analyzed in both multi-armed bandit problems [25, 1] and reinforcement learning [35, 37]. Specifically, Osband et al. [37] provides a regret rate $\tilde{O}(H\sqrt{SAK})$ for vanilla Thompson sampling in RL, which is called the PSRL algorithm. Recently, other works adapted Thompson sampling to hierarchical Bayesian problems [17, 26, 18, 19]. Mixture Thompson Sampling (MixTS) [19], which is similar to PSRL but samples the unknown MDP from a mixture prior, is arguably the closest to our setting. In this paper, we take inspiration from their algorithm to design C-PSRL and derive its analysis, even though we tackle a fundamentally different problem on factored MDPs resulting from a casual graph prior instead of their tabular setting, which induces unique challenges.

Factored MDPs.   Our setting is also related to FMDPs [3]. Previous works considered reinforcement learning in FMDPs with either known [36, 56, 50, 52, 7] or unknown [47, 54, 10, 5, 16, 15, 42] factorization. Especially, the PSRL algorithm has been adapted to both finite-horizon [36] and infinite-horizon [56] FMDPs. The former assumes knowledge of the factorization, which is close to our setting with an oracle causal graph prior, and provides Bayesian regret rate of order $\tilde{O}(Hd_Y^{3/2}N^{Z/2}\sqrt{K})$. Previous works have also studied reinforcement learning in FMDPs in a frequentist sense, either with known [7] or unknown [42] factorization. The latter [42] employs an optimistic method that is orthogonal to ours, whereas they leave as an open problem capturing the effect of prior knowledge, for which we provide answers in a Bayesian setting.

Causal RL.   Previous works have addressed the reinforcement learning problem with a causal perspective (see [24, Chapter 7] for a survey of such methods). Those works typically exploit causal principles to obtain compact representations of states and transitions [53, 12], or to pursue generalization across tasks and environments [58, 20, 11, 34]. Closer to our setting, Lu et al. [28] address the problem of exploiting prior causal knowledge to learn in both MDPs and FMDPs. Our work differs from theirs in two key aspects: We show how to exploit a partial causal graph prior instead of assuming knowledge of the full causal graph, and we consider a Bayesian formulation of the problem while they tackle a frequentist setting through optimism principles. Finally, the work in [61] shows an interesting application of causal RL for designing treatments in a DTR problem.

8   Conclusion

In this paper, we presented how to exploit prior knowledge expressed through a partial causal graph to improve the statistical efficiency of reinforcement learning. Before reporting some concluding remarks, it is worth commenting on where such a causal graph prior might be originated from.

Exploiting experts' knowledge.   One natural application of our methodology is to exploit domain-specific knowledge coming from experts. In several domains, e.g., medical or scientific applications, experts practitioners have some knowledge over the causal relationships between the domain's variables. However, they might not have a full picture of the causal structure, especially when they face complex systems such as the human body or biological processes. Our methodology allows those practitioners to easily encode their partial knowledge into a graph prior, instead of having to deal with technically involved Bayesian statistics to specify parametric prior distributions, and then let C-PSRL figure out a competent decision policy with the given information.

Exploiting causal identification.   Identifying the causal graph over domain's variables, which is usually referred as causal identification or causal discovery, is a main focus of *causality* [38, Chapter 3]. The literature provides plenty of methods to perform causal identification from data [39, Chapter 4], including learning causal variables and their relationships in MDP settings [58, 34]. However, learning the full causal graph, even when it is represented with a bigraph as in MDP settings [34], can be statistically costly or even prohibitive [13, 55]. Moreover, not all the causal edges are guaranteed to transfer across environments [34], which would force to perform causal identification anew for any slight variation of the domain (e.g., changing the patient in a DTR setting). Our methodology allows to focus on learning the *universal* causal relationships [34], which transfer across environments (e.g., different patients), and then specify the prior through a partial causal graph.

The latter paragraphs describe two scenarios in which our work enhance the applicability of PSRL, bridging the gap between how the prior might be specified in practical applications and what previous methods currently require, i.e., a parametric prior distribution. To summarize our contributions, we first provided a Bayesian formulation of reinforcement learning with prior knowledge expressed through a partial causal graph. Then, we presented an algorithm, C-PSRL, tailored for the latter problem, and we analyzed its regret to obtain a rate that is sublinear in the number of episodes and shows a direct dependence with the degree of causal knowledge. Finally, we derived an ancillary result to show that C-PSRL embeds a notion of causal identification, and we provided an empirical validation of the algorithm against relevant baselines. C-PSRL resulted nearly competitive with F-PSRL, which enjoys a richer prior, while clearly outperforming PSRL with an uninformative prior.

Future works may derive a tighter analysis of the Bayesian regret of C-PSRL, as well as a stronger causal identification result that allows to recover a minimal causal graph instead of a super-graph. Finally, another important future direction is to address computational issues inherent to planning in FMDPs to scale the implementation of C-PSRL to complex domains.

References

[1] Shipra Agrawal and Navin Goyal. Analysis of Thompson sampling for the multi-armed bandit problem. In *Conference on Learning Theory*, 2012.

[2] Richard Bellman. Dynamic programming. *Princeton University Press*, 1957.

[3] Craig Boutilier, Richard Dearden, and Moisés Goldszmidt. Stochastic dynamic programming with factored representations. *Artificial Intelligence*, 121(1-2):49–107, 2000.

[4] Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

[5] Doran Chakraborty and Peter Stone. Structure learning in ergodic factored mdps without knowledge of the transition function's in-degree. In *International Conference on Machine Learning*, 2011.

[6] Olivier Chapelle and Lihong Li. An empirical evaluation of Thompson sampling. In *Advances in Neural Information Processing Systems*, 2011.

[7] Xiaoyu Chen, Jiachen Hu, Lihong Li, and Liwei Wang. Efficient reinforcement learning in factored mdps with application to constrained rl. In *International Conference on Learning Representations*, 2020.

[8] Zihao Deng, Siddartha Devic, and Brendan Juba. Polynomial time reinforcement learning in factored state mdps with linear value functions. In *International Conference on Artificial Intelligence and Statistics*, 2022.

[9] Thomas G. Dietterich. Hierarchical reinforcement learning with the maxq value function decomposition. *Journal of Artificial Intelligence Research*, 13:227–303, 2000.

[10] Carlos Diuk, Lihong Li, and Bethany R Leffler. The adaptive k-meteorologists problem and its application to structure learning and feature selection in reinforcement learning. In *International Conference on Machine Learning*, 2009.

[11] Fan Feng, Biwei Huang, Kun Zhang, and Sara Magliacane. Factored adaptation for non-stationary reinforcement learning. In *Advances in Neural Information Processing Systems*, 2022.

[12] Maxime Gasse, Damien Grasset, Guillaume Gaudron, and Pierre-Yves Oudeyer. Causal reinforcement learning using observational and interventional data. *arXiv preprint arXiv:2106.14421*, 2021.

[13] Steven B Gillispie and Michael D Perlman. Enumerating Markov equivalence classes of acyclic digraph models. In *Uncertainty in Artificial Intelligence*, 2001.

[14] Carlos Guestrin, Daphne Koller, Ronald Parr, and Shobha Venkataraman. Efficient solution algorithms for factored mdps. *Journal of Artificial Intelligence Research*, 19:399–468, 2003.

[15] Zhaohan Daniel Guo and Emma Brunskill. Sample efficient feature selection for factored mdps. *arXiv preprint arXiv:1703.03454*, 2017.

[16] Assaf Hallak, François Schnitzler, Timothy Mann, and Shie Mannor. Off-policy model-based learning under unknown factored dynamics. In *International Conference on Machine Learning*, 2015.

[17] Joey Hong, Branislav Kveton, Manzil Zaheer, Yinlam Chow, Amr Ahmed, and Craig Boutilier. Latent bandits revisited. In *Advances in Neural Information Processing Systems*, 2020.

[18] Joey Hong, Branislav Kveton, Manzil Zaheer, and Mohammad Ghavamzadeh. Hierarchical bayesian bandits. In *International Conference on Artificial Intelligence and Statistics*, 2022.

[19] Joey Hong, Branislav Kveton, Manzil Zaheer, Mohammad Ghavamzadeh, and Craig Boutilier. Thompson sampling with a mixture prior. In *International Conference on Artificial Intelligence and Statistics*, 2022.

[20] Biwei Huang, Fan Feng, Chaochao Lu, Sara Magliacane, and Kun Zhang. Adarl: What, where, and how to adapt in transfer reinforcement learning. In *International Conference on Learning Representations*, 2022.

[21] Chi Jin, Zeyuan Allen-Zhu, Sebastien Bubeck, and Michael I Jordan. Is Q-learning provably efficient? In *Advances in Neural Information Processing Systems*, 2018.

[22] Chi Jin, Akshay Krishnamurthy, Max Simchowitz, and Tiancheng Yu. Reward-free exploration for reinforcement learning. In *International Conference on Machine Learning*, 2020.

[23] Chi Jin, Zhuoran Yang, Zhaoran Wang, and Michael I Jordan. Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*, 2020.

[24] Jean Kaddour, Aengus Lynch, Qi Liu, Matt J Kusner, and Ricardo Silva. Causal machine learning: A survey and open problems. *arXiv preprint arXiv:2206.15475*, 2022.

[25] Emilie Kaufmann, Nathaniel Korda, and Rémi Munos. Thompson sampling: An asymptotically optimal finite-time analysis. In *Algorithmic Learning Theory*, 2012.

[26] Branislav Kveton, Chih wei Hsu, Craig Boutilier, Csaba Szepesvari, Manzil Zaheer, Martin Mladenov, and Michael Konobeev. Meta-Thompson sampling. In *International Conference on Machine Learning*, 2021.

[27] Tor Lattimore and Csaba Szepesvári. *Bandit Algorithms*. Cambridge University Press, 2020.

[28] Yangyi Lu, Amirhossein Meisami, and Ambuj Tewari. Efficient reinforcement learning with prior causal knowledge. In *Conference on Causal Learning and Reasoning*, 2022.

[29] Christopher Lusena, Judy Goldsmith, and Martin Mundhenk. Nonapproximability results for partially observable markov decision processes. *Journal of Artificial Intelligence Research*, 14:83–103, 2001.

[30] Olivier Marchal and Julyan Arbel. On the sub-Gaussianity of the Beta and Dirichlet distributions. *Electronic Communications in Probability*, 22:1–14, 2017.

[31] Alexander Marx, Arthur Gretton, and Joris M Mooij. A weaker faithfulness assumption based on triple interactions. In *Uncertainty in Artificial Intelligence*, 2021.

[32] Martin Mundhenk, Judy Goldsmith, Christopher Lusena, and Eric Allender. Complexity of finite-horizon Markov decision process problems. *Journal of the ACM (JACM)*, 47(4):681–720, 2000.

[33] Susan A Murphy. Optimal dynamic treatment regimes. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 65(2):331–355, 2003.

[34] Mirco Mutti, Riccardo De Santi, Emanuele Rossi, Juan Felipe Calderon, Michael Bronstein, and Marcello Restelli. Provably efficient causal model-based reinforcement learning for systematic generalization. In *AAAI Conference on Artificial Intelligence*, 2023.

[35] Ian Osband, Daniel Russo, and Benjamin Van Roy. (More) efficient reinforcement learning via posterior sampling. In *Advances in Neural Information Processing Systems*, 2013.

[36] Ian Osband and Benjamin Van Roy. Near-optimal reinforcement learning in factored mdps. In *Advances in Neural Information Processing Systems*, 2014.

[37] Ian Osband and Benjamin Van Roy. Why is posterior sampling better than optimism for reinforcement learning? In *International Conference on Machine Learning*, 2017.

[38] Judea Pearl. *Causality*. Cambridge University Press, 2009.

[39] Jonas Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of causal inference: Foundations and learning algorithms*. The MIT Press, 2017.

[40] Martin L Puterman. *Markov decision processes: Discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

[41] Robert W Robinson. Counting labeled acyclic digraphs. *New Directions in the Theory of Graphs*, pages 239–273, 1973.

[42] Aviv Rosenberg and Yishay Mansour. Oracle-efficient regret minimization in factored mdps with unknown structure. In *Advances in Neural Information Processing Systems*, 2021.

[43] Daniel Russo and Benjamin Van Roy. Learning to optimize via posterior sampling. *Mathematics of Operations Research*, 39(4):1221–1243, 2014.

[44] Rajen D. Shah and Jonas Peters. The hardness of conditional independence testing and the generalised covariance measure. *Annals of Statistics*, 48(3):1514–1538, 2020.

[45] Thiago D Simão and Matthijs TJ Spaan. Safe policy improvement with baseline bootstrapping in factored environments. In *AAAI Conference on Artificial Intelligence*, 2019.

[46] Peter Spirtes, Clark N Glymour, Richard Scheines, and David Heckerman. *Causation, prediction, and search*. The MIT Press, 2000.

[47] Alexander L Strehl, Carlos Diuk, and Michael L Littman. Efficient structure learning in factored-state mdps. In *AAAI Conference on Artificial Intelligence*, 2007.

[48] Malcolm Strens. A Bayesian framework for reinforcement learning. In *International Conference on Machine Learning*, 2000.

[49] Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[50] Mohammad Sadegh Talebi, Anders Jonsson, and Odalric Maillard. Improved exploration in factored average-reward mdps. In *International Conference on Artificial Intelligence and Statistics*, 2021.

[51] William R. Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 1933.

[52] Yi Tian, Jian Qian, and Suvrit Sra. Towards minimax optimal reinforcement learning in factored Markov decision processes. In *Advances in Neural Information Processing Systems*, 2020.

[53] Manan Tomar, Amy Zhang, Roberto Calandra, Matthew E Taylor, and Joelle Pineau. Model-invariant state abstractions for model-based reinforcement learning. *arXiv preprint arXiv:2102.09850*, 2021.

[54] Christopher M Vigorito and Andrew G Barto. Incremental structure learning in factored mdps with continuous states and actions. *University of Massachusetts Amherst-Department of Computer Science, Technical Report*, 2009.

[55] Samir Wadhwa and Roy Dong. On the sample complexity of causal discovery and the value of domain expertise. *arXiv preprint arXiv:2102.03274*, 2021.

[56] Ziping Xu and Ambuj Tewari. Reinforcement learning in factored mdps: Oracle-efficient algorithms and tighter regret bounds for the non-episodic setting. In *Advances in Neural Information Processing Systems*, 2020.

[57] Lin Yang and Mengdi Wang. Sample-optimal parametric Q-learning using linearly additive features. In *International Conference on Machine Learning*, 2019.

[58] Amy Zhang, Clare Lyle, Shagun Sodhani, Angelos Filos, Marta Kwiatkowska, Joelle Pineau, Yarin Gal, and Doina Precup. Invariant causal prediction for block mdps. In *International Conference on Machine Learning*, 2020.

[59] Jiji Zhang. A comparison of three Occam's razors for Markovian causal models. *The British Journal for the Philosophy of Science*, 2020.

[60] Jiji Zhang and Peter Spirtes. Detection of unfaithfulness and robust causal inference. *Minds and Machines*, 18(2):239–271, 2008.

[61] Junzhe Zhang. Designing optimal dynamic treatment regimes: A causal reinforcement learning approach. In *International Conference on Machine Learning*, 2020.

Table of Contents

 # A List of Symbols

Basic Mathematical Objects

$\mathcal{A}$	$\triangleq$	Set or space
A	$\triangleq$	Constant or random variable
a	$\triangleq$	Element of a set
$\Delta(\mathcal{A})$	$\triangleq$	Probability simplex over $\mathcal{A}$
$f : \mathcal{A} \to \mathcal{B}$	$\triangleq$	Function from $\mathcal{A}$ to $\mathcal{B}$
$[A]$	$\triangleq$	Set of integers $[A] = \{1, \dots, A\}$
$x[\mathcal{I}]$	$\triangleq$	Scope operator $x[\mathcal{I}] := \bigotimes_{i \in \mathcal{I}} x_i$ for any set $\mathcal{I} \subseteq [d]$, $x \in \mathbb{R}^d$

Causal Graph

$\mathcal{G}$	$\triangleq$	Directed acyclic bigraph $\mathcal{G} = (\mathcal{X}, \mathcal{Y}, z)$
$\mathcal{X}$	$\triangleq$	Set of d_X random variables $\{X_j\}_{j=1}^{d_X}$ taking values $x_j \in [N]$
$\mathcal{Y}$	$\triangleq$	Set of d_Y random variables $\{Y_j\}_{j=1}^{d_Y}$ taking values $y_j \in [N]$
z	$\triangleq$	Directed edges $z \subseteq \mathcal{X} \times \mathcal{Y}$
z_j	$\triangleq$	Parents of Y_j such that $z_j = \{i \mid (X_i, Y_j) \in z\}$
Z	$\triangleq$	Degree of sparseness such that $|z_j| < Z, \forall j \in [d_Y]$
N	$\triangleq$	Size of the support of random variables

MDP

$\mathcal{M}$	$\triangleq$	Markov decision process $\mathcal{M} = (\mathcal{S}, \mathcal{A}, p, r, \mu, H)$
$\mathcal{S}$	$\triangleq$	State space
$\mathcal{A}$	$\triangleq$	Action space
p	$\triangleq$	Transition model $p : \mathcal{S} \times \mathcal{A} \to \Delta(\mathcal{S})$
r	$\triangleq$	Reward function $r : \mathcal{S} \times \mathcal{A} \to \Delta([0,1])$
μ	$\triangleq$	Initial state distribution $\mu \in \Delta(\mathcal{S})$
H	$\triangleq$	Episode horizon $H < \infty$
S	$\triangleq$	Size of the state space $S = |\mathcal{S}|$
A	$\triangleq$	Size of the action space $A = |\mathcal{A}|$
s	$\triangleq$	State $s \in \mathcal{S}$
a	$\triangleq$	Action $a \in \mathcal{A}$
$R(s, a)$	$\triangleq$	Mean reward $\mathbb{E}[r(s, a)]$

Factored MDP

$\mathcal{F}$	$\triangleq$	Factored Markov Decision Process $\mathcal{F} = (\{\mathcal{X}_j\}_{j=1}^{d_X}, \{\mathcal{Y}_j, z_j, p_j, r_j,\}_{j=1}^{d_Y}, \mu, H, Z, N)$
d_X	$\triangleq$	Number of state-action variables
d_Y	$\triangleq$	Number of state variables
$\mathcal{X}$	$\triangleq$	Factored state-action space $\mathcal{X} = \mathcal{X}_1 \times \dots \times \mathcal{X}_{d_X}$
$\mathcal{Y}$	$\triangleq$	Factored state space $\mathcal{Y} = \mathcal{Y}_1 \times \dots \times \mathcal{Y}_{d_Y}$
z	$\triangleq$	Directed edges $z \subseteq \mathcal{X} \times \mathcal{Y}$, i.e., a *factorization*
z_j	$\triangleq$	Parents of Y_j such that $z_j = \{i \mid (X_i, Y_j) \in z\}$
p	$\triangleq$	Factored transition model $p(y|x) = \prod_{j=1}^{d_Y} p_j(y[j] \mid x[z_j])$
r	$\triangleq$	Factored reward function $r(x) = \sum_{j=1}^{d_Y} r_j(x[z_j])$
μ	$\triangleq$	Initial state distribution $\mu \in \Delta(\mathcal{Y})$
H	$\triangleq$	Episode horizon $H < \infty$
Z	$\triangleq$	Degree of sparseness such that $|z_j| < Z, \forall j \in [d_Y]$
N	$\triangleq$	Size of the support of state and action variables

Learning Problem

K	$\triangleq$	Number of episodes
k	$\triangleq$	Episode index
h	$\triangleq$	Step index

$\mathcal{Z}$	$\triangleq$	Space of the consistent factorizations $\mathcal{Z} \subseteq \mathcal{X} \times \mathcal{Y}$
$\mathcal{Z}_j$	$\triangleq$	Space of the consistent parents of Y_j such that $\mathcal{Z} = \mathcal{Z}_1 \times \ldots \mathcal{Z}_{d_Y}$
$\mathcal{BR}(K)$	$\triangleq$	K-episodes Bayesian regret

Analysis

Ω	$\triangleq$	Maximum cardinality set of possible assignments of a factor
d_R	$\triangleq$	Number of factors of the reward function
n	$\triangleq$	Value index on support of random variable, $n \in [N]$
$\mathcal{H}_k$	$\triangleq$	History until episode k
Z_k	$\triangleq$	Random variable of the global factorization at episode k
Z_j^k	$\triangleq$	Random variable of the local factorization at episode k for factor j
Z_*	$\triangleq$	Random variable of the true global factorization
Z_{j*}	$\triangleq$	Random variable of the true local factorization for j-th factor
C	$\triangleq$	Size of space of global factorizations $\mathcal{Z}$
$\overline{C}$	$\triangleq$	Upper bound on the size of space of local factorizations $\mathcal{Z}_j, \forall j \in [d_Y]$
$\mathbb{E}_k[\cdot]$	$\triangleq$	Conditional expectation given history $\mathcal{H}_k$, $\mathbb{E}_k[\cdot] := \mathbb{E}[\cdot \mid \mathcal{H}_k]$
$\mathbb{P}_k[\cdot]$	$\triangleq$	Conditional probability given history $\mathcal{H}_k$, $\mathbb{P}_k[\cdot] := \mathbb{P}[\cdot \mid \mathcal{H}_k]$

B   Parametric Priors and Posterior Updates

In the following, we detail how the hyper-priors and priors of C-PSRL (Algorithm 2) can be specified through parametric distributions, and how the corresponding parameters are updated with the evidence provided by the collected data.

The hyper-prior $P_0 = \{P_{0,j}\}_{j=1}^{d_Y}$ is defined through d_Y distributions over the set of *local factorizations* $\mathcal{Z}_1, \ldots, \mathcal{Z}_{d_S}$, where each $\mathcal{Z}_j$ contains the parents assignments for the variable Y_j consistent with the graph prior $\mathcal{G}_0$. Let assume any arbitrary ordering of the local factorizations $z_i \in \mathcal{Z}_j$, such that each z_i is indexed by $i \in [|\mathcal{Z}_j|]$. Then, we can specify the hyper-prior j as a categorical distribution

$$P_{0,j}(z_i; \boldsymbol{\omega}) = \mathrm{Cat}(i; \boldsymbol{\omega}) = \frac{\omega_i}{\sum_t \omega_t},$$

where the sum is over $t \in [|\mathcal{Z}_j|]$, and the vector of parameters $\boldsymbol{\omega}$ is initialized as $\boldsymbol{\omega} = (1, \ldots, 1)$.

Then, for each local factorization $z_i \in \mathcal{Z}_j$ of the variable Y_j, we specify the prior $P_{0,j}(\cdot|z_i)$ over the model parameters of the corresponding transition factor p_j. The transition factor p_j is an $(N^{|\mathcal{Z}_j|}, N)$ stochastic matrix. The prior is specified through a Dirichlet distribution for each row of p_j, i.e.,

$$p_{0,j}(\cdot \mid z_i; \boldsymbol{\alpha}) = \mathrm{Dir}(\theta_1, \ldots, \theta_N; \alpha_1, \ldots, \alpha_N) = \frac{1}{B(\boldsymbol{\alpha})} \prod_{n=1}^{N} \theta_n^{\alpha_n - 1},$$

where $\boldsymbol{\alpha}$ is a vector of parameters initialized as $\boldsymbol{\alpha} = (1, \ldots, 1)$ and $B(\alpha) = \prod_{n=1}^{N} \Gamma(\alpha_n) / \Gamma(\sum_n \alpha_n)$ is a normalizing factor.

Having specified the hyper-prior and prior, we now show how to update them with the new evidence. Let be $\theta_1, \ldots \theta_N \sim P_{k,j}(\cdot|x[z_j]; \boldsymbol{\alpha})$, and assume to collect the transition $(x[z_j], y[j] = i)$ from the true FMDP $\mathcal{F}_*$. Then, the posterior is

$$P_{k+1,j}(\theta_1, \ldots, \theta_N) \propto P(y[j] = i \mid \theta_1, \ldots, \theta_N) P_{k,j}(\theta_1, \ldots, \theta_N; \boldsymbol{\alpha}) \propto \theta_i \prod_{n=1}^{N} \theta^{\alpha_n - 1},$$

which is still a Dirichlet distribution with parameters $\mathrm{Dir}(\theta_1, \ldots, \theta_N; \alpha_1, \ldots, \alpha_i + 1, \ldots, \alpha_N)$. Then, we can propagate the posterior up the hierarchy to update the hyper-prior as

$$P_{k+1,j}(z) \propto P(y[j] = i \mid z) P_{t,j}(z; \boldsymbol{\omega})$$

$$\propto P_{k,j}(z; \boldsymbol{\omega}) \int P(y[j] = i \mid \theta_1, \ldots, \theta_N) P_{t,j}(\theta_1, \ldots, \theta_N \mid z) \mathrm{d}(\theta_1, \ldots, \theta_N) \quad (1)$$

$$\propto P_{k,j}(z; \boldsymbol{\omega}) \int \theta_i \frac{1}{B(\boldsymbol{\alpha})} \prod_{n=1}^{N} \theta_n^{\alpha_n - 1} \mathrm{d}(\theta_1, \ldots, \theta_N) \quad (2)$$

$$\propto P_{k,j}(z; \boldsymbol{\omega}) \frac{1}{B(\boldsymbol{\alpha})} B(\alpha_1, \ldots, \alpha_i + 1, \ldots, \alpha_N) \quad (3)$$

$$\propto P_{k,j}(z; \boldsymbol{\omega}) \frac{\alpha_i + 1}{\sum_t \alpha_t + 1} \quad (4)$$

where (2) is obtained by plugging the parametric prior in (1), we derive (3) by computing the integral over the simplex of $(\theta_1, \ldots, \theta_N)$, and (4) follows from $\Gamma(\alpha_i + 1) \prod_{t \neq i} \Gamma(\alpha_t) = (\alpha_i + 1) \prod_t \Gamma(\alpha_t)$ and $\Gamma(\alpha_i + 1 + \sum_{t \neq i} \alpha_t) = \Gamma(\sum_t \alpha_t) \sum_t (\alpha_t + 1)$. The resulting posterior is still a categorical distribution with the parameters $\omega_i \leftarrow \omega_i \frac{\alpha_i + 1}{\sum_t \alpha_t + 1}$.

C Weak Causal Identification

In the following, we show that we can extract, under a relatively mild causal minimality assumption, a Z-sparse super-DAG of the true causal graph $\mathcal{G}_{\mathcal{F}_*}$ as a byproduct of a run of Algorithm 2. We call this result *weak causal identification*, to make a clear distinction between discovering a sparse super-DAG of a causal graph and true causal identification, in which the minimal graph is discovered.

As required for any causal discovery algorithm, we need to state an assumption that connects the causal graph $\mathcal{G}_{\mathcal{F}_*}$ with the distribution p_* (i.e., the transition model) from which our observations are sampled in an i.i.d. manner [46]. Typically, in causal discovery, it is assumed that p_* fulfills the faithfulness assumption with regard to $\mathcal{G}_{\mathcal{F}_*}$, i.e., every independence in p_* implies a d-separation (see Definition 4 below) in $\mathcal{G}_{\mathcal{F}_*}$. Faithfulness, however, is a rather strong assumption which can be violated by path cancellations or xor-type dependencies, and weaker assumptions have been proposed [46, 38, 31]. In this work, we build upon a strictly weaker assumption than faithfulness: causal minimality [46].[7]

Definition 3 (Causal Minimality). *A distribution P satisfies causal minimality with respect to a DAG $\mathcal{G}$ if P fulfills the Markov factorization property with respect to $\mathcal{G}$, but not with respect to any proper subgraph of $\mathcal{G}$.*

Intuition   More intuitively, a distribution is minimal with respect to $\mathcal{G}$ if and only if there is no node that is conditionally independent of any of its parents, given the remaining parents [39]. There are two important points in this statement: i) none of the parents of a node is redundant, and ii) the dependence to a parent may only be detected given the remaining parents. Aspect ii) is a strictly weaker statement than required by faithfulness, which can be illustrated with a simple example. Consider the causal structure $X \to Y \leftarrow Z$, where all random variables are binary. If we generate X and Z via an unbiased coin and assign Y as $Y := X$ xor Z, Y will be marginally independent of X, as well as marginally independent of Z. However, Y is not independent of X (resp. Z) when we condition on its second parent Z (resp. X). Such an example violates faithfulness, i.e., there is a causal edge that is not matched by a dependence, but it does not violate causal minimality. For a more detailed discussion on such triples, we refer to Marx et al. [31].

In our context, Algorithm 2 has a positive probability of sampling all parents jointly (or a superset of them), and does not rely on checking pairs individually. Therefore, we can build upon the weaker assumption, causal minimality. Beyond identifiability in the limit, we are interested in the finite sample behaviour of our approach. Therefore, we propose a slightly stronger assumption for the value function, which is inspired by causal minimality.

Definition 2 (ϵ-Value Minimality). *An FMDP $\mathcal{F}$ fulfills ϵ-value minimality, if for any FMDP $\mathcal{F}'$ encoding a proper subgraph of $\mathcal{G}_{\mathcal{F}}$, i.e., $\mathcal{G}_{\mathcal{F}'} \subset \mathcal{G}_{\mathcal{F}}$, it holds that $V_{\mathcal{F}}^* > V_{\mathcal{F}'}^* + \epsilon$, where $V_{\mathcal{F}}^*, V_{\mathcal{F}'}^*$ are the value functions of the optimal policies in $\mathcal{F}$, $\mathcal{F}'$ respectively.*

Intuitively, ϵ-value minimality ensures that if we were to miss a true parent, the resulting optimal value function would be at most ϵ-optimal compared to the optimal value function evaluated on a graph that contains all true parents. Based on this rather lightweight assumption, we can extract from Algorithm 2 a graph $\mathcal{G}_{\mathcal{F}_K}$ that is guaranteed to be either the true DAG $G_{\mathcal{F}_*}$, or a Z-sparse super-DAG of $\mathcal{G}_{\mathcal{F}_*}$ with high probability.

Corollary 5.1 (Weak Causal Identification). *Let $\mathcal{F}_*$ be an FMDP in which the transition model p_* fulfill the causal minimality assumption with respect to $\mathcal{G}_{\mathcal{F}_*}$, and let $\mathcal{F}_*$ fulfill ϵ-value minimality. Then, $\mathcal{G}_{\mathcal{F}_*} \subseteq \mathcal{G}_{\mathcal{F}_K}$ holds with high probability, where $\mathcal{G}_{\mathcal{F}_K}$ is a Z-sparse graph randomly selected within the sequence $\{\mathcal{G}_{\mathcal{F}_k}\}_{k=0}^{K-1}$ produced by C-PSRL over $K \geq \tilde{O}(H^5 d_Y^2 2^{d_X - \eta}/\epsilon^2)$ episodes.*

Proof. From Theorem 4.1, we have that the K-episodes Bayesian regret of Algorithm 2 is

$$\mathbb{E}\left[\sum_{k=0}^{K-1} V_*(\pi_*) - V_*(\pi_t)\right] \leq C_1 \sqrt{H^5 d_Y^2 2^{d_X - \eta}} \cdot \sqrt{K},$$

---

[7]The definition refers SGS-minimality proposed by Spirte, Glymour, and Scheines [46]. There exists an alternative definition called P-minimality, proposed by [38]. In our setting, both assumptions are equivalent, since they only differ on graphs that violate triangle faithfulness [59, 60]. Since no nodes within $\mathcal{X}$ or within $\mathcal{Y}$ are allowed to be adjacent, such triangle structures cannot occur within our assumptions.

with high probability for some constant C_1 that does not depend on K. Through a standard regret-to-pac argument [21], it follows

$$\mathbb{E}\left[V_*(\pi_*) - V_*(\pi_K)\right] \leq c_2 \sqrt{H^5 d_Y^2 2^{d_X - \eta}} \cdot \frac{1}{\sqrt{K}} \tag{5}$$

with high probability for some constant C_2 that does not depend on K, and for a policy π_K that is randomly selected within the sequence of policies $\{\pi_k\}_{k=0}^{K-1}$ produced by Algorithm 2. By noting that π_K can be ϵ-optimal in the true FMDP $\mathcal{F}_*$ only if $\mathcal{G}_{\mathcal{F}_*} \subseteq \mathcal{G}_{\mathcal{F}_K}$ through the ϵ-value minimality assumption (Definition 2), we let $\mathbb{E}\left[V_*(\pi_*) - V_*(\pi_K)\right] = \epsilon$ in (5), which gives $K \geq C_2 H^5 d_Y^2 2^{d_X - \eta} / \epsilon^2$ and concludes the proof. $\qquad\square$

d-**Separation**   For the reader's convenience, here we report a brief definition of *d*-separation. More details can be found in [39].

Definition 4 (*d*-Separation). *A path $\langle X, \dots, Y \rangle$ between two vertices X, Y in a DAG is d-connecting given a set $\mathbf{Z}$, if*

  1. every collider[8] on the path is an ancestor of $\mathbf{Z}$, and

  2. every non-collider on the path is not in $\mathbf{Z}$.

If there is no path d-connecting X and Y given $\mathbf{Z}$, then X and Y are d-separated given $\mathbf{Z}$. Sets $\mathbf{X}$ and $\mathbf{Y}$ are d-separated given $\mathbf{Z}$, if for every pair X, Y, with $X \in \mathbf{X}$ and $Y \in \mathbf{Y}$, X and Y are d-separated given $\mathbf{Z}$.

---

[8]A collider C on a path $\langle \dots, Q, C, W, \dots \rangle$ is a node with two arrowhead pointing towards it, i.e. $\rightarrow C \leftarrow$.

D Regret Analysis

Theorem 4.1. *Let $\mathcal{G}_0$ be a causal graph prior with degree of sparseness Z and degree of prior knowledge η. The K-episodes Bayesian regret incurred by* C-PSRL *is upper bounded as*[9]

$$\mathcal{BR}(K) \leq \tilde{O}\left(\left(H^{5/2}N^{1+Z/2}d_Y + \sqrt{H2^{d_X - \eta}}\right)\sqrt{K}\right).$$

In the following paragraphs, the proof of Theorem 4.1 is derived employing the notation in section A. For the sake of clarity and modularity, the analysis is split into three parts, each reaching an independent regret bound and becoming progressively tighter and easier to interpret by exploiting more structure of the algorithm and input data. Each part leads to an upper bound of the Bayesian regret, and together they cover the following cases:

1. General (non-product) latent space, independent on degree of prior causal knowledge. This intermediate regret bound is reported in D.2;

2. Product latent space, independent on degree of prior causal knowledge. This intermediate regret bound is reported in D.3;

3. Product latent space, with explicit dependency on the degree of prior causal knowledge. This proves the regret bound in the theorem above, and it is reached in D.4.

For the sake of generality we derive some results without assuming that reward and transition model share the same factors. In particular, we express with $\left\{z_i^R\right\}_{i=1}^{d_R}$ the scopes of the reward function, and with $\left\{z_j^P\right\}_{i=1}^{d_Y}$ the scopes of the transition model. In order to derive the final regret bounds we assume $\left\{z_i^R\right\}_{i=1}^{d_R} = \left\{z_j^P\right\}_{i=1}^{d_Y} = \left\{z_j\right\}_{j=1}^{d_Y}$ as in the rest of the paper.

For a fixed state variable $j \in [d_Y]$, we define as Ω the space of all possible assignments of a factor $x[z_j]$ with scope z_j of maximum cardinality, i.e., $|z_j| = d_X$. Such a space Ω is composed by elements indexed with values in $[N]^{d_X}$ since each of the d_X nodes within the scope can have N values. For the sake of concision, we will express $p_k\left(y[j] \mid x[z_j]\right)$ as $p_k\left(x[z_j]\right)$.

D.1 High Probability Confidence Widths

The high probability confidence widths are built along the lines of [19] by exploiting the σ-subgaussianity of the random variables defined by the deviations, with the difference that the confidence widths are uniform over all factors and their possible assignments, rather than over state-action pairs as in the tabular setting. We express as $c_k(x[z_i^R])$ and $\phi_k(x[z_j^P])$ the confidence widths for the i-th factor of the reward function, and for the j-th factor of the transition model respectively.

Reward function First, we write the posterior mean reward as $\bar{r}_k(x[z_i^R]) = \mathbb{E}_{M \sim P_k(\cdot|z)}[R_M(x[z_i^R])]$. We wish to have a high probability bound of the type

$$\mathbb{P}_k\left(\left|R_M(x[z_i^R]) - \bar{r}_k(x[z_i^R])\right| \geq c_k(x[z_i^R])\right) \leq \frac{1}{K}$$

uniformly over all $i \in [d_R]$ and possible assignments $x[z_i^R] \in \Omega$. By the union bound, we have

$$\mathbb{P}_k\left(\left|R_M(x[z_i^R]) - \bar{r}_k(x[z_i^R])\right| \geq c_k(x[z_i^R])\right)$$

$$= \mathbb{P}_k\left(\bigcup_{i=1}^{d_R} \bigcup_{x[z_i^R] \in \Omega} \left\{\left|R_M(x[z_i^R]) - \bar{r}_k(x[z_i^R])\right| \geq c_k(x[z_i^R])\right\}\right)$$

$$\leq \sum_{i=1}^{d_R} \sum_{x[z_i^R] \in \Omega} \mathbb{P}_k\left(\left|R_M(x[z_i^R]) - \bar{r}_k(x[z_i^R])\right| \geq c_k(x[z_i^R])\right)$$

---

[9]We report the regret rate with the common "Big-Oh" notation, in which $\tilde{O}$ hides logarithmic factors.

From which, applying a union bound again, we can derive the following one-sided bound:

$$\mathbb{P}_k \left(R_M(x[z_i^R]) - \bar{r}_k(x[z_i^R]) \geq c_k(x[z_i^R]) \right) \leq \frac{1}{2Kd_RN^{d_x}}$$

According to Lemma D.1 $R_\Delta := R_M(x[z_i^R]) - \bar{r}_k(x[z_i^R])$ is a σ^2-subgaussian random variable with $\sigma^2 = 1/\left(4 \left(\|\alpha_k^R(z_i^R)\|_1 + 1 \right) \right)$. Therefore, through the Cramèr-Chernoff method exploited in Lemma D.2, we have that the high probability bound above holds if

$$\exp \left(-\frac{c_k(x[z_i^R])^2}{2\sigma^2} \right) \leq \frac{1}{2Kd_RN^{d_x}}$$

which holds if and only if

$$c_k(x[z_i^R]) \geq \sqrt{2\sigma^2 \log(2Kd_RN^{d_x})}$$

$$= \sqrt{\frac{\log(2Kd_RN^{d_x})}{2 \left(\|\alpha_k^R(x[z_i^R])\|_1 + 1 \right)}} \qquad \text{plugged-in } \sigma^2 \text{ of } R_\Delta$$

Hence, we pick $c_k(x[z_i^R]) := \sqrt{\frac{\log(2Kd_RN^Z)}{2\left(\|\alpha_k^R(x[z_i^R])\|_1 + 1 \right)}}$, where Z is an upper bound of d_X.

Transition model   The derivation is analogous to the one for the reward function, hence here we report only the differences. First, we write the posterior mean transition probability as $\bar{p}_k(x[z_j^P], n) = \mathbb{E}_{M \sim P_k(\cdot|z)} \left[p_M(x[z_j^P], n) \right]$, which is the probability, according to the posterior at time k, over the element $n \in [N]$ of the domain of the j-th component of Y. Since we want to bound the deviations over all components of a factor, we define the vector form of the previous expression as $\bar{p}_k(x[z_j^P]) = \left(\bar{p}_k(x[z_j^P], n) \right)_{n \in [N]}$. By following the same steps as for the confidence width of the reward function, we get

$$\phi_k(x[z_j^P]) := \sqrt{\frac{N \log(2Kd_YN^Z)}{2 \left(\|\alpha_k^P(x[z_j^P])\|_1 + 1 \right)}}$$

where the $\sqrt{N}$ term is due to [27, Theorem 5.4.c], since the l^1 norm sums over $N\sigma^2$-subgaussian random variables and therefore the induced random variable is $(N\sigma^2)$-subgaussian.

D.2   Part 1 - Bayesian Regret Decomposition

For episode k, we define $\overline{V}_k(\pi, z) = \mathbb{E}_{M \sim P_k(\cdot|z)} \left[V_M(\pi) \right]$ as the expected value of policy π according to the posterior conditioned on the latent factorization z and history $\mathcal{H}_k$. As shown in [43, Proposition 1] for the bandit setting and in [19, Section 5.1, equation 6] for the reinforcement learning setting, we can decompose the Bayesian regret as

$$\mathcal{BR}(n) = \mathbb{E}\left[\sum_{k=1}^K \mathbb{E}_k \left[V_*(\pi_*) - \overline{V}_k(\pi_*, Z_*) \right] \right] + \mathbb{E}\left[\sum_{k=1}^K \mathbb{E}_k \left[\overline{V}_k(\pi_k, Z_k) - V_*(\pi_k) \right] \right] \qquad (6)$$

by adding and subtracting $\overline{V}_k(\pi_*, Z_*)$ and noticing that π_*, Z_* are identically distributed to π_k, Z_k given $\mathcal{H}_k$. The first term represents the regret incurred due to the concentration of the posteriors of the reward and transition models given the true factorization, meanwhile the second term captures the cost to identify the true latent factorization. We will bound each term of the regret decomposition separately.

Upper bounding the first term of (6)   For episode k, we define the event

$$E_k = \Big\{ \forall j \in [d_Y], \forall x[Z_j] \in \Omega : \left| R_{M_k}(x[Z_j]) - \bar{r}_k(x[Z_j^k]) \right| \leq c_k(x[Z_j^k])$$

$$\text{and } \|p_{M_k}(x[Z_j]) - \bar{p}_k(x[Z_j^k])\|_1 \leq \phi(x[Z_j^k]) \Big\}$$

657 which express that the sampled rewards and transitions, which together constitute the (sampled)
658 environment M_t, are close to the posterior means for all possible assignments of the scopes.

659 We can rewrite the inner part of the first term of (6) as

$$\mathbb{E}_k \left[V_{M_k}(\pi_k) - \overline{V}_k(\pi_k, Z_k) \right]$$

$$= \mathbb{E}_k \left[\mathbb{E}_{M \sim P_k(\cdot | Z_k)} \left[V_{M_k}(\pi_k) - V_M(\pi_k) \right] \right]$$

$$\leq \mathbb{E}_k \left[\sum_{h=1}^{H} \left(R_{M_k}(S_{k,h}, A_{k,h}) - \bar{r}_k(S_{k,h}, A_{k,h}, Z_k) \right) + H \| p_{M_k}(S_{k,h}, A_{k,h}) - \bar{p}_k(S_{k,h}, A_{k,h}, Z_k) \|_1 \right]$$

$$\leq \mathbb{E}_k \left[\sum_{h=1}^{H} \sum_{j=1}^{d_Y} \left(R_{M_k}(X_{k,h}[Z_j]) - \bar{r}_k(X_{k,h}[Z_j^k]) \right) + H \sum_{j=1}^{d_Y} \| p_{M_k}(X_{k,h}[Z_j]) - \bar{p}_k(X_{k,h}[Z_j^k]) \|_1 \right]$$

$$\leq \mathbb{E}_k \left[H \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \left(R_{M_k}(X_{k,h}[Z_j]) - \bar{r}_k(X_{k,h}[Z_j^k]) \right) + \| p_{M_k}(X_{k,h}[Z_j]) - \bar{p}_k(X_{k,h}[Z_j^k]) \|_1 \right]$$

$$\leq \mathbb{E}_k \left[H \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \left(R_{M_k}(X_{k,h}[Z_j]) - \bar{r}_k(X_{k,h}[Z_j^k]) + \| p_{M_k}(X_{k,h}[Z_j]) - \bar{p}_k(X_{k,h}[Z_j^k]) \|_1 \right) \mathbb{1}\{\bar{E}_k\} \right]$$

$$+ \mathbb{E}_k \left[H \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \left(c_k(X_{k,h}[Z_j^k]) + \phi_k(X_{k,h}[Z_j^k]) \right) \mathbb{1}\{E_k\} \right]$$

660 where we have used the definition of $\overline{V}_k(\pi_k, Z_k)$ in the first step, the Lemma D.3 in the second step,
661 the Lemma D.4 in the third step, and the definition of E_k in the last step. We define $\beta_k(X_{k,h}[Z_j^k]) :=$
662 $c_k(X_{k,h}[Z_j^k]) + \phi_k(X_{k,h}[Z_j^k])$ as the some of both confidence widths. Hence, we can bound the
663 second term of the equation obtained at the last step by using Lemma D.5, while we bound the first
664 term of the same equation by showing that $\bar{E}_k$ conditioned on $\mathcal{H}_k$ is unlikely. We rewrite the first
665 term of (6) as

$$H \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \left(\mathbb{E}_k \left[\left(R_{M_k}(X_{k,h}[Z_j]) - \bar{r}_k(X_{k,h}[Z_j^k]) \right) \mathbb{1}\{\bar{E}_k\} \right] \right. \tag{7}$$

$$\left. + \mathbb{E}_k \left[\| p_{M_k}(X_{k,h}[Z_j]) - \bar{p}_k(X_{k,h}[Z_j^k]) \|_1 \mathbb{1}\{\bar{E}_k\} \right] \right)$$

666 For the first term of equation (7), we have

$$\mathbb{E}_k \left[\left(R_{M_k}(X_{k,h}[Z_j]) - \bar{r}_k(X_{k,h}[Z_j^k]) \right) \mathbb{1}\{\bar{E}_k\} \right]$$

$$\leq \sum_{x[Z_j] \in \Omega} \int_{r = c_k(X_{k,h}[Z_j^k])}^{\infty} r \, \mathbb{P}_k \left(\left(R_{M_k}(x[Z_j]) - \bar{r}_k(x[Z_j^k]) \right) = r \right) dr$$

$$\leq \sum_{x[Z_j] \in \Omega} \mathbb{P}_k \left(R_{M_k}(x[Z_j]) - \bar{r}_k(x[Z_j^k]) \geq c_k(x[Z_j^k]) \right)$$

$$\leq \sum_{x[Z_j] \in \Omega} \exp \left(-\frac{c_k(x[Z_j^k])^2}{2/4(\| \alpha_{k, Z_k}^R(x[Z_j]) \|_1 + 1)} \right)$$

$$= \sum_{x[Z_j] \in \Omega} \exp \left(-\frac{\frac{\log(2K d_R N^Z)}{2(\| \alpha_{k,z}^R(x[Z_j]) \|_1 + 1)}}{2/4(\| \alpha_{k, Z_k}^R(x[Z_j]) \|_1 + 1)} \right)$$

$$= \sum_{x[Z_j] \in \Omega} \exp \left(-\log(2K d_R N^Z) \right) = \frac{1}{2K d_R}$$

where in the third step we have used Lemma D.2 and D.1, and in the fourth step we have plugged-in the definition of $c_k(x[Z_j^k])$. For the second term of equation (7), we have

$$
\mathbb{E}_k \left[\| p_{M_k}(X_{k,h}[Z_j]) - \bar{p}_k(X_{k,h}[Z_j^k]) \|_1 \mathbb{1}\{\bar{E}_k\} \right]
$$

$$
\leq N \mathbb{E}_k \left[\max_{n \in [N]} |p_{M_k}(X_{k,h}[Z_j], n) - \bar{p}_k(X_{k,h}[Z_j^k], n)| \mathbb{1}\{\bar{E}_k\} \right]
$$

$$
\leq \sum_{x[Z_j] \in \Omega} \sum_{n \in [N]} \int_{p=\phi_k(X_{k,h}[Z_j^k])/\sqrt{N}}^{\infty} p\, \mathbb{P}_k(|p_{M_k}(X_{k,h}[Z_j], n) - \bar{p}_k(X_{k,h}[Z_j^k], n)| = p)\, dp
$$

$$
\leq 2 \mathbb{P}_k \left(|p_{M_k}(X_{k,h}[Z_j], n) - \bar{p}_k(X_{k,h}[Z_j^k], n)| \geq \frac{\phi_k(x[Z_j^k])}{\sqrt{N}} \right)
$$

$$
\leq \sum_{x[Z_j] \in \Omega} \sum_{n \in [N]} 2 \exp\left(-\frac{\phi_k(x[Z_j^k])^2}{2N/4(\|\alpha_{k,Z_t}^P(x[Z_j])\|_1 + 1)} \right)
$$

$$
= \frac{N}{K d_Y}
$$

by following the same steps as for the reward, but considering the confidence widths of each element of the vector. Due to lemma [27, Theorem 5.4.c] we divide by $\sqrt{N}$, and in the first step we use a trivial upper bound on the l^1-norm.

Combining the results of this section, we can bound the first term of (6) as

$$
\mathbb{E}\left[\sum_{k=1}^{K} \mathbb{E}_k \left[V_*(\pi_*) - \overline{V}_k(\pi_*, Z_*) \right] \right] \leq N H^2 + H \sum_{k=1}^{K} \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \mathbb{E}_k \left[\beta_k(X_{k,h}[Z_j^k]) \right] \tag{8}
$$

where we have used that $\beta_k(X_{k,h}[Z_j^k]) := c_k(X_{k,h}[Z_j^k]) + \phi_k(X_{k,h}[Z_j^k])$.

High probability confidence widths for latent factorizations To bound the second term of (6), we define confidence sets over latent factorizations. The analysis in this section is close to that in [19, Appendix B.3, step 2] since we are not assuming a product latent space yet and there is not a fundamental difference between latent states in the tabular and factored MDP settings. Hence, here we mainly translate the analysis into our factored MDPs notation.

For each episode k, we build C_k so that $Z_* \in C_k$ with high probability. Since the latent factorization is unobserved, we can exploit a proxy statistic for how well the model parameter posterior of each latent factorization predicts the rewards. We start defining $N_k(z) = \sum_{l=1}^{k-1} \mathbb{1}\{Z_l = z\}$ as the number of times z has been sampled until episode k. Next, we define

$$
G_k(z) = \sum_{l=1}^{k-1} \mathbb{1}\{Z_l = z\} \left(\overline{V}_l(\pi_l, z) - h\sqrt{2} \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \beta_l(X_{l,h}[z_j]) - \sum_{h=0}^{H-1} \sum_{j=1}^{d_Y} R_{l,h}[j] \right)
$$

as the total under-estimation of observed returns, since it expresses the difference between the lower confidence bound on the returns and the observed ones, assuming that z is the true latent factorization. Let $C_k = \{z \in \mathcal{Z} : G_k(z) \leq \sqrt{H N_k(z) \log K}\}$ be the set of latent factorizations with at most $\sqrt{H N_k(z) \log K}$ excess. In the following, we show that $Z_* \in C_k$ holds with high probability for any episode.

Fix $Z_* = z$. Let $\mathcal{T}_{k,z} = \{l < k : Z_l = z\}$ the set of episodes where z has been sampled until episode k. We will first upper bound $G_k(z)$ by a martingale with respect to the history, then bound the martingale using Azuma-Hoeffding's inequality. We define the event

$$
\mathcal{E}_{k,h,j} = \left\{ \left| R_{M_k}(X_{k,h}[Z_j]) - \bar{r}_k(X_{k,h}[Z_j^k]) \right| \leq \sqrt{2} c_k(X_{k,h}[Z_j^k]) \right.
$$

$$
\left. \text{and } \| p_{M_k}(X_{k,h}[Z_j]) - \bar{p}_k(X_{k,h}[Z_j^k]) \|_1 \leq \sqrt{2}\phi_k(X_{k,h}[Z_j^k]) \right\}
$$

691 in which the sampled reward and transition probabilities for factor j in step h of episode k are not
692 far from their posterior means. Let $\mathcal{E} = \cup_{k=1}^{K} \cup_{h=1}^{H} \cup_{j=1}^{d_Y} \mathcal{E}_{k,h,j}$ be the event that this holds for every
693 factor, step, and episode. By union bound we have that

$$
\begin{aligned}
\mathbb{P}_k(\bar{\mathcal{E}}_{k,h,j}) &\leq \mathbb{P}_k\left(\left|R_{M_k}(X_{k,h}[Z_j]) - \bar{r}_k(X_{k,h}[Z_j^k])\right| \geq \sqrt{2}c_k(X_{k,h}[Z_j^k])\right) \\
&\quad + \mathbb{P}_k\left(\|p_{M_k}(X_{k,h}[Z_j]) - \bar{p}_k(X_{k,h}[Z_j^k])\|_1 \geq \sqrt{2}\phi_k(X_{k,h}[Z_j^k])\right) \\
&\leq \exp\left(\frac{2c_k(X_{k,h}[Z_j^k])^2}{\sigma^2}\right) + \exp\left(\frac{2\phi_k(X_{k,h}[Z_j^k])^2}{N\sigma^2}\right) \\
&\leq (Kd_Y N^{d_X})^{-2}
\end{aligned}
$$

694 where we have used Lemmas D.2 and D.1. Therefore, for $\bar{\mathcal{E}}$ we have

$$
\mathbb{P}(\bar{\mathcal{E}}) = \sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{z\in\mathcal{Z}}\sum_{j=1}^{d_Y}\sum_{x[Z_j]\in\Omega}\mathbb{P}_k(\bar{\mathcal{E}}_{k,h,j}) \leq \sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{z\in\mathcal{Z}}\sum_{j=1}^{d_Y}\sum_{x[Z_j]\in\Omega}(Kd_Y N^{d_X})^{-2} \leq HCK^{-1}
$$

695 For episode $l \in \mathcal{T}_{k,z}$ let $\Delta_l = V_*(\pi_l) - \sum_{h=1}^{H}\sum_{j=1}^{d_Y} R_{l,h}[j]$. Since $\mathbb{E}_l[\Delta_l] = 0$, $(\Delta_l)_{l\in\mathcal{T}_{k,z}}$ is a
696 martingale difference sequence with respect to the histories $(\mathcal{H}_l)_{l\in\mathcal{T}_{k,z}}$. Following the same steps as
697 in [19], we derive the upper bound

$$
\mathbb{P}(Z_* \notin C_k) \leq 2CHK^{-1} \tag{9}
$$

698 **Bounding the second term of** (6)   We can now decompose the second term of (6) according to
699 whether the sampled latent factorization is in C_k or not. Formally, we have

$$
\mathbb{E}\left[\sum_{k=1}^{K}\mathbb{E}_k\left[\overline{V}_k(\pi_k, Z_k) - V_*(\pi_k)\right]\right] \leq \mathbb{E}\left[\sum_{k=1}^{K}\left(\overline{V}_k(\pi_k, Z_k) - V_*(\pi_k)\right)\mathbb{1}\{Z_k \in C_k\}\right]
$$
$$
+ H\sum_{k=1}^{K}\mathbb{P}(Z_* \notin C_k)
$$

700 From the previous steps, using equation (9), we have that the second term is bounded as $2CH^2$, while
701 in the following we derive an upper bound for the first term as in [19, Appendix B.3, step 4]. We have

$$
\begin{aligned}
&\mathbb{E}\left[\sum_{k=1}^{K}\left(\overline{V}_k(\pi_k, Z_k) - V_*(\pi_k)\right)\mathbb{1}\{Z_k \in C_k\}\right] \\
&= H\sqrt{2}\,\mathbb{E}\left[\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y}\beta_k(X_{k,h}[Z_j^k])\right] \\
&\quad + \mathbb{E}\left[\sum_{k=1}^{K}\left(\overline{V}_k(\pi_k, Z_k) - H\sqrt{2}\sum_{h=1}^{H}\sum_{j=1}^{d_Y}\beta_k(X_{k,h}[Z_j^k]) - \sum_{h=1}^{H}\sum_{j=1}^{d_Y}R_{k,h}[j]\right)\mathbb{1}\{Z_k \in C_k\}\right] \\
&\leq H\sqrt{2}\,\mathbb{E}\left[\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y}\beta_k(X_{k,h}[Z_j^k])\right] + \mathbb{E}\left[\sum_{z\in\mathcal{Z}}G_{K+1}(z) + CH\right] \\
&\leq H\sqrt{2}\,\mathbb{E}\left[\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y}\beta_k(X_{k,h}[Z_j^k])\right] + \sqrt{CKH\log K} + CH
\end{aligned}
$$

702 **Regret bound for general latent spaces**   Combining the upper bounds of the two terms of (6), we
703 get

$$
\mathcal{BR}(K) \leq NH^2 + H\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y}\mathbb{E}_k\left[\beta_k(X_{k,h}[Z_j^k])\right] + H\sqrt{2}\,\mathbb{E}\left[\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y}\beta_k(X_{k,h}[Z_j^k])\right]
$$

$$+ \sqrt{CKH \log K} + CH + 2CH^2$$

$$\leq NH^2 + 3H^2 d_Y N^{d_X} + 3H^2 d_Y N \sqrt{N^{d_X} KH \log(4K d_Y N^{d_X}) \log\left(1 + \frac{KH}{2N^{d_X}\Lambda_{0,z}}\right)}$$

$$+ \sqrt{CKH \log K} + 3CH^2$$

Which, due to the Z-sparseness assumption, we can rewrite as

$$\mathcal{BR}(K)$$

$$\leq NH^2 + 3H^2 d_Y N^Z + 3H^2 d_Y N \sqrt{N^Z KH \log(4K d_Y N^Z) log\left(1 + \frac{KH}{2N^Z \Lambda_{0,z}}\right)}$$

$$+ \sqrt{CKH \log K} + 3CH^2$$

$$= O\left(H^2 d_Y N^Z + \sqrt{CKH \log K} + CH^2 + H^{\frac{5}{2}} d_Y N^{1+\frac{Z}{2}} \sqrt{K \log(4K d_Y N^Z) log\left(1 + \frac{KH}{2N^Z \Lambda_{0,z}}\right)}\right)$$

$$= \tilde{O}\left(H^2 d_Y N^Z + H^{\frac{5}{2}} d_Y N^{1+\frac{Z}{2}} \sqrt{K} + \sqrt{CKH} + CH^2\right)$$

Notably, this rate is sub-linear in the number of episodes K, sub-linear in the number of latent factorizations Z, and exponential in the degree of sparseness Z.

D.3   Part 2 - Product Latent Spaces

Since the algorithm we propose does not sample at each episode $k \in [K]$ a global factorization but samples d_Y local ones from independent hyper-priors, we can refine our analysis accordingly. Intuitively, the statistical efficiency gain that we wish to capture through the analysis is due to the fact that $\overline{C}$, an upper bound on the space of local factorizations, is significantly smaller than C, i.e., $|\overline{C}| \ll |C|$. Hence, in the following, we extend the sections above in order to derive regret bounds as a function of the number of admissible local factorizations $\overline{C}$ rather than the number of admissible global ones C.

For episode $k \in [K]$, we define $C_k^j = \left\{ z_j \in \mathcal{Z}_j : G_k^j(\bar{z}) \leq \sqrt{HN_k^j(z_j) \log K} \right\}$ where

$$G_k^j(z_j)$$

$$= \sum_{l=1}^{k-1} \mathbb{1}\{Z_j^l = z_j\} H \sum_{h=1}^H \left(\left(\bar{r}_l(X_{l,h}[z_j]) - R_{l,h}[j]\right) + \|\bar{p}_k(X_{l,h}[z_j]) - p_*(X_{l,h}[z_{j*}])\|_1 - \sqrt{2}\beta_k(X_{l,h}[z_j]) \right)$$

and $N_k^j(z_j) = \sum_{l=1}^{k-1} \mathbb{1}\{Z_j^l = z_j\}$. While $G_k^j(z_j)$ captures the under-estimation of the observed returns at the level of a single factor, $N_k^j(z_j)$ counts the number of times that the local factorization z_j has been sampled for node j until episode k. Next, we define $\mathcal{T}_{k,z_j}^j = \{l < k : Z_j^l = z_j\}$ as the set of episodes where z_j has been sampled for node j.

First, we can derive an upper bound of $\mathbb{P}(\bar{\mathcal{E}})$ depending on $\overline{C}$ by noticing that the inner-most sum depends only on the local factorization hence we can swap the two previous sums as follows

$$\mathbb{P}(\bar{\mathcal{E}}) = \sum_{k=1}^K \sum_{h=1}^H \sum_{z \in \mathcal{Z}} \sum_{j=1}^{d_Y} \sum_{x[z_j] \in \Omega} \mathbb{P}_k(\bar{\mathcal{E}}_{k,h,j})$$

$$\leq \sum_{k=1}^K \sum_{h=1}^H \sum_{z \in \mathcal{Z}} \sum_{j=1}^{d_Y} \sum_{x[z_j] \in \Omega} (K d_Y N^{d_X})^{-2}$$

$$= \sum_{k=1}^K \sum_{h=1}^H \sum_{j=1}^{d_Y} \sum_{z_j \in \mathcal{Z}_j} \sum_{x[z_j] \in \Omega} (K d_Y N^{d_X})^{-2}$$

$$\leq H\overline{C}K^{-1}$$

Now, we wish to upper bound $\mathbb{P}(Z_{j*} \notin C_k^j)$. For episode $l \in \mathcal{T}_{k,z_j}^j$ let $\Delta_l^j = \sum_{h=1}^H R_*(X_{l,h}[Z_{j*}]) - \sum_{h=1}^H R_{l,h}[j]$. Since $\mathbb{E}_l[\Delta_l^j] = 0$ we have that $(\Delta_l^j)_{l \in \mathcal{T}_{t,z_j}^j}$ is a martingale difference sequence with respect to the histories $(\mathcal{H}_l)_{l \in \mathcal{T}_{t,z_j}^j}$.

By following the same steps as in [19], we get

$$
G_k^j(z_j)\mathbb{1}\{\mathcal{E}\} = \sum_{l \in \mathcal{T}_{t,z_j}^j} H \sum_{h=1}^H \left(\left(\bar{r}_l(X_{l,h}[z_j]) - R_{l,h}[j]\right) + \|\bar{p}_k(X_{l,h}[z_j]) - p_*(X_{l,h}[z_{j*}])\|_1 - \sqrt{2}\beta_k(X_{l,h}[z_j]) \right)
$$

$$
\leq \sum_{l \in \mathcal{T}_{k,z_j}^j} \Delta_l^j
$$

and by fixing $|\mathcal{T}_{t,z_j}^j| = N_t^j(z_j) = u < t$, and using Azuma-Hoeffding's inequality, we get

$$
\mathbb{P}_k\left(G_k^j(\bar{z})\mathbb{1}\{\mathcal{E}\} \geq \sqrt{Hu \log K}\right) \leq \mathbb{P}\left(\sum_{l \in \mathcal{T}_{k,z_j}^j} \Delta_l^j \geq \sqrt{hu \log K}\right) \leq K^{-2}.
$$

Therefore, through union bounds, we can write

$$
\mathbb{P}\left(Z_* \notin C_k\right) \leq \sum_{j=1}^{d_Y} \mathbb{P}(Z_{j*} \notin C_k^j)
$$

$$
\leq \sum_{j=1}^{d_Y} \sum_{z_j \in \mathcal{Z}_j} \sum_{u=1}^{k-1} \mathbb{P}\left(G_k^j(z_j) \geq \sqrt{Hu \log K}\right)
$$

$$
\leq \mathbb{P}(\bar{\mathcal{E}}) + \sum_{j=1}^{d_Y} \sum_{z_j \in \mathcal{Z}_j} \sum_{u=1}^{k-1} \mathbb{P}\left(G_k^j(z_j)\mathbb{1}\{\mathcal{E}\} \geq \sqrt{Hu \log K}\right)
$$

$$
\leq d_Y H \overline{C} K^{-1} \tag{10}
$$

We can now decompose the second term of (6) according to whether the sampled latent factorization is in C_k or not, as done in the non-factored version above. Formally, we have

$$
\mathbb{E}\left[\sum_{k=1}^K \mathbb{E}_k \left[\overline{V}_k(\pi_k, Z_k) - V_*(\pi_k)\right]\right] \leq \mathbb{E}\left[\sum_{k=1}^K \left(\overline{V}_k(\pi_k, Z_k) - V_*(\pi_k)\right)\mathbb{1}\{Z_k \in C_k\}\right] + H \sum_{k=1}^K \mathbb{P}(Z_* \notin C_k)
$$

From the previous steps, in particular equation (10), we know that the second term is bounded as $d_Y \overline{C} H^2$. Meanwhile, we can bound the first term as follows

$$
\mathbb{E}\left[\sum_{k=1}^K \left(\overline{V}_k(\pi_k, Z_k) - V_*(\pi_k)\right)\mathbb{1}\{Z_k \in C_k\}\right]
$$

$$
\leq \mathbb{E}\left[\sum_{k=1}^K H \sum_{h=1}^H \sum_{j=1}^{d_Y} \left(\bar{r}_k(X_{k,h}[Z_j^k]) - R_*(X_{k,h}[Z_{j*}]) + \|\bar{p}_k(X_{l,h}[Z_j^k]) - p_*(X_{l,h}[Z_{j*}])\|_1\right)\mathbb{1}\{Z_j^k \in C_k^j\}\right]
$$

$$
= H\sqrt{2}\,\mathbb{E}\left[\sum_{k=1}^K \sum_{h=1}^H \sum_{j=1}^{d_Y} \beta_k(X_{k,h}[Z_j^k])\right] + \mathbb{E}\left[\sum_{k=1}^K H \sum_{h=1}^H \sum_{j=1}^{d_Y} \left(\bar{r}_k(X_{k,h}[Z_j^k]) - R_*(X_{k,h}[Z_{j*}])\right.\right.
$$

$$
\left.\left. + \|\bar{p}_k(X_{l,h}[Z_j^k]) - p_*(X_{l,h}[Z_{j*}])\|_1 - \sqrt{2}\beta_k(X_{k,h}[Z_j^k])\right)\mathbb{1}\{Z_j^k \in C_k^j\}\right]
$$

$$
\leq H\sqrt{2}\,\mathbb{E}\left[\sum_{k=1}^K \sum_{h=1}^H \sum_{j=1}^{d_Y} \beta_k(X_{k,h}[Z_j^k])\right] + \mathbb{E}\left[\sum_{j=1}^{d_Y} \sum_{z_j \in \mathcal{Z}_j} G_{K+1}^j(z_j) + d_Y \overline{C} H\right]
$$

$$\leq H\sqrt{2}\,\mathbb{E}\left[\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y}\beta_k(X_{k,h}[Z_j^k])\right] + \sum_{j=1}^{d_Y}\sum_{z_j\in\mathcal{Z}_j}\frac{1}{d_Y}\sqrt{HN_{K+1}^j(z_j)\log K} + d_Y\overline{C}H$$

$$\leq H\sqrt{2}\,\mathbb{E}\left[\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y}\beta_k(X_{k,h}[Z_j^k])\right] + \sqrt{\overline{C}KH\log K} + d_Y\overline{C}H$$

Regret bound for product latent spaces Exploiting the Z-sparseness assumption, we can write

$$\mathcal{BR}(K)\leq\tilde{O}\left(H^2 d_Y N^Z + H^{\frac{5}{2}} d_Y N^{1+\frac{Z}{2}}\sqrt{K} + \sqrt{\overline{C}KH} + d_Y\overline{C}H^2\right) \tag{11}$$

Notably, this rate is sub-linear in the number of episodes K, sub-linear in the number of latent local factorizations $\overline{C}$, and exponential in the degree of sparseness Z.

D.4 Step 3 - Prior Causal Knowledge

In the following, we formally express the dependency of the Bayesian regret on the number of edges encoded in the causal graph prior. Given the assumption of Z-sparseness, we can count the number of admissible local factorizations for each node $j\in[d_Y]$ as

$$\overline{C} = \sum_{i=0}^{Z}\binom{d_X}{i} = \sum_{i=0}^{Z}C_i^{d_X}$$

where we count the empty factorization when $i=0$. Given a graph hyper-prior that fixes $\eta < Z$ edges for each node $j\in[d_Y]$, we can count the number of admissible local factorizations as

$$\overline{C} = \sum_{i=0}^{Z-\eta}\binom{d_X-\eta}{i}$$

where we count the factorization with only the edges fixed a priori when $i=0$. We can build an upper bound on $\overline{C}$ as follows.

$$\begin{aligned}
\overline{C} &= \sum_{i=0}^{Z-\eta}\binom{d_X-\eta}{i}\\
&\leq 2^{d_X-\eta-1}\exp\left(\frac{(d_X+\eta-2Z-2)^2}{4(1+Z-d_X)}\right)\\
&\leq 2^{d_X-\eta}\exp\left(\frac{(d_X+\eta-2Z)^2}{4(1+Z-d_X)}\right) =: \phi(d_X,Z,\eta)
\end{aligned}$$

The actual rate is hard to interpret from the previous bound. Hence, we derive a bound that is looser but easier to interpret. We have

$$\begin{aligned}
\overline{C} &= \sum_{i=0}^{Z-\eta}\binom{d_X-\eta}{i}\\
&= 2^{d_X-\eta} - \sum_{i=0}^{d_X-Z-1}\binom{d_X-\eta}{i}\\
&\leq 2^{d_X-\eta} - 2^{d_X-Z} + 1\\
&\leq 2^{d_X-\eta}
\end{aligned}$$

Here we can notice that each given edge in the causal graph prior shrinks with an exponential rate the hypothesis space and the relative regret terms as well. In particular, by plugging-in the upper bound $\overline{C}\leq 2^{d_X-\eta} = \frac{2^{d_X}}{2^\eta}$ in the Bayesian regret expression (11), we get the following upper bound.

Final regret bound

$$\mathcal{BR}(K)\leq\tilde{O}\left(H^2 d_Y N^Z + H^{\frac{5}{2}} d_Y N^{1+\frac{Z}{2}}\sqrt{K} + \sqrt{2^{d_X-\eta}KH} + d_Y 2^{d_X-\eta}H^2\right). \tag{12}$$

 D.5 Auxiliary Lemmas

Lemma D.1 (Theorem 1 and 3 of [30]). *Let $X \sim \text{Beta}(\alpha, \beta)$ for $\alpha, \beta > 0$. Then $X - \mathbb{E}[X]$ is σ^2-subgaussian with $\sigma^2 = 1/(4(\alpha+\beta+1))$. Similarly, let $X \sim \text{Dir}(\alpha)$ for $\alpha \in \mathbb{R}_+^d$. Then $X - \mathbb{E}[X]$ is σ^2-subgaussian with $\sigma^2 = 1/\left(4\left(\|\alpha\|_1 + 1\right)\right)$.*

Lemma D.2 (Theorem 5.3 of [27]). *If X is σ^2-subgaussian, then for any $\varepsilon \geq 0$,*

$$\mathbb{P}(X \geq \varepsilon) \leq \exp\left(-\frac{\varepsilon^2}{2\sigma^2}\right)$$

Lemma D.3 (Value difference lemma, Lemma 6 [19]). *For any MDPs M', M, and policy π,*

$$V_{M'}(\pi) - V_M(\pi) \leq \mathbb{E}_M\left[\sum_{h=1}^{H} R_{M'}(S_h, A_h) - R_M(S_h, A_h) + H \|p_{M'}(S_h, A_h) - p_M(S_h, A_h)\|_1\right]$$

Proof. This upper bound can be obtained by trivially upper bounding with 1 the reward at each step, and therefore with h the value function within the statement in [22, Lemma C.1]. □

Lemma D.4 (Upper bounds on deviations of factorized R and P [36]). *Given two reward functions R and $\bar{R}$ with scopes $\{Z_i^R\}_{i=1}^{d_R}$ we can upper bound the deviations by*

$$|R(x) - \bar{R}(x)| \leq \sum_{i=1}^{d_R} |R_i(x[Z_i^R]) - \bar{R}_i(x[Z_i^R])|$$

and, given two transition models p and $\bar{p}$ with scopes $\{Z_j^P\}_{j=1}^{d_Y}$ we can upper bound the deviations by

$$|p(x) - \bar{p}(x)| \leq \sum_{j=1}^{d_Y} |p_j(x[Z_j^P]) - \bar{p}_j(x[Z_j^P])|$$

Lemma D.5 (Bound confidence widths factor level). *For episode k and latent factorization $z \in \mathcal{Z}$, let $\beta_k(x[z_j]) = c_k(x[z_j]) + \phi_k(x[z_j])$ for any $j \in [d_Y]$ and $x[z_j] \in \Omega$. Let $\Lambda_{0,z} = \min\left\{\min_{i,x[z_i]} \|\alpha_{0,z}^R(x[z_i^R])\|_1, \min_{j,x[z_j]} \|\alpha_{0,z}^P(x[z_j^P])\|_1\right\}$ indicate the minimum level of concentration between the reward function and transition model for any factor, given the latent factorization z. Then, we have*

$$\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y} \beta_k(X_{k,h}[z_j]) \leq Hd_Y N^{d_X} + d_Y NH\sqrt{N^{d_X}KH\log(4Kd_YN^{d_X})\log\left(1 + \frac{KH}{2N^{d_X}\Lambda_{0,z}}\right)}$$

Proof. We define $N_k(x[z_j]) = \sum_{l=1}^{k-1}\sum_{h=1}^{H} \mathbb{1}\{X_{l,h}[z_j] = x[z_j]\}$ as the number of times the assignment $x[z_j]$ was sampled up to episode k for factor j. We can decompose the sum as

$$\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y} \beta_k(X_{k,h}[z_j])$$

$$\leq \sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y} \mathbb{1}\{N_k(X_{k,h}[z_j]) \leq h\} + \sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y} \mathbb{1}\{N_k(X_{k,h}[Z_j]) > H\}\beta_k(X_{k,h}[z_j])$$

where we upper bound by 1 the regret in a step due to one factor. Therefore, the first term is upper bounded by $Hd_Y N^{d_X}$ since there are at most N^{d_X} assignments for each $j \in [d_Y]$ and the same one can appear in the sum at most H times, thus removing the dependency on K. Due to the assumption of Z-sparseness, we will later use the bound $Hd_Y N^Z$. As for the second term, we define $N_{k,h}(x[z_j]) = N_k(x[z_j]) + \sum_{p=1}^{h-1} \mathbb{1}\{X_{k,p}[z_j] = x[z_j]\}$ as the number of times $x[z_j]$ was sampled up to step h of episode k, for factor j. We split β_k into c_k and ϕ_k. For c_k we have:

$$\sum_{k=1}^{K}\sum_{h=1}^{H}\sum_{j=1}^{d_Y} \mathbb{1}\{N_k(X_{k,h}[z_j]) > H\}c_k(X_{k,h}[z_j])$$

$$= \sum_{k=1}^{K} \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \mathbb{1}\{N_k(X_{k,h}[z_j]) > H\} \sqrt{\frac{\log(2Kd_R N^Z)}{2\left(\|\alpha_{k,z}^R(X_{k,h}[z_j])\|_1 + 1\right)}}$$

$$= \sum_{k=1}^{K} \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \sum_{x[z_j] \in \Omega} \mathbb{1}\{N_k(x[z_j]) > H\} \sqrt{\frac{\log(2Kd_R N^Z)}{2\|2\alpha_{k,z}^R(X_{k,h}[z_j])\|_1 + 2N_k(x[z_j]) + 2}}$$

$$\leq \sum_{k=1}^{K} \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \sum_{x[z_j] \in \Omega} \sqrt{\frac{\log(2Kd_R N^Z)}{2\|2\alpha_{k,z}^R(X_{k,h}[z_j])\|_1 + N_{k,h}(x[z_j])}}$$

$$\leq \sqrt{\log(2Kd_R N^Z)} \sum_{j=1}^{d_Y} \sum_{x[z_j] \in \Omega} \sqrt{N_{K+1}(x[z_j]) \sum_{u=1}^{N_{K+1}(x[z_j])} \frac{1}{2\|2\alpha_{k,z}^R(X_{k,h}[z_j])\|_1 + u}}$$

$$\leq \sqrt{N^{d_X} KH \log(2Kd_R N^Z)} \sum_{j=1}^{d_Y} \sqrt{\sum_{u=1}^{KH/N^{d_X}} \frac{1}{2\Lambda_{0,z} + u}}$$

$$\leq d_Y \sqrt{N^{d_X} KH \log\left(2Kd_R N^Z\right) \log\left(1 + \frac{KH}{2N^{d_X} \Lambda_{0,z}}\right)}$$

where in the first step we have plugged-in c_k as picked in Section 4, in the second step have exploited the posterior update rule, in step three we have used that if $N_k(x[z_j]) > H$ we have that $N_{k,h}(x[z_j]) \leq N_k(x[z_j]) + H \leq 2N_k(x[z_j])$, and in the remaining passages we have used known bounds as in [19, Lemma 6]. Analogously, for ϕ_k we can derive the following.

$$\sum_{k=1}^{K} \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \mathbb{1}\{N_k(X_{k,h}[z_j]) > H\} \phi_k(X_{k,h}[z_j])$$

$$\leq d_Y NH \sqrt{N^{d_X} KH \log\left(4Kd_R N^Z\right) \log\left(1 + \frac{KH}{2N^{d_X} \Lambda_{0,z}}\right)}$$

Notice that again, due to the Z-sparseness, we can replace in the steps above N^{d_X} with N^Z. Combining the terms, we have:

$$\sum_{k=1}^{K} \sum_{h=1}^{H} \sum_{j=1}^{d_Y} \beta_k(X_{k,h}[z_j]) \leq Hd_Y N^{d_X} + 2d_Y NH \sqrt{N^{d_X} KH \log\left(4Kd_R N^Z\right) \log\left(1 + \frac{KH}{2N^{d_X} \Lambda_{0,z}}\right)}$$

$\square$