A Simple Decentralized Cross-Entropy Method

Abstract

Cross-Entropy Method (CEM) is commonly used for planning in model-based reinforcement learning (MBRL) where a *centralized* approach is typically utilized to update the sampling distribution based on only the top-k operations' results on samples. In this paper, we show that such a *centralized* approach makes CEM vulnerable to local optima, thus impairing its sample efficiency. To tackle this issue, we propose **Decent**ralized **CEM (DecentCEM)**, a simple but effective improvement over classical CEM, by using an ensemble of CEM instances running independently from one another, and each performing a local improvement of its own sampling distribution. We provide both theoretical and empirical analysis to demonstrate the effectiveness of this simple *decentralized* approach. We empirically show that, compared to the classical centralized approach using either a single or even a mixture of Gaussian distributions, our DecentCEM finds the global optimum much more consistently thus improves the sample efficiency. Furthermore, we plug in our DecentCEM in the planning problem of MBRL, and evaluate our approach in several continuous control environments, with comparison to the state-of-art CEM based MBRL approaches (PETS and POPLIN). Results show sample efficiency improvement by simply replacing the classical CEM module with our DecentCEM module, while only sacrificing a reasonable amount of computational cost, which can be alleviated by using the advantage of parallelism of our ensemble method. Lastly, we conduct ablation studies for more in-depth analysis.

1 Introduction

Model-based reinforcement learning (MBRL) uses a model as a proxy of the environment for planning actions in multiple steps. This paper studies planning in MBRL with a specific focus on the Cross-Entropy Method (CEM) [De Boer et al., 2005, Mannor et al., 2003], which is popular in MBRL due to its ease of use and strong empirical performance [Chua et al., 2018, Hafner et al., 2019, Wang and Ba, 2020, Zhang et al., 2021, Yang et al., 2020]. CEM is a stochastic, derivative-free optimization method. It uses a sampling distribution to generate imaginary trajectories of environment-agent interactions with the model. These trajectories are then ranked based on their returns computed from the rewards given by the model. The sampling distribution is updated to increase the likelihood of producing the top-k trajectories with higher returns. These steps are iterated and eventually yield an improved distribution over the action sequences to guide the action execution in the real environment.

Despite the strong empirical performance of CEM for planning, it is prone to two problems: (1) lower sample efficiency as the dimensionality of solution space increases, and (2) the Gaussian distribution that is commonly used for sampling may cause the optimization to get stuck in local optima of multi-modal solution spaces commonly seen in real-world problems. Previous works addressing these problems either add gradient-based updates of the samples to optimize the parameters of CEM, or adopt more expressive sampling distributions, such as using Gaussian Mixture Model [Okada and Taniguchi, 2020] or masked auto-regressive neural network [Hakhamaneshi et al., 2020]. Nevertheless,

all CEM implementations to date are limited to a *centralized* formulation where the ranking step involves *all samples*. As analyzed below and in Section 3, such a centralized design makes CEM vulnerable to local optima and impairs its sample efficiency.

We propose **Decent**ralized **CEM (DecentCEM)**, a simple but effective improvement over classical CEM, to address the above problems. Rather than ranking *all samples*, as in the *centralized* design, our method distribute the sampling budget across an ensemble of CEM instances. These instances run independently from one another, and each performs a local improvement of its own sampling distribution based on the ranking of its generated samples. The best action is then aggregated by taking an $\arg\max$ among the solution of the instances. It recovers the conventional CEM when the number of instance is one.

We hypothesize that by shifting to this *decentralized* design, CEM can be less susceptible to premature convergence caused by the *centralized* ranking step. As illustrated in Fig. 1, the *centralized* sampling distribution exhibits a bias toward the sub-optimal solutions near top right, due to the *global* top-k ranking. This bias would occur regardless of the family of distributions used. In comparison, a *decentralized* approach could maintain enough diversity thanks to its *local* top-k ranking in each sampling instance.

(a) Centralized CEM   (b) Decentralized CEM

Figure 1: Illustration of CEM approaches in optimization. Shades of red indicate relative value of the 2D optimization landscape: brighter is better. Optimal solutions are near bottom left corner of the solution space. Blue dots • are top-k samples, and black dots • are other samples. Open dots O represent the sampling distributions whose sizes indicate the number of generated samples.

Through a one-dimensional multi-modal optimization problem in Section 3, we show that DecentCEM empirically finds the global optimum more consistently than centralized CEM approaches that use either a single or a mixture of Gaussian distributions. Also we show that DecentCEM is theoretically sound that it converges almost surely to a local optimum. We further apply it to sequential decision making problems and use neural networks to parameterize the sampling distributions. Empirical results in several continuous control environments suggest that DecentCEM offers an effective mechanism to improve the sample efficiency over the baseline CEM under the same sample budget for planning.

2 Preliminaries

We consider a Markov Decision Process (MDP) specified by (S,A,R,P,γ,d_0,T). $S \subset \mathbb{R}^{d_s}$ is the state space, $A \subset \mathbb{R}^{d_a}$ is the action space. d_s, d_a are scalars denoting the dimensionality. $R : S \times A \to \mathbb{R}$ is the reward function that maps a state and action pair to a real-valued reward. $P(s'|s,a) : S \times A \times S \to \mathbb{R}^+$ is the transition probability from a state and action pair s, a to the next state s'. $\gamma \in [0,1]$ is the discount factor. d_0 denotes the distribution of the initial state s_0. At time step t, the agent receives a state s_t [1] and takes an action a_t according to a policy $\pi(\cdot|s)$ that maps the state to a probability distribution over the action space. The environment transitions to the next state $s_{t+1} \sim P(\cdot|s_t, a_t)$ and gives a reward $r_t = R(s_t, a_t)$ to the agent [2]. The return $G_t = \sum_{i=0}^{T} \gamma^i r_{t+i}$, is the sum of discounted reward within an episode length of T. The agent aims to find a policy π that maximizes the expected return. We denote the learned model in MBRL as $f_\omega(\cdot|s,a)$, which is parameterized by ω and approximates $P(\cdot|s,a)$.

Planning with the Cross Entropy Method Planning in MBRL is about leveraging the model to find the best action in terms of its return. Model-Predictive-Control (MPC) performs decision-time planning at each time step up to a horizon to find the optimal action sequence:

$$\pi_{\text{MPC}}(s_t) = \arg\max_{a_{t:t+H-1}} \mathbb{E}[\Sigma_{i=0}^{H-1} \gamma^i r(s_{t+i}, a_{t+i}) + \gamma^H V(s_H)] \tag{1}$$

---

[1]We assume full observability, i.e. agent has access to the state.

[2]We assume that the reward function is known and deterministic, which is a mild assumption [Agarwal et al., 2019]. We limit the scope of this paper to compare with MBRL methods that also make this assumption.

where H is the planning horizon, $a_{t:t+H-1}$ denotes the action sequence from time step t to $t+H-1$, and $V(s_H)$ is the terminal value function at the end of the horizon. The first action in this sequence is executed and the rest are discarded. The agent then re-plans at the next time step.

Figure 2: Cross Entropy Method (CEM) for Planning in MBRL

The Cross-Entropy Method (CEM) is a gradient-free optimization method that can be used for solving Eq. (1). The workflow is shown in Fig. 2. CEM planning starts by generating N samples $\{\tau_j\}_{j=1}^N = \{(\hat{a}_{j,0}, \hat{a}_{j,1}, \cdots, \hat{a}_{j,H-1})\}_{j=1}^N$ from an initial sampling distribution $g_\phi(\tau)$ parameterized by ϕ, where each sample τ_j is an action sequence from the current time step up to the planning horizon H. The domain of $g_\phi(\tau)$ has a dimension of $d_\tau = d_a H$.

Using a model f, CEM generates imaginary rollouts based on the action sequence $\{\tau_j\}$ (in the case of a stochastic model) and estimate the associated value $v(\tau_j) = \mathbb{E}[\Sigma_{i=0}^{H-1}\gamma^i r(s_{j,i}, a_{j,i})]$ where $s_{j,0}$ is the current state s and $s_{j,i+1} \sim f(\cdot|s_{j,i}, a_{j,i})$. The terminal value $\gamma^H V(s_{j,H})$ is omitted here following the convention in the CEM planning literature but the MPC performance can be further improved if paired with an accurate value predictor [Bertsekas, 2005, Lowrey et al., 2019]. The sampling distribution is then updated by fitting to the current top-k samples in terms of their value estimates $v(\tau_j)$, using the Maximum Likelihood Estimation (MLE) which solves:

$$\phi' = \arg\max_\phi \sum_{j=1}^N \mathbb{1}(v(\tau_j) \geq v_{\text{th}}) \log g_\phi(\tau_j) \tag{2}$$

where v_{th} is the threshold equal to the value of the k-th best sample and $\mathbb{1}(\cdot)$ is the indicator function. In practice, the update to the distribution parameters are smoothed by $\phi^{l+1} = \alpha\phi' + (1-\alpha)\phi^l$ where $\alpha \in [0,1]$ is a smoothing parameter that balances between the solution to Eq. (2) and the parameter at the current internal iteration l. CEM repeats this process of sampling and distribution update in an inner-loop, until it reaches the stopping condition. In practice, it is stopped when either a maximum number of iterations has been reached or the parameters have not changed for a few iterations. The output of CEM is an action sequence, typically set as the expectation[3] of the most recent sampling distribution for uni-modal distributions such as Gaussians $\hat{\mu} = \mathbb{E}(g_\phi) = (\hat{a}_0, \hat{a}_1, \cdots, \hat{a}_{H-1})$.

Choices of Sampling Distributions in CEM: A common choice is a multivariate Gaussian distribution under which Eq.(2) has an analytical solution. But the uni-modal nature of Gaussian makes it inadequate in solving multi-modal optimization that often occurs in MBRL. To increase the capacity of the distribution, a Gaussian Mixture Model (GMM) can be used [Okada and Taniguchi, 2020]. We denote such an approach as *CEM-GMM*. Going forward, we use *CEM* to refer to the vanilla version that employs a Gaussian distribution. Computationally, the major difference between *CEM* and *CEM-GMM* is that the distribution update in *CEM-GMM* is more intensive since it solves for more parameters. Detailed steps can be found in Okada and Taniguchi [2020].

3 Decentralized CEM

In this section, we first introduce the formulation of the proposed *decentralized* approach called the **Decent**ralized **CEM (DecentCEM)**. Then we illustrate the intuition behind the proposed approach using a one-dimensional synthetic multi-modal optimization example where we show the issues of the existing CEM methods and how they can be addressed by DecentCEM.

Formulation of DecentCEM DecentCEM is composed of an ensemble of M CEM instances indexed by i, each having its own sampling distributions g_{ϕ_i}. They can be described by a set of distribution parameters $\Phi = \{\phi_i\}_{i=1}^M$. Each instance i manages its own sampling and distribution update by the steps described in Section 2, independently from other instances.

---

[3]Other options are discussed in Appendix A.2

127 Note that the N samples and k elites are evenly split among the M instances. The top-$\frac{k}{M}$ sample
128 sets are decentralized and managed by each instance independently whereas the centralized approach
129 only keeps one set of top-k samples regardless of the distribution family used.

130 After the stopping condition is reached for all instances, the final sampling distribution is taken as the
131 best distribution in the set Φ according to (the $\arg\max$ uses a deterministic tie-breaking):

$$\phi_{\text{DecentCEM}} = \arg\max_{\phi_i \in \Phi} \mathbb{E}_{\phi_i}[v(x)] \approx \arg\max_{\phi_i \in \Phi} \sum_{j=1}^{\frac{N}{M}} v(\tau_{i,j}) \qquad (3)$$

132 where $\mathbb{E}_{\phi_i}[v(x)]$ denotes the expectation with respect to the distribution g_{ϕ_i}, approximated by the
133 sample mean of $\frac{N}{M}$ samples. When $M = 1$, it recovers the conventional CEM.

Motivational Example Consider
a one dimensional multi-modal
optimization problem shown in
Fig.3 (Left): $\arg\min_x \sin(x) +$
$\sin(10x/3), -7.5 \le x \le 7.5$. There
are eight local optima, including one
global optimum $f(x^*) = -1.9$ where
$x^* = 5.146$. This objective function
mimics the RL value landscape that
has many local optima, as shown
by Wang and Ba [2020]. This
optimization problem is "easy" in
the sense that a grid search over the
domain can get us a solution close to
the global optimum. However, only
our proposed *DecentCEM* method

Figure 3: Left: The objective function in a 1D optimization task.
Right: Comparison of our proposed *DecentCEM* method to *CEM*
and *CEM-GMM*, wherein the line and the shaded region denote the
mean and the min/max cost from 10 independent runs. $\hat{x}$: resulting
solution of each method.

150 successfully converges to the global optimum consistently under varying population size (i.e., number
151 of samples) and random runs, as shown in Fig.3 (Right)[4].

Figure 4: How the sampling distributions evolve in the 1D optimization task, *after* the specified iteration.
Symbols include samples •, elites •, local optima ▲, global +. 2nd row in each figure shows the weighted p.d.f of
individual distribution. Population size: 200.

152 Both *CEM-GMM* and the proposed *DecentCEM* are equipped with multiple sampling distributions.
153 The fact that *CEM-GMM* is outperformed by *DecentCEM* may appear surprising. To gain some
154 insights, we illustrate in Fig. 4 how the sampling distribution evolves during the iterative update (more
155 details in Fig. 10 in Appendix). *CEM* updated the unimodal distribution toward a local optimum
156 despite seeing the global optimum. *CEM-GMM* appears to have a similar issue. During MLE on the
157 top-k samples, it moved most distribution components towards the same local optimum which quickly
158 led to mode collapse. On the contrary, *DecentCEM* successfully escaped the local optima thanks
159 to its independent distribution update over *decentralized* top-k samples and was able to maintain a
160 decent diversity among the distributions.

161 GMM suits density estimation problems like distribution-based clustering where the samples are
162 drawn from a *fixed true* distribution that can be represented by multi-modal Gaussians. However,
163 in CEM for optimization, exploration is coupled with density estimation: the sampling distribution
164 in CEM is *not fixed* but rather gets updated iteratively toward the top-k samples. And the "true"
165 distribution in optimization puts uniform non-zero densities to the global optima and zero densities

---

[4]For a fair comparison, hyperparameter search has been conducted on all methods for each population size
(Appendix A).

everywhere else. When there is a unique global optimum, it degenerates into a Dirac measure that assigns the entire density to the optimum. Density estimation of such a distribution only needs one Gaussian but the exploration is challenging. In other words, the conditions for GMM to work well are not necessarily met when used as the sampling distribution in *CEM*. *CEM-GMM* is subject to mode collapse during the iterative top-k greedification, causing premature convergence, as observed in Fig 4. In comparison, our proposed decentralized approach takes care of the exploration aspect by running multiple CEM instances independently, each performing its own local improvement. This is shown to be effective from this optimization example and the benchmark results in Section 6. *CEM-GMM* only consistently converge to the global optimum when we increase the population size to the maximum 1,000 which causes expensive computations. Our proposed *DecentCEM* runs more than 100 times faster than *CEM-GMM* at this population size, shown in Table A.3 in Appendix.

Convergence of DecentCEM   The convergence of DecentCEM requires the following assumption:

Assumption 1. *Let M be the number of instances in DecentCEM and each instance has a sample size of $\frac{N_k}{M}$ where N_k is the total number of samples that satisfies $N_k = \Theta(k^\beta)$ where $\beta > \max\{0, 1-2\lambda\}$. M and λ are some positive constant and $0 < M < N_k \ \forall \ k$.*

Here the assumption of the total sample size follows the same one as in the CEM literature. Other such standard assumptions are summarized in the appendix.

Theorem 3.1 (Convergence of DecentCEM)**.** *If a CEM instance described in Algorithm 3 converges, and we decentralize it by evenly dividing its sample size N_k into M CEM instances which satisfies the Assumption 1, then the resulting DecentCEM converges almost surely to the best solution of the individual instances.*

Proof. (sketch) We show that the previous convergence result of CEM [Hu et al., 2011] extends to DecentCEM under the same sample budget. The key observation is that the convergence property of each CEM instance still holds since the number of samples in each instance is only changed by a constant factor, i.e., number of instances. Each CEM instance converges to local optima. The convergence of DecentCEM to the best solution comes from the argmax operator and applying the strong law of large numbers. The detailed proof is left to the appendix H. □

4 DecentCEM for Planning

In this section, we develop two instantiations of DecentCEM for planning in MBRL where the sampling distributions are parameterized by policy networks. For the dynamics model learning, we adopt the ensemble of probabilistic neural networks proposed in [Chua et al., 2018]. Each network predicts the mean and diagonal covariance of a Gaussian distribution and is trained by minimizing the negative log likelihood. Our work focuses on the planning aspect and refer to Chua et al. [2018] for further details on the model.

CEM Planning with a Policy Network   In MBRL, CEM is applied to every state separately to solve the optimization problem stated in Eq. (1). The sampling distribution is typically initialized to a fixed distribution at the beginning of every episode [Okada and Taniguchi, 2020, Pinneri et al., 2020], or more frequently at every time step [Hafner et al., 2019]. Such initialization schemes are sample inefficient since there is no mechanism that allows the information of the high-value region in the value space of one state to generalize to nearby states. Also, the information is discarded after the initialization. It is hence difficult to scale the approach to higher dimensional

Figure 5: DecentCEM planning architecture. $\psi_i = \phi_i$ for planning in action space and $\psi_i = \theta_i$ for planning in policy network parameter space.

solution spaces, present in many continuous control environments. Wang and Ba [2020] proposed to use a policy network in CEM planning that helped to mitigate the issues above.

They developed two methods: *POPLIN-A* that plans in the action space, and *POPLIN-P* that plans in the parameter space of the policy network. In *POPLIN-A*, the policy network is used to learn to output the mean of a Gaussian sampling distribution of actions. In *POPLIN-P*, the policy network parameters serve as the initialization of the mean of the sampling distribution of parameters. The improved policy network can then be used to generate an action. They show that when compared to the vanilla method of using a fixed sampling distribution in the action space, both modes of CEM planning with such a learned distribution perform better. The same principle of combining a policy network with CEM can be applied to the DecentCEM approach as well, which we describe next.

DecentCEM Planning with an Ensemble of Policy Networks   For better sample efficiency in MBRL setting, we extend DecentCEM to use an ensemble of policy networks to learn the sampling distributions in the CEM instances. Similar to the *POPLIN* variations, we develop two instantiations of *DecentCEM*, namely *DecentCEM-A* and *DecentCEM-P*. The architecture of the proposed algorithm is illustrated in Fig. 5. *DecentCEM-A* plans in the action space. It consists of an ensemble of policy networks followed by CEM instances. Each policy network takes the current state s_t as input, outputs the parameters θ_i of the sampling distribution for CEM instance i. There is no fundamental difference from the DecentCEM formulation in Section 3 except that the initialization of sampling distributions is learned by the policy networks rather than a fixed distribution.

The second instantiation *DecentCEM-P* plans in the parameter space of the policy network. The initial sampling distribution is a Gaussian distribution over the policy parameter space with the mean at the current parameter values. In the $\arg\max$ operation in Eq. (3), the sample $\tau_{i,j}$ denotes the parameters of the policy network. Its value is obtained by computing the value of the action sequence generated from the policy network with the parameters $\tau_{i,j}$.

The ensemble of policy networks in both instantiations *DecentCEM-A* and *DecentCEM-P* are initialized with random weights, which is empirically found to be adequate to ensure that the output of the networks do not collapse into the same distribution (Sec. 6.2 and Appendix F).

Training the Policy Networks in DecentCEM   When planning in action space, the policy networks are trained by behavior cloning, similar to the scheme in *POPLIN* [Wang and Ba, 2020]. Denote the first action in the planned action sequence at time step t by the i-th CEM instance as $\hat{a}_{t,i}$, the i-th policy network is trained to mimic $\hat{a}_{t,i}$ and the training objective is $\min_{\theta_i} \mathbb{E}_{s_t, \hat{a}_{t,i} \sim D_i} \|a_{\theta_i}(s_t) - \hat{a}_{t,i}\|^2$ where D_i denotes the replay buffer with the state and action pairs $(s_t, \hat{a}_{t,i})$. $a_{\theta_i}(s_t)$ is the action prediction at state s_t from the policy network parameterized by θ_i.

While the above training scheme can be applied to both planning in action space and parameter space, we follow the *setting parameter average* (AVG) [Wang and Ba, 2020] training scheme when planning in parameter space. The parameter is updated as $\theta_i = \theta_i + \frac{1}{|D_i|} \sum_{\delta_i \in D_i} \delta_i$ where $D_i = \{\delta_i\}$ is a dataset of policy network parameter updates planned from the i-th CEM instance previously. It is more effective than behavior cloning based on the experimental result reported by Wang and Ba [2020] and our own preliminary experiments.

Note that each policy network in the ensemble is trained independently from the data observed by its corresponding CEM instance rather than from the aggregated result after taking the $\arg\max$. This allows for enough diversity among the instances. More importantly, it increases the size of the training dataset for the policy networks compared to the approach taken in *POPLIN*. For example, with an ensemble of M instances, there would be M training data samples available from one real environment interaction, compared to the one data sample in *POPLIN-A/P*. As a result, *DecentCEM* is able to train larger policy networks than is otherwise possible, shown in Sec. 6.2 and Appendix F.

5   Related Work

We limit the scope of related works to CEM planning methods, which is one of the broad class of planning algorithms in MBRL. For a review of different families of planning algorithms, the readers are referred to Wang et al. [2019]. Vanilla CEM planning in action space with a single Gaussian distribution has been adopted as the planning method for both simulated and real-world robot control [Chua et al., 2018, Finn and Levine, 2017, Ebert et al., 2018, Hafner et al., 2019, Yang et al., 2020, Zhang et al., 2021]. Previous attempts to improving the performance of CEM-based planning can be grouped into two types of approaches. **The first type** includes CEM in a hybrid of CEM+X where "X"

is some other component or algorithm. POPLIN [Wang and Ba, 2020] is a prominent example where "X" is a policy network that learns a state conditioned distribution that initializes the subsequent CEM process. Another common choice of "X" is gradient-based adjustment of the samples drawn in CEM. GradCEM [Bharadhwaj et al., 2020] adjusts the samples in each iteration of CEM by taking gradient ascent of the return estimate w.r.t the actions. CEM-RL [Pourchot and Sigaud, 2019] also combines CEM with gradient based updates from RL algorithms but the samples are in the parameter space of the actor network. To improve computational efficiency, Lee et al. [2020] proposes an asynchronous version of CEM-RL where each CEM instance updates the sampling distribution asynchronously.

The second type of approach aims at improving CEM itself. Amos and Yarats [2020] proposes a fully-differentiable version of CEM called *DCEM*. The key is to make the top-k selection in CEM differentiable such that the entire CEM module can be trained in an end-to-end fashion. Despite cutting down the number of samples needed in CEM, this method does not beat the vanilla CEM in benchmark test. *GACEM* [Hakhamaneshi et al., 2020] increase the capacity of the sampling distribution by replacing the Gaussian distribution with an auto-regressive neural network. This change allows CEM to perform search in multi-modal solution space but it is only verified in toy examples and its computation seems too high to be scaled to MBRL tasks. Another method that increases the capacity of the sampling distribution is *PaETS* [Okada and Taniguchi, 2020] that uses a GMM with CEM. It is the approach that we followed for our *CEM-GMM* implementation. The running time results in the optimization task in Sec.3 shows that it is computationally heavier than the *CEM* and *DecentCEM* methods, limiting its use in complex environments. Macua et al. [2015] proposed a "distributed" CEM that is similar in spirit to our method in that they used multiple sampling distributions and applied the top-k selection locally to samples from each instance. However, their instances are cooperative as opposed to being independent as in our work. They applied "collaborative smoothed projection steps" to update each sampling distribution as an average of its neighboring instances including itself. The updating procedure is more complicated than our proposed method and proper network topology of the instances is needed: a naive approach of updating according to all instances will lead to mode collapse since the resulting sampling distributions will be identical. The method was tested in toy optimization examples only. Overall, this second type of approach did not outperform vanilla CEM, a situation that motivated our move to a decentralized formulation.

6 Experiments

We evaluate the proposed *DecentCEM* methods in simulated environments with continuous action space. The experimental evaluation is mainly setup to understand if *DecentCEM* improves the performance and sample efficiency over conventional CEM approaches.

6.1 Benchmark Setup

Environments We run the benchmark in a set of OpenAI Gym environments commonly used in the MBRL literature: Pendulum, InvertedPendulum, Cartpole, Acrobot, FixedSwimmer[5], Reacher, Hopper, Walker2D, HalfCheetah, PETS-Reacher3D, PETS-HalfCheetah, PETS-Pusher, Ant. The three environments prefixed by "PETS" are proposed by Chua et al. [2018]. Note that MBRL algorithms often make different assumptions about the dynamics model or the reward function. Their benchmark environments are often modified from the original OpenAI gym environments such that the respective algorithm is runnable. Whenever possible, we inherit the same environment setup from that of the respective baseline methods. This is so that the comparison against the baselines is fair. More details on the environments and their reward functions are in Appendix B.

Algorithms The baseline algorithms are *PETS* [Chua et al., 2018] and *POPLIN* [Wang and Ba, 2020]. *PETS* uses CEM with a single Gaussian distribution for planning. The *POPLIN* algorithm combines a single policy network with CEM. As described in Sec.4, *POPLIN* comes with two modes: *POPLIN-A* and *POPLIN-P* with the suffix "A" denotes planning in action space and "P" for the network parameter space. We reuse default hyperparameters for these algorithms from the original papers if not mentioned specifically. For our proposed methods, we include two variations *DecentCEM-A* and *DecentCEM-P* as described in Sec. 4 where the suffix carries the same meaning as in *POPLIN-A/P*. The ensemble size of *DecentCEM-A/P* as well as detailed hyperparameters for

---

[5]a modified version of the original Gym Swimmer environment where the velocity sensor on the neck is moved to the head. This fix was proposed by Wang and Ba [2020]

319 all algorithms are listed in the Appendix D.2. We also included Decentralized PETS. All MBRL
320 algorithms studied in this benchmark uses the same ensemble networks proposed by Chua et al.
321 [2018] for model learning. We also include a model-free RL baseline SAC [Haarnoja et al., 2018].

322 **Evaluation Protocol** The learning curve shows the mean and standard error of the test performance
323 out of 5 independent training runs. The test performance is an average return of 5 episodes of
324 the *evaluation* environment, evaluated at every training episode. At the beginning of each training
325 run, the evaluation environment is initialized with a fixed random seed such that the *evaluation*
326 environments are consistent across different methods and multiple runs to make it a fair comparison.
All experiments were conducted using Tesla V100-PCIE-16GB GPUs.

Figure 6: Learning curves of the proposed *DecentCEM* methods and the baselines on continuous control
environments. The line and shaded region shows the mean and standard error of evaluation results from 5
training runs with different random seeds. Evaluation is performed per training episode in an environment
independent from training and reports the average return of 5 evaluation episodes.

327
328 **6.2 Results**

329 **Learning Curves** The learning curves of the algorithms are shown in Fig. 6 for InvertedPendulum,
330 Acrobot, Reacher, Walker2D, PETS-Pusher and Ant, sorted by the state and action dimensionality of
331 task. The curves are smoothed with a sliding window of 10 data points. The full results for all environ-
332 ments are included in Appendix E. *We can observe two main patterns from the results.* One pattern was
333 that in most environments, the *decentralized* methods *DecentPETS, DecentCEM-A/P* either matched
334 or outperformed their counterpart that took a *centralized* approach. In fact, the former can be seen as
335 a generalization of the later, by an additional hyperparameter that controls the ensemble size with size
336 one recovering the centralized approach. The optimal ensemble size depends on the task. This addi-
337 tional hyperparameter offers flexibility in fine-tuning CEM for individual domains. For instance in
338 Fig. 6, for the P-mode where the planning is performed in policy parameter space, an ensemble size of
339 larger than one works better in most environments while an ensemble size of one works better in Ant.
340

341 The other pattern was that using pol-
342 icy networks to learn the sampling dis-
343 tribution in general helped improving
344 the performance of *centralized* CEM
345 but not necessarily in *decentralized*
346 formulation. This is perhaps due to
347 that the added exploration from multi-
348 ple instances makes it possible to iden-
349 tify good solutions in some environ-
350 ments. And adding a policy net may
351 hinder the exploration due to overfit-
352 ting to previous actions.

Figure 7: Ablation study on the policy network size where
POPLIN-A&P have a bigger policy network equivalent in the total
number of network weights to their *DecentCEM* counterparts.

Ablation Study A natural question to ask about the *DecentCEM-A/P* methods is whether the increased performance is from the larger number of neural network parameters. We added two variations of the *POPLIN* baselines where a bigger policy network was used. The number of the network parameters was equivalent to that of the ensemble of policy networks in *DecentCEM-A/P*. We show the comparison in Reacher(2) and PETS-Pusher(7) (action dimension in

Figure 8: Ablation study on the ensemble size, e.g. E2 denotes an ensemble with 2 instances. The total number of samples during planning are the same across all variations.

parenthesis) in Fig. 7. In both action space and parameter space planning, a bigger policy network in *POPLIN* either did not help or significantly impaired the performance (see the *POPLIN-P* results in reacher and PETS-Pusher). This is expected since unlike *DecentCEM*, the training data in *POPLIN* do not scale with the size of the policy network, as explained at the end of Sec. 4.

Fig. 8 shows the impact of ensemble size under the action space planning (left) and parameter space planning (right). Since we fix the total number of samples the same across the methods, the larger the ensemble size is, the fewer samples that each instance has access to. As the ensemble size goes up, we are trading off the accuracy of the sample mean for better exploration by more instances. Varying this hyperparameter allows us to find the best trade-off, as can be observed from the figure where increasing the ensemble size beyond a sweet spot yields diminishing or worse returns.

Figure 9 (Left) shows the cumulative selection ratio of each CEM instance during training of *DecentCEM-A* with an ensemble size of 5. It suggests that the random initialization of the policy network is sufficient to avoid mode collapse. We also plot the action statistics of the instances in Figure 9 (Right). For visual clarity, we show a time segment toward the end of the training rather than all the 10k steps. DecentCEM has maintained enough diversity in the instances even toward the end of the training. *DecentCEM-P* is excluded from both plots since it

Figure 9: Ablation of ensemble diversity. Left: Cumulative selection ratio of each CEM instance. Right: Action statistics of the instances, with the line and shaded region representing the mean and min/max action.

shows a similar trend as *DecentCEM-A*. More ablations results are included in Appendix F.

7 Conclusion and Future Work

In this paper, we study CEM planning in the context of continuous-action MBRL. We propose a novel *decentralized* formulation of CEM named *DecentCEM*, which generalizes CEM to run multiple independent instances and recovers the conventional CEM when the number of instances is one. We illustrate the strengths of the proposed DecentCEM approach in a motivational one-dimensional optimization task and show how it fundamentally differs from the CEM approach that uses a Gaussian or GMM. We also show that DecentCEM has almost sure convergence to a local optimum. We extend the proposed approach to MBRL by instantiating two *decentralized* CEM methods that combine with policy networks. We show their efficacy in benchmark control tasks and ablations studies.

There is a gap between the convergence result and practice where the theory assumes that the number of samples grow polynomially with the iterations whereas a constant sample size is commonly used in practice including our work. Investigating the convergence properties of *CEM* under a constant sample size makes an interesting direction for future work. Another interesting direction to pursue is finite-time analysis of both *CEM* and *DecentCEM*.

References

A. Agarwal, N. Jiang, and S. M. Kakade. Reinforcement learning: Theory and algorithms. 2019.

B. Amos and D. Yarats. The differentiable cross-entropy method. In *International Conference on Machine Learning*, pages 291–302. PMLR, 2020.

D. P. Bertsekas. Dynamic programming and optimal control 3rd edition, volume i. *Belmont, MA: Athena Scientific*, 2005.

H. Bharadhwaj, K. Xie, and F. Shkurti. Model-predictive control via cross-entropy and gradient-based optimization. In *Learning for Dynamics and Control*, pages 277–286. PMLR, 2020.

K. Chua, R. Calandra, R. McAllister, and S. Levine. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, page 4759–4770, 2018.

P.-T. De Boer, D. P. Kroese, S. Mannor, and R. Y. Rubinstein. A tutorial on the cross-entropy method. *Annals of operations research*, 134(1):19–67, 2005.

F. Ebert, C. Finn, S. Dasari, A. Xie, A. Lee, and S. Levine. Visual foresight: Model-based deep reinforcement learning for vision-based robotic control. *arXiv preprint arXiv:1812.00568*, 2018.

C. Finn and S. Levine. Deep visual foresight for planning robot motion. In *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pages 2786–2793. IEEE, 2017.

T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International conference on machine learning*, pages 1861–1870. PMLR, 2018.

D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. In *International Conference on Machine Learning*, pages 2555–2565. PMLR, 2019.

K. Hakhamaneshi, K. Settaluri, P. Abbeel, and V. Stojanovic. Gacem: Generalized autoregressive cross entropy method for multi-modal black box constraint satisfaction. *arXiv preprint arXiv:2002.07236*, 2020.

J. Hu, P. Hu, and H. S. Chang. A stochastic approximation framework for a class of randomized optimization algorithms. *IEEE Transactions on Automatic Control*, 57(1):165–178, 2011.

K. Lee, B.-U. Lee, U. Shin, and I. S. Kweon. An efficient asynchronous method for integrating evolutionary and gradient-based policy search. *Advances in Neural Information Processing Systems*, 33, 2020.

K. Lowrey, A. Rajeswaran, S. Kakade, E. Todorov, and I. Mordatch. Plan online, learn offline: Efficient learning and exploration via model-based control. In *International Conference on Learning Representations, ICLR*, 2019.

S. V. Macua, S. Zazo, and J. Zazo. Distributed black-box optimization of nonconvex functions. In *2015 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3591–3595. IEEE, 2015.

S. Mannor, R. Y. Rubinstein, and Y. Gat. The cross entropy method for fast policy search. In *Proceedings of the 20th International Conference on Machine Learning (ICML-03)*, pages 512–519, 2003.

M. Okada and T. Taniguchi. Variational inference mpc for bayesian model-based reinforcement learning. In *Conference on Robot Learning*, pages 258–272. PMLR, 2020.

C. Pinneri, S. Sawant, S. Blaes, J. Achterhold, J. Stueckler, M. Rolinek, and G. Martius. Sample-efficient cross-entropy method for real-time planning. *arXiv preprint arXiv:2008.06389*, 2020.

A. Pourchot and O. Sigaud. CEM-RL: combining evolutionary and gradient-based methods for policy search. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9*, 2019.

T. Wang and J. Ba. Exploring model-based planning with policy networks. In *8th International Conference on Learning Representations, ICLR, Addis Ababa, Ethiopia, April 26-30*, 2020.

T. Wang, X. Bao, I. Clavera, J. Hoang, Y. Wen, E. Langlois, S. Zhang, G. Zhang, P. Abbeel, and J. Ba. Benchmarking model-based reinforcement learning. *CoRR*, abs/1907.02057, 2019.

Y. Yang, K. Caluwaerts, A. Iscen, T. Zhang, J. Tan, and V. Sindhwani. Data efficient reinforcement learning for legged robots. In *Conference on Robot Learning*, pages 1–10. PMLR, 2020.

B. Zhang, R. Rajan, L. Pineda, N. Lambert, A. Biedenkapp, K. Chua, F. Hutter, and R. Calandra. On the importance of hyperparameter optimization for model-based reinforcement learning. In *International Conference on Artificial Intelligence and Statistics*, pages 4015–4023. PMLR, 2021.