Incentivizing Combinatorial Bandit Exploration

Abstract

Consider a bandit algorithm that recommends actions to self-interested users in a recommendation system. The users are free to choose other actions and need to be incentivized to follow the algorithm's recommendations. While the users prefer to *exploit*, the algorithm can incentivize them to *explore* by leveraging the information collected from the previous users. All published work on this problem, known as *incentivized exploration*, focuses on small, unstructured action sets and mainly targets the case when the users' beliefs are independent across actions. However, realistic exploration problems often feature large, structured action sets and highly correlated beliefs. We focus on a paradigmatic exploration problem with structure: combinatorial semi-bandits. We prove that Thompson Sampling, when applied to combinatorial semi-bandits, is incentive-compatible when initialized with a sufficient number of samples of each arm (where this number is determined in advance by the Bayesian prior). Moreover, we design incentive-compatible algorithms for collecting the initial samples.

1 Introduction

We consider *incentivized exploration*: how to incentivize self-interested users to explore. A social planner interacts with self-interested users (henceforth, *agents*) and can make recommendations, but cannot enforce the agents to comply with these recommendations. The agents face uncertainty about the available alternatives. The social planner would like the agents to trade off *exploration* for the sake of acquiring new information and *exploitation*, making optimal near-term decisions based on the current information. The agents, on the other hand, prefer to *exploit*. However, the algorithm can incentivize them to *explore* by leveraging the information collected from the previous users. This problem has been studied since Kremer et al. (2014), see Slivkins (2019, Ch. 11) for an overview.

All published work on this problem focuses on small, unstructured action sets. Moreover, the case of *independent priors* – when the users' beliefs are independent across actions – is emphasized as the main, paradigmatic special case when specific performance guarantees are derived. However, realistic exploration problems often feature large sets with some known structure that connects actions to one another. A major recurring theme in the vast literature on multi-armed bandits is taking advantage of the available structure so as to enable the algorithm to cope with the large number of actions.

We focus on a paradigmatic, well-studied exploration problem with structured actions: *combinatorial semi-bandits*. Here, each arm is a subset of some ground set, whose elements are called *atoms*. In each round, the algorithm chooses an arm, and observes/collects reward for each atom in this arm. The reward for each atom is drawn independently from some fixed (but unknown) distribution specific to this atom. The set of feasible arms reflects the structure of the problem, *e.g.,* it can comprise all subsets of atoms of a given cardinality, or all edge-paths in a given graph. Since the number of arms (K) can be exponential in the number of atoms (d), the main theme is replacing the dependence on K in regret bounds for "unstructured" K-armed bandits with a similar dependence on d.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

We adopt a standard model for incentivized exploration from Kremer et al. (2014). The social planner is implemented as a bandit algorithm. Each round corresponds to a new agent which arrives and receives the arm chosen by the algorithm as a recommendation. Agents have Bayesian beliefs, independent across the atoms (but highly correlated across the arms). The algorithm must ensure that following its recommendation is in each agent's best interest, a condition called *Bayesian incentive-compatibility* (*BIC*). Each agent does not observe what happened with the previous agents, but the algorithm does. This information asymmetry is crucial for creating incentives.

Our contributions. We prove that Thompson Sampling is BIC when initialized with at least n_{TS} samples of each atom, where n_{TS} is determined by the prior and scales polynomially in the number of atoms (d). Thompson Sampling (Thompson, 1933) is a well-known bandit algorithm with near-optimal regret bounds and good empirical performance. The initial samples can be provided by another BIC algorithm (more on this below), or procured exogenously, *e.g.,* bought with money.

Next, we consider the problem of *initial exploration*: essentially, design a BIC algorithm that samples each atom at least once. Such algorithms are interesting in their own right, and can be used to bootstrap Thompson Sampling, as per above. We present two such algorithms, which build on prior work (Mansour et al., 2020; Simchowitz and Slivkins, 2021) and extend it in non-trivial ways. The objective to be optimized is the sufficient number of rounds T_0, and particularly its dependence on d. To calibrate, prior work on incentivized exploration in multi-armed bandits with correlated priors does not provide any guarantees for a super-constant number of arms (K), and is known to have $T_0 > \exp(\Omega(K))$ in some natural examples (Mansour et al., 2020). In contrast, our algorithms satisfy $T_0 \leq \exp(O(d))$ for a paradigmatic special case, and $T_0 \leq \exp(O(d^3))$ in general.

Discussion. Like all prior work on incentivized exploration, we consider standard, yet idealized models for agents' economic behavior and the machine-learning problem being solved by the social planner. The modeling captures something essential about exploration and incentives in recommendation systems, but is not supposed to capture all the particularities of any specific application scenario. The goal of this paper is to bring more complexity into the machine-learning problem; advancing the economic model is beyond our scope.

We focus on establishing the BIC property and asymptotic guarantees in terms of the number of atoms, without attempting to optimize the dependence on the per-atom Bayesian priors. Our Thompson Sampling result has an encouraging practical implication: a standard, well-performing bandit algorithm plays well with users' incentives, provided a small (in theory) amount of initial data.

The significance of focusing on combinatorial semi-bandits is primarily that it is a paradigmatic example of exploration with large, structured action sets, with a number of motivating examples established in the literature. (Stylized) motivating examples specific to incentivized exploration include: recommending online content, *e.g.,* for news or entertainment (with atoms as *e.g.,* specific news articles); recommending complementary products, *e.g.,* a suit that consists of multiple items of clothing; recommending driving directions. In all cases, the social planner corresponds to the online platform issuing the respective recommendations. Such online platforms are often interested in maximizing users' happiness, rather than (or in addition to) the immediate revenue, as a way to ensure user engagement and long-term success.

As a theoretical investigation, this paper appears unlikely to cause social harms. If anything, our goal here is to ensure that the aggregate welfare is not harmed by users' myopia.

Related work. Incentivized exploration, as defined in this paper, has been introduced in Kremer et al. (2014) and subsequently studied, *e.g.,* in Mansour et al. (2020, 2022); Immorlica et al. (2020); Bahar et al. (2016, 2019), along with some extensions. Most related is Sellke and Slivkins (2021), which obtains similar BIC results for the special case of multi-armed bandits with independent priors, both for Thompson Sampling and for initial exploration. A yet unpublished working paper of Simchowitz and Slivkins (2021) provides a BIC algorithm for initial exploration in reinforcement learning; we build on this result in one of ours. Similar, but technically incomparable versions have been studied, *e.g.,* with time-discounted rewards (Bimpikis et al., 2018) and creating incentives via money (Frazier et al., 2014; Chen et al., 2018).

From the perspective of theoretical economics, incentivized exploration is related to the literature on information design (Kamenica, 2019; Bergemann and Morris, 2019): essentially, one round of incentivized exploration is an instance of Bayesian persuasion, a central model in this literature. Other "online" models of Bayesian persuasion have been studied (*e.g.,* Castiglioni et al., 2020; Zu

et al., 2021), but are very different from ours in that the planner's problem has nothing to do with exploration, and is not even meaningful without incentives.

On the machine learning side, this paper is related to the work on combinatorial semi-bandits, starting from György et al. (2007), *e.g.,* (Chen et al., 2013; Kveton et al., 2015, 2014), and the work on Thompson Sampling, see Russo et al. (2018) for a survey. In particular, near-optimal Bayesian regret bounds have been derived in Russo and Van Roy (2014, 2016), and frequentist ones in (Agrawal and Goyal, 2017; Kaufmann et al., 2012). Thompson Sampling has been applied to combinatorial semi-bandits, (*e.g.,* Gopalan et al., 2014; Wen et al., 2015; Degenne and Perchet, 2016; Wang and Chen, 2018), with Bayesian regret bounds derived in Russo and Van Roy (2016).

2 Problem Formulation and Preliminaries

Our algorithm operates according to the standard protocol for *combinatorial semi-bandits*, with an ancillary incentive-compatibility constraint, standard in the literature on *incentivized exploration*.

Combinatorial semi-bandits. There are T rounds, d atoms and K arms, where each arm is a subset of atoms. The set $\mathcal{A}$ of feasible arms is fixed and known. In each round t, each atom ℓ generates reward $r_\ell^{(t)} \in [0, 1]$. The algorithm chooses an arm $A^{(t)} \in \mathcal{A}$ and observes the reward of each atom in this arm (and nothing else). Algorithm's reward in this round is the total reward of these atoms.

Formally, we write $[T] := \{1, \dots, T\}$ for the set of all rounds and $[d]$ for the set of all atoms, so that arms are subsets $A \subset [d]$. Let θ_ℓ be the expected reward of atom $\ell \in [d]$, and let $\mu(A) = \sum_{\ell \in A} \theta_\ell$ be the expected reward of a given arm $A \subset [d]$. Note that d-armed bandits are a special case when the feasible arms are singleton sets $\{\ell\}$, $\ell \in [d]$.

Stochastic rewards and Bayesian priors. The reward of each atom $\ell \in [0, 1]$ is drawn independently in each round from a fixed distribution $\mathcal{D}_\ell$ specific to this atom. This distribution comes from a parametric family, parameterized by the expected reward θ_ℓ. The (realized) problem instance is therefore specified by the *mean reward vector* $\theta = (\theta_1, \dots, \theta_d)$. Initially, each θ_ℓ is drawn independently from a Bayesian prior $\mathcal{P}_\ell$ with support $\Theta \subset [0, 1]$. Put differently, the mean reward vector θ is drawn from the product prior $\mathcal{P} = \mathcal{P}_1 \times \cdots \times \mathcal{P}_d$.

Incentive-compatibility. The algorithm must ensure that in each round t, conditional on a particular arm $A = A^{(t)}$ being chosen, the expected reward of this arm is at least as good as that of any other arm. Formally, the algorithm is called *Bayesian incentive-compatible* (BIC) if for each round $t \in [T]$,

$$\mathbb{E}[\mu(A) - \mu(A') \mid A^{(t)} = A] \geq 0 \qquad \forall \text{ arms } A, A' \in \mathcal{A} \text{ with } \mathbb{P}[A^{(t)} = A] > 0. \tag{1}$$

This definition is based on the following stylized story . In each round t, a new user arrives to a recommendation system, observes the arm $A^{(t)}$ chosen by our algorithm, and interprets it as a recommendation. Then the user decides which arm to choose (not necessarily the arm recommended), and receives the corresponding reward. Accordingly, the user needs to be incentivized to follow the recommendation. We adopt a standard setup from economic theory (and the prior work on incentivized exploration): each user has the same prior $\mathcal{P}$, knows the algorithm, and wishes to maximize her expected reward. We posit that the user does not observe anything else before making her decision, other than the recommended arm. In particular, she does not observe anything about the previous rounds. Then, (1) ensures that she is (weakly) incentivized to follow her recommendation, assuming that the previous users followed theirs. We posit that under (1), the user does follow recommendations, and then reports the rewards of all atoms to the algorithm.

We emphasize that this story is not a part of our formal model (although it can be expressed as such if needed). In fact, the story can be extended to allow the algorithm to reveal an arbitrary "message" to each user, but this additional power is useless: essentially, anything that can be achieved with arbitrary messages can also be achieved with arm recommendations. This can easily be proved as a version of Myerson's *direct revelation principle* from theoretical economics.

Conventions. Each atom ℓ satisfies $\mathbb{P}[\theta_\ell > 0] > 0$: else, its rewards are all 0, so it can be ignored.

No arm is contained in any the other arm. This is w.l.o.g. for Bernoulli rewards, and more generally if $\mathbb{P}[r_\ell^{(t)} = 0 \mid \theta_\ell > 0] > 0$: if $A \subset A'$ for arms A, A' then A cannot be chosen by any BIC algorithm.

W.l.o.g., order the atoms ℓ by their prior mean rewards $\theta_\ell^0 := \mathbb{E}[\theta_\ell]$, so that $\mathbb{E}[\theta_1^0] \geq \cdots \geq \mathbb{E}[\theta_d^0]$.

142 Let $A^* = \arg\max_{A \in \mathcal{A}} \mu(A)$ denote the best arm overall, with some fixed tie-breaking rule.

143 By a slight abuse of notation, each arm $A \subset [d]$ is sometimes identified with a binary vector
144 $v \in \{0,1\}^d$ such that $v_\ell = 1 \Leftrightarrow \ell \in A$, for each atom $\ell \in [d]$. In particular, we write $A_\ell = v_\ell$.

145 **Thompson Sampling** has a very simple definition, generic to many versions of multi-armed bandits.
146 Let $\mathcal{F}_t$ denote the realized history (tuples of chosen actions and realized rewards of all atoms) up to
147 and not including round t. Write $\mathbb{E}^{(t)}[\,\cdot\,] = \mathbb{E}[\,\cdot\,|\,\mathcal{F}_t\,]$ and $\mathbb{P}^{(t)}[\,\cdot\,] = \mathbb{P}[\,\cdot\,|\,\mathcal{F}_t\,]$ as a shorthand for
148 posterior updates. Thompson Sampling in a given round t draws an arm independently at random
149 from distribution $p^{(t)}(A) = \mathbb{P}^{(t)}[A^* = A]$, $A \in \mathcal{A}$. If Thompson Sampling is started from some
150 fixed round $t_0 > 1$, this is tantamount to starting the algorithm from round 1, but with prior $\mathcal{P}(\cdot \mid \mathcal{F}_{t_0})$
151 rather than $\mathcal{P}$. The algorithm is well-defined for an arbitrary prior $\mathcal{P}$.

152 While this paper is not concerned with computational issues, they are as follows. The posterior
153 update $\mathcal{P}(\cdot \mid \mathcal{F}_t)$ can be performed for each atom ℓ separately: $\mathcal{P}_\ell(\cdot \mid \mathcal{F}_{t,\ell})$, where $\mathcal{F}_{t,\ell}$ is the
154 corresponding history of samples from this atom. A standard implementation draws $\theta'_\ell \in [0,1]$
155 independently from $\mathcal{P}_\ell(\cdot \mid \mathcal{F}_{t,\ell})$, for each atom ℓ, then chooses the best arm according to these
156 draws: $\arg\max_{A \in \mathcal{A}} \sum_{\ell \in A} \theta'_\ell$. The posterior updates $\mathcal{P}_\ell(\cdot \mid \mathcal{F}_{t,\ell})$ and the $\arg\max$ choice are not
157 computationally efficient in general, and may require heuristics (this is a common situation for all
158 variants of Thompson Sampling). A paradigmatic special case is Beta priors $\mathcal{P}_\ell$ and Bernoulli reward
159 distributions $\mathcal{D}_\ell$, so that the posterior update $\mathcal{P}_\ell(\cdot \mid \mathcal{F}_{t,\ell})$ is another Beta prior.

160 **Composition of BIC algorithms.** We rely on a generic observation from Mansour et al. (2020, 2022)
161 that the composition of two BIC algorithms is also BIC.

162 **Lemma 2.1.** *Let* `ALG` *be a BIC algorithm which stops after some round* T_0. *Let* `ALG'(H)` *be another*
163 *algorithm that initially inputs the history H collected by* `ALG`, *and suppose it is BIC. Consider*
164 *the composite algorithm:* `ALG` *followed by* `ALG'(H)`, *which stops at the time horizon T. If T_0 is*
165 *determined before the composite algorithm starts, then this algorithm is BIC.*

3   Thompson Sampling is BIC

167 Our main result is that Thompson Sampling is BIC when initialized with at least $n_{\mathtt{TS}}$ samples of each
168 atom, where $n_{\mathtt{TS}}$ is determined by the prior and scales polynomially in d, the number of atoms.

169 **Theorem 3.1.** *Let* `ALG` *be any BIC algorithm such that by some time T_0 (which is determined by the*
170 *prior) it almost surely collects at least $n_{\mathtt{TS}} = C_{\mathtt{TS}} \cdot d^2 \cdot \epsilon_{\mathtt{TS}}^{-2} \cdot \log(\delta_{\mathtt{TS}}^{-1})$ samples from each atom, where*

$$\epsilon_{\mathtt{TS}} = \min_{A, A' \in \mathcal{A}} \mathbb{E}[(\mu(A) - \mu(A'))_+] \quad and \quad \delta_{\mathtt{TS}} = \min_{A \in \mathcal{A}} \mathbb{P}[A^* = A], \tag{2}$$

171 *and $C_{\mathtt{TS}}$ is a large enough absolute constant. Consider the composite algorithm which runs* `ALG` *for*
172 *the first T_0 rounds, followed by Thompson sampling. This algorithm is BIC.*

173 Note that T_0 are $n_{\mathtt{TS}}$ are "constants" once the prior is fixed, in the sense that they do not depend on
174 the time horizon T, the mean reward vector θ, or the rewards in the data collected by `ALG`.

175 **Remark 3.2.** For statistical guarantees, consider Bayesian regret, *i.e.,* regret in expectation over
176 the Bayesian prior. Bayesian regret of the composite algorithm in Theorem 3.1 is at most T_0 plus
177 Bayesian regret of Thompson Sampling. The latter is $O(\sqrt{dT \log d})$ for any prior (Russo and Van
178 Roy, 2016). For an end-to-end result, we provide a suitable `ALG` in Section 4.1, with a specific T_0.

179 **Remark 3.3.** We can invoke Lemma 2.1 since T_0 is determined in advance. So, it suffices to show
180 that each round t of Thompson Sampling satisfies the BIC condition (1).

181 Let us clarify the dependence on d. Note that parameters $\epsilon_{\mathtt{TS}}$ and $\delta_{\mathtt{TS}}$ may depend on d through the
182 prior. To separate the dependence on d from that on the prior, we posit that each per-atom prior $\mathcal{P}_\ell$
183 belongs to a fixed collection $\mathcal{C}$. We make mild non-degeneracy assumptions:[1]

$$\mathbb{P}[\,\mu(A') < \mathbb{E}[\mu(A)]\,] > 0 \qquad \text{for all arms } A \neq A'. \tag{3}$$

$$\mathbb{P}[\theta_\ell > \tau] > 0 \qquad \text{for all atoms } \ell \in [d] \text{ and some } \tau \in (0,1). \tag{4}$$

$$\mathbb{P}[\theta_\ell < x] > \text{poly}(1/x) \cdot \exp(-x^{-\alpha}) \qquad \text{for all atoms } \ell \in [d], x \in (0, 1/2) \text{ and some } \alpha \geq 0. \tag{5}$$

---

[1]For the special case of d-armed bandits, assumption (3) is necessary and sufficient for the respective arm A
to be *explorable*: chosen in some round by some BIC algorithm (Sellke and Slivkins, 2021).

Corollary 3.4. *Suppose all priors $\mathcal{P}_\ell$ of atoms $\ell \in [d]$ belong to some fixed, finite collection $\mathcal{C}$ of priors and assumptions (3-5) are satisfied with some absolute constants α, τ. Then $n_{\mathrm{TS}} = O_{\mathcal{C}}(d^{3+\alpha} \log d)$, where $O_{\mathcal{C}}$ hides the absolute constants and the dependency on $\mathcal{C}$.*

Remark 3.5. The initial data can also be provided to Thompson Sampling exogenously (rather than via a BIC algorithm `ALG`), *e.g.,* purchased with money. More formally, one would need to provide a collection of (arm, reward) datapoints such that each atom is sampled at least n_{TS} times.[2]

Proof Sketch for Theorem 3.1 (full proof in Appendix B). In order to establish the BIC condition in (1) for Thompson Sampling, we first observe that $\mathbb{P}[A^* = A]$ is a positive prior-dependent constant for all arms A, so it suffices to prove $\mathbb{E}\left[\mathbb{E}^{(t)}[\mu(A) - \mu(A')] \cdot \mathbf{1}_{\{A^*=A\}}\right] \geq 0$ for all A, A'.

Next, to show a lower bound on $\mathbb{E}\left[(\mu(A) - \mu(A')) \cdot \mathbf{1}_{\{A^*=A\}}\right]$, we will leverage the Harris inequality Theorem D.3, which says increasing functions of independent random variables are non-negatively correlated. Observe that the functions $(\mu(A) - \mu(A'))_+$ and $\mathbf{1}_{\{A^*=A\}}$ are co-monotone in each coordinate of θ (*i.e.,* either both increasing or both decreasing in a coordinate). Then, the mixed-monotonicity Harris inequality (see Theorem D.3) implies that:

$$\mathbb{E}\left[(\mu(A) - \mu(A')) \cdot \mathbf{1}_{\{A^*=A\}}\right] = \mathbb{E}\left[(\mu(A) - \mu(A'))_+ \cdot \mathbf{1}_{\{A^*=A\}}\right] \geq \epsilon_{\mathrm{TS}} \cdot \delta_A \tag{6}$$

where $\delta_A = \mathbb{P}[A^* = A] \geq \delta_{\mathrm{TS}}$.

To finish the proof, we show the expected absolute difference between $\mathbb{E}^{(t)}[\mu(A) - \mu(A')] \cdot \mathbf{1}_{\{A^*=A\}}$ and $(\mu(A) - \mu(A')) \cdot \mathbf{1}_{\{A^*=A\}}$ is upper bounded by $\epsilon_{\mathrm{TS}} \cdot \delta_A$. By regrouping and using triangle inequality as well as $\left|x \cdot \mathbf{1}_{\{A^*=A\}}\right| = |x| \cdot \mathbf{1}_{\{A^*=A\}}$, we can upper bound this estimation error by sum of $\mathbb{E}\left[\left|\mathbb{E}^{(t)}\left[\mu_A\right] - \mu_A\right| \cdot \mathbf{1}_{\{A^*=A\}}\right]$ and $\mathbb{E}\left[\left|\mathbb{E}^{(t)}\left[\mu'_A\right] - \mu'_A\right| \cdot \mathbf{1}_{\{A^*=A\}}\right]$. Since the mean reward of each atom can be estimated by their empirical average, we can apply Bayesian Chernoff (see Lemma D.2) and observe that these two terms are $n_{\mathrm{TS}}^{-1/2}$ times $O(1)$-sub-Gaussian random variables. By the sub-Gaussian tail bound (see Lemma D.5), we upper bound both terms by $O(n_{\mathrm{TS}}^{-1/2} \delta_A \sqrt{\log(1/\delta_A)})$. We conclude by using our choices of n_{TS} and observing that $\delta_{\mathrm{TS}} \leq \delta_A$. $\qquad\square$

Proof Sketch for Corollary 3.4 (full proof in Appendix B). To derive the dependence of n_{TS} on d, we investigate how the prior-dependent constants ϵ_{TS} and δ_{TS} depends on d. First, we can let $\epsilon_{\mathcal{C}}$ be a version of ϵ_{TS} where the $\min$ is taken over all ordered pairs of priors in $\mathcal{C}$. Since $\mathcal{C}$ is finite and satisfies the pairwise non-dominance assumption (3), $\epsilon_{\mathrm{TS}} \geq \epsilon_{\mathcal{C}} > 0$.

By definition, $\delta_{\mathrm{TS}} = \min_{A \in \mathcal{A}} \mathbb{P}[A^* = A]$ is the minimum probability that arm A is the best arm overall. Fix an arm A. We observe that the event where arm A is the best arm is more likely than the event where each atom in A is larger than τ, and all other atoms not in A is smaller than τ/d. Hence, we can lower bound $\mathbb{P}[A^* = A]$ by $\mathbb{E}\left[\mathbf{1}_{\{\forall \ell \in A, \theta_\ell \geq \tau\}} \cdot \mathbf{1}_{\{\forall x \notin A, \theta_x \leq \tau/d\}}\right]$. Since the prior $\mathcal{P}$ is independent across atoms, we can write the expression above as product of $\mathbb{E}\left[\mathbf{1}_{\{\forall \ell \in A, \theta_\ell \geq \tau\}}\right]$ and $\mathbb{E}\left[\mathbf{1}_{\{\forall x \notin A, \theta_x \leq \tau/d\}}\right]$. As the values $\{\theta_\ell\}_{\ell \in [d]}$ are independent and co-monotone in each in coordinate of θ, repeated application of mixed-monotonicity Harris inequality (see Remark D.4) implies that:

$$\mathbb{P}[A^* = A] \geq \prod_{\ell \in A} \mathbb{E}\left[\mathbf{1}_{\{\theta_\ell \geq \tau\}}\right] \cdot \prod_{x \notin A} \mathbb{E}\left[\mathbf{1}_{\{\theta_x \leq \tau/d\}}\right]$$

$$= \prod_{\ell \in A} \mathbb{P}[\theta_\ell \geq \tau] \cdot \prod_{x \notin A} \mathbb{P}[\theta_x \leq \tau/d]$$

$$\geq \prod_{\ell=1}^{d} \mathbb{P}[\theta_\ell \geq \tau] \, \mathbb{P}[\theta_\ell \leq \tau/d]$$

By full support assumption (4), we define a prior-dependent constant $\rho_\tau = \min_{A \in \mathcal{A}} \mathbb{P}[\theta_\ell \geq \tau] > 0$. Then, by definition of ρ_τ and the non-degeneracy assumption (5), the expression above is lower bounded by $\rho_\tau^d \cdot \mathrm{poly}(d^d/(\tau)^d) \cdot \exp(-d(\tau/d)^{-\alpha})$. Plugging this bound into n_{TS}, we obtain $n_{TS} = O_{\mathcal{C}}(d^{3+\alpha} \log d)$. $\qquad\square$

---

[2] A subtlety: the number of samples of each arm should be known in advance. This is because otherwise Bayesian update on this data may become dependent on the data-collection algorithm.

3.1 The two-arm case with arbitrary correlation

What if the prior is *not* independent across atoms? Our analysis extends to the case of $K = 2$ arms A, A' with arbitrary correlation between the atoms. In fact, we do not assume combinatorial semi-bandit structure, and instead focus on the fundamental special case of incentivized exploration: when one has two arms A, A' with arbitrary joint prior on $(\mu(A), \mu(A'))$. [3] We prove that Theorem 3.1 extends to this scenario, with $d = 2$. The analysis is very similar, and omitted.

This result completes our understanding of incentivized exploration with two correlated arms: indeed, a necessary and sufficient condition (and the algorithm) are known for collecting the initial data (Mansour et al., 2020). A similar result for two *independent* arms is in (Sellke and Slivkins, 2021).

4   BIC algorithms for initial exploration

We present two BIC algorithms for *initial exploration*, where the objective is to sample each atom at least once (*i.e.,* choose arms whose union is $[d]$) and complete in N_0 rounds for some N_0 determined by the prior. Such algorithms are interesting in their own right, and can be used to bootstrap Thompson Sampling as per Theorem 3.1. (To collect n samples of each arm, repeat the algorithm n times.) Both algorithms complete in the number of rounds that is exponential in $\operatorname{poly}(d)$. The first algorithm completes in $\exp(O_{\mathcal{P}}(d))$ rounds, but is restricted to arms of the same size and Beta-Bernoulli priors. We obtain $\exp(O_{\mathcal{P}}(d^2))$ for arbitrary sets of arms. The second algorithm sidesteps the Beta-Bernoulli restriction, but completes in $\exp(O_{\mathcal{P}}(d^3))$ rounds.

4.1   Reduction to K-armed bandits

The first algorithm builds on the approach from Mansour et al. (2020), which is defined for K-armed bandits and explores a given sequence of arms as long as a certain property (P) holds for this sequence. This property is proved to hold for arms with independent priors, ordered by their prior mean rewards. However, for combinatorial semi-bandits the arms' priors are highly correlated, and satisfying (P) is non-trivial. Our technical contribution here to provide a sequence of arms and prove that (P) holds. Note that it suffices to explore a sequence of arms which collectively cover all the atoms.

Throughout this subsection, we make the following assumptions:

$$\text{the prior } \mathcal{P}_\ell \text{ for each atom } \ell \text{ is a Beta distribution with parameters } (\alpha_\ell, \beta_\ell); \qquad (7)$$

$$\text{the reward distributions } \mathcal{D}_\ell \text{ are Bernoulli distributions.} \qquad (8)$$

This is a paradigmatic special case for Thompson Sampling (and Bayesian inference in general).

Let $\nu_\ell(n) = \alpha_\ell / (\alpha_\ell + \beta_\ell + n), n \geq 0$ be the posterior mean reward of atom ℓ when conditioned on n samples of this atom such that each of these samples returns reward 0.

Given any number $n \in \mathbb{N}$, let us define a sequence of $\kappa(n)$ arms $V_1^n, \ldots, V_{\kappa(n)}^n \in \mathcal{A}$. Let V_1 be a prior-best arm: any arm with the largest prior mean reward. The subsequent arms are defined inductively. Essentially, we pretend that each atom in each arm in the sequence so far has been sampled exactly n times and received 0 each time it has been sampled. The next arm is defined as the posterior-best arm: an arm with a largest posterior reward after seing these samples. Formally, for each $i \geq 2$, we define arm V_i^n given the previous arms $V_1^n, \ldots, V_{i-1}^n$. For each atom $\ell \in [d]$ define $Z_i^n(\ell) = n$ if this atom is contained in one of the previous arms in the sequence, and set $Z_i^n(\ell) = 0$ otherwise. Then, define V_i^n as the posterior-best arm if the posterior mean rewards for atoms ℓ are given by $\nu_\ell(Z_i^n(\ell))$. That is:

$$V_i^n \in \arg\max_{A \in \mathcal{A}} \sum_{\ell \in A} \nu_\ell(Z_i^n(\ell)). \qquad (9)$$

The sequence stops when the arms therein cover all atoms at least once; this defines $\kappa(n)$.

To state the requisite property (P), we focus on this sequence for a particular, prior-dependent choice of n. Let $H_i^n, i \in [\kappa(n)]$ be a dataset that consists of exactly n samples of each arm $V_1^n, \ldots, V_i^n$; each sample contains the reward for each atom in the respective arm. Let H_0^n be an empty dataset.

---

[3] Equivalently, we have $d = 2$ atoms with an arbitrary joint prior on (θ_1, θ_2), and two singleton arms.

(P) There exist numbers $n_{\mathcal{P}} \in \mathbb{N}$ and $\tau_{\mathcal{P}}, \rho_{\mathcal{P}} \in (0,1)$, determined by the prior $\mathcal{P}$, which satisfy the following. Focus on the sequence of arms $V_1, \ldots, V_\kappa$, where $\kappa = \kappa(n_{\mathcal{P}})$ and $V_i = V_i^{n_{\mathcal{P}}}$ for each $i \in [\kappa]$. Then

$$\mathbb{P}\left[X_i^N > \tau_{\mathcal{P}} \right] \geq \rho_{\mathcal{P}} \quad \forall i \in [\kappa] \text{ and } N \geq n_{\mathcal{P}}, \tag{10}$$

where the random variable X_i^N is defined as

$$X_i^N = \min_{\text{arms } A \neq V_i} \mathbb{E}\left[\mu(V_i) - \mu(A) \mid H_{i-1}^N \right].$$

In intuition, any given arm V_i can be the posterior best arm with a margin $\tau_{\mathcal{P}}$ and probability at least $\rho_{\mathcal{P}}$ after seeing at least $n_{\mathcal{P}}$ samples of the previous arms $V_1, \ldots, V_{i-1}$.

Given Property (P), prior work guarantees the following (without relying on assumptions (7-8).

Theorem 4.1 (Mansour et al. (2020))**.** *Assume Property (P) holds with constants $n_{\mathcal{P}}, \tau_{\mathcal{P}}, \rho_{\mathcal{P}}$ and $\kappa = \kappa(n_{\mathcal{P}})$. Then there exists a BIC algorithm which explores each arm $V_1, \ldots, V_\kappa$ at least $n_{\mathcal{P}}$ times and completes in T_0 rounds, where $T_0 = \kappa \cdot n_{\mathcal{P}} \cdot (1 + d) / (\tau_{\mathcal{P}} \cdot \rho_{\mathcal{P}})$.*

Next, we establish (P). First we state a result for a paradigmatic case when all arms have the same cardinality, then relax it in what follows (with a somewhat weaker guarantee).

Theorem 4.2. *Assume Beta-Bernoulli priors (7-8). Further, assume that*

$$\text{The arms are all subsets of } [d] \text{ of a given size } m; \tag{11}$$

Then Property (P) holds with $\kappa = \kappa(n_{\mathcal{P}}) = \lceil d/m \rceil$ and

$$n_{\mathcal{P}} = \lceil \beta_d / \alpha_d \rceil \cdot \max_{\ell \in [d]} \lceil \alpha_\ell \rceil \tag{12}$$

$$\tau_{\mathcal{P}} = \min_{\text{atoms } \ell \neq \ell' \in [d], \, n,n' \in \{0, n_{\mathcal{P}}\}} |\nu_\ell(n) - \nu_{\ell'}(n')|. \tag{13}$$

$$\rho_{\mathcal{P}} = (1 - \theta_1^0)^{d \cdot n_{\mathcal{P}}}, \tag{14}$$

as long as $\tau_{\mathcal{P}}$ and $\rho_{\mathcal{P}}$ are strictly positive.

Proof Sketch. For each arm V_i, $i \in [\kappa]$ we consider the event that the dataset H_i^n from Property (P) contains the reward of 0 for each samples of each atom. We take n to be large enough so that this event makes all arms $V_1, \ldots, V_{i-1}$ look inferior to V_i, in terms of the posterior mean reward. The key is to lower-bound the probability of this event; a non-trivial step here requires Harris inequality. $\square$

We show that T_0, the requisite number of rounds, depends exponentially on the number of atoms d. To this end, we define a suitable parameterization of the priors. To handle $\tau_{\mathcal{P}}$ in Theorem 4.2, we posit a lower bound that depends on d, but this dependence is very mild.

Corollary 4.3. *Assume (7-8) and (11). Fix some absolute constants $c_0 \in \mathbb{N}$ and $c, c' \in (0,1)$. Suppose the priors satisfy $\max_{\ell,\ell' \in [d]} \lceil \beta_\ell / \alpha_\ell \rceil \cdot \lceil \alpha_{\ell'} \rceil = c_0$ and $\min_{\ell,\ell' \in [d], n,n' \in \{0, c_0\}} (|\nu_\ell(n) - \nu_{\ell'}(n')|) \geq \Omega(c^{-d})$ for all atoms ℓ, ℓ'. Further, the prior mean rewards for all atoms are $\leq c'$. Then there exists a BIC algorithm which samples each atom at least once and completes in*

$$N_0 = O\left(c_0 \, d \cdot \Phi^d \right)$$

rounds, where $\Phi = c \cdot (1 - c')^{-n}$ is a constant.

Finally, we handle general feasible sets, *i.e.,* without assumption (7). The guarantee becomes slightly weaker, in that we have d^2 in the exponent rather than d.

Theorem 4.4. *Assume Beta-Bernoulli priors (7-8). Then Property (P) holds with $\kappa(n_{\mathcal{P}}) \leq d$ and*

$$n_{\mathcal{P}} = \lceil (\alpha_d + \beta_d) / \alpha_d \rceil \cdot \max_{\ell \in [d]} \lceil \alpha_\ell \rceil \cdot d \tag{15}$$

$$\tau_{\mathcal{P}} = \min_{\text{atoms } \ell \neq \ell' \in [d], \, n,n' \in \{0, n_{\mathcal{P}}\}} |\nu_\ell(n) - \nu_{\ell'}(n')|. \tag{16}$$

$$\rho_{\mathcal{P}} = (1 - \theta_1^0)^{d \cdot n_{\mathcal{P}}}, \tag{17}$$

as long as $\tau_{\mathcal{P}}$ and $\rho_{\mathcal{P}}$ are strictly positive.

Corollary 4.5. *Assume (7-8). Fix some absolute constants $c_1 \in \mathbb{N}$ and $c_2, c_3 \in (0,1)$. Suppose the priors satisfy $\max_{\ell, \ell' \in [d]} \lceil (\alpha_\ell + \beta_\ell)/\alpha_\ell \rceil \cdot \lceil \alpha_{\ell'} \rceil \leq c_1$ and $\min_{n, n' \in \{0, c_1 d\}} (|\nu_\ell(n) - \nu_{\ell'}(n')|) \geq \Omega(c_2^{-d^2})$ for all atoms ℓ, ℓ'. Further, the prior mean rewards for all atoms are $\leq c_3$. Then there exists a BIC algorithm which samples each atom at least once and completes in*

$$N_0 = O\left(c_1 \, d^3 \cdot \Phi^{d^2} \right)$$

rounds, where $\Phi = c_2 \cdot (1 - c_3)^{-n}$ is a constant.

4.2 Reduction to incentivized reinforcement learning

Our second algorithm builds on the Hidden Hallucination approach from Simchowitz and Slivkins (2021), which targets incentivized exploration for episodic reinforcement learning. We use this approach by "encoding" a problem instance of combinatorial semi-bandits as a tabular MDP, so that actions in the MDP correspond to atoms, and feasible trajectories correspond to feasible arms. Then we invoke a theorem in Simchowitz and Slivkins (2021) and "translate" this theorem back to combinatorial semi-bandits.

More specifically, consider a tabular MDP with deterministic transitions and unique initial state. Each action in this MDP correspond to some atom ℓ; then the action's reward is drawn from the corresponding reward distribution $\mathcal{D}_\ell$. In general, only a subset of actions is feasible at a given state-stage pair of the MDP. Let G be the transition graph in such MDP: it is a rooted directed graph such that the nodes of G correspond to state-stage pairs in the MDP (the root node corresponding to the initial state and stage 0). Each edge (u, v) in G corresponds to some MDP action feasible at u, *i.e.,* to some atom. While different edges in G can correspond to the same atom, we require that any rooted directed path in G cannot contain two edges that correspond to the same atom. Let A_P be the subset of atoms that corresponds to a given rooted directed path P, and let $\mathcal{A}_G = \{ A_P : \text{rooted directed paths in } G \}$ be the family of arms "encoded" by G. A family of arms $\mathcal{A}$ is called *MDP-encodable* if $\mathcal{A} = \mathcal{A}_G$ for some transition graph G as defined above with $O(d^2)$ nodes.

Our result applies to all MDP-encodable feasible sets. In particular, the set of all subsets of exactly m atoms, for some fixed $m \leq d$, is MDP-encodable. To see this, consider an MDP with m stages and d states, where each state $\ell \in [d]$ corresponds to the largest atom already included in the arm, and actions feasible at a given stage i and state ℓ correspond to all atoms larger than ℓ.

Our result allows for arbitrary per-atom priors $\mathcal{P}_\ell$, subject to a minor non-degeneracy condition, and reward distributions $\mathcal{D}_\ell$ that are supported on the same countable set.

Theorem 4.6. *Consider a feasible arm set $\mathcal{A}$ that is MDP-encodable, as defined above. Suppose the per-atom priors $\mathcal{P}_\ell$ lie in some fixed, finite collection $\mathcal{C}$ such that any $\mathcal{P}_\ell \in \mathcal{C}$ satisfies $\mathbb{P}[\theta_\ell \leq \epsilon] > 0$ for all $\epsilon > 0$ and $\mathbb{E}[\theta_\ell] > 0$. Further, suppose all reward distributions $\mathcal{D}_\ell$ that are supported on the same countable set. Fix parameter $\delta \in (0,1)$. There is a BIC algorithm such that with probability at least $1 - \delta$ each atom is sampled at least once. This algorithm completes in N_0 rounds, where $N_0 = \Phi_{\mathcal{C}}^{-d^3} \cdot O_{\mathcal{C}}\left(\text{poly}(d) \cdot \log(\delta^{-1}) \right)$ for some constant $\Phi_{\mathcal{C}} \in (0,1)$ determined by collection $\mathcal{C}$.*

Remark 4.7. While the guarantee in Theorem 4.4 holds with probability $1 - \delta$, rather than almost surely, it suffices to bootstrap Thompson Sampling in Theorem 3.1. To see this, let `ALG` be an algorithm that runs for $T_0 = N_0 \cdot n_{\texttt{TS}} + d \cdot n_{\texttt{TS}}$ rounds (with $n_{\texttt{TS}}$ from Theorem 3.1), and proceeds as follows: first it repeats the algorithm from Theorem 4.4 $n_{\texttt{TS}}$ times, and in the remaining rounds it deterministically plays an arm with the largest prior mean reward (this algorithm is BIC). Define the "success event" as one in which `ALG` samples each atom $\geq n_{\texttt{TS}}$ times in the first $N_0 \cdot N_{\texttt{TS}}$ rounds. Consider *another* algorithm, `ALG`*, which runs for T_0 rounds, coincides with `ALG` on the first $N_0 \cdot N_{\texttt{TS}}$ rounds, and in the remaining rounds coincides with `ALG` on the success event, and otherwise plays some arms so as to sample each atom at least once (this algorithm is not necessarily BIC). Now, if Thompson Sampling is preceded by `ALG`*, then the analysis in Theorem 3.1 guarantees that each round t of Thompson Sampling satisfies the BIC property (1), and does so with a strictly positive prior-dependent constant on the right hand side of (1). Therefore, the same holds for `ALG`, since it coincides with `ALG`* w.h.p., if the failure probability δ in Theorem 4.4 is chosen small enough.

References

S. Agrawal and N. Goyal. Near-optimal regret bounds for thompson sampling. *J. of the ACM*, 64(5): 30:1–30:24, 2017. Preliminary version in *AISTATS 2013*.

G. Bahar, R. Smorodinsky, and M. Tennenholtz. Economic recommendation systems. In *16th ACM Conf. on Electronic Commerce (ACM-EC)*, 2016.

G. Bahar, R. Smorodinsky, and M. Tennenholtz. Social learning and the innkeeper's challenge. In *ACM Conf. on Economics and Computation (ACM-EC)*, pages 153–170, 2019.

D. Bergemann and S. Morris. Information design: A unified perspective. *Journal of Economic Literature*, 57(1):44–95, March 2019.

K. Bimpikis, Y. Papanastasiou, and N. Savva. Crowdsourcing exploration. *Management Science*, 64 (4):1477–1973, 2018.

M. Castiglioni, A. Celli, A. Marchesi, and N. Gatti. Online bayesian persuasion. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

B. Chen, P. I. Frazier, and D. Kempe. Incentivizing exploration by heterogeneous users. In *Conf. on Learning Theory (COLT)*, pages 798–818, 2018.

W. Chen, Y. Wang, and Y. Yuan. Combinatorial multi-armed bandit: General framework and applications. In *20th Intl. Conf. on Machine Learning (ICML)*, pages 151–159, 2013.

R. Degenne and V. Perchet. Combinatorial semi-bandit with known covariance. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/e816c635cad85a60fabd6b97b03cbcc9-Paper.pdf.

P. Frazier, D. Kempe, J. M. Kleinberg, and R. Kleinberg. Incentivizing exploration. In *ACM Conf. on Economics and Computation (ACM-EC)*, 2014.

A. Gopalan, S. Mannor, and Y. Mansour. Thompson sampling for complex online problems. In *ICML*, 2014.

A. György, T. Linder, G. Lugosi, and G. Ottucsák. The on-line shortest path problem under partial monitoring. *J. of Machine Learning Research (JMLR)*, 8:2369–2403, 2007.

T. E. Harris. A lower bound for the critical probability in a certain percolation process. *Mathematical Proceedings of the Cambridge Philosophical Society*, 56(1):13–20, 1960. doi: 10.1017/S0305004100034241.

N. Immorlica, J. Mao, A. Slivkins, and S. Wu. Incentivizing exploration with selective data disclosure. In *ACM Conf. on Economics and Computation (ACM-EC)*, 2020. Working paper available at https://arxiv.org/abs/1811.06026.

E. Kamenica. Bayesian persuasion and information design. *Annual Review of Economics*, 11(1): 249–272, 2019.

E. Kaufmann, N. Korda, and R. Munos. Thompson sampling: An asymptotically optimal finite-time analysis. In *23rd Intl. Conf. on Algorithmic Learning Theory (ALT)*, pages 199–213, 2012.

I. Kremer, Y. Mansour, and M. Perry. Implementing the "wisdom of the crowd". *J. of Political Economy*, 122(5):988–1012, 2014. Preliminary version in *ACM EC 2013*.

B. Kveton, Z. Wen, A. Ashkan, H. Eydgahi, and B. Eriksson. Matroid bandits: Fast combinatorial optimization with learning. In *13th Conf. on Uncertainty in Artificial Intelligence (UAI)*, pages 420–429, 2014.

B. Kveton, Z. Wen, A. Ashkan, and C. Szepesvári. Tight regret bounds for stochastic combinatorial semi-bandits. In *18th Intl. Conf. on Artificial Intelligence and Statistics (AISTATS)*, 2015.

Y. Mansour, A. Slivkins, and V. Syrgkanis. Bayesian incentive-compatible bandit exploration. *Operations Research*, 68(4):1132–1161, 2020. Preliminary version in *ACM EC 2015*.

Y. Mansour, A. Slivkins, V. Syrgkanis, and S. Wu. Bayesian exploration: Incentivizing exploration in Bayesian games. *Operations Research*, 2022. To appear. Preliminary version in *ACM EC 2016*.

D. Russo and B. Van Roy. Learning to optimize via posterior sampling. *Mathematics of Operations Research*, 39(4):1221–1243, 2014.

D. Russo and B. Van Roy. An information-theoretic analysis of thompson sampling. *J. of Machine Learning Research (JMLR)*, 17:68:1–68:30, 2016.

D. Russo, B. Van Roy, A. Kazerouni, I. Osband, and Z. Wen. A tutorial on thompson sampling. *Foundations and Trends in Machine Learning*, 11(1):1–96, 2018. Published with *Now Publishers* (Boston, MA, USA). Also available at `https://arxiv.org/abs/1707.02038`.

M. Sellke and A. Slivkins. The price of incentivizing exploration: A characterization via thompson sampling and sample complexity. In *22th ACM Conf. on Economics and Computation (ACM-EC)*, 2021.

M. Simchowitz and A. Slivkins. Incentives and exploration in reinforcement learning, 2021. Working paper, available at `https://arxiv.org/abs/2103.00360`.

A. Slivkins. Introduction to multi-armed bandits. *Foundations and Trends® in Machine Learning*, 12(1-2):1–286, Nov. 2019. Published with *Now Publishers* (Boston, MA, USA). Also available at `https://arxiv.org/abs/1904.07272`. Latest online revision: Jan 2022.

W. R. Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3-4):285–294, 1933.

S. Wang and W. Chen. Thompson sampling for combinatorial semi-bandits. In J. Dy and A. Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 5114–5122. PMLR, 10–15 Jul 2018. URL `https://proceedings.mlr.press/v80/wang18a.html`.

Z. Wen, B. Kveton, and A. Ashkan. Efficient learning in large-scale combinatorial semi-bandits. In *32nd Intl. Conf. on Machine Learning (ICML)*, pages 1113–1122, 2015.

Y. Zu, K. Iyer, and H. Xu. Learning to persuade on the fly: Robustness against ignorance. In *ACM Conf. on Economics and Computation (ACM-EC)*, pages 927–928, 2021.