# Affordance-Driven Next-Best-View Planning for Robotic Grasping

**Abstract:** Grasping occluded objects in cluttered environments is an essential component in complex robotic manipulation tasks. In this paper, we, for the first time, introduce an AffordanCE-driven Next-Best-View planning policy (ACE-NBV) that tries to find a feasible grasp for target object via continuously observing scenes from new viewpoints. This policy is motivated by the observation that the grasp affordances of an occluded object can be better-measured under the view when the view-direction are the same as the grasp view. Specifically, our method leverages the novel view imagery ability of the neural radiance field (NeRF) to predict the imagined grasps affordances under previously unobserved view, and select next observation view based on the gain of the highest imagined grasp quality of the target object. The experimental results in simulation and on the real robot demonstrate the effectiveness of the proposed affordance-driven next-best-view planning policy. Additional results, code, and videos of real robot experiments can be found in the supplementary materials.

**Keywords:** Grasp Synthesis, Neural Radiance Fields, Next-Best-View Planning

## 1 Introduction

When we aim to pick up an occluded object from an unstructured environment, observations from a single perspective often fail to provide sufficient affordances information, and we spontaneously move our heads to obtain new perspectives of the occluded object. The driving force behind the actions that lead us to seek the next observation relies on our imagination and spatial reasoning abilities. We know in which direction we can better interact with objects, and we will choose to observe in this direction the next time. However, current intelligent robotic systems are not able to perform these tasks efficiently, and a unified framework for addressing this challenges is lacking. In this work, we aim to investigate the feasibility of endowing robots with this capability.

As shown in Fig. 1, we focus on the task of grasping a specific object in cluttered scenes by a robotic arm with a parallel-jaw gripper. There are relatively mature approaches for predicting grasp poses for unknown objects in cluttered scenes, and most of them first observe the entire scene from one or more fixed viewpoints [1, 2] and predict grasps of all objects at once. However, these methods may fail to predict a feasible grasp for a specific object due to heavy occlusions between objects. In order to design a more stable grasp affordances prediction pipeline, some previous works [3, 4] introduced active perception modules to observe the scene from several new selected viewpoints before executing the grasp. They all select the new observation view directions based on the information gain of object geometry reconstruction. However, the improvement of geometry reconstruction does not always indicate a better grasp quality.

In this paper, as shown in Fig. 1, we build on the intuition that the grasp affordances can be better-measured using the observation when the observation view direction is the same as the grasp view. Based on this insight, we leverage the novel view imagery ability of the neural radiance field to

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

Figure 1: The task of the robotic arm is to grasp the red target object, but the view of its in-hand camera is hindered by a cluttered scene, making it difficult to provide high-quality and collision-free grasping pose predictions. In this study, we draw insight that the grasp affordance of occluded target object can be well-measured when the view-direction are same with grasp view, and propose a framework that plans the next observation based on the increment of grasp affordances to find a feasible grasp on target object.

predict the grasp affordances of imagined novel grasps, and set the next best observation view to the imagined grasp view that yields the highest gain in the grasp quality rather than object geometry reconstruction. Specifically, we first propose a view-aware grasp affordances prediction module to effectively exploit the target object geometry information and occlusion relationships between objects for better grasp synthesis. Then, we adopt the neural radiance field training paradigm to enable our model imagine the scene representation from previously unobserved viewpoints. With this scene imagery ability, we predict the grasp affordances of target object under many imagined views with proposed view-aware grasp affordances prediction module. Last, one next-best-view planning policy is designed to continuously observe the scene from selected new view until finding a feasible grasp on target object. In summary, the contributions of this work are as follows:

- We propose a view-aware grasp affordances prediction module for better grasp synthesis on an occluded target object in cluttered environments.

- We design a next-best-view planning framework that leverages the neural radiance field to jointly predict imagined grasp affordances under unseen views and select next observation view based grasp affordances prediction.

- We demonstrate significant improvements of our model over the state-of-the-art in the clutter grasp task in simulation and on the real robot.

## 2 Related Works

### 2.1 Grasp Detection

Grasping objects is one of the fundamental abilities for robotic manipulators in manipulation tasks. In order to grasp diverse unknown objects in any environment, a robotic system must effectively utilize the geometric information gathered from its sensors to calculate the feasible grasping poses. Recent advances in deep learning methods have led to rapid developments in robot object grasping [5, 6, 7, 8]. A significant portion of these methods do not require object localization and object pose estimation, but instead perform grasp affordances prediction using end-to-end approaches [1, 9]. In particular, Dex-Net [9, 10] adopts a two-step generate-and-evaluate approach for top-down antipodal grasping, and VGN [1] introduced an one-step approach for predicting 6-DoF grasping configurations in cluttered environments. GIGA [2] exploits the synergistic relationships between grasp affordances prediction and 3D reconstruction of scenes in clutter for grasp detection. These works all take fixed single or multiple images as input [1, 2, 9, 11], and the robustness of these methods is largely influenced by the observation camera viewpoints [12]. When dealing with com-

plex environments with strong occlusions, many works [3, 4, 13] try to grasp objects by dynamically moving the observation sensors to obtain additional scene and object geometry information.

## 2.2 Next-Best-View Planning

Next-Best-View (NBV) planning, which aims to recursively plan the next observation position for sensors, is one of the most challenging problems in active vision for robotics [14]. Compared to the passive observation paradigm, active perception with next-best-view planning enables a more flexible way of obtaining environment information. It has been applied in various fields, such as object reconstruction [15, 16, 17], object recognition [18, 19], and grasp detection [3, 4, 13]. NBV planning is typically divided into two categories: synthesis methods and search methods. Synthesis methods directly calculate the next observation position based on current observations and task constraints [20], while search methods first generate a certain number of candidate viewpoints and then select viewpoints based on human-designed criteria. Most search-based approaches use the gain of 3D geometry reconstruction as the metric to select next viewpoints [3, 4, 15]. In particular, Arruda et al. [3] propose a next-best-view planning policy that maximizes object surface reconstruction quality between the object and a given grasp. Breyer et al. [4] design a closed-loop next-best-view planner based volumetric reconstruction of target object. Recent work based on neural radiation fields has also proposed some uncertainty-driven methods [21, 22, 23, 24, 25]. However, for grasp tasks, evaluating viewpoints from grasp affordances is a more direct approach [13]. In this article, we mainly explore how to use grasp affordances information for NBV planning.

## 3 Problem Formulation

We consider the same active grasp problem in [4]: picking up an occluded target object in cluttered scenes using a robotic arm with an eye-in-hand depth camera. As shown in Fig. 2, the target object is partly visible within the initial camera view field and a 3D bounding box is given to locate the target object. Our goal is to design a policy that moves the robotic arm to find a feasible grasp for the target object.

An overview of the whole system is shown in Fig. 2. Given a cluttered scene on a tabletop and an occluded target object $\mathbf{T}$ with corresponding bounding box $\mathbf{T}_{\mathrm{bbox}}$, we aim to predict a feasi-

Figure 2: Overview of the next-best-view planning policy for grasping.

ble 6-DoF grasp $\mathbf{G}$ for the target object $\mathbf{T}$. Specifically, at each time $t$, we obtain the observation $\mathbf{D}_t$ and integrate it into a Truncated Signed Distance Function (TSDF) $\mathbf{M}_t$. Then we predict several possible grasps $\mathbf{G}_1, \mathbf{G}_2, \ldots, \mathbf{G}_N$ for the target object based on current $\mathbf{M}_t$. Next, we use a stopping criterion to determine whether a feasible grasp on the target object has been found. If the stopping criterion is satisfied, we select the grasp of $\mathbf{G}^*$ with the highest predicted quality to execute. Otherwise, our proposed model computes a Next-Best-View $\mathbf{O}_{t+1}$ and moves the robotic arm to this viewpoint to get a new observation $\mathbf{D}_{t+1}$ which will be integrated into $\mathbf{M}_{t+1}$. Then, a set of new grasps are predicted using $\mathbf{M}_{t+1}$. This observe-predict-plan closed-loop policy is continuously running until the stopping criterion is met.

## 4 Method

We now present the AffordanCE-driven Next-Best-View planning policy (ACE-NBV), a learning framework that leverages the novel view synthesis ability of the neural radiance field to predict the grasp affordances for the unseen views and achieve the closed-loop next-best-view planning according to predicted grasp affordances. As shown in Fig. 3, our model is composed of two modules: 1)

Figure 3: Architecture of the proposed ACE-NBV. The input is a TSDF voxel field $\mathbf{M}$ obtained from the depth image. The upper branch predicts the grasp affordances for the target object and the lower branch synthesizes the depth image of the different views, including the previously unseen views. Both branches share the same tri-plane feature volume $\mathbf{C}$.

a view-aware grasp affordances prediction module, and 2) an affordance imagery of unseen novel views module. We discuss these two modules in Sec. 4.1 and Sec. 4.2 respectively, followed by the proposed next-best-view planning policy in Sec. 4.3 and training details in Sec. 4.4.

## 4.1 View-Aware Grasp Affordances Prediction

In this work, we define the grasp affordances in the form of grasp quality $\mathbf{G}_q$, grasp center $\mathbf{G_P} = (x, y, z)$, grasp orientation $\mathbf{G_R} \in SO(3)$, and opening width $\mathbf{G}_w$ of the parallel-jaw gripper. Following the grasp pose representation in [26], we decouple the grasp orientation $\mathbf{G_R}$ as the grasp view $\mathbf{G_v}$ and in-plane rotation $\mathbf{G}_r$. Because of the heavy occlusions in the cluttered scenes, we draw insight that the grasp affordances can be better estimated using the observation whose the view-direction $\mathbf{O_v}$ is the same as grasp view $\mathbf{G_v}$. Motivated by this, we propose a novel view-aware grasp affordances prediction module to predict the in-plane rotation $\mathbf{G}_r$, grasp quality $\mathbf{G}_q$ and gripper width $\mathbf{G}_w$ given a specific grasp center $\mathbf{G_P}$ and grasp direction $\mathbf{G_v}$.

Specifically, given a depth image $\mathbf{D}_t \in \mathbb{R}^{H \times W}$ captured by the depth camera on a robotic arm, we first integrate it into a TSDF $\mathbf{M}_t \in \mathbb{R}^{40 \times 40 \times 40}$, which represents a cubic workspace of size $L$ and can be incrementally updated with the new observed depth images. As shown in Fig. 3, at each time step $t$, our model takes the current TSDF voxel $\mathbf{M}_t$ as input and processes it with a 3D CNN network to obtain a tri-plane feature volume $\mathbf{C} \in \mathbb{R}^{h \times w \times 3}$, which is shared for view-aware grasp affordances prediction and novel view depth synthesis.

For grasp affordances prediction of the occluded target object, we first uniformly sample $N$ points in 3D as grasp centers $\mathbf{G_{P_1}}, \mathbf{G_{P_2}}, ..., \mathbf{G_{P_N}}$ in the given 3D bounding box, and set the current observation view $\mathbf{O_v}$ to grasp view $\mathbf{G_v}$. To predict grasp affordance for a specific grasp center $\mathbf{G_P}$, we cast a ray $\mathbf{r} = (\mathbf{G_P}, \mathbf{v})$ from orthographic cameras [27] origins $\mathbf{o}$ along the direction $\mathbf{v}$ passing through the grasp center $\mathbf{G_P}$. In particular, as shown in Fig. 3, these rays are cast into the tri-plane feature volume $\mathbf{C}$ and $n$ points $\mathbf{S} = \{\mathbf{s}_1, \mathbf{s}_2, ..., \mathbf{s}_n\}$ are uniformly sampled along each ray. Then, we query the local features $\mathbf{C}_{\mathbf{s}_i}$ of these 3D points from the shared tri-plane feature volume, and these local features are integrated together as a ray feature $\mathbf{C}_{\text{ray}}$ via max pooling, i.e.,

$$\mathbf{C}_{\text{ray}} = \text{maxpool}(\mathbf{C}_{\mathbf{s}_1}, \mathbf{C}_{\mathbf{s}_2}, ..., \mathbf{C}_{\mathbf{s}_n}). \tag{1}$$

This ray feature captures the occlusion relationships between objects along the ray direction, which is essential for grasp affordances prediction in cluttered scenes.

In addition, local geometry information around the grasp center is another key factor for grasp affordances prediction on a target object. Therefore, as shown in Fig. 3, we draw a small 3D bounding box along the view-direction $\mathbf{O_v}$ with fixed length and width around grasp center $\mathbf{G_P}$. Then we

obtain the tri-plane features of the eight vertices of this cuboid $\mathbf{C}_{\mathbf{vert}_1}, \mathbf{C}_{\mathbf{vert}_2}, ..., \mathbf{C}_{\mathbf{vert}_8}$ and concatenate these features with the feature of grasp center $\mathbf{C}_{\mathbf{p}_i}$. This concatenated feature is denoted as local geometry feature $\mathbf{C}_{\mathrm{geo}}$, i.e.,

$$\mathbf{C}_{\mathrm{geo}} = \mathrm{concat}(\mathbf{C}_{\mathbf{vert}_1}, \mathbf{C}_{\mathbf{vert}_2}, ..., \mathbf{C}_{\mathbf{vert}_8}, \mathbf{C}_{\mathbf{G_p}}). \tag{2}$$

Based on the above ray feature and local geometry feature, we implement the grasp affordances prediction module as a small fully-connected neural network $f_{\mathbb{G}}$ that takes $\mathbf{G_v}, \mathbf{C}_{\mathrm{ray}}, \mathbf{C}_{\mathrm{geo}}$ as input and outputs the in-plane rotation $\mathbf{G}_r$, grasp quality $\mathbf{G}_q$ and gripper width $\mathbf{G}_w$,

$$f_{\mathbf{G}}(\mathbf{G_v}, \mathbf{C}_{\mathrm{ray}}, \mathbf{C}_{\mathrm{geo}}) \rightarrow \mathbf{G}_r, \mathbf{G}_q, \mathbf{G}_w. \tag{3}$$

In (3), $\mathbf{G_v}$ is a 3-dimensional unit vector that represents view direction, $\mathbf{G}_w \in [0, w_{\max}]$ where $w_{\max}$ is the maximum gripper width, and grasp quality $\mathbf{G}_q \in [0, 1]$.

## 4.2 Affordance Imagery with Neural Radiance Field

Inspired by the impressive performance of neural radiance fields in the new view synthesis, we adopt the same paradigm to enable our model to imagine the scene geometry from previously unobserved viewpoints. With this scene imagery ability, our model can predict reasonable grasp affordances under unseen viewpoints, and the imagined grasp affordances are used for the next-best-view selection. Specifically, as in Fig. 3, we share the same tri-plane feature volume $\mathbf{C}$ for novel view depth synthesis and grasp affordances prediction, and the network is trained with two tasks simultaneously.

First, we build a geometry decoder upon the shared tri-plane feature volume $\mathbf{C}$ for novel view depth synthesis. We implement this geometry decoder as an MLP network that takes local feature $\mathbf{C}_{xyz}$ of a 3D point $\mathbf{p} = (x, y, z)$ as input and predict its signed distance function (SDF) value. Then, we sample $\eta$ depth images $\mathbf{D}_1, \mathbf{D}_2, ..., \mathbf{D}_\eta$ for one scene from different views and select a subset (less than or equal to $\gamma$ depth images) as input to synthesize all $\eta$ depth images via volume rendering in NeuS [28], i.e.,

$$F_{\mathbf{S}}(\mathbf{D}_1, ..., \mathbf{D}_{\leq\gamma}) \rightarrow \mathbf{D}_1, \mathbf{D}_2, ..., \mathbf{D}_\eta, \tag{4}$$

where $F_{\mathbf{S}}$ denotes the whole network branch for novel view depth synthesis. The optimization with (4) makes the shared tri-plane feature volume able to reason scene geometry under unseen viewpoints, which aids us in grasping affordances imagery.

To achieve generalizable grasp affordances imagery, we generate three types of observe-grasp data pairs: front-observe-front-grasp, front-observe-side-grasp, and multi-observe-front-grasp. The front-observe-front-grasp means that our model takes one front view depth image as input and predicts grasp affordances under the same front view. Similarly, the other two types of data pairs represent different input depth images and grasp affordances predictions under different views. Formally, let $(\mathbf{D}_{\mathrm{front}}, \mathbf{G}_{\mathrm{front}}), (\mathbf{D}_{\mathrm{front}}, \mathbf{G}_{\mathrm{side}}), (\mathbb{D}_{\mathrm{multi}}(\mathbf{D}_1, \mathbf{D}_2, ..., \mathbf{D}_\zeta), \mathbf{G}_{\mathrm{front}})$ represent the above three types of data pairs, $F_{\mathbf{G}}$ represent the whole network branch for grasp affordances prediction, the affordances imagery pipeline is formulated as:

$$\begin{aligned} F_{\mathbf{G}}(\mathbf{D}_{\mathrm{front}}) &\rightarrow \mathbf{G}_{\mathrm{front}}, \\ F_{\mathbf{G}}(\mathbf{D}_{\mathrm{front}}) &\rightarrow \mathbf{G}_{\mathrm{side}}, \\ F_{\mathbf{G}}(\mathbb{D}_{\mathrm{multi}}) &\rightarrow \mathbf{G}_{\mathrm{front}}. \end{aligned} \tag{5}$$

## 4.3 Next-Best-View Planning for Grasping

We design a closed-loop next-best-view planning policy $\pi$ to determine the next observation view which is most beneficial for grasping the target object when no feasible grasp is found. Let $\mathbf{G_v}$ be a view from a set of potential next observation views $\mathbb{G_v} \subset SE(3)$, the goal of the our next-best-view planning policy is to find the next observation view $\mathbf{O}_{\mathbf{v}, t+1}$ with the highest predicted grasp quality $\mathbf{G}_q^*$ from a set of imagined grasp affordances for target object, i.e.,

$$\mathbf{O}_{\mathbf{v}, t+1} \leftarrow \underset{\mathbf{G_v} \in \mathbb{G_v}}{\arg\max} \mathbf{G}_q^*(\mathbf{T}_{\mathrm{bbox}}, \mathbf{G_v}). \tag{6}$$

We adopt a methodology similar to that presented in [4] to generate potential next grasping views $\mathbb{G}_\mathbf{v}$, and predict the imagined grasp affordances under these potential views with the above affordances imagery module. In addition, we use two simple stopping criteria to decide whether to stop or to continue to find the next observation view. First, the policy is terminated if the highest grasp quality $\mathbf{G}_q^*$ of currently predicted grasps is above a given threshold $q_{max}$. Second, we impose a maximum number of next-best-view planning steps $T_{max}$. We summarize the overall next-best-view planning policy for grasping as an algorithm in the appendix.

## 4.4 Training

The network is trained end-to-end using ground-truth grasps obtained through simulated trials. The training loss consists of two components: the grasp affordances prediction loss $\mathcal{L}_A$ and the novel view depth synthesis loss $\mathcal{L}_S$. For the grasp affordances prediction loss, we adopt a similar training objective as VGN [1]:

$$\mathcal{L}_A(\mathbf{G}, \hat{\mathbf{G}}) = \mathcal{L}_q(\mathbf{G}_q, \hat{\mathbf{G}}_q) + \mathcal{L}_\mathbf{r}(\mathbf{G}_r, \hat{\mathbf{G}}_\mathbf{r}) + \mathcal{L}_w(\mathbf{G}_w, \hat{\mathbf{G}}_w)). \tag{7}$$

In (7), $\hat{\mathbf{G}}$ represents the ground-truth grasp, and $\mathbf{G}$ represents the predicted grasp. The ground-truth grasp quality is denoted by $\hat{\mathbf{G}}_q$, which takes on a value of 0 (representing failure) or 1 (representing success). The binary cross-entropy loss between the predicted and ground-truth grasp quality is represented by $\mathcal{L}_q$. The cosine similarity between the predicted rotation $\hat{\mathbf{G}}_r$ and the ground-truth rotation $\mathbf{G}_r$ is denoted as $\mathcal{L}_r$, while $\mathcal{L}_w$ represents the $\ell_2$-distance between the predicted gripper width $\hat{\mathbf{G}}_w$ and the ground-truth gripper width $\mathbf{G}_w$. The supervision of the grasp rotation and gripper width is only applied when the grasp is successful ($\hat{\mathbf{G}}_q = 1$).

The geometry loss is calculated using the standard $\ell_1$ loss between the synthesized depth image and the actual depth image, and is denoted by $\mathcal{L}_S$. The final loss $\mathcal{L}$ is obtained by adding the affordances loss and the geometry loss together, i.e., $\mathcal{L} = \mathcal{L}_A + \mathcal{L}_S$.

## 5 Experiments

We evaluate the performance of our algorithm by grasping an occluded target object in simulation and real-world environments. We use a 7-DoF Panda robotic arm from Franka Emika, with a RealSense D435 attached to the end effector. Our algorithm was implemented in Python, using PyTorch for neural network inference and ROS as the hardware interface. We use Open3D [29] for TSDF fusion, and all experiments use TRAC-IK [30] for IK computations, and MoveIt [31] for motion planning and are run on a same computer.

In our experiments, we evaluate the performance of our and compared methods with the following metrics. **Success Rate (SR)**: the proportion of successful grasps. **Failure Rate (FR)**: the proportion of failed grasps. **Abort Rate (AR)**: the proportion of cases where no valid grasp was found even after the maximum number of views was reached. **View-Num.**: the average number of views planned by the algorithm for each round.

We compare the performance of our algorithm with the following baselines: 1) **initial-view**: most work in visual grasp detection considers only a single viewpoint for grasp detection. In this baseline the robot detects a grasp using the initial view. 2) **top-view**: the robot detect grasps from a single top-down image captured on the top of the workspace center, which is typically a common setting for tabletop robotic manipulation. 3) **fixed-trajecotry**: the robot follows a pre-defined trajectory and collects a series of depth image for TSDF fusion and grasp detection. 4) **Breyer's**: the state-of-the-art closed-loop next-best-view policy from [4], using the geometry-based information gain approach to plan next-best-view for target object grasping. All baselines use the same controller described above to generate the robot motion.

## 5.1 Simulated Experiments

As shown in Fig. 4, in simulation environments, we generate simulation scenes in PyBullet [32] using the "packed" approach described in [1] and the object with the smallest amount of visible pixels in initial view is selected as the grasping target. Table 1 shows the results of the 400 experiment trials with each method in simulation environments.

We observe that the success rate of the *initial-view* method is the lowest since the strong occlusion of the target object in initial view leads to a difficult grasp affordance prediction. *Top-view* results in a high success rate because the target can always be grasped from the top in the generated scenes, making it a simple and effective strategy to find feasible grasps. The success rate of the *fixed-trajectory* algorithm is higher than the *initial-view* as it collects more scene information from 4 predefined viewpoints. On the other hand, the state-of-the-art closed-loop next-best-view planning method *Breyer's* achieves superior grasping performance and it requires only a few new observations. Finally, compared to *Breyer's*, our method achieves a comparable success rate with fewer new observations and obtains a significant improvement on the success rate when only one new observation (2-Views SR) is allowed. This indicates that our model can find more informative views for grasping the target object. Moreover, the qualitative results of next-best-view planning of our model is shown in Fig. 4, and the examples verify the effectiveness next-best-view planning ability of our proposed method.

To investigate the influence of different components within our model, we test two variants in Table 1: (i) **ours w/o feature $\mathbf{C}_{\mathbf{geo}}$ and $\mathbf{C}_{\mathbf{ray}}$** where the features $\mathbf{C}_{\mathrm{geo}}$ and $\mathbf{C}_{\mathrm{ray}}$ is replaced with feature $\mathbf{C}_{\mathbf{G_p}}$ of grasp center, and (ii) **ours w/o novel view synthesis branch** that removes the novel view depth synthesis in Sec. 4.2. We find that ours w/o features $\mathbf{C}_{\mathrm{geo}}$ and $\mathbf{C}_{\mathrm{ray}}$ results in significantly worse grasp affordances prediction, and ours w/o novel view synthesis branch needs more observation views to achieve a comparable performance. Moreover, the results of 2-View SR suggests their importance in finding informative views.

Figure 4: The above images illustrate the next-best-view planning in two simulation scenes. Red and blue pixels in the depth images represent randomly sampled grasp candidates, with red indicating successful grasps and blue indicating unsuccessful grasps as predicted by the model.

Table 1: Results from the simulation experiments

| Method | SR | FR | AR | View-Num. | 2-Views SR |
|---|---|---|---|---|---|
| initial-view | 71% | 7% | 22% | 1.00 | N/A |
| top-view | 79% | 6% | 15% | 1.00 | N/A |
| fixed-trajecotry | 77% | 6% | 17% | 4.00 | N/A |
| Breyer's [4] | 81% | 8% | 11% | 4.31 | 77% |
| Our w/o feature $\mathbf{C}_{\mathrm{geo}}$ and $\mathbf{C}_{\mathrm{ray}}$ | 74% | 8% | 18% | 2.54 | 72% |
| Ours w/o novel view synthesis branch | 80% | 10% | 10% | 3.86 | 75% |
| Ours | 83% | 7% | 10% | 2.97 | 80% |

## 5.2 Real Robot Experiments

We test our model with a 7-DoF Panda robotic arm in real-world cluttered scenes shown in Fig. 1. We initialize the robotic arm to a position where the target object is partially visible in the initial view. Note that each scene is tested 10 times with small perturbations in the initial robotic arm position and object locations.

The results from 10 grasping trials are reported in Table 2. Intuitively, the difficulty of scenes 1 to 4 increases gradually, as evidenced by the decreasing number of pixels occupied by objects in the initial view. For easier scenes 1 and 2, our method outperforms the *initial-view* and *fixed-trajectory* baselines and obtains a comparable performance with the state-of-the-art *Breyer's* method. Our algorithm has advantages in much more difficult scenes 3 and 4, where it finds a feasible grasp for the occluded target object with only one or two additional observations. The smaller number of observation views demonstrates the superiority of our model in challenging scenarios. For more results, please refer to the supplementary appendix and videos.

Table 2: Real-world experiments setup and results. The metal plate corresponds to the grasping workspace, and the target object is circled in red.

| Figure | Scene | Method | SR | FR | AR | View-Num. |
|---|---|---|---|---|---|---|
|  | 1 | initial-view | 7/10 | 2/10 | 1/10 | 1.0 |
| | | fixed-trajecotry | 8/10 | 2/10 | 0/10 | 4.0 |
| | | Breyer's [4] | 10/10 | 0/10 | 0/10 | $1.3 \pm 0.5$ |
| | | Ours | 9/10 | 1/10 | 0/10 | $1.8 \pm 0.4$ |
|  | 2 | initial-view | 5/10 | 2/10 | 3/10 | 1.0 |
| | | fixed-trajecotry | 7/10 | 3/10 | 0/10 | 4.0 |
| | | Breyer's [4] | 8/10 | 1/10 | 1/10 | $3.2 \pm 1.6$ |
| | | Ours | 9/10 | 1/10 | 0/10 | $3.5 \pm 1.2$ |
|  | 3 | initial-view | 0/10 | 0/10 | 10/10 | 1.0 |
| | | fixed-trajecotry | 5/10 | 3/10 | 2/10 | 4.0 |
| | | Breyer's [4] | 8/10 | 2/10 | 0/10 | $4.3 \pm 1.5$ |
| | | Ours | 8/10 | 0/10 | 2/10 | $3.2 \pm 0.8$ |
|  | 4 | initial-view | 0/10 | 1/10 | 9/10 | 1.0 |
| | | fixed-trajecotry | 6/10 | 3/10 | 1/10 | 4.0 |
| | | Breyer's [4] | 8/10 | 1/10 | 1/10 | $4.5 \pm 1.0$ |
| | | Ours | 8/10 | 1/10 | 1/10 | $3.3 \pm 0.8$ |

# 6 Conclusion and Limitations

In this paper, we introduce a next-best-view planning framework that leverages the imagined grasp affordances to plan the robotic arm's new observation views for grasping target object in occluded environments. This framework is motivated by the idea that the grasp affordances can be well-predicted when the observation direction is aligned with the grasping direction. Through both simulated and real-world experiments, we demonstrate the effectiveness and robustness of our approach compared to previous works.

**Limitations:** Our next-best-view planning framework involves neural network inference and requires the sampling of multiple views, leading to a high computational cost. In addition, the robotic arm motion planning is not considered in our method, and some unsatisfactory grasp executions exist in real robot experiments. In the future, we plan to integrate motion planning into our method to perform more complex tasks in more challenging environments.

# References

[1] M. Breyer, J. J. Chung, L. Ott, R. Siegwart, and J. Nieto. Volumetric Grasping Network: Real-time 6 DOF Grasp Detection in Clutter. In Proceedings of the 2020 Conference on Robot Learning, pages 1602–1611. PMLR, Oct. 2021.

[2] Z. Jiang, Y. Zhu, M. Svetlik, K. Fang, and Y. Zhu. Synergies Between Affordance and Geometry: 6-DoF Grasp Detection via Implicit Representations. Robotics: science and systems, 2021.

[3] E. Arruda, J. Wyatt, and M. Kopicki. Active Vision for Dexterous Grasping of Novel Objects. In IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), pages 2881–2888, Daejeon, South Korea, Oct. 2016. IEEE. ISBN 978-1-5090-3762-9.

[4] M. Breyer, L. Ott, R. Siegwart, and J. J. Chung. Closed-Loop Next-Best-View Planning for Target-Driven Grasping. In IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), pages 1411–1416, Oct. 2022.

[5] R. Newbury, M. Gu, L. Chumbley, A. Mousavian, C. Eppner, J. Leitner, J. Bohg, A. Morales, T. Asfour, D. Kragic, and others. Deep Learning Approaches to Grasp Synthesis: A Review. arXiv e-prints, pages arXiv–2207, 2022.

[6] G. Du, K. Wang, S. Lian, and K. Zhao. Vision-based Robotic Grasping from Object Localization, Object Pose Estimation to Grasp Estimation for Parallel Grippers: A Review. Artificial Intelligence Review, 54(3):1677–1734, 2021.

[7] A. Mousavian, C. Eppner, and D. Fox. 6-DoF GraspNet: Variational Grasp Generation for Object Manipulation. In Proceedings of the IEEE/CVF International Conference on Computer Vision, pages 2901–2910, 2019.

[8] K. Fang, Y. Zhu, A. Garg, A. Kurenkov, V. Mehta, L. Fei-Fei, and S. Savarese. Learning Task-Oriented Grasping for Tool Manipulation from Simulated Self-Supervision. The International Journal of Robotics Research, 39(2-3):202–216, 2020.

[9] J. Mahler, J. Liang, S. Niyaz, M. Laskey, R. Doan, X. Liu, J. A. Ojea, and K. Goldberg. Dex-net 2.0: Deep Learning to Plan Robust Grasps with Synthetic Point Clouds and Analytic Grasp Metrics. Robotics: Science and Systems (RSS), 2017.

[10] J. Mahler, M. Matl, V. Satish, M. Danielczuk, B. DeRose, S. McKinley, and K. Goldberg. Learning Ambidextrous Robot Grasping Policies. Science Robotics, 4(26):eaau4984, 2019.

[11] M. Sundermeyer, A. Mousavian, R. Triebel, and D. Fox. Contact-GraspNet: Efficient 6-DoF Grasp Generation in Cluttered Scenes. In IEEE International Conference on Robotics and Automation (ICRA), pages 13438–13444. IEEE, 2021.

[12] M. Gualtieri, A. Ten Pas, K. Saenko, and R. Platt. High Precision Grasp Pose Detection in Dense Clutter. In IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), pages 598–605. IEEE, 2016.

[13] D. Morrison, P. Corke, and J. Leitner. Multi-View Picking: Next-best-view Reaching for Improved Grasping in Clutter. In International Conference on Robotics and Automation (ICRA), pages 8762–8768, 2019.

[14] R. Zeng, Y. Wen, W. Zhao, and Y.-J. Liu. View Planning in Robot Active Vision: A Survey of Systems, Algorithms, and Applications. Computational Visual Media, 6(3):225–245, Sept. 2020. ISSN 2096-0433, 2096-0662.

[15] J. Delmerico, S. Isler, R. Sabzevari, and D. Scaramuzza. A Comparison of Volumetric Information Gain Metrics for Active 3D Object Reconstruction. Autonomous Robots, 42(2):197–208, 2018.

[16] S. Kriegel, C. Rink, T. Bodenmüller, and M. Suppa. Efficient Next-best-scan Planning for Autonomous 3D Surface Reconstruction of Unknown Objects. Journal of Real-Time Image Processing, 10:611–631, 2015.

[17] W. R. Scott, G. Roth, and J.-F. Rivest. View Planning for Automated Three-dimensional Object Reconstruction and Inspection. ACM Computing Surveys (CSUR), 35(1):64–96, 2003.

[18] S. A. Hutchinson, R. L. Cromwell, and A. C. Kak. Planning Sensing Strategies in a Robot Work Cell with Multi-sensor Capabilities. In Proceedings. 1988 IEEE International Conference on Robotics and Automation, pages 1068–1075. IEEE, 1988.

[19] E. Johns, S. Leutenegger, and A. J. Davison. Pairwise Decomposition of Image Sequences for Active Multi-View Recognition. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, pages 3813–3822, 2016.

[20] M. Mendoza, J. I. Vasquez-Gomez, H. Taud, L. E. Sucar, and C. Reta. Supervised Learning of the Next-Best-View for 3D Object Reconstruction. Pattern Recognition Letters, 133:224–231, May 2020. ISSN 01678655.

[21] S. Lee, L. Chen, J. Wang, A. Liniger, S. Kumar, and F. Yu. Uncertainty Guided Policy for Active Robotic 3D Reconstruction using Neural Radiance Fields. IEEE Robotics and Automation Letters, 7(4):12070–12077, 2022.

[22] E. J. Smith, M. Drozdzal, D. Nowrouzezahrai, D. Meger, and A. Romero-Soriano. Uncertainty-Driven Active Vision for Implicit Scene Reconstruction. arXiv preprint arXiv:2210.00978, 2022.

[23] L. Jin, X. Chen, J. Rückin, and M. Popović. NeU-NBV: Next Best View Planning Using Uncertainty Estimation in Image-Based Neural Rendering. arXiv preprint arXiv:2303.01284, 2023.

[24] K. Lin and B. Yi. Active View Planning for Radiance Fields. In Robotics Science and Systems, 2022.

[25] X. Pan, Z. Lai, S. Song, and G. Huang. ActiveNeRF: Learning where to See with Uncertainty Estimation. In ECCV 2022: 17th European Conference, Oct. 2022, Proceedings, Part XXXIII, pages 230–246. Springer, 2022.

[26] H.-S. Fang, C. Wang, M. Gou, and C. Lu. GraspNet-1Billion: A Large-Scale Benchmark for General Object Grasping. In 2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 11441–11450. IEEE, June 2020. ISBN 978-1-72817-168-5.

[27] Y.-C. Lin, P. Florence, A. Zeng, J. T. Barron, Y. Du, W.-C. Ma, A. Simeonov, A. R. Garcia, and P. Isola. MIRA: Mental Imagery for Robotic Affordances. In Conference on Robot Learning, pages 1916–1927. PMLR, 2023.

[28] P. Wang, L. Liu, Y. Liu, C. Theobalt, T. Komura, and W. Wang. NeuS: Learning Neural Implicit Surfaces by Volume Rendering for Multi-view Reconstruction. In Advances in Neural Information Processing Systems, 2021.

[29] Q.-Y. Zhou, J. Park, and V. Koltun. Open3D: A Modern Library for 3D Data Processing. arXiv preprint arXiv:1801.09847, 2018.

[30] P. Beeson and B. Ames. TRAC-IK: An Open-source Library for Improved Solving of Generic Inverse Kinematics. In IEEE-RAS 15th International Conference on Humanoid Robots (Humanoids), pages 928–935. IEEE, 2015.

[31] S. Chitta, I. Sucan, and S. Cousins. Moveit![ros topics]. IEEE Robotics & Automation Magazine, 19(1):18–19, 2012.

[32] E. Coumans and Y. Bai. Pybullet, a Python Module for Physics Simulation for Games, Robotics and Machine Learning. 2016.