ADAPTIVE-SATURATED RNN:
REMEMBER MORE WITH LESS INSTABILITY

ABSTRACT

Orthogonal parameterization has offered a compelling solution to the vanishing gradient problem (VGP) in recurrent neural networks (RNNs). Thanks to orthogonal parameters and non-saturated activation functions, gradients in such models are constrained to unit norms. On the other hand, although the traditional vanilla RNN have been observed to possess higher memory capacity, they suffer from the VGP and perform badly in many applications. This work connects the aforementioned approaches by proposing Adaptive-Saturated RNNs (asRNN), a variant that dynamically adjusts the saturation level between the two. Consequently, asRNN enjoys both the capacity of a vanilla RNN and the training stability of orthogonal RNNs. Our experiments show encouraging results of asRNN on challenging sequence learning benchmarks compared to several strong competitors. We will make the implementation publicly available upon acceptance.

1 MOTIVATION

RNNs is an important model class in Artificial Intelligence (Hyötyniemi, 1996). However, training a vanilla RNN (with tanh activation) is notoriously challenging due to the VGP, in which gradients' magnitudes become *exponentially* smaller (Zhao et al., 2020; Collins et al., 2017). Thus, extensive efforts have been devoted to this phenomenon to develop more stable, effective models such as orthogonal RNNs (Lezcano-Casado & Martínez-Rubio, 2019), and LSTM (Hochreiter & Schmidhuber, 1997). Empirically, orthogonal RNNs show more competitive performances compared to LSTM and vanilla RNN on long-sequence tasks. However, due to non-saturated activations and unitary constrain, their memory capacity is also more limited compared to vanilla RNN (Collins et al., 2017).

This study aims to realize the memory capacity potential of vanilla RNNs by endowing them with the capability to address the VGP of orthogonal RNNs. As a result, we propose the *adaptive-saturated RNN* (asRNN), a vanilla RNN variant that dynamically adjusts the activation's saturation level. Particularly, we observe that, let $f(x; a) = \frac{\tanh(ax)}{a}$, then:

$$\lim_{a \to 0} f(x; a) = x, \quad \text{and} \quad \lim_{a \to 1} f(x; a) = \tanh(x). \tag{1}$$

By adjusting a and updating parameters with more freedom than an orthogonal RNN, it is possible to have high memory capacity without being affected by the VGP, thereby maintaining high training stability. Therefore, we can generalize and use $f(x; a)$ as an activation function, which let us to further control gradient norms. Remarkably, adjusting a also relieves the exploding gradient problem (EGP), which is achievable with gradient clipping (Appendix A.4.1). In the next section, we formally introduce asRNN and outline a key result of a condition for avoiding the VGP in asRNN. Finally, we demonstrate asRNN's promising performance on challenging sequence learning problems against several strong competitors.

2 METHODOLOGY

Formulation Based on the observation Eq. 1, we formally define the hidden cell of asRNN as:

$$h_t = \boldsymbol{W}_f^{-1}\tanh(\boldsymbol{W}_f(\boldsymbol{W}_{xh}\boldsymbol{x}_t + \boldsymbol{W}_{hh}\boldsymbol{h}_{t-1} + \boldsymbol{b})), \tag{2}$$

where $\mathcal{W} = \{\boldsymbol{W}_f, \boldsymbol{W}_{xh}, \boldsymbol{W}_{hh}, \boldsymbol{b}\}$ is the set of trainable parameters, $\boldsymbol{W}_f$ introduces an end-to-end composite layer to control the saturation level of asRNN. To ensure the non-singularity of $\boldsymbol{W}_f$,

| (a) Copy task ($L = 2000$) | (b) Sequential MNIST | (c) Permuted MNIST |

Figure 1: Results on the long sequence learning task. We report training loss for the Copy task and test errors for the sequential and permuted MNIST.

we parameterize $\boldsymbol{W}_f = \boldsymbol{U}_f \boldsymbol{D}_f$, where $\boldsymbol{U}_f$ is orthogonal, $\boldsymbol{D}_f$ is positively diagonal. Remarkably, we observe that: (i) by fixing $\boldsymbol{W}_f$ to be identity, we recover a vanilla RNN; and (ii) let $\boldsymbol{W}_{hh}$ be orthogonal, fix $\boldsymbol{U}_f$ to be the identity, and let $\boldsymbol{D}_f \to \mathbb{0}$, we recover an orthogonal RNN. From such construction, asRNN not only dynamically adjusts the saturation level but also controls the singular values of the temporal Jacobian (Thm. 2.1), which in turn alleviates the VGP.

Key theoretical result Let $\boldsymbol{w} \in \mathcal{W}$, we define the gradient and Jacobian as (Pascanu et al., 2012): $\frac{\partial \mathcal{L}}{\partial \boldsymbol{w}} = \sum_{1 \le t_1 \le T} \frac{\partial \mathcal{L}}{\partial \boldsymbol{h}_T} \boldsymbol{J}(T, t_1) \frac{\partial \boldsymbol{h}_{t_1}}{\partial \theta}$, where $\boldsymbol{J}(t_2, t_1) = \prod_{t_1 < t \le t_2} \boldsymbol{J}(t)$ and $\boldsymbol{J}(t) = \boldsymbol{W}_f^{-1} \text{diag}[1 - (\boldsymbol{W}_f \boldsymbol{h}_t)^2] \bar{\boldsymbol{W}}_f \boldsymbol{W}_{hh}$. The vanishing gradient problem in RNNs is credited to the existence of a temporal Jacobian $\boldsymbol{J}(t_2, t_1) \approx 0$ that bottlenecks the backpropagated signal. Under mild assumptions (Appendix A.2), we show a condition for asRNN where all singular values of temporal Jacobian matrices are lower bounded by 1. Thanks to this, the VGP is alleviated on vanilla RNN.

Theorem 2.1. *Let G and H be respectively the d_h-th degree generalized permutation group and its signed permutation subgroup. Under the assumptions in Appendix A.2, if $||\boldsymbol{D}_f||_2 \le \frac{arctanh(\sqrt{1-||\boldsymbol{W}_{hh}^{-1}||_2})}{(||\boldsymbol{W}_{xh}||_2 C_x + ||\boldsymbol{b}||_\infty) \sum_{i=0}^{t-1}(||\boldsymbol{W}_{hh}||_{max}+1)^i}$ and $\min_{\boldsymbol{E} \in G} ||\boldsymbol{W}_{hh} - \boldsymbol{E}||_2 \le \frac{\sigma_{min}(\boldsymbol{D}_f)}{||\boldsymbol{D}_f||_2}$, then*

$$\exists \epsilon \ge 0 : \min_{\boldsymbol{E} \in H} ||\boldsymbol{U}_f - \boldsymbol{E}||_2 \le \epsilon \to \forall t_2 > t_1 \in \mathbb{N}^* : \sigma_{min}(\boldsymbol{J}(t_2, t_1)) \ge 1.$$

Importantly, Zhao et al. (2020) conjectured and showed a scenario where RNNs and LSTM have short-term memories, a problem associated with the VGP. Thm. 2.1 shows another where vanilla RNN does not exhibit the VGP. Hence, the conjecture of Zhao et al. (2020) is suggested to be false.

3 EXPERIMENT

To validate the model's memory capacity, we consider the Copy task(Hochreiter & Schmidhuber, 1997), sequential MNIST(LeCun et al., 1998), and permuted MNIST(Goodfellow et al., 2014). Next, we use the Penn Treebank character-level prediction (PTB-c)(Marcus et al., 1993) task to explore the model's expressivity (Kerg et al., 2019; Bojanowski et al., 2016). We benchmark asRNN against the strong orthogonal RNNs with long memories and high trainability such as expRNN(Lezcano-Casado & Martínez-Rubio, 2019), scoRNN(Helfrich et al., 2018), uRNN(Arjovsky et al., 2016), and the popular LSTM(Hochreiter & Schmidhuber, 1997) with high expressivity from the gated mechanism. We follow the setting described in Appendix A.4

Model	$T = 150$	$T = 300$
LSTM	$\mathbf{1.41 \pm 0.005}$	$\mathbf{1.43 \pm 0.004}$
asRNN	1.46 ± 0.006	1.49 ± 0.005
nnRNN	1.47 ± 0.003	1.49 ± 0.002
expRNN	1.49 ± 0.008	1.52 ± 0.001
EURNN	1.61 ± 0.001	1.62 ± 0.001
RNN-orth	1.62 ± 0.004	1.66 ± 0.006
RNN	2.89 ± 0.002	2.90 ± 0.002

Table 1: Test bit-per-character at PTB-c. The best results are in bold. T denotes the BPTT length.

and report the results in Fig. 1 and Tab. 1. On long sequence learning tasks (Fig. 1), our asRNN shows excellent performance by converging stably on the Copy task, and achieves better generalization on the sequential and permuted MNIST tasks. On the PTB task, asRNN achieved encouraging results by outperforming all orthogonal RNN baselines, only second to LSTM. Overall, our empirical results

show that asRNN possesses both high memory capacity and expressivity compared to other non-gated RNNs and can alleviate the EVGP, which corroborates our motivation in Sec. 1.

URM STATEMENT

The authors acknowledge that at least one key author of this work meets the URM criteria of the ICLR 2023 Tiny Papers Track.

REFERENCES

Martin Arjovsky, Amar Shah, and Yoshua Bengio. Unitary evolution recurrent neural networks. In Maria Florina Balcan and Kilian Q. Weinberger (eds.), *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pp. 1120–1128, New York, New York, USA, 20–22 Jun 2016. PMLR. URL https://proceedings.mlr.press/v48/arjovsky16.html.

Piotr Bojanowski, Armand Joulin, and Tomas Mikolov. Alternative structures for character-level rnns. *4th International Conference on Learning Representations*, Workshop track, 2016.

Jasmine Collins, Jascha Sohl-Dickstein, and David Sussillo. Capacity and trainability in recurrent neural networks. In *International Conference on Learning Representations*, 2017. URL https://openreview.net/forum?id=BydARw9ex.

Jensen Jinhui Wang David Kewei Lin. uRNN: An Approach to Bounded Gradients. *Stanford*, CS224n: Natural Language Processing with Deep Learning, 2019. URL https://web.stanford.edu/class/archive/cs/cs224n/cs224n.1194/reports/custom/15842215.pdf.

Ian J. Goodfellow, Mehdi Mirza, Xia Da, Aaron C. Courville, and Yoshua Bengio. An empirical investigation of catastrophic forgeting in gradient-based neural networks. In Yoshua Bengio and Yann LeCun (eds.), *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014. URL http://arxiv.org/abs/1312.6211.

Kyle Helfrich, Devin Willmott, and Qiang Ye. Orthogonal recurrent neural networks with scaled Cayley transform. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1969–1978. PMLR, 10–15 Jul 2018. URL https://proceedings.mlr.press/v80/helfrich18a.html.

Mikael Henaff, Arthur Szlam, and Yann LeCun. Recurrent orthogonal networks and long-memory tasks. In *Proceedings of the 33rd International Conference on International Conference on Machine Learning - Volume 48*, ICML'16, pp. 2034–2042. JMLR.org, 2016.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Comput.*, 9(8): 1735–1780, nov 1997. ISSN 0899-7667. doi: 10.1162/neco.1997.9.8.1735. URL https://doi.org/10.1162/neco.1997.9.8.1735.

Heikki Hyötyniemi. Turing machines are recurrent neural networks. *Proceedings of step*, 96, 1996.

Li Jing, Yichen Shen, Tena Dubcek, John Peurifoy, Scott Skirlo, Yann LeCun, Max Tegmark, and Marin Soljačić. Tunable efficient unitary neural networks (eunn) and their application to rnns. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, pp. 1733–1741. JMLR.org, 2017.

Giancarlo Kerg, Kyle Goyette, Maximilian Puelma Touzel, Gauthier Gidel, Eugene Vorontsov, Yoshua Bengio, and Guillaume Lajoie. Non-normal recurrent neural network (nnrnn): learning long time dependencies while improving expressivity with transient dynamics. *Advances in neural information processing systems*, 32, 2019.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

106 Mario Lezcano-Casado and David Martínez-Rubio. Cheap orthogonal constraints in neural networks:
107   A simple parametrization of the orthogonal and unitary group. In Kamalika Chaudhuri and Ruslan
108   Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*,
109   volume 97 of *Proceedings of Machine Learning Research*, pp. 3794–3803. PMLR, 09–15 Jun
110   2019. URL `https://proceedings.mlr.press/v97/lezcano-casado19a.html`.

111 Mitchell P. Marcus, Beatrice Santorini, and Mary Ann Marcinkiewicz. Building a large annotated
112   corpus of English: The Penn Treebank. *Computational Linguistics*, 19(2):313–330, 1993. URL
113   `https://aclanthology.org/J93-2004`.

114 Razvan Pascanu, Tomas Mikolov, and Yoshua Bengio. On the difficulty of training recurrent neural
115   networks. In *International Conference on Machine Learning*, 2012.

116 Jingyu Zhao, Feiqing Huang, Jia Lv, Yanjie Duan, Zhen Qin, Guodong Li, and Guangjian Tian.
117   Do RNN and LSTM have long memory? In Hal Daumé III and Aarti Singh (eds.), *Pro-*
118   *ceedings of the 37th International Conference on Machine Learning*, volume 119 of *Pro-*
119   *ceedings of Machine Learning Research*, pp. 11365–11375. PMLR, 13–18 Jul 2020. URL
120   `https://proceedings.mlr.press/v119/zhao20c.html`.

A   Appendix

A.1   Related work

Long short-term memory. A dominant approach in preventing the exploding and vanishing gradient problem in RNN is with gated mechanisms, such as LSTM (Hochreiter & Schmidhuber, 1997). This model is easily trained and gives good performance on a variety of sequence learning tasks. Despite the fact that LSTM has a lower memory capacity compared to vanilla RNN (Collins et al., 2017), and that it performs badly on long-memory tasks (Helfrich et al., 2018), we include this model for its high effectiveness in language modeling, where the decisive factor is expressivity such as mechanism or hidden size (Bojanowski et al., 2016).

Orthogonal RNN. This class of models addressed the VGP with non-saturated activation functions (e.g. modReLU) and a unitary hidden weight matrix. To constrain the unitarity during gradient descent, scoRNN followed a scaled Cayley transformation, while uRNN and EURNN used pre-selected unitary transformation compositions (Helfrich et al., 2018; Arjovsky et al., 2016; Jing et al., 2017). To compensate for the expressivity loss, expRNN proposed to use the computationally cheap exponential map stemming from Lie group theory (Lezcano-Casado & Martínez-Rubio, 2019). As a result, the gradients grow only *linearly* in sequence length. There is also an initialization scheme proposed for this class to directly solve many long sequence learning tasks (Henaff et al., 2016).

Non-normal RNN. Despite having high trainability, being unitary limits the expressivity of Orthogonal RNNs compared to their free parameters counterparts. Non-normal RNN, which leverages Schur decomposition to acquire non-unit eigenvalues, is proposed to overcome this problem while maintaining the trainability of Orthogonal RNNs (Kerg et al., 2019). Consequently, nnRNN outperforms Orthogonal RNNs on both long sequence learning tasks and language modeling tasks.

A.2   Assumptions

Assumption A.1. *(scale-independent loss) it is* **not** $\forall \epsilon > 0, \exists \delta > 0 : \mathcal{L}(\boldsymbol{y}, \hat{\boldsymbol{y}}) < \epsilon \rightarrow ||\boldsymbol{y} - \hat{\boldsymbol{y}}||_2 < \delta$.

Assumption A.1 prevents the convergence from closing the gap between $||\hat{\boldsymbol{y}}||_2$ and $||\boldsymbol{y}||_2$ by re-scaling the output layer with a factor of $||\boldsymbol{D}_f||_2$, which potentially causes the VGP. As a remark, it is possible to reduce this effect on scale-dependent loss with $\mathcal{L}(\delta^{-1}\boldsymbol{y}, \hat{\boldsymbol{y}})$, for some small hyperparameter $\delta > 0$. We leave this for consecutive works.

Assumption A.2. *(bounded input distribution)* $\exists C_x > 0, \forall t : ||\boldsymbol{x}_t||_\infty \leq C_x$.

In practice, it is common to normalize input with $C_x = 1$ before training neural network-based architectures. Assumption A.2 prevents the absurdity of an infinitely large input saturating asRNN and causing the VGP.

Assumption A.3. *(no nil-potent singular value)* $\sigma_{\min}(\boldsymbol{W}_{hh}) \geq 1$.

Even though Assumption A.3 is required for Theorem 2.1, we observe that it might be unnecessary to prevent the VGP in practice. By relaxing the Theorem 2.1 to the dominant eigenvalue, we might be able to relax Assumption A.3. We leave this for consecutive works.

A.3 PROOF OF THEOREM 2.1

Lemma A.1. *David Kewei Lin (2019) For a diagonal matrix $\boldsymbol{D}$ and a conformable matrix $\boldsymbol{A}$, we have $||\boldsymbol{D}\boldsymbol{A}||_2 \leq ||\boldsymbol{D}||_{\max}||\boldsymbol{A}||_2$.*

Lemma A.2. *Let G and H be respectively the d_h-th degree generalized permutation group and its signed permutation subgroup. Under the assumptions in Appendix A.2, if $||\boldsymbol{D}_f||_2 \leq$*

$$\frac{arctanh\left(\sqrt{1 - ||\boldsymbol{W}_{hh}^{-1}||_2}\right)}{(||\boldsymbol{W}_{xh}||_2 C_x + ||\boldsymbol{b}||_\infty)\sum_{i=0}^{t-1}(||\boldsymbol{W}_{hh}||_{\max} + 1)^i} \text{ and } \min_{\boldsymbol{E}\in G}||\boldsymbol{W}_{hh} - \boldsymbol{E}||_2 \leq \frac{\sigma_{\min}(\boldsymbol{D}_f)}{||\boldsymbol{D}_f||_2}, \text{ then}$$

$$\exists \epsilon(t) \geq 0 : \min_{\boldsymbol{E}\in H}||\boldsymbol{U}_f - \boldsymbol{E}||_2 \leq \epsilon(t) \to \forall t \in \mathbb{N}^* : \sigma_{\min}(\boldsymbol{J}(t)) \geq 1.$$

Proof. Let $\boldsymbol{E}_{hh} = \underset{\boldsymbol{E}\in G}{\arg\min} ||\boldsymbol{W}_{hh} - \boldsymbol{E}||_2$ and $\boldsymbol{R}_{hh} = \boldsymbol{W}_{hh} - \boldsymbol{E}_{hh}$. First we show that $||\boldsymbol{W}_f\boldsymbol{h}_t||_\infty$ is bounded:

$$||\boldsymbol{W}_f\boldsymbol{h}_t||_\infty = ||\tanh\left(\boldsymbol{W}_f\left(\boldsymbol{W}_{xh}\boldsymbol{x}_t + \boldsymbol{W}_{hh}\boldsymbol{h}_{t-1} + \boldsymbol{b}\right)\right)||_\infty \tag{3}$$

$$= \tanh\left(||\boldsymbol{W}_f\left(\boldsymbol{W}_{xh}\boldsymbol{x}_t + \boldsymbol{W}_{hh}\boldsymbol{h}_{t-1} + \boldsymbol{b}\right)||_\infty\right) \tag{4}$$

$$\leq \tanh\left(||\boldsymbol{W}_f\boldsymbol{W}_{xh}\boldsymbol{x}_t||_\infty + ||\boldsymbol{W}_f\boldsymbol{W}_{hh}\boldsymbol{h}_{t-1}||_\infty + ||\boldsymbol{W}_f\boldsymbol{b}||_\infty\right) \tag{5}$$

$$\leq \tanh\left(||\boldsymbol{D}_f||_2\left(||\boldsymbol{W}_{xh}||_2 C_x + ||\boldsymbol{b}||_\infty\right) + ||\boldsymbol{D}_f\boldsymbol{W}_{hh}\boldsymbol{D}_f^{-1}||_2||\boldsymbol{W}_f\boldsymbol{h}_{t-1}||_\infty\right) \tag{6}$$

$$\leq \tanh\left(||\boldsymbol{D}_f||_2\left(||\boldsymbol{W}_{xh}||_2 C_x + ||\boldsymbol{b}||_\infty\right)\sum_{i=0}^{t-1}||\boldsymbol{D}_f(\boldsymbol{E}_{hh} + \boldsymbol{R}_{hh})\boldsymbol{D}_f^{-1}||_2^i\right) \tag{7}$$

$$\leq \tanh\left(||\boldsymbol{D}_f||_2\left(||\boldsymbol{W}_{xh}||_2 C_x + ||\boldsymbol{b}||_\infty\right)\sum_{i=0}^{t-1}\left(||\boldsymbol{W}_{hh}||_{\max} + \frac{||\boldsymbol{R}_{hh}||_2||\boldsymbol{D}_f||_2}{\sigma_{\min}(\boldsymbol{D}_f)}\right)^i\right) \tag{8}$$

$$\leq \tanh\left(||\boldsymbol{D}_f||_2\left(||\boldsymbol{W}_{xh}||_2 C_x + ||\boldsymbol{b}||_\infty\right)\sum_{i=0}^{t-1}\left(||\boldsymbol{W}_{hh}||_{\max} + 1\right)^i\right) \tag{9}$$

$$\leq 1 - \frac{1}{\sigma_{\min}(\boldsymbol{W}_{hh})} \tag{10}$$

Let $\boldsymbol{E}_f = \underset{\boldsymbol{E}\in H}{\arg\min} ||\boldsymbol{U}_f - \boldsymbol{E}||_2, \boldsymbol{R}_f = \boldsymbol{U}_f - \boldsymbol{E}_f, \boldsymbol{D}_t = \mathrm{diag}[1 - (\boldsymbol{W}_f\boldsymbol{h}_t)^2]$. Then

$$\sigma_{min}(\boldsymbol{J}(t)) = \sigma_{\min}\left(\boldsymbol{D}_f^{-1}\boldsymbol{U}_f^\mathsf{T}\mathrm{diag}\boldsymbol{D}_t\boldsymbol{U}_f\boldsymbol{D}_f\boldsymbol{W}_{hh}\right) \tag{11}$$

$$\geq \sigma_{\min}\left(\boldsymbol{D}_f^{-1}\left(\boldsymbol{R}_f^\mathsf{T} + \boldsymbol{E}_f^\mathsf{T}\right)\boldsymbol{D}_t\left(\boldsymbol{R}_f + \boldsymbol{E}_f\right)\boldsymbol{D}_f\right)\sigma_{\min}(\boldsymbol{W}_{hh}) \tag{12}$$

$$\geq \left(\sigma_{\min}\left(\boldsymbol{D}_f^{-1}\boldsymbol{E}_f^\mathsf{T}\boldsymbol{D}_t\boldsymbol{E}_f\boldsymbol{D}_f\right) - ||\boldsymbol{D}_f^{-1}\left(\boldsymbol{E}_f^\mathsf{T}\boldsymbol{D}_t\boldsymbol{R}_f + \boldsymbol{R}_f^\mathsf{T}\boldsymbol{D}_t\boldsymbol{E}_f +\right.\right.$$

$$\left.\left.\boldsymbol{R}_f^\mathsf{T}\boldsymbol{D}_t\boldsymbol{R}_f\right)\boldsymbol{D}_f||_2\right)\sigma_{\min}(\boldsymbol{W}_{hh}) \tag{13}$$

$$\geq \left(1 - \max_i(\boldsymbol{W}_f\boldsymbol{h}_t)_i^2 - \frac{||\boldsymbol{D}_f||_2^2}{\sigma_{\min}(\boldsymbol{D}_f)}\left(2||\boldsymbol{R}_f||_2 + ||\boldsymbol{R}_f||_2^2\right)\right)\sigma_{\min}(\boldsymbol{W}_{hh}) \tag{14}$$

$$\geq \left(\frac{1}{\sigma_{\min}(\boldsymbol{W}_{hh})} - \frac{||\boldsymbol{D}_f||_2^2}{\sigma_{\min}(\boldsymbol{D}_f)}||\boldsymbol{R}_f||_2\right)\sigma_{\min}(\boldsymbol{W}_{hh}) \tag{15}$$

The rest of the proof follows directly from the previous inequality. $\square$

Theorem 2.1. *Let G and H be respectively the d_h-th degree generalized permutation group and its signed permutation subgroup. Under the assumptions in Appendix A.2, if $||\boldsymbol{D}_f||_2 \leq \frac{arctanh(\sqrt{1-||\boldsymbol{W}_{hh}^{-1}||_2})}{(||\boldsymbol{W}_{xh}||_2 C_x + ||\boldsymbol{b}||_\infty) \sum_{i=0}^{t-1}(||\boldsymbol{W}_{hh}||_{\max}+1)^i}$ and $\min_{\boldsymbol{E} \in G} ||\boldsymbol{W}_{hh} - \boldsymbol{E}||_2 \leq \frac{\sigma_{\min}(\boldsymbol{D}_f)}{||\boldsymbol{D}_f||_2}$, then*

$$\exists \epsilon \geq 0 : \min_{\boldsymbol{E} \in H} ||\boldsymbol{U}_f - \boldsymbol{E}||_2 \leq \epsilon \to \forall t_2 > t_1 \in \mathbb{N}^* : \sigma_{\min}(\boldsymbol{J}(t_2, t_1)) \geq 1.$$

Proof. From Lemma A.1 and Lemma A.2, if $\epsilon = \min_t \epsilon(t)$, then $||\boldsymbol{U}_f - \boldsymbol{E}||_2 \leq \epsilon \to \forall t_2 > t_1 \in \mathbb{N}^* : \sigma_{\min}(\boldsymbol{J}(t_2, t_1)) \geq 1$ $\qquad \square$

A.4 EXPERIMENTAL SUPPLEMENTARY

Figure 2: Copy task ($L = 1000$).

Model	T=150	T=300
LSTM	**69.81 ± 0.001**	**69.60 ± 0.0003**
asRNN	68.93 ± 0.001	68.59 ± 0.001
nnRNN	68.78 ± 0.001	68.52 ± 0.0004
expRNN	68.07 ± 0.15	67.58 ± 0.04
RNN-orth	66.29 ± 0.07	65.53 ± 0.09
EURNN	65.68 ± 0.002	65.55 ± 0.002
RNN	40.01 ± 0.026	39.97 ± 0.025

Table 2: Test accuracy at PTB-c. The best results are in bold. T denotes the BPTT length.

A.4.1 COMMON SETTING

The batch size across all experiments was 128. Unless specified otherwise, asRNN is optimized using RMSprop with $\alpha = 0.99$. We report the best results on a similar setup to ours in Jing et al. (2017), Arjovsky et al. (2016), Helfrich et al. (2018), Lezcano-Casado & Martínez-Rubio (2019), and Kerg et al. (2019). For other experiments, we replicate the same setup of Lezcano-Casado & Martínez-Rubio (2019) (copy memory and pixelated MNIST), and of Kerg et al. (2019) (Penn Treebank character-level prediction).

Since no advantage was observed when $\boldsymbol{W}_{hh}$ is updated freely during preliminary empirical testing, this layer is kept strictly orthogonal for the maximum memory-per-parameter capacity. As a result, both $\boldsymbol{U}_f$ and $\boldsymbol{W}_{hh}$ are parameterized as described in Lezcano-Casado & Martínez-Rubio (2019). The diagonal matrix is parameterized as $\boldsymbol{D}_f = \text{diag}(\boldsymbol{d}_f)$, where $\boldsymbol{d}_{f_i} = |s_i| + \epsilon, \boldsymbol{s} \in \mathbb{R}^{d_h}, \epsilon > 0$.

According to Theorem 2.1, we initialize $\boldsymbol{U}_f, \boldsymbol{W}_{hh}$ close to a permutation matrix, such as the identity or those in Henaff et al. (2016) and Helfrich et al. (2018). When a, b, and ϵ are close to zero, asRNN resembles a linear RNN. For this reason, we find the hyperparameter setting of expRNN to be compatible with asRNN. Thus, $\ln(\boldsymbol{W}_{hh})$ uses Henaff initialization (Henaff et al., 2016) for copy memory tasks and Cayley initialization (Helfrich et al., 2018) for other tasks. We also initialize $\boldsymbol{W}_{xh}$ as random semi-orthogonal and $\boldsymbol{b}$ as zero for a greater bound of $\boldsymbol{D}_f$. Ultimately, we initialize $\boldsymbol{s} \sim \mathcal{U}(x; a, b)$, where the optimal settings of a, b, ϵ are task-dependent.

Not only we can avoid the VGP by setting up a, b, ϵ close to zero, but we can also avoid the exploding gradient problem (EGP) by setting a, b, ϵ far from zero (See PTB-c in Table 3). As mitigating the EGP is not our main focus, we use gradient clipping with norm 10 on pixelated MNIST and Penn Treebank tasks, then we select the best hyperparameters for asRNN.

A.4.2 COPY MEMORY TASK

Copy memory is a synthetic many-to-many classification task first introduced in Hochreiter & Schmidhuber (1997) to test the ability to recall information bits after a very long delay. This task is designed to be extremely difficult for the vanilla RNN due to the VGP (Henaff et al., 2016).

193 Input samples contain the alphabets 2-9, and the blank and start letters 0, 1, are one-hot encoded
194 into vectors of dim 10. The recalling sequence $\mathcal{A}$ contains the first K letters of the input and are
195 uniformly sampled from the alphabet. It is followed by L blank letters, 1 start letter, and another
196 $K - 1$ blank letters. An output sample contains $K + L + 1$ blanks letter and the recalling sequence
197 $\mathcal{A}$. The baseline model output $K + L + 1$ blanks letter and another $K - 1$ letters sampled uniformly
198 of the alphabet, which has the loss of $\frac{K \ln 8}{L + 2K}$.

199 On this task, we benchmark asRNN against the architectures: LSTM, scoRNN, and expRNN. The
200 recalling length K is 10 for both of the experiments in Figure 2 and Figure 1a). The seed on this
201 task is set at 5544 and the number of parameters is fixed at 22K. All experiments are optimized with
202 smoothing constant $\alpha = 0.9$.

A.4.3 PIXELATED MNIST

204 Pixelated MNIST is a classification task for hand-written numbers (LeCun et al., 1998). It benchmarks
205 RNN sequence learning under a continuous stream of input.

206 On the unpermuted pixelated MNIST task (sMNIST), each 28×28 image of a decimal digit is
207 pixelated into a 784 input sequence, then is fed into the RNN to produce an embed vector used for
208 classification. On the permuted pixelated MNIST task (pMNIST), a permutation is applied to all
209 samples before they are pixelated.

210 On this task, we benchmark asRNN against the following architecture: LSTM, scoRNN, expRNN,
211 restricted-capacity unitary RNN (uRNN)(Arjovsky et al., 2016). The seed on this task is set at 5544.

A.4.4 PENN TREEBANK CHARACTER-LEVEL PREDICTION (PTB-C) TASK

213 Penn Treebank is a corpus that has an alphabet size of 50, including the end of sentence symbol, and
214 is first introduced in (Marcus et al., 1993). We choose this many-to-many character-level modeling
215 task because rather than bottlenecking RNNs' memory capacity, it tests their expressiveness, which
216 includes structural design and the hidden size Bojanowski et al. (2016). Gated mechanisms such as
217 LSTM is known to be effective for PTB-c.

218 On this task, we benchmark asRNN against the following architecture: LSTM, expRNN, nnRNN
219 (Kerg et al., 2019), EURNN (Jing et al., 2017), modReLU RNN with Glorot initialization (RNN),
220 modReLU RNN with orthogonal initialization (RNN-orth). For the Penn Treebank character-level
221 prediction, each experiment is carried out for 5 repeated trials. On this task, the number of parameters
222 for each model is fixed at 1.32M.

Task	#epoch/iter	d_h	lr	lr $\boldsymbol{W}_{hh}$	a	b	ϵ
Copy memory	4000	138	$2 \cdot 10^{-4}$	10^{-4}	0	0	$2 \cdot 10^{-5}$
sMNIST	70	122	$7 \cdot 10^{-4}$	$7 \cdot 10^{-5}$	$2 \cdot 10^{-2}$	$2 \cdot 10^{-2}$	10^{-2}
sMNIST	70	257	$5 \cdot 10^{-4}$	$5 \cdot 10^{-5}$	$2 \cdot 10^{-2}$	$2 \cdot 10^{-2}$	10^{-2}
sMNIST	70	364	$3 \cdot 10^{-4}$	$3 \cdot 10^{-5}$	$2 \cdot 10^{-2}$	$2 \cdot 10^{-2}$	10^{-2}
pMNIST	70	122	10^{-3}	10^{-4}	$2 \cdot 10^{-2}$	$2 \cdot 10^{-2}$	10^{-2}
pMNIST	70	257	$7 \cdot 10^{-4}$	$7 \cdot 10^{-5}$	$2 \cdot 10^{-2}$	$2 \cdot 10^{-2}$	10^{-2}
pMNIST	70	364	$7 \cdot 10^{-4}$	$7 \cdot 10^{-5}$	$2 \cdot 10^{-2}$	$2 \cdot 10^{-2}$	10^{-2}
PTB-c (T=150)	100	1024	10^{-3}	10^{-3}	$8 \cdot 10^{-1}$	3	0
PTB-c (T=300)	100	1024	10^{-3}	10^{-3}	$8 \cdot 10^{-2}$	3	0

Table 3: Hyperparameters for asRNN.

B CONCLUSION & FUTURE WORK

224 In this work, we propose asRNN, a novel variant of vanilla RNN. Under mild assumptions and
225 conditions, we show that asRNN does not exhibit the VGP and potentially possesses long memory.
226 We also conduct experiments to demonstrate asRNN superior trainability on tasks requiring high
227 memory capacity and expressivity.

In near future, we plan to extend asRNN to scale-dependent loss (Assumption A.1). We also aim to reduce the computational cost using non-exponential sigmoids such as $\frac{x}{(1+|x|^k)^{k-1}}$. Ultimately, since memory capacity is observed to be a bottleneck in gated mechanisms (Collins et al., 2017), we hope to extend our work beyond vanilla RNN by investigating whether this problem is related to the VGP and whether we can do anything to change it.