Continuous-Utility Direct Preference Optimization

Abstract

Large language model reasoning is often treated as a monolithic capability, relying on binary preference supervision that fails to capture partial progress or fine-grained reasoning quality. We introduce continuous utility direct preference optimization (**CU-DPO**), a framework that aligns models to a portfolio of prompt-based cognitive strategies by replacing binary labels with continuous scores that capture fine-grained reasoning quality, proving that learning with K strategies yields a $\Theta(K \log K)$ improvement in sample complexity over binary preferences and that DPO converges to the entropy-regularized utility-maximizing policy. To exploit this signal, we propose a two-stage pipeline: (i) strategy selection, which optimizes the model to choose the best strategy via best-vs-all comparisons, and (ii) execution refinement, which trains correct execution using margin-stratified pairs. The framework is domain-agnostic: any task admitting cognitively distinct solution strategies and a decomposable continuous utility signal can be incorporated into the portfolio. On mathematical reasoning benchmarks, **CU-DPO** improves strategy selection accuracy from 35–46% to 68–78% across seven base models, yielding downstream reasoning gains of up to +6.6 points on in-distribution datasets with effective out-of-distribution transfer, and demonstrates consistent gains on code generation and causal reasoning benchmarks, confirming generalization beyond the mathematical domain.

1 Introduction

Large language models (LLMs) exhibit strong mathematical reasoning capabilities, yet they often commit to a single "thinking style" and collapse when problems demand different cognitive procedures, applying uniform strategies regardless of problem structure. This contrasts with human mathematical cognition, where experts fluidly select among diverse reasoning modalities based on problem characteristics (Schoenfeld, 1985; Pólya, 1945a).

The dominant alignment paradigm, direct preference optimization (DPO) (Rafailov et al., 2023), relies on binary labels that misrepresent the continuous nature of reasoning quality: a chain containing correct sub-derivations that fails at a single arithmetic step receives the same reject label as a fundamentally flawed chain. We introduce **CU-DPO**, which replaces binary supervision with *continuous, high-fidelity utilities* aggregating LLM-judged scores across answer correctness, reasoning quality, and completeness. Under the Bradley-Terry model $P(y_w \succ y_l|x) = \sigma(U(x, y_w) - U(x, y_l))$, the DPO optimal policy satisfies $r_\theta(x, y_i) - r_\theta(x, y_j) = U(x, y_i) - U(x, y_j)$, recovering continuous utility structure up to a problem-dependent constant (Theorem 3.4). Learning from binary preferences requires $\Omega(NK^2 \log K)$ samples to recover the latent quality ranking of K candidates across N problems; continuous utilities achieve the same accuracy with $O(NK)$ samples, a $\Theta(K \log K)$ multiplicative improvement.

A further challenge is conflicting supervision signals: comparing a correctly executed "bad strategy" to a poorly executed "good strategy" confuses whether to optimize strategy choice or execution quality. We address this by constructing two distinct preference pair sets for sequential training — Phase 1 for strategy selection via best-vs-all comparisons, Phase 2 for execution refinement via margin-stratified intra-strategy pairs.

Empirical analysis across 450 problems from DeepMath, HARDMath2, and ProofNet reveals that strategy-conditioned generation produces utility scores ranging from 0.1 to 0.9 *for the same problem* depending on strategy choice (Appendix B), demonstrating that strategy selection alone accounts for substantial solution quality variance. While grounded in mathematical reasoning, CU-DPO extends naturally to any domain admitting

Figure 1: **CU-DPO** overview. Strategy-conditioned sampling → LLM-judged continuous utilities → progressive refinement → high-signal pair construction (Phase 1 [p1]: strategy selection, Phase 2 [p2]: execution refinement) → utility-weighted DPO training.

diverse problem-solving strategies and decomposable continuous quality metrics, as we validate on code generation and causal reasoning.

Contributions. We present **CU-DPO**, a unified framework for structured reasoning alignment applicable to any domain admitting cognitively distinct solution strategies and a decomposable continuous utility signal. **(1)** We train models to select optimal reasoning strategies from a domain-agnostic portfolio, instantiated for mathematical reasoning (8 strategies), code generation (4 strategies), and causal reasoning (6 strategies). **(2)** We replace binary preferences with continuous utility scores, proving a $\Theta(K \log K)$ sample complexity improvement and establishing convergence to the entropy-regularized optimal policy with learned implicit reward $r_\theta(x, y) = U(x, y) + c(x)$ (Theorems 3.2 and 3.4). **(3)** We separate strategy selection (Phase 1) from execution refinement (Phase 2), preventing supervision conflicts; combined with step-level supervision, CU-DPO addresses orthogonal failure modes and yields strictly complementary gains (Appendix D). **(4)** We validate across in-distribution and out-of-distribution math datasets, code generation, and causal reasoning across seven base models.

2 Utility and Pairwise Preferences

CU-DPO addresses two key questions: **(i)** how to define the utility function and **(ii)** how to construct preference pairs that cleanly separate strategy selection from execution quality. As illustrated in Figure 1, input problems are transformed into high-signal preference pairs via strategy-conditioned sampling, continuous utility scoring (correctness, preciseness, coherence) through an LLM judge, and selective refinement, yielding 3,150 strategy selection pairs (Phase 1) and 2,680 execution re-

finement pairs (Phase 2) for mathematical reasoning. For code generation and causal reasoning, the same pipeline is instantiated with domain-specific strategy portfolios and utility decompositions, confirming that pair construction generalizes without architectural modification.

2.1 Strategy-conditioned chain sampling

For each problem instance $x \in \mathcal{X}$, we generate $K=8$ candidate reasoning chains from a fixed base model π_0 using a set of strategy prompts $\mathcal{S} = \{s_1, \ldots, s_K\}$. Each strategy $s \in \mathcal{S}$ is implemented by a prompt template $g_s(\cdot)$ that induces a distinct problem-solving approach (e.g., step-by-step, backwards reasoning, verification, more details in Appendix O). We sample one chain per strategy as $y^{(s)} \sim \pi_0(\cdot \mid x, g_s(x))$, yielding a problem-specific set of reasoning chains as $\mathcal{C}_0(x) = \{y^{(s)}\}_{s \in \mathcal{S}}$. Across $N=450$ problems, this produces $NK=3{,}600$ strategy-conditioned chains.

The motivation is mechanism mismatch: models commit to inappropriate approaches even when the correct one is within their capabilities. Strategy conditioning makes this observable at the instance level, inducing a utility landscape over approaches for the same x. The per-problem utility range has mean 0.295 (min 0.050, max 0.889), with 87% of problems having range > 0.3, providing the core signal for Phase 1.

2.2 Continuous utility scoring via LLM Judge

Each chain y is evaluated by an LLM judge that outputs a decomposed utility score as $U(x, y) = \frac{1}{3} \sum_{c=1}^{3} w_c \cdot s_c(x, y) \in [0, 1]$, where $s_c \in [0, 1]$ represents three scoring components: **(1)** correctness verification, **(2)** step efficiency, and **(3)** reasoning coherence. The LLM judge (Qwen 2.5 7B) produces both scoring components s_c and weights

w_c, with higher weight assigned to correctness and lower weights to coherence and validity. This weighting achieves high correlation ($r = 0.85$, Appendix M.1) between utility scores and ground-truth correctness. Continuous utilities preserve fine-grained quality distinctions that binary labels collapse: a chain with correct reasoning but a minor arithmetic error scores moderately ($U \approx 0.5$) rather than receiving the same reject label as a fundamentally flawed chain ($U \approx 0.2$). To mitigate length bias, step efficiency penalizes verbosity; utility correlates only weakly with chain length ($r = 0.23$). Further details appear in Appendix M.

2.3 Progressive refinement for signal amplification

Low-utility chains often contain recoverable sub-structure, such as correct initial steps or valid algebraic manipulations that fail due to localized errors. We selectively refine chains below threshold $\tau = 0.4$ using a refinement operator $\mathcal{R}$ as $y' = \mathcal{R}(x, y)$ applied if $U(x, y) < \tau$. The threshold $\tau = 0.4$ targets chains in the bottom 40th percentile of the utility distribution (Appendix B), which empirically exhibit fixable errors rather than fundamental reasoning failures. Refinement proceeds iteratively for up to $T_{\max} = 5$ rounds with empirically monotone utility improvement $y^{[s,0]} \xrightarrow{\mathcal{R}} y^{[s,1]} \xrightarrow{\mathcal{R}} \cdots \xrightarrow{\mathcal{R}} y^{[s,T]}$, $U(x, y^{[s,t+1]}) \geq U(x, y^{[s,t]})$, where $y^{[s,t]} \in \mathcal{C}_s^{\mathrm{ref}}(x)$ denotes the t-th refinement iteration using strategy s, and $\mathcal{C}_s^{\mathrm{ref}}(x)$ is the set of all refined chains using strategy s for problem x. Refinement terminates when $U(x, y^{[s,T]}) \geq 0.6$ or $T = T_{\max}$. Empirically, 87.8% of refinement attempts succeed within three rounds, with post-refinement utilities concentrated in $[0.6, 1.0]$. Additional details are provided in Appendix G.

2.4 High-signal preference pair construction

We construct preference pairs in two stages, each targeting a distinct learning objective. The first stage isolates coarse-grained strategy selection, while the second focuses on fine-grained execution quality within a fixed strategy. Separating these objectives prevents conflicting supervision signals that arise when cross-strategy pairs allocate gradients to ordering suboptimal strategies (formalized in Section 3.2).

Strategy selection pairs (Phase 1). To maximize signal for strategy selection, we construct preference pairs that directly compare the best strategy against all alternatives. For each problem x, we identify the optimal strategy $s^*(x) = \arg \max_{s \in \mathcal{S}} U(x, s)$ from the original chains $\mathcal{C}_0(x)$ and form the set

$$
\mathcal{D}_{\mathrm{Phase1}}(x) = \Big\{ (x, y^{(s^*(x))}, y^{(s)}) : s \in \mathcal{S} \backslash \{s^*(x)\},
$$
$$
U(x, y^{(s^*(x))}) > U(x, y^{(s)}) \Big\}, \quad (1)
$$

where $|\mathcal{D}_{\mathrm{Phase1}}(x)| = K - 1$, yielding exactly one comparison per suboptimal strategy. This construction ensures that every training pair reinforces the optimal strategy, providing large utility margins that clearly signal which reasoning mechanism best matches the problem.

Execution quality pairs (Phase 2). After establishing strategy selection, we train on refined chains to improve execution quality. For each strategy $s \in \mathcal{S}$, let $\mathcal{C}_s(x) = \mathcal{C}_s^0(x) \cup \mathcal{C}_s^{\mathrm{ref}}(x)$ denote all chains (original and refined) using strategy s for problem x. We construct margin-stratified pairs comparing executions *within the same strategy*: pairs (y_i, y_j) where both $y_i, y_j \in \mathcal{C}_s(x)$ for some s. Sampling uniformly from all possible pairs yields an imbalanced distribution, failing to leverage subtle comparisons [1]. We use margin-stratified sampling in Phase 2 to prioritize weak-margin comparisons (margin < 0.15), forcing the model to learn subtle, step-level reasoning improvements; refined chains naturally populate this regime due to their concentrated high-utility distribution (see Section 3.2).

3 Continuous-Utility Direct Preference Optimization

Given original chains $C_0(x)$ and refined chains $C_{\mathrm{ref}}(x)$ (Section 2.4), we describe our two-phase training procedure and its theoretical justification; strategy selection and execution refinement require different utility distributions and are therefore trained sequentially to avoid conflating objectives. Sequential training provides clear supervision. As such, in phase 1, we leverage best-vs-rest pairs from original chains in $\mathcal{C}_0$ to optimize for strategy selection, whereas in Phase 2, we turn to strategy-matched pairs from chain refinements in $\mathcal{C}_{\mathrm{ref}}$ to optimize for execution quality.

---

[1] In practice, we primarily sample pairs where one chain is refined ($y_i \in \mathcal{C}_s^{\mathrm{ref}}(x)$) and the other is original ($y_j \in \mathcal{C}_s^0(x)$) but both use the same strategy s, so the preference signal reflects execution improvements rather than a change in strategy.

Figure 2: **Win-rate evolution per preference optimization step.** Win rate versus fine-tuning steps for DeepMath, HARDMath2, and ProofNet. **CU-DPO** surpasses the baseline earlier and maintains a consistent advantage, demonstrating improved sample efficiency. Error bars indicate variability across evaluation batches and runs; the dashed line marks the 50% win-rate threshold (DeepSeek-R1-8B).

3.1 Bradley-Terry preference model and DPO loss

We first establish the preference modeling framework underlying our approach.

Bradley-Terry preference model. The Bradley-Terry model (Bradley and Terry, 1952) converts continuous quality scores into pairwise preference probabilities. For two reasoning chains y_w and y_ℓ with continuous utilities $U(x, y_w)$ and $U(x, y_\ell)$, the probability that y_w is preferred over y_ℓ is

$$P(y_w \succ y_\ell \mid x) = \sigma(\Delta U) = \frac{1}{1 + \exp(-\Delta U)}, \quad (2)$$

where $\Delta U = U(x, y_w) - U(x, y_\ell)$ and σ is the sigmoid function. Larger utility margins correspond to stronger, more confident preferences, a property we exploit in margin-stratified sampling.

DPO loss. DPO (Rafailov et al., 2023) bypasses explicit reward modeling by reparameterizing the reward function in terms of the policy. The implicit reward is $r_\theta(x, y) = \beta\left[\log \pi_\theta(y \mid x) - \log \pi_{\text{ref}}(y \mid x)\right]$, where π_{ref} is a reference policy and β is the inverse temperature controlling regularization strength. Given a preference pair (y_w, y_ℓ) where y_w is preferred, DPO minimizes the negative log-likelihood under the Bradley-Terry model:

$$\mathcal{L}_{\text{DPO}}(x; y_w, y_\ell) = -\log \sigma\left(r_\theta(x, y_w) - r_\theta(x, y_\ell)\right). \quad (3)$$

At optimality, the implicit reward difference matches the utility difference: $r_\theta(x, y_w) - r_\theta(x, y_\ell) = U(x, y_w) - U(x, y_\ell)$ (Lemma 3.3).

3.2 Two-phase training

Consider a single-phase DPO objective trained on pairs (y^{s_i}, y^{s_j}) where chains are generated using different strategies $s_i \neq s_j$. If the dataset contains pairs $(y^{s_1}_{\text{best}}, y^{s_2}_{\text{good}})$ and $(y^{s_2}_{\text{good}}, y^{s_3}_{\text{bad}})$ where utilities decrease monotonically, jointly optimizing produces ambiguous gradients: the first comparison encourages preferring s_1 over s_2, while the second encourages s_2 over s_3, allocating gradient updates to ordering suboptimal strategies rather than consistently reinforcing the optimal choice.

To prevent these conflicting signals, we decompose training into two sequential phases using the preference datasets constructed in Section 2.4.

Phase 1: Strategy selection. Recall the construction of $\mathcal{D}_{\text{Phase1}}$ from Section 2.4. For each problem x, we identify the optimal strategy $s^*(x) = \arg\max_{s \in \mathcal{S}} U(x, s)$ and form preference pairs comparing the best strategy against every alternative:

$$\mathcal{D}_{\text{Phase1}} = \Big\{(x, y^{(s^*(x))}, y^{(s_k)}) : s_k \in \mathcal{S} \setminus \{s^*(x)\},$$
$$U(x, y^{(s^*(x))}) > U(x, y^{(s_k)})\Big\}. \quad (4)$$

This yields exactly $K - 1$ pairs per problem, and every pair directly reinforces the optimal strategy choice with large utility margins (mean 0.35).

Phase 2: Execution quality refinement. After Phase 1 stabilizes strategy selection, we train on intra-strategy pairs to improve execution quality. For each strategy $s \in \mathcal{S}$, let $\mathcal{C}_s(x) = \mathcal{C}_s^0(x) \cup \mathcal{C}_s^{\text{ref}}(x)$ be the set of all chains (original and refined) using strategy s on problem x. We form strategy-matched pairs:

$$\mathcal{D}_{\text{Phase2}} = \bigcup_{s \in \mathcal{S}} \Big\{(x, y_i, y_j) : y_i, y_j \in \mathcal{C}_s(x),$$
$$U(x, y_i) > U(x, y_j)\Big\}, \quad (5)$$

For training in phase 2, we further by utility margin $\Delta U = U(x, y_i) - U(x, y_j)$. We partition pairs into three margin bins: strong ($\Delta U \geq 0.30$, 45%), medium ($0.15 \leq \Delta U < 0.30$, 30%), and weak ($\Delta U < 0.15$, 25%). The mixture emphasizes strong margins for robust learning while including weak-margin pairs that force discrimination of subtle execution differences, which is critical for refined chains whose post-refinement utilities concentrate in $[0.6, 1.0]$. This stratification yields mean margins of 0.18-0.29 (combined 0.244) versus 0.15-0.20 under uniform sampling (Appendix G).

3.3 Sample efficiency for continuous utilities

We formalize the sample complexity advantage of continuous utilities. Our goal is to learn a reward function $r : \mathcal{X} \times \mathcal{Y} \to \mathbb{R}$ from a hypothesis class $\mathcal{H}$ with VC-dimension d such that the induced policy $\pi_r(y \mid x) \propto \pi_{\text{ref}}(y \mid x) \exp(r(x,y)/\beta)$ maximizes expected utility.

We compare two observation models across N problems: a *binary preference model* observing $\ell_{ij} = \mathbb{1}[U(x, y_i) > U(x, y_j)]$ for sampled pairs, and a *continuous utility model* observing $\{U(x, y_1), \ldots, U(x, y_K)\}$ directly. From Appendix J.1, learning from binary pairwise preferences requires at least

$$m_{\text{binary}} = \Omega\left(NK^2 \log K + \frac{d}{\varepsilon^2}\right) \qquad (6)$$

comparisons to achieve ε-suboptimal expected utility with probability at least $1 - \delta$.

Theorem 3.1 (Sample complexity under continuous utilities). *When continuous utilities $\{U(x, y_1), \ldots, U(x, y_K)\}$ are observed for each problem, a reward function can be learned using $m_{\text{utility}} = O\left(NK + \frac{d}{\varepsilon^2}\right)$ samples.*

Proof. See Appendix J.2. □

Theorem 3.2 (Utility-guided sample efficiency gain). *In the regime where $NK^2 \log K \gg d/\varepsilon^2$, continuous utility observation provides a multiplicative efficiency gain of $\frac{m_{\text{binary}}}{m_{\text{utility}}} = \Theta(K \log K)$.*

Proof. Under the regime assumption, the PAC learning term becomes negligible, yielding $\frac{m_{\text{binary}}}{m_{\text{utility}}} = \frac{\Omega(NK^2 \log K)}{O(NK)} = \Omega(K \log K)$. Matching upper bounds from Appendix J.1 establish $\Theta(K \log K)$. □

For $K = 8$, this yields an approximately $24\times$ theoretical speedup. Our empirical 5,830 pairs achieve a $2.16\times$ compression relative to the 12,600 exhaustive pairs ($450 \times \binom{8}{2}$), reflecting Phase 1's best-vs-all construction ($K - 1 = 7$ pairs per problem rather than $\binom{K}{2} = 28$) and binary DPO's inability to compare chains within the same correctness category.

Figure 3: **Empirical evidence for reward–utility alignment.** Learned implicit reward $r_\theta(x, y) = \beta(\log \pi_\theta - \log \pi_{\text{ref}})$ aligns linearly with utility $U(x, y)$, supporting the relation $r_\theta(x, y) = U(x, y) + c(x)$ and Theorem 3.4.

3.4 Convergence to utility-maximizing policy

We show that DPO with utility-weighted preferences converges to the entropy-regularized utility-maximizing policy.

Lemma 3.3 (Reward-utility alignment). *At the global minimum of the DPO objective (Eq. 3), the implicit reward satisfies $r_\theta(x, y_i) - r_\theta(x, y_j) = U(x, y_i) - U(x, y_j)$ for all pairs (i, j), implying $r_\theta(x, y) = U(x, y) + c(x)$ for some problem-dependent constant $c(x)$.*

Proof sketch. The DPO objective minimizes negative log-likelihood under the Bradley-Terry model. At the optimum, the model's predicted preference probabilities must match the true preference probabilities: $\sigma(\Delta r_{ij}) = \sigma(\Delta U_{ij})$. Since σ is strictly monotone, this implies $\Delta r_{ij} = \Delta U_{ij}$ for all pairs. These pairwise constraints uniquely determine $r_\theta(x, y)$ up to an additive constant $c(x)$. Full proof is in Appendix I. □

Corollary 3.4 (DPO converges to utility-maximizing policy). *The optimal policy π_θ^* learned by DPO with utility-based preferences (Eq. 2) satisfies*

$$\pi_\theta^*(y \mid x) \propto \pi_{\text{ref}}(y \mid x) \exp\left(\frac{U(x,y)}{\beta}\right), \quad (7)$$

which is the entropy-regularized utility-maximizing policy.

Proof. By Lemma 3.3, at optimality $r_\theta(x, y) = U(x, y) + c(x)$. The DPO closed-form solution (Rafailov et al., 2023) gives $\pi_\theta^*(y \mid x) \propto \pi_{\text{ref}}(y \mid x) \exp(r_\theta(x, y)/\beta)$. Substituting and noting that $\exp(c(x)/\beta)$ is constant in y yields the result. $\qquad\square$

Remark 3.5 (Problem-dependent constant invariance). The problem-dependent constant $c(x)$ does not affect policy ranking: for any two chains y_i, y_j given problem x, the probability ratio satisfies $\frac{\pi_\theta^*(y_i|x)}{\pi_\theta^*(y_j|x)} = \frac{\pi_{\text{ref}}(y_i|x)}{\pi_{\text{ref}}(y_j|x)} \exp\left(\frac{U(x,y_i)-U(x,y_j)}{\beta}\right)$, where $c(x)$ cancels. Thus, even if $c(x)$ varies widely across problems, the learned policy correctly ranks chains within each problem by utility differences ΔU, which is the training objective. Cross-problem comparisons are not required for generation.

Figure 3 empirically validates Lemma 3.3: the learned implicit reward exhibits strong linear correlation ($R^2 = 0.97$) with ground-truth utilities, confirming that DPO recovers the utility function up to a problem-dependent constant.

4 Experiments

We evaluate **CU-DPO** across three domains to demonstrate both task performance and domain generalization. For mathematical reasoning, we use three in-distribution datasets (Deep-Math, HARDMath2, ProofNet) and three out-of-distribution datasets (GSM8K, MATH-500, U-MATH), with 450 training problems drawn from the in-distribution benchmarks and held-out test sets of 150 problems per dataset to ensure no data leakage. We further evaluate on code generation (HumanEval) and causal reasoning (α-NLI) to confirm that continuous utility supervision generalizes beyond mathematical reasoning to any domain admitting a strategy portfolio and decomposable utility signal. All experiments were conducted on an AWS g4dn.12xlarge instance, and all primary results are reported as mean $\pm$ standard deviation across three independent runs with different random seeds; paired t-tests with Bonferroni correction are reported in Appendix F.

4.1 Problem-strategy correlation analysis

Table 1 confirms that optimal strategies shift systematically across mathematical domains with no single strategy dominating (mean margin 0.30), validating that strategy selection is problem- dependent and motivating the portfolio approach.

4.2 Strategy Selection

We compare against prompt-selected baselines without fine-tuning, evaluating accuracy, Top-3 selection rate, and Spearman's ρ (rank correlation over all strategies). Additional comparisons with preference learning and inference-time baselines are in Appendix C.

In-distribution (Table 6). Phase 1 separates strategy choice from execution. Prompt-only baselines

Table 2: Comparison with step-level supervision on in-distribution benchmarks (Pass@1, %) for DeepSeek-R1 (8B).

Setting	DM	HM2	PN	Δ
Baseline	64.2	42.1	38.5	—
+ Step-DPO	66.8	44.3	40.1	+2.4
+ **CU-DPO**	69.8	48.7	44.2	+5.0
+ **CU-DPO** + Step-DPO	**71.9**	**51.2**	**46.3**	**+7.1**

Table 3: **Out-of-distribution strategy selection.** DeepSeek-R1-Distill-Llama-8B evaluated on benchmarks unseen during training to test zero-shot transfer of learned strategy selection capabilities.

Benchmark	Baseline	+ **CU-DPO**	Δ
GSM8K (Acc., %)	48.3	**62.7**	**+14.4**
MATH-500 (Acc., %)	42.6	**65.9**	**+23.3**
U-MATH (Acc., %)	31.2	**49.8**	**+18.6**

Table 1: **Strategy-problem alignment across domains.** Distribution of optimal strategies across 450 training problems grouped by mathematical domain. Avg. utility is the mean utility of the best strategy per problem; avg. margin is the mean utility gap between best and worst strategies, indicating problem-strategy sensitivity.

Domain	N	Best strategy	Second-best	Avg. utility	Avg. margin
Calculus	200	step_by_step (25%)	alternative (16%)	0.763	0.32
Proof	135	direct (27%)	verification (16%)	0.768	0.27
Other	75	step_by_step (19%)	verification (17%)	0.819	0.30
Algebra	22	algebraic (27%)	backward (18%)	0.755	0.35
Analysis	18	alternative (33%)	direct (22%)	0.847	0.28
Overall	**450**	—	—	**0.777**	**0.30**

Table 4: In-distribution and out-of-distribution reasoning accuracy (Pass@1, %) after two-phase **CU-DPO** training. Δ shows Phase 2 improvement over Phase 1 within each split.

Base model	Setting	In-distribution				Out-of-distribution			
		DM	HM2	PN	Δ	GSM	M500	UM	Δ
DeepSeek-R1	Baseline	64.2	42.1	38.5	—	69.8	59.5	6.9	—
(8B)	+ **CU-DPO**	**69.8**	**48.7**	**44.2**	**+5.0**	**72.3**	**64.8**	**8.2**	**+1.8**
Qwen3	Baseline	61.5	39.4	35.2	—	66.4	56.2	5.8	—
(8B)	+ **CU-DPO**	**67.2**	**45.9**	**41.3**	**+5.4**	**68.9**	**61.3**	**7.1**	**+2.2**
Llama-3.1	Baseline	28.4	18.2	14.8	—	58.2	48.3	4.2	—
(8B)	+ **CU-DPO**	**34.8**	**24.7**	**20.9**	**+5.6**	**60.7**	**52.9**	3.8	**+1.9**
Gemma-2	Baseline	26.1	15.5	12.1	—	52.7	42.8	3.1	—
(9B)	+ **CU-DPO**	**32.4**	**21.8**	**17.6**	**+5.6**	**55.4**	**47.6**	**3.4**	**+2.2**
Mistral-8x7B	Baseline	22.8	12.4	9.5	—	48.5	38.6	2.4	—
	+ **CU-DPO**	**28.9**	**18.3**	**14.8**	**+5.5**	**50.2**	37.9	2.1	**+0.1**
Llama-3	Baseline	18.3	8.1	6.4	—	44.2	34.1	1.8	—
(8B)	+ **CU-DPO**	**24.7**	**14.2**	**11.8**	**+5.6**	**46.8**	**37.4**	1.5	**+1.6**
Mistral-7B	Baseline	14.2	5.3	3.8	—	38.6	28.4	1.2	—
	+ **CU-DPO**	**20.3**	**11.7**	**9.2**	**+5.7**	37.9	**30.8**	1.0	**+0.4**

Table 5: **Empirical sample efficiency (data scaling).** Win-rate (%) on held-out preference comparisons as a function of training data fraction.

Base model	Train %	Binary DPO	CU-DPO	Δ
DeepSeek-R1 (8B)	25%	46.8	45.6	−1.2
	50%	50.7	**52.6**	+1.9
	75%	53.9	**56.1**	+2.2
	100%	56.4	**58.9**	+2.5
Qwen3 (8B)	25%	45.9	45.1	−0.8
	50%	49.6	**51.4**	+1.8
	75%	52.8	**55.0**	+2.2
	100%	55.3	**57.6**	+2.3
Gemma-2 (9B)	25%	44.1	43.3	−0.8
	50%	48.2	**50.0**	+1.8
	75%	51.6	**53.7**	+2.1
	100%	54.0	**56.2**	+2.2

Table 6: **In-distribution strategy selection.** Comparison between prompt-only baselines and the same base model after **CU-DPO** Phase 1 fine-tuning, isolating improvements in *strategy selection* rather than reasoning accuracy.

Base model	Setting	Acc.	Top-3	Spear. ρ
DeepSeek-Math (7B)	Baseline	0.46	0.76	0.41
	+ **CU-DPO**	**0.78**	**0.94**	**0.71**
DeepSeek-R1 (8B)	Baseline	0.44	0.74	0.39
	+ **CU-DPO**	**0.76**	**0.93**	**0.69**
Gemma-2 (9B)	Baseline	0.39	0.69	0.33
	+ **CU-DPO**	**0.71**	**0.91**	**0.65**
Mistral-7B	Baseline	0.35	0.66	0.31
	+ **CU-DPO**	**0.68**	**0.89**	**0.62**
Mistral-8x7B	Baseline	0.44	0.74	0.39
	+ **CU-DPO**	**0.77**	**0.93**	**0.70**
Qwen3 (8B)	Baseline	0.43	0.73	0.38
	+ **CU-DPO**	**0.75**	**0.92**	**0.68**
Llama-3 (8B)	Baseline	0.40	0.70	0.35
	+ **CU-DPO**	**0.73**	**0.91**	**0.66**
Llama-3.1 (8B)	Baseline	0.42	0.72	0.37
	+ **CU-DPO**	**0.74**	**0.92**	**0.67**

frequently select mismatched strategies despite seeing all prompts, while **CU-DPO** Phase 1 shifts selections toward better-matched strategies and improves Spearman's ρ, indicating more consistent strategy ordering.

Out-of-distribution (Table 3). The same behavior transfers to unseen benchmarks, with larger gains when mismatch is most harmful. Using DeepSeek-R1-Distill-Llama-8B trained on Deep-Math/HARDMath2/ProofNet and evaluated zero-shot on GSM8K/MATH-500/U-MATH, **CU-DPO** improves strategy choice consistently under distribution shift.

4.3 Execution Refinement and Downstream Reasoning

Phase 2 improves execution quality and downstream reasoning. After Phase 1 learns *which strategy to invoke*, Phase 2 improves *how well* it is executed using preference pairs between original and self-refined chains. Because winner and loser usually share the same high-level approach, supervision focuses on localized corrections such as fixing algebraic errors, improving justifications, and adding verification, producing cleaner gradients than cross-strategy comparisons. Table 4 shows consistent in-distribution gains; for example, DeepSeek-R1 on DeepMath improves from 66.1% (Phase 1 only) to 69.8% after

Table 7: Code generation results. Pass@1 (%) on HumanEval for DeepSeek-R1 (8B) and Qwen3 (8B).

Method	DeepSeek-R1 (8B)	Qwen3 (8B)
Baseline (greedy)	74.3	71.8
Binary DPO	76.1	73.5
Best-of-8	**79.8**	77.1
CU-DPO (ours)	79.2	77.4

Table 8: Causal reasoning results. Accuracy (%) on α-NLI (Abductive NLI) for DeepSeek-R1 (8B) and Qwen3 (8B).

Method	DeepSeek-R1 (8B)	Qwen3 (8B)
Baseline (greedy)	78.4	76.1
Binary DPO	80.1	77.8
Best-of-8	**83.9**	**81.6**
CU-DPO (ours)	83.3	80.8

Phase 2. Table 4 further shows mostly positive out-of-distribution transfer, with modest regressions on ultra-hard problems requiring major insight jumps beyond local refinement.

Comparison with step-level supervision. Table 2 shows that CU-DPO outperforms Step-DPO by +3.0 points on DeepMath and +4.4 on HARD-Math2, indicating that strategy selection is the primary bottleneck. Combining both methods yields additional gains across all datasets, demonstrating complementary roles in horizontal strategy selection and vertical step-level execution refinement. Full analysis is provided in Appendix D and further ablation studies are present in Appendix C.

4.4 Data scaling

Table 5 evaluates sample efficiency by training binary DPO and CU-DPO on 25%, 50%, 75%, and 100% of Phase 2 data, measuring win rate on held-out preference comparisons. We use win rate rather than Pass@1 to isolate optimization efficiency from generation stochasticity.

Under data scarcity (25%), binary DPO holds a slight advantage: discrete labels provide stronger gradients when sample size is insufficient to accurately calibrate continuous utilities. However, CU-DPO overtakes binary DPO at 50% data, with the gap widening monotonically thereafter. This crossover validates our hypothesis: continuous utilities encode richer preference structure but require sufficient data to exploit fine-grained signals. Further ablation studies on comparisons with baseline methods are present in Appendix C.

4.5 Domain Generalization

We evaluate CU-DPO on code generation and causal reasoning to test whether continuous utility supervision generalizes beyond mathematical reasoning. For code generation, we use **HumanEval** (Chen et al., 2021) with four strategies: *direct implementation*, *test-driven development*, *modular decomposition*, and *defensive programming*, with utilities decomposed into correctness, efficiency, and solution clarity. For causal reasoning, we use α-**NLI** (Bhagavatula et al., 2020) with six strategies: *mechanistic*, *counterfactual*, *statistical*, *eliminative*, *analogical*, and *temporal* reasoning, with utilities decomposed into correctness, reasoning validity, and causal coherence.

Tables 7 and 8 report results for DeepSeek-R1 (8B) and Qwen3 (8B). On HumanEval, CU-DPO achieves 79.2% Pass@1, closely matching Best-of-8 (79.8%) at $1\times$ inference cost while improving over binary DPO by +3.1 points; Qwen3 (8B) shows a similar +2.9 point gain. On α-NLI, CU-DPO improves over binary DPO by +3.2 and +3.0 points respectively. Although gains are smaller than in mathematical reasoning due to lower inter-strategy utility separation, CU-DPO consistently outperforms binary DPO and matches inference-heavy baselines at constant cost. Full analyses are provided in Appendices N and E.

5 Conclusion

We introduced CU-DPO, a framework for continuous utility-guided preference optimization that improves sample efficiency through continuous utility scoring, structured pair construction, and two-phase training. Unlike binary supervision, continuous utilities capture finer-grained information such as partial correctness and reasoning coherence, while the separation of strategy selection and execution refinement avoids conflicting optimization signals. Beyond mathematical reasoning, we show that CU-DPO generalizes to code generation and causal reasoning, demonstrating applicability to domains with multiple cognitively distinct reasoning strategies and decomposable quality metrics.

Future directions include autonomous strategy portfolio generation via LLM conditioning, adaptive phase scheduling exploiting Phase 1's faster convergence, and error-type-specialized refinement operators for improved correction efficiency.

Limitations

While CU-DPO demonstrates significant sample efficiency and performance gains across multiple domains, several limitations need to be acknowledged. (a) The framework heavily relies on the quality and calibration of the offline LLM judge used to decompose and score continuous utilities. Although our cross-judge validation indicates high agreement among top-tier models, utilizing smaller or poorly calibrated judges could introduce stochastic noise that increases the sample complexity required to accurately recover latent rankings. (b) The progressive refinement operator $\mathcal{R}$ used in Phase 2 incurs an additional computational overhead during the offline dataset generation phase, particularly for highly complex tasks where models may require multiple iterative rounds to reach the utility success threshold. (c) As observed in our OOD mathematical evaluations, CU-DPO exhibits modest performance regressions on ultra-hard problems that demand substantial, non-local cognitive insight jumps, which suggests that localized, intra-strategy execution refinement is less effective when a problem requires an unrepresented paradigm shift.

Impact Statement

This paper presents work whose goal is to advance the field of machine learning. There are many potential societal consequences of our work, none of which we feel must be specifically highlighted here.

References

Maciej Besta, Nils Blach, Ales Kubicek, Robert Gerstenberger, Michal Podstawski, Lukas Gianinazzi, Joanna Gajda, Tomasz Lehmann, Hubert Niewiadomski, Piotr Nyczyk, and Torsten Hoefler. 2024. Graph of thoughts: Solving elaborate problems with large language models. *Proceedings of the AAAI Conference on Artificial Intelligence*, 38(16):17682–17690.

Chandra Bhagavatula, Ronan Le Bras, Chaitanya Malaviya, Keisuke Sakaguchi, Ari Holtzman, Hannah Rashkin, Doug Downey, Scott Wen tau Yih, and Yejin Choi. 2020. Abductive commonsense reasoning. *Preprint*, arXiv:1908.05739.

Ralph Allan Bradley and Milton E. Terry. 1952. Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, 39(3/4):324–345.

Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, and 39 others. 2021. Evaluating large language models trained on code.

Xinyun Chen, Renat Aksitov, Uri Alon, Jie Ren, Kefan Xiao, Pengcheng Yin, Sushant Prakash, Charles Sutton, Xuezhi Wang, and Denny Zhou. 2023. Universal self-consistency for large language model generation. *Preprint*, arXiv:2311.17311.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*.

Hanze Dong, Wei Xiong, Deepanshu Goyal, Yihan Zhang, Winnie Chow, Rui Pan, Shizhe Diao, Jipeng Zhang, Kashun Shum, and Tong Zhang. 2023. Raft: Reward ranked finetuning for generative foundation model alignment. *Preprint*, arXiv:2304.06767.

Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Nan Duan, and Weizhu Chen. 2024a. Critic: Large language models can self-correct with tool-interactive critiquing. *Preprint*, arXiv:2305.11738.

Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Minlie Huang, Nan Duan, and Weizhu Chen. 2024b. Tora: A tool-integrated reasoning agent for mathematical problem solving. *Preprint*, arXiv:2309.17452.

Caglar Gulcehre, Tom Le Paine, Srivatsan Srinivasan, Ksenia Konyushkova, Lotte Weerts, Abhishek Sharma, Aditya Siddhant, Alex Ahern, Miaosen Wang, Chenjie Gu, Wolfgang Macherey, Arnaud Doucet, Orhan Firat, and Nando de Freitas. 2023. Reinforced self-training (rest) for language modeling. *Preprint*, arXiv:2308.08998.

Shibo Hao, Yi Gu, Haodi Ma, Joshua Jiahua Hong, Zhen Wang, Daisy Zhe Wang, and Zhiting Hu. 2023. Reasoning with language model is planning with world model. *Preprint*, arXiv:2305.14992.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arber, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the MATH dataset. In *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*.

Jiwoo Hong, Noah Lee, and James Thorne. 2024. Orpo: Monolithic preference optimization without reference model. *Preprint*, arXiv:2403.07691.

Arian Hosseini, Xingdi Yuan, Nikolay Malber, Aaron Courville, Alessandro Sordoni, and Rishabh Agarwal. 2024. V-STaR: Training verifiers for self-taught reasoners. *arXiv preprint arXiv:2402.06457*.

Jiaxin Huang, Shixiang Shane Gu, Le Hou, Yuexin Wu, Xuezhi Wang, Hongkun Yu, and Jiawei Han. 2022. Large language models can self-improve. *Preprint*, arXiv:2210.11610.

Robert Kirk, Ishita Mediratta, Christoforos Nalmpantis, Jelena Luketina, Eric Hambro, Edward Grefenstette, and Roberta Raileanu. 2024. Understanding the effects of rlhf on llm generalisation and diversity. *Preprint*, arXiv:2310.06452.

Xin Lai, Zhuotao Tian, Yukang Chen, Senqiao Yang, Xiangru Peng, and Jiaya Jia. 2024. Step-dpo: Step-wise preference optimization for long-chain reasoning of llms. *Preprint*, arXiv:2406.18629.

Aitor Lewkowycz, Anders Andreassen, David Dohan, Ethan Dyer, Henryk Michalewski, Vinay Ramasesh, Ambrose Slone, Cem Anil, Imanol Schlag, Theo Gutman-Solo, Yuhuai Wu, Behnam Neyshabur, Guy Gur-Ari, and Vedant Misra. 2022. Solving quantitative reasoning problems with language models. *Preprint*, arXiv:2206.14858.

Shijie Li, Mengmeng Xia, Jiayu Zou, Xiaobing Wang, Zhengzhong Wang, Yuan Zhao, and Ming Gao. 2024. Xwin-Math: Enhancing mathematical reasoning through diverse solution synthesis. *arXiv preprint arXiv:2403.06024*.

Yifei Li, Zeqi Lin, Shizhuo Zhang, Qiang Fu, Bei Chen, Jian-Guang Lou, and Weizhu Chen. 2023. Making large language models better reasoners with step-aware verifier. *Preprint*, arXiv:2206.02336.

Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2023. Let's verify step by step. *arXiv preprint arXiv:2305.20050*.

Haipeng Luo, Qingfeng Sun, Can Xu, Pu Zhao, Jianguang Lou, Chongyang Tao, Xiubo Geng, Qingwei Lin, Shifeng Chen, Yansong Tang, and Dongmei Zhang. 2025. Wizardmath: Empowering mathematical reasoning for large language models via reinforced evol-instruct. *Preprint*, arXiv:2308.09583.

Stanislas Polu and Ilya Sutskever. 2020. Generative language modeling for automated theorem proving. *Preprint*, arXiv:2009.03393.

George Pólya. 1945a. *How to Solve It: A New Aspect of Mathematical Method*. Princeton University Press, Princeton, NJ.

George Pólya. 1945b. *How to solve it: A new aspect of mathematical method*, 2nd edition. Princeton University Press, Princeton, NJ. Expanded version published in 1957.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems*, volume 36.

Melissa Roemmele, Cosmin Adrian Bejan, and Andrew S Gordon. 2011. Choice of plausible alternatives: An evaluation of commonsense causal reasoning. In *AAAI spring symposium: logical formalizations of commonsense reasoning*, pages 90–95.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language models can teach themselves to use tools. *Preprint*, arXiv:2302.04761.

Alan H. Schoenfeld. 1985. *Mathematical Problem Solving*. Academic Press, Orlando, FL.

Bilgehan Sel, Ahmad Al-Tawaha, Vanshaj Khattar, Ruoxi Jia, and Ming Jin. 2024. Algorithm of thoughts: Enhancing exploration of ideas in large language models. *Preprint*, arXiv:2308.10379.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. 2024. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*.

Avi Singh, John D. Co-Reyes, Rishabh Agarwal, Ankesh Anand, Piyush Patil, Xavier Garcia, Peter J. Liu, James Harrison, Jaehoon Lee, Kelvin Xu, Aaron Parisi, Abhishek Kumar, Alex Alemi, Alex Rizkowsky, Azade Nova, Ben Adlam, Bernd Bohnet, Gamaleldin Elsayed, Hanie Sedghi, and 22 others. 2024. Beyond human data: Scaling self-training for problem-solving with language models. *Preprint*, arXiv:2312.06585.

Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, and 1 others. 2023. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *Transactions on machine learning research*.

Shubham Toshniwal, Ivan Moshkov, Sean Narenthiran, Daria Gitman, Fei Jia, and Igor Gitman. 2024. Openmathinstruct-1: A 1.8 million math instruction tuning dataset. *Preprint*, arXiv:2402.10176.

Lewis Tunstall, Edward Beeching, Nathan Lambert, Nazneen Rajani, Kashif Rasul, Younes Belkada, Shengyi Huang, Leandro von Werra, Clémentine Fourrier, Nathan Habib, Nathan Sarrazin, Omar Sanseviero, Alexander M. Rush, and Thomas Wolf. 2023. Zephyr: Direct distillation of lm alignment. *Preprint*, arXiv:2310.16944.

Jonathan Uesato, Nate Kushman, Ramana Kumar, Francis Song, Noah Siegel, Lisa Wang, Antonia Creswell, Geoffrey Irving, and Irina Higgins. 2022. Solving math word problems with process- and outcome-based feedback. *arXiv preprint arXiv:2211.14275*.

Peiyi Wang, Lei Li, Zhihong Shao, R. X. Xu, Damai Dai, Yifei Li, Deli Chen, Y. Wu, and Zhifang Sui. 2024a. Math-shepherd: Verify and reinforce llms

step-by-step without human annotations. *Preprint*, arXiv:2312.08935.

Peiyi Wang, Lei Li, Zhihong Shao, R. X. Xu, Damai Dai, Yifei Li, Deli Chen, Y. Wu, and Zhifang Sui. 2024b. Math-shepherd: Verify and reinforce llms step-by-step without human annotations. *Preprint*, arXiv:2312.08935.

Peiyi Wang, Lei Li, Zhihong Shao, Runxin Xu, Damai Dai, Yifei Li, Deli Chen, Yu Wu, and Zhifang Sui. 2024c. Math-shepherd: Verify and reinforce LLMs step-by-step without human annotations. *arXiv preprint arXiv:2312.08935*.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2023. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*.

Zeqiu Wu, Yushi Hu, Weijia Shi, Nouha Dziri, Alane Suhr, Prithviraj Ammanabrolu, Noah A. Smith, Mari Ostendorf, and Hannaneh Hajishirzi. 2023. Fine-grained human feedback gives better rewards for language model training. *Preprint*, arXiv:2306.01693.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. *Preprint*, arXiv:2305.10601.

Longhui Yu, Weisen Jiang, Han Shi, Jincheng Yu, Zhengying Liu, Yu Zhang, James T. Kwok, Zhenguo Li, Adrian Weller, and Weiyang Liu. 2024. Metamath: Bootstrap your own mathematical questions for large language models. *Preprint*, arXiv:2309.12284.

Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Xian Li, Sainbayar Sukhbaatar, Jing Xu, and Jason Weston. 2025. Self-rewarding language models. *Preprint*, arXiv:2401.10020.

Zheng Yuan, Hongyi Yuan, Chengpeng Li, Guanting Dong, Keming Lu, Chuanqi Tan, Chang Zhou, and Jingren Zhou. 2023. Scaling relationship on learning mathematical reasoning with large language models. *Preprint*, arXiv:2308.01825.

Xiang Yue, Xingwei Qu, Ge Zhang, Yao Fu, Wenhao Huang, Huan Sun, Yu Su, and Wenhu Chen. 2023. Mammoth: Building math generalist models through hybrid instruction tuning. *Preprint*, arXiv:2309.05653.

Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah D. Goodman. 2022. STaR: Bootstrapping reasoning with reasoning. In *Advances in Neural Information Processing Systems*, volume 35, pages 15476–15488.

A Related Work

Mathematical reasoning with LLMs. Prior work improves mathematical reasoning through instruction tuning on curated corpora (Hendrycks et al., 2021; Cobbe et al., 2021; Luo et al., 2025; Yue et al., 2023; Yu et al., 2024), tool-augmented reasoning (Gou et al., 2024a; Polu and Sutskever, 2020; Gou et al., 2024b; Schick et al., 2023), and self-improvement via iterative refinement (Zelikman et al., 2022; Huang et al., 2022; Gulcehre et al., 2023). Large-scale supervised fine-tuning (Toshniwal et al., 2024; Shao et al., 2024; Lewkowycz et al., 2022) achieves strong performance but requires massive trajectory collections and treats strategy choice as manual curriculum design.

DPO for reasoning. Recent work applies DPO (Rafailov et al., 2023) to reasoning using binary correctness signals (Wang et al., 2024a; Li et al., 2024; Yuan et al., 2023; Hong et al., 2024; Tunstall et al., 2023), step-level reward modeling (Lightman et al., 2023; Uesato et al., 2022), and RLHF-based iterative refinement (Gulcehre et al., 2023; Yuan et al., 2025; Dong et al., 2023). These approaches collapse solution quality into binary preferences and suffer from mode collapse when strategies succeed on disjoint problem subsets (Wu et al., 2023; Kirk et al., 2024).

Reasoning trajectory diversity. Multiple works recognize that problems admit diverse solution strategies, exploring trajectory selection via correctness filtering (Zelikman et al., 2022; Singh et al., 2024; Hosseini et al., 2024), majority voting (Wang et al., 2023; Chen et al., 2023; Li et al., 2023), search-based exploration (Yao et al., 2023; Besta et al., 2024; Hao et al., 2023; Sel et al., 2024), and outcome or process supervision (Uesato et al., 2022; Lightman et al., 2023; Wang et al., 2024c). However, these methods apply uniform thresholds across strategies, treat all paths equivalently during aggregation, require handcrafted heuristics, or need expensive human annotation.

B Dataset Characteristics and Signal Composition

Our method relies on a deliberately structured two-phase preference dataset whose *signal* is controlled by three design knobs: (i) *within-problem utility diversity* induced by sampling $K = 8$ cognitive strategies, (ii) *continuous utility margins* that determine how informative a comparison is, and (iii) *selective refinement* that injects fine-grained structure for reasoning quality optimization. This section characterizes the resulting datasets and isolates which properties enable effective two-phase learning.

Two-phase dataset pipeline. For each problem x, we sample $K = 8$ chains $\{y_k\}_{k=1}^K$ using fixed prompts corresponding to distinct mechanisms (direct, step-by-step, backwards, alternative, verification, algebraic, numerical, conceptual). An LLM judge assigns continuous utilities $U(x, y_k) \in [0, 1]$. **Phase 1** constructs strategy selection pairs from original chains using a "best vs all" acquisition rule that reinforces optimal strategy choice. **Phase 2** applies selective refinement to low-utility chains, producing an auxiliary pool of refined candidates, and constructs reasoning quality pairs from the merged pool using margin-stratified sampling to enable both coarse and fine-grained supervision.

Strategy selection statistics. Table 9 reports statistics for Phase 1 pairs across datasets. Each problem generates exactly 7 pairs comparing the optimal strategy against all others, yielding 3,150 total pairs from 450 problems. Mean margins of 0.214 reflect coarse-grained distinctions, with substantial spread (std 0.201) capturing varying difficulty across strategy-problem alignments. HARDMath2 exhibits the largest margins (mean 0.320), indicating clearer strategy preferences, while ProofNet shows smaller margins (mean 0.119), suggesting multiple viable strategies for proof-oriented problems. Critically, *every pair in Phase 1 includes the optimal strategy*, eliminating conflicting supervision signals that plagued our initial single-phase approach.

Reasoning quality statistics. Table 10 reports statistics for Phase 2 pairs. From the union of original and refined chains, we sample 6 pairs per problem using margin-stratified acquisition, yielding 2,680 total pairs. Mean margins increase to 0.244 compared to Phase 1 (0.214), as refinement concentrates utilities in higher ranges where fine-grained distinctions emerge. The margin distribution is deliberately balanced to leverage subtle comparisons where nuanced reasoning improvements must be learned.

Which mechanisms create informative conflicts. Table 11 lists the most frequent strategy pairings. In Phase 1, dominant combinations reflect systematic strategy-problem alignments (e.g., alternative

Table 9: **Strategy selection dataset statistics.** High margins in HARDMath2 indicate clear strategy dominance; lower margins in ProofNet suggest strategy interchangeability.

Dataset	Problems	Pairs	Mean ΔU	Median ΔU	Std Dev	Max ΔU
DeepMath-150	150	1,050	0.204	0.113	0.201	0.759
HARDMath2-150	150	1,050	0.320	0.298	0.166	0.750
ProofNet-Final	150	1,050	0.119	0.086	0.131	0.684
Combined	**450**	**3,150**	**0.214**	**0.136**	**0.201**	**0.759**

Table 10: **Reasoning quality dataset statistics.** Margin-stratified sampling ensures representation of weak margins (hard comparisons), which are crucial for learning fine-grained execution details.

Dataset	Problems	Pairs	Mean ΔU	Strong %	Medium %	Weak %
DeepMath-150	149	888	0.258	34.6%	20.2%	45.3%
HARDMath2-150	150	900	0.293	44.2%	28.8%	27.0%
ProofNet-Final	149	892	0.182	17.8%	25.6%	56.6%
Combined	**448**	**2,680**	**0.244**	**32.2%**	**24.9%**	**42.9%**

`vs direct`), capturing fundamental tradeoffs between exploratory versus procedural reasoning. Phase 2 combinations shift toward execution-level distinctions (e.g., `numerical vs step-by-step`), indicating comparisons where both strategies are viable but differ in rigor or completeness.

Selective refinement and hybrid sampling behavior. Table 12 summarizes refinement utilization in Phase 2. Overall, 74.2% of pairs are original vs original, while 25.8% are hybrid. This ratio varies by dataset: HARDMath2 uses the most refinement, indicating that its problems benefit substantially from execution-level improvements, while ProofNet uses minimal refinement, suggesting its original chains already provide sufficient signal. DeepMath falls in between. Importantly, refinement is a *signal amplifier* applied selectively in Phase 2: it increases fine-grained comparison density without diluting the coarse-grained strategy selection signal established in Phase 1.

Global dataset summary. Table 13 aggregates statistics across both training phases. The two-phase construction separates coarse-grained mechanism selection from fine-grained execution refinement, addressing the fundamental issue that plagued single-phase training: conflicting signals about which strategy to use versus how to use it well.

C Comparison With Baselines

Table 14 highlights a clear tradeoff between test-time compute and distributional alignment. Test-time methods such as Best-of-K and self-consistency achieve stronger out-of-distribution performance by repeatedly sampling from the unfine-tuned base model, thereby avoiding the distribution shift introduced by task-specific fine-tuning, but at an $8\times$ inference cost. In contrast, CU-DPO explicitly aligns the model to the training distribution through continuous-utility supervision, yielding consistent and substantial gains on in-distribution benchmarks at constant inference cost. The modest OOD regression relative to test-time methods reflects this intentional alignment rather than a failure of generalization. Binary DPO underperforms across all settings, confirming that collapsing graded reasoning quality into binary labels discards informative preference structure and limits sample efficiency. Overall, CU-DPO offers a more favorable accuracy–compute tradeoff when inference cost matters.

D Step-Level Comparison and Complementarity Analysis

This appendix provides a comprehensive comparison between CU-DPO and step-level supervision methods, extending the abbreviated results reported in Table 2 of the main text. We first describe the experimental setup for each method (Section D.1), then report full results across all seven base models and three in-distribution benchmarks (Section D.2), followed by a systematic mechanism-mismatch

Table 11: **Top 5 strategy combinations by dataset and phase.** Phase 1 is dominated by fundamental approach conflicts, while Phase 2 shifts to execution-heavy comparisons.

Phase	Dataset	Strategy combination	Count (%)
Phase 1	DeepMath-150	Alternative vs Direct	58 (5.5%)
		Direct vs Step-by-Step	56 (5.3%)
		Alternative vs Step-by-Step	56 (5.3%)
		Direct vs Verification	50 (4.8%)
		Alternative vs Verification	50 (4.8%)
	HARDMath2-150	Numerical vs Verification	44 (4.2%)
		Step-by-Step vs Verification	43 (4.1%)
		Numerical vs Step-by-Step	43 (4.1%)
		Alternative vs Verification	42 (4.0%)
		Alternative vs Numerical	42 (4.0%)
	ProofNet-Final	Direct vs Verification	47 (4.5%)
		Step-by-Step vs Verification	46 (4.4%)
		Alternative vs Verification	46 (4.4%)
		Direct vs Step-by-Step	45 (4.3%)
		Alternative vs Direct	45 (4.3%)
Transition to execution refinement			
Phase 2	DeepMath-150	Numerical vs Step-by-Step	42 (4.7%)
		Conceptual vs Direct	39 (4.4%)
		Alternative vs Numerical	37 (4.2%)
		Backwards vs Step-by-Step	36 (4.1%)
		Algebraic vs Backwards	35 (3.9%)
	HARDMath2-150	Algebraic vs Backwards	40 (4.4%)
		Numerical vs Step-by-Step	38 (4.2%)
		Alternative vs Direct	37 (4.1%)
		Alternative vs Step-by-Step	37 (4.1%)
		Backwards vs Conceptual	36 (4.0%)
	ProofNet-Final	Backwards vs Numerical	41 (4.6%)
		Alternative vs Step-by-Step	40 (4.5%)
		Algebraic vs Step-by-Step	39 (4.4%)
		Conceptual vs Numerical	38 (4.3%)
		Numerical vs Step-by-Step	36 (4.0%)

decomposition that empirically establishes the orthogonality of the two supervision signals (Section D.3), and conclude with a gradient-level theoretical account of their complementarity (Section D.4).

D.1 Experimental Setup

Step-DPO. Step-DPO (Lai et al., 2024) extends the standard DPO objective to the step level by assigning per-step correctness labels to individual reasoning steps within a fixed chain, rather than assigning a single binary preference label to the complete response. We implement Step-DPO using the same seven base models, the same 450 training problems drawn from DeepMath, HARDMath2, and ProofNet, and the same held-out test sets (150 problems per dataset) used throughout the main paper, ensuring that all comparisons are conducted under identical data conditions. Step-level correctness labels are derived from Math-Shepherd annotations (Wang et al., 2024b) (described below). For each problem, we generate a single step-by-step reasoning chain from the base model and annotate each intermediate step as correct or incorrect according to the Math-Shepherd process reward model. Preference pairs are then constructed by comparing chains that diverge at a specific step, with the preferred chain being the one that maintains correctness through that step. Training follows the standard DPO objective (Eq. 3 of the main text) applied at the step level, with $\beta = 0.1$ and a learning rate of 5×10^{-7}, matching the hyperparameters used for CU-DPO Phase 2. All other training configurations, including batch size, number of epochs, and optimizer, are held constant across methods to ensure fair comparison.

Math-Shepherd. Math-Shepherd (Wang et al., 2024b) is a process reward model (PRM) that assigns per-step correctness scores to mathematical reasoning chains without requiring human annotation, instead using automated step-level verification based on outcome consistency across multiple sampled completions. We train a Math-Shepherd PRM on the same 450 training problems using the Qwen 2.5 7B base as the

Table 12: **Phase 2 source combination.** Refinement is used most heavily in HARDMath2, acting as a signal amplifier for execution quality.

Dataset	Original-Original	Hybrid	Hybrid %	Utility Range
DeepMath-150	682	206	23.2%	0.05–0.88
HARDMath2-150	517	383	42.6%	0.05–0.86
ProofNet-Final	790	102	11.4%	0.05–0.80
Combined	**1,989**	**691**	**25.8%**	**0.05–0.88**

Table 13: **Complete dataset statistics.** Aggregated counts for Phase 1 and Phase 2.

Dataset	Problems	Chains	Phase 1	Phase 2	Total Pairs	Mean ΔU
DeepMath-150	150	1,200	1,050	888	1,938	0.229
HARDMath2-150	150	1,200	1,050	900	1,950	0.307
ProofNet-Final	150	1,200	1,050	892	1,942	0.149
Combined	**450**	**3,600**	**3,150**	**2,680**	**5,830**	**0.228**

reward backbone, consistent with our LLM judge configuration described in Section 2.2 and Appendix I. For each problem and each generated chain, the PRM assigns a binary correctness label $c_t \in \{0, 1\}$ to each step t, where $c_t = 1$ indicates that step t is consistent with a correct final answer across at least $k = 8$ sampled completions from that step onward. These step-level labels serve as the supervision signal for Step-DPO training. The PRM is trained offline on the same 3,600 strategy-conditioned chains generated during CU-DPO data collection, using the step-by-step strategy chains specifically, as these provide the clearest step boundaries for annotation. Importantly, the Math-Shepherd PRM is used solely to generate training labels for Step-DPO; it is not used at inference time, ensuring that all methods operate at $1\times$ inference cost during evaluation.

Combined CU-DPO + Step-DPO Pipeline. The combined pipeline applies the three training phases sequentially. Phase 1 of CU-DPO is run first, training the base model on strategy selection pairs (Section 3.2) to optimize strategy identification. Phase 2 of CU-DPO is then applied on top of the Phase 1

Table 14: **Comparison to alternative reasoning methods.** Pass@1 (%) on in-distribution (DeepMath, HARDMath2) and out-of-distribution (GSM8K) benchmarks. CU-DPO achieves best in-distribution performance with $1\times$ inference cost but exhibits modest OOD regression compared to test-time methods that sample from the unfine-tuned base model. Standard binary DPO underperforms due to information loss from collapsing continuous quality into binary labels.

Base Model	Method	In-Distribution		OOD	Test-time
		DeepMath	HARDMath2	GSM8K	cost
DeepSeek-R1 (8B)	Baseline (greedy)	64.2	42.1	69.8	1×
	Standard DPO (binary)	65.3	43.2	70.9	1×
	Best-of-8 sampling	67.8	46.2	**73.6**	8×
	Self-Consistency (K=8)	68.9	47.4	**74.5**	8×
	CU-DPO (ours)	**69.8**	**48.7**	73.1	**1×**
Qwen3 (8B)	Baseline (greedy)	61.5	39.4	66.4	1×
	Standard DPO (binary)	62.7	40.6	67.5	1×
	Best-of-8 sampling	65.3	43.8	**70.2**	8×
	Self-Consistency (K=8)	66.4	44.9	**71.0**	8×
	CU-DPO (ours)	**67.2**	**45.9**	68.9	**1×**
Gemma-2 (9B)	Baseline (greedy)	26.1	15.5	52.7	1×
	Standard DPO (binary)	27.8	16.9	53.4	1×
	Best-of-8 sampling	30.6	19.7	**56.8**	8×
	Self-Consistency (K=8)	31.5	20.8	**57.6**	8×
	CU-DPO (ours)	**32.4**	**21.8**	56.8	**1×**

checkpoint, training on margin-stratified intra-strategy execution pairs to refine execution quality within the selected strategy. Finally, Step-DPO is applied as a third fine-tuning phase on top of the Phase 2 checkpoint, providing step-level correctness supervision within the strategy already selected and refined by Phases 1 and 2.

This ordering is theoretically motivated by the hierarchical structure of mathematical reasoning failures. Strategy selection is the most upstream failure mode: committing to an inappropriate cognitive mechanism renders all downstream supervision ineffective regardless of its granularity, since even perfect step-level execution of the wrong strategy cannot produce a correct solution. Execution refinement addresses the next layer of failure: given the correct strategy, the model may still produce incorrect derivations due to arithmetic errors, algebraic gaps, or incomplete justifications, which Phase 2 targets through margin-stratified intra-strategy pairs. Step-level polishing addresses the most fine-grained failure mode: localized step errors within an otherwise correctly executed strategy, which Step-DPO targets through per-step correctness labels. Applying Step-DPO before strategy selection has been established (i.e., without Phase 1) would risk providing step-level supervision conditioned on an incorrect strategy, propagating mechanism-mismatch errors through the step-level gradient updates. The sequential ordering ensures that each phase operates on a progressively more refined policy, with each stage addressing a distinct and well-defined failure mode.

D.2   Full Results

Table 15 reports Pass@1 (%) for all four conditions — Baseline, Step-DPO, CU-DPO, and CU-DPO + Step-DPO — across all seven base models and three in-distribution benchmarks. Several consistent patterns emerge across the full result set.

First, CU-DPO alone outperforms Step-DPO alone across all seven base models and all three benchmarks without exception, with margins ranging from $+2.2$ to $+3.8$ points on DeepMath, $+3.7$ to $+5.1$ points on HARDMath2, and $+3.4$ to $+4.8$ points on ProofNet. This is consistent with the theoretical prediction that strategy selection is the binding constraint on these benchmarks: step-level corrections applied within a mismatched strategy cannot address the upstream mechanism-mismatch failure that determines the majority of quality variance (Table 1 of the main text, mean inter-strategy margin 0.35).

Second, the combined CU-DPO + Step-DPO pipeline consistently outperforms CU-DPO alone across all models and benchmarks, with additional gains of $+1.8$ to $+2.4$ points on DeepMath, $+2.2$ to $+2.8$ points on HARDMath2, and $+1.9$ to $+2.3$ points on ProofNet. This confirms that Step-DPO provides a complementary supervision signal that is not subsumed by CU-DPO Phase 2, and that the two methods address genuinely orthogonal failure modes.

Third, stronger base models show larger absolute gains from the combined pipeline, consistent with the hypothesis that stronger models have already minimized the most egregious strategy-mismatch errors through pretraining, and therefore benefit more from the fine-grained step-level signal provided by Step-DPO on top of CU-DPO's strategy selection.

D.3   Mechanism-Mismatch Analysis

The central theoretical claim of CU-DPO is that strategy selection and step-level execution are orthogonal failure modes: mechanism mismatch determines which strategy is applied, while step-level errors determine how well that strategy is executed. If this claim is correct, then CU-DPO should provide the largest advantage over Step-DPO precisely on problems where strategy choice is the binding constraint, while Step-DPO should be most competitive on problems where the strategy is already approximately correct and execution quality is the marginal bottleneck. This section provides a direct empirical test of this prediction by partitioning the 450 training problems by mechanism-mismatch sensitivity and analyzing method performance within each partition.

Problem Partitioning.   We partition the 450 problems into two subsets based on the inter-strategy utility gap $\Delta U_{\max}(x) = \max_{s \in \mathcal{S}} U(x, s) - \min_{s \in \mathcal{S}} U(x, s)$, which measures the range of utility scores across all eight strategies for problem x. Problems with $\Delta U_{\max}(x) > 0.35$ are classified as *high-mismatch* problems, indicating that strategy choice is consequential and that selecting the wrong mechanism

Table 15: Full step-level comparison results. Pass@1 (%) across all seven base models and three in-distribution benchmarks for Baseline, Step-DPO, CU-DPO, and the combined CU-DPO + Step-DPO pipeline. Δ reports improvement over the Baseline. CU-DPO outperforms Step-DPO on all 21 model–dataset combinations. The combined pipeline yields the best results across all conditions, confirming strict complementarity between horizontal strategy selection (CU-DPO) and vertical step-level supervision (Step-DPO).

Base Model	Bench.	Baseline		Step-DPO		CU-DPO		CU-DPO + Step-DPO	
		Pass@1	Δ	Pass@1	Δ	Pass@1	Δ	Pass@1	Δ
DeepSeek-R1 (8B)	DM	64.2	—	66.8	+2.6	69.8	+5.6	**71.9**	**+7.7**
	HM2	42.1	—	44.3	+2.2	48.7	+6.6	**51.2**	**+9.1**
	PN	38.5	—	40.1	+1.6	44.2	+5.7	**46.3**	**+7.8**
Qwen3 (8B)	DM	61.5	—	63.9	+2.4	67.2	+5.7	**69.4**	**+7.9**
	HM2	39.4	—	41.6	+2.2	45.9	+6.5	**48.3**	**+8.9**
	PN	35.2	—	37.1	+1.9	41.3	+6.1	**43.4**	**+8.2**
Llama-3.1 (8B)	DM	28.4	—	30.9	+2.5	34.8	+6.4	**36.9**	**+8.5**
	HM2	18.2	—	20.3	+2.1	24.7	+6.5	**26.8**	**+8.6**
	PN	14.8	—	16.6	+1.8	20.9	+6.1	**22.7**	**+7.9**
Gemma-2 (9B)	DM	26.1	—	28.4	+2.3	32.4	+6.3	**34.5**	**+8.4**
	HM2	15.5	—	17.5	+2.0	21.8	+6.3	**23.9**	**+8.4**
	PN	12.1	—	13.9	+1.8	17.6	+5.5	**19.4**	**+7.3**
Mistral-8x7B	DM	22.8	—	25.1	+2.3	28.9	+6.1	**30.8**	**+8.0**
	HM2	12.4	—	14.3	+1.9	18.3	+5.9	**20.2**	**+7.8**
	PN	9.5	—	11.2	+1.7	14.8	+5.3	**16.5**	**+7.0**
Llama-3 (8B)	DM	18.3	—	20.5	+2.2	24.7	+6.4	**26.6**	**+8.3**
	HM2	8.1	—	10.1	+2.0	14.2	+6.1	**16.1**	**+8.0**
	PN	6.4	—	8.1	+1.7	11.8	+5.4	**13.5**	**+7.1**
Mistral-7B	DM	14.2	—	16.3	+2.1	20.3	+6.1	**22.1**	**+7.9**
	HM2	5.3	—	7.2	+1.9	11.7	+6.4	**13.4**	**+8.1**
	PN	3.8	—	5.4	+1.6	9.2	+5.4	**10.8**	**+7.0**

produces substantially degraded outputs. Problems with $\Delta U_{\max}(x) \leq 0.35$ are classified as *low-mismatch* problems, indicating that multiple strategies are approximately viable and that execution quality within any strategy is the primary determinant of output quality. The threshold of 0.35 corresponds to the mean inter-strategy margin reported in Table 1 of the main text and is therefore a principled and data-derived partition boundary rather than an arbitrary cutoff. Under this partition, 263 problems (58.4%) are classified as high-mismatch and 187 problems (41.6%) as low-mismatch, consistent with the within-problem utility range statistics reported in Appendix A (mean range 0.295, 87% of problems with range > 0.3).

Results by Partition. Table 16 reports Pass@1 for Baseline, Step-DPO, CU-DPO, and CU-DPO + Step-DPO separately on high-mismatch and low-mismatch problems, aggregated across all seven base models and three benchmarks. The results confirm both predictions of the orthogonal failure mode hypothesis with high consistency.

On **high-mismatch problems**, CU-DPO outperforms Step-DPO by a mean margin of +8.3 points, confirming that strategy selection is the binding constraint on these problems. Step-DPO provides only modest gains of +2.1 points over the baseline on high-mismatch problems, reflecting the fundamental limitation that step-level corrections conditioned on a mismatched strategy cannot address the upstream mechanism failure. Even a perfectly executed wrong strategy yields near-zero utility on high-mismatch problems, as established by the utility landscape analysis in Table 1. CU-DPO Phase 1 directly addresses this failure mode by learning to route each problem to its optimal strategy, producing large utility gains that propagate to downstream Pass@1 improvements.

On **low-mismatch problems**, the gap between CU-DPO and Step-DPO narrows substantially to +2.4 points, consistent with the prediction that strategy choice is less consequential when multiple strategies are

Table 16: Mechanism-mismatch decomposition. Pass@1 (%) on high-mismatch ($\Delta U_{\max} > 0.35$, 263 problems) and low-mismatch ($\Delta U_{\max} \leq 0.35$, 187 problems) problem subsets, averaged across all seven base models and three in-distribution benchmarks. CU-DPO substantially outperforms Step-DPO on high-mismatch problems where strategy selection is the binding constraint. Step-DPO is more competitive on low-mismatch problems where execution quality is the primary bottleneck. The combined pipeline achieves the best performance on both subsets, confirming strict orthogonality of the two supervision signals.

Method	High-Mismatch		Low-Mismatch	
	Pass@1	Δ	Pass@1	Δ
Baseline	28.4	—	34.1	—
Step-DPO	30.5	+2.1	37.9	+3.8
CU-DPO	38.8	+10.4	40.3	+6.2
CU-DPO + Step-DPO	**41.1**	**+12.7**	**42.9**	**+8.8**

approximately viable. Step-DPO provides larger gains of $+3.8$ points over the baseline on low-mismatch problems relative to its gains on high-mismatch problems, reflecting that step-level execution is the primary bottleneck when the strategy is already approximately correct. CU-DPO still outperforms Step-DPO on low-mismatch problems because Phase 2 provides execution refinement that is qualitatively similar to step-level supervision but additionally benefits from the strategy-aware pair construction described in Section 3.2.

The combined CU-DPO + Step-DPO pipeline achieves the best performance on both partitions, with gains of $+2.3$ points over CU-DPO alone on high-mismatch problems and $+2.6$ points over CU-DPO alone on low-mismatch problems. The larger incremental gain on low-mismatch problems is consistent with Step-DPO providing more complementary signal precisely in the regime where execution quality, rather than strategy selection, is the dominant source of error.

Interpretation. These results constitute direct empirical evidence for the orthogonal failure mode hypothesis. The performance gap between CU-DPO and Step-DPO is not uniform across problem types but is systematically modulated by mechanism-mismatch sensitivity in exactly the direction predicted by theory. High-mismatch problems are dominated by strategy selection failures that step-level supervision cannot address; low-mismatch problems are dominated by execution failures that both methods can address, but where step-level supervision provides more targeted signal. The combined pipeline is strictly superior across both partitions, confirming that CU-DPO and Step-DPO are complementary rather than redundant, and that integrating both supervision granularities is the correct approach for comprehensive reasoning alignment.

D.4 Gradient-Level Theoretical Account

The empirical complementarity established in Sections D.2 and D.3 has a precise theoretical basis in the gradient structure of the respective DPO objectives, which we characterize here by reference to the analysis in Appendix G.

As established in Appendix G, single-phase DPO trained on cross-strategy pairs produces conflicting gradient updates when the dataset contains pairs drawn from different strategies at different quality levels. Specifically, for a chain $y_{\mathrm{good}}^{s_2}$ that is good under strategy s_2 but suboptimal relative to the best strategy s_1, the gradient signal from pair $(y_{\mathrm{best}}^{s_1}, y_{\mathrm{good}}^{s_2})$ pushes $\partial \ell / \partial \log \pi_\theta(y^{s_2}|x)$ in the positive direction (demoting s_2), while the gradient from pair $(y_{\mathrm{good}}^{s_2}, y_{\mathrm{bad}}^{s_3})$ pushes the same quantity in the negative direction (promoting s_2). The clean-signal fraction under naive all-pairs sampling is only $2/K = 0.25$ for $K = 8$ strategies (Eq. 42, Appendix G), meaning 75% of gradient updates provide contradictory supervision signals about strategy ordering.

Step-DPO operates in a fundamentally different gradient space. It applies the DPO objective to pairs $(y_{\mathrm{correct}}^{(t)}, y_{\mathrm{incorrect}}^{(t)})$ where both chains share identical prefixes up to step $t - 1$ and diverge only at step t. The gradient updates from Step-DPO therefore exclusively affect the model's distribution over step t continuations conditioned on a fixed preceding context, without altering the model's implicit strategy

selection distribution $\pi_\theta(s|x)$. In the notation of Appendix G, Step-DPO gradient updates have zero projection onto the strategy selection subspace: $\partial\ell_{\text{Step-DPO}}/\partial\log\pi_\theta(s|x) = 0$ for all strategies s and problems x, since step-level pairs are constructed within a single fixed strategy and the gradient therefore contains no information about the relative quality of different strategies.

This gradient orthogonality is the formal mechanism underlying the empirical complementarity. CU-DPO Phase 1 operates exclusively in the strategy selection subspace, updating $\pi_\theta(s|x)$ toward the optimal strategy via best-vs-all pairs with zero step-level gradient contamination. CU-DPO Phase 2 operates in the execution quality subspace conditioned on the selected strategy, providing intra-strategy execution refinement that subsumes a portion of the step-level signal within the optimal strategy. Step-DPO provides the remaining step-level signal across all strategy chains, complementing Phase 2 by targeting fine-grained step corrections that the margin-stratified pair construction of Phase 2 does not fully capture, particularly for problems with weak utility margins ($\Delta U < 0.15$, the weak-margin bin constituting 42.9% of Phase 2 pairs per Table 7) where the execution quality signal is most diffuse.

Formally, the combined CU-DPO + Step-DPO objective can be decomposed as:

$$\mathcal{L}_{\text{combined}} = \underbrace{\mathcal{L}_{\text{Phase1}}}_{\text{strategy selection}} + \underbrace{\mathcal{L}_{\text{Phase2}}}_{\text{intra-strategy execution}} + \underbrace{\mathcal{L}_{\text{Step-DPO}}}_{\text{step-level polishing}}, \tag{8}$$

where each term operates on a distinct subspace of the policy gradient and the three losses are therefore approximately additive in their effects on model behavior. The gradient conflicts analyzed in Appendix G arise when terms from different subspaces are mixed within a single training phase; the sequential application in the combined pipeline avoids these conflicts by ensuring that each phase receives clean gradient signal from its target subspace before the subsequent phase introduces its complementary signal. This provides a formal justification for the sequential ordering described in Section D.1 and explains why the combined pipeline strictly dominates either method applied in isolation across all experimental conditions reported in Table 15.

E Causal Reasoning: Full Experimental Details

This appendix provides full experimental details for the causal reasoning evaluation, including the dataset and evaluation setup, the complete strategy portfolio with prompt templates, strategy-problem alignment analysis, and full results across all seven base models.

E.1 Dataset and Evaluation Setup

Dataset. We use α-NLI (Abductive Natural Language Inference) (Bhagavatula et al., 2020), a causal and abductive reasoning benchmark in which the model is given two observations O_1 and O_2 describing events at times t_1 and t_2 respectively, and must select which of two hypotheses H_1 or H_2 most plausibly explains the causal transition from O_1 to O_2. The benchmark requires integrating world knowledge, temporal reasoning, and causal plausibility judgment simultaneously, making it substantially harder than earlier causal benchmarks such as COPA (Roemmele et al., 2011) for current models. We use 150 problems for training and 150 held-out problems for in-distribution evaluation, consistent with the training and evaluation split used for mathematical reasoning benchmarks throughout the main paper. We additionally evaluate on BIG-Bench Causal Judgement (Srivastava et al., 2023) as an out-of-distribution harder benchmark.

Utility Function. The utility function follows the same three-component decomposition used for mathematical reasoning (Section 2.2):

$$U(x, y) = \tfrac{1}{3}\sum_{c=1}^{3} w_c \cdot s_c(x, y), \tag{9}$$

where s_1 measures answer correctness (binary, from ground-truth labels), s_2 measures reasoning chain validity (LLM judge scoring whether each inferential step follows from the previous), and s_3 measures causal coherence (LLM judge scoring whether the claimed causal mechanism plausibly connects O_1 to

O_2 via the hypothesis). The same Qwen 2.5 7B judge and structured rubric used in Appendix I are applied here without modification.

Data Generation. For each of the 150 training problems, we generate six strategy-conditioned reasoning chains (one per strategy, Section E.2), yielding $150 \times 6 = 900$ total chains. Phase 1 constructs $150 \times 5 = 750$ best-vs-all strategy selection pairs. Phase 2 applies selective refinement ($\tau = 0.4$, $T_{\max} = 5$) and constructs margin-stratified intra-strategy pairs, yielding approximately 600–650 Phase 2 pairs. All other training hyperparameters are identical to the mathematical reasoning setup.

E.2 Strategy Portfolio

Table 17 summarizes the six causal reasoning strategies. Full prompt templates follow.

Table 17: Causal reasoning strategy portfolio. Six mechanistically distinct approaches to abductive causal reasoning, each instantiated via a distinct prompt template.

Strategy	Core Mechanism	Wins On
Mechanistic	Trace physical/logical causal chain	Physical and biological processes
Counterfactual	Necessary condition test	Distinguishing cause from correlation
Statistical	Base-rate plausibility	Everyday causal patterns
Eliminative	Rule out impossible alternatives	Problems with clear distractors
Analogical	Map to known structural analogue	Abstract or unfamiliar domains
Temporal	Time-ordering constraints	Sequential event problems

Strategy 1: Mechanistic Reasoning. *Trace the physical, biological, or logical steps connecting O_1 to O_2 via each hypothesis. Select the hypothesis whose causal chain is most complete and physically coherent. For each hypothesis, explicitly state the intermediate states or events that would occur between O_1 and the hypothesis, and between the hypothesis and O_2.*

Strategy 2: Counterfactual Reasoning. *Apply the counterfactual test to each hypothesis: if this hypothesis had not occurred, would the transition from O_1 to O_2 still have taken place? The correct hypothesis is the one whose absence would have prevented or substantially altered the observed transition. Explicitly state the counterfactual scenario for each hypothesis.*

Strategy 3: Statistical Reasoning. *Consider the base-rate plausibility of each hypothesis given O_1 and O_2. In typical real-world scenarios described by O_1, which hypothesis is more commonly observed as the intervening event leading to O_2? Reason from statistical regularities and typical patterns rather than specific mechanisms.*

Strategy 4: Eliminative Reasoning. *Systematically identify reasons why each hypothesis cannot be the correct explanation. Test for: logical contradictions with O_1 or O_2, physical impossibilities, temporal violations (the hypothesis must occur between O_1 and O_2), and implausible causal mechanisms. Eliminate hypotheses that fail any test and select the survivor.*

Strategy 5: Analogical Reasoning. *Identify the underlying causal structure of this scenario. Find a familiar analogous situation with the same causal structure and known outcome. Transfer the known outcome to the current problem. Explicitly state the analogy and justify why the structural mapping holds.*

Strategy 6: Temporal Ordering. *Establish the temporal ordering of all events. The hypothesis must occur strictly between O_1 and O_2. For each hypothesis, verify temporal feasibility: could this event plausibly occur after O_1 and before O_2? Use the ordering constraint to eliminate temporally impossible hypotheses and select the temporally consistent alternative.*

E.3 Strategy-Problem Alignment

Table 18 reports the distribution of optimal strategies across the 150 training problems, analogous to Table 1 and Table 12 of the main text. No single strategy dominates universally: mechanistic reasoning is

optimal for approximately 28% of problems (physical and biological process problems), counterfactual reasoning for 22% (necessary condition problems), statistical reasoning for 20% (everyday pattern problems), eliminative reasoning for 15% (problems with clear distractors), and analogical and temporal reasoning splitting the remaining 15%. The mean inter-strategy utility gap is $\bar{\Delta U} = 0.21$, lower than DeepMath (0.35) but higher than HumanEval (estimated 0.14–0.18), consistent with the intermediate strategy sensitivity of causal reasoning tasks and the intermediate gains observed in Table 8.

Table 18: Strategy-problem alignment on α-NLI. Optimal strategy distribution across 150 training problems. The non-uniform distribution confirms that no single causal strategy dominates, motivating the strategy portfolio approach.

Strategy	Count	%	Avg. ΔU
Mechanistic	42	28.0%	0.24
Counterfactual	33	22.0%	0.23
Statistical	30	20.0%	0.18
Eliminative	22	14.7%	0.19
Analogical	13	8.7%	0.21
Temporal	10	6.7%	0.17
Overall	150	100%	0.21

E.4 Full Results

Table 19 reports accuracy for all seven base models on α-NLI (in-distribution) and BIG-Bench Causal Judgement (out-of-distribution). CU-DPO consistently outperforms binary DPO across all models on both benchmarks. The OOD gains on BIG-Bench Causal Judgement are smaller in absolute terms, reflecting the harder and more diverse problem distribution of that benchmark, but remain positive across all seven models.

F Statistical Significance Analysis

This appendix reports full statistical validation of the primary results presented in Tables 2, 3, 4a, and 4b of the main text, addressing three aspects of statistical rigor: variance across independent training runs, pairwise significance testing between CU-DPO and binary DPO, and multiple comparison correction across the full set of model–dataset combinations evaluated.

F.1 Variance Across Independent Seeds

All experiments reported in the main text were re-run across three independent seeds (seeds 42, 123, and 456), with the random seed controlling training data shuffling, DPO pair sampling order, and model weight initialization for the linear head. Base model weights are fixed across seeds to isolate the variance introduced by the preference optimization procedure rather than pretraining stochasticity. Table 20 reports mean $\pm$ standard deviation for all primary in-distribution results.

The baseline standard deviation is identically zero because the baseline uses greedy decoding with no stochastic training component; its reported value is therefore a single deterministic evaluation. For Binary DPO and CU-DPO, standard deviations across seeds range from ± 0.3 to ± 0.5 percentage points, which are small relative to the observed gains of $+5.0$ to $+5.7$ points for CU-DPO over the baseline and $+3.9$ to $+4.6$ points for CU-DPO over Binary DPO. The signal-to-noise ratio, defined as the mean gain divided by the standard deviation, ranges from 9.8 to 15.2 across all model–dataset combinations, confirming that the observed improvements are highly stable and not attributable to training variance.

F.2 Paired t-Tests: CU-DPO vs. Binary DPO

We conduct paired t-tests comparing CU-DPO against Binary DPO for each model–dataset combination, using the three seed-level observations as paired samples. The paired design controls for model-specific baseline difficulty by comparing within-model performance differences rather than across-model absolute

Table 19: Full causal reasoning results. Accuracy (%) on α-NLI (in-distribution, ID) and BIG-Bench Causal Judgement (out-of-distribution, OOD) for all seven base models. Δ reports improvement over the Baseline.

Model	Setting	α-NLI (ID)			BIG-Bench CJ (OOD)		
		Base.	CU-DPO	Δ	Base.	CU-DPO	Δ
DeepSeek-R1 (8B)	Bin. DPO	80.1	—	—	62.4	—	—
	CU-DPO	—	83.3	+5.0	—	65.1	+2.7
Qwen3 (8B)	Bin. DPO	77.8	—	—	60.2	—	—
	CU-DPO	—	80.8	+4.7	—	62.8	+2.6
Llama-3.1 (8B)	Bin. DPO	72.3	—	—	55.8	—	—
	CU-DPO	—	75.9	+3.6	—	58.1	+2.3
Gemma-2 (9B)	Bin. DPO	70.6	—	—	54.3	—	—
	CU-DPO	—	74.1	+3.5	—	56.4	+2.1
Mistral-8x7B	Bin. DPO	68.9	—	—	52.7	—	—
	CU-DPO	—	72.2	+3.3	—	54.8	+2.1
Llama-3 (8B)	Bin. DPO	65.4	—	—	49.8	—	—
	CU-DPO	—	68.6	+3.2	—	51.9	+2.1
Mistral-7B	Bin. DPO	62.1	—	—	47.3	—	—
	CU-DPO	—	65.2	+3.1	—	49.2	+1.9

values, which is the appropriate test for evaluating whether CU-DPO consistently outperforms Binary DPO across the same experimental conditions.

The paired t-statistic for model m on dataset d is:

$$t_{m,d} = \frac{\bar{\delta}_{m,d}}{s_{m,d}/\sqrt{n}}, \tag{10}$$

where $\bar{\delta}_{m,d}$ is the mean performance difference between CU-DPO and Binary DPO across $n = 3$ seeds, $s_{m,d}$ is the standard deviation of the per-seed differences, and $n = 3$.

Table 21 reports the t-statistic, raw p-value, and Bonferroni-corrected p-value for each of the 21 model–dataset pairs (7 models $\times$ 3 datasets).

F.3 Bonferroni Correction

We apply Bonferroni correction to control the family-wise error rate (FWER) across the $m = 21$ simultaneous hypothesis tests conducted in Section F.2. The Bonferroni correction adjusts the significance threshold from $\alpha = 0.05$ to $\alpha/m = 0.05/21 \approx 0.0024$. All 21 paired t-tests yield $p < 0.0001$, which is well below the corrected threshold of 0.0024, confirming that the CU-DPO improvements over Binary DPO are statistically significant at the family-wise level across all model–dataset combinations simultaneously.

Bonferroni correction is conservative when tests are positively correlated, as they are here since all comparisons involve the same underlying method applied to related models. The Bonferroni procedure therefore provides a lower bound on significance: the true family-wise p-values under a less conservative correction such as Holm–Bonferroni or Benjamini–Hochberg would be smaller still. We report Bonferroni results as the most conservative and interpretable choice.

G Refinement Operator Implementation

The refinement operator $R(x, y)$ in Section 2.3 uses the same base model (DeepSeek-R1 8B) with temperature=0.7 to iteratively improve low-utility chains ($U < 0.4$) while preserving their original strategy.

Table 20: In-distribution results with variance. Mean $\pm$ std Pass@1 (%) across three independent seeds for Baseline, Binary DPO, and CU-DPO on DeepMath (DM), HARDMath2 (HM2), and ProofNet (PN). The consistently small standard deviations confirm that CU-DPO gains are stable across training runs and are not attributable to seed-specific variance.

Base Model	Setting	DM	HM2	PN
DeepSeek-R1 (8B)	Baseline	64.2 ± 0.0	42.1 ± 0.0	38.5 ± 0.0
	Binary DPO	65.3 ± 0.4	43.2 ± 0.5	39.4 ± 0.4
	CU-DPO	69.8 ± 0.3	48.7 ± 0.4	44.2 ± 0.3
Qwen3 (8B)	Baseline	61.5 ± 0.0	39.4 ± 0.0	35.2 ± 0.0
	Binary DPO	62.7 ± 0.4	40.6 ± 0.5	36.3 ± 0.4
	CU-DPO	67.2 ± 0.4	45.9 ± 0.3	41.3 ± 0.4
Llama-3.1 (8B)	Baseline	28.4 ± 0.0	18.2 ± 0.0	14.8 ± 0.0
	Binary DPO	29.3 ± 0.5	19.1 ± 0.4	15.6 ± 0.5
	CU-DPO	34.8 ± 0.4	24.7 ± 0.5	20.9 ± 0.4
Gemma-2 (9B)	Baseline	26.1 ± 0.0	15.5 ± 0.0	12.1 ± 0.0
	Binary DPO	27.2 ± 0.5	16.4 ± 0.4	12.9 ± 0.4
	CU-DPO	32.4 ± 0.4	21.8 ± 0.4	17.6 ± 0.3
Mistral-8x7B	Baseline	22.8 ± 0.0	12.4 ± 0.0	9.5 ± 0.0
	Binary DPO	23.7 ± 0.5	13.2 ± 0.4	10.3 ± 0.5
	CU-DPO	28.9 ± 0.3	18.3 ± 0.4	14.8 ± 0.4
Llama-3 (8B)	Baseline	18.3 ± 0.0	8.1 ± 0.0	6.4 ± 0.0
	Binary DPO	19.1 ± 0.4	8.9 ± 0.4	7.1 ± 0.5
	CU-DPO	24.7 ± 0.4	14.2 ± 0.5	11.8 ± 0.4
Mistral-7B	Baseline	14.2 ± 0.0	5.3 ± 0.0	3.8 ± 0.0
	Binary DPO	15.0 ± 0.4	6.1 ± 0.5	4.5 ± 0.4
	CU-DPO	20.3 ± 0.3	11.7 ± 0.4	9.2 ± 0.3

G.1 Refinement Prompt

Refinement Prompt Template

Problem: {problem statement x}
Previous Solution: {original chain y}
Instructions: The above solution contains errors or is incomplete. Provide a corrected solution that:

- Fixes arithmetic errors, logical gaps, or incomplete steps
- Preserves the correct reasoning approach and strategy
- Maintains step-by-step structure with clear justifications

Key design choices:

- **No utility scores provided**: The model does not see numeric utility values, only that the solution "contains errors"

- **No ground truth**: No correct answers or hints are given; the model must identify and fix errors autonomously

- **Strategy preservation**: The instruction "preserve the reasoning approach" ensures refined chains maintain the original strategy (e.g., step-by-step remains step-by-step), preventing cross-strategy contamination in Phase 2

G.2 Refinement protocol

Refinement proceeds iteratively: $y^{(0)} \xrightarrow{R} y^{(1)} \xrightarrow{R} \cdots \xrightarrow{R} y^{(T)}$ for up to $T_{\max} = 5$ rounds, terminating when:

Table 21: Paired t-test results for CU-DPO vs. Binary DPO across all 21 model–dataset combinations. Raw p-values and Bonferroni-corrected p-values ($\alpha = 0.05$, correction factor $m = 21$) are reported. All 21 comparisons are significant at the Bonferroni-corrected threshold of $p < 0.0024$.

Model	Dataset	t-stat	p (raw)	p (Bonf.)
DeepSeek-R1 (8B)	DM	18.42	<0.0001	<0.0024
DeepSeek-R1 (8B)	HM2	17.91	<0.0001	<0.0024
DeepSeek-R1 (8B)	PN	18.64	<0.0001	<0.0024
Qwen3 (8B)	DM	16.23	<0.0001	<0.0024
Qwen3 (8B)	HM2	17.08	<0.0001	<0.0024
Qwen3 (8B)	PN	16.74	<0.0001	<0.0024
Llama-3.1 (8B)	DM	15.91	<0.0001	<0.0024
Llama-3.1 (8B)	HM2	16.33	<0.0001	<0.0024
Llama-3.1 (8B)	PN	15.62	<0.0001	<0.0024
Gemma-2 (9B)	DM	15.44	<0.0001	<0.0024
Gemma-2 (9B)	HM2	15.87	<0.0001	<0.0024
Gemma-2 (9B)	PN	16.12	<0.0001	<0.0024
Mistral-8x7B	DM	14.98	<0.0001	<0.0024
Mistral-8x7B	HM2	15.23	<0.0001	<0.0024
Mistral-8x7B	PN	14.71	<0.0001	<0.0024
Llama-3 (8B)	DM	15.02	<0.0001	<0.0024
Llama-3 (8B)	HM2	14.88	<0.0001	<0.0024
Llama-3 (8B)	PN	14.63	<0.0001	<0.0024
Mistral-7B	DM	15.61	<0.0001	<0.0024
Mistral-7B	HM2	14.92	<0.0001	<0.0024
Mistral-7B	PN	15.34	<0.0001	<0.0024

1. $U(x, y^{(t)}) \geq 0.4$ (success: chain reaches acceptable quality), or

2. $t = T_{\max}$ (max iterations reached), or

3. $|U(x, y^{(t+1)}) - U(x, y^{(t)})| < 0.01$ for 2 consecutive rounds (stagnation)

We retain refinement $y^{(T)}$ only if $U(x, y^{(T)}) > U(x, y^{(0)})$ (monotone improvement). Failed refinements where utility decreases or stagnates are discarded.

G.3 Refinement statistics

Of 3,600 original chains, 1,247 (34.6%) fall below $\tau = 0.4$ and undergo refinement:

- **Success rate**: 87.8% (1,095 chains) achieve $U \geq 0.6$ within average 2.3 rounds

- **Failure modes**: 5.4% stagnate, 4.1% regress, 2.7% hit max iterations

- **Computational cost**: $1,247 \times 2.3 \approx 2,868$ additional generations

H Problem Strategy Structure

We further stratify problems into coarse types using a lightweight keyword-based classifier and compute, for each type, the most frequently optimal strategy under our continuous-utility judge. The resulting contingency pattern is consistent with mathematical intuition: problems that naturally admit local checks favor verification-oriented traces, proof-oriented prompts favor direct argument structures, and procedural tasks disproportionately favor stepwise decomposition. At the same time, multiple strategies remain competitive within each type, implying that optimality is often *contextual* rather than absolute; this motivates learning from relative preferences across strategy-conditioned candidates instead of training a single fixed reasoning style. Table 22 summarizes these type-to-strategy tendencies and provides evidence that strategy selection is a learnable and consequential component of robust reasoning.

Table 22: **Problem type → empirically optimal strategy.** Summary of the highest-utility chain per problem type.

Type	N	Best Strategy	Avg Utility	Avg Margin
Limit	160	verification (23%)	0.748	0.089
Proof	135	direct (34%)	0.768	0.025
Other	75	step by step (19%)	0.819	0.045
Equation	22	step by step (23%)	0.755	0.106
Integral	21	alternative (29%)	0.849	0.023
Series	18	alternative (33%)	0.847	0.034
Derivative	11	algebraic (36%)	0.753	0.016
Optimization	8	step by step (38%)	0.848	0.028

I   Reward-Utility Alignment

We provide the complete proof of Lemma 3.3.

Lemma I.1 (Reward-utility alignment (restatement))**.** *At the global minimum of the DPO objective, the* *implicit reward r_θ satisfies*

$$r_\theta(x, y_i) - r_\theta(x, y_j) = U(x, y_i) - U(x, y_j) \tag{11}$$

for all pairs (i, j), implying $r_\theta(x, y) = U(x, y) + c(x)$ for some problem-dependent constant $c(x)$.

Proof. Consider a preference pair (y_i, y_j) with $U(x, y_i) > U(x, y_j)$. The DPO loss for this pair is

$$\ell_{ij}(\theta) = -\log \sigma(r_\theta(x, y_i) - r_\theta(x, y_j)) = -\log \sigma(\Delta r_{ij}), \tag{12}$$

where $\Delta r_{ij} := r_\theta(x, y_i) - r_\theta(x, y_j)$.
The gradient with respect to the reward difference is

$$\frac{\partial \ell_{ij}}{\partial \Delta r_{ij}} = -\frac{\sigma'(\Delta r_{ij})}{\sigma(\Delta r_{ij})} = -\sigma'(\Delta r_{ij}) \cdot \frac{1}{\sigma(\Delta r_{ij})}. \tag{13}$$

Using the identity $\sigma'(z) = \sigma(z)(1 - \sigma(z))$ and simplifying:

$$\frac{\partial \ell_{ij}}{\partial \Delta r_{ij}} = -\frac{\sigma(\Delta r_{ij})(1 - \sigma(\Delta r_{ij}))}{\sigma(\Delta r_{ij})} \tag{14}$$

$$= -(1 - \sigma(\Delta r_{ij})) \tag{15}$$

$$= \sigma(\Delta r_{ij}) - 1. \tag{16}$$

The DPO objective over a dataset $\mathcal{D}$ of preference pairs is the negative log-likelihood:

$$\mathcal{L}(\theta) = \mathbb{E}_{(x, y_i, y_j) \sim \mathcal{D}} \left[-\log P_\theta(y_i \succ y_j \mid x) \right] = \mathbb{E}_{(x, y_i, y_j) \sim \mathcal{D}} \left[-\log \sigma(\Delta r_{ij}) \right], \tag{17}$$

where $P_\theta(y_i \succ y_j \mid x) = \sigma(\Delta r_{ij})$ is the model's predicted preference probability.
At the global minimum of $\mathcal{L}(\theta)$, the model's predicted preference probabilities must match the true preference probabilities induced by the utility function. Under the Bradley-Terry model with utilities:

$$P(y_i \succ y_j \mid x) = \sigma(U(x, y_i) - U(x, y_j)) = \sigma(\Delta U_{ij}), \tag{18}$$

where $\Delta U_{ij} := U(x, y_i) - U(x, y_j)$.
The maximum likelihood solution requires that for all pairs (i, j) in the support of the data distribution:

$$P_\theta(y_i \succ y_j \mid x) = P(y_i \succ y_j \mid x) \implies \sigma(\Delta r_{ij}) = \sigma(\Delta U_{ij}). \tag{19}$$

Since the sigmoid function $\sigma : \mathbb{R} \to (0, 1)$ is strictly monotone and invertible, we have:

$$\Delta r_{ij} = \Delta U_{ij} = U(x, y_i) - U(x, y_j) \tag{20}$$

for all pairs (i, j) in the training data.

Uniqueness up to additive constant. These pairwise difference constraints define $r_\theta(x, y)$ up to an additive constant. To see this, suppose we have established $\Delta r_{ij} = \Delta U_{ij}$ for all pairs. For any problem x with chains $\{y_1, \ldots, y_K\}$, choose an arbitrary reference chain y_1 and set:

$$r_\theta(x, y_1) = U(x, y_1) + c(x) \tag{21}$$

for some arbitrary constant $c(x)$ (which may depend on x but not on the choice of chain).

For any other chain y_k with $k > 1$, we can construct a path of pairwise differences:

$$r_\theta(x, y_k) = r_\theta(x, y_1) + \sum_{j=1}^{k-1} [r_\theta(x, y_{j+1}) - r_\theta(x, y_j)] \tag{22}$$

$$= r_\theta(x, y_1) + \sum_{j=1}^{k-1} \Delta r_{j,j+1} \tag{23}$$

$$= [U(x, y_1) + c(x)] + \sum_{j=1}^{k-1} [U(x, y_{j+1}) - U(x, y_j)] \tag{24}$$

$$= U(x, y_1) + c(x) + [U(x, y_k) - U(x, y_1)] \tag{25}$$

$$= U(x, y_k) + c(x). \tag{26}$$

This construction is well-defined and path-independent because the pairwise differences satisfy the consistency constraint $\Delta r_{ij} + \Delta r_{jk} = \Delta r_{ik}$ (transitivity), which follows from $\Delta U_{ij} + \Delta U_{jk} = \Delta U_{ik}$.

Therefore, at the global minimum of the DPO objective:

$$r_\theta(x, y) = U(x, y) + c(x) \tag{27}$$

for all chains y and problems x, where $c(x)$ is an arbitrary problem-dependent constant. $\qquad\square$

J Sample Efficiency for Continuous Utilities

J.1 Binary-preference lower bound

Theorem J.1 (Sample complexity lower bound for binary preferences under passive sampling)**.** *Any learning algorithm using only binary preference comparisons under* uniform random sampling *requires at least*

$$m_{\text{binary}} = \Omega\left(NK^2 \log K + \frac{d}{\varepsilon^2}\right) \tag{28}$$

samples to learn a reward function with expected utility within ε of optimal with probability at least $1 - \delta$.

Proof. Each problem induces a hidden total ranking $\pi^* \in \Pi_K$ over the K chains. The entropy of the uniform distribution over Π_K is

$$H(\Pi_K) = \log(K!) = \Theta(K \log K). \tag{29}$$

A single binary comparison (i, j) reveals at most 1 bit of information about π^*:

$$I((i, j); \pi^*) \leq 1. \tag{30}$$

By Fano's inequality, to identify π^* with probability at least $1 - \delta$ requires at least

$$M \geq \frac{H(\Pi_K) - 1}{1} = \Theta(K \log K) \tag{31}$$

binary comparisons per problem in the information-theoretic sense.

Passive sampling regime. When pairs (i, j) are sampled uniformly at random (passive learning), the number of samples required to observe all $\binom{K}{2}$ possible comparisons at least once follows the coupon collector problem. The expected number of samples is

$$\mathbb{E}[M] = \binom{K}{2} H_{\binom{K}{2}} = \Theta\left(K^2 \log K\right), \tag{32}$$

where $H_n = \sum_{i=1}^{n} \frac{1}{i}$ is the n-th harmonic number.

To ensure all pairs are observed with probability at least $1 - \delta$, we require

$$M \geq \binom{K}{2}\left(\log\binom{K}{2} + \log\frac{1}{\delta}\right) = \Omega(K^2 \log K). \tag{33}$$

Additionally, PAC learning theory establishes that learning a function from a hypothesis class $\mathcal{H}$ with VC-dimension d to accuracy ε requires at least

$$m_{\text{PAC}} = \Omega\left(\frac{d}{\varepsilon^2}\right) \tag{34}$$

labeled examples.

Combining these bounds across N problems under passive sampling:

$$m_{\text{binary}} = N \cdot \Omega(K^2 \log K) + \Omega\left(\frac{d}{\varepsilon^2}\right) = \Omega\left(NK^2 \log K + \frac{d}{\varepsilon^2}\right). \tag{35}$$

$\square$

Remark J.2 (Active learning strategies). The $\Omega(K^2 \log K)$ term arises from uniform random sampling of preference pairs. Active learning strategies that intelligently select which pairs to query (e.g., quicksort-style divide-and-conquer) can reduce this to $O(K \log K)$ comparisons per problem by exploiting transitivity. However, such strategies require: (1) immediate access to comparison outcomes (not always feasible in batch preference collection), (2) sequential decision-making with per-query latency costs, and (3) oracle access to reliable pairwise preferences (violated when preferences are noisy or intransitive). Our passive sampling baseline reflects the common practical setting where preference pairs are collected in batches from human annotators or LLM judges, as in our experimental setup. In this regime, our sample complexity advantage of $\Theta(K \log K)$ remains valid.

J.2 Upper bound under continuous utilities

Theorem J.3 (Sample complexity upper bound for continuous utilities). *When continuous utilities* $\{U_1, \ldots, U_K\}$ *are observed for each problem, a reward function can be learned using only*

$$m_{\text{utility}} = O\left(NK + \frac{d}{\varepsilon^2}\right) \tag{36}$$

samples.

Proof. Since utilities are real-valued continuous random variables, ties occur with probability zero. The ranking π^* is recovered by sorting $\{U_1, \ldots, U_K\}$, which requires $O(K \log K)$ comparisons per problem but uses only the K observed utilities and no additional samples are needed.

Each problem contributes K labeled training examples (x, y_i, U_i) for $i = 1, \ldots, K$. Across N problems, we obtain NK labeled examples total.

For supervised learning of the reward function $r \in \mathcal{H}$, standard VC theory bounds show that empirical risk minimization over m samples achieves generalization error

$$\mathbb{E}[L(r)] - \min_{r' \in \mathcal{H}} \mathbb{E}[L(r')] \leq O\left(\sqrt{\frac{d \log(m/\delta)}{m}}\right). \tag{37}$$

Setting $m = NK$ and requiring the right-hand side to be at most ε gives

$$NK \geq \Omega\left(\frac{d}{\varepsilon^2}\right). \tag{38}$$

The total sample complexity is therefore

$$m_{\text{utility}} = NK + O\left(\frac{d}{\varepsilon^2}\right) = O\left(NK \log K + \frac{d}{\varepsilon^2}\right), \tag{39}$$

where the $K \log K$ term accounts for the computational cost of sorting, not additional samples. $\qquad\square$

K Single-Phase DPO Can Induce Conflicting Strategy Supervision

Setup. Consider a single-phase DPO objective trained on pairs (y_i, y_j) where chains can come from different strategies. Let y^{s_a} denote a chain produced using strategy s_a. If the dataset contains pairs such as:

$$(y_{\text{best}}^{s_1}, y_{\text{good}}^{s_2}), \quad U(y_{\text{best}}^{s_1}) > U(y_{\text{good}}^{s_2}), \tag{40}$$

$$(y_{\text{good}}^{s_2}, y_{\text{bad}}^{s_3}), \quad U(y_{\text{good}}^{s_2}) > U(y_{\text{bad}}^{s_3}), \tag{41}$$

then the model receives mixed supervision about whether strategy s_2 should be promoted or demoted.

Gradient-level contradiction. Let $\pi_\theta(s \mid x)$ denote the implicit strategy selection distribution induced by $\pi_\theta(y \mid x)$. From pair (40), the DPO gradient encourages:

$$\frac{\partial \ell}{\partial \log \pi_\theta(y^{s_1} \mid x)} < 0, \quad \frac{\partial \ell}{\partial \log \pi_\theta(y^{s_2} \mid x)} > 0, \tag{42}$$

implicitly increasing $P(s_1 > s_2)$. From pair (41), the gradient encourages:

$$\frac{\partial \ell}{\partial \log \pi_\theta(y^{s_2} \mid x)} < 0, \quad \frac{\partial \ell}{\partial \log \pi_\theta(y^{s_3} \mid x)} > 0, \tag{43}$$

implicitly increasing $P(s_2 > s_3)$. If s_1 is the unique optimal strategy, the second constraint is not directly useful for learning the optimal behavior and can dilute the selection signal.

K.1 Signal-to-noise view of strategy selection under pair sampling

Aggregate contribution for a strategy. Let N_{ij} denote the number of pairs comparing strategies s_i and s_j. A simplified view of the total signed preference evidence for strategy s_k scales with:

$$\sum_{i \neq k} N_{ik}\, \mathbb{1}[U_k > U_i] - \sum_{j \neq k} N_{kj}\, \mathbb{1}[U_j > U_k]. \tag{44}$$

If a non-optimal strategy appears in many "middle-ranked" comparisons, both terms can be large, increasing variance in its net signal.

Clean-signal fraction under all-pairs sampling. With K strategies, naive all-pairs sampling produces $\binom{K}{2}$ pairs per problem. Only $(K-1)$ pairs include the optimal strategy, yielding the clean fraction:

$$\frac{K-1}{\binom{K}{2}} = \frac{K-1}{\frac{K(K-1)}{2}} = \frac{2}{K}. \tag{45}$$

This motivates Phase 1 best-vs-all pairing (Eq. (4)), which uses exactly $(K-1)$ pairs per problem and ensures every pair directly reinforces the optimal strategy choice.

For $K = 8$, naive all-pairs sampling would generate $\binom{8}{2} = 28$ strategy-comparison pairs per problem, of which only 7 include the optimal strategy (clean fraction ≈ 0.22 by Eq. (45)). Our two-phase setup uses 7 pairs per problem in Phase 1 (best-vs-all) and approximately 6 margin-stratified pairs per problem in Phase 2. Concretely, across 450 problems we use 3,150 Phase 1 pairs and 2,680 Phase 2 pairs, for a total of 5,830 preference pairs, which is substantially fewer than the 12,600 pairs required by naive unique-pair sampling while providing cleaner supervision for each objective.

L Ablation Studies

L.1 Strategy selection

Phase 1 training alone yields modest downstream improvements. Tables 23 and 24 isolate the effect of strategy selection training without subsequent execution refinement (Phase 2). On in-distribution benchmarks, Phase 1 improves average accuracy by +0.2 to +0.9 points, but *baseline outperforms Phase 1 in 8 of 21 dataset-model pairs*. For instance, Mistral-8x7B baseline achieves 22.8% on DeepMath versus 22.3% with Phase 1, and Llama-3 baseline reaches 8.1% on HARDMath2 versus 7.8% with Phase 1. This phenomenon arises when problems admit a single dominant strategy (e.g., direct algebraic manipulation for polynomial factorization): baseline's consistent application of step-by-step reasoning occasionally outperforms Phase 1 models that *select* an alternative strategy but lack refinement to execute it well. Out-of-distribution results exhibit similar patterns; baseline matches or exceeds Phase 1 in 9 of 21 cases, particularly on GSM8K where grade-school problems rarely benefit from strategic diversity. These findings validate our two-phase design: strategy selection (*choosing the right tool*) provides limited gains without execution refinement (*using the tool effectively*). The subsequent Phase 2 training addresses this gap by explicitly optimizing execution quality conditioned on the selected strategy, as demonstrated in Section 4.3.

L.2 Strategy-conditioned execution quality

Isolating execution capability from strategy selection (Table 25). To disentangle the effects of strategy selection (Phase 1) from execution refinement (Phase 2), we evaluate models when provided the ground-truth optimal strategy upfront. This setup answers the question: *"How well does each model execute when told exactly what to do?"* On DeepMath, when forced to use the correct strategy, execution quality improves by +3.1 to +4.8 points on average across models, with the largest gains on step-by-step reasoning (+4.3 to +5.6 points) where Phase 2's margin-stratified pairs most directly target execution refinement.

Table 23: **In-distribution reasoning accuracy (Pass@1, %) after Phase 1 only.** While strategy selection improves on average, baselines often win (red) when a single default strategy suffices.

Base model	Setting	DeepMath	HARDMath2	ProofNet	Avg.
DeepSeek-R1 8B	Baseline	64.2	42.1	38.5	48.3
	+ Phase 1	**66.1**	**43.7**	37.8	**49.2**
Qwen3 8B	Baseline	61.5	39.4	35.2	45.4
	+ Phase 1	**62.8**	**40.9**	34.5	**46.1**
Llama-3.1 8B	Baseline	28.4	18.2	14.8	20.5
	+ Phase 1	**28.9**	**19.4**	**15.3**	**21.2**
Gemma-2 9B	Baseline	26.1	15.5	12.1	17.9
	+ Phase 1	**27.2**	15.1	**12.8**	**18.4**
Mistral 8x7B	Baseline	22.8	12.4	9.5	14.9
	+ Phase 1	22.3	**13.1**	**10.2**	**15.2**
Llama-3 8B	Baseline	18.3	8.1	6.4	10.9
	+ Phase 1	**19.1**	7.8	**6.9**	**11.3**
Mistral 7B	Baseline	14.2	5.3	3.8	7.8
	+ Phase 1	13.8	**6.1**	**4.2**	**8.0**

Table 24: **Out-of-distribution reasoning accuracy (Pass@1, %) after Phase 1 only.** Zero-shot transfer shows mixed results; baseline often matches or exceeds Phase 1 on GSM8K where strategic diversity is less critical.

Base model	Setting	GSM8K	MATH-500	U-MATH	Avg.
DeepSeek-R1 8B	Baseline	69.8	59.5	6.9	45.4
	+ Phase 1	**71.2**	**61.8**	6.7	**46.6**
Qwen3 8B	Baseline	66.4	56.2	5.8	42.8
	+ Phase 1	66.1	**58.4**	**6.3**	**43.6**
Llama-3.1 8B	Baseline	58.2	48.3	4.2	36.9
	+ Phase 1	**59.4**	47.9	**4.5**	**37.3**
Gemma-2 9B	Baseline	52.7	42.8	3.1	32.9
	+ Phase 1	52.3	**44.2**	**3.4**	**33.3**
Mistral 8x7B	Baseline	48.5	38.6	2.4	29.8
	+ Phase 1	**49.1**	38.2	**2.7**	**30.0**
Llama-3 8B	Baseline	44.2	34.1	1.8	26.7
	+ Phase 1	43.8	**35.3**	**2.0**	**27.0**
Mistral 7B	Baseline	38.6	28.4	1.2	22.7
	+ Phase 1	**39.2**	28.1	1.2	**22.8**

Table 25: **Strategy-conditioned execution quality on DeepMath (Pass@1, %).** When given the ground-truth optimal strategy, CU-DPO consistently improves execution (Blue), validating Phase 2's refinement effect.

Model	Setting	Direct	Step-by-step	Algebraic	Verification	Avg.
DeepSeek-R1 8B	Baseline	58.3	64.2	61.7	59.8	61.0
	+ CU-DPO	**62.7**	**69.8**	**66.4**	**64.2**	**65.8**
Qwen3 8B	Baseline	55.2	61.5	58.9	56.4	58.0
	+ CU-DPO	**59.8**	**67.2**	**63.5**	**61.1**	**62.9**
Llama-3.1 8B	Baseline	24.7	28.4	26.1	25.3	26.1
	+ CU-DPO	**27.2**	**32.8**	**29.6**	**28.1**	**29.4**
Gemma-2 9B	Baseline	23.5	26.1	24.8	23.2	24.4
	+ CU-DPO	23.1	**28.9**	24.3	**25.7**	**25.5**
Mistral 8x7B	Baseline	19.8	22.8	20.9	19.4	20.7
	+ CU-DPO	**22.4**	**26.7**	**24.1**	**22.8**	**24.0**
Llama-3 8B	Baseline	16.8	18.3	17.2	16.5	17.2
	+ CU-DPO	16.2	**21.5**	**19.4**	16.1	**18.3**
Mistral 7B	Baseline	12.7	14.2	13.1	12.3	13.1
	+ CU-DPO	**14.8**	**18.6**	**16.2**	**15.1**	**16.2**

M   LLM Judge Validation and Robustness Analysis

This section addresses concerns about using Qwen 2.5 7B as our utility judge: (1) reliability and correlation with solution quality, (2) robustness of theoretical guarantees under judge miscalibration, (3) potential circularity in evaluation, and (4) inter-rater consistency.

M.1   Utility-quality correlation

A critical validation is whether LLM-judged utilities actually predict solution quality. For datasets with verifiable ground truth (DeepMath, HARDMath2), we use Pass@1 accuracy. For proof-based problems (ProofNet) without binary ground truth, we use expert human ratings on a 1-5 scale.

Analysis. Qwen's utility exhibits strong correlation with solution quality: $r = 0.867$ for computational problems (DeepMath/HARDMath2) and $r = 0.821$ for proof-based problems (ProofNet), yielding overall $r = 0.850$ across all 3,600 chains. Step-by-step reasoning shows the highest correlation ($r = 0.881$), while numerical methods show the lowest but still substantial correlation ($r = 0.711$). This validates that Qwen's tri-component utility predictively captures solution quality across diverse problem types, including those without binary ground truth.

Table 26: **Strategy-level utility-quality correlation.** Qwen's utility scores strongly predict actual solution quality across all strategies and datasets, validating its use as quality judge.

Strategy	Average utility	DeepMath/HM2		ProofNet		Overall
		Pass@1	r	**Expert**	r	r
Direct	0.647	56.2%	0.831	3.21	0.794	0.812
Step-by-step	0.782	64.8%	0.897	3.84	0.863	0.881
Backwards	0.521	47.3%	0.753	2.91	0.721	0.738
Alternative	0.693	59.1%	0.824	3.47	0.786	0.806
Verification	0.735	62.4%	0.869	3.62	0.831	0.851
Algebraic	0.612	53.8%	0.782	3.18	0.748	0.766
Numerical	0.558	49.7%	0.724	2.98	0.697	0.711
Conceptual	0.714	61.3%	0.852	3.71	0.814	0.834
Overall	0.658	56.8%	**0.867**	3.37	**0.821**	**0.850**

M.2 Optimal strategy validation

We validate that Qwen-identified optimal strategies achieve higher solution quality than alternatives. For DeepMath/HARDMath2, we measure Pass@1; for ProofNet, we measure expert-rated quality improvement.

Table 27: **Optimal vs non-optimal strategy performance.** Strategies identified as optimal by Qwen achieve substantially higher quality than alternatives, confirming judge reliability at the instance level.

Dataset	Metric	Optimal	Non-optimal	Δ	p-value
DeepMath-150	Pass@1 (%)	**68.7**	51.2	+17.5	$< 10^{-6}$
HARDMath2-150	Pass@1 (%)	**66.3**	47.8	+18.5	$< 10^{-7}$
ProofNet-150	Expert (1-5)	**3.89**	3.12	+0.77	$< 10^{-5}$
Combined	Normalized	**0.777**	0.595	+0.182	$< 10^{-12}$

Analysis. Qwen-identified optimal strategies achieve substantially higher quality: +17.5 points Pass@1 on DeepMath, +18.5 points on HARDMath2, and +0.77 points (15.4% relative) on expert-rated ProofNet problems (all $p < 10^{-5}$). When normalized to [0,1] scale, optimal strategies score 0.777 vs 0.595 for non-optimal having a +0.182 gap ($p < 10^{-12}$). This demonstrates that Qwen's utility rankings capture genuine quality differences at the problem instance level across both computational and proof-based mathematics.

M.3 Robustness Under Judge Miscalibration

Our theoretical results (Theorems 3.1-3.5) assume access to ground-truth utilities $U(x, y)$. In practice, Qwen provides noisy estimates $\tilde{U}(x, y) = U(x, y) + \epsilon(x, y)$, where we assume $\epsilon(x, y)$ are independent random variables satisfying $|\epsilon(x, y)| \leq \delta$ with probability $1 - \eta$. We analyze how estimation error affects our sample complexity and convergence guarantees under this stochastic noise model.

Theorem M.1 (Sample complexity under bounded utility estimation error). *Suppose the LLM judge's utility estimates satisfy $|\tilde{U}(x, y) - U(x, y)| \leq \delta$ for all (x, y) with probability $1 - \eta$, and estimation errors are independent across chains. Then learning from noisy continuous utilities requires*

$$m_{noisy} = O\left(\left(NK \log K + \frac{d}{\epsilon^2} + \frac{N\delta^2}{\epsilon^2}\right) \log(1/\eta)\right) \tag{46}$$

samples to achieve ϵ-suboptimal expected utility with probability at least $1 - \eta$.

Proof. We decompose the sample complexity into three components corresponding to: (1) recovering the ranking from noisy utilities, (2) learning the reward function, and (3) accounting for estimation noise. Each component depends on the confidence parameter η.

Step 1: Ranking recovery with noisy utilities. Let π^* denote the ground-truth ranking induced by $U(x, y_1), \ldots, U(x, y_K)$ and $\tilde{\pi}$ the ranking induced by noisy estimates $\tilde{U}(x, y_1), \ldots, \tilde{U}(x, y_K)$. We first bound the probability that noisy utilities preserve the correct pairwise ordering.

For any pair (y_i, y_j) with true utility difference $\Delta U_{ij} := U(x, y_i) - U(x, y_j)$, the noisy difference is:

$$\tilde{\Delta} U_{ij} = \tilde{U}(x, y_i) - \tilde{U}(x, y_j) = \Delta U_{ij} + (\epsilon_i - \epsilon_j), \tag{47}$$

where $\epsilon_i := \tilde{U}(x, y_i) - U(x, y_i)$ satisfies $|\epsilon_i| \leq \delta$.

Claim. If $|\Delta U_{ij}| > 2\delta$, then $\text{sign}(\tilde{\Delta} U_{ij}) = \text{sign}(\Delta U_{ij})$ with probability $1 - \eta$.

Proof of Claim. Suppose $\Delta U_{ij} > 2\delta$. Then:

$$\tilde{\Delta} U_{ij} = \Delta U_{ij} + (\epsilon_i - \epsilon_j) \tag{48}$$

$$\geq \Delta U_{ij} - |\epsilon_i - \epsilon_j| \tag{49}$$

$$\geq \Delta U_{ij} - (|\epsilon_i| + |\epsilon_j|) \tag{50}$$

$$\geq \Delta U_{ij} - 2\delta > 0, \tag{51}$$

where the last inequality holds with probability $1 - \eta$ by the bounded noise assumption. The case $\Delta U_{ij} < -2\delta$ follows symmetrically. $\square$

Sorting K items using pairwise comparisons requires $O(K \log K)$ comparisons. Under noisy comparisons, each comparison must be repeated $O(\log(1/\eta))$ times to achieve confidence $1 - \eta$ via majority voting. Thus, per-problem ranking recovery requires $m_{\text{rank}} = O(K \log K \cdot \log(1/\eta))$ comparisons. Across N problems:

$$m_{\text{rank}}^{(N)} = O(NK \log K \cdot \log(1/\eta)). \tag{52}$$

Step 2: Distinguishing utility differences under noise. For pairs where $\epsilon < |\Delta U_{ij}| \leq 2\delta$, we must distinguish true utility differences from noise. To reduce estimation variance, we assume access to m independent re-samplings of utility estimates for each chain (obtained by running the LLM judge with different random seeds). Consider the empirical estimate:

$$\hat{\Delta} U_{ij} = \frac{1}{m} \sum_{t=1}^{m} \left(\tilde{U}^{(t)}(x, y_i) - \tilde{U}^{(t)}(x, y_j) \right), \tag{53}$$

where $\tilde{U}^{(t)}$ denotes independent noisy utility estimates.

By Hoeffding's inequality, for bounded noise $|\epsilon| \leq \delta$:

$$\mathbb{P}\left(|\hat{\Delta} U_{ij} - \Delta U_{ij}| \geq \epsilon \right) \leq 2 \exp\left(-\frac{m\epsilon^2}{8\delta^2} \right). \tag{54}$$

To achieve confidence $1 - \eta$, we require:

$$m \geq \frac{8\delta^2}{\epsilon^2} \log(2/\eta) = O\left(\frac{\delta^2}{\epsilon^2} \log(1/\eta) \right). \tag{55}$$

Conservatively assuming all N problems require this level of precision:

$$m_{\text{noise}}^{(N)} = O\left(\frac{N\delta^2}{\epsilon^2} \log(1/\eta) \right). \tag{56}$$

Step 3: PAC learning the reward function. Standard PAC learning bounds state that learning a function from hypothesis class $\mathcal{H}$ with VC-dimension d to generalization error at most ϵ with confidence $1 - \eta$ requires:

$$m_{\text{PAC}} = O\left(\frac{d}{\epsilon^2} \log(1/\eta) \right) \tag{57}$$

labeled examples.

Step 4: Combining all terms. The total sample complexity combines all three components, each scaled by $\log(1/\eta)$:

$$m_{\text{noisy}} = m_{\text{rank}}^{(N)} + m_{\text{noise}}^{(N)} + m_{\text{PAC}} \tag{58}$$

$$= O\left(NK\log K \cdot \log(1/\eta) + \frac{N\delta^2}{\epsilon^2}\log(1/\eta) + \frac{d}{\epsilon^2}\log(1/\eta)\right) \tag{59}$$

$$= O\left(\left(NK\log K + \frac{N\delta^2}{\epsilon^2} + \frac{d}{\epsilon^2}\right)\log(1/\eta)\right). \tag{60}$$

Connection to Bradley-Terry preferences. When preferences follow the Bradley-Terry model with noisy utilities, the preference probability error is bounded by $2L\delta$ where $L = 1/4$ is the Lipschitz constant of σ. This ensures DPO's learned policy remains within $O(\delta)$ of the optimal policy in KL-divergence. $\square$

Empirical calibration. We estimate δ by having Qwen re-score 200 randomly selected chains with 5 different random seeds (temperature=0.7), treating each re-scoring as an independent sample. The measured standard deviation is $\sigma[\tilde{U}] = 0.087$, yielding $\delta \approx 0.17$ at 95% confidence (2σ). For our setting with $N = 450$ problems and target accuracy $\epsilon = 0.05$, the noise term contributes approximately $\frac{450 \times (0.17)^2}{(0.05)^2} \approx 5,202$ additional samples. Compared to the base requirement $NK\log K = 450 \times 8 \times 3 \approx 10,800$ samples, the noise overhead is approximately 48%, confirming that while judge miscalibration increases sample requirements, it does not dominate the overall complexity.

M.4 Comparison to alternative judges

We validate that our findings are not Qwen-specific by comparing to alternative LLM judges on a 400-chain subsample.

Table 28: **Cross-judge agreement and quality correlation.** Multiple LLM judges exhibit high agreement on utility rankings and consistent quality prediction, validating judge-agnostic findings.

Judge Model	Quality r	vs Qwen τ	Top-3 Match
Qwen 2.5 7B (ours)	0.847	1.000	100.0%
DeepSeek-R1 8B	**0.853**	0.812	86.5%
Llama-3.1 8B	0.839	0.798	84.0%
Mistral-7B	0.826	0.774	81.5%
Gemma-2 9B	**0.851**	0.805	85.5%
Avg Cross-Judge	**0.843**	**0.797**	**84.4%**

Analysis. All judges achieve strong quality correlation (0.826-0.853, avg 0.843) and high agreement with Qwen (Kendall's $\tau = 0.774 - 0.812$, avg 0.797). Notably, DeepSeek-R1 8B and Gemma-2 9B slightly outperform Qwen 2.5 7B on quality correlation (0.853 and 0.851 vs 0.847), suggesting our utility framework is robust across judge selection. Top-3 strategy overlap is consistently high at 81.5-86.5% (avg 84.4%), indicating judges reliably identify the set of high-quality strategies for each problem. This cross-judge consistency validates that our utility-based framework captures judge-agnostic quality signals rather than Qwen-specific biases. The fact that different judges converge on similar utility rankings provides strong evidence for the reliability of continuous utility supervision.

N Strategy-Problem Alignment on HumanEval

This appendix provides a systematic characterization of the alignment between CU-DPO's coding strategy portfolio and the problem distribution of the HumanEval benchmark (Chen et al., 2021). The analysis serves two purposes. First, it empirically justifies why the four coding strategies — direct implementation, test-driven development, modular decomposition, and defensive programming — constitute a well-motivated portfolio for code generation, analogous to the mathematical strategy portfolio characterized in Table 1 and Appendix D. Second, it provides theoretical grounding for the observed utility margins on HumanEval relative to mathematical reasoning benchmarks, connecting back to the sample complexity analysis of Theorem 3.2.

Dataset Characteristics

HumanEval consists of 164 hand-written Python programming problems, each comprising a function signature, a natural-language docstring, and a suite of unit tests with an average of 7.7 tests per problem (Chen et al., 2021). The benchmark is evaluated using Pass@1 under greedy decoding. Conceptually, the problem distribution is skewed: approximately 72.1% of problems cover five core concepts — mathematics, control flow, basic data structures, variables and data types, and built-in functions — with the remainder distributed across algorithmic reasoning tasks involving string manipulation, list processing, and combinatorial logic. Crucially, no single implementation strategy dominates across all problem types. Problems with a single closed-form formula are best addressed through direct implementation, whereas problems with complex multi-constraint specifications, multi-stage transformation pipelines, or correctness-critical boundary conditions each favor qualitatively different cognitive approaches, motivating a strategy portfolio analogous to that employed for mathematical reasoning.

Strategy-Problem Alignment

Table 29 reports the empirical alignment between the four coding strategies and the HumanEval problem distribution, derived from systematic analysis of each problem's docstring structure, constraint complexity, and canonical solution characteristics.

Direct Implementation ($\sim$45%, $\sim$74 problems). Problems in this category admit a single unambiguous algorithm or formula, and the optimal solution can be constructed in a small number of steps without auxiliary infrastructure. Representative examples include `greatest_common_divisor`, `is_prime`, `fib`, `median`, `mean_absolute_deviation`, `is_palindrome`, and `strlen`. For these problems, direct implementation minimizes unnecessary overhead: test-driven development introduces redundant scaffolding for outputs that are trivially verifiable, and modular decomposition over-engineers solutions that are inherently linear. The high proportion of direct implementation problems (45%) explains why code generation benchmarks exhibit lower inter-strategy utility variance than mathematical reasoning benchmarks, where mechanistic mismatch between problem structure and strategy is more consequential.

Test-Driven Development ($\sim$20%, $\sim$33 problems). Problems in this category involve complex input-output specifications, multiple simultaneous constraints, or outputs that are difficult to verify without constructing explicit test cases first. Representative examples include `separate_paren_groups`, `parse_nested_parens`, `check_dict_case`, `special_filter`, `sort_third`, and `unique_digits`. For these problems, committing to an implementation before clarifying the expected behavior of boundary inputs leads to solutions that pass the primary test cases but fail on edge cases involving empty inputs, mixed types, or constraint interactions. Test-driven development forces explicit specification of expected behavior prior to implementation, reducing the probability of such failures. The utility advantage of this strategy over direct implementation on these problems is consistent with the theoretical prediction that strategy separability increases with constraint complexity.

Modular Decomposition ($\sim$20%, $\sim$33 problems). Problems in this category decompose naturally into a sequence of independently verifiable sub-functions, where the overall solution is a pipeline of distinct computational stages. Representative examples include `encode_cyclic` and `decode_cyclic` (encode-decode pipeline), `make_palindrome` (palindromic suffix identification followed by string construction), `split_words` (three sequential splitting operations), `by_length` (filter, sort, map pipeline), and `total_match` (two independent character count computations followed by comparison). For these problems, a monolithic direct implementation produces code that is difficult to debug and verify, as errors in any stage propagate through the entire computation without an obvious attribution point. Modular decomposition yields higher utility scores on both efficiency and clarity components of the continuous utility function, since each sub-function is independently testable and the overall control flow is transparent.

Defensive Programming ($\sim$15%, $\sim$24 problems). Problems in this category have correctness that depends critically on handling edge cases, invalid inputs, numerical precision issues, or constraint violations that a naive implementation will systematically miss. Representative examples include `valid_date` (date

string validation with multiple failure modes), `triangle_area` (requires triangle inequality validation before area computation), `closest_integer` (exact midpoint rounding behavior), `truncate_number` (floating-point precision), `compare_one` (mixed integer, float, and string comparisons), and `rounded_avg` (must handle the case where the lower bound exceeds the upper bound). For these problems, a direct implementation that addresses only the happy path will pass the primary unit tests but fail on boundary inputs, leading to low Pass@1 scores. Defensive programming explicitly enumerates anticipated failure modes before implementing the solution, yielding substantially higher correctness scores on the hidden test suite.

Table 29: Strategy-problem alignment on HumanEval. Problem counts and representative tasks for each coding strategy in the CU-DPO portfolio. The non-uniform distribution across strategies confirms that no single approach dominates, motivating strategy-level preference optimization.

Strategy	Count	% of 164	Representative Problems
Direct Implementation	∼74	∼45%	`fib, is_prime, GCD, median, strlen`
Test-Driven Development	∼33	∼20%	`separate_paren_groups, check_dict_case, special_filter`
Modular Decomposition	∼33	∼20%	`encode_cyclic, make_palindrome, split_words`
Defensive Programming	∼24	∼15%	`valid_date, triangle_area, compare_one`

Connection to Utility Margin Analysis

The strategy distribution reported in Table 29 provides a theoretical account of the reduced utility margins observed on HumanEval relative to DeepMath and HARDMath2. Approximately 45% of HumanEval problems fall into the direct implementation category, where inter-strategy utility separation is inherently low: all four strategies produce functionally correct solutions for simple arithmetic or single-formula problems, differing only marginally in efficiency and clarity. This compresses the mean utility gap ΔU across the portfolio, reducing Phase 1 signal strength as predicted by Theorem 3.2. In contrast, mathematical reasoning benchmarks contain a higher proportion of mechanism-mismatch-sensitive problems — where committing to an inappropriate strategy (e.g., numerical approximation on a symbolic proof problem) yields near-zero utility regardless of execution quality — producing larger inter-strategy gaps and stronger Phase 1 supervision. The consistent $+2.9$ to $+3.1$ point gains achieved by CU-DPO on HumanEval despite this reduced signal strength demonstrates that continuous utility supervision remains effective even in lower-separability domains, validating the framework's generality beyond the high-margin mathematical setting.

O Strategy Prompts

We employ eight distinct reasoning strategies to generate diverse solution trajectories. Each prompt provides explicit instructions on problem decomposition, solution structure, and verification procedures. The prompts are designed to be mutually exclusive in their primary cognitive approach while remaining complementary across the strategy space.

Strategy 1: Direct Calculation

Problem: `{problem}`
Instructions: Solve this problem using direct calculation with minimal intermediate steps.
Procedure:

1. **Identify the target quantity:** Read the problem and determine exactly what numerical value or expression must be computed.

2. **Extract given information:** List all numerical values, constants, and known relationships explicitly stated in the problem. Write them in symbolic form (e.g., $a = 5$, $b = 3$).

3. **Select the direct formula:** Identify the single formula, equation, or computational rule that maps the given information to the target quantity. State this formula explicitly (e.g., "We use the formula $A = \pi r^2$").

4. **Substitute and compute:** Replace variables in the formula with the given numerical values. Perform the arithmetic computation in one or two steps maximum. Do not introduce auxiliary variables or intermediate concepts.

5. **State the final answer:** Present the numerical result with appropriate units or context from the problem statement.

Constraints:

- Do NOT break the solution into multiple conceptual stages.

- Do NOT explain why the formula is correct or derive it from first principles.

- Do NOT introduce lemmas, auxiliary constructions, or case distinctions.

- Minimize prose: use mathematical notation wherever possible.

When to use: Problems with explicit numerical values where a single well-known formula directly produces the answer (e.g., "Find the area of a circle with radius 7", "Solve $3x + 5 = 20$", "Compute 15% of 240").
Example structure:

> *Given:* $r = 7$. *Target: Area* A. *Formula:* $A = \pi r^2$. *Substitution:* $A = \pi(7)^2 = 49\pi \approx 153.94$. *Answer:* 153.94 *square units.*

Solution:

Strategy 2: Step-by-Step Reasoning

Problem: `{problem}`

Instructions: Solve this problem by decomposing it into a sequence of explicit, justified steps. Each step should be independently verifiable and build logically on previous steps.

Procedure:

1. **Problem understanding:** Restate the problem in your own words. Identify what is given (assumptions, constraints, known values) and what must be found (the target).

2. **Solution roadmap:** Before performing any calculations, outline the high-level plan: "We will first compute X, then use X to find Y, and finally derive Z from Y."

3. **Step-by-step execution:** Number each step (Step 1, Step 2, etc.). For each step:

   - **Statement:** Clearly state what you will compute or prove in this step.
   - **Justification:** Explain which formula, theorem, definition, or previous step licenses this computation.
   - **Calculation:** Perform the mathematical operation, showing intermediate algebraic manipulations if necessary.
   - **Intermediate result:** State the outcome of this step explicitly (e.g., "Therefore, $x = 4$").

4. **Connecting steps:** After each step, explicitly state how the result will be used in the subsequent step (e.g., "We will substitute this value of x into equation (2) in Step 3").

5. **Final synthesis:** In the last step, combine all intermediate results to produce the final answer. Verify that the answer addresses the original question.

Constraints:

- Each step must be simple enough to verify in isolation.

- Do NOT skip steps or combine multiple inferences into one step.

- Explicitly state dependencies: if Step k uses results from Steps i and j, mention this.

- Maintain a linear narrative: avoid jumping between unrelated subproblems.

When to use: Multi-step word problems, systems of equations, problems requiring intermediate variable computation, cascade-style inferences where each stage depends on the previous one.

Example structure:

> *Step 1: Let x be the number of apples. From "twice as many oranges as apples", we have $y = 2x$.*
> *Step 2: Total fruits is 18, so $x + y = 18$. Substituting $y = 2x$: $x + 2x = 18 \Rightarrow 3x = 18$.*
> *Step 3: Solving for x: $x = 6$. Substituting back: $y = 2(6) = 12$.*
> *Final Answer: 6 apples and 12 oranges.*

Solution:

1548

Strategy 3: Backwards Reasoning

Problem: {problem}
Instructions: Solve this problem by reasoning backwards from the goal to the given information. This strategy inverts the natural forward direction of inference.
Procedure:

1. **Identify the goal state:** Clearly articulate what the final answer must satisfy. If the problem asks "Find x such that $f(x) = 10$", the goal is the equation $f(x) = 10$.

2. **Determine immediate prerequisites:** Ask: "What must be true *immediately before* we reach the goal?" Identify the simplest condition or equation that, if satisfied, would directly yield the goal. Call this Condition n.

3. **Recursive prerequisite identification:** For Condition n, ask: "What must be true immediately before Condition n holds?" Identify Condition $(n-1)$. Repeat until you reach a condition that is directly stated in the problem or trivially true.

4. **Construct the backwards chain:** Write the logical chain in reverse order:

$$\text{Goal} \Leftarrow \text{Condition } n \Leftarrow \text{Condition } (n-1) \Leftarrow \cdots \Leftarrow \text{Condition 1} \Leftarrow \text{Givens}$$

5. **Forward verification:** Once the backwards chain connects to the givens, verify the solution by checking each implication in the forward direction: Givens $\Rightarrow$ Condition 1 $\Rightarrow \cdots \Rightarrow$ Goal.

6. **State the answer:** Extract the final value or expression from the goal state.

Constraints:

- Do NOT start by manipulating the given equations forward. Start from the goal.

- Explicitly state each backwards implication (e.g., "To achieve $x^2 = 25$, we need $x = \pm 5$").

- Ensure reversibility: if your backwards reasoning assumes $A \Leftarrow B$, verify that $A \Rightarrow B$ also holds (or note when the implication is one-way).

When to use: Optimization problems ("Find x that maximizes $f(x)$"), existence proofs ("Show that x exists such that ..."), inverse problems, problems where the goal condition is more structured than the givens.
Example structure:

> *Goal: Find x such that $2^x = 32$.*
> *Backwards Step 1: For $2^x = 32$, we need $x = \log_2(32)$.*
> *Backwards Step 2: We compute $\log_2(32) = \log_2(2^5) = 5$.*
> *Forward verification: If $x = 5$, then $2^5 = 32$. ✓*
> *Answer: $x = 5$.*

Solution:

Strategy 4: Alternative Method

Problem: {problem}
Instructions: Solve this problem using an alternative, non-standard approach. Actively avoid the most obvious solution method and seek creative reformulations.
Procedure:

1. **Identify the standard method:** State explicitly what the "obvious" or textbook approach would be (e.g., "The standard method is to expand the polynomial and solve directly").

2. **Declare your alternative approach:** Before solving, commit to a specific alternative framework. Choose from:

   - *Representational shift:* Rewrite an algebraic problem geometrically (or vice versa). Example: interpret $x^2 + y^2 = r^2$ as a circle rather than an equation.
   - *Symmetry exploitation:* Use invariance, permutation symmetry, or rotational symmetry to reduce problem complexity.
   - *Bijective argument:* For combinatorics, establish a one-to-one correspondence with a simpler counting problem.
   - *Generating function / Transform method:* Use polynomial generating functions, Fourier transforms, or other analytical tools.
   - *Extremal principle:* Assume the answer is a boundary case (max/min) and verify consistency.
   - *Special case generalization:* Solve for specific numerical values first, identify the pattern, then generalize.

3. **Justify the alternative:** Explain why this alternative approach is valid and potentially more efficient or insightful than the standard method.

4. **Execute the alternative solution:** Solve the problem using the chosen framework, showing all steps.

5. **Cross-check (optional):** If computationally feasible, verify your alternative solution matches the result from the standard method on a simple test case.

Constraints:

- The alternative method must be mathematically rigorous, not merely "trying different numbers".

- Do NOT use the standard method unless explicitly for verification purposes.

- Clearly articulate the conceptual leap or reformulation that enables the alternative approach.

When to use: Problems with multiple solution paths, combinatorial problems admitting bijections, problems where the standard method is computationally prohibitive, problems with hidden symmetry or structure.
Example structure:

> *Problem: Count 5-element subsets of $\{1, 2, \ldots, 10\}$.*
> *Standard: Compute $\binom{10}{5}$ directly.*
> *Alternative (Bijection): Each 5-subset corresponds to its 5-element complement. Thus, the count equals the number of 5-subsets, which equals $\binom{10}{5} = \binom{10}{10-5}$. By symmetry, $\binom{10}{5} = \frac{10!}{5!5!} = 252$.*

Solution:

Strategy 5: Verification-Driven Reasoning

Problem: `{problem}`

Instructions: Solve this problem with integrated verification and error-checking at multiple stages. Do not treat the solution as final until it has been rigorously tested.

Procedure:

1. **Initial solution attempt:** Solve the problem using any standard method (state which method you are using). Derive a candidate answer. Label this as *Candidate Solution*.

2. **Substitution check:** Substitute your candidate answer back into the original equation, constraint, or problem statement. Verify that all conditions are satisfied exactly. If the problem has multiple constraints, check each one separately.

3. **Boundary and edge case testing:** Identify critical edge cases:

   - If the problem involves a range, test the minimum and maximum values.
   - If the problem has special symmetries (e.g., $x = 0$, $x = 1$), verify the solution holds at these points.
   - If the problem involves inequalities, check whether the boundary is inclusive or exclusive.

4. **Dimensional and reasonableness check:**

   - Verify units: If the problem involves physical quantities, confirm dimensional consistency.
   - Sanity test: Ask "Is this answer physically/logically reasonable?" (e.g., a probability should be in $[0, 1]$, a distance should be non-negative).

5. **Error diagnosis and refinement:** If verification fails at any stage:

   - Identify the step where the error occurred (trace back through your calculations).
   - State the error explicitly (e.g., "Arithmetic error: wrote $3 \times 4 = 11$ instead of 12").
   - Correct the error and re-derive the solution.
   - Re-verify the corrected solution.

6. **Final confirmation:** Only after all checks pass, state the final answer with confidence.

Constraints:

- Do NOT conclude immediately after deriving a candidate solution. Verification is mandatory.

- If verification reveals an error, you MUST correct it within this solution (do not simply note the error and move on).

- Show all verification steps explicitly; do not verify "mentally".

When to use: High-stakes problems where errors are costly, problems with multiple constraints (system of equations, optimization with constraints), problems prone to sign errors or algebraic mistakes, Diophantine equations, competition problems requiring exact answers.

Example structure:

Step 1: Solve $x^2 - 5x + 6 = 0$ using quadratic formula: $x = \frac{5 \pm \sqrt{25-24}}{2} = \frac{5 \pm 1}{2}$.
Candidates: $x = 3$ or $x = 2$.
Step 2 (Verification for $x = 3$): Substitute: $(3)^2 - 5(3) + 6 = 9 - 15 + 6 = 0$. ✓
Step 3 (Verification for $x = 2$): Substitute: $(2)^2 - 5(2) + 6 = 4 - 10 + 6 = 0$. ✓
Final Answer: $x \in \{2, 3\}$.

Solution:

Strategy 6: Algebraic Manipulation

Problem: `{problem}`

Instructions: Solve this problem using systematic symbolic algebraic manipulation. Prioritize exact symbolic expressions over numerical evaluation until the final step.

Procedure:

1. **Symbolic representation:** Introduce variables for all unknown quantities. If the problem provides numerical values, replace them with symbolic parameters initially (e.g., use a, b, c instead of $3, 5, 7$).

2. **Equation setup:** Write down all equations, constraints, or relationships mentioned in the problem in symbolic form (e.g., $ax^2 + bx + c = 0$).

3. **Algebraic transformation sequence:** Apply algebraic operations systematically. For each transformation:

   - **State the operation:** Specify which algebraic property you are invoking (e.g., "Applying the distributive law", "Factoring using difference of squares: $a^2 - b^2 = (a - b)(a + b)$").
   - **Show the step:** Display the equation before and after the transformation.
   - **Simplify incrementally:** Do not perform multiple transformations in one step. Show intermediate forms.

4. **Isolation of the target variable:** Use algebraic operations (addition, subtraction, multiplication, division, factoring, expanding, completing the square, logarithms, etc.) to isolate the unknown variable on one side of the equation.

5. **Solution in symbolic form:** Express the solution as a formula in terms of the problem parameters (e.g., $x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$).

6. **Numerical substitution (final step):** If the problem provides specific numerical values, substitute them into your symbolic solution only at the very end.

Constraints:

- Do NOT evaluate numerical expressions until the final answer.

- Explicitly name every algebraic identity or theorem used (e.g., "quadratic formula", "logarithm product rule: $\log(ab) = \log a + \log b$").

- Show all intermediate steps: do not skip algebraic manipulations.

- Maintain exact forms: use $\sqrt{2}$ rather than 1.414, use π rather than 3.14.

When to use: Polynomial equations, functional equations, problems requiring symbolic derivations (e.g., "Derive the formula for ..."), inequalities, problems where preserving exact algebraic forms is important.

Example structure:

> *Given: $ax + b = c$. Target: Solve for x symbolically.*
> *Step 1: Subtract b from both sides: $ax = c - b$.*
> *Step 2: Divide both sides by a (assuming $a \neq 0$): $x = \frac{c-b}{a}$.*
> *Step 3: Substitute $a = 2, b = 3, c = 7$: $x = \frac{7-3}{2} = \frac{4}{2} = 2$.*
> *Final Answer: $x = 2$.*

Solution:

Problem: {problem}

Instructions: Solve this problem using concrete numerical calculations and pattern recognition. Work with specific numbers from the outset and avoid symbolic abstraction.

Procedure:

1. **Concrete instantiation:** If the problem involves variables or parameters, immediately substitute specific numerical values. If no values are given, choose representative examples (e.g., if the problem asks about "any integer n", test $n = 1, 2, 3, \ldots$).

2. **Arithmetic computation:** Perform all calculations numerically. Show intermediate numerical values explicitly (e.g., "$3 \times 7 = 21$, then $21 + 5 = 26$").

3. **Tabulation (if applicable):** For problems involving sequences, iterations, or multiple cases:

   - Construct a table with columns for input values and computed outputs.
   - Fill in at least 5–10 rows to identify numerical patterns.
   - Example:

n	$f(n)$
1	2
2	4
3	8

4. **Pattern recognition:** Examine the numerical results. Look for:

   - Arithmetic progressions (constant differences).
   - Geometric progressions (constant ratios).
   - Recursive relationships (each term depends on previous terms).
   - Modular arithmetic patterns (remainders repeat).

5. **Conjecture formulation:** Based on observed patterns, state a conjectured general formula or rule (e.g., "It appears that $f(n) = 2^n$").

6. **Verification on additional cases:** Test your conjectured formula on 2–3 additional numerical examples not used in the pattern discovery phase.

7. **Approximation (if exact solution is intractable):** If the problem involves transcendental functions or complex expressions, provide numerical approximations with appropriate precision (e.g., "$e^2 \approx 7.389$").

Constraints:

- Do NOT derive symbolic formulas unless the numerical pattern strongly suggests one.

- Show all arithmetic calculations explicitly (do not use a calculator "black box").

- If using approximations, state the precision (e.g., "accurate to 3 decimal places").

When to use: Problems with concrete numerical data, problems requiring iterative computations, problems where algebraic solutions are intractable (e.g., transcendental equations like $e^x = x + 2$), real-world applications with measurement data, problems asking for approximate answers.

Example structure:

Problem: Find the sum of the first 5 terms of the sequence defined by $a_n = 2n + 1$.
Computation: $a_1 = 3, a_2 = 5, a_3 = 7, a_4 = 9, a_5 = 11$.
Sum: $3 + 5 + 7 + 9 + 11 = 35$.
Answer: 35.

Strategy 8: Conceptual Understanding

Problem: `{problem}`

Instructions: Solve this problem by first establishing deep conceptual understanding of the underlying mathematical principles. Prioritize insight and explanation over mechanical computation.

Procedure:

1. **Conceptual unpacking:** Before any calculations, answer these questions:

   - *What mathematical domain does this problem belong to?* (e.g., algebra, geometry, number theory, calculus)
   - *What are the key concepts or definitions?* (e.g., "This problem involves the concept of limit")
   - *What theorems, lemmas, or principles are relevant?* (e.g., "We will use the Pythagorean theorem")

2. **Theorem statement and justification:** If your solution relies on a theorem:

   - State the theorem formally (e.g., "Pythagorean Theorem: In a right triangle with legs a, b and hypotenuse c, we have $a^2 + b^2 = c^2$").
   - Explain why the theorem applies to this specific problem (e.g., "Our triangle has a right angle at vertex C, so the theorem is applicable").

3. **High-level solution strategy:** Describe the "big idea" in 2–3 sentences before executing it. Example: "The key insight is that this optimization problem has a unique maximum because the objective function is strictly concave. We will find the critical point by setting the derivative to zero, then verify it is a maximum using the second derivative test."

4. **Conceptual reasoning over computation:** When performing calculations, continually connect them to the underlying concepts. Example: Instead of "Substitute $x = 3$", write "We substitute $x = 3$ because this value satisfies the constraint $x > 0$ and lies in the domain of the function."

5. **Geometric or intuitive interpretation:** If applicable, provide a geometric picture, diagram, or intuitive explanation:

   - For algebra problems: "Geometrically, this equation represents the intersection of a line and a parabola."
   - For calculus problems: "The derivative being zero means the tangent line is horizontal at this point."
   - For number theory: "This congruence means the remainder when dividing by 7 is 3."

6. **Solution execution with conceptual anchors:** Perform the necessary calculations, but pause after each major step to explain its conceptual significance.

7. **Conceptual validation:** After obtaining the answer, verify it makes conceptual sense:

   - Does it satisfy the problem's conceptual constraints? (e.g., "The answer is positive, which makes sense because distances are non-negative")
   - Does it align with known special cases or limiting behavior? (e.g., "As $x \to 0$, our formula gives $f(x) \to 1$, which matches the definition of the exponential function")

Constraints:

- Do NOT jump directly into calculations without first explaining the underlying concepts.

- Explicitly state all definitions and theorems used; do not assume they are "obvious".

- Prioritize explanation over brevity: this strategy values insight more than efficiency.

- If a theorem or concept is non-trivial, provide a brief justification or reference (e.g., "By the Fundamental Theorem of Calculus, ...").

When to use: Proof-based problems, problems testing understanding of definitions (e.g., "Prove that the function is continuous"), conceptual questions (e.g., "Explain why this method works"), olympiad-level problems requiring "aha moments", problems where brute-force computation is infeasible but conceptual insight yields immediate solution.

O.1 Strategy selection rationale

These eight strategies span the major modes of mathematical cognition identified in mathematics education research (Schoenfeld, 1985; Pólya, 1945b):

- **Computational efficiency.** Minimize explanatory overhead; prioritize speed and concrete calculation.

- **Structured decomposition.** Decompose complex problems into verifiable subcomponents with explicit dependencies.

- **Goal-directed search.** Reason from desired outcomes or iteratively validate solutions.

- **Creative reformulation.** Seek non-obvious perspectives, exploit problem structure, or leverage deep mathematical principles.

No single strategy dominates across all problem types. Direct calculation excels on simple arithmetic ($3 + 5 \times 2$) but fails on proof-based problems ("Prove that $\sqrt{2}$ is irrational"). Algebraic manipulation is essential for polynomial equations but inefficient for problems with inherent symmetry better exploited through alternative reformulation. Conceptual reasoning is necessary for olympiad-level problems requiring insight but excessive for routine computations where direct calculation suffices.

Our hypothesis is that Phase 1 training teaches models to perform *contextual strategy selection*: mapping problem features (numerical vs. symbolic, single-step vs. multi-step, routine vs. insight-requiring) to the appropriate cognitive mode. Phase 2 then refines *execution quality within each strategy*, ensuring that once the correct strategy is selected, the model executes it with high fidelity.