# Explainable Reinforcement Learning Through Goal-Based Explanations

## Abstract

Many algorithms in Reinforcement Learning rely on neural networks to achieve state-of-the-art performance, but this has the cost of making the agents black-boxes, hard to interpret and understand, making their use difficult in trusted applications, such as robotics or industrial applications. To address this lack of explainability, we introduce goal-based explanations, a new explanation mechanism where the agent produces goals and attempts to reach those goals one-by-one while maximizing the collected reward. These goals form the agent's plan to solve the task, explaining the purpose of its current actions (reach the current goal) and predicting its future behavior. To obtain the agent's goals without domain knowledge, we use 2-layer hierarchical agents where the top layer produces goals and the bottom layer attempts to reach those goals. To train those hierarchical agents, we develop HAC-General with Teacher, a generalization of the Hindsight Actor-Critic (HAC) algorithm that maximizes the rewards collected from the environment and does not require the environment to provide an end-goal. The algorithm leverages a black-box agent to vastly improve the training process. A goal is composed of an end state $s$ to be reached and an amount of reward $r$ to be collected.

We demonstrate that leveraging a black-box agent allows HAC-General with Teacher to solve environments that are not solvable using HAC (the current state-of-the-art hierarchical algorithm) even if it is helped by knowing the desired end-goal. The trained hierarchical agent can produce clear and reliable explanations which can be visualized to make them easier to understand for non-experts.

## 1 Introduction

Deep learning has had a huge impact on Reinforcement Learning, making it possible to solve certain problems for the first time, vastly improving performance in many old problems and often exceeding human performance in difficult tasks (Schrittwieser et al., 2019; Badia et al., 2020). These improvements come at a price though: deep agents are black-boxes which are difficult to understand and their decisions are hard to explain due to the complexity and non-obvious behavior of neural networks. In safety-critical applications, it is often fundamental to check that certain properties are respected or to understand what the behavior of the agent will be (García & Fernández, 2015; Bragg & Habli, 2018). Simply observing the behavior of the agent is often not enough, since it might take its actions for the wrong reasons or it might have surprising behavior when faced with an unexpected state. Ideally, the agent would explain its behavior, which would allow for auditing, accountability, and safety-checking (Puiutta & Veith, 2020), unlocking the use of Reinforcement Learning systems in critical areas such as robotics, semi-autonomous driving, or industrial applications.

We provide three contributions to better understand deep agents. First, we develop a new type of explanation for the agent's behavior. Imagine the following scenario: a robotic agent has to traverse a difficult terrain until it reaches a specific building, where it collects a reward. The agent decomposes its task into a series of goals (for example, positions it has to reach) and tries to reach these goals successively until it reaches the reward zone. Knowing the agent's goals would add clarity to its decision-making process: the current goal explains its short-term behavior (the joint movements are done to reach the current goal position) and the remaining goals help us understand the agent's overall plan to solve the task and predict its future behavior. In a way, the agent is explaining its own behavior by explicitly producing the successive goals it is trying to accomplish. We call this plan composed by a series of goals a **goal-based explanation**.

Both model-based reinforcement learning (Moerland et al., 2020) and planning techniques (Fox et al., 2017) appear similar to goal-based explanations but there are important differences that make this technique novel. Goal-based explanations do not require learning a model of the environment (neither the reward function nor the transition function), thus being compatible with both model-free and model-based reinforcement learning. Planning can be a useful explainability technique, but it has a few limitations: it typically requires knowing the end goals, they often cannot be applied to complex Markov Decision Problems and they may have difficulty handling very large or continuous action spaces or state spaces. Our approach suffers from none of these limitations.

Second, we develop a method to create goal-based explanations using hierarchical agents. To obtain the goals, the agent is structured as a 2-level hierarchy of policies, with a goal-picking policy that produces goals and a goal-reaching policy that attempts to reach them. Goals are *(state, minimum desired reward)* pairs, meaning the goal-reaching policy has to reach a specific state in at most $H$ steps and collect a minimum amount of reward along the way. To create a goal-based explanation, the goal-picking policy is queried repeatedly: given the agent's state $s$, we query for the current goal $g_1 = (s_1, r_1)$; we then assume the agent reaches the state $s_1$ and query for the next goal $g_2 = (s_2, r_2)$; this process repeats until the desired amount of goals has been collected.

Our third contribution is developing a new algorithm to train hierarchical agents, which we denote HAC-General. This algorithm builds upon the Hindsight Actor-Critic (HAC) algorithm (Levy et al., 2019), extending it to environments that do not provide an explicit end-goal. Instead of trying to reach the end-goal as fast as possible and ignoring the environment's rewards, the HAC-General algorithm trains the agent to maximize the collected reward. Our extension tries to preserve the key property that makes the Hindsight Actor-Critic algorithm effective: having an effective strategy to deal with non-stationarity by giving the illusion that the policies in sub-levels are optimal. The HAC-General algorithm is also able to leverage a black-box expert to improve and speed up the training for the hierarchical agent.

## 2 BACKGROUND & RELATED WORK

### 2.1 EXPLAINABLE REINFORCEMENT LEARNING

The Reinforcement Learning community has recognized the need for interpretable and explainable agents, and researchers have developed several methods to add explainability and interpretability. Puiutta & Veith (2020) survey explainability techniques; we briefly describe some key methods.

To add interpretability, *saliency-map methods* determine the importance of each input feature for the policy when it generates its output. Perturbation-based methods (Greydanus et al., 2018) measure importance by perturbing different parts of the input and measuring the change in the policy's output. The larger the change in output, the more important the feature; the magnitude of the change quantifies the relative importance of features, making it possible to build the saliency map. In object-based saliency maps (Iyer et al., 2018), in addition to measuring the importance of raw features, they also measure the importance of the whole objects present in the image. The importance of each object is measured by masking it and measuring the change in the policy's output. Thus, a higher-level object saliency map is created which can be more easily interpreted by non-experts.

Another approach is to *distill* the policy of the black-box agent into a simpler, more interpretable model while trying to preserve the behavior and performance of the black-box policy. Coppens et al. (2019) distill the black-box policy into a soft decision tree, a type of decision tree where the leaves output a static distribution over the actions and the inner nodes select the sub-branch using a logistic model. A different approach is taken by Liu et al. (2019) which distill the model into a linear model U-Trees, a type of decision tree in which leaf nodes use a linear model to produce their output (Q-values) instead of outputting a constant value. Both types of decision trees are more interpretable since they follow clear and simpler rules to go down the tree and to pick the output value.

To avoid the problem of having a black-box, another approach is to create inherently interpretable agents, without the need for a post-processing step such as creating saliency maps or distillation. Among these intrinsic methods are structural causal models (Madumal et al., 2020) which rely on structural equations to explicitly model the causal link between actions and their effect on the environment, and then use those causal links to pick actions which have a favorable effect. Since

this model captures explicit causal relationships, it has inherent explainability. A different approach is to explicitly specify the degree of complexity that the model can have and then find the best model within that class of complexity. Hein et al. (2018) pick algebraic equations as their class of models. The number of operations done in the equation is limited according to the maximum allowed complexity and good policies are found using genetic approaches. For visual or high-dimensional inputs, models that incorporate attention-like mechanisms focus on some part of the input, adding some explainability since it shows which features the model focused on (Yang et al., 2018).

## 2.2 HIERARCHICAL REINFORCEMENT LEARNING

In Hierarchical Reinforcement Learning (HRL), an agent is composed of a hierarchy of policies. The top layer decomposes the task into sub-tasks, the layer below decomposes sub-tasks into sub-sub-tasks, and so on until the lowest level receives a low-level task and attempts to solve it by interacting with the environment. Policies at higher layers learn to act at higher temporal and abstraction levels.

A subtask $\phi^i$ can be defined in multiple ways, for example as simpler linearly solvable Markov Decision Problem (Earle et al., 2018) or as a tuple $(P^i, C^i_{comp}, R_i)$ were the subtask $\phi^i$ is eligible to start any time the precondition $P_i$ is satisfied and it is completed once the current state is part of the completion set $C^i_{comp}$ upon which it receives a reward $r^t \sim R_i$ (Sohn et al., 2020).

Our approach is based upon **goal-oriented** hierarchical reinforcement learning, where completing a task means reaching a goal where that goal typically is a state $s$ which the agent must reach. Policies that receive a goal have only $H$ steps to reach it instead of an unlimited time budget. The policy at the bottom of the hierarchy interacts with the environment while the other policies act by picking goals (i.e. their actions are goals for the policy below them). In some problem settings the reward must be maximized. However, in other settings, the agent receives a goal $g_{env}$ from the environment which must be reached as fast as possible. In that setting, it is important to note that the agent ignores the rewards produced by the environment; it only uses its internal reward scheme which gives the agent a small negative reward at each step, encouraging it to find short paths.

While goal-oriented hierarchical reinforcement learning has a long history (Dayan & Hinton, 1992), there has been a resurgence in interest in recent years. Hierarchical-DQN (Kulkarni et al., 2016) combines hierarchical learning with deep learning for the first time; Hierarchical Actor-Critic (Levy et al., 2017) improves performance by carefully setting up the hierarchy of actor-critic policies; Deep Feudal Reinforcement Learning (Vezhnevets et al., 2017) use abstract goals in a latent space instead of an actual state in the real state space $\mathcal{S}$. More recently, Hierarchical Learning with Off-Policy Correction (Nachum et al., 2018) tries to support off-policy learning even though that all layers are constantly evolving by correcting the goals present in the transitions using a heuristic method.

Our work leverages the Hindsight Actor-Critic (Levy et al., 2019) algorithm which achieves state-of-the-art performance by addressing the key problem in hierarchical reinforcement learning: the *non-stationarity problem*. Since all levels in the hierarchy are training at the same time, a policy at level $l$ must continuously adapt to the changes of the policies below it in the hierarchy. This non-stationarity makes training difficult; in fact, the policy at level $l$ may train successfully only when all the policies below it in the hierarchy have stabilized.

The key insight of Hindsight Actor-Critic is that optimal policies are static and therefore stable, so if the policy at level $l$ could assume that the policies below it were optimal and therefore stationary, then it would train faster and more efficiently. To create this illusion that the policies below are optimal, the algorithm relies on carefully constructing 3 types of transitions, where a transition is a tuple of the form *(state, action, reward, next state, goal, discount)*. Due to space reasons, we detail the 3 types of transitions and their purpose in Appendix A.

## 3 GENERALIZED HINDSIGHT ACTOR-CRITIC

While the Hindsight Actor-Critic (HAC) algorithm achieves good results in specific settings such as maze environments, it is designed for a very specific setting: environments that provide an end goal and where the objective is to reach the goal as fast as possible.

This specialization leads to 2 limitations: (1) HAC requires a goal, making it incompatible with all environments which do not provide a goal for the agent and (2) HAC ignores the rewards given by

Figure 1: Interaction between a HAC-General hierarchical agent with 2 levels of policies and the environment. The goal-picking policy at the top produces goals and the goal-reaching policy at the bottom interacts with the environment to reach those goals in at most $H$ steps. The environment produces a reward and the state changes at each interaction. The objective of the goal-picking policy at the top is to pick goals that maximize the reward that is collected, while the objective of the goal-reaching policy at the bottom is to reach the goal states and collects at least the desired amount of reward dictated in the goal.

the environment since it uses an internal reward scheme. This makes it inapplicable to the majority of environments, in which rewards can be given at any point.

To address these issues, we generalize HAC, creating the **HAC-General** algorithm which doesn't require a goal and that considers the reward given by the environment. To avoid requiring a goal, the policy at the top of the hierarchy (the goal-picking policy) produces its output (a shorter-term goal) using only the state as input (no end goal in the input). To take into account the rewards, the objective of the goal-picking becomes picking goals such that the maximum amount of reward is collected during the episode. The objective of policy at the bottom of the hierarchy (the goal-reaching policy) stays the same: reaching the short-term goal in at most $H$ steps; it ignores environment rewards.

### 3.1 PRESERVING THE OPTIMALITY ILLUSION

These changes address the 2 limitations of HAC, but they break the optimality illusion that makes HAC's training process effective: giving the goal-picking policy the illusion that goal-reaching policy below it acts optimally. Figure 2 shows how the HAC algorithm creates the optimality illusion (assuming environment rewards can be ignored): if the goal-reaching policy fails to reach the goal-picking policy's action $g$ and reaches $s$ instead, $a$ is replaced by the hindsight action $s$.

(a) Original action            (b) Hindsight action

Figure 2: The optimality illusion created by HAC: the goal-reaching policy doesn't reach the original action/goal but after replacing the original goal/action by the hindsight action it appears optimal.

This technique breaks down in the more general setting where environment rewards matter and must be maximized. Replacing $g$ by $s$ is not enough anymore to give the illusion that the goal-reaching acted optimally: while it reached state $s$, the goal-reaching policy might not have collected the

maximum amount of reward possible. As shown in Figure 3, there might be an alternative path to the same final state where more reward would have been collected. In most environments, it is unfortunately impractical to determine if the optimal path was taken (or what the optimal path is).

Figure 3: Now that rewards matter, reaching the goal isn't enough to guarantee optimality: the highest-reward path to the goal must be picked.

To address this issue, HAC-General uses a new definition of goals. The new goals have 2 components: a state $s$ which must be reached and a minimum amount of reward $r_{min}$ which must be collected. As shown in Figure 4, if the original action/goal is $(s, r_{min})$ but the goal-reaching policy reaches instead $s'$ and collects $r'$ reward, then the goal-picking policy's action is replaced by the hindsight action $(s', r_{hindsight})$ where $r_{hindsight} \leq r$, creating again the optimality illusion. It is important to note HAC-General creates the same 3 types of transitions as HAC; the major change is the way goals are defined.

(a) Original action                    (b) Hindsight action

Figure 4: HAC-General re-creates optimality by re-defining goals as a *(state, desired reward)* pair. If we replace the original action by the hindsight action, the goal-reaching policy looks optimal again. This is true because optimality was relaxed: the policy must collect at least the desired reward to appear optimal, but not necessarily the maximum amount possible of reward.

The goal-picking policy now has 2 mechanisms to maximize the reward it collects[1]: (1) pick goal states $s$ that lead to high rewards and (2) force the goal-reaching policy to take a high-reward path to $s$ by making the minimum reward threshold $r_{min}$ as high as possible.

## 3.2 Leveraging the Black-Box Agent

We can leverage the black-box non-explainable agent to train the explainable agent more quickly and efficiently. The black box agent acts as a teacher which provides partial demonstrations to the explainable hierarchical agent, which acts as a student. Since the goal of this paper is to create an explainable agent and there is no requirement that it should be trained from scratch with no help, leveraging a black-box agent does not contradict our chosen setting.

During an episode, the goal-picking policy produces a series of goals and the goal-reaching policy tries to reach each of those goals. To train the goal-producing policy of the hierarchical agent, we need to obtain goals from the black box expert but the expert doesn't produce any goals explicitly since it is not a hierarchical agent. However, it produces goals implicitly: if we let the expert act for roughly $H$ steps, the last states it reaches are good goals. Additionally, the expert reached those final states using a series of actions $a_1, ..., a_n$ that can be used to train the goal-reaching policy.

---

[1]Note: during the training process, the agent must learn to pick both good states and good desired rewards

Therefore, during an episode, each time a new goal needs to be picked, we stochastically decide whether the hierarchical agent or the black-box expert acts. If the black-box expert is chosen, it acts for a number $n \in [0.75H, H]$ of steps, reaching the state $s_n$ and collecting a total reward $r_n$

Given the last state we can create a goal $g_{hindsight} = (s_n, r_{hindsight})$ where $r_{hindsight} \leq r_n$. The algorithm then proceeds as usual, creating the transitions as if it was the goal-picking policy in the hierarchy that had picked the goal. To train the goal-reaching policy, for each action $a$ taken by the expert agent while it was reaching for $s_n$ we create a transition as if had been the goal-reaching policy acting with the short-term goal $g_{hindsight}$.

By interleaving the use of the hierarchical agent and the black-box expert during an episode, the behavior cloning problem is avoided (Ross & Bagnell, 2010) which ensures the hierarchical agent can achieve good performance even in states outside the expert-induced state distribution, *i.e.* even if it is in a state the expert would rarely or never visit when it interacts with the environment by itself (without the intervention of the hierarchical agent).

Algorithm 1 shows the pseudo-code to train a specific level (Appendix B contains the full pseudo-code). The HAC-General With Teacher algorithm uses the generalized goals with a desired state $s$ which must be reached and a minimum reward threshold $r_{min}$ which must be collected. It interleaves the use of the black-box expert and the hierarchical algorithm during an episode, to leverage the effective behavior of the expert to train the hierarchical agent more efficiently. *Note*: the 3 types of transitions created in the algorithm are detailed in Appendix A

---

**Algorithm 1:** Train-Level function of HAC-General (With Teacher)

---

1   **Input**: Initialized hierarchy of actor-critics with $k$ levels
2   **Input**: Expert policy $\pi^*$
3   **Input**: Probability C of using the teacher
4   **Function** `TrainLevel` (*level $l$, state $s$, goal $g$, $\pi^*$, $C$*) :
5     $s_i, g_i, cumulR \leftarrow s, g, 0$
6     **repeat**
7       Decide if will test action/subgoal
8       Pick action $a_i$
9       **if** $l > 0$ **then**
10         **if** *useTeacherInIterationRandomly(C)* **then**
11           $s_i', r, \text{lowLevelTransitions} \leftarrow \textbf{expertRollout}(s_i, \pi^*)$
12           $a_i \leftarrow [s_i', \textbf{reduceReward}(r)]$
13           Replay Buffer$_0$ $\leftarrow$ lowLevelTransitions
14         **else**
15           Determine whether to test subgoal $a_i$
16           $s_i', r \leftarrow$ `TrainLevel` $(l-1, s_i, a_i, \pi^*, C)$
17       **else**
18         Execute primitive action $a_0$
19         Observe next state $s_0'$ and reward $r$
20
21       $cumulR \leftarrow cumulR + r$
22       Create subgoal testing transition if failed to reach the subgoal and testing subgoals
23       Create the hindsight action
24       Create the hindsight action transition
25       Create incomplete hindsight goals transitions and put them in the HER buffer
26       $s_i \leftarrow s_i'$
27     **until** *episode ended **OR** (H steps done or until any goal from above $g_{n, l \leq n < k}$ is reached)*;
28
29     Complete hindsight goal transition in buffer using HER and move them to the replay buffer
30     Return the final state $s_i$ and total reward $cumulR$

---

## 4 EXPERIMENTS

The goal of our experiments is to evaluatethe HAC-General With Teacher algorithm in environments that provide no goal and can give a reward at any step. We compare 3 different algorithms: HAC-General with Teacher, HAC-General without Teacher, and the original HAC algorithm (to which we manually provide the end goal). We then use the trained hierarchical agent to generate explanations, which are visualized, showing the agent's plan to collect as much reward as possible.

We evaluate the agent in 2 environments from the Open AI Gym (Brockman et al., 2016) which present different challenges: Mountain Car Continuous and Lunar Lander Continuous. In Mountain Car, a car has to reach the top of a mountain to its right but does not have enough power to reach it directly; it has to move left and then leverage momentum to reach the right mountain. The challenge of Mountain Car is good exploration since it only gets a positive reward at the top of the mountain but random exploration will very rarely lead to it; for other actions it is punished through small negative rewards. In the Lunar Lander environment, a lander has to stabilize and land on the ground softly. This environment has more complex dynamics than Mountain Car, higher dimensional states (which makes picking good goals harder), and more complex actions for controlling the engines. The main challenge is predicting good states and desired rewards for the short-term goals, and learning how to reach those high dimensional goal states.

Figures 5 displays the performance of the HAC, HAC-General Without Teacher and HAC-General With Teacher algorithms. As we can see HAC achieves good performance in the Mountain Car (likely through knowing the end goal in an environment where exploration is the main challenge) but fails to solve the more complex Lunar Lander environment (despite knowing the end goal). HAC-General Without Teacher solves the Mountain Car environments on some runs and fails on others but always fails to solve Lunar Lander. However, HAC-General With Teacher can solve both environments beating the other hierarchical algorithms and demonstrating how effective leveraging a black box expert can be to train the explainable hierarchical agent.

(a) Mountain Car          (b) Lunar Lander

Figure 5: Evolution of the performance of the agent during the training process in the Mountain Car and Lunar Lander environments. The HAC-General With Teacher outperforms both competing algorithms, showing both its ability to be effective despite being in a more general and harder setting than HAC and the usefulness of leveraging a black box expert during training.

### 4.1 CREATING GOAL-BASED EXPLANATIONS

Given a trained hierarchical agent, we can leverage its goal-picking component to explain the agent's actions and future behavior. The current goal explains the short-behavior of the agent since it reveals the state the agent is trying to reach. We can obtain more useful explanations by querying for a series of goals instead of only knowing the current goal. These goals form the agent's plan to solve the environment and collect the maximum amount of reward; the goals help the user understand the agent's present and future behavior. To obtain this series of goals, the goal-picking policy is queried repeatedly: given the agent's state $s$, we query for the current goal $g_1 = (s_1, r_1)$; we then assume the agent reaches the state $s_1$ and query for the next goal $g_2 = (s_2, r_2)$; this process repeats until the desired amount of goals has been collected.

Figure 6 displays the goal-based explanations at different time-steps of an episode, for both environments. If the goal-reaching policy has good performance and the goal-picking policy is not too sensitive to small changes to the input state, then the explanations have several attractive properties:

- **Good predictive abilities**: if we generate a plan $P$ at state $s$ and then let the agent act, it will reach each of the goals in $P$ (or come close to them). Thus, these goals are an effective tool to predict the future behavior of the agent for the whole episode, given a single state. Appendix C shows statistics on the percentage of goals that are reached.

- **Smoothness**: if we generate a plan $P_1$ at time-step $t$ and another plan $P_2$ at time-step $t+1$, the goals in $P_2$ should be roughly equal to the goals in $P_1$ shifted by the effect of one action.

- **Resistance to small errors**: if the agent fails the reach the next goal in the plan by a small amount, the remainder of the plan stays relevant because the goal-picking policy isn't overly sensitive to small changes in input state. Therefore, the rest of the plan is still useful even though it might be less accurate than if the state was reached.

- **Dynamic**: the plans can be created from any state $s$, which makes it possible to re-create the plan if the goal-reaching fails to reach the goal or an unexpected stochastic events happens in the environment. This acts as a safety measure in case the plan becomes invalid.

(a) Mountain Car          (b) Lunar Lander

Figure 6: Explanations produced by the hierarchical agent at different time steps of an episode. The red or yellow rectangle indicates the current goal. A plan composed of goals $g_1, g_2, ...$ is generated given the current state and shown as progressively darker green rectangles. A video version of the explanations is provided in the supplementary material.

## 5   CONCLUSION

In this paper, we tackle the problem of understanding the decisions taken by deep reinforcement learning agents, which tend to be inscrutable black-boxes. We develop a new technique to understand agents, **goal-based explanations**, in which the agent explicitly produces a series of goals and attempts to reach those goals one by one, collecting as much reward as possible along the way. These goals make the agent more explainable since the agent's current behavior is clear (reach the next goal) and the user knows the agent's long term plan for solving the task. Given certain assumptions, these goal-based plans are smooth, resistant to small misses to the goal, and predict well the future behavior of the agent.

To create the goals, we rely on a 2-layer **hierarchical agent**, where the top layer produces goals and the bottom layer attempts to reach these goals. We contribute a new algorithm to train hierarchical agents, which we call **HAC-General With Teacher**, which generalizes the Hindsight Actor-Critic (HAC) algorithm. Contrarily to HAC, HAC-General attempts to maximize the reward collected from the environment and doesn't require the environment to provide an end goal the agent must reach. HAC-General is also able to leverage black-box agents to improve the training process of the hierarchical agent. We detail possible improvements in Appendix D and note that the algorithm can be adapted to accommodate different definitions of goals, allowing for further research.

Our experiments show that HAC-General can train hierarchical agents to solve certain environments (Mountain Car and Lunar Lander) where the previous state-of-the-art hierarchical algorithm HAC failed. The trained hierarchical agent produces reliable and **clear explanations** which can be visualized, helping users understand the agent's short-term and long-term behavior.

# REFERENCES

Adrià Puigdomènech Badia, Bilal Piot, Steven Kapturowski, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, and Charles Blundell. Agent57: Outperforming the atari human benchmark. *CoRR*, abs/2003.13350, 2020. URL https://arxiv.org/abs/2003.13350.

John Bragg and Ibrahim Habli. What is acceptably safe for reinforcement learning? In Barbara Gallina, Amund Skavhaug, Erwin Schoitsch, and Friedemann Bitsch (eds.), *Computer Safety, Reliability, and Security - SAFECOMP 2018 Workshops, ASSURE, DECSoS, SASSUR, STRIVE, and WAISE, Västerås, Sweden, September 18, 2018, Proceedings*, volume 11094 of *Lecture Notes in Computer Science*, pp. 418–430. Springer, 2018. doi: 10.1007/978-3-319-99229-7\_35. URL https://doi.org/10.1007/978-3-319-99229-7_35.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *CoRR*, abs/1606.01540, 2016.

Youri Coppens, Kyriakos Efthymiadis, Tom Lenaerts, and Ann Nowe. Distilling deep reinforcement learning policies in soft decision trees. In *Proceedings of the IJCAI 2019 Workshop on Explainable Artificial Intelligence*, pp. 1–6, 8 2019.

Peter Dayan and Geoffrey E. Hinton. Feudal reinforcement learning. In Stephen Jose Hanson, Jack D. Cowan, and C. Lee Giles (eds.), *Advances in Neural Information Processing Systems 5, [NIPS Conference, Denver, Colorado, USA, November 30 - December 3, 1992]*, pp. 271–278. Morgan Kaufmann, 1992.

Adam Christopher Earle, Andrew M. Saxe, and Benjamin Rosman. Hierarchical subtask discovery with non-negative matrix factorization. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=ry80wMW0W.

Maria Fox, Derek Long, and Daniele Magazzeni. Explainable planning. *CoRR*, abs/1709.10256, 2017. URL http://arxiv.org/abs/1709.10256.

Javier García and Fernando Fernández. A comprehensive survey on safe reinforcement learning. *J. Mach. Learn. Res.*, 16:1437–1480, 2015. URL http://dl.acm.org/citation.cfm?id=2886795.

Samuel Greydanus, Anurag Koul, Jonathan Dodge, and Alan Fern. Visualizing and understanding atari agents. In Jennifer G. Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1787–1796. PMLR, 2018.

Daniel Hein, Steffen Udluft, and Thomas A. Runkler. Interpretable policies for reinforcement learning by genetic programming. *Eng. Appl. Artif. Intell.*, 76:158–169, 2018.

Rahul Iyer, Yuezhang Li, Huao Li, Michael Lewis, Ramitha Sundar, and Katia P. Sycara. Transparency and explanation in deep reinforcement learning neural networks. In Jason Furman, Gary E. Marchant, Huw Price, and Francesca Rossi (eds.), *Proceedings of the 2018 AAAI/ACM Conference on AI, Ethics, and Society, AIES 2018, New Orleans, LA, USA, February 02-03, 2018*, pp. 144–150. ACM, 2018.

Tejas D. Kulkarni, Karthik Narasimhan, Ardavan Saeedi, and Josh Tenenbaum. Hierarchical deep reinforcement learning: Integrating temporal abstraction and intrinsic motivation. In Daniel D. Lee, Masashi Sugiyama, Ulrike von Luxburg, Isabelle Guyon, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 3675–3683, 2016.

Andrew Levy, Robert Platt Jr., and Kate Saenko. Hierarchical actor-critic. *CoRR*, abs/1712.00948, 2017.

Andrew Levy, George Dimitri Konidaris, Robert Platt Jr., and Kate Saenko. Learning multi-level hierarchies with hindsight. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA*, 2019.

Guiliang Liu, Oliver Schulte, Wang Zhu, and Qingcan Li. Toward interpretable deep reinforcement learning with linear model u-trees. In Michele Berlingerio, Francesco Bonchi, Thomas Gärtner, Neil Hurley, and Georgiana Ifrim (eds.), *Machine Learning and Knowledge Discovery in Databases*, pp. 414–429, Cham, 2019. Springer International Publishing. ISBN 978-3-030-10928-8.

Prashan Madumal, Tim Miller, Liz Sonenberg, and Frank Vetere. Explainable reinforcement learning through a causal lens. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pp. 2493–2500. AAAI Press, 2020. URL https://aaai.org/ojs/index.php/AAAI/article/view/5631.

Thomas M. Moerland, Joost Broekens, and Catholijn M. Jonker. Model-based reinforcement learning: A survey. *CoRR*, abs/2006.16712, 2020. URL https://arxiv.org/abs/2006.16712.

Ofir Nachum, Shixiang Gu, Honglak Lee, and Sergey Levine. Data-efficient hierarchical reinforcement learning. In *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, Montréal, Canada*, pp. 3307–3317, 2018.

Erika Puiutta and Eric M. S. P. Veith. Explainable reinforcement learning: A survey. *CoRR*, abs/2005.06247, 2020.

Stéphane Ross and Drew Bagnell. Efficient reductions for imitation learning. In Yee Whye Teh and D. Mike Titterington (eds.), *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2010, Chia Laguna Resort, Sardinia, Italy, May 13-15, 2010*, volume 9 of *JMLR Proceedings*, pp. 661–668. JLMR, 2010.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy P. Lillicrap, and David Silver. Mastering atari, go, chess and shogi by planning with a learned model. *CoRR*, abs/1911.08265, 2019. URL http://arxiv.org/abs/1911.08265.

Sungryull Sohn, Hyunjae Woo, Jongwook Choi, and Honglak Lee. Meta reinforcement learning with autonomous inference of subtask dependencies. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=HkgsWxrtPB.

Alexander Sasha Vezhnevets, Simon Osindero, Tom Schaul, Nicolas Heess, Max Jaderberg, David Silver, and Koray Kavukcuoglu. Feudal networks for hierarchical reinforcement learning. *CoRR*, abs/1703.01161, 2017.

Zhao Yang, Song Bai, Li Zhang, and Philip H. S. Torr. Learn to interpret atari agents. *CoRR*, abs/1812.11276, 2018.

# A  TRANSITIONS CREATED IN THE HINDSIGHT-ACTOR-CRITIC ALGORITHM

Figure 7 summarizes the transitions and we detail them below:

1. **Hindsight action transitions**: consider the scenario where the policy $\pi_l$ at level $l$ picked as action the goal $a_l = s$ and the policy below $\pi_{l-1}$ reached state $s'$. If $s'$ is close enough to $s$, then the goal was reached and the policy below $\pi_{l-1}$ acted optimally. If the goal wasn't reached, the action taken by the policy $\pi_l$ at level $l$ is substituted by the hindsight action $a_{hindsight} = s'$. Under this scenario, the policy below now acted optimally, since it reached the updated goal.

2. **Hindsight goal transitions**: for a policy $\pi_l$ at level $l$, while hindsight action transitions give the illusion that the policy below $\pi_{l-1}$ is optimal, the reward signal may still be extremely sparse if the policy $\pi_l$ never reaches the goal $g_l$ it received from above as input. To fix this issue, new transitions are created by replacing the goal $g_l$ of the hindsight action transitions by one of the states reached by policy $\pi_l$ while it was doing actions. This ensures that during at least one step of the episode the policy gets a positive reward since the hindsight goal is one of the states it visited.

3. **Subgoal testing transitions**: in the two previous types of transitions, the hindsight action is always a state that the policy below reached. Therefore, there are no transitions in which the action is a goal the policy below didn't reach in at most $H$ steps, which makes it impossible for the policy $\pi_l$ to learn which states are unreachable in $H$ steps. These unreachable states should not be picked, because then the policy below $\pi_{l-1}$ can never reach the goal it received, which will considerably slow down its training process and may lead to erratic and unstable behavior. To avoid picking unreachable goals as actions, we want to assign very low Q-values to those actions. However, there is one key uncertainty: if the policy $\pi_l$ produced the goal $g_l$ but the policy below $\pi_{l-1}$ reached the state $s$ instead, it might be either because the policy $\pi_{l-1}$ hasn't learned to reach the goal or because $g_l$ is unreachable in at most $H$ steps. Since it is not possible to distinguish between the cases with certainty, subgoal testing transitions are created a random fraction of the time (say 20%). In these transitions, the raw action is used (instead of the hindsight action) and a very low reward is attributed to that action, to avoid picking that goal again in the future.

*Note*: for the bottom-level policy, we only create hindsight goal transitions (using the original action). Since the bottom-level policy interacts with the environment instead of producing goals as actions, it is not possible to create hindsight action transitions and subgoal testing transitions.

Figure 7: The three types of transitions created by the Hindsight Actor-Critic algorithm: hindsight action transitions (replace the action by the state that was reached by the policy below), hindsight goal transition (replace action; replace the goal by a state reached by the policy during the episode) and subgoal testing transition (if the policy at level L picks an action/goal the policy below fails to reach, occasionally attribute that action a very low reward).

.

## B  Pseudocode for the HAC-General with Teacher algorithm

The pseudo-code of the training loop and a more detailed version of the *TrainLevel* function is shown below. The HAC-General without Teacher algorithm can be obtained by setting $C = 0$.

The full implementation can be consulted in the supplementary material. The supplementary material also contains the implementation of the teacher agents as well as the code to show visualise the goals in the environment. For both environment, a GIF file shows the trained hierarchical agent acting, and both the current goal and future goals are visualised at all steps.

---

**Algorithm 2:** Train-Level (2-level hierarchy)

---

1  **Input**: Level $i$
2  **Input**: Start state $s$ and goal $g$
3  **Input**: Expert policy $\pi^*$
4  **Input**: Probability C of using the teacher
5  **Output**: Final state $s_i'$, total reward $cumulR$
6
7  $s_i, g_i, cumulR \leftarrow s, g, 0$
8
9  **repeat**
10  $\quad$ Decide if will test action/subgoal
11  $\quad$ $a_i \leftarrow \pi_i(s_i, g_i)$ (no noise *noise* if subgoal testing)
12
13  $\quad$ **if** $i > 0$ **then**
14  $\quad\quad$ **if** *useTeacherInIteration(C)* **then**
15  $\quad\quad\quad$ $s_i', r, \text{lowLevelTransitions} \leftarrow \textbf{expertRollout}(s_i, \pi^*)$
16  $\quad\quad\quad$ $a_i \leftarrow [s_i', \textbf{reduceReward}(r)]$
17  $\quad\quad\quad$ Replay Buffer$_0$ $\leftarrow$ lowLevelTransitions
18  $\quad\quad$ **else**
19  $\quad\quad\quad$ Determine whether to test subgoal $a_i$
20  $\quad\quad\quad$ $s_i', r \leftarrow \texttt{TrainLevel}(i-1, s_i, a_i, \pi^*, C)$
21  $\quad$ **else**
22  $\quad\quad$ Execute primitive action $a_0$
23  $\quad\quad$ Observe next state $s_0'$ and reward $r$
24  $\quad$ $cumulR \leftarrow cumulR + r$
25
26  $\quad$ **if** $i > 0$ *and subgoal $a_i$ was tested and wasn't reached* **then**
27  $\quad\quad$ Replay Buffer$_i$ $\leftarrow [s_i, a_i, Penalty, s_i', g_i, \gamma = 0]$ // Subgoal testing transition
28
29  $\quad$ **if** $i > 0$ *and $a_i$ wasn't reached* **then**
30  $\quad\quad$ $a_i \leftarrow [s_i', \textbf{reduceReward}(r)]$ // Hindsight action
31
32  $\quad$ $R_t \leftarrow \textbf{getTransitionReward}(s_i', cumulR, a_i)$
33  $\quad$ Replay Buffer$_i$ $\leftarrow [s_i, a_i, R_t, s_i', g_i, \gamma \in \{\gamma, 0\}]$ // Hindsight action transition
34
35  $\quad$ // Hindsight goal transition (step 1)
36  $\quad$ **if** *not* *isTopLevel*$(i)$ **then**
37  $\quad\quad$ HER$_i$ $\leftarrow [s_i, a_i, r = TBD, s_i', g = TBD, \gamma = TBD]$
38
39  $\quad$ $s_i \leftarrow s_i'$
40  **until** *episode ended **OR** (H steps done or until any goal from above $g_{n, i \leq n < k}$ is reached)*;
41
42  // Hindsight goal transition (step 2): perform HER; complete $r$, $g$ and $\gamma$
43  Replay Buffer$_i$ $\leftarrow$ Perform HER(HER$_i$)

---

**Algorithm 3:** HAC-General (With Teacher)

1 **Input**: Initialized hierarchy of actor-critics with $k$ levels
2 **Input**: Expert policy $\pi^*$
3 **Input**: Probability C of using the teacher
4
5 **for** $M$ *episodes* **do**
6     $s \leftarrow reset\_environment()$
7     `TrainLevel`$(k-1, s, goal = None, \pi^*, C)$
8     Update all the actor-critic networks in the hierarchy
9 **end**

## C  PERCENTAGE OF GOALS THAT ARE REACHED

(a) Mountain Car

(b) Lunar Lander

Figure 8: The trained hierarchical agent runs for a hundred episodes and for each episode we measure the percentage of goals that were reached during the episode. The distribution of those percentages makes it possible to better understand how often the goals are reached. In the Mountain Car environment the goal is almost always reached (92 % median, 92% average) and in the Lunar Lander environment the goal is reached the majority of the time (96 % median, 74% average) despite goals being much more difficult to pick and reach.

## D  POSSIBLE IMPROVEMENTS

While we displayed explanations generated by the good-performance hierarchical agents and saw their effectiveness at gaining insight into the agent's decision-making mechanism and future behavior, improvements could be made:

1. While we generated plans at different time steps to validate them, this does not prove the plans are always effective (this is similar to the principle that tests can show the presence of bugs but cannot prove an absence of bugs). Finding mechanisms to further verify the reliability of the explanations would be interesting future work.

2. Work could be done to verify that the assumptions behind the plan-generating routine are met. Experiments show that the goal is reached the vast majority of the time for both the Lunar Lander and the Mountain Car environment (Figure 8), but more detailed examination could be useful. Additionally, we could also verify that the goal-picking policy isn't sensitive to small changes to the state it receives as input.

3. Training hierarchical agents in the setting where no goal is provided and the agent attempts to maximize the collected reward is a challenging task. Developing better algorithms to train hierarchical agents would make it possible to tackle more difficult environments and improve the efficiency and speed of the training process.

4. The experiments done in this paper did not deal with very high-dimensional states such as images. Predicting good states is likely very challenging in such environments and determining whether a goal has been reached or not becomes a more difficult question, so new techniques need to be developed for those scenarios, such as for example re-defining goals so that only the relevant part of the state is included in the goal (and background visuals are ignored, for example).

5. While the goals give insight into the agent's behavior, it would be interesting to understand better how these goals are picked. To do so, we could use already existing explainability techniques, such as distillation or saliency maps. Our explainability method is orthogonal to other explainability techniques, making it possible to combine it with other techniques, which is a strength of our approach.

## E  HEURISTIC TO DETECT THE END OF A PLAN

One heuristic to determine how many goal-states should be queried when creating the plan is to detect when the goal-states stabilize. For example, when the lunar lander has reached the ground, the next goal should be to stay in the same state. Similarly, if the mountain car reaches the top of the mountain, the next goal should be to stay at the top of the mountain. Therefore, if we detect that the state-goal $s'$ produced by the goal-picking policy is very similar to the current state $s$, we may stop querying for new goals.