Secure Federated Learning of User Verification Models

Abstract

We consider the problem of training User Verification (UV) models in federated setup, where the conventional loss functions are not applicable due to the constraints that each user has access to the data of only one class and user embeddings cannot be shared with the server or other users. To address this problem, we propose Federated User Verification (`FedUV`), a framework for private and secure training of UV models. In `FedUV`, users jointly learn a set of vectors and maximize the correlation of their instance embeddings to a secret user-defined linear combination of those vectors. We show that choosing the linear combinations from the codewords of an error-correcting code allows users to collaboratively train the model without revealing their embedding vectors. We present experimental results for user verification with voice, face and handwriting data and show that `FedUV` is on par with existing approaches, while providing security by not sharing the embeddings with other users or the server.

1 Introduction

There has been a recent increase in research and development of User Verification (UV) models with various modalities such as voice (Snyder et al., 2017; Yun et al., 2019), face (Wang et al., 2018), fingerprint (Cao & Jain, 2018), or iris (Nguyen et al., 2017). Many commercial smart devices such as mobile phones, AI speakers and automotive infotainment systems have adopted machine learning-based UV features for unlocking the system or providing a user-specific service, e.g., music recommendation, schedule notification, or other configuration adjustments (Matei, 2017; Barclays, 2013; Mercedes, 2020).

User verification is a binary decision problem of accepting or rejecting a test example based on its similarity to the user's training examples. We consider embedding-based classifiers, in which a test example is accepted if its embedding is close enough to a reference embedding, and otherwise rejected. Such classifiers are usually trained with a loss function that is composed of two terms, 1) a positive loss that minimizes the distance of the instance embedding to the positive class embedding, and 2) a negative loss that maximizes the distance to the negative class embeddings. The negative loss term is needed to prevent the class embeddings from collapsing into a single point (Bojanowski & Joulin, 2017).

Verification models need to be trained with a large variety of users' data so that the model learns different data characteristics and can reliably reject imposters. However, due to the privacy-sensitive nature of the biometric data used for verification, it is not possible to centrally collect large training datasets. One approach to address the data collection problem is to train the model in the federated setting, which is a framework for training models by repeatedly communicating the model weights and gradients between a central server and a group of users (McMahan et al., 2017a). Federated learning (FL) allows training models without users having to share their data with the server or other users and, hence, helps enable private training of verification models.

Training UV models in federated setup, however, imposes an additional constraint that each user has access to the data of only one class and cannot share their embedding with the server or other users. As a result, users cannot compute the negative loss term for training the model in the federated setup. A recent work (Yu et al., 2020) studied the problem of federated learning with only positive labels and proposed `FedAwS`, a method that allows the users and server to jointly train the model. In `FedAwS`, at each round, users train the model with the positive loss function and send the new models to the

server. The server then updates the averaged model using an approximated negative loss function that maximizes the pairwise distances between user embeddings. `FedAwS` keeps the embedding of each user private from other users but reveals all embeddings to the server. Sharing embeddings with the server undermines the security of verification models in real-world applications and can lead to both training- and test-time attacks. Specifically, the server can run a poisoning attack (Biggio et al., 2012) and train the model so that it verifies fake examples for a particular user. It can also carry out evasion attacks at test time (Biggio et al., 2013; Szegedy et al., 2013) to fool the model to verify impostors.

In this paper, we propose Federated User Verification (`FedUV`), a framework for training UV models in federated setup using only the positive loss term. Our contributions are summarized in the following.

- We propose a method where users jointly learn a set of vectors, but each user maximizes the correlation of their instance embeddings with a secret linear combination of those vectors. We show that, under a condition that the secret vectors are designed with guaranteed minimum pairwise correlations, the model can be trained using only the positive loss term. Our framework, hence, addresses the security problem of existing approaches where embeddings are shared with other users or the server (Yu et al., 2020).

- We propose to use error-correcting codes to generate binary secret vectors. We also develop a method where the server distributes unique IDs to users, which are used to generate unique vectors without revealing the selected vector to the server or other users.

- We present a verification method, where a test example is accepted if the correlation of the predicted embedding with the secret vector is more than a threshold, and otherwise rejected. We develop a "warm-up phase" to determine the threshold for each user independently, in which a set of inputs is collected and then the threshold is computed so as to obtain a desired True Positive Rate (TPR).

- We present the experimental results for voice, face and handwriting recognition using Vox-Celeb (Nagrani et al., 2017), CelebA (Liu et al., 2015) and MNIST-UV datasets, where MNIST-UV is a dataset we created from images of the EMNIST dataset (Cohen et al., 2017). Our experimental results show that `FedUV` performs on par with `FedAwS`, despite not sharing the embedding vectors with the server.

2 BACKGROUND

2.1 FEDERATED LEARNING

Consider a setting where K users want to train a model on their data. Federated learning (FL) allows users to train the model by the help of a central coordinator, called server, and without sharing their local data with other users (or the server). The most commonly-used algorithm for FL is Federated Averaging (`FedAvg`) described in Algorithm (1) (McMahan et al., 2017a).

2.2 USER VERIFICATION WITH MACHINE LEARNING

User verification (UV) is a binary decision problem where a test example is accepted (reference user) or rejected (impostor user) based on its similarity to the training data. We consider embedding-based classifiers, in which both the classes and the inputs are mapped into an embedding space such that

---

Algorithm 1 (McMahan et al., 2017a) `FedAvg`.
θ_t: model parameters at round t, K: number of users, ϵ: fraction of users selected at each round, D_u: dataset of user u with n_u examples.

FedAvg:
  Server: Initialize θ_0
  Server: $\kappa \leftarrow \max(\epsilon \cdot K, 1)$
  for each global round $t = 1, 2, \ldots$ **do**
    Server: $S_t \leftarrow$ (random set of κ users)
    Server: Send θ_{t-1} to users $u \in S_t$
    Users $u \in S_t$: $\theta_t^u, n_u \leftarrow$ UserUpdate(θ_{t-1}, D_u)
    Server: $\theta_t \leftarrow \frac{\sum_{u \in S_t} n_u \theta_t^u}{\sum_{u \in S_t} n_u}$

UserUpdate(θ, D): // *Done by users*
  $\mathcal{B} \leftarrow$ (split D into batches of size B)
  for each local epoch i from 1 to E **do**
    for batch $b \in \mathcal{B}$ **do**
      $\theta \leftarrow \theta - \eta \nabla \ell(\theta; b)$
  return θ and $|D|$ to server

---

the embedding of each input is closest to the embedding of their corresponding class. Let $w_y \in \mathbb{R}^{n_d}$ be the embedding vector of class y and $g_\theta : \mathcal{X} \to \mathbb{R}^{n_d}$ be a network that maps an input x from the

input space $\mathcal{X}$ to an n_d-dimensional embedding $g_\theta(x)$. Let d be a distance function. The model is trained on (x, y) so as to have $y = \arg\min_u d(g_\theta(x), w_u)$ or, equivalently,

$$d(g_\theta(x), w_y) < \min_{u \neq y} d(g_\theta(x), w_u). \tag{1}$$

Hence, the loss function can be defined as follows:

$$\ell(x, y; \theta, w) = d(g_\theta(x), w_y) - \lambda \min_{u \neq y} d(g_\theta(x), w_u). \tag{2}$$

Minimizing the loss function reduces to minimizing the distance of the instance embedding to the true class embedding and maximizing the distance to the embeddings of other classes. The two terms are called positive and negative loss terms, respectively. The negative loss term is needed to ensure that the training does not lead to a trivial solution that all inputs and classes collapse to a single point in the embedding space (Bojanowski & Joulin, 2017).

2.3 ERROR-CORRECTING CODES

Error correcting codes (ECCs) are techniques that enable restoring binary sequences from noise. A binary block code is an injective function $C : \{0, 1\}^m \to \{0, 1\}^c, c \geq m$, that takes a binary message vector and generates the corresponding *codeword* by adding some redundancy, which can be used to obtain the original message from the corrupted codeword. ECCs are designed to maximize the minimum Hamming distance $d_{\min}$ between distinct codewords, where Hamming distance between two sequences is defined as the number of positions at which they differ. A code with minimum distance δ allows correcting up to $(\delta - 1)/2$ errors (Richardson & Urbanke, 2008). In this paper, we use binary BCH codes which are a class of block codes with codewords of length $c = 2^i - 1, i \geq 3$ (Bose & Ray-Chaudhuri, 1960).

3 USER VERIFICATION WITH FEDERATED LEARNING

In this section, we outline the privacy and security requirements of UV applications and describe the challenges of training UV models in the federated setting.

3.1 PROBLEM STATEMENT

Verification models need to be trained with a large variety of users' data so that the model learns different data characteristics and can reliably verify users. For example, speaker recognition models need to be trained with the speech data of users with different ages, genders, accents, etc., to be able to reject impostors with high accuracy. One approach for training UV models is to collect the users' data and train the model centrally. This approach is, however, not privacy-preserving due to the need to have direct access to the users' biometric data.

An alternative approach is using the FL framework, which enables training with data of a large number of users while keeping their data private by design. Training UV models in federated setup, however, poses its own challenges. As stated in Section (2.2), training embedding-based classifiers requires having access to all class embeddings to compute the loss function in (2). In UV applications, however, class embeddings are used for the verification and, hence, are considered security-sensitive information and cannot be shared with the server or other users.

Providing security is particularly important in UV applications, where the model might be potentially trained and deployed in adversarial settings. Specifically, the leakage of the embedding vector makes the verification model vulnerable to both training- and test-time attacks, examples of which are provided in the following.

- **Poisoning attack** (Biggio et al., 2012): The server participates in training and trains the model with the loss function $d(g_\theta(x_u^*), w_u)$ for some x_u^*. At test time, the model generates w_u for the input x_u^* and thus wrongly verifies x_u^* as a true example from user u.

- **Evasion attack** (Biggio et al., 2013; Szegedy et al., 2013): Attacks based on adversarial examples are known to be highly effective against deep neural networks (Carlini & Wagner, 2017). In the context of UV models, when a target embedding vector is known, an evasion attack can be performed to slightly perturb any given input such that the predicted embedding matches a target embedding and thus is accepted by the model.

Without the knowledge of embeddings of other users, users cannot compute the negative loss term in (2) for training the model in the federated setup. Training only with the positive loss function also causes all class embeddings to collapse into a single point. Hence, the question is how we can train embedding-based classifiers without the negative loss term.

3.2 RELATED WORK: FEDERATED AVERAGING WITH SPREADOUT (FEDAwS)

In embedding-based classifiers, the negative loss term maximizes the distance of instance embeddings to the embeddings of other classes. A recent paper (Yu et al., 2020) observed that, alternatively, the model could be trained to maximize the pairwise distance of class embeddings. They proposed Federated Averaging with Spreadout (FedAwS) framework, where the server, in addition to averaging the gradients, performs an optimization step to ensure that embeddings are separated from each other by at least a margin of ν. Formally, in each round of training, the server applies the following geometric regularization:

$$\text{reg}_{\text{sp}}(W) = \sum_{u \in [K]} \sum_{u' \neq u} \left(\max(0, \nu - d(w_u, w_{u'})) \right)^2. \tag{3}$$

FedAwS eliminates the need for users to share their instance embedding vector with other users, but still requires sharing class embeddings with the server, which seriously undermines the security of the real-world verification models. In the next section, we present a federated learning framework for training UV models while keeping embeddings private.

4 PROPOSED METHOD

4.1 TRAINING WITH ONLY POSITIVE LOSS

Training UV models using the loss function in (2) requires users to jointly learn the class embeddings, which causes the security problem of sharing the embeddings with other users. To address this problem, we propose a method where users jointly learn a set of vectors, but each user maximizes the correlation of their instance embeddings with a secret linear combination of those vectors. The same linear combination is also used for user verification at test time.

Let $W \in \mathbb{R}^{c \times n_d}$ be a set of c vectors and $v_u \in \{-1, 1\}^c$ be the secret vector of user u. We modify the loss function in (2) as follows:

$$\ell(x, y, v; \theta, W) = \ell_{\text{pos}} + \lambda \ell_{\text{neg}}, \tag{4}$$
$$\text{where } \ell_{\text{pos}} = d(g_\theta(x), W^T v_y) \text{ and } \ell_{\text{neg}} = -\min_{u \notin y} d(g_\theta(x), W^T v_u).$$

Let us call $s_u = W^T v_u$ the *secret embedding* of user u. Note that users still need to know the secret vector, v_u, or the secret embedding, s_u, of other users to compute the negative loss term. We, however, show that under certain conditions, the model can be trained using only the positive loss term.

Let us define the positive and negative loss terms as follows:

$$\ell_{\text{pos}} = \max(0, 1 - \frac{1}{c} v_y^T W g_\theta(x)) \text{ and } \ell_{\text{neg}} = \max_{u \notin y} \frac{1}{c} v_u^T W g_\theta(x). \tag{5}$$

The positive loss term maximizes the correlation of the instance embedding with the true secret embedding, while the negative loss term minimizes the correlation with secret embeddings of other users. We have the following Lemma.

Lemma 1. *Assume $\|W g_\theta(x)\| = \sqrt{c}$ and $v_y \in \{-1, 1\}^c$. For ℓ_{pos} defined in (5), we have $\ell_{\text{pos}} = 0$ if and only if $W g_\theta(x) = v_y$.*

Proof. Let $z = W g_\theta(x)$. The term $\ell_{\text{pos}} = 0$ is equivalent to $\frac{1}{c} v_y^T z \geq 1$. We have $\frac{1}{c} v_y^T z \leq \frac{1}{c} \|v_y\| \|z\| = 1$ and the equality holds if and only if $z = \alpha v_y$. Since $\|z\| = \|v_y\| = \sqrt{c}$, then $\alpha = 1$ and, hence, we have $\ell_{\text{pos}} = 0$ if and only if $z = v_y$. $\square$

The following Theorem links the positive and negative loss terms of (5) when secret vectors are chosen from ECC codewords.

Algorithm 2 Federated User Authentication (FedUV). K: number of users, C: block code, θ, W: model parameters, σ: a function that scales its input to have norm of $\sqrt{c}$, q: TPR.

Codeword Selection:
   Server: Send a unique binary vector, $b_u, u \in [K]$, of length $l_b \geq \log_2 K$ to user u
   User $u \in [K]$:
      Choose a random binary vector, r_u, of length l_r
      Construct message vector $m_u = b_u \| r_u$
      Compute codeword $v_u = C(m_u)$

Training:
   Server and users: Trained UV model using FedAvg algorithm (1) and with the loss function
   $\ell_{\text{pos}} = \max(0, 1 - \frac{1}{c} v_y^T \sigma(W g_\theta(x)))$

Warm-up Phase(θ, W, v_y, q):   *// Done by users*
   Collect inputs $x'_j, j \in [n]$, and compute $e_j = \frac{1}{c} v_y^T \sigma(W g_\theta(x'_j))$
   Set τ equal to the i-th smallest value in e where $i = \lfloor n \cdot (1 - q) \rfloor$

Verification$(\theta, W, v_y, \tau, x')$:   *// Done by users*
   $e = \frac{1}{c} v_y^T \sigma(W g_\theta(x'))$
   if $e \geq \tau$ **then** ACCEPT **else** REJECT

Theorem 1. *Assume $\|W g_\theta(x)\| = \sqrt{c}$ and $v_y \in \{-1, 1\}^c$. Assume v_i's are chosen from ECC codewords. For ℓ_{pos} and ℓ_{neg} defined in (5), minimizing ℓ_{pos} also minimizes ℓ_{neg}.*

Proof. Since $v_i \in \{-1, 1\}^c$, the Hamming distance between v_{u_1} and v_{u_2} is defined as

$$\Delta_{u_1, u_2} = \frac{1}{4} \|v_{u_1} - v_{u_2}\|^2 = \frac{1}{4}(\|v_{u_1}\|^2 + \|v_{u_2}\|^2 - 2 v_{u_1}^T v_{u_2}) = \frac{c}{2}(1 - \frac{1}{c} v_{u_1}^T v_{u_2}).$$

The minimum Hamming distance between codewords is obtained as $d_{\min} = \min_{u_1 \neq u_2} \Delta_{u_1, u_2}$. As stated in Section 2.3, ECCs are designed to maximize $d_{\min}$ or, equivalently, minimize $\max_{u_1 \neq u_2} \frac{1}{c} v_{u_1}^T v_{u_2}$. Using Lemma (1), we have $\ell_{\text{pos}} = 0$ if and only if $z = v_y$, which results in $\ell_{\text{neg}} = \max_{u \notin y} \frac{1}{c} v_u^T v_y$. As a result, ℓ_{neg} is at its minimum when $\ell_{\text{pos}} = 0$ and v_i's are chosen from ECC codewords. $\qquad\square$

Theorem (1) states that the negative loss term in (4) is redundant when $\|W g_\theta(x)\| = \sqrt{c}$ and secret vectors are chosen from ECC codewords. As a result, users can train the UV model in federated setup without sharing their secret embedding with the server or other users.

4.2   FEDERATED USER VERIFICATION (FEDUV)

In this section, we present Federated User Verification (FedUV), a framework for training UV models in the federated setup. FedUV consists of three phases of choosing unique codewords, training and verification, details of which are provided in the following.

Choosing Unique Codewords. To train the UV model with the positive loss function defined in (5), users must choose unique codewords without sharing the vectors with each other or the server. To do so, we propose to partition the space between users by the server and let users select a random message in their assigned space. Specifically, the server chooses unique binary vectors b_u of length l_b for each user $u \in [K]$ and sends each vector to the corresponding user. Each user u then chooses a random binary vector, r_u, of length l_r, constructs the message vector $m_u = b_u \| r_u$, and computes the codeword $v_u = C(m_u)$, where C is the block code.

The length of the base vectors is determined such that the total number of vectors is greater than or equal to the number of users, i.e., $l_b \geq \log_2 K$. In practice, the server can set $l_b \gg \log_2 K$ so that new users can be added to the training after training started. In experiments, we set $l_b = 32$, which is sufficient for most practical purposes. The code length is also determined by the server based on the number of users and the desired minimum distance obtained according to the estimated difficulty of the task. Using larger codewords improves the performance of the model but also increases the

training complexity and communication cost of the `FedAvg` method. The proposed method has the following properties.

- It ensures that codewords are unique, because the base vectors b_u's and, in turn, m_u's are unique for all users. Moreover, due to using the ECC algorithm, the minimum distance between codewords are guaranteed to be more than a threshold determined by the code characteristics.

- The method is secure since the final codewords are not shared among users or with the server. Moreover, there are 2^{l_r} vectors for each user to choose their codeword from. Increasing l_r improves the security of the method by making it harder to guess the user codeword but reduces the minimum distance of the code for a given code length. In experiments, we set $l_r \geq 32$, which is sufficient for most practical purposes.

- The method adds only a small overhead to vanilla FL algorithms. Specifically, the server assigns and distributes unique binary vectors to users and users construct message vectors and compute the codewords.

Training. Figure 1 shows the model structure used in `FedUV` method. The model is trained using the `FedAvg` algorithm and with the loss function $\ell_{\text{pos}} = \max(0, 1 - \frac{1}{c} v_y^T \sigma(W g_\theta(x)))$, where σ is a function that scales its input to have norm of $\sqrt{c}$.

Figure 1: Model structure for `FedUV`.

Verification. After training, each user deploys the model as a binary classifier to accept or reject test examples. For an input x', the verification is done as

$$\frac{1}{c} v_y^T \sigma(W g_\theta(x')) \underset{\text{reject}}{\overset{\text{accept}}{\gtrless}} \tau, \qquad (6)$$

where τ is the verification threshold. The threshold is determined by each user separately such that the True Positive Rate (TPR) is more than a value, say $q = 90\%$. The TPR is defined as the rate that the reference user is correctly verified. To do so, in a warm-up phase, n inputs $x'_j, j \in [n]$, are collected and their corresponding scores are computed as $\frac{1}{c} v_y^T \sigma(W g_\theta(x'_j))$. The threshold is then set such that a desired fraction q of inputs are verified.

Our proposed `FedUV` framework is described in Algorithm (2).

5   RELATED WORK

The problem of training UV models in federated setup has been studied in (Granqvist et al., 2020) for on-device speaker verification and in (Yu et al., 2020) as part of a general setting of FL with only positive labels. However, to the best of our knowledge, our work is the first to explore secure training of UV models in federated setup. In our proposed framework, neither raw inputs nor the embeddings will be shared with the server or other users, which makes the model robust against attacks such as poisoning and evasion attacks. Our method, however, inherits potential privacy leakage of FL methods, where users' data might be recovered from a trained model or the gradients (Melis et al., 2019). It has been suggested that adding noise to gradients or using secure aggregation methods improve the privacy of FL (McMahan et al., 2017b; Bonawitz et al., 2017). Such approaches can be applied to our framework as well.

Our approach of assigning a codeword to each user is related to distributed output representation (Sejnowski & Rosenberg, 1987), where a binary function is learned for each bit position. It follows (Hinton et al., 1986) in that functions are chosen to be meaningful and independent, so that each combination of concepts can be represented by a unique representation. Another related method is distributed output coding (Dietterich & Bakiri, 1991; 1994), which uses ECCs to improve the generalization performance of classifiers, with the codes constructed such that the length of codewords is greater or equal to number of classes. We use codewords to enable secure training of UV models in the federated setup. Moreover, in experiments, we use vectors of length much smaller than the number of users to provide scalability to a large number of users.

6   EXPERIMENTAL RESULTS

In this section, we describe the datasets and provide the experimental results of UV models trained in federated setup. More details on the experiments are provided in Appendix A.

6.1 DATASETS

VoxCeleb (Nagrani et al., 2017) is created for text-independent speaker identification in real environments dataset. The dataset contains $1,251$ speakers' data with 45 to 250 number of utterances per speaker, which are generated from YouTube videos recorded in various acoustic environments. We selected $1,000$ speakers and generated 25 training, 10 validation and 10 test examples for each speaker. The examples are 2-second audio clips obtained from videos recorded in one setting. We also generated a separate test set of $1,000$ examples by choosing 5 utterances from 200 of the remaining speakers that were not selected for training. All 2-second audio files were sampled at 8 kHz to obtain vectors of length 2^{14} for model input.

CelebA (Liu et al., 2015) contains more than $200,000$ facial images from $10,177$ unique individuals, where each image has the annotation of 40 binary attributes and 5 landmark locations. We use CelebA for user verification by assigning the data of each individual to one client and training the model to recognize faces. We selected $1,000$ identities from those who had at least 30 images, which we split into 20, 5 and 5 examples for training, validation, and test sets, respectively. We also generated a separate test set with $1,000$ images from individuals that were not selected for training (one example per person). All images were resized to 64×64.

MNIST-UV. We created MNIST-UV dataset for user verification based on handwriting recognition. MNIST-UV examples are generated using the EMNIST-byclass dataset (Cohen et al., 2017), which contains $814,255$ images from 62 unbalanced classes (10 digits and 52 lower- and upper-case letters) written by $3,596$ writers. A version of this dataset, called FEMNIST, has been used to train a 62-class classifier in federated setup by assigning the data of each writer to one client (Caldas et al., 2018). In FEMNIST, the difference in handwritings is used to simulate the non-iid nature of the clients' data in federated setup.

We repurpose EMNIST for the task of user verification by training a classifier that recognizes the handwritings., i.e., similar to FEMNIST, the data of each writer is assigned to one client but the model is trained to predict the *writer IDs*. To this end, we created MNIST-UV dataset that contains data of $1,000$ writers each with 50 training, 15 validation and 15 test examples. Each example in the dataset is of size $28 \times 28 \times 4$ and is composed of images of digits $2, 3, 4$ and 5 obtained from one writer. For each writer, the training examples are unique; however, the same sub-image (images of digits $2, 3, 4$ or 5) might appear in several examples. This also holds for validation and test sets. The sub images are, however, not shared between training, validation and test sets. We also generated a separate test set with $1,000$ examples from writers that were not selected for training (one example per writer). Figure 3 in Appendix A shows few examples of the MNIST-UV dataset.

6.2 EXPERIMENT SETTINGS

Training setup. We train UV models using the `FedAvg` method with 1 local epoch and $20,000$ rounds with 0.01 of users selected at each round. The model structures are provided in Appendix A.

Generating codewords. We use BCH coding algorithm to generate codewords of lengths $127, 255$ and 511. The code lengths are chosen to be smaller than the number of users ($1,000$) to emulate the setting with a very large number of users. For each code length, we find the message length of greater than or equal to 64 that produces a valid code. Table 1 shows the code statistics.

Table 1: Statistics of BCH codewords used in experiments.

Code length	Message length	$d_{\min}$
127	64	21
255	71	59
511	67	175

Baslines. We compare our `FedUV` method with the `FedAwS` algorithm (Yu et al., 2020) and regular federated training with the softmax cross-entropy loss function, which we refer to as `softmax` algorithm. Note that `softmax` and `FedAwS` are not secure training algorithms as they share the embedding of each user with other users and/or the server. Similar to `FedUV`, we perform a warm-up phase for the two baselines to determine the verification threshold for each user.

6.3 VERIFICATION RESULTS

We evaluate the verification performance on different data, namely 1) training data, 2) validation data of users who participated in training, and 3) data of users who did not participate in training. Figure 2

(a) VoxCeleb dataset   (b) CelebA dataset   (c) MNIST-UV dataset

Figure 2: ROC curves for models trained in federated setup using `softmax`, `FedAwS` and `FedUV` algorithms. `FedUV` (c) denotes `FedUV` with code length of c. The models are evaluated on training data (top), test data of users who participated in training (middle) and data of users who did not participate in training (bottom). It can be seen that `FedUV` performs on par with `FedAwS`, while `softmax` outperforming both methods. Also, as expected, increasing the code length improves the performance of `FedUV` algorithm. Note that, unlike `FedUV`, both `softmax` and `FedAwS` share embeddings with other users and/or the server.

shows the ROC curves. [1] The verification performance is best on training data and slightly degrades when the model is evaluated on validation data of users who participated in training and further reduces on data of new users. All methods, however, achieve notably high TPR, e.g., greater than 80%, at low False Positive Rates (FPRs) of smaller than 10%, implying that trained UV models can reliably reject the impostors. The regular `softmax` training outperforms both `FedAwS` and `FedUV` algorithms in most cases, especially at high TPRs of greater than 90%. `FedUV`'s performance is on par with `FedAwS`, despite not sharing the embedding vectors with the server. Also, as expected, increasing the code length in `FedUV` improves the performance.

7 CONCLUSION

In this paper, we presented `FedUV`, a framework for private and secure training of user verification models. In `FedUV`, users first collaboratively choose unique codewords in a secure way and then train the model using `FedAvg` method and with a loss function that only uses their own codeword. After training, a warm-up phase is performed to obtain the verification threshold for each user separately. We show our framework addresses the security problem of existing approaches where embeddings are shared with other users or the server. Our experimental results for user verification with voice, face and handwriting data show `FedUV` performs on par with existing approaches that share embeddings with other users and/or the server.

---

[1]We present the experimental results for the models trained in federated setup. In all cases, the difference in accuracy between centralized and federated cases is less than 5%.

REFERENCES

Barclays. *Say goodbye to the pin: voice recognition takes over at Barclays Wealth*, 2013. `https://www.biometrie-online.net/actualites/annonces-communiques/say-goodbye-to-the-pin-voice-recognition-takes-over-at-barclays-wealth`.

Battista Biggio, Blaine Nelson, and Pavel Laskov. Poisoning attacks against support vector machines. *arXiv preprint arXiv:1206.6389*, 2012.

Battista Biggio, Igino Corona, Davide Maiorca, Blaine Nelson, Nedim Šrndić, Pavel Laskov, Giorgio Giacinto, and Fabio Roli. Evasion attacks against machine learning at test time. In *Joint European conference on machine learning and knowledge discovery in databases*. Springer, 2013.

Piotr Bojanowski and Armand Joulin. Unsupervised learning by predicting noise. *arXiv preprint arXiv:1704.05310*, 2017.

Keith Bonawitz, Vladimir Ivanov, Ben Kreuter, Antonio Marcedone, H Brendan McMahan, Sarvar Patel, Daniel Ramage, Aaron Segal, and Karn Seth. Practical secure aggregation for privacy-preserving machine learning. In *Proceedings of the 2017 ACM SIGSAC Conference on Computer and Communications Security*, 2017.

Raj Chandra Bose and Dwijendra K Ray-Chaudhuri. On a class of error correcting binary group codes. *Information and control*, 3(1):68–79, 1960.

Sebastian Caldas, Peter Wu, Tian Li, Jakub Konečný, H Brendan McMahan, Virginia Smith, and Ameet Talwalkar. Leaf: A benchmark for federated settings. *arXiv preprint arXiv:1812.01097*, 2018.

Kai Cao and Anil K Jain. Automated latent fingerprint recognition. *IEEE transactions on pattern analysis and machine intelligence*, 2018.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 ieee symposium on security and privacy (sp)*. IEEE, 2017.

Gregory Cohen, Saeed Afshar, Jonathan Tapson, and Andre Van Schaik. Emnist: Extending mnist to handwritten letters. In *2017 International Joint Conference on Neural Networks (IJCNN)*, pp. 2921–2926. IEEE, 2017.

Thomas G Dietterich and Ghulum Bakiri. Error-correcting output codes: A general method for improving multiclass inductive learning programs. In *AAAI*, 1991.

Thomas G Dietterich and Ghulum Bakiri. Solving multiclass learning problems via error-correcting output codes. *Journal of artificial intelligence research*, 1994.

Filip Granqvist, Matt Seigel, Rogier van Dalen, Áine Cahill, Stephen Shum, and Matthias Paulik. Improving on-device speaker verification using federated learning with privacy. *arXiv preprint arXiv:2008.02651*, 2020.

Geoffrey E Hinton et al. Learning distributed representations of concepts. In *Proceedings of the eighth annual conference of the cognitive science society*, 1986.

Kevin Hsieh, Amar Phanishayee, Onur Mutlu, and Phillip B Gibbons. The non-iid data quagmire of decentralized machine learning. *arXiv preprint arXiv:1910.00189*, 2019.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Mihai Matei. *Voice Match Will Allow Google Home To Recognize Your Voice*, 2017. `https://www.androidheadlines.com/2017/10/voice-match-will-allow-google-home-to-recognize-your-voice.html`.

H Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Proceedings of International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2017a.

H Brendan McMahan, Daniel Ramage, Kunal Talwar, and Li Zhang. Learning differentially private recurrent language models. *arXiv preprint arXiv:1710.06963*, 2017b.

Luca Melis, Congzheng Song, Emiliano De Cristofaro, and Vitaly Shmatikov. Exploiting unintended feature leakage in collaborative learning. In *2019 IEEE Symposium on Security and Privacy (SP)*, 2019.

Mercedes. *Mercedes Updated Infotainment System Features Biometric Security*, 2020. https://findbiometrics.com/mercedes-updated-infotainment-system-features-biometric-security/.

Arsha Nagrani, Joon Son Chung, and Andrew Zisserman. VoxCeleb: A large-scale speaker identification dataset. In *Proceedings of the INTERSPEECH*, 2017.

Kien Nguyen, Clinton Fookes, Arun Ross, and Sridha Sridharan. Iris recognition with off-the-shelf cnn features: A deep learning perspective. *IEEE Access*, 2017.

Tom Richardson and Ruediger Urbanke. *Modern coding theory*. Cambridge university press, 2008.

Terrence J Sejnowski and Charles R Rosenberg. Parallel networks that learn to pronounce english text. *Complex systems*, 1987.

David Snyder, Daniel Garcia-Romero, Daniel Povey, and Sanjeev Khudanpur. Deep neural network embeddings for text-independent speaker verification. In *Proceedings of the INTERSPEECH*, 2017.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Feng Wang, Jian Cheng, Weiyang Liu, and Haijun Liu. Additive margin softmax for face verification. *IEEE Signal Processing Letters*, 2018.

Felix X Yu, Ankit Singh Rawat, Aditya Krishna Menon, and Sanjiv Kumar. Federated learning with only positive labels. *arXiv preprint arXiv:2004.10342*, 2020.

Sungrack Yun, Janghoon Cho, Jungyun Eum, Wonil Chang, and Kyuwoong Hwang. An end-to-end text-independent speaker verification framework with a keyword adversarial network. In *Proceedings of the INTERSPEECH*, 2019.

A APPENDIX: EXPERIMENTAL SETUP

MNIST-UV dataset. Figure 3 shows examples from MNIST-UV dataset. Note that, in figure, sub-images are placed in a 2×2 grid for clarity.

Figure 3: Examples from MNIST-UV dataset created for user verification by handwriting. Each example in the dataset is of size $28 \times 28 \times 4$ and is composed of images of digits $2, 3, 4$ and 5 obtained from one writer. In figure, sub-images are placed in a 2×2 grid for clarity. MNIST-UV dataset contains data of $1,000$ writers each with 50 training, 15 validation and 15 test examples. It also contains a separate test set with $1,000$ examples from writers that were not selected for training (one example per writer).

Network architectures. Table 2 shows network architectures used for each dataset. In models, we use Group Normalization (GN) instead of batch-normalization (BN) following the observations that BN does not work well in non-iid data setting of federated learning (Hsieh et al., 2019).

Table 2: Network architectures for training UV models with different datasets. convxd$(c1, c2, k, p)$ is x-dimensional convolutional layer with $c1$ and $c2$ input and output channels, respectively, kernel size of k and padding of p. The default value of p is 1. GN(G) is group normalization layer with G groups. `Normalization` layer scales its input to have norm of $\sqrt{c}$. c is the code length in case of `FedUV` and the number of users in `softmax` and `FedAwS` algorithms.

VoxCeleb	CelebA	MNIST-UV
conv1d$(1, 64, k = 15)$	conv2d$(3, 64, k = 3)$	conv2d$(4, 64, k = 3, p = 3)$
relu, max_pool1d(4), GN(2)	relu, max_pool2d(2), GN(2)	relu, max_pool2d(2), GN(2)
conv1d$(64, 128, k = 9)$	conv2d$(64, 128, k = 3)$	conv2d$(64, 128, k = 3, p = 1)$
relu, max_pool1d(8), GN(2)	relu, max_pool2d(2), GN(2)	relu, max_pool2d(2), GN(2)
conv1d$(128, 256, k = 7)$	conv2d$(128, 256, k = 3)$	conv2d$(128, 256, k = 3, p = 1)$
relu, max_pool1d(8), GN(2)	relu, max_pool2d(2), GN(2)	relu, max_pool2d(2), GN(2)
conv1d$(256, 512, k = 5)$	conv2d$(256, 512, k = 3)$	conv2d$(256, 512, k = 3, p = 1)$
relu, max_pool1d(8), GN(2)	relu, max_pool2d(2), GN(2)	relu, max_pool2d(2), GN(2)
conv1d$(512, 1024, k = 3)$	conv2d$(512, 1024, k = 3)$	conv2d$(512, 1024, k = 3, p = 1)$
relu, max_pool1d(8), GN(2)	relu, max_pool2d(4), GN(2)	relu, max_pool2d(2), GN(2)
Flatten	Flatten	Flatten
FC$(1024, c)$	FC$(1024, c)$	FC$(1024, c)$
`Normalization` // for `FedUV`	`Normalization` // for `FedUV`	`Normalization` // for `FedUV`