Approximate Birkhoff-von-Neumann decomposition: a differentiable approach

Abstract

The Birkhoff-von-Neumann (BvN) decomposition is a standard tool used to draw permutation matrices from a doubly stochastic (DS) matrix. The BvN decomposition represents such a DS matrix as a convex combination of several permutation matrices. Currently, most algorithms to compute the BvN decomposition employ either greedy strategies or custom-made heuristics. In this paper, we present a novel differentiable approach to approximate the BvN decomposition. Our algorithm builds upon recent advances in Riemannian optimization on Birkhoff polytopes. We offer an empirical evaluation of this approach in the fairness of exposure in rankings, where we show that the outcome of our method behaves similarly to greedy algorithms. Our approach is an excellent addition to existing methods for sampling from DS matrices, such as sampling from a Gumbel-Sinkhorn distribution. However, our approach is better suited for applications where the latency in prediction time is a constraint. Indeed, we can generally precompute an approximated BvN decomposition offline. Then, we select a permutation matrix at random with probability proportional to its coefficient. Finally, we provide an implementation of our method.

1 Introduction & Related work

Sampling from a doubly stochastic (DS) matrix is a significant problem that recently caught the attention of the machine learning community, with applications such as exposure fairness in ranking algorithms (Kahng et al., 2018; Singh & Joachims, 2018), strategies to reduce bribery (Keller et al., 2018; 2019), and learning latent representations (Mena et al., 2018; Grover et al., 2018; Linderman et al., 2018). We consider the Birkhoff-von-Neumann decomposition (BvND) (Birkhoff, 1946), which is deterministic and represents a DS matrix as the convex combination of permutations matrices (or permutation sub-matrices). In general, the BvND of a particular DS matrix is not unique. Sampling from a BvND boils down to selecting a sub-permutation matrix with a probability proportional to its coefficient. Current BvND algorithms rely on greedy heuristics (Dufossé & Uçar, 2016; Lei et al., 2018), mixed-integer linear programming (Dufossé et al., 2018), or quantization (Liu et al., 2018). Hence, these methods are not differentiable.

We rely on reparametrization techniques to use gradient-based algorithms (Grover et al., 2018; Linderman et al., 2018). Recently, Mena et al. (2018) introduced a reparametrization trick to draw samples from a Gumbel-Sinkhorn distribution. However, these methods can underperform in applications where there is a constraint in the prediction, as reparametrization methods require to solve a perturbed Sinkhorn matrix scaling problem.

In this work, we propose an alternative to Gumbel-matching-related approaches, which is well-suited for applications where we do not need to sample permutations online. Thus, our method is fast during prediction time by saving all components in memory. We call our algorithm: differentiable approximate Birkhoff-von-Neumann decomposition, and it is a continuous relaxation of the BvND. We rely on the recently proposed Riemannian gradient descent on Birkhoff polytopes. The main parameter is the number of components of the decomposition. We enforce an approximate orthogonality constraint on each component of the BvND. To our knowledge, this is the first gradient-based approximation of the BvND.

2 Preliminaries

We first present some background on the BvND and comment on recent advances on Riemannian optimization in Birkhoff polytopes.

Notations. We write column vectors using bold lower-case, e.g., $\mathbf{x}$. $\mathbf{x}_i$ denotes the i-th component of $\mathbf{x}$. We write matrices using bold capital letters, e.g., $\mathbf{X}$. $\mathbf{X}_{ij}$ denotes the element in the i-row and j-column of $\mathbf{X}$. $[n] = \{1, \ldots, n\}$. Letters in calligraphic, e.g. $\mathcal{P}$ denotes sets. $\|\cdot\|_F$ denotes the Frobenius norm of a matrix. $\mathbf{I}_p$ is the $p \times p$ identity matrix. $\mathbf{1}_n$ is a 1 vector of size n. $\oslash$ is the Hadamard division. $(\cdot)^+$ denotes the pseudo-inverse and $\odot$ the Hadamard product. Let $\{\mathbf{X}^i\}_{i=1}^k$ be short for the set $\{\mathbf{X}^1, \ldots, \mathbf{X}^k\}$. $|\cdot|$ denotes the cardinality of a set. Δ_n denotes the $n-1$ probability simplex.

2.1 Technical background.

Definition 1 (Doubly stochastic matrix (DS)) *A DS matrix is a non-negative, square matrix whose rows and columns sums to 1. The set of DS matrices is defined as:*

$$\mathcal{DP}_n := \left\{ \mathbf{X} \in \mathbb{R}_+^{n \times n} : \quad \mathbf{X}\mathbf{1}_n = \mathbf{1}_n, \mathbf{1}_n^\mathsf{T}\mathbf{X} = \mathbf{1}_n^\mathsf{T} \right\} \tag{1}$$

Definition 2 (Birkhoff polytope) *The multinomial manifold of DS matrices is incident to the convex object called the Birkhoff Polytope (Birkhoff, 1946), an $(n-1)^2$ dimensional convex submanifold of the ambient $\mathbb{R}^{n \times n}$ with $n!$ vertices. We use $\mathcal{DP}_n$ to refer to the Birkhoff Polytope.*

Theorem 1 (Birkhoff-von Neumann Theorem) *The convex hull of the set of all permutation matrices is the set of doubly-stochastic matrices and there exists a potentially non-unique θ such that any DS matrix can be expressed as a linear combination of k permutation matrices (Birkhoff, 1946; Hurlbert, 2008)*

$$\mathbf{X} = \theta_1 \mathbf{P}^1 + \ldots + \theta_k \mathbf{P}^k, \quad \theta_i > 0, \theta^\mathsf{T}\mathbf{1}_k = 1. \tag{2}$$

While finding the minimum k is shown to be NP-hard (Dufossé et al., 2018), by Marcus-Ree theorem, we know that there exists one constructible decomposition where $k < (n-1)^2 + 1$. Fig. 1 shows an illustration of the BvND.

Figure 1: Illustration of the Birkhoff-von-Neumann decomposition (BvND): One can represent a doubly stochastic matrix as a convex combination of permutation matrices.

Definition 3 (Permutation Matrix) *A permutation matrix is defined as a sparse, square binary matrix, where each column and each row contains only a single true (1) value:*

$$\mathcal{P}_n := \left\{ \mathbf{P} \in \{0,1\}^{n \times n} : \quad \mathbf{P}\mathbf{1}_n = \mathbf{1}_n, \mathbf{1}_n^\mathsf{T}\mathbf{P} = \mathbf{1}_n^\mathsf{T} \right\}. \tag{3}$$

The (orthogonal) Stiefel manifold is an embedded submanifold of $\mathbb{R}^{n \times p}$. For $p \leq n$, let $St(p, n)$ denote the set of all $n \times p$ orthogonal matrices; i.e., $St(p, n) := \left\{ \mathbf{X} \in \mathbb{R}^{n \times p} : \mathbf{X}^\mathsf{T}\mathbf{X} = \mathbf{I}_p \right\}$. The orthogonal group O_n is $St(p, n)$ with $p = n$ (Absil et al., 2009). In particular, we have that the discrete set of permutation matrices $\mathcal{P}_n$ is the intersection of the convex set of DS matrices and the $\mathcal{DP}_n \cap \mathcal{O}_n$, $\mathcal{P}_n = \left\{ \mathbf{X} \in \mathcal{DP}_n : \mathbf{X}^\mathsf{T}\mathbf{X} = \mathbf{I} \right\}$ (Goemans, 2015).

Riemannian Geometry of the Birkhoff Polytope. Recently, Douik & Hassibi (2019) endowed $\mathcal{DP}_n$ with the Fisher information metric, resulting in the Riemannian manifold of $\mathcal{DP}_n$. They provide closed-forms of the retraction and projection onto the tangent space, both necessary to compute Riemannian gradient descent based methods. Let $R_{\mathbf{X}}$ be a retraction at $\mathbf{X}$, and $\Pi_{\mathbf{X}}$ denote projection onto the tangent space at $\mathbf{X}$. See Appendix B.

3 Approximate Birkhoff-von-Neumann decomposition

We propose a differentiable loss to approximate the BvND of a DS matrix. This approach is valuable when one can save the resulting decomposition in memory.

3.1 Formulation

Plis et al. (2011) showed that on $\mathcal{DP}_n$, all permutations are equidistant from the center of mass $\mathbf{C}_n = \frac{1}{n}\mathbf{1}_n\mathbf{1}_n^\mathsf{T}$. Thus, the permutation matrices are located on an $(n-1)^2$-dimensional hypersphere $\mathcal{S}^{(n-1)^2}$ of radius $\sqrt{n-1}$, centered at $\mathbf{C}_n$. Therefore, we can rely on the hypersphere relaxations (Plis et al., 2011; Zanfir & Sminchisescu, 2018) to learn the sub-permutation matrices. However, we have two main reasons to avoid the hypersphere relaxations in our setting: *i)* Birdal & Simsekli (2019) showed that the gap as a ratio between $\mathcal{DP}_n$ and both $\mathcal{S}^{(n-1)^2}$ and $\mathcal{O}_n$ grows to infinity as n grows. *ii)* While there exist polynomial-time projections of the n!-element permutation space onto the continuous hypersphere representation and back, these algorithms are prohibitive in iterative algorithms, as each operation displays a time complexity of f $O(n^4)$.

A $n \times n$ matrix $\mathbf{M}'$ is an ϵ-close matrix of $\mathbf{M} \in \mathcal{DP}_n$ if $\left|\mathbf{M}_{ij} - \mathbf{M}'_{ij}\right| \leq \epsilon$, $\forall (i,j) \in [n]^2$. Barman (2018) showed that it is possible to build an ϵ-close representation using at most $O(\log(n)/\epsilon^2)$ matrices. Kulkarni et al. (2017) further improve this result to using at most $1/\epsilon$ matrices. Therefore, we can build a matrix $\mathbf{M}'$ that satisfies $\|\mathbf{M} - \mathbf{M}'\|_{\mathrm{F}}^2 \leq \epsilon$, where $\mathbf{M}' = \sum_{l=1}^k \eta_l \mathbf{X}^l$ and $\mathbf{X}^l \in \mathcal{P}_n$ for $l \in [k]$. However, it is not currently practical to operate directly on $\mathcal{P}_n$ as we have to solve a combinatorial optimization problem. Additionally, $\mathcal{P}_n$ lacks a manifold structure. Thus, we relax the domain of the absolute permutations by assuming that each $\mathbf{X}^l \in \mathcal{DP}_n$ for $l \in [k]$ (Linderman et al., 2018; Birdal & Simsekli, 2019; Lyzinski et al., 2015; Yan et al., 2016). We add an orthogonal regularization to ensure that each matrix $\mathbf{X}^l$ is approximately orthogonal. We can use Riemannian gradient descent-based methods to minimize the total loss.

3.2 Optimization problem

Reconstruction loss. This loss measures the reconstruction error for a given set of candidate DS matrices, $\left\{\mathbf{X}^l\right\}_{l=1}^k$ and weight vector $\eta \in \Delta_n$, as follows:

$$L_{\mathrm{recons}}\left(\eta, \left\{\mathbf{X}^l\right\}_{l=1}^k\right) = \left\|\mathbf{M} - \sum_{l=1}^k \eta_l \mathbf{X}^l\right\|_F^2. \tag{4}$$

Orthogonal regularization. This loss encourages a DS matrix $\mathbf{X}$ to be approximately orthogonal by pushing them towards the nearest orthogonal manifold Brock et al. (2017). We compute it as follows:

$$L_{\mathrm{ortho}}\left(\mathbf{X}\right) = \sum_{(i,j)\in[n]^2} \left|\left(\mathbf{X}^\mathsf{T}\mathbf{X} - \mathbf{I}\right)_{ij}\right|. \tag{5}$$

Optimization objective. We compute the total loss by adding the reconstruction loss and an orthogonal regularization for each $\mathbf{X}^l$ for $l \in [k]$, as follows:

$$\min_{\left\{\mathbf{X}^i \in \mathcal{DP}_n\right\}_{i=1}^k, \eta \in \Delta^k} L\left(\eta, \left\{\mathbf{X}^i\right\}_{i=1}^k; \mu, \omega\right) = L_{\mathrm{recons}}\left(\eta, \left\{\mathbf{X}^i\right\}_{i=1}^k\right) + \mu \sum_{i=1}^k L_{\mathrm{ortho}}\left(\mathbf{X}^i\right) + \omega\,\Omega(\eta),$$

$$\tag{6}$$

where $\omega > 0, \mu > 0$ are regularization hyper-parameters that control the trade-off between reconstruction and orthogonality. $\Omega(\cdot)$ is a regularization function, which induces weight diversity. The regularization function is necessary to avoid trivial solutions and to force using various components into the reconstruction. We set $\Omega(\cdot) = \| \cdot \|_2^2$. Algorithm 1 displays a summary of our proposed solution.

Refinement. The primary use of the BvND is to sample (binary) permutations matrices from a DS matrix. However, the solution of Eq. 6 yields approximately orthogonal matrices. Thus, we still need to round/refine the solution to return a permutation matrix. We can use two different approaches: deterministic rounding or rounding by stochastic sampling. The deterministic rounding finds a feasible permutation of a given DS matrix via the Hungarian algorithm (Birdal & Simsekli, 2019). However, the matching is not differentiable. In that case, we can also use the Sinkhorn algorithm with a small entropic regularization (temperature). Another approach consists of sampling from Gumbel-Sinkhorn distribution (Mena et al., 2018).

Algorithm 1 Differentiable approximate BvND

Require: DS matrix $\mathbf{M}$, number k of sub-permutation matrices, learning rate γ, regularization parameters μ and ω

Ensure: $\left(\eta^*, \left\{\mathbf{X}^{i*}\right\}_{i=1}^{k}\right)$ that minimizes Eq. 6

1: **while** not converge **do**
2:   **for** $i \in [k]$ **do**
3:     Update using Riemannian gradient descent:

$$\mathbf{X}^{i(t+1)} \leftarrow R_{\mathbf{X}^{i(t)}} \left[-\gamma \, \Pi_{\mathbf{X}^{i(t)}} \left[\nabla_{\mathbf{X}^{i(t)}} L \left(\text{softmax}(\eta^{(t)}), \left\{\mathbf{X}^{i(t)}\right\}_{i=1}^{k} ; \mu, \omega \right) \right] \right]$$

4:   **end for**
5:   Update using gradient descent:

$$\eta^{(t+1)} \leftarrow \eta^{(t)} - \gamma \nabla_{\eta^{(t)}} L \left(\text{softmax}(\eta^{(t)}), \left\{\mathbf{X}^{i(t)}\right\}_{i=1}^{k} ; \mu, \omega \right)$$

6: **end while**

---

4 APPLICATION: FAIRNESS OF EXPOSURE IN RANKINGS

We rely on the approach developed by Singh & Joachims (2018), which tackles the presentation bias in ranking systems. Learning to rank algorithms tends to display top-ranked results more often given the user feedback (usually clicks), which leads to ignoring other potentially relevant results. In brief, the method finds a probabilistic re-ranking system which satisfies specific presentation bias constraints We encode this probabilistic re-ranking in a DS matrix. We decompose this DS matrix using the BvN algorithm. Then, one can select a sub-permutation matrix at random using a probability proportional to the decomposition coefficient. Thus, this re-ranking approach will satisfy group fairness constraints in expectation.

For simplicity, we assume a single query $\mathbf{q}$ and consider that we want to present a ranking of a set of n documents/items $\mathcal{D} = \{\mathbf{d}_i\}_{i=1}^{n}$. We denote by $\mathcal{U}$ the set of all users $\mathbf{u}$ that lead to identical $\mathbf{q}$. We represent $\text{rel}(\mathbf{d}, \mathbf{q})$ the measure of relevances for a given query[1]. We assume a full information setting. Thus relevances are known. We use the relevances to compute the utility, e.g., discounted cumulative gain (DCG), or the Normalized DCG (NDCG, the DCG normalized by the DCG of the optimal ranking) (Järvelin & Kekäläinen, 2002).

---

[1]We can extend this definition to include user preferences, $\text{rel}(\mathbf{d}, \mathbf{q}, \mathbf{u})$.

4.1 STATIC CASE

We can write a utility function U in terms of a probabilistic ranking $\mathbf{M}$ for a query $\mathbf{q}$ as

$$U(\mathbf{M}|\mathbf{q}) = \sum_{\mathbf{d}_i \in \mathcal{D}} \sum_{j=1}^{n} \mathbf{M}_{ij} \, u(\mathbf{d}_i|\mathbf{q}) \, v(j), \qquad (7)$$

where $\mathbf{M} \in \mathcal{DP}_n$ is the probabilistic ranking. Thus $\mathbf{M}_{ij}$ represents the probability of replacing document $\mathbf{d}_i$ (indexed at position i) at rank j. $u(\mathbf{d}|\mathbf{q}) \coloneqq \sum_{\mathbf{u} \in \mathcal{U}} \Pr[\mathbf{u}|\mathbf{q}] \, f(\mathrm{rel}(\mathbf{d}, \mathbf{q}))$, is the expected utility of document $\mathbf{d}$ for query $\mathbf{q}$, where $f(\cdot)$ maps the relevance of the document for a user to its utility. $v(j)$ is the examination propensity; it models how much attention an item $\mathbf{d}$ at position j. We use a logarithmic discount in the position $\mathbf{v}_j = v(j) = \frac{1}{\log_2(1+j)}$ and $f(\mathrm{rel}(\mathbf{d}, \mathbf{q})) = 2^{\mathrm{rel}(\mathbf{d}, \mathbf{q})} - 1$. Thus, the utility function Eq. 7 corresponds to the expected DCG.

We include fairness constraint by solving: $\mathbf{M}^* = \arg\max_{\mathbf{M} \in \mathcal{DP}_n} U(\mathbf{M}|\mathbf{q})$ subject to $\mathbf{M}$ is fair. Singh & Joachims (2018) define several fairness constraints that are linear in $\mathbf{M}$, and this problem boils down to solving a linear program. However, in prediction time, one needs to sample from $\mathbf{M}$. Thus, we use the BvN algorithm to decompose $\mathbf{M}$ into the convex combination of k permutation matrices $\mathbf{P}^k$. One chooses a permutation at random with a probability proportional to the coefficient. The resulting model satisfies the fairness constraint in expectation.

To set our fairness constraints, we need first to define the merit, impact, and exposure of an item $\mathbf{d}$. The merit of item is its expected average relevance. The exposure of item $\mathbf{d}$ is the probability $P(\mathbf{d})$ that the user will see $\mathbf{d}$ and thus can read that article, buy that product, etc. We note that estimating the position bias is not part of our study. We assume full knowledge of these position-based probabilities. We use the feedback C, e.g., clicks, as a measure of impact. We extend these definitions to group $\mathcal{G} \subseteq \mathcal{D}$ by aggregating over the group. Then, we have for a protected group $\mathcal{G}$

$$\mathrm{Merit}(\mathcal{G}) = \frac{1}{|\mathcal{G}|} \sum_{\mathbf{d} \in \mathcal{G}} u(\mathbf{d}|\mathbf{q}), \quad \mathrm{Imp}(\mathcal{G}) = \frac{1}{|\mathcal{G}|} \sum_{\mathbf{d} \in \mathcal{G}} C(\mathbf{d}), \text{ and } \mathrm{Expo}(\mathcal{G}) = \frac{1}{|\mathcal{G}|} \sum_{\mathbf{d} \in \mathcal{G}} P(\mathbf{d}). \quad (8)$$

Setting the constraints as functions of the probabilistic ranking $\mathbf{M}$. $\hat{\mathrm{Expo}}(\mathbf{d}_i|\mathbf{M}) = \sum_{j=1}^{n} \mathbf{M}_{ij} \mathbf{v}_j$. Assuming the Position-Based Model (PBM) click model, the estimated probability of a click is the exposure $\times$ conditional relevancy. Thus, the estimated probability of click on a document $\mathbf{d}_i$ is $C(\mathbf{d}) = \hat{\mathrm{Expo}}(\mathbf{d}|\mathbf{M}) u(\mathbf{d}|\mathbf{q})$. Therefore, we can estimate the average impact and exposure on the items in group G for the rankings defined by $\mathbf{M}$ as

$$\hat{\mathrm{Imp}}(\mathcal{G}|\mathbf{M}) = \frac{1}{|\mathcal{G}|} \sum_{\mathbf{d}_i \in \mathcal{G}} u(\mathbf{d}|\mathbf{q}) \left(\sum_{j=1}^{n} \mathbf{M}_{ij} \mathbf{v}_j \right) \text{ and } \hat{\mathrm{Expo}}(\mathcal{G}|\mathbf{M}) = \frac{1}{|\mathcal{G}|} \sum_{\mathbf{d}_i \in \mathcal{G}} \sum_{j=1}^{n} \mathbf{M}_{ij} \mathbf{v}_j. \quad (9)$$

Here, we only use disparate exposure and impact constraints as fairness constraints. The disparity constraints $D(\mathcal{G}_i, \mathcal{G}_j)$ is the difference of the fairness metric between protected groups $\mathcal{G}_i$ and $\mathcal{G}_j$, divided by their respective merit. We denote $D^E(\mathcal{G}_i, \mathcal{G}_j)$ and $D^I(\mathcal{G}_i, \mathcal{G}_j)$ to be the Disparity Exposure Constraint and Disparity Impact Constraint, respectively. Let $\hat{D}(\mathcal{G}_i, \mathcal{G}_j)$ be the difference in estimations.

4.2 FAIRNESS IN DYNAMIC LEARNING-TO-RANK

Morik et al. (2020) present an extension of the fairness of exposure (see Section 4) to a dynamic setting. They propose a fairness controller algorithm that ensures notions group fairness amortized through time. This algorithm dynamically adapts both utility function and fairness as more data becomes available.

Here, we assume that both the exposure and the impact vary through time, $\mathrm{Imp}_t(\mathcal{G})$, and $\mathrm{Expo}_t(\mathcal{G})$. Then, we use the cumulative fairness constraint over τ time steps, e.g., $\frac{1}{\tau} \sum_{t=1}^{\tau} \mathrm{Imp}_t(\mathcal{G})$. We extend it to their estimations too.

The optimization problem is

$$\mathbf{M}^* = \underset{\mathbf{M} \in \mathcal{DP}_n, \zeta_{ij} \geq 0}{\arg\max} \ U(\mathbf{M}\,|\,\mathbf{q}) - \lambda \sum_{ij} \zeta_{ij}$$

$$\text{s.t.} \ \ \forall \mathcal{G}_i, \mathcal{G}_j : \ \hat{D}_\tau(\mathcal{G}_i, \mathcal{G}_j) + D_{\tau-1}(\mathcal{G}_i, \mathcal{G}_j) \leq \zeta_{ij},$$

(10)

where $\lambda \geq 0$ controls the trade-off between ranking score and fairness.

5 EXPERIMENTS

We explore our differentiable approximate BvND's behavior on synthetic data and validate its usefulness in the fairness of exposure in ranking problems.

Optimization. We build DS Random matrices naively to initialize each component $\mathbf{X}^l$. For $l \in [k]$, we sample each element of matrix $\mathbf{M}_{ij}^l, \forall (i,j) \in [n]^2$ from a half-normal distribution, i.e., the absolute value of an i.i.d. sample drawn from a Gaussian. Then, we project onto DS using the Sinkhorn algorithm.

Technical aspects. We give a Pytorch (Paszke et al., 2019) implementation in Appendix A. We use RiemannianADAM implemented in the geootp library (Kochurov et al., 2020). We run all the experiments on a single desktop machine with a 4-core Intel Core i7 2.4 GHz.

5.1 SYNTHETIC DATA

Setup. We build a set of ten DS Random matrices $\{\mathcal{DP}_n\}_{n=1}^{10}$, where $n \in [4, 6, 10]$. To add sparsity, we mask each matrix by thresholding at $[0.1, 0.5, 0.9]$ divided n, respectively. Then, we project the masking result using the Sinkhorn algorithm. We explore the performance of the differentiable BvND as a function of the number of k components. We measure the computation time, the reconstruction error, and the orthogonalization error.

n	k	computation time (min)
4	20	4.43 ± 1.28
6	30	8.68 ± 2.18
10	40	15.13 ± 5.49

Table 1: Computation time

Results. We observe in Fig. 2 the reconstruction error is monotonically decreasing. However, the approximate orthogonalization constraint becomes more challenging to satisfy when increasing the DS input matrix's dimensionality. Table 1 shows the the computation time for each parameter.

5.2 STATIC FAIRNESS OF EXPOSURE

Setup. We use the toy example presented in Singh & Joachims (2018). These data represent a web-service that connects employers (users) to potential employees (items). The set contains three males and three females. The male applicants have relevance for the employers of 0.80, 0.79, 0.78, respectively, while the female applicants have

Figure 2: Performance of the differentiable BvND on synthetic data: We use different matrix sizes. *(top)* Reconstruction error as a function of the number of components. *(bottom)* Histogram of the orthogonalization error of each component.

the relevance of 0.77, 0.76, 0.75, respectively. Here we follow the standard probabilistic definition of relevance, where 0.77 means that 77% of all employers issuing the query find that applicant relevant. The Probability Ranking Principle suggests ranking these applicants in the decreasing order of relevance, i.e., the three males at the top positions, followed by the females. The task is to re-rank them so that the system satisfies equal opportunity

of exposure across groups. Thus, we solve a linear program to maximize Eq 7 such that $\hat{D}^E(\mathcal{G}_{\text{Male}}, \mathcal{G}_{\text{Female}}) \leq 10^{-6}$.

(a) DCG: 2.37   (b) DCG: 2.36

Figure 3: Static fairness exposure on toy data: *a)* Unfair ranking; *b)* Ranking satisfies the disparate exposure constraint. We decompose a fair probabilistic ranking using the approximate and differentiable BvND using three components.

Results. Fig. 3 shows a toy example of the fairness of exposure. Fig. 3a presents the original biased ranking, whereas Fig. 3b shows a fair probabilistic ranking, which has a negligible loss in performance. Note that solving this problem does not imply that each sub-permutation matrix is unique. In practice, we often find a decomposition with repeated sub-permutations.

5.3 Dynamic Fairness of Exposure

Setup. We rely on Morik et al. (2020) to simulate an environment based on articles in the Ad Fontes Media Bias dataset, which generates a dynamic ranking on a set of news articles belonging to two groups left-leaning and right-leaning news articles, $\mathcal{G}_{\text{left}}$ and $\mathcal{G}_{\text{right}}$, respectively. See Appendix C for a full description of this simulation. We use dynamic learning to rank settings to minimize amortized fairness disparities. We solve Eq. 10 using linear programming. We evaluate the effectiveness of our differentiable approximate BvND (Diff-BvN) algorithm compared to the standard implementation of the BvND (BvN). We explore the difference between both models over various trade-offs between ranking score and fairness λ. Then, we measure their performance for a fixed λ.

Baseline. We use as a baseline the greedy heuristic of BvN (Dufossé & Uçar, 2016; Dufossé et al., 2018). For the Diff-BvN, we set the number of components to $k = 10$, the learning rate $\gamma = 10^{-3}$, and relative tolerance of 10^4. We use $\omega = 1$ and $\mu = 10^{-2}$. We refine the matrix using the Hungarian algorithm (Kuhn, 1955) to ensure returning a permutation matrix. However, we also tried the stabilized Sinkhorn used in Cuturi et al. (2019) with the same performance.

Results. Fig. 4 presents the performance of BvN and Diff-BvN over various values of the fairness regularization parameter λ. Fig. 4a shows the NDCG of both methods, whereas Fig. 4c shows their unfairness of impact. Regarding the NDCG, BvN and Diff-BvN display the same performance across different values of λ. We observe the same pattern in the unfairness of exposure and impact, Fig.4b and Fig.4c, respectively.

We set the fairness regularization parameter to $\lambda = 10^{-2}$. We see in Fig. 5 that the performance of the re-ranked system is the same for BvN and Diff-BvN.

6 Discussion and Conclusion

In this paper, we proposed a differentiable approximated Birkhoff-von-Neumann decomposition (Diff-BvN). Our algorithm approximates a DS matrix by a convex combination of matrices on the Birkhoff polytope, where each matrix in the decomposition is approximately orthogonal. We can minimize the final loss function using Riemannian gradient descent. Our algorithm is easy to implement on standard auto-diff-based libraries. Experiments on the fairness of exposure in ranking problems show that our algorithm yields similar

(a) Averaged cumulative NDCG

(b) Group-difference of exposure per true relevance

(c) Group-difference of clicks per true relevance

Figure 4: Performance of the fairness controller as a function of the parameter λ: Both methods, BvN and Diff-BvN display almost the same behavior across values of the regularization parameter. These values correspond to ten trials of the simulated news data of 3000 users.

(a) Average cumulative NDCG

(b) Group-difference of exposure per true relevance

(c) Group-difference of clicks per true relevance

Figure 5: Performance of the fairness controller ($\lambda = 0.01$) as a function of the number of users: Both methods, BvN and Diff-BvN display the same convergence behavior on various metrics computed on ten trials of the simulated news data (3000 users).

results to the Birkhoff-von-Neumann decomposition algorithm with a greedy heuristic. Our algorithm provides an alternative to existing approaches to sample permutation matrices from a DS matrix. In particular, it offers the option to balance the trade-off between memory and time in prediction settings. Fewer assignments lead to improved performance in some applications (Porter et al., 2013; Liu et al., 2015). Thus, our algorithm can display better performance that greedy approaches as one sets the number of assignments a priory.

Potential improvements. The current implementation of our algorithm does not impose diversity on the sub-permutation matrices. Thus, it often produces repeated sub-permutations matrices. In practice, our algorithm is sensitive to the orthogonal constraints. Therefore, we believe than there is a need to define a scheduler for the orthogonal regularization parameter. Additionally, we note that the current implementation of our algorithm is still limited to small matrices. Thus, we need to explore different possible directions to make it scalable, e.g., randomization.

REFERENCES

P-A Absil, Robert Mahony, and Rodolphe Sepulchre. *Optimization algorithms on matrix manifolds*. Princeton University Press, 2009.

Siddharth Barman. Approximating nash equilibria and dense subgraphs via an approximate version of carathéodory's theorem. *SIAM Journal on Computing*, 47:960–981, 2018.

Tolga Birdal and Umut Simsekli. Probabilistic permutation synchronization using the riemannian structure of the birkhoff polytope. In *CVPR*, pp. 11105–11116, 2019.

Garrett Birkhoff. Three observations on linear algebra. *Univ. Nac. Tacuman, Rev. Ser. A*, 5: 147–151, 1946.

Silvere Bonnabel. Stochastic gradient descent on riemannian manifolds. *IEEE Transactions on Automatic Control*, 58:2217–2229, 2013.

Andrew Brock, Theodore Lim, James Millar Ritchie, and Nicholas J Weston. Neural photo editing with introspective adversarial networks. In *ICLR*, 2017.

A Chuklin, I Markov, and M de Rijke. Click models for web search. synthesis lectures on information concepts, retrieval, and services. *vol*, 7:1–115, 2015.

Marco Cuturi, Olivier Teboul, and Jean-Philippe Vert. Differentiable ranking and sorting using optimal transport. In *NeurIPS*, pp. 6861–6871, 2019.

Ahmed Douik and Babak Hassibi. Manifold optimization over the set of doubly stochastic matrices: A second-order geometry. *IEEE Transactions on Signal Processing*, 67:5761–5774, 2019.

Fanny Dufossé and Bora Uçar. Notes on birkhoff–von neumann decomposition of doubly stochastic matrices. *Linear Algebra and its Applications*, 497:108–115, 2016.

Fanny Dufossé, Kamer Kaya, Ioannis Panagiotas, and Bora Uçar. Further notes on birkhoff–von neumann decomposition of doubly stochastic matrices. *Linear Algebra and its Applications*, 554:68–78, 2018.

Michel X Goemans. Smallest compact formulation for the permutahedron. *Mathematical Programming*, 153:5–11, 2015.

Aditya Grover, Eric Wang, Aaron Zweig, and Stefano Ermon. Stochastic optimization of sorting networks via continuous relaxations. In *ICLR*, 2018.

GLENN Hurlbert. A short proof of the birkhoff-von neumann theorem. *preprint (unpublished)*, 2008.

Kalervo Järvelin and Jaana Kekäläinen. Cumulated gain-based evaluation of ir techniques. *ACM TOIS*, 20:422–446, 2002.

Anson Kahng, Yasmine Kotturi, Chinmay Kulkarni, David Kurokawa, and Ariel D Procaccia. Ranking wily people who rank each other. *AAAI 2018*, 2018.

Orgad Keller, Avinatan Hassidim, and Noam Hazon. Approximating bribery in scoring rules. In *AAAI*, pp. 1121–1129, 2018.

Orgad Keller, Avinatan Hassidim, and Noam Hazon. Approximating weighted and priced bribery in scoring rules. *Journal of Artificial Intelligence Research*, 66:1057–1098, 2019.

Max Kochurov, Rasul Karimov, and Serge Kozlukov. Geoopt: Riemannian optimization in pytorch, 2020.

Harold W Kuhn. The hungarian method for the assignment problem. *Naval research logistics quarterly*, 2:83–97, 1955.

Janardhan Kulkarni, Euiwoong Lee, and Mohit Singh. Minimum birkhoff-von neumann decomposition. In *International Conference on Integer Programming and Combinatorial Optimization*, pp. 343–354. Springer, 2017.

Yanzhe Murray Lei, Stefanus Jasin, Joline Uichanco, and Andrew Vakhutinsky. Randomized product display (framing), pricing, and order fulfillment for e-commerce retailers. *Stefanus and Uichanco, Joline and Vakhutinsky, Andrew, Randomized Product Display (Framing), Pricing, and Order Fulfillment for E-commerce Retailers (November 9, 2018)*, 2018.

Scott Linderman, Gonzalo Mena, Hal Cooper, Liam Paninski, and John Cunningham. Reparameterizing the birkhoff polytope for variational permutation inference. In *AISTATS*, pp. 1618–1627. PMLR, 2018.

He Liu, Matthew K Mukerjee, Conglong Li, Nicolas Feltman, George Papen, Stefan Savage, Srinivasan Seshan, Geoffrey M Voelker, David G Andersen, Michael Kaminsky, et al. Scheduling techniques for hybrid circuit/packet networks. In *Proceedings of the 11th ACM Conference on Emerging Networking Experiments and Technologies*, pp. 1–13, 2015.

Liang Liu, Jun Xu, and Lance Fortnow. Quantized bvnd: A better solution for optical and hybrid switching in data center networks. In *IEEE/ACM UCC*, pp. 237–246. IEEE, 2018.

Vince Lyzinski, Donniell E Fishkind, Marcelo Fiori, Joshua T Vogelstein, Carey E Priebe, and Guillermo Sapiro. Graph matching: Relax at your own risk. *IEEE TPAMI*, 38:60–73, 2015.

Gonzalo Mena, David Belanger, Scott Linderman, and Jasper Snoek. Learning latent permutations with gumbel-sinkhorn networks. In *ICLR*, 2018.

Marco Morik, Ashudeep Singh, Jessica Hong, and Thorsten Joachims. Controlling fairness and bias in dynamic learning-to-rank. *arXiv preprint arXiv:2005.14713*, 2020.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *NeurIPS*, pp. 8024–8035. Curran Associates, Inc., 2019.

Sergey Plis, Stephen McCracken, Terran Lane, and Vince Calhoun. Directional statistics on permutations. In *AISTATS*, pp. 600–608, 2011.

George Porter, Richard Strong, Nathan Farrington, Alex Forencich, Pang Chen-Sun, Tajana Rosing, Yeshaiahu Fainman, George Papen, and Amin Vahdat. Integrating microsecond circuit switching into the data center. *ACM SIGCOMM Computer Communication Review*, 43:447–458, 2013.

Ashudeep Singh and Thorsten Joachims. Fairness of exposure in rankings. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 2219–2228, 2018.

Richard Sinkhorn and Paul Knopp. Concerning nonnegative matrices and doubly stochastic matrices. *Pacific Journal of Mathematics*, 21:343–348, 1967.

Steven T Smith. Optimization techniques on riemannian manifolds. *Fields Institute Communications*, 3, 1994.

Stefan Sommer, Tom Fletcher, and Xavier Pennec. Introduction to differential and riemannian geometry. In *Riemannian Geometric Statistics in Medical Image Analysis*, pp. 3–37. Elsevier, 2020.

Junchi Yan, Xu-Cheng Yin, Weiyao Lin, Cheng Deng, Hongyuan Zha, and Xiaokang Yang. A short survey of recent advances in graph matching. In *Proceedings of the 2016 ACM on International Conference on Multimedia Retrieval*, pp. 167–174, 2016.

Andrei Zanfir and Cristian Sminchisescu. Deep learning of graph matching. In *CVPR*, pp. 2684–2693, 2018.

A PYTORCH IMPLEMENTATION

```python
import torch
import geoopt
from torch import nn
from geoopt import ManifoldParameter
from geoopt.manifolds import BirkhoffPolytope

class BirkhoffVonNeumannDecomposition(nn.Module):
    """ Approximate differentiable Birkhoff-von-Neumann decompsition
    of a doubly-stochastic matrix.

    Parameters
    ----------
    n : int, size of the matrix.

    n_components : int (optional), the number of coefficients in the
    approximation.

    Attributes
    ----------
    manifold : BirkhoffPolytope
    Matrices: ManifoldParameter, Matrix on the Birkhoff Polytope.
            Used to compute compute RiemannianADAM.
    weight : nn.Parameter, Tensor of coefficients.

    """
    def __init__(self, n, n_components=2):
        super(BirkhoffVonNeumannDecomposition, self).__init__()
        self.n = n
        self.n_components = n_components
        self.manifold_ = BirkhoffPolytope()
        self.Matrices = nn.ParameterDict(
            {
                str(ind):
                ManifoldParameter(
                    data=self.manifold_.random((n, n)),
                    manifold=self.manifold_)
                for ind in range(n_components)
            } )
        self.weight = nn.Parameter(data=torch.rand(1, 1, n_components))

    def forward(self, input=None):
        w = torch.softmax(self.weight, dim=-1)
        Ms = torch.cat([
            self.Matrices[str(choice)].unsqueeze(2)
            for choice in range(self.n_components)
            ], dim=2)
        return (Ms * w).sum(-1)
```

Listing 1: Approximate Birkhoff-von-Neumann decomposition (ApproxBvND)

```python
import torch
import numpy as np

def ortho_error(X):
    n_samples = len(X)
    return (X.T @ X - torch.eye(n_samples)).abs().sum()

def reconstruction_error(A, A_approx):
```

```python
        return torch.norm(A - A_approx, p='fro').pow(2)

def train(model,
          A: torch.Tensor,
          lr: float=1e-2,
          max_iter: int=5000,
          reg_weights: float=1.,
          reg_ortho: float=.01,
          stop_thr: float=1e-4):
    """Training function.

    A :  Tensor, is the doubly-stochastic matrix to approximate.

    lr : float (optional), learning rate of the RiemannianADAM.

    max_iter :  int (optional), maximum number of iterations.

    reg_weights : float (optional), regularization parameter for the
    weigths.

    reg_ortho : float (optional), regularization parameter for the
    orthogonal constraints.

    stop_thr : float (optional), stopping threshold.

    """
    optimizer = RiemannianAdam(list(model.parameters()), lr=lr)
    vloss = [stop_thr]
    loop = 1 if max_iter > 0 else 0
    it = 0
    while loop:
        it += 1
        optimizer.zero_grad()
        with torch.enable_grad():
            orth_loss = torch.zeros(1)
            for param in model.parameters():
                if isinstance(param,
                              geoopt.tensor.ManifoldParameter):
                    orth_loss += ortho_error(param)
                else:
                    weight_reg = model.weight.pow(2).sum()

        A_recons = model()
        reconstruction_loss = reconstruction_error(
            A, A_recons)

        loss = (
            reconstruction_loss
            + reg_ortho * orth_loss
            + reg_weights * weight_reg
        )
        vloss.append(loss.item())

        relative_error = (
            abs(vloss[-1] - vloss[-2]) / abs(vloss[-2])
            if vloss[-2] != 0 else 0.)

        if ((it >= max_iter) or
           (np.isnan(vloss[-1])) or
           (relative_error < stop_thr)):
            loop = 0

        loss.backward()
        optimizer.step()
```

```
    return model
```

Listing 2: Training utils

B RIEMANNIAN OPTIMIZATION

A Riemannian manifold is a smooth manifold $\mathcal{M}$ of dimension d that can be locally approximated by an Euclidean space $\mathbb{R}^d$. At each point $\mathbf{x} \in \mathcal{M}$ one can define a d-dimensional vector space, the tangent space $T_\mathbf{x}\mathcal{M}$. We characterize the structure of this manifold by a Riemannian metric, which is a collection of scalar products $\rho = \{\rho(\cdot, \cdot)_\mathbf{x}\}_{\mathbf{x} \in \mathcal{M}}$, where $\rho(\cdot, \cdot)_\mathbf{x} : T_\mathbf{x}\mathcal{M} \times T_\mathbf{x}\mathcal{M} \to \mathbb{R}$ on the tangent space $T_\mathbf{x}\mathcal{M}$ varying smoothly with $\mathbf{x}$. The Riemannian manifold is a pair $(\mathcal{M}, \rho)$ (Sommer et al., 2020).

The tangent space linearizes the manifold at a point $\mathbf{x} \in \mathcal{M}$, making it suitable for practical applications as it leverages the implementation of algorithms in the Euclidean space. We use the Riemannian exponential and logarithmic maps to project samples onto the manifold and back to tangent space, respectively. The Riemannian exponential map, when well-defined, $\mathrm{Exp}_\mathbf{x} : T_\mathbf{x}\mathcal{M} \to \mathcal{M}$ realizes a local diffeomorphism from a sufficiently small neighborhood $\mathbf{0}$ in $T_\mathbf{x}\mathcal{M}$ into a neighborhood of the point $\mathbf{x} \in \mathcal{M}$.

Riemannian gradient descent. The base Riemannian gradient methods (Bonnabel, 2013; Smith, 1994) use the following update rule $\mathbf{w}_{t+1} = \mathrm{Exp}_{\mathbf{w}_t}(-\gamma_t H(\mathbf{w}_t))$, where $\mathbf{w}_{t+1} = \mathrm{Exp}_{\mathbf{w}_t}(-\gamma_t H(\mathbf{w}_t))$ is the Riemannian gradient of the loss $L : \mathcal{M} \to \mathbb{R}$ at $\mathbf{w}_t$, and γ_t is the learning rate. However, the exponential map is not easy to compute in many cases, as one needs to solve a calculus of variations problem or know the Christoffel symbols (Bonnabel, 2013). Thus, it is much easier and faster to use a first-order approximation of the exponential map, called a retraction. A retraction $R_\mathbf{w}(\mathbf{v}) : T_\mathbf{w}\mathcal{M} \to \mathcal{M}$ maps the tangent space at $\mathbf{w}$ to the manifold such that $d(R_\mathbf{w}(t\mathbf{v}), \mathrm{Exp}_\mathbf{w}(t\mathbf{v})) = O(t^2)$, this imposes a local rigidity condition that preserves gradients. Therefore, one can rely on the retraction to compute the alternative update $\mathbf{w}_{t+1} = R_{\mathbf{w}_t}(-\gamma_t H(\mathbf{w}_t))$ (Absil et al., 2009).

Douik & Hassibi (2019) introduced the following computation of the retraction mapping and the projection onto the tangent space of DS matrices. The proofs can be found in (Douik & Hassibi, 2019).

Theorem 2 *The projection operator $\Pi_\mathbf{X}(\mathbf{Y})$ maps $\mathbf{Y} \in \mathcal{DP}_n$ onto the tangent space at $\mathbf{X} \in \mathcal{DP}_n$, $T_\mathbf{X}\mathcal{DP}_n$ is written as*

$$\Pi_\mathbf{X}(\mathbf{Y}) = \mathbf{Y} - \left(\alpha\mathbf{1}^\mathsf{T} + \mathbf{1}\beta^\mathsf{T}\right) \odot \mathbf{X}, \tag{11}$$

where $\alpha = \left(\mathbf{I} - \mathbf{X}\mathbf{X}^\mathsf{T}\right)^+ \left(\mathbf{Y} - \mathbf{X}\mathbf{Y}^\mathsf{T}\right)\mathbf{1}$ and $\beta = \mathbf{Y}^\mathsf{T}\mathbf{1} - \mathbf{X}^\mathsf{T}\alpha$.

Theorem 3 (Retraction) *For a vector $\zeta_\mathbf{X} \in T_\mathbf{X}\mathcal{DP}_n$ lying on the tangent space at $\mathbf{X} \in \mathcal{DP}_n$, the first order retraction map $R_\mathbf{X}$ is given by*

$$R_\mathbf{X}(\zeta_\mathbf{X}) = \Pi\left(\mathbf{X} \odot \exp\left(\zeta_\mathbf{X} \oslash \mathbf{X}\right)\right), \tag{12}$$

where the operator Π denotes the projection onto $\mathcal{DP}_n$, efficiently computed using the Sinkhorn algorithm (Sinkhorn & Knopp, 1967).

C SIMULATIONS

News data. Morik et al. (2020) contain the description of this dataset. Nevertheless, we added it for completeness. In each trial, we sample a set of 30 news articles $\mathcal{D}$. For each article $\mathbf{d}$, the dataset contains a polarity value $\rho^\mathbf{d}$ that we rescale to the interval between -1 and 1. We simulate the user polarities. We draw the polarity for each user from a mixture of two normal distributions clipped to $[-1, 1]$, $\rho^{\mathbf{u}_t} \sim \mathrm{clip}_{[-1,1]}\left(p_{\mathrm{neg}}\mathcal{N}(-.5, .2) + (1 - p_{\mathrm{neg}})\mathcal{N}(.5, .2)\right)$, where p_{neg} is the probability of the user to be left-learning (mean -0.5). We use $p_{\mathrm{neg}} = 0.5$. Besides, each user has an openness parameter $o^{\mathbf{u}_t} \sim \mathcal{U}(.05, .55)$, indicating the breadth of interest outside their polarity.

We draw the true relevance from the Bernoulli distribution $\mathbf{r}_t(\mathbf{d}) \sim$ Berrnoulli $\left[p = \exp\left(\frac{-(\rho^{\mathbf{u}_t} - \rho^{\mathbf{d}})^2}{2(o^{\mathbf{u}_t})^2}\right)\right]$. We use the Position-based click model (PBM (Chuklin et al., 2015)) to model user behavior, where the marginal probability that a user $\mathbf{u}_t$ examines an article $\mathbf{d}$ depends only on its position. The remainder of the simulation follows the dynamic ranking setup. At each time step t a user $\mathbf{u}_t$ arrives at the system, the algorithm presents an unpersonalized ranking and the user provides feedback $\mathbf{c}_t$ according to $\mathbf{p}_t$ and $\mathbf{r}_t$. The algorithm only observes $\mathbf{c}_t$ and not $\mathbf{r}_t$.