Active Labeling: Streaming Stochastic Gradients

Abstract

The workhorse of machine learning is stochastic gradient descent. To access stochastic gradients, it is common to consider iteratively input/output pairs of a training dataset. Interestingly, it appears that one does not need full supervision to access stochastic gradients, which is the main motivation of this paper. After formalizing the "active labeling" problem, which generalizes active learning based on partial supervision, we provide a streaming technique that provably minimizes the ratio of generalization error over number of samples. We illustrate our technique in depth for robust regression.

1 Introduction

A large amount of the current hype around artificial intelligence was fueled by the recent successes of supervised learning. Supervised learning consists in designing an algorithm that maps inputs to outputs by learning from a set of input/output examples. When accessing many samples, and given enough computation power, this framework is able to tackle complex tasks. Interestingly, many of the difficulties arising in practice do not emerge from choosing the right statistical model to solve the supervised learning problem, but from the problem of collecting and cleaning enough data (see Chapters 1 and 2 of Géron, 2017, for example). Those difficulties are not disjoint from the current trends towards data privacy regulations (Council of European Union, 2016). This fact motivates this work, where we focus on how to efficiently collect information to carry out the learning process.

In this paper, we formalize the "active labeling" problem for weak supervision, where the goal is to learn a target function by acquiring the most informative dataset given a restricted budget for annotation. We focus explicitly on weak supervision that comes as a set of label candidates for each input, aiming to partially supervise input data in the most efficient way to guide a learning algorithm. We also restrict our study to the streaming variant where, for each input, only a single partial information can be collected about its corresponding output. The crux of this work is to leverage the fact that full supervision is not needed to acquire unbiased stochastic gradients, and perform stochastic gradient descent.

The following summarizes our contributions.

1. First, we introduce the "active labeling" problem, which is a relevant theoretical framework that encompasses many useful problems encountered by practitioners trying to annotate their data in the most efficient fashion, as well as its streaming variation, in order to deal with privacy preserving issues. This is the focus of Section 2.
2. Then, in Section 3, we give a high level framework to access unbiased stochastic gradients with weak information only. This provides a simple solution to the streaming "active labeling" problem.

3. Finally, we detail this framework for a robust regression task in Section 4, and provide an algorithm whose optimality is proved in Section 5.

As a proof of concept, we provide numerical simulations in Section 6. We conclude with a high-level discussion around our methods in Section 7.

Related work. Active query of information is relevant to many settings. The most straightforward applications are searching games, such as Bar Kokhba or twenty questions (Walsorth, 1882). We refer to Pelc (2002) for a in-depth survey of such games, especially when liars introduce uncertainty, and their relations with coding on noisy channels. But applications are much more diverse, *e.g.* for numerical simulation (Chevalier et al., 2014), database search (Qarabaqi and Riedewald, 2014), or shape recognition (Geman and Jedynak, 1993), to name a few.

In terms of motivations, many streams of research can be related to this problem, such as experimental design (Chernoff, 1959), statistical queries (Kearns, 1998; Fotakis et al., 2021), crowd sourcing (Doan et al., 2011), or aggregation methods in weak supervision (Ratner et al., 2020). More precisely, "active labeling"[1] consists in having several inputs and querying partial information on the labels. It is close to active learning (Settles, 2010; Dasgupta, 2011; Hanneke, 2014), where there are several inputs but exact outputs are queried; and to active ranking (Valiant, 1975; Ailon, 2011; Braverman et al., 2019), where partial information is queried but there is only one input. The streaming variant introduces privacy preserving constraints, a problem that is usually tackled through the notion of differential privacy (Dwork et al., 2006).

In terms of formalization, we build on the partial supervision formalization of Cabannes et al. (2020), which casts weak supervision as sets of label candidates and generalizes semi-supervised learning (Chapelle et al., 2006). Finally, our sequential setting with a unique final reward is similar to combinatorial bandits in a pure-exploration setting (Garivier and Kaufmann, 2016; Fiez et al., 2019).

2 The "active labeling" problem

Supervised learning is traditionally modeled in the following manner. Consider $\mathcal{X}$ an input space, $\mathcal{Y}$ an output space, $\ell : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}$ a loss function, and $\rho \in \Delta_{\mathcal{X} \times \mathcal{Y}}$ a joint probability distribution. The goal is to recover the function

$$f^* \in \arg\min_{f:\mathcal{X} \to \mathcal{Y}} \mathcal{R}(f) := \mathbb{E}_{(X,Y) \sim \rho}[\ell(f(X), Y)], \tag{1}$$

yet, without accessing ρ, but a dataset of independent samples distributed according to ρ, $\mathcal{D}_n = (X_i, Y_i)_{i \leq n} \sim \rho^{\otimes n}$. In practice, accessing data comes at a cost, and it is valuable to understand the cheapest way to collect a dataset allowing to discriminate f^*.

We shall suppose that the input data $(X_i)_{i \leq n}$ are easy to collect, yet that labeling those inputs to get outputs $(Y_i)_{i \leq n}$ demands a high amount of work. For example, it is relatively easy to scrap the web or medical databases to access radiographies, but labeling them by asking radiologists to recognize tumors on zillions of radiographies will be both time-consuming and expensive. As a consequence, *we assume the $(X_i)_{i \leq n}$ given but the $(Y_i)_{i \leq n}$ unknown*. As getting information on the labels comes at a cost (*e.g.*, paying a pool of label workers, or spending your own time), given a budget constraint, what information should we query on the labels?

To quantify this problem, we will assume that *we can sequentially and adaptively query T information of the type $\mathbf{1}_{Y_{i_t} \in S_t}$, for any index $i_t \in \{1, \cdots, n\}$ and any set of labels $S_t \subset \mathcal{Y}$ (belonging to a specified set of subsets of $\mathcal{Y}$). Here, $t \in \{1, \cdots, T\}$ indexes the query sequence, and $T \in \mathbb{N}$ is a fixed budget. The goal is to optimize the design of the sequence (i_t, S_t) in order to get the best estimate of f^* in terms of risk minimization (1). In the following, we give some examples to make this setting more concrete.*

---

[1]Note that the wording "active labeling" has been more or less used as a synonymous of "active learning" (*e.g.,* Wang and Shang, 2014). In contrast, we use "active labeling" to design "active weakly supervised learning".

Example 1 (Classification with attributes). *Suppose that a labeler is asked to provide fine-grained classes on images (Krause et al., 2016; Zheng et al., 2019), such as the label "caracal" in Figure 6. This would be difficult for many people. Yet, it is relatively easy to recognize that the image depicts a "feline" with "tufted-ears" and "sandy color". As such, a labeler can give the weak information that Y belongs to the set "feline", S_1 = {"cat", "lion", "tiger", ...}, and the set "tufted ears", S_2 = {"Great horned owl", "Aruacana chicken", ...}. This is enough to recognize that $Y \in S_1 \cap S_2$ = {"caracal"}. The question $\mathbf{1}_{Y \in S_1}$, corresponds to asking if the image depicts a feline. Literature on hierarchical classification and autonomic taxonomy construction provides interesting ideas for this problem (e.g., Cesa-Bianchi et al., 2006; Gangaputra and Geman, 2006).*

Example 2 (Ranking with partial ordering). *Consider a problem where for a given input x, characterizing a user, we are asked to deduce their preferences over m items. Collecting such a label requires to know the exact ordering of the m items induced by a user. This might be hard to ask for. Instead, one can easily ask the user which items they prefer in a collection of few items. The user's answer will give weak information about the labels, which can be modelled as knowing $\mathbf{1}_{Y_i \in S}$ = 1, for S the set of total orderings that satisfy this partial ordering. We refer the curious reader to active ranking and dueling bandits for additional contents (Jamieson and Nowak, 2011; Bengs et al., 2021).*

Example 3 (Pricing a product). *Suppose that we want to sell a product at a consumer characterized by some features x, this consumer is ready to pay a price $y \in \mathbb{R}$ for this product. We price it $f(x) \in \mathbb{R}$, and we observe $\mathbf{1}_{f(x)<y}$, that is if the consumer is willing to buy this product at this price tag or not (Cesa-Bianchi et al., 2019; Liu et al., 2021). Although, in this setting, the goal is often to minimize the regret, which contrasts with our pure exploration setting.*

As a counter-example, our assumptions are not set to deal with missing data, *i.e.* if some coordinates of some input feature vectors X_i are missing (Rubin, 1976). Typically, this happens when input data comes from different sources (*e.g.*, when trying to predict economical growth from country information that are self-reported).

Streaming variation. The special case of the active labeling problem we shall consider consists in its variant without resampling. This corresponds to the online setting where one can only ask one question by sample, formally $i_t = t$. This setting is particularly appealing for privacy concerns, in settings where the labels (Y_i) contain sensitive information that should not be revealed totally. For example, some people might be more comfortable giving a range over a salary rather than the exact value; or in the context of polling, one might not call back a previous respondent characterized by some features X_i to ask them again about their preferences captured by Y_i. Similarly, the streaming setting is relevant for web marketing, where inputs model new users visiting a website, queries model sets of advertisements chosen by an advertising company, and one observes potential clicks.

3 Weak information as stochastic gradients

In this section, we discuss how stochastic gradients can be accessed through weak information.

Suppose that we model $f = f_\theta$ for some Hilbert space $\Theta \ni \theta$. With some abuse of notations, let us denote $\ell(x, y, \theta) := \ell(f_\theta(x), y)$. We aim at to minimizing $\mathcal{R}(\theta) = \mathbb{E}_{(X,Y)}\left[\ell(X, Y, \theta)\right]$. Assume that $\mathcal{R}$ is differentiable (or subdifferentiable) and denote its gradients by $\nabla_\theta \mathcal{R}$.

Definition 1 (Stochastic gradient). *A stochastic gradient of $\mathcal{R}$ is any random function $G : \Theta \to \Theta$ such that $\mathbb{E}[G(\theta)] = \nabla_\theta \mathcal{R}(\theta)$. Given some stepsize function $\gamma : \mathbb{N} \to \mathbb{R}^*$, a stochastic gradient descent (SGD) is a procedure, $(\theta_t) \in \Theta^\mathbb{N}$, initialized with some θ_0 and updated as $\theta_{t+1} = \theta_t - \gamma(t)G(\theta_t)$, where the realization of $G(\theta_t)$ given θ_t is independent of the previous realizations of $G(\theta_s)$ given θ_s.*

In supervised learning, SGD is usually performed with the stochastic gradients $\nabla_\theta \ell(X, Y, \theta)$. More generally, stochastic gradients are given by

$$G(\theta) = \mathbf{1}_{\nabla_\theta \ell(X,Y,\theta) \in T} \cdot \tau(T), \tag{2}$$

for $\tau : \mathcal{T} \to \Theta$ with $\mathcal{T} \subset 2^\Theta$ a set of subsets of Θ, and T a random variable on $\mathcal{T}$, such that

$$\forall \theta \in \Theta, \quad \mathbb{E}_T[\mathbf{1}_{\theta \in T} \cdot \tau(T)] = \theta. \tag{3}$$

124 For $\psi : \mathcal{Y} \to \Theta$ a function from $\mathcal{Y}$ to Θ (*e.g.*, $\psi = \nabla_\theta(X, \cdot, \theta)$), a question $\mathbf{1}_{\psi(Y) \in T}$ translates into a
125 question $\mathbf{1}_{Y \in S}$ for some set $S = \psi^{-1}(T) \subset \mathcal{Y}$, meaning that the stochastic gradient (2) can be evaluated
126 from a single query. As a proof of concept, we derive a generic implementation for T and τ in
127 Appendix B. This provides a generic SGD scheme to learn functions from weak queries.

128 **Remark 2** (Cutting plane methods). *While we provide here a descent method, one could also develop*
129 *cutting-plane/ellipsoid methods to localize θ^* according to weak information, which corresponds to*
130 *the techniques developed for pricing by Cohen et al. (2020) and related literature.*

4 Median regression

132 In this section, we focus on efficiently acquiring weak information providing stochastic gradients for
133 regression problems. In particular, we motivate and detail our methods for the absolute deviation loss.

134 Motivated by seminal works on censored data (Tobin, 1958), we shall suppose that *we query half-*
135 *spaces*. For an output $y \in \mathcal{Y} = \mathbb{R}^m$, and any hyper-plane $z + u^\perp \subset \mathbb{R}^m$ for $z \in \mathbb{R}^m$, $u \in \mathbb{S}^{m-1}$, we can
136 ask a labeler to tell us which half-space y belongs to. Formally, *we access the quantity* $\text{sign}(\langle y - z, u \rangle)$
137 *for a given unit cost.*

138 **Least-squares.** For regression problems, it is common to look at the mean square loss

$$\ell(X, Y, \theta) = \|f_\theta(X) - Y\|^2, \qquad \nabla_\theta \ell(X, Y, \theta) = 2(f_\theta(X) - Y)^\top D f_\theta(X),$$

139 where $D f_\theta(x) \in \mathcal{Y} \otimes \Theta$ denotes the Jacobian of $\theta \to f_\theta(x)$. In rich parametric models, it is preferable
140 to ask questions on $Y \in \mathcal{Y}$ rather than on gradients in Θ which is a potentially much bigger space.
141 If we assume that Y and $f_\theta(X)$ are bounded in ℓ^2-norm by $M \in \mathbb{R}_+$, we can adapt Eqs. (2) and (3)
142 through the fact that for any $z \in \mathcal{Y}$, such that $\|z\| \leq 2M$, as proven in Appendix B,

$$\mathbb{E}_{U,V} \left[\mathbf{1}_{\langle z, U \rangle \geq V} \cdot U \right] = c_1 \cdot z, \quad \text{where} \quad c_1 = \mathbb{E}_{U,V} \left[\mathbf{1}_{\langle e_1, U \rangle \geq V} \cdot \langle e_1, U \rangle \right] = \frac{\pi^{3/2}}{2M(m^2 + 4m + 3)},$$

143 for U uniform on the sphere $\mathbb{S}^{m-1}$ and V uniform on $[0, 2M]$. Applied to $z = f_\theta(X) - Y$, it designs a
144 SGD procedure by querying information of the type $\mathbf{1}_{\langle Y, U \rangle < \langle f_\theta(X), U \rangle - V}$.

145 **A case for median regression.** Motivated by robustness purposes, we will rather expand on median
146 regression. In general, we would like to learn a function that, given an input, replicates the output
147 of I/O samples generated by the joint probability ρ. In many instances, X does not characterize all
148 the sources of variations of Y, *i.e.* input features are not rich enough to characterize a unique output,
149 leading to randomness in the conditional distributions $(Y|X)$. When many targets can be linked to a
150 vector $x \in \mathcal{X}$, how to define a consensual $f(x)$? For analytical reasons, statisticians tend to use the
151 least-squares error which corresponds to asking for $f(x)$ to be the mean of the distribution $(Y|X = x)$.
152 Yet, means are known to be too sensitive to rare but large outputs (see *e.g.,* Huber, 1981), and cannot
153 be defined as good and robust consensus in a world of heavy-tailed distributions. This contrasts with
154 the median, which, as a consequence, is often much more valuable to summarize a range of value.
155 For instance, median income is preferred over mean income as a population indicator (see *e.g.*, US
156 Census Bureau, 2021).

157 **Median regression.** The geometric median is variationally defined through the absolute deviation
158 loss, leading to

$$\ell(X, Y, \theta) = \|f_\theta(X) - Y\|, \qquad \nabla_\theta \ell(X, Y, \theta) = \left(\frac{f_\theta(X) - Y}{\|f_\theta(X) - Y\|} \right)^\top D f_\theta(X). \tag{4}$$

159 Similarly to the least-squares case, we can access weakly supervised stochastic gradients through the
160 fact that for $z \in \mathbb{S}^{m-1}$, as shown in Appendix B,

$$\mathbb{E}_U \left[\text{sign}(\langle z, U \rangle) \cdot U \right] = c_2 \cdot z, \quad \text{where} \quad c_2 = \mathbb{E}_U \left[\text{sign}(\langle e_1, U \rangle) \cdot \langle e_1, U \rangle \right] = \frac{\sqrt{\pi}\Gamma(\frac{m-1}{2})}{m\Gamma(\frac{m}{2})}, \tag{5}$$

161 where U is uniformly drawn on the sphere $\mathbb{S}^{m-1}$, and Γ is the gamma function. This suggests
162 Algorithm 1.

Algorithm 1: Median regression with SGD.

Data: A model f_θ for $\theta \in \Theta$, some data $(X_i)_{i \le n}$, a labeling budget T, a stepsize rule $\gamma : \mathbb{N} \to \mathbb{R}_+$
Result: A learnt parameter $\hat\theta$ and the predictive function $\hat{f} = f_{\hat\theta}$.
Initialize θ_0.
163 **for** $t \leftarrow 1$ **to** T **do**
  Sample U_t uniformly on $\mathbb{S}^{m-1}$.
  Query $\varepsilon = \text{sign}(\langle Y_t - z, U_t \rangle)$ for $z = f_{\theta_{t-1}}(X_t)$.
  Update the parameter $\theta_t = \theta_{t-1} + \gamma(t)\varepsilon \cdot U_t^\top(Df_{\theta_{t-1}}(X_t))$.
Output $\hat\theta = \theta_T$, or some average, *e.g.*, $\hat\theta = T^{-1}\sum_{t=1}^T \theta_t$.

---

164 5   Statistical analysis

165 In this section, we quantify the performances of Algorithm 1 by proving optimal rates of convergence
166 when the median regression problem is approached with (reproducing) kernel. For simplicity, we will
167 assume that f^* can be parameterized by a linear model (potentially of infinite dimension).

168 **Assumption 1.** *Assume that the solution $f^* : \mathcal{X} \to \mathbb{R}^m$ of the median regression problem Eqs.* (1) *and*
169 (4) *can be parameterized by some separable Hilbert space $\mathcal{H}$, and a bounded feature map $\varphi : \mathcal{X} \to \mathcal{H}$,*
170 *such that, for any $i \in [m]$, there exists some $\theta_i^* \in \mathcal{H}$ such that $\langle f^*(\cdot), e_i \rangle_\mathcal{Y} = \langle \theta_i^*, \varphi(\cdot) \rangle_\mathcal{H}$, where*
171 (e_i) *is the canonical basis of $\mathbb{R}^m$. Written into matrix form, there exists $\theta^* \in \mathcal{Y} \otimes \mathcal{H}$, such that*
172 $f^*(\cdot) = \theta^* \varphi(\cdot)$.

173 The curious reader can easily relax this assumption in the realm of reproducing kernel Hilbert spaces
174 following the work of Pillaud-Vivien et al. (2018). Under the linear model of Assumption 1, Algorithm 1
175 is specified with $u^\top Df_\theta(x) = u \otimes \varphi(x)$. Note that rather than working with $\Theta = \mathcal{Y} \otimes \mathcal{H}$ which is
176 potentially infinite-dimensional, empirical estimates can be represented in the finite-dimensional
177 space $\mathcal{Y} \otimes \text{Span}\{\varphi(X_i)\}_{i \le n}$, and well approximated by small-dimensional spaces to ensure efficient
178 computations (Williams and Seeger, 2000; Meanti et al., 2020).

179 One of the key points of SGD is that gradient descent is so gradual that one can use noisy or stochastic
180 gradients without loosing statistical guarantees while speeding up computations. This is especially
181 true when minimizing convex functions that are nor strongly-convex, *i.e.*, bounded below by a
182 quadratic, nor smooth, *i.e.*, with Lipschitz-continuous gradient (see, *e.g.*, Bubeck, 2015). In particular,
183 the following theorem, proven in Appendix A.1, states that Algorithm 1 minimizes the population
184 risk at a speed at least proportional to $O(T^{-1/2})$.

185 **Theorem 1** (Convergence rates). *Under Assumption 1, and under the knowledge of κ and M two*
186 *real values such that $\mathbb{E}[\|\varphi(X)\|^2] \le \kappa^2$ and $\|\theta^*\| \le M$, with a budget $T \in \mathbb{N}$, a constant stepsize*
187 $\gamma = \frac{M}{\kappa\sqrt{T}}$ *and the average estimate $\hat\theta = \frac{1}{T}\sum_{t=0}^{T-1}\theta_t$, Algorithm 1 leads to an estimate f that suffers from*
188 *an excess of risk*

$$\mathbb{E}\left[\mathcal{R}\left(f_{\hat\theta}\right)\right] - \mathcal{R}(f^*) \le \frac{2\kappa M}{c_2\sqrt{T}} \le \kappa M m^{3/2} T^{-1/2}, \tag{6}$$

189 *where the expectation is taken with respect to the randomness of $\hat\theta$ that depends on the dataset (X_i, Y_i)*
190 *as well as the questions $(i_t, S_t)_{t \le T}$.*

191 While we give here a result for a fixed stepsize, one could retake the extensive literature on SGD to
192 prove similar results for decaying stepsizes that do not require to know the labeling budget in advance
193 (*e.g.* setting $\gamma(t) \propto t^{-1/2}$ at the expense of an extra term in $\log(T)$ in front of the rates), as well as
194 different averaging strategies (see *e.g.*, Bach, 2023). In pratice, one might not know *a priori* the
195 parameter M but could nontheless find the right scaling for γ based on cross-validation.

196 The rate in $O(T^{-1/2})$ applies more broadly to all the strategies described in Section 3 as long as the
197 loss ℓ and the parametric model f_θ ensure that $\mathcal{R}(\theta)$ is convex and Lipschitz-continuous. Although

the constants appearing in front of rates depend on the complexity to reconstruct the full gradient $\nabla_\theta \ell(f_\theta(X_i, Y_i))$ from the reconstruction scheme (3). Those constants correspond to the second moment of the stochastic gradient. For example, for the least-squares technique described earlier one would have to replace c_2 by c_1 in Eq. (6).

Theorem 2, proven in Appendix A.3, states that any algorithm that accesses a fully supervised learning dataset of size T cannot beat the rates in $O(T^{-1/2})$, hence any algorithm that collects weaker information on $(Y_i)_{i \leq T}$ cannot display better rates than the ones verified by Algorithm 1. This proves minimax optimality of our algorithm up to constants.

Theorem 2 (Minimax optimality). *Under Assumption 1 and the knowledge of an upper bound on $\|\theta^*\| \leq M$, assuming that φ is bounded by κ, there exists a universal constant c_3 such that for any algorithm $\mathcal{A}$ that takes as input $\mathcal{D}_T = (X_i, Y_i)_{i \leq T} \sim \rho^{\otimes T}$ for any $T \in \mathbb{N}$ and output a parameter θ,*

$$\sup_{\rho \in \mathcal{M}_M} \mathbb{E}_{\mathcal{D}_T \sim \rho^{\otimes T}} \left[\mathcal{R}(f_{\mathcal{A}(\mathcal{D}_T; \rho)}) \right] - \mathcal{R}(f_\rho; \rho) \geq c_3 M \kappa T^{-1/2}. \tag{7}$$

The supremum over $\rho \in \mathcal{M}_M$ has to be understood as the supremum over all distributions $\rho \in \Delta_{\mathcal{X} \times \mathcal{Y}}$ such that the problem defined through the risk $\mathcal{R}(f; \rho) := \mathbb{E}_\rho[\ell(f(X), Y)]$ is minimized for f_ρ that verifies Assumption 1 with $\|\theta^*\|$ bounded by a constant M.

The same theorem applies for least-squares with a different universal constant. It should be noted that minimax lower bounds are in essence quantifying worst cases of a given class of problems. In particular, to prove Theorem 2, we consider distributions that lead to hard problems; more specifically, we assumed the variance of the conditional distribution $(Y \mid X)$ to be high. The practitioner should keep in mind that it is possible to add additional structure on the solution, leverage active learning or semi-supervised strategy such as uncertainty sampling (Nguyen et al., 2021), or Laplacian regularization (Zhu et al., 2003; Cabannes et al., 2021a), and reduce the optimal rates of convergence.

To conclude this section, let us remark that most of our derivations could easily be refined for practitioners facing a slightly different cost model for annotation. In particular, they might prefer to preform batches of annotations before updating θ rather than modifying the question strategy after each input annotation. This would be similar to mini-batch in gradient descent. Indeed, the dependency of our result on the annotation cost model and on Assumption 1 should not be seen as a limitation but rather as a proof of concept.

6 Numerical analysis

In this section, we illustrate the differences between our active method versus a classical passive method, for regression and classification problems. Extensive details are provided in Appendix E. Our code is available online at `anonymized-url`.

Let us begin with the regression problem that consists in estimating the function f^* that maps $x \in [0, 1]$ to $\sin(2\pi x) \in \mathbb{R}$. Such a regular function, which belongs to any Hölder or Sobolev classes of functions, can be estimated with the Gaussian kernel, which would ensure Assumption 1, and that corresponds to a feature map φ such that $k(x, x') := \langle \varphi(x), \varphi(x') \rangle = \exp(-|x - x'|/(2\sigma^2))$ for any bandwidth parameter $\sigma > 0$.[2] On Figure 1, we focus on estimating f^* given data $(X_i)_{i \in [T]}$ that are uniform on $[0, 1]$ in the noiseless setting where $Y_i = f^*(X_i)$, based on the minimization of the absolute deviation loss. The passive baseline consists in randomly choosing a threshold $U_i \sim \mathcal{N}(0, 1)$ and acquiring the observations $(\mathbf{1}_{Y_i > U_i})_{i \in [T]}$ that can be cast as the observation of the half-space $S_i = \left\{ y \in \mathcal{Y} \,\middle|\, \mathbf{1}_{y > U_i} = \mathbf{1}_{Y_i > U_i} \right\} =: s(Y_i, U_i)$. In this noiseless setting, a good baseline to learn f^* from the data (X_i, S_i) is provided by the infimum loss characterization (see Cabannes et al., 2020)

$$f^* = \arg\min_{f: \mathcal{X} \to \mathcal{Y}} \mathbb{E}_{(X, S)} [\inf_{y \in S} \ell(f(X), y)],$$

---

[2] A noteworthy computational aspect of linear models, often refer as the "kernel trick", is that the features map φ does not need to be explicit, the knowledge of $k : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$ being sufficient to compute all quantities of interest (Scholkopf and Smola, 2001). This "trick" can be applied to our algorithms.

where the distribution over X corresponds to the marginal of ρ over $\mathcal{X}$, and the distribution over $(S \mid X = x)$ is the pushforward of $U \sim \mathcal{N}(0, 1)$ under $s(f^*(x), \cdot)$. The left plot on Figure 1 corresponds to an instance of SGD on such an objective based on the data (X_i, S_i), while the right plot corresponds to Algorithm 1. We take the same hyperparameters for both plots, a bandwidth $\sigma = 0.2$ and a SGD stepsize $\gamma = 0.3$. We refer the curious reader to Figure 7 in Appendix E for plots illustrating the streaming history, and to Figure 9 for "real-world" experiments.

Figure 1: *Visual comparison of active and passive strategies.* Estimation in orange of the original signal f^* in dashed blue based on median regression in a noiseless setting. Any orange point $(x, u) \in \mathbb{R}^2$ corresponds to an observation made that u is below $f^*(x)$, while a blue point corresponds to u above $f^*(x)$. The passive strategy corresponds to acquiring information based on $(U \mid x)$ following a normal distribution, while the active strategy corresponds to $(u \mid x) = f_\theta(x)$. The active strategy reconstructs the signal much better given the budget of $T = 30$ observations.

To illustrate the versatility of our method, we approach a classification problem through the median surrogate technique presented in Proposition 3. To do so, we consider the classification problem with $m \in \mathbb{N}$ classes, $\mathcal{X} = [0, 1]$ and the conditional distribution $(Y \mid X)$ linearly interpolating between Dirac in y_1, y_2 and y_3 respectively for $x = 0$, $x = 1/2$ and $x = 1$ and the uniform distribution for $x = 1/4$ and $x = 3/4$; and X uniform on $\mathcal{X} \setminus ([1/4 - \varepsilon, 1/4 + \varepsilon] \cup [3/4 - \varepsilon, 3/4 + \varepsilon])$.

Figure 2: *Comparison of generalization errors of passive and active strategies* as a function of the annotation budget T. This error is computed by averaging over 100 trials. In solid is represented the average error, while the height of the dark area represents one standard deviations on each side. In order to consider the streaming setting where T is not known in advance, we consider the decreasing stepsize $\gamma(t) = \gamma_0/\sqrt{t}$; and to smooth out the stochasticity due to random gradients, we consider the average estimate $\bar{\theta}_t = (\theta_1 + \cdots + \theta_t)/t$. The left figure corresponds to the noiseless regression setting of Figure 1, with $\gamma_0 = 1$. We observe the convergence behavior in $O(T^{-1/2})$ of our active strategy. The right setting corresponds to the classification problem setting described in the main text with $m = 100$, $\varepsilon = 1/20$, and approached with the median surrogate. We observe the exponential convergence phenomenon described by Cabannes et al. (2021b), its kicks in earlier for the active strategy. The two plots are displayed with logarithmic scales on both axis.

7 Discussion

7.1 Discrete output problems

Learning problems with discrete output spaces are not as well understood as regression problems. This is a consequence ot the complexity of dealing with combinatorial structures in contrast with continuous metric spaces. In particular, gradients are not defined for discrete output models. The current state-of-the-art framework to deal with discrete output problems is to introduce a continuous surrogate problem whose solution can be decoded as a solution on the original problem (Bartlett et al., 2006). For example, one could solve a classification task with a median regression surrogate problem, which is the object of the next proposition, proven in Appendix C.

Proposition 3 (Consistency of median surrogate). *The classification setting where $\mathcal{Y}$ is a finite space, and $\ell : \mathcal{Y} \times \mathcal{Y} \to \mathbb{R}$ is the zero-one loss $\ell(y, z) = \mathbf{1}_{y \neq z}$ can be solved as a regression task through the simplex embedding of $\mathcal{Y}$ in $\mathbb{R}^{\mathcal{Y}}$ with the orthonormal basis $(e_y)_{y \in \mathcal{Y}}$. More precisely, if $g^* : \mathcal{X} \to \mathbb{R}^{\mathcal{Y}}$ is the minimizer of the median surrogate risk $\mathcal{R}_S(g) = \mathbb{E}\left[\|g(X) - e_Y\|\right]$, then $f^* : \mathcal{X} \to \mathcal{Y}$ defined as $f^*(x) = \arg\max_{y \in \mathcal{Y}} g_y^*(x)$ minimizes the original risk $\mathcal{R}(f) = \mathbb{E}\left[\ell(f(X), Y)\right]$.*

More generally, any discrete output problem can be solved reusing the consistent least-squares surrogate of Ciliberto et al. (2020). Algorithm 1 can be adapted to the least-squares problem based on specifications at the beginning of Section 4. This allows to use our method in an off-the-shelve fashion for all discrete output problems. In this setting, Theorem 1 can be refined under margin conditions where our approach would exhibit exponential convergence rates as illustrated on Figure 2. As a side note, while we are not aware of any generic theory encompassing the absolute-deviation surrogate of Proposition 3, we showcase its superiority over least-squares on at least two types of problems on Figures 3 and 4 in Appendix C.

7.2 Supervised learning baseline with resampling

When resampling is allowed a simple baseline for the active labeling problem is provided by supervised learning. In regression problems with the query of any half-space, a method that consists in annotating each $(Y_i)_{i \leq n(T,\varepsilon)}$ up to precision ε, before using any supervised learning method to learn f from $(X_i, Y_i)_{i \leq n(T,\varepsilon)}$ could acquire $n(T, \varepsilon) \simeq T/m \log_2(\varepsilon^{-1})$ datapoints with a dichotomic search along all directions, assuming Y_i bounded or sub-Gaussian. In term of minimax rates, such a procedure cannot perform better than in $n(T, \varepsilon)^{-1/2} + \varepsilon$, the first term being due to the statistical limit in Theorem 2, the second due to the incertitude ε on each Y_i that transfers to the same level of incertitude on f. Optimizing with respect to ε yields a bound in $O(T^{-1/2} \log(T)^{1/2})$. Therefore, this not-so-naive baseline is only sub-optimal by a factor $\log(T)^{1/2}$. In the meanwhile, Algorithm 1 can be rewritten with resampling, as well as Theorem 1, which we prove in Appendix A.2. Hence, our technique will still achieve minimax optimality for the problem "with resampling". In other terms, by deciding to acquire more imprecise information, our algorithm reduces annotation cost for a given level of generalization error (or equivalently reduces generalization error for a given annotation budget) by a factor $\log(T)^{1/2}$ when compared to this baseline.

The picture is slightly different for discrete-output problems. If one can ask any question $s \in 2^{\mathcal{Y}}$ then with a dichotomic search, one can retrieve any label with $\log_2(m)$ questions. Hence to theoretically beat the fully supervised baseline with the SGD method described in Section 3, one would have to derive a gradient strategy (2) with a small enough second moment (*e.g.*, for convex losses that are non-smooth nor strongly convex, the increase in the second moment compared to the usual stochastic gradients should be no greater than $\log_2(m)^{1/2}$). How to best refine our technique to better take into account the discrete structure of the output space is an open question. Introducing bias that does not modify convergence properties while reducing variance eventually thanks to importance sampling is a potential way to approach this problem. A simpler idea would be to remember information of the type $Y_i \in s$ to restrict the questions asked in order to locate $f_{\theta_t}(X_i) - Y_i$ when performing stochastic gradient descent with resampling. Combinatorial bandits might also provide helpful insights on the matter. Ultimately, we would like to build an understanding of the whole distribution $(Y \mid X)$ and not only of $f^*(X)$ as we explore labels in order to refine this exploration.

7.3 Min-max approaches

Min-max approaches have been popularized for searching games and active learning, where one searches for the question that minimizes the size of the space where a potential guess could lie under the worse possible answer to that question. A particularly well illustrative example is the solution of the Mastermind game proposed by Knuth (1977). While our work leverages plain SGD, one could build on the vector field point-of-view of gradient descent (see, *e.g.*, Bubeck, 2015) to tackle min-max convex concave problems with similar guarantees. In particular, we could design weakly supervised losses $L(f(x), s; \mathbf{1}_{y \in s})$ and min-max games where a prediction player aims at minimizing such a loss with respect to the prediction f, while the query player aims at maximizing it with respect to the question s, that is querying information that best elicit mistakes made by the prediction player. For example, the dual norm characterization of the norm leads to the following min-max approach to the median regression

$$\min_{g:\mathcal{X}\to\mathcal{Y}} \mathcal{R}(f) = \min_{f:\mathcal{X}\to\mathcal{Y}} \max_{U \in (\mathbb{S}^{m-1})^{\mathcal{X}\times\mathcal{Y}}} \mathbb{E}_{(X,Y)\sim\rho} \left[\langle U(x,y), f(x) - y \rangle \right].$$

Such min-max formulations would be of interest if they lead to improvement of computational and statistical efficiencies, similarly to the work of Babichev et al. (2019). For classification problems, the following proposition introduces such a game and suggests its suitability. Its proof can be found in Appendix D.

Proposition 4. *Consider the classification problem of learning $f^* : \mathcal{X} \to \mathcal{Y}$ where $\mathcal{Y}$ is of finite cardinality, with the 0-1 loss $\ell(z, y) = \mathbf{1}_{z \neq y}$, minimizing the risk* (1) *under a distribution ρ on $\mathcal{X} \times \mathcal{Y}$. Introduce the surrogate score functions $g : \mathcal{X} \to \Delta_{\mathcal{Y}}; x \to v$ where $v = (v_y)_{y \in \mathcal{Y}}$ is a family of nonnegative weights that sum to one, as well as the surrogate loss function $L : \Delta_{\mathcal{Y}} \times \mathcal{S} \times \{-1, 1\} \to \mathbb{R}; (v, S, \varepsilon) = \varepsilon(1 - 2 \sum_{y \in S} v_y)$, and the min-max game*

$$\min_{g:\mathcal{X}\to\Delta_{\mathcal{Y}}} \max_{\mu:\mathcal{X}\to\Delta_{\mathcal{S}}} \mathbb{E}_{(X,Y)\sim\rho} \mathbb{E}_{S\sim\mu(x)} \left[L(f(x), Y; \mathbf{1}_{Y \in S} - \mathbf{1}_{Y \notin S}) \right]. \tag{8}$$

When $\mathcal{S}$ contains the singletons and with the low-noise condition that almost everywhere $\mathbb{P}(Y \neq f^*(x) \mid X = x) < 1/2$, then f^* can be learned through the relation $f^*(x) = \arg\min_{y \in \mathcal{Y}} g^*(x)_y$ for the unique minimizer g^* of (8). *Moreover, the minimization of the empirical version of this objective with the stochastic gradient updates for saddle point problems provides a natural "active labeling" scheme to find this g^*.*

8 Conclusion

We have introduced the "active labeling" problem, which corresponds to "active partially supervised learning". We provided a solution to this problem based on stochastic gradient descent. Although our method can be used for any discrete output problem, we detailed how it works for median regression, where we show that it optimizes the generalization error for a given annotation budget. In a near future, we would like to focus on better exploiting the discrete structure of classification problems, eventually with resampling strategies.

Understanding more precisely the key issues in applications concerned with privacy, and studying how weak gradients might provide a good trade-off between learning efficiently and revealing too much information also provide interesting follow-ups. Finally, regarding dataset annotation, exploring different paradigms of weakly supervised learning would lead to different active weakly supervised learning frameworks. While this work is based on partial labeling, similar formalizations could be made based on other weak supervision models, such as aggregation (*e.g.*, Ratner et al., 2020), or group statistics (Dietterich et al., 1997). In particular, annotating a huge dataset is often done by bagging inputs according to predicted labels and correcting errors that can be spotted on those bags of inputs (Deng et al., 2009). We left for future work the study of variants of the "active labeling" problem that model those settings.

References

Nir Ailon. Active learning ranking from pairwise preferences with almost optimal query complexity. In *Advances in Neural Information Processing Systems*, 2011.

Martin Anthony and Peter Bartlett. *Neural Network Learning: Theoretical Foundations*. Cambridge University Press, 1999.

Dmitry Babichev, Dmitrii Ostrovskii, and Francis Bach. Efficient primal-dual algorithms for large-scale multiclass classification. Technical Report 1902.03755, arXiv, 2019.

Francis Bach. *Learning Theory from First Principles*. To appear at MIT Press, 2023.

Francis Bach and Eric Moulines. Non-strongly-convex smooth stochastic approximation with convergence rate $O(1/n)$. In *Advances in Neural Information Processing Systems*, 2013.

Peter Bartlett, Michael Jordan, and Jon McAuliffe. Convexity, classification, and risk bounds. *Journal of the American Statistical Association*, 101(473):138–156, 2006.

Viktor Bengs, Róbert Busa-Fekete, Adil El Mesaoudi-Paul, and Eyke Hüllermeier. Preference-based online learning with dueling bandits: A survey. *Journal of Maching Learning Research*, 22(7): 1–108, 2021.

Mark Braverman, Jieming Mao, and Yuval Peres. Sorted top-k in rounds. In *Conference on Learning Theory*, 2019.

Sébastien Bubeck. Convex optimization: Algorithms and complexity. *Foundations and Trends in Machine Learning*, 8(3-4):231–357, 2015.

Vivien Cabannes, Alessandro Rudi, and Francis Bach. Structured prediction with partial labelling through the infimum loss. In *International Conference on Machine Learning*, 2020.

Vivien Cabannes, Loucas Pillaud-Vivien, Francis Bach, and Alessandro Rudi. Overcoming the curse of dimensionality with Laplacian regularization in semi-supervised learning. In *Advances in Neural Information Processing Systems*, 2021a.

Vivien Cabannes, Alessandro Rudi, and Francis Bach. Fast rates in structured prediction. In *Conference on Learning Theory*, 2021b.

Andrea Caponnetto and Ernesto De Vito. Optimal rates for the regularized least-squares algorithm. *Foundations of Computational Mathematics*, 7(3):331–368, 2006.

Nicolò Cesa-Bianchi, Claudio Gentile, and Luca Zaniboni. Incremental algorithms for hierarchical classification. *Journal of Machine Learning Research*, 7(2):31–54, 2006.

Nicolò Cesa-Bianchi, Tommaso Cesari, and Vianney Perchet. Dynamic pricing with finitely many unknown valuations. In *International Conference on Algorithmic Learning Theory*, 2019.

Chih-Chung Chang and Chih-Jen Lin. LIBSVM: a library for support vector machines. *ACM Transactions on Intelligent Systems and Technology*, 2(3):1–27, 2011.

Olivier Chapelle, Bernhard Schölkopf, and Alexander Zien, editors. *Semi-Supervised Learning*. MIT Press, 2006.

Herman Chernoff. Sequential design of experiments. *The Annals of Mathematical Statistics*, 30(3): 755–770, 1959.

Clément Chevalier, Julien Bect, David Ginsbourger, Emmanuel Vázquez, Victor Picheny, and Yann Richet. Fast parallel kriging-based stepwise uncertainty reduction with application to the identification of an excursion set. *Technometrics*, 56(4):455–465, 2014.

Carlo Ciliberto, Lorenzo Rosasco, and Alessandro Rudi. A general framework for consistent structured prediction with implicit loss embeddings. *Journal of Machine Learning Research*, 21(98):1–67, 2020.

Maxime Cohen, Ilan Lobel, and Renato Paes Leme. Feature-based dynamic pricing. *Management Science*, 66(11):4921–4943, 2020.

Council of European Union. Regulation (EU) 2016/679 of the European parliament (General Data Protection Regulation), 2016.

Timothée Cour, Benjamin Sapp, and Ben Taskar. Learning from partial labels. *Journal of Machine Learning Research*, 12(42):1501–1535, 2011.

Thomas Cover and Joy Thomas. *Elements of Information Theory*. Wiley, 1991.

Sanjoy Dasgupta. Two faces of active learning. *Theoretical Computer Science*, 412(19):1767–1781, 2011.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Fei-Fei Li. Imagenet: A large-scale hierarchical image database. In *Conference on Computer Vision and Pattern Recognition*, 2009.

Thomas Dietterich, Richard Lathrop, and Tomás Lozano-Pérez. Solving the multiple instance problem with axis-parallel rectangles. *Artificial Intelligence*, 89(1-2):31–71, 1997.

AnHai Doan, Raghu Ramakrishnan, and Alon Halevy. Crowdsourcing systems on the world-wide web. *Communication of the ACM*, 54(4):86–96, 2011.

Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of Cryptography Conference*, 2006.

Robert Fano. *Transmission of Information: A Statistical Theory of Communications*. MIT Press, 1968.

Tanner Fiez, Lalit Jain, Kevin G Jamieson, and Lillian Ratliff. Sequential Experimental Design for Transductive Linear Bandits. In *Advances in Neural Information Processing Systems*, 2019.

Dimitris Fotakis, Alkis Kalavasis, Vasilis Kontonis, and Christos Tzamos. Efficient algorithms for learning from coarse labels. In *Conference on Learning Theory*, 2021.

Sachin Gangaputra and Donald Geman. A design principle for coarse-to-fine classification. In *Conference on Computer Vision and Pattern Recognition*, 2006.

Aurélien Garivier and Emilie Kaufmann. Optimal best arm identification with fixed confidence. In *Conference on Learning Theory*, 2016.

Donald Geman and Bruno Jedynak. Shape recognition and twenty questions. Technical report, INRIA, 1993.

Aurélien Géron. *Hands-On Machine Learning with Scikit-Learn & TensorFlow*. O'Reilly, 2017.

Edgar Gilbert. A comparison of signalling alphabets. *Bell System Technical Journal*, 31(3):504–522, 1952.

Steve Hanneke. Theory of disagreement-based active learning. *Foundations and Trends in Machine Learning*, 7(2-3):131–309, 2014.

Charles Harris, Jarrod Millman, Stéfan van der Walt, Ralf Gommers, Pauli Virtanen, David Cournapeau, Eric Wieser, Julian Taylor, Sebastian Berg, Nathaniel Smith, Robert Kern, Matti Picus, Stephan Hoyer, Marten van Kerkwijk, Matthew Brett, Allan Haldane, Jaime Fernández del Río, Mark Wiebe, Pearu Peterson, Pierre Gérard-Marchant, Kevin Sheppard, Tyler Reddy, Warren Weckesser, Hameer Abbasi, Christoph Gohlke, and Travis Oliphant. Array programming with NumPy. *Nature*, 585(7825):357–362, 2020.

Wassily Hoeffding. Probability inequalities for sums of bounded random variables. *Journal of the American Statistical Association*, 58(301):13–30, 1963.

Peter Huber. *Robust Statistics*. Wiley, 1981.

John Hunter. Matplotlib: A 2D graphics environment. *Computing in Science & Engineering*, 9(3): 90–95, 2007.

Kevin Jamieson and Robert Nowak. Active ranking using pairwise comparisons. In *Advances in Neural Information Processing Systems*, 2011.

Michael Kearns. Efficient noise-tolerant learning from statistical queries. *Journal of the Asoociation for Computing Machinery*, 45(6):983–1006, 1998.

Donald Knuth. The computer as master mind. *Journal of Recreational Mathematics*, 9(1):1–6, 1977.

Andrey Kolmogorov and Vladimir Tikhomirov. ε-entropy and ε-capacity of sets in functional spaces. *Uspekhi Matematicheskikh Nauk*, 14(2):3–86, 1959.

Jonathan Krause, Benjamin Sapp, Andrew Howard, Howard Zhou, Alexander Toshev, Tom Duerig, James Philbin, and Li Fei-Fei. The unreasonable effectiveness of noisy data for fine-grained recognition. In *European Conference on Computer Vision*, 2016.

Allen Liu, Renato Paes Leme, and Jon Schneider. Optimal contextual pricing and extensions. In *Symposium on Discrete Algorithms*, 2021.

Andreas Maurer. A vector-contraction inequality for Rademacher complexities. In *International Conference on Algorithmic Learning Theory*, 2016.

Giacomo Meanti, Luigi Carratino, Lorenzo Rosasco, and Alessandro Rudi. Kernel methods through the roof: Handling billions of points efficiently. In *Advances in Neural Information Processing Systems*, 2020.

Vu-Linh Nguyen, Mohammad Hossein Shaker, and Eyke Hüllermeier. How to measure uncertainty in uncertainty sampling for active learning. *Machine Learning*, 111(1):89–122, 2021.

Andrzej Pelc. Searching games with errors - fifty years of coping with liars. *Theoretical Compututer Science*, 270(1):71–109, 2002.

Loucas Pillaud-Vivien, Alessandro Rudi, and Francis Bach. Statistical optimality of stochastic gradient descent on hard learning problems through multiple passes. In *Advances in Neural Information Processing Systems*, 2018.

Bahar Qarabaqi and Mirek Riedewald. User-driven refinement of imprecise queries. In *International Conference on Data Engineering*, 2014.

Alexander Ratner, Stephen Bach, Henry Ehrenberg, Jason Fries, Sen Wu, and Christopher Ré. Snorkel: rapid training data creation with weak supervision. *The VLDB Journal*, 29(2):709–730, 2020.

Donald Rubin. Inference and missing data. *Biometrika*, 63(3):581–592, 1976.

Bernhard Scholkopf and Alexander Smola. *Learning with Kernels: Support Vector Machines, Regularization, Optimization, and Beyond*. MIT press, 2001.

Burr Settles. Active learning literature survey. Technical report, University of Wisconsin-Madison, 2010.

Karthik Sridharan, Shai Shalev-shwartz, and Nathan Srebro. Fast rates for regularized objectives. In *Advances in Neural Information Processing Systems*, 2008.

James Tobin. Estimation of relationships for limited dependent variables. *Econometrica*, 26(1):24–36, 1958.

US Census Bureau. Income and poverty in the United States: 2020, 2021.

Leslie Valiant. Parallelism in comparison problems. *SIAM Journal on Computing*, 4(3):348–355, 1975.

Vladimir Vapnik. *The Nature of Statistical Learning Theory*. Springer-Verlag, 1995.

Rom Varshamov. Estimate of the number of signals in error correcting codes. *Doklady Akademii Nauk SSSR*, 117:739–741, 1957.

Anatoliy Vitushkin. On Hilbert's thirteenth problem. *Proceedings of the USSR Academy of Sciences*, 95(4):701–704, 1954.

John von Neumann and Oskar Morgenstern. *Theory of Games and Economic Behavior*. Princeton University Press, 1944.

Mansfield Tracy Walsorth. *Twenty Questions: A Short Treatise on the Game*. Holt, 1882.

Dan Wang and Yi Shang. A new active labeling method for deep learning. In *International Joint Conference on Neural Networks*, 2014.

Harold Widom. Asymptotic behavior of the eigenvalues of certain integral equations. *Transactions of the American Mathematical Society*, 109(2), 1963.

Christopher Williams and Matthias Seeger. Using the Nyström method to speed up kernel machines. In *Advances in Neural Information Processing Systems*, 2000.

Bin Yu. Assouad, Fano, and Le Cam. In *Festschrift for Lucien Le Cam: Research Papers in Probability and Statistics*. Springer, 1997.

Heliang Zheng, Jianlong Fu, Zheng-Jun Zha, and Jiebo Luo. Looking for the devil in the details: Learning trilinear attention sampling network for fine-grained image recognition. In *Conference on Computer Vision and Pattern Recognition*, 2019.

Xiaojin Zhu, Zoubin Ghahramani, and John Lafferty. Semi-supervised learning using Gaussian fields and harmonic functions. In *International Conference of Machine Learning*, 2003.