PSA-GAN: Progressive Self Attention GANs for Synthetic Time Series

Abstract

Realistic synthetic time series data of sufficient length enables practical applications in time series modeling tasks, such as forecasting, but remains a challenge. In this paper we present PSA-GAN, a generative adversarial network (GAN) that generates long time series samples of high quality using progressive growing of GANs and self-attention. We show that PSA-GAN can be used to reduce the error in several downstream forecasting tasks over baselines that only use real data. We also introduce a Frechet-Inception Distance-like score for time series, Context-FID, assessing the quality of synthetic time series samples. We find that Context-FID is indicative for downstream performance. Therefore, Context-FID could be a useful tool to develop time series GAN models.

1 Introduction

In the past years, methods such as (Salinas et al., 2020; Franceschi et al., 2019; Kurle et al., 2020; de Bézenac et al., 2020; Oreshkin et al., 2019; Rasul et al., 2021; Cui et al., 2016; Wang et al., 2016) have consistently showcased their effectiveness of deep learning in time series analysis tasks. Although these deep learning based methods are effective when sufficient clean data is available, this assumption is not always met in practice. For example, sensor outages can cause gaps in IoT data, which might render the data unusable for machine learning applications (Zhang et al., 2019b). An additional problem is that time series panels often have insufficient size for forecasting tasks, leading to research in meta-learning for forecasting (Oreshkin et al., 2020). Cold starts are another common problem in time series forecasting where some time series have little and no data (like a new product in a demand forecasting use case). Thus, designing flexible and task-independent models that generate synthetic, but realistic time series for arbitrary tasks poses an important challenge. Generative adversarial networks (GAN) are a flexible model family that has had success in other domains. However, for their success to carry over to time series, synthetic time series data must be of realistic length, which current state-of-the-art synthetic time series models struggle to generate because they often rely on recurrent networks to capture temporal dynamics (Esteban et al., 2017; Yoon et al., 2019).

In this work, we make three contributions: i) We propose `PSA-GAN`, a progressively growing, convolutional time series GAN model augmented with self-attention (Karras et al., 2018; Vaswani et al., 2017). `PSA-GAN` scales to long time series because the progressive growing architecture starts modeling the coarse-grained time series features and moves towards modeling fine-grained details during training. The self-attention mechanism captures long-range dependencies in the data (Zhang et al., 2019a). ii) We show empirically that `PSA-GAN` samples are of sufficient quality and length to boost several downstream forecasting tasks: far-forecasting and data imputation during inference, data imputation of missing value stretches during training, forecasting under cold start conditions, and data augmentation. Furthermore, we show that `PSA-GAN` can be used as a forecasting model and has competitive performance when using the same context information as an established baseline. iii) Finally, we propose a Frechet Inception distance (FID)-like score (Salimans et al., 2016), Context-FID, leveraging unsupervised time series embeddings (Franceschi et al., 2019). We show that the lowest scoring models correspond to the best-performing models in our downstream tasks and therefore could be a useful general-purpose tool to select GAN models for downstream applications.

We structure this work as follows: We discuss the related work in Section 2 and introduce the model in Section 3. In Section 4, we evaluate our proposed GAN model using the proposed Context-FID

score and through several downstream forecasting tasks. We also directly evaluate our model as a forecasting algorithm and perform an ablation study. Section 5 concludes this manuscript.

2 RELATED WORK

GANs (Goodfellow et al., 2014) are an active area of research (Karras et al., 2019; Yoon et al., 2019; Engel et al., 2019; Lin et al., 2017; Esteban et al., 2017; Brock et al., 2019) that have recently been applied to the time series domain (Esteban et al., 2017; Yoon et al., 2019) to synthesize data (Takahashi et al., 2019; Esteban et al., 2017), and to forecasting tasks (Wu et al., 2020b). Many time series GAN architectures use recurrent networks to model temporal dynamics (Mogren, 2016; Esteban et al., 2017; Yoon et al., 2019). Modeling long-range dependencies and scaling recurrent networks to higher lengths is inherently difficult and limits the application of time series GANs to short sequence lengths (less than 100 time steps) (Yoon et al., 2019; Esteban et al., 2017). One way to achieve longer realistic synthetic time series is by employing convolutional (van den Oord et al., 2016; Bai et al., 2018; Franceschi et al., 2020) and self-attention architectures (Vaswani et al., 2017). Convolutional architectures are able to learn relevant features from the raw time series data (van den Oord et al., 2016; Bai et al., 2018; Franceschi et al., 2020), but are ultimately limited to local receptive fields and can only capture long-range dependencies via many stacks of convolutional layers. Self-attention can bridge this gap and allow for modeling long-range dependencies from convolutional feature maps, which has been a successful approach in the image (Zhang et al., 2019a) and time series forecasting domain (Li et al., 2019; Wu et al., 2020a). Another technique to achieve long sample sizes is progressive growing, which successively increases the resolution by adding layers to generator and discriminator during training (Karras et al., 2018). Additionally, the synthetic time series should preserve the dynamics of the real data. This can be achieved by using the latent state of an autoencoder network (Yoon et al., 2019). In PSA-GAN, we explore whether unsupervised techniques could instead provide meaningful embeddings that can act as an additional signal to the GAN to model realistic time series.

Our proposal, `PSA-GAN`, synthesizes progressive growing with convolutions, self-attention, and embeddings into a novel architecture particularly geared towards time series.

Another challenge is the evaluation of synthetic data. While the computer vision domain uses standard scores like the Inception Score and the Frechet Inception Distance (FID) (Salimans et al., 2016; Heusel et al., 2018), such universally accepted scores do not exist in the time series field. Thus, researchers rely on a *Train on Synthetic–Test on Real* setup and assess the quality of the synthetic time series in a downstream classification and/or prediction task (Esteban et al., 2017; Yoon et al., 2019). In this work, we build on this idea and assess the GAN models through downstream forecasting tasks. Additionally, we suggest a Frechet Inception Distance-like score that is based on unsupervised time series embeddings (Franceschi et al., 2020). Critically, we want to be able to score the fit of our fixed length synthetic samples into their context of (often much longer) true time series, which is taken into account by the contrastive training procedure in (Franceschi et al., 2020). As we will later show, the lowest scoring models correspond to the best performing models in downstream tasks.

3 MODEL

Problem formulation   We denote the values of a time series dataset by $z_{i,t} \in \mathbb{R}$ (or $\mathbb{N}$), where $i \in \{1, 2, \ldots, N\}$ is the index of the individual time series and $t \in \{1, 2, \ldots, T\}$ is the time index. Additionally, we consider an associated matrix of time feature vectors $\mathbf{X}_{1:T} = (\mathbf{x}_1, \ldots, \mathbf{x}_T) \in \mathbb{R}^{D \times T}$, where D is the number of time features. Our goal is to model a time series of fixed length τ, $\hat{Z}_{i,t,\tau} = (\hat{z}_{i,t}, \ldots, \hat{z}_{i,t+\tau})$, from this dataset using a conditional generator function G and a fixed time point t. Thus, we aim to model $\hat{Z}_{i,t,\tau} = G(\mathbf{n}, \phi(i), \mathbf{X}_{t:t+\tau})$, where $\mathbf{n}$ is a noise vector drawn from a standard Gaussian and ϕ is an embedding function that maps the index of a time series to a vector representation. An overview of the model architecture is shown in Figure 1.

Spectral Normalised Residual Self Attention with Convolution   The generator and discriminator use a main function m that is a composition of convolution, self attention and spectral normalisation

$$m : \mathbb{R}^{n_f \times l} \to \mathbb{R}^{n_f \times l}$$
$$x \mapsto \gamma \, \mathrm{SA}(f(x)) + f(x) \tag{1}$$

Figure 1: *Left*: Architecture of our proposed model, PSA-GAN. The generator contains n blocks where each doubles the size of the output, by linear interpolation. It contains (dashed drawing) a Multi Layer Perceptron block, that incorporates knowledge of the past in the generator. This block is used in the PSA-GAN-C model. The discriminator contains n blocks that halves the size of the input using an average pooling. *Right*: The main block used in the generator and discriminator.

where $f(x) = \mathrm{LR}(\mathrm{SN}(c(x)))$, c is a one dimensional convolution operator, LR the LeakyReLU operator (Xu et al., 2015), SN the Spectral Normalisation operator (Miyato et al., 2018) and SA the Self Attention module. The variable n_f is the number of in and out-channels of c, l is the length of the sequence. Following the work of (Zhang et al., 2019a), the parameter γ is learnable. It is initialized to zero to allow the network to learn local features directly from the building block f, and is later enriched with distant features as the absolute value of gamma increases, hereby more heavily factoring the self-attention term $SA \circ f$. The module $m : f(x) \to m(f(x))$ is referenced as Residual Self-Attention in Fig. 1 (*Right*).

Downscaling and Upscaling The following sections mention upscaling (UP) and downscaling (DOWN) operators that double and halve the length of the time series, respectively. In this work, the upscaling operator is a linear interpolation and the downscaling operator is the average pooling.

PSA-GAN `PSA-GAN` is a progressively growing GAN (Karras et al., 2018); thus, trainable modules are added during training. Hereby, we model the generator and discriminator as a composition of functions: $G = g_{L+1} \circ ... \circ g_1$ and $D = d_1 \circ ... \circ d_{L+1}$ where each function g_i and d_i for $i \in [1, L+1]$ corresponds to a module of the generator and discriminator.

GENERATOR As a preprocessing step, we first map the input features from a sequence of length τ to a sequence of length 8, denoted by $\tilde{Z}_0$, using average pooling. Then, the first layer of the generator g_1 applies the main function m:

$$g_1 : \; \mathbb{R}^{n_f \times 2^3} \to \mathbb{R}^{n_f \times 2^3}$$
$$\tilde{Z}_0 \mapsto \tilde{Z}_1 = m(\tilde{Z}_0) \tag{2}$$

For $i \in [2, L]$, g_i maps an input sequence $\tilde{Z}_{i-1}$ to an output sequence $\tilde{Z}_i$ by applying an upscaling of the input sequence and the function m:

$$g_i : \; \mathbb{R}^{n_f \times 2^{i+1}} \to \mathbb{R}^{n_f \times 2^{i+2}}$$
$$\tilde{Z}_{i-1} \mapsto \tilde{Z}_i = m(\mathrm{UP}(\tilde{Z}_{i-1})) \tag{3}$$

The output of g_i is concatenated back to the time features $\mathbf{X}_{t:t+\tau}$ and forwarded to the next block.

Lastly the final layer of the generator g_{L+1} reshapes the multivariate sequence $\tilde{Z}_L$ to a univariate time series $\hat{Z}_{i,t,\tau}$ of length $\tau = 2^{L+3}$ using a one dimensional convolution and a spectral normalisation layer.

DISCRIMINATOR The architecture of the discriminator mirrors the architecture of the generator. It maps the generator's output $\hat{Z}_{i,t,\tau}$ and the time features $\mathbf{X}_{t:t+\tau}$ to a score d. The first module of the discriminator d_{L+1} uses a one dimensional convolution c_1 and a LeakyReLU activation function:

$$d_{L+1} : \; \mathbb{R}^{1+D,\tau} \to \mathbb{R}^{n_f,\tau}$$
$$(\tilde{Z}_{L+1}, \mathbf{X}_{t:t+\tau}) \mapsto \tilde{Z}_L = \mathrm{LR}(c_1(\tilde{Z}_{L+1}, \mathbf{X}_{t:t+\tau})) \tag{4}$$

For $i \in [L, 2]$, the module d_i applies a downscale operator and the main function m:

$$d_i : \mathbb{R}^{n_f \times 2^{i+2}} \to \mathbb{R}^{n_f \times 2^{i+1}}$$
$$Y_i \mapsto Y_{i-1} = \text{DOWN}(m(Y_i)) \tag{5}$$

The last module d_1 turns its input sequence into a score:

$$d_1 : \mathbb{R}^{n_f \times 2^3} \to \mathbb{R}$$
$$Y_1 \mapsto Y_0 = \text{SN}(\text{FC}(\text{LR}(\text{SN}(c(m(Y_1)))))) \tag{6}$$

where FC is a fully connected layer.

PSA-GAN-C We introduce a second version of PSA-GAN, named PSA-GAN-Context in which we forward to each generator block g_i knowledge about the past. The output of g_i is concatenated with the subseries $\hat{Z}_{i,t-L_C,L_C}$ ranging from $[t - L_C, t - 1]$, with L_C being the context length. It is then passed through a two layers perceptron before being added back to the output of g_i.

3.1 Loss functions

`PSA-GAN` is trained via least squares loss (Mao et al., 2017). We use an auxiliary moment loss 7 to the generator to match the first and second order moment between a batch of synthetic samples and real samples. This loss helps align the periodicity of the synthetic time series with the real times series:

$$\text{ML}\left(\hat{\mathbf{Z}}_\tau, \mathbf{Z}_\tau\right) = \left|\mu\left(\hat{\mathbf{Z}}_\tau\right) - \mu\left(\mathbf{Z}_\tau\right)\right| + \left|\sigma\left(\hat{\mathbf{Z}}_\tau\right) - \sigma\left(\mathbf{Z}_\tau\right)\right| \tag{7}$$

where μ is the mean operator and σ is the standard deviation operator.

Training procedures GANs are notoriously difficult to training, have hard-to-interpret learning curves, and are susceptible to mode collapse. The training procedure to address those issues are presented in the appendix.

4 Experiments

The evaluation of synthetic time series data from GAN models is challenging and there is no widely accepted evaluation scheme in the time series community. We evaluate the GAN models by two guiding principles: i) Measuring to what degree the time series recover the statistics of the training dataset. ii) Measuring the performance of of the GAN models in challenging, downstream forecasting scenarios.

For i), we introduce the Context-FID (Context-Frechet Inception Distance) score to measure whether the GAN models are able to recover the training set statistics. The FID score is widely used for evaluating synthetic data in computer vision (Heusel et al., 2018) and uses features from an inception network (Szegedy et al., 2015) to compute the difference between the real and synthetic sample statistics in this feature space. In our case, we are interested how well the the synthetic time series windows "fit" into the local context of the time series. Therefore, we use the time series embeddings from Franceschi et al. (2019) that uses a contrastive learning scheme to learn embeddings of time series that fit into the local context. Note that we train the embedding network for each dataset separately. This allows us to directly quantify the quality of the synthetic time series samples.

For ii), we set out to mimic several challenging time series forecasting tasks that are common for time series forecasting practitioners. These tasks often have in common that practitioners face missing or corrupted data during training or inference, which increases the error of deep-learning based forecasting models. Here, we set out to use the synthetic samples to complement an established baseline model, `DeepAR` in these forecasting tasks. These tasks are: Far-forecasting and missing values during inference, missing values during training, cold starts, and data augmentation. We evaluate these tasks by the normalized root mean squared distance (NRMSE) Additionally, we evaluate `PSA-GAN` model when used as a forecasting model. Note that, where applicable, we re-train our GAN models on the modified datasets to ensure that they have the same data available as the baseline model during the downstream tasks.

Dataset	Length	EBGAN	TIMEGAN	PSA-GAN	PSA-GAN-C
Electricity	64	$2.07_{\pm 0.3}$	$0.77_{\pm 0.12}$	$0.018_{\pm 0.009}$	$\mathbf{0.011}_{\pm 0.002}$
	128	$1.93_{\pm 0.28}$	$1.03_{\pm 0.13}$	$0.03_{\pm 0.01}$	$\mathbf{0.022}_{\pm 0.01}$
	256	$3.02_{\pm 0.25}$	$1.58_{\pm 0.08}$	$0.042_{\pm 0.018}$	$\mathbf{0.036}_{\pm 0.02}$
M4	64	$0.93_{\pm 0.15}$	$0.93_{\pm 0.1}$	$\mathbf{0.113}_{\pm 0.051}$	$0.158_{\pm 0.088}$
	128	$2.53_{\pm 0.27}$	$0.6_{\pm 0.07}$	$\mathbf{0.156}_{\pm 0.072}$	$0.22_{\pm 0.11}$
	256	$2.08_{\pm 0.13}$	$0.89_{\pm 0.13}$	$0.356_{\pm 0.125}$	$\mathbf{0.235}_{\pm 0.066}$
Solar-Energy	64	$0.48_{\pm 0.11}$	$0.13_{\pm 0.02}$	$0.012_{\pm 0.003}$	$\mathbf{0.004}_{\pm 0.001}$
	128	$1.87_{\pm 0.43}$	$0.22_{\pm 0.05}$	$0.007_{\pm 0.001}$	$\mathbf{0.002}_{\pm 0.001}$
	256	$2.38_{\pm 0.43}$	$0.09_{\pm 0.02}$	$0.064_{\pm 0.002}$	$\mathbf{0.004}_{\pm 0.001}$
Traffic	64	$2.65_{\pm 0.15}$	$0.59_{\pm 0.06}$	$0.241_{\pm 0.041}$	$\mathbf{0.058}_{\pm 0.009}$
	128	$2.09_{\pm 0.26}$	$2.13_{\pm 0.12}$	$0.182_{\pm 0.029}$	$\mathbf{0.044}_{\pm 0.005}$
	256	$1.86_{\pm 0.14}$	$1.82_{\pm 0.12}$	$\mathbf{0.13}_{\pm 0.017}$	$0.488_{\pm 0.027}$

Table 1: Context FID-scores (lower is better) of `PSA-GAN` and baselines. We score 5120 randomly selected windows and report the mean and standard deviation.

In addition, we discuss whether the Context-FID scores are indicative for downstream forecasting tasks and perform an ablation study of our model. For reproducibility, we will make the model code available on Github along with scripts to replicate the experiments.

4.1 Context-FID Score on Time Series Embeddings

To compute the Context-FID, we replace InceptionV3 (Szegedy et al., 2015) with the encoder E of Franceschi et al. (2019), which we train separately for each dataset.

Our proposed Context-FID score is computed as follows: we first select a time range $[t, t + \tau]$. We then sample a batch of synthetic time series $\hat{\mathbf{Z}}_{t,\tau} = [\hat{Z}_{1,t,\tau}, ..., \hat{Z}_{N,t,\tau}]$ and a batch of real time series $\mathbf{Z}_{t,\tau} = [Z_{1,t,\tau}, ..., Z_{N,t,\tau}]$ that we encode with E into $\hat{\mathbf{Z}}_{t,\tau}^e$ and $\mathbf{Z}_{t,\tau}^e$ respectively. Finally, we compute the FID score of the embeddings.

4.2 Datasets and Baselines

We use the following public, standard benchmark datasets in the time series domain: M4, hourly time series competition data (414 time series) (Makridakis et al., 2020); Solar, hourly solar energy collection data in Alabama State (137 stations) (Lai et al., 2017); Electricity, hourly electricity consumption data (370 customers) (Dheeru & Karra Taniskidou, 2017); Traffic: hourly occupancy rate of lanes in San Francisco (963 lanes) (Dheeru & Karra Taniskidou, 2017). Unless stated otherwise, we split all data into a training/test set with a fixed date and use all data before that date for training. For testing, we use a rolling window evaluation with a window size of 32 and seven windows. We minmax scale each dataset to be within $[0, 1]$ for all experiments in this paper (we scale the data back before evaluating the forecasting experiments). In lieu of finding public datasets that represent the downstream forecasting tasks, we modify each the datasets above to mimic each tasks for the respective experiment (see later sections for more details).

We compare `PSA-GAN` with different GAN models from the literature (`TIMEGAN` (Yoon et al., 2019) and `EBGAN` (Zhao et al., 2017)). In what follows `PSA-GAN-C` and `PSA-GAN` denote our proposed model with and without context, respectively. In the forecasting experiments, we use the GluonTS (Alexandrov et al., 2019) implementation of `DeepAR` which is a well-performing forecasting model and established baseline (Salinas et al., 2019).

4.3 Evaluation Results

Direct Evaluation with Context-FID Scores: Table 1 shows the Context-FID scores for `PSA-GAN`, `PSA-GAN-C` and baselines. For all sequence lengths, we find that `PSA-GAN` or `PSA-GAN-C` consistently produce the lowest Context-FID scores. For a sequence length of 256 time steps, `TIMEGAN` is the second best performing model for all datasets. We show samples from our GAN model in the dowstream task sections (Figures 3 and 6). Note that even though using a context

NRMSE				
Dataset Model	Electricity	M4	Solar	Traffic
DeepAR	$3.31_{\pm0.78}$	$0.84_{\pm0.44}$	$1.43_{\pm0.02}$	$1.0_{\pm0.15}$
EBGAN	$2.46_{\pm0.3}$	$1.26_{\pm0.29}$	$2.02_{\pm0.07}$	$0.9_{\pm0.22}$
TIMEGAN	$1.57_{\pm0.25}$	$1.32_{\pm0.13}$	$\mathbf{1.21}_{\pm0.05}$	$0.86_{\pm0.17}$
PSA-GAN	$\mathbf{0.99}_{\pm0.44}$	$\mathbf{0.62}_{\pm0.3}$	$1.22_{\pm0.05}$	$\mathbf{0.59}_{\pm0.2}$

Figure 2: NRMSE of far-forecasting experiments (lower is better). Mean and confidence intervals are obtained by re-running each method ten times **Left**: NRMSE average over different forecast windows. `DeepAR` is only run on the real time series data. The other models correspond to `DeepAR` and one of the GAN models for filling missing observations. **Right**: NRMSE by forecast window. The first window will have no missing values during inference (we forecast the first 32 steps after the training range) and we increase the missing values during inference with each window (the last window will have $32 * 6$ missing values). For `DeepAR`, the NRMSE increases noticeably at the fourth forecast window while using `PSA-GAN` to impute the missing values at inference keeps the NRMSE low.

in the `PSA-GAN` model results in the best overall performance, we are interested to use the GAN in downstream tasks where the context is not available. Thus, the next section will use `PSA-GAN` without context, unless otherwise stated.

Evaluation of Downstream Forecasting Tasks: In the next four paragraphs, we will show the performance of `PSA-GAN` on several downstream forecasting tasks: Far-forecasting, missing value stretches in training data, cold start forecasts, and data augmentation. For the downstream tasks, we do not use the GAN models directly to perform forecasts but rather use it to support `DeepAR` under challenging forecasting conditions. Furthermore, we show the performance of `PSA-GAN` when used as a forecasting model.

Far-forecasting: In this experiment, we forecast far into the future by assuming that the data points between the training end time and the rolling evaluation window are not observed. For example, the last evaluation window would have $32 * 6$ unobserved values between the training end time and the forecast start date. This setup reflects two possible use cases: Forecasting far into the future (where no context data is available) and imputing missing data during inference because of a data outage just before forecasting. Neural network-based forecasting models such as `DeepAR` struggle under these conditions because they rely on the recent context and need to impute these values during inference. Furthermore, `DeepAR` only imputes values in the immediate context and not for the lagged values. Here, we use the GAN models during inference to fill the missing observations with synthetic data. As a baseline, we use `DeepAR` and impute the missing observations of lagged values with a moving average (window size 10) during inference. Here, we find that using the synthetic data from GAN models drastically improve over the `DeepAR` baseline and using samples from `PSA-GAN` results into the lowest NRMSE for three out of four datasets (see left Table in Figure 2). Figure 2 also shows the NRMSE as a function of the forecast window. When more values are unobserved, the error of DeepAR increases sharply while using the `PSA-GAN` samples during inference results in lower error. Figure 3 shows an example of a imputed time series and the resulting forecast from the `electricity` dataset when using `PSA-GAN`.

Missing Value Stretches: Missing values are present in many real world time series applications and are often caused by outages of a sensor or service that generates a time series (Zhang et al., 2019b). Therefore, missing values in real-world scenarios are often not evenly distributed over the time series but instead form missing value "stretches". In this experiment, we simulate missing value stretches and remove time series values of length 50 and 110 from the datasets. This results into 5.4-7.7% missing values for a stretch length of 50 and and 9.9-16.9% missing values for a stretch length of 110 (depending on the dataset.) Here, we split the training dataset into two parts along the time axis and only introduce missing values in the second part. We use the first (unchanged) part of the training dataset to train the GAN models and both parts of the training set to train `DeepAR`. We then use the GAN models to impute missing values during training and inference of `DeepAR`.

Figure 3: Example of the far-forecasting experiment for the `electricity` dataset. True data is shown in blue and the imputed sequence and forecasts of the model in orange. The orange line between the dashed lines corresponds to the `PSA-GAN` imputed sequence and is used by `DeepAR` for forecasting. Note that this part is unobserved in this experiment. The imputed sequence allows to generate a reasonable forecast, even if many data points before the forecast start date are unobserved.

Figure 4 shows that using the GAN models to impute missing values during *training* `DeepAR` on data with missing value stretches reduces its forecasting error. While all GAN models reduce the NRMSE in this setup, `PSA-GAN` is most effective in reducing the error in this experiment. The Appendix shows a detailed Figure with a split by dataset.

Figure 4: Performance of using different GAN models for imputation in the missing value stretch length experiment. Markers denote the mean NRMSE averaged over datasets and error bars the 68% confidence interval over ten runs. For 50 and 110 missing value stretch length, using `PSA-GAN` to impute missing values results in the lowest overall error, whereas `DeepAR` returns the highest.

Cold Starts: In this experiment, we explore whether the GAN models can support `DeepAR` in a cold start forecasting setting. Cold starts refer to new time series (like a new product in demand forecasting) for which little or no data is available. Here, we randomly truncate 10%, 20%, and 30% of the time series from our datasets such that only the last 24 (representing 24 hours of data) values before inference are present. We only consider a single forecasting window in this experiment. We then again use the GAN models to impute values for the lags and context that `DeepAR` conditions for forecasting the cold start time series. Cold start time series are not used for training the GAN models. Figure 5 shows the forecasting error of the different models for the cold start time series only. In this experiment, `PSA-GAN` and `TIMEGAN` improve the NRMSE over `DeepAR` and are on-par overall (mean NMRSE 0.70 and 0.71 for `PSA-GAN` and `TIMEGAN`, respectively). The Appendix shows a detailed Figure with a split by dataset.

Data Augmentation: In this experiment, we average the real data and GAN samples to augment the data during training. [1] During inference, `DeepAR` is conditioned on real data only to generate forecasts. In our experiments, none of the GAN models for data augmentation consistently improves over `DeepAR`. Overall, `TIMEGAN` is the best-performing GAN model but plain `DeepAR` still performs better. We hypothesize that the GAN models cannot improve in the data augmentation setup because they are trained to generate realistic samples and not necessarily to produce relevant invariances. Furthermore, the dataset sizes might be sufficient for `DeepAR` to train a well-performing model and therefore the augmentation might not be able to reduce the error further. More research is required to understand whether synthetic data can improve forecasting models via data augmentation.

---

[1]We also tried using only the GAN generated data for training and experimented with ratios of mixing synthetic and real samples, similar to the work in (Ravuri & Vinyals, 2019).

Figure 5: Performance of using different GAN models for imputation in the cold start experiment. Markers denote the mean NRMSE averaged over datasets and error bars the 68% confidence interval over ten runs. Note that this figure only shows the error of the cold start time series. Overall, `TIMEGAN` and `PSA-GAN` improve the NRMSE over DeepAR in this setup, while `PSA-GAN` is the best method when 30% of time series are cold starts.

NRMSE				
Dataset Model	Electricity	M4	Solar	Traffic
DeepAR	$\mathbf{0.49}_{\pm 0.03}$	$\mathbf{0.26}_{\pm 0.02}$	$1.07_{\pm 0.01}$	$\mathbf{0.45}_{\pm 0.01}$
EBGAN	$0.64_{\pm 0.05}$	$0.32_{\pm 0.09}$	$1.18_{\pm 0.03}$	$0.50_{\pm 0.03}$
TIMEGAN	$0.56_{\pm 0.05}$	$0.28_{\pm 0.02}$	$\mathbf{1.06}_{\pm 0.02}$	$0.47_{\pm 0.004}$
PSA-GAN	$0.64_{\pm 0.22}$	$0.3_{\pm 0.04}$	$1.07_{\pm 0.03}$	$0.50_{\pm 0.11}$

Table 2: NRMSE accuracy comparison of data augmentation experiments (lower is better, best method in bold). Mean and 95% confidence intervals are obtained by re-running each method five times. `DeepAR` is only run on the real time series data. The other models correspond to `DeepAR` and one of the GAN models for data augmentation.

Forecasting Experiments: In this experiment, we use the GAN models directly for forecasting (Table 3). We can see that `DeepAR` consistently performs best. This is expected as `DeepAR` takes into account context information and lagged values. This kind of information is not available to the GAN models. To test this we further consider `PSA-GAN-C`, i.e. `PSA-GAN` with 64 previous time series values as context, and further evaluate `DeepAR` with restricted lags to the previous 64 values (`DeepAR-C`). We can see that in this case `PSA-GAN-C` outperforms `DeepAR-C` in 3 out of 4 datasets. Moreover, both `PSA-GAN` and `PSA-GAN-C` are the best performing GAN models. Adding lagged values to the GAN models as context could further improve their performance and adversarial/attention architectures have been previously used for forecasting (Wu et al., 2020a). Finally, in Figure 6 we present samples generated from each GAN model. We can see that our proposed models `PSA-GAN` and `PSA-GAN-C` present more accurate samples to the ground truth values.

NRMSE				
Dataset Model	Electricity	M4	Solar	Traffic
DeepAR	$\mathbf{0.49}_{\pm 0.03}$	$\mathbf{0.26}_{\pm 0.02}$	$\mathbf{1.07}_{\pm 0.01}$	$\mathbf{0.45}_{\pm 0.01}$
DeepAR-C	$1.43_{\pm 0.40}$	$0.73_{\pm 0.46}$	$0.95_{\pm 0.01}$	$0.89_{\pm 0.16}$
EBGAN	$3.63_{\pm 0.07}$	$1.14_{\pm 0.01}$	$2.31_{\pm 0.01}$	$2.02_{\pm 0.00}$
TIMEGAN	$3.04_{\pm 0.00}$	$1.12_{\pm 0.00}$	$1.83_{\pm 0.00}$	$1.13_{\pm 0.00}$
PSA-GAN	$1.53_{\pm 0.00}$	$0.61_{\pm 0.00}$	$1.35_{\pm 0.00}$	$0.66_{\pm 0.00}$
PSA-GAN-C	$1.18_{\pm 0.00}$	$0.33_{\pm 0.00}$	$1.32_{\pm 0.00}$	$0.57_{\pm 0.00}$

Table 3: NRMSE accuracy comparison of forecasting experiments (lower is better, best method in bold). Mean and 95% confidence intervals are obtained by re-running each method five times. `DeepAR-C` and `PSA-GAN-C` use the same 64 previous values as context. Among GAN models `PSA-GAN` and `PSA-GAN-C` perform best.

Low Context-FID Score Models Correspond to Best-performing Forecasting Models: One other observation is that the lowest Context-FID score models correspond to the best models in the data augmentation and far-forecasting experiments. `PSA-GAN` and `TIMEGAN` produce the lowest Context-FID samples and both models also improve over the baseline in most downstream tasks. Overall, `PSA-GAN` has lowest Context-FID and also outperforms the other models in the downstream forecasting tasks, except for the cold start task. This suggests that the Context-FID score could be a useful score to develop time series GAN models for downstream use.

(a) `EBGAN`   (b) `TIMEGAN`   (c) `PSA-GAN`   (d) `PSA-GAN-C`

Figure 6: Forecast samples from different GAN models with prediction length 32 from the Traffic dataset. GAN samples are shown in blue and true time series values in red. We can see that `PSA-GAN` and `PSA-GAN-C` produce more accurate samples to the ground truth values.

Ablation Study: Figure 7 shows the results of our ablation study where we disable important components of our model: moment loss, self-attention, and fading in of new layers. We measure the performance of the ablation models by Context-FID score. Overall, our proposed `PSA-GAN` model performs better than the ablations which confirms that these components contribute to the performance of the model.

Figure 7: We perform an ablation study by disabling moment loss, self-attention, and fading in of new layers of `PSA-GAN`. We show the mean performance over three runs on four datasets and the 68% confidence interval. `PSA-GAN` has the lowest Context-FID score which confirms that the proposed model requires these components for good performance. **SA**: Self Attention, **ML**: Moment Loss, **fade in**: Progressive fade in of new layers

5   CONCLUSION

We have presented `PSA-GAN`, a progressive growing time series GAN augmented with self-attention, that produces long realistic time series and improves downstream forecasting tasks that are challenging for deep learning-based time series models. Furthermore, we introduced the Context-FID score to assess the quality of synthetic time series samples produced by GAN models. We found that the lowest Context-FID scoring models correspond to the best-performing models in downstream tasks. We believe that time series GANs that scale to long sequences combined with a reliable metric to assess their performance might lead to their routine use in time series modeling.

REFERENCES

Alexander Alexandrov, Konstantinos Benidis, Michael Bohlke-Schneider, Valentin Flunkert, Jan Gasthaus, Tim Januschowski, Danielle C Maddix, Syama Rangapuram, David Salinas, Jasper Schulz, Lorenzo Stella, Ali Caner Türkmen, and Yuyang Wang. GluonTS: Probabilistic time series models in python. *arXiv preprint arXiv:1906.05264*, 2019.

Shaojie Bai, J. Zico Kolter, and Vladlen Koltun. An empirical evaluation of generic convolutional and recurrent networks for sequence modeling, 2018.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale gan training for high fidelity natural image synthesis, 2019.

Zhicheng Cui, Wenlin Chen, and Yixin Chen. Multi-scale convolutional neural networks for time series classification, 2016.

Emmanuel de Bézenac, Syama Sundar Rangapuram, Konstantinos Benidis, Michael Bohlke-Schneider, Richard Kurle, Lorenzo Stella, Hilaf Hasson, Patrick Gallinari, and Tim Januschowski. Normalizing kalman filters for multivariate time series analysis. *Advances in Neural Information Processing Systems*, 33, 2020.

Dua Dheeru and Efi Karra Taniskidou. UCI machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

Jesse Engel, Kumar Krishna Agrawal, Shuo Chen, Ishaan Gulrajani, Chris Donahue, and Adam Roberts. GANSynth: Adversarial neural audio synthesis. In *International Conference on Learning Representations*, 2019.

Cristóbal Esteban, Stephanie L. Hyland, and Gunnar Rätsch. Real-valued (Medical) Time Series Generation with Recurrent Conditional GANs. *arXiv:1706.02633 [cs, stat]*, December 2017. arXiv: 1706.02633.

Jean-Yves Franceschi, Aymeric Dieuleveut, and Martin Jaggi. Unsupervised scalable representation learning for multivariate time series. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Jean-Yves Franceschi, Aymeric Dieuleveut, and Martin Jaggi. Unsupervised scalable representation learning for multivariate time series, 2020.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks, 2014.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium, 2018.

Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation, 2018.

Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization, 2017.

Richard Kurle, Syama Sundar Rangapuram, Emmanuel de Bézenac, Stephan Günnemann, and Jan Gasthaus. Deep rao-blackwellised particle filters for time series forecasting. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 15371–15382. Curran Associates, Inc., 2020.

Guokun Lai, Wei-Cheng Chang, Yiming Yang, and Hanxiao Liu. Modeling long- and short-term temporal patterns with deep neural networks. *CoRR*, abs/1703.07015, 2017.

Shiyang Li, Xiaoyong Jin, Yao Xuan, Xiyou Zhou, Wenhu Chen, Yu-Xiang Wang, and Xifeng Yan. Enhancing the locality and breaking the memory bottleneck of transformer on time series forecasting. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Kevin Lin, Dianqi Li, Xiaodong He, Zhengyou Zhang, and Ming-ting Sun. Adversarial ranking for language generation. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

Spyros Makridakis, Evangelos Spiliotis, and Vassilios Assimakopoulos. The M4 Competition: 100,000 time series and 61 forecasting methods. *International Journal of Forecasting*, 36(1):54–74, 2020. ISSN 0169-2070.

Xudong Mao, Qing Li, Haoran Xie, Raymond Y. K. Lau, Zhen Wang, and Stephen Paul Smolley. Least squares generative adversarial networks, 2017.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks, 2018.

Olof Mogren. C-RNN-GAN: Continuous recurrent neural networks with adversarial training. *arXiv:1611.09904 [cs]*, November 2016. arXiv: 1611.09904.

Boris N Oreshkin, Dmitri Carpov, Nicolas Chapados, and Yoshua Bengio. N-beats: Neural basis expansion analysis for interpretable time series forecasting. *arXiv preprint arXiv:1905.10437*, 2019.

Boris N Oreshkin, Dmitri Carpov, Nicolas Chapados, and Yoshua Bengio. Meta-learning framework with applications to zero-shot time-series forecasting. *arXiv preprint arXiv:2002.02887*, 2020.

Kashif Rasul, Calvin Seward, Ingmar Schuster, and Roland Vollgraf. Autoregressive denoising diffusion models for multivariate probabilistic time series forecasting, 2021.

Suman Ravuri and Oriol Vinyals. Seeing is Not Necessarily Believing: Limitations of BigGANs for Data Augmentation. March 2019.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved Techniques for Training GANs. *arXiv:1606.03498 [cs]*, June 2016. arXiv: 1606.03498.

David Salinas, Valentin Flunkert, Jan Gasthaus, and Tim Januschowski. DeepAR: Probabilistic forecasting with autoregressive recurrent networks. *International Journal of Forecasting*, 2019.

David Salinas, Valentin Flunkert, Jan Gasthaus, and Tim Januschowski. Deepar: Probabilistic forecasting with autoregressive recurrent networks. *International Journal of Forecasting*, 36(3): 1181–1191, 2020.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jonathon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. *CoRR*, abs/1512.00567, 2015.

Shuntaro Takahashi, Yu Chen, and Kumiko Tanaka-Ishii. Modeling financial time-series with generative adversarial networks. *Physica A Statistical Mechanics and its Applications*, 527:121261, August 2019. doi: 10.1016/j.physa.2019.121261.

Aaron van den Oord, Sander Dieleman, Heiga Zen, Karen Simonyan, Oriol Vinyals, Alex Graves, Nal Kalchbrenner, Andrew Senior, and Koray Kavukcuoglu. Wavenet: A generative model for raw audio, 2016.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need, 2017.

Zhiguang Wang, Weizhong Yan, and Tim Oates. Time series classification from scratch with deep neural networks: A strong baseline, 2016.

Sifan Wu, Xi Xiao, Qianggang Ding, Peilin Zhao, Ying Wei, and Junzhou Huang. Adversarial sparse transformer for time series forecasting. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 17105–17115. Curran Associates, Inc., 2020a. URL https://proceedings.neurips.cc/paper/2020/file/c6b8c8d762da15fa8dbbdfb6baf9e260-Paper.pdf.

Sifan Wu, Xi Xiao, Qianggang Ding, Peilin Zhao, Ying Wei, and Junzhou Huang. Adversarial sparse transformer for time series forecasting. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 17105–17115. Curran Associates, Inc., 2020b.

Bing Xu, Naiyan Wang, Tianqi Chen, and Mu Li. Empirical evaluation of rectified activations in convolutional network, 2015.

Jinsung Yoon, Daniel Jarrett, and Mihaela van der Schaar. Time-series generative adversarial networks. In *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019.

Han Zhang, Ian Goodfellow, Dimitris Metaxas, and Augustus Odena. Self-attention generative adversarial networks, 2019a.

Yi-Fan Zhang, Peter J. Thorburn, Wei Xiang, and Peter Fitch. Ssim—a deep learning approach for recovering missing time series sensor data. *IEEE Internet of Things Journal*, 6(4):6618–6628, 2019b. doi: 10.1109/JIOT.2019.2909038.

Junbo Jake Zhao, Michaël Mathieu, and Yann LeCun. Energy-based generative adversarial networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017.

A TIME SERIES FEATURES

We use time series features to represent the time dimension for the GAN models and also for DeepAR. We use `HourOfDay`, `DayOfWeek`, `DayOfMonth` and `DayOfYear` features. Each feature is encoded using a single index number (for example, between $[0, 365[$ for `DayOfYear`) and normalized to be within [-0.5, 0.5]. We also use an age feature to represent the age of the time series to be $log(2.0 + t)$ where t is the time index. Lastly we embed each time series index in a 10 dimension vector using a look-up table.

B TRAINING PROCEDURE

`PSA-GAN` uses spectral normalization and progressive fade-in of new layers to stabilize training.

Progressive fade in of new layers As training progresses, new layers are added to double the length of time series. However, simply adding new untrained layers drastically changes the number of parameters and the loss landscape, which destabilizes training. Progressive fade in of new layers is a technique introduce by Karras et al., 2018 to mitigate this effect where each layer g_i and d_i is smoothly introduced. For $i \in [2, L]$ the fade in of new layers is written as:

$$
\begin{aligned}
g_i : &\mathbb{R}^{n_f \times 2^{i+1}} \to \mathbb{R}^{n_f \times 2^{i+2}} \\
&\tilde{Z}_{i-1} \mapsto \tilde{Z}_i = \alpha m(\mathrm{UP}(\tilde{Z}_{i-1})) + (1-\alpha)\,\mathrm{UP}(\tilde{Z}_{i-1})
\end{aligned}
\tag{8}
$$

$$
\begin{aligned}
d_i : &\mathbb{R}^{n_f \times 2^{i+2}} \to \mathbb{R}^{n_f \times 2^{i+1}} \\
&Y_i \mapsto Y_{i-1} = \alpha \,\mathrm{DOWN}(m(Y_i)) + (1-\alpha)\,\mathrm{DOWN}(Y_i)
\end{aligned}
\tag{9}
$$

where α is a scalar initialized to be zero and grows linearly to one over 500 epochs.

Spectral Normalisation   Both the generator and the discriminator benefit from using spectral normalisation layers. In the discriminator, Spectral Normalisation stabilizes training (Miyato et al., 2018). It constrains the Lipschitz constant of the discriminator to be bounded by one. In the generator the spectral normalisation stabilises the training and avoids escalation of the gradient magnitude (Zhang et al., 2019a).

C   TRAINING DETAILS

PSA-GAN has been trained over 6500 epochs, where a new block is added every 1000 epochs and is faded over 500 epochs. At each epoch, PSA-GAN trains on 100 batches of size 512. It optimises its parameters using the Adam (Kingma & Ba, 2017) with a learning rate of 0.0005 and betas of $(0.9, 0.999)$ for both the generator and the discriminator.

PSA-GAN (and its variants) has been trained on ml.p2.xlarge Amazon instances for 21 hours.

The number of in-channels and out-channels n_f in the Main Block (Figure 1, *Right*) equals 32. The number of out-channels in the convolution layer c equals 1 (Eq.6). The number of time features D equals 15.

For the case of PSA-GAN-C, the MLP block is a two layers perceptron with LeakyReLU. It incorporates knowledge of the past by selecting the $L_C = 64$ time points and concatenates them with its input.

D   FORECASTING EXPERIMENT DETAILS

We use the `DeepAR` (Salinas et al., 2020) implementation in `GluonTS` (Alexandrov et al., 2019) for the forecasting experiments. We use the default hyperparameters of `DeepAR` with the following exceptions: `epochs=100, num batches per epoch=100, dropout rate=0.01, scaling=False, prediction length=32, context length=64, use feat static cat=True`. We use the Adam optimizer with a learning rate of $1e-3$ and weight decay of $1e-8$. Additionally, we clip the gradient to 10.0 and reduce the learning rate by a factor of 2 for every 10 consecutive updates without improvement, up to a minimum learning rate of $5e-5$. `DeepAR` also uses lagged values from previous time steps that are used as input to the LSTM at each time step t. We set the time series window size that DeepAR samples to 256 and truncate the default hourly lags to fit the context window, the prediction window, and the longest lag into the window size 256. We use the following lags: [1, 2, 3, 4, 5, 6, 7, 23, 24, 25, 47, 48, 49, 71, 72, 73, 95, 96, 97, 119, 120, 121, 143, 144, 145].

E   ADDITIONAL EXPERIMENT FIGURES

Figure 8: Detailed performance of using different GAN models for imputation in the missing value stretch length experiment. Markers denote the mean NRMSE averaged over ten runs and error bars represent the 95% confidence interval. For 50 and 110 missing value stretch length, using `PSA-GAN` to impute missing values results in the lowest error for three out of four datasets.

Figure 9: Detailed performance of using different GAN models for the cold start experiment Markers denote the mean NRMSE averaged over ten runs and error bars the 95% confidence interval. `TIMEGAN` and `PSA-GAN` improve over `DeepAR` in three out of four datasets.

F SAMPLE FORECASTS

We present more sample forecasts under the framework of the forecasting experiment. In Figs. 10, 11, 12, 13 we present sample forecast for Electricity, M4, Solar Energy, and Traffic datasets, respectively. We can see that the synthetic time series generated by `PSA-GAN` and `PSA-GAN-C` consistently convey a better approximation to the ground truth values. One can further observe that this task is particularly challenging for GANs as data generation is located in a time-frame that is not covered while training.

Figure 10: Sample forecasts for dataset **Electricity**

(a) EBGAN (b) TIMEGAN (c) PSA-GAN (d) PSA-GAN-C

Figure 11: Sample forecasts for dataset **M4**

(a) EBGAN (b) TIMEGAN (c) PSA-GAN (d) PSA-GAN-C

Figure 12: Sample forecasts for dataset **Solar**

(a) EBGAN (b) TIMEGAN (c) PSA-GAN (d) PSA-GAN-C

Figure 13: Sample forecasts for dataset **Traffic**

(a) EBGAN (b) TIMEGAN (c) PSA-GAN (d) PSA-GAN-C