Learning Representation from Neural Fisher Kernel with Low-rank Approximation

Abstract

In this paper, we study the representation of neural networks from the view of kernels. We first define the Neural Fisher Kernel (NFK), which is the Fisher Kernel (Jaakkola et al.) applied to neural networks. We show that NFK can be computed for both supervised and unsupervised learning models, which can serve as a unified tool for representation extraction. Furthermore, we show that practical NFKs exhibit low-rank structures. We then propose an efficient algorithm that computes a low rank approximation of NFK, which scales to large datasets and networks. We show that the low-rank approximation of NFKs derived from unsupervised generative models and supervised learning models gives rise to high-quality compact representations of data, achieving competitive results on a variety of machine learning tasks.

1 Introduction

Modern deep learning systems rely on finding good representations of data. For supervised learning models with feed forward neural networks, representations can naturally be equated with the activations of each layer. Empirically, the community has developed a set of effective heuristics for representation extraction given a trained network. For example, ResNets (He et al., 2016) trained on Imagenet classification yield intermediate layer representations that can benefit downstream tasks such as object detection and semantic segmentation. The logits layer of a trained neural network also captures rich correlations across classes which can be distilled to a weaker model (Knowledge Distillation) (Hinton et al., 2015).

Despite empirical prevalence of using intermediate layer activations as feature representation, it's far from being the optimal approach to representation extraction. For *supervised learning* models, it remains a manual procedure that relies on trial and error to select the optimal layer from a pre-trained model to facilitate transfer learning scenario. Similar observations also apply to *unsupervised learning* models including GANs (Goodfellow et al., 2014), VAEs (Kingma and Welling, 2013), as evident from recent studies (Chen et al., 2020a) that the quality of representation in generative models heavily also depends on the choice of layer from which we extract activations as features. Furthermore, although that GANs and VAEs are known to be able to generate high-quality samples of the training distribution, there is no strong evidence that they encode explicit layerwise representations to similar quality as in supervised learning models, which implies that there doesn't exist a natural way to explicitly extract a representation from intermediate layer activations in unsupervisedly pre-trained generative models. Additionally, layer activations alone don't suffice to reach the full power of learned representations hidden in neural network models, as shown in recent works (Mu et al., 2020) that incorporating additional gradients-based features into representation leads to substantial improvement over solely using activations-based features.

In light of these constraints, we are interested in the question: **is there a principled method for representation extraction beyond layer activations?** In this work, we turn to the kernel view of neural networks. Recently, initiated by the Neural Tangent Kernel (NTK) (Jacot et al., 2018) work, there have been growing interests in the kernel interpretation of neural networks. It was shown that neural networks in the infinite width regime are reduced to kernel regression with the induced NTK. Our key intuition is that, the kernel machine induced by the neural network provides a powerful and principled way of investigating the non-linear feature transformation in neural networks using the *linear* feature space of the kernel. Kernel machines provide drastically different representations than

layer activations, where the knowledge of a neural network is instantiated by the induced kernel function over data points.

In this work, we propose to make use of the linear feature space of the kernel, induced by the pre-trained neural network model, as data representation. As a step towards a general kernel formulation for both supervised learning and unsupervised learning models, we introduce Neural Fisher Kernel (NFK) and show that NFK exhibit a low-rank structure. We then propose a highly efficient and scalable algorithm for low-rank kernel approximation, so that we can obtain a compact low-dimensional embedding from the NFK of the given neural network as the extracted representation, and verify the effectiveness of the introduced approach across various benchmarks.

2 PRELIMINARY AND RELATED WORKS

In this section, we present technical background and formalize the motivation. We start by introducing the notion of data representation from the perspective of kernel methods, then introduce the connections between neural network models and kernel methods.

Notations Throughout this paper, we consider dataset with N data examples $\mathcal{D} \equiv \{(\mathbf{x}_i, y_i)\}$, we use $p(\mathbf{x})$ to denote the probability density function for the data distribution and use $p_{\text{data}}(\mathbf{x})$ to denote the empirical data distribution from $\mathcal{D}$.

Kernel Methods Kernel methods (Hofmann et al., 2008) have long been a staple of practical machine learning. At their core, a kernel method relies on a kernel function which acts as a similarity function between different data examples in some feature space. Here we consider positive definite kernels $\mathcal{K} : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$ over a metric space $\mathcal{X}$ which defines a reproducing kernel Hilbert space $\mathcal{H}$ of function from $\mathcal{X}$ to $\mathbb{R}$, along with a mapping function $\varphi : \mathcal{X} \to \mathcal{H}$, such that the kernel function can be decomposed into the inner product $\mathcal{K}(\mathbf{x}, \mathbf{z}) = \langle \varphi(\mathbf{x}), \varphi(\mathbf{z}) \rangle$. Kernel methods aim to find a predictive linear function $f(\mathbf{x}) = \langle f, \varphi(\mathbf{x}) \rangle_{\mathcal{H}}$ in $\mathcal{H}$, which gives label output prediction for each data point $\mathbf{x} \in \mathcal{X}$. The kernel maps each data example $\mathbf{x} \in \mathcal{X}$ to a linear feature space $\varphi(\mathbf{x})$, which is the **data representation** of interest. Given dataset $\mathcal{D}$, the predictive model function f is typically estimated via Kernel Ridge Regression (KRR), $\widehat{f} = \text{argmin}_{f \in \mathcal{H}} \frac{1}{N} \sum_{i=1}^{N} (f(\mathbf{x}_i) - y_i)^2 + \lambda \|f\|_{\mathcal{H}}^2$.

Neural Networks and Kernel Methods A long line of works (Neal, 1996; Williams, 1996; Roux and Bengio, 2007; Hazan and Jaakkola, 2015; Lee et al., 2018; de G. Matthews et al., 2018; Jacot et al., 2018) have studied that many kernel formulations can be associated to neural networks, while most of them correspond to neural network where only the last layer is trained, e.g., Conjugate Kernel (CK) (Daniely et al., 2016), also called as NNGP kernel (Lee et al., 2018). On the other hand, Neural Tangent Kernel (NTK) (Jacot et al., 2018) is a fundamentally different formulation corresponding to training the entire infinitely wide neural network models. Let $f(\boldsymbol{\theta}; \mathbf{x})$ denote a neural network function with parameters $\boldsymbol{\theta}$, then the empirical NTK is defined as $\mathcal{K}_{\text{ntk}}(\mathbf{x}, \mathbf{z}) = \langle \nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta}; \mathbf{x}), \nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta}; \mathbf{z}) \rangle$. (Jacot et al., 2018; Lee et al., 2018) showed that under the so-called NTK parametrization and other proper assumptios, the function $f(\mathbf{x}; \boldsymbol{\theta})$ learned by training the neural network model with gradient descent is equivalent to the function estimated via ridgeless KRR using $\mathcal{K}_{\text{ntk}}$ as the kernel. For finite-width neural networks, by taking first-order Taylor expansion of funnction f around the $\boldsymbol{\theta}$, kernel regression under $\mathcal{K}_{\text{ntk}}$ can be seen as linearized neural network model at parameter $\boldsymbol{\theta}$, suggesting that pre-trained neural network models can also be studied and approximated from the perspective of kernel methods.

Fisher Kernel The Fisher Kernel (FK) is first introduced in the seminal work (Jaakkola et al.). Given a probabilistic generative model $p_{\boldsymbol{\theta}}(x)$, the Fisher kernel is defined as: $\mathcal{K}_{\text{fisher}}(\mathbf{x}, \mathbf{z}) = \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{x})^{\top} \mathcal{I}^{-1} \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{z}) = U_{\mathbf{x}}^{\top} \mathcal{I}^{-1} U_{\mathbf{x}}$ where $U_{\mathbf{x}} = \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{x})$ is the so-called Fisher score and $\mathcal{I}$ is the Fisher Information Matrix (FIM) defined as the variance of the Fisher score: $\mathbb{E}_{\mathbf{x} \sim p_{\boldsymbol{\theta}}(\mathbf{x})} \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{x}) \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{x})^{\top}$. Then the Fisher vector is defined as $V_{\mathbf{x}} = \mathcal{I}^{-\frac{1}{2}} \nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{x}) = \mathcal{I}^{-\frac{1}{2}} U_{\mathbf{x}}$. One can utilize the Fisher Score as the mapping from the data space $\mathcal{X}$ to parameter space Θ, and obtain representations that are linearized. As proposed in (Jaakkola et al.; Perronnin and Dance, 2007), the Fisher vector $V_{\mathbf{x}}$ can be used as the feature representation derived from probabilistic generative models, which was shown to be superior to hand-crafted visual descriptors in a variety of computer vision tasks.

3 LEARNING REPRESENTATION FROM NEURAL FISHER KERNEL

We aim to propose a general and efficient method for extracting high-quality representation from pre-trained neural network models. As formalized in previous section, we can describe the outline of our proposed approach as: given a pre-trained neural network model $f(\mathbf{x}; \boldsymbol{\theta})$ (either unsupervised generative model $p(\mathbf{x}; \boldsymbol{\theta})$ or supervised learning model $p(\mathbf{y} \mid \mathbf{x}; \boldsymbol{\theta})$), with pre-trained weights $\boldsymbol{\theta}$, we adopt the kernel formulation $\mathcal{K}_f$ induced by model $f(\mathbf{x}; \boldsymbol{\theta})$ and make use of the associated linear feature embedding $\varphi(\mathbf{x})$ of the kernel $\mathcal{K}_f$ as the feature representation of data $\mathbf{x}$.

At this point, however, there exist both theoretical difficulties and practical challenges which impede a straightforward application of our proposed approach. On theoretical side, the NTK theory is only developed in supervised learning setting, and its extension to unsupervised learning is not established yet. Though Fisher kernel is immediately applicable in unsupervised learning setting, deriving Fisher vector from supervised learning model $p(\mathbf{y} \mid \mathbf{x}; \boldsymbol{\theta})$ can be tricky, which needs the log-density estimation of *marginal* distribution $p_{\boldsymbol{\theta}}(\mathbf{x})$ from $p(\mathbf{y} \mid \mathbf{x}; \boldsymbol{\theta})$. Note that it's a drastically different problem from previous works (Achille et al., 2019) where Fisher kernel is applied to the joint distribution over $p(\mathbf{x}, \mathbf{y})$. On practical efficiency side, the dimensionality of the feature space associated with NTK or FK is same as the number of model parameters $|\boldsymbol{\theta}|$, which poses unmanageably high time and space complexity when it comes to modern large-scale neural network models. Additionally, the size of the NTK scales quadratically with the number of classes in multi-class supervised learning setting, which gives rise to more efficiency concerns.

To address the kernel formulation issue, we propose Neural Fisher Kernel (NFK) in Sec. 3.1 as a unified kernel for both supervised and unsupervised learning models. To tackle the efficiency challenge, we investigate the structural properties of proposed NFK and propose a highly scalable low-rank kernel approximation algorithm in Sec. 3.2 to extract compact low-dimensional feature representation from NFK.

3.1 NEURAL FISHER KERNEL

In this section, we propose Neural Fisher Kernel (NFK) as a principled and general kernel formulation for neural network models. The key intuition is that we can extend classical Fisher kernel theory to unify the procedure of deriving Fisher vector from supervised learning models and unsupervised learning models by using Energy-based Model (EBM) formulation.

3.1.1 UNSUPERVISED NFK

We consider unsupervised probabilistic generative models $p_{\boldsymbol{\theta}}(\mathbf{x}) = p(\mathbf{x}; \boldsymbol{\theta})$ here. Our proposed NFK formulation can be applied to all generative models with tractable gradient evaluation (or approximation) of the log-density function $\nabla_{\boldsymbol{\theta}} \log p_{\boldsymbol{\theta}}(\mathbf{x})$.

GANs We consider the EBM formulation of GANs (Dai et al., 2017; Zhai et al., 2019; Che et al., 2020). Given pre-trained GAN model, we use $D(\mathbf{x}; \boldsymbol{\theta})$ to denote the output of the discriminator D, and use $G(\mathbf{h})$ to denote the output of generator G given latent code $\mathbf{h} \sim p(\mathbf{h})$. As a brief recap, GANs can be interpreted as an implementation of EBM training with a variational distribution, where we have the energy-function $E(\mathbf{x}; \boldsymbol{\theta}) = -D(\mathbf{x}; \boldsymbol{\theta})$. Please refer to (Zhai et al., 2019; Che et al., 2020) for more details. Thus we have the unnormalized density function $p_{\boldsymbol{\theta}}(\mathbf{x}) \propto e^{-E(\mathbf{x}; \boldsymbol{\theta})}$ given by the GAN model. Following (Zhai et al., 2019), we can then derive the Fisher kernel $\mathcal{K}_{\mathrm{nfk}}$ and Fisher vector from standard GANs as shown below:

$$
\begin{aligned}
\mathcal{K}_{\mathrm{nfk}}(\mathbf{x}, \mathbf{z}) = \langle V_{\mathbf{x}}, V_{\mathbf{z}} \rangle \qquad V_{\mathbf{x}} = (\mathtt{diag}(\mathcal{I})^{-\frac{1}{2}}) U_{\mathbf{x}} \\
U_{\mathbf{x}} = \nabla_{\boldsymbol{\theta}} D(\mathbf{x}; \boldsymbol{\theta}) - \mathbb{E}_{\mathbf{h} \sim p(\mathbf{h})} \nabla_{\boldsymbol{\theta}} D(G(\mathbf{h}); \boldsymbol{\theta})
\end{aligned}
\tag{1}
$$

where $\mathbf{x}, \mathbf{z} \in \mathcal{X}$, $\mathcal{I} = \mathbb{E}_{\mathbf{h} \sim p(\mathbf{h})} \langle U_{G(\mathbf{h})}, U_{G(\mathbf{h})} \rangle$. Note that we use diagonal approximation of FIM throughout this work for the consideration of scalability.

VAEs Given a VAE model pre-trained via maximizing the variational lower-bound ELBO $\mathcal{L}_{\mathrm{ELBO}}(\mathbf{x}) \equiv \mathbb{E}_{q(\mathbf{h} \mid \mathbf{x})} \left[\log \frac{p(\mathbf{x}, \mathbf{h})}{q(\mathbf{h} \mid \mathbf{x})} \right]$, we can approximate the marginal log-likelihood $\log p_{\boldsymbol{\theta}}(\boldsymbol{\theta})$ by evaluating $\mathcal{L}_{\mathrm{ELBO}}(\mathbf{x})$ via Monte-Carlo estimations or importance sampling techniques (Burda et al.,

2016). Thus we have our NFK formulation as

$$
\begin{aligned}
\mathcal{K}_{\mathrm{nfk}}(\mathbf{x}, \mathbf{z}) &= \langle V_{\mathbf{x}}, V_{\mathbf{z}} \rangle \qquad V_{\mathbf{x}} = (\mathrm{diag}(\mathcal{I})^{-\frac{1}{2}}) U_{\mathbf{x}} \\
U_{\mathbf{x}} &\approx \nabla_{\boldsymbol{\theta}} \mathcal{L}_{\mathrm{ELBO}}(\mathbf{x})
\end{aligned}
\tag{2}
$$

where $\mathbf{x}, \mathbf{z} \in \mathcal{X}$, $\mathcal{I} = \mathbb{E}_{\mathbf{x} \sim p_{\boldsymbol{\theta}}(\mathbf{x})} \langle U_{\mathbf{x}}, U_{\mathbf{x}} \rangle$.

Flow-based Models, Auto-Regressive Models For generative models with explicit exact data density modeling $p_{\boldsymbol{\theta}}(\mathbf{x})$, we can simply apply the classical Fisher kernel formulation in Sec. 2.

3.1.2 SUPERVISED NFK

In the supervised learning setting, we consider conditional probabilistic models $p_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x}) = p(\mathbf{y} \mid \mathbf{x}; \boldsymbol{\theta})$. In particular, we focus on classification problems where the conditional probability is parameterized by a softmax function over the logits output $f(\mathbf{x}; \boldsymbol{\theta})$: $p_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x}) = \exp(f^{\mathbf{y}}(\mathbf{x}; \boldsymbol{\theta})) / \sum_{\mathbf{y}} \exp(f^{\mathbf{y}}(\mathbf{x}; \boldsymbol{\theta}))$, where $\mathbf{y}$ is a discrete label and $f^{\mathbf{y}}(\mathbf{x}; \boldsymbol{\theta})$ denotes $\mathbf{y}$-th logit output. We then borrow the idea from JEM (Grathwohl et al., 2019) and write out a joint energy function term over $(\mathbf{x}, \mathbf{y})$ as $E(\mathbf{x}, \mathbf{y}; \boldsymbol{\theta}) = -f^{\mathbf{y}}(\mathbf{x}; \boldsymbol{\theta})$. It is easy to see that joint energy yields exactly the same conditional probability, at the same time leading to a free energy function:

$$
E(\mathbf{x}; \boldsymbol{\theta}) = -\log \sum_{\mathbf{y}} \exp(f^{\mathbf{y}}(\mathbf{x}; \boldsymbol{\theta})).
\tag{3}
$$

Eq. 3 essentially reframes a conditional distribution over $\mathbf{y}$ given $\mathbf{x}$ to an induced unconditional distribution over $\mathbf{x}$, while maintaining the same conditional probability $p_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x})$. This allows us to write out the NFK formulation as:

$$
\begin{aligned}
\mathcal{K}_{\mathrm{nfk}}(\mathbf{x}, \mathbf{z}) &= \langle V_{\mathbf{x}}, V_{\mathbf{z}} \rangle \quad V_{\mathbf{x}} = (\mathrm{diag}(\mathcal{I})^{-\frac{1}{2}}) U_{\mathbf{x}} \\
U_{\mathbf{x}} &= \sum_{\mathbf{y}} p_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x}) \nabla_{\boldsymbol{\theta}} f^{\mathbf{y}}(\mathbf{x}; \boldsymbol{\theta}) - \mathbb{E}_{\mathbf{x}' \sim p_{\boldsymbol{\theta}}(\mathbf{x}')} \sum_{\mathbf{y}} p_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x}) \nabla_{\boldsymbol{\theta}} f^{\mathbf{y}}(\mathbf{x}'; \boldsymbol{\theta})
\end{aligned}
\tag{4}
$$

where $\mathcal{I} = \mathbb{E}_{\mathbf{x} \sim p_{\boldsymbol{\theta}}(\mathbf{x})} \langle U_{\mathbf{x}}, U_{\mathbf{x}} \rangle$, and $p_{\boldsymbol{\theta}}(\mathbf{x})$ is the normalized density corresponding to the free energy E_{θ}, which could be sampled from via Markov chain Monte Carlo (MCMC) algorithm. In this work, we use empirical data distribution as practical approximation.

3.2 NFK WITH LOW-RANK APPROXIMATION

Fisher vector $V_{\mathbf{x}}$ is the linear feature embedding $\varphi(\mathbf{x})$ given by NFK $\mathcal{K}_{\mathrm{nfk}}(\mathbf{x}, \mathbf{z}) = \langle V_{\mathbf{x}}, V_{\mathbf{z}} \rangle$ for neural network model $f(\mathbf{x}; \boldsymbol{\theta})$. However, straightforward application of NFK by using V_x as feature representation suffers from scalability issue, since $V_{\mathbf{x}} \in \mathbb{R}^{|\boldsymbol{\theta}|}$ shares same dimensionality as the number of parameters $|\boldsymbol{\theta}|$. It's with that in mind that $|\boldsymbol{\theta}|$ can be tremendously large considering the scale of modern neural networks, it's unfortunately infeasible to directly leverage $V_{\mathbf{x}}$ as feature representation.

Low-Rank Structure of NFK Motivated by the *Manifold Hypothesis of Data* that it is widely believed that real world high dimensional data lives in a low dimensional manifold (Roweis and Saul, 2000; Rifai et al., 2011a;b), we investigate the structure of NFKs and present empirical evidence that *NFKs of good models have low-rank spectral structure*. Firstly, we start by examining supervised learning models. We study the spectrum structure of the empirical NFK of trained neural networks with different architectures. We trained a LeNet-5 (LeCun et al., 1998) CNN and a 3-layer MLP network by minimizing binary cross entropy loss, and then compute the eigen-decomposition of the NFK Gram matrix. We show the explained ratio plot in Figure 1. We see that the spectrum of CNN NTK concentrates on fewer large eigenvalues, thus exhibits a lower effective-rank structure compared to the MLP, which can be explained by the fact that CNN has better model inductive bias for image data domain. For unsupervised learning models, we trained a small unconditional DCGAN (Radford et al., 2015) model on MNIST dataset. We compare the results of a fully trained model against a randomly initialized model in Fig. 1 (note the logarithm scale of the x axis). Remarkably, the trained model demonstrates an extreme degree of low-rankness that top 100 principle components explain over 99.5% of the overall variance, where 100 is two orders of magnitude smaller than both number of examples and number of parameters in the discriminator. We include more experimental results and discussions in appendix due to the space constraints.

Efficient Low-Rank Approximation of NFK The theoretical insights and empirical evidence presented above hint at a natural solution to address the challenge of high-dimensionality of $V_{\mathbf{x}} \in \mathbb{R}^{|\boldsymbol{\theta}|}$: we can turn to seek a low-rank approximation to the NFK. According to the Mercer's theorem (Mercer, 1909), for positive definite kernel $\mathcal{K}(\mathbf{x}, \mathbf{z}) = \langle \varphi(\mathbf{x}), \varphi(\mathbf{z}) \rangle$ we have $\mathcal{K}(\mathbf{x}, \mathbf{z}) = \sum_{i=1}^{\infty} \lambda_i \phi_i(\mathbf{x}) \phi_i(\mathbf{z}), \; \mathbf{x}, \mathbf{z} \in \mathcal{X}$, where $\{(\lambda_i, \phi_i)\}$ are the eigenvalues and eigenfunctions of the kernel $\mathcal{K}$, with respect to the integral operator $\int p(\mathbf{z}) \mathcal{K}(\mathbf{x}, \mathbf{z}) \phi_i(\mathbf{z}) \, d\mathbf{z} = \lambda_i \phi_i(\mathbf{x})$. The linear feature embedding representation $\varphi(\mathbf{x})$ can thus be constructed from the orthonormal eigenbasis $\{(\lambda_i, \phi_i)\}$ as $\varphi(\mathbf{x}) \equiv \left[\sqrt{\lambda_1} \phi_1(\mathbf{x}), \sqrt{\lambda_2} \phi_2(\mathbf{x}), \dots \right] \equiv \left[\sqrt{\lambda_i} \phi_i(\mathbf{x}) \right], \; i = 1, \dots, \infty$. To obtain a low-rank approximation, we only keep top-k largest eigen-basis $\{(\lambda_i, \phi_i)\}$ ordered by corresponding eigenvalues λ_i to form the low-rank k-dimensional feature embedding $\mathbf{e}(\mathbf{x}) \in \mathbb{R}^k, \, k \ll N, k \ll |\boldsymbol{\theta}|$

$$\mathbf{e}(\mathbf{x}) \equiv \left[\sqrt{\lambda_1} \phi_1(\mathbf{x}), \sqrt{\lambda_2} \phi_2(\mathbf{x}), \dots \sqrt{\lambda_k} \phi_k(\mathbf{x}) \right] \equiv \left[\sqrt{\lambda_i} \phi_i(\mathbf{x}) \right], \; i = 1, \dots, k \qquad (5)$$

By applying our proposed NFK formulation $\mathcal{K}_{\mathrm{nfk}}$ to pre-trained neural network model $f(\mathbf{x}; \boldsymbol{\theta})$, we can obtain a compact low-dimensional feature representation $\mathbf{e}_{\mathrm{nfk}}(\mathbf{x}) \in \mathbb{R}^k$ in this way. We call this the **low-rank NFK feature embedding**.

We then illustrate how to estimate the eigenvalues and eigenfunctions of NFK $\mathcal{K}_{\mathrm{nfk}}$ from data. Given dataset $\mathcal{D}$, the Gram matrix $\mathbf{K} \in \mathbb{R}^{N \times N}$ of kernel $\mathcal{K}$ is defined as $\mathbf{K}(\mathbf{x}_i, \mathbf{x}_j) = \mathcal{K}(\mathbf{x}_i, \mathbf{x}_j)$. We use $\mathbf{X} \equiv [\mathbf{x}_i]_{i=1}^N$ to denote the matrix of all data examples, and use $\phi_i(\mathbf{X}) \in \mathbb{R}^N$ to denote the concatenated vector of evaluting i-th eigenfunction ϕ_i at all data examples. Then by performing eigen-decomposition of the Gram matrix $\mathbf{K} = \boldsymbol{\Phi} \mathtt{diag}(\Lambda) \boldsymbol{\Phi}^\top$, the i-th eigenvector $\boldsymbol{\Phi}_i \in \mathbb{R}^N$ and eigenvalue Λ_i can be seen as unbiased estimation of the i-th eigenfunction ϕ_i and eigenvalue λ_i of the kernel $\mathcal{K}$, evaluated at training data examples $\mathbf{X}$, $\phi_i(\mathbf{X}) \approx \sqrt{N} \boldsymbol{\Phi}_i, \lambda_i \approx \frac{1}{N} \Lambda_i$. Based on these estimations, we can thus approximate the eigenfunction ϕ_i via the integral operator by Monte-Carlo estimation with empirical data distribution,

$$\lambda_i \phi_i(\mathbf{x}) = \int p(\mathbf{z}) \mathcal{K}(\mathbf{x}, \mathbf{z}) \phi_i(\mathbf{z}) \, d\mathbf{z} \approx \mathbb{E}_{\mathbf{x}_j \in p_{\mathrm{data}}} \mathcal{K}(\mathbf{x}, \mathbf{x}_j) \phi_j(\mathbf{x}_j) \approx \frac{1}{N} \sum_{j=1}^N \mathcal{K}(\mathbf{x}, \mathbf{x}_j) \boldsymbol{\Phi}_{ji} \qquad (6)$$

Given new test data example $\mathbf{x}^\star$, we can now approximate the eigenfunction evluation $\phi_i(\mathbf{x}^\star)$ by the projection of kernel function evaluation results centered on training data examples $\mathcal{K}(\mathbf{x}^\star, \mathbf{X}) \equiv [\mathcal{K}(\mathbf{x}^\star, \mathbf{x}_j)]_{j=1}^N$ onto the i-th eigenvector $\boldsymbol{\Phi}_i$ of kernel Gram matrix $\mathbf{K}$. We adopt this method as the baseline approach for low-rank approximation, and present the baseline algorithm description in Alg. 1.

However, due to the fact that it demands explicit computation and manipulation of the Fisher vector matrix $\mathbf{V} \in \mathbb{R}^{N \times |\boldsymbol{\theta}|}$ and the Gram matrix $\mathbf{K} \in \mathbb{R}^{N \times N}$ in Alg. 1, straightforward application of the baseline approach, as well as other off-the-shelf classical kernel approximation (Williams and Seeger, 2000; Rahimi and Recht, 2007) and SVD methods (Halko et al., 2011), are practically infeasible to scale to larger-scale machine learning settings, where both the number of data examples N and the number of model parameters $|\boldsymbol{\theta}|$ can be extremely large.

To tackle the posed scalability issue, we propose a novel highly efficient and scalable algorithm for computing low-rank approximation of NFK. Given dataset $\mathcal{D}$ and model $f(\mathbf{x}; \boldsymbol{\theta})$, We aim to compute the truncated SVD of the Fisher vector matrix $\mathbf{V} = \boldsymbol{\Phi} \mathtt{diag}(\Sigma) \mathbf{P}^\top, \mathbf{P} \in \mathbb{R}^{|\boldsymbol{\theta}| \times k}$. Based on the idea of power methods (Golub and Van der Vorst, 2000; Bathe, 1971) for finding leading top eigenvectors, we starting from a random vector $\mathbf{v}_0$ and iteratively construct the sequence $\mathbf{v}_{t+1} = \frac{\mathbf{V} \mathbf{V}^\top \mathbf{v}_t}{\|\mathbf{V} \mathbf{V}^\top \mathbf{v}_t\|}$. By leveraging the special structure of $\mathbf{V}$ that it can be obtained from the Jacobian matrix $J_{\boldsymbol{\theta}}(\mathbf{X}) \in \mathbb{R}^{N \times |\boldsymbol{\theta}|}$ up to element-wise linear transformation under the NFK formulation in Sec. 3, we can decompose each iterative step into a Jacobian Vector Product (JVP) and a Vector Jacobian Product (VJP). With modern automatic-differentiation techniques, we can evaluate both JVP and VJP efficiently, which only requires the same order of computational costs of one vanilla backward-pass and forward-pass of neural networks respectively. With computed truncated SVD results, we can approximate the projection term in Eq. 6 by $\mathcal{K}(\mathbf{x}, \mathbf{X})^\top \boldsymbol{\Phi}_i = V_{\mathbf{x}} \mathbf{V}^\top \boldsymbol{\Phi}_i \approx V_{\mathbf{x}} \mathtt{diag}(\Sigma_i) \mathbf{P}_i$, which is again in the JVP form so that we can pre-compute and store the truncated SVD results and evaluate the eigenfunction of any test data example via one efficient JVP forward-pass. We describe our proposed algorithm briefly in Alg. 2.

Figure 1: **Left**: The spectrum structure of NFKs from a CNN (green) and a MLP (red), trained on MNIST binary classification task. The NFK of CNN concentrates on fewer eigen-modes compared to the MLP. **Right**: The low-rankness of the NFK on a DCGAN trained on MNIST. For a trained model, the first 100 principle components of the Fisher Vector matrix explains 99.5% of all variances. An untrained model with the same architecture on the other hand, demonstrates a much lower degree of low-rankness.

Algorithm 1 Baseline method: compute low-rank NFK feature embedding

---

Input dataset $\mathcal{D}$; pre-train NN model $f(\mathbf{x}; \boldsymbol{\theta})$; NFK feature dimensionality k; test data input $\mathbf{x}^\star$
Output low-rank NFK feature embedding $\mathbf{e}_{\mathrm{nfk}}(\mathbf{x}^*)$

1: compute Fisher vector for all data examples $\mathbf{V} = [V_{\mathbf{x}_i}] \in \mathbb{R}^{N \times |\boldsymbol{\theta}|}$
2: compute kernel Gram matrix $\mathbf{K} = \mathbf{V}\mathbf{V}^\top \in \mathbb{R}^{N \times N}$
3: compute truncated eigen-decomposition $\mathbf{K} = \boldsymbol{\Phi}\,\mathrm{diag}(\Lambda)\boldsymbol{\Phi}^\top, \boldsymbol{\Phi} \in \mathbb{R}^{N \times k}$
4: kernel function evaluations between $\mathbf{x}^*$ and all data examples $\mathcal{K}(\mathbf{x}^\star, \mathbf{X}) \equiv [\mathcal{K}(\mathbf{x}^\star, \mathbf{x}_j)]_{j=1}^{N}$
5: obtain $\mathbf{e}_{\mathrm{nfk}}(\mathbf{x}^*) \in \mathbb{R}^k$ via Eq. 6 and Eq. 5

---

4 EXPERIMENTS

In this section we evaluate NFK in the following settings. We first evaluate the proposed low-rank kernel approximation algorithm (Sec. 3.2), in terms of both approximation accuracy and running time efficiency. Next, we evaluate NFK on various representation learning tasks in both supervised, semi-supervised and unsupervised learning settings.

4.1 QUALITY AND EFFICIENCY OF LOW-RANK NFK APPROXIMATIONS

We implement our proposed low-rank kernel approximation algorithm in Jax (Bradbury et al., 2018) with distributed multi-GPU parallel computation support. For the baseline methods for comparison, we first compute the full kernel Gram matrix using the `neural-tangents` (Novak et al., 2019) library, and then use `sklearn.decomposition.TruncatedSVD` to obtain the truncated SVD results. All model and algorithm hyperparmeters are included in the Appendix.

Computational Costs We start by comparing running time costs of computing top NFK eigen-vectors via truncated SVD. We use two models for the comparison, a DCGAN-like GAN model in (Zhai et al., 2019) and a Wide ResNet (WRN) with 40 layers and 2 times wider than original network (denoted as WRN-40-2). Please see appendix for the detailed description of hyper-parameters. We observed that our proposed algorithm could achieve nearly linear time scaling, while the baseline method won't be able to handle more than 2^{14} data examples as the memory usage and time complexity are too high to afford. We also see in Fig. 2 that by utilizing multi-GPU parallelism, we achieved further speed-up which scales almost linearly with the number of GPUs. We emphasize that given the number of desired eigenvectors, the time complexity of our method scales linearly with the number of data examples and the demanded memory usage remains constant with adequate data batch size, since explicit computation and storage of the full kernel matrix is never needed.

Algorithm 2 Our proposed method: compute low-rank NFK feature embedding

1: $\mathbf{V} = \mathbf{\Phi}\mathtt{diag}(\Sigma)\mathbf{P}^{\top}, \mathbf{P} \in \mathbb{R}^{|\boldsymbol{\theta}| \times k}$ using power iteration methods via JVP/VJP evaluations
2: compute $\mathcal{K}\left(\mathbf{x}, \mathbf{X}\right)^{\top}\mathbf{\Phi}_i \approx V_{\mathbf{x}}\mathtt{diag}(\Sigma_i)\mathbf{P}_i$ via JVP evaluation
3: obtain $\mathbf{e}_{\mathrm{nfk}}(\mathbf{x}^*) \in \mathbb{R}^k$ via Eq. 6 and Eq. 5

Figure 2: **Top row**: Running time efficiency evaluation for truncated SVD algorithm on single GPU. We vary the number of data examples used, shown in x-axis. y-axis denotes the wall-clock running time (in seconds). Red crosses mark the cases when it's no longer possible for the baseline method to obtain the results in an affordable waiting time and memory consumption. **Bottom left**: Running time costs with different number of GPUs used in our distributed SVD implementation. **Bottom right**: Approximation errors (in blue) of our proposed implementation for each eigenmode (in descending order of eigenvalues), v.s. the explained variance (in red). Best viewed in color.

Approximation accuracy We investigate the approximation error of our proposed low-rank approximation method. Since we didn't introduce any additional approximations, our method shares the same approximation error bound with the existing randomized SVD algorithm (Martinsson and Tropp, 2020; Halko et al., 2011) and would only expect differences compared to the baseline randomized SVD algorithm up to numerical errors. To evaluate the quality of the low-rank kernel approximation, we use LeNet-5 and compute its full NFK Gram matrix on MNIST dataset. Please see appendix for detailed hyper-parameter setups. We show in Fig. 2 the approximation errors of top-128 eigenvalues along with corresponding explained variances. We obtain less than $1e-8$ absolute error and less than $1e-7$ relative error in top eigen-modes which explains most of the data.

4.2 Low-rank NFK Embedding as Data Representations

In this section we evaluate NFK to answer the following: **Q1**. In line with the question raised in Sec. 1, how does our proposed low-rank NFK embedding differ from the intermediate layer activations for data representation? **Q2**. How does the low-rank NFK embedding compare to simply using gradients (Jacobians) as data representation? **Q3**. To what extent can the low-rank NFK embedding preserve the information in full Fisher vector? **Q4**. Does the NFK embedding representation lead

Table 1: CIFAR-10 accuracies of linear evaluation on top of representations learned with unsupervised and self-supervised methods. NFK-128d denotes the 128 dimensional embeddings from the low-rank approximation of the NFK (ie AFV). Remarkably, we can use 128 dimensions to exactly recover the performance of the 5.9M dimensional Fisher Vectors.

Model	Acc	Category	#Features
Examplar CNN (Dosovitskiy et al., 2015)	84.3	Unsupervised	-
BiGAN (Mu et al., 2020)	70.5	Unsupervised	-
RotNet Linear (Gidaris et al., 2018)	81.8	Self-Supervised	$\sim 25K$
AET Linear (Zhang et al., 2019)	83.3	Self-Supervised	$\sim 25K$
VAE(Mu et al., 2020)	61.5	Unsupervised	-
VAE-NFK-128d (ours)	63.2	Unsupervised	**128**
VAE-NFK-256d (ours)	68.7	Unsupervised	**256**
GAN-Supervised	92.7	Supervised	-
GAN-Activations	65.3	Unsupervised	-
GAN-AFV (Zhai et al., 2019)	89.1	Unsupervised	5.9M
GAN-AFV (re-implementation) (Zhai et al., 2019)	89.8	Unsupervised	5.9M
GAN-NFK-128d (ours)	**89.8**	Unsupervised	**128**
GAN-NFK-256d (ours)	**89.8**	Unsupervised	**256**

to better generalization performance in terms of better sample efficiency and faster adaptation? We conduct comparative studies on different tasks to understand the NFK embedding and present empirical observations to answer these questions in following sections.

NFK Representations from Unsupervised Generative Models In order to examine the effectiveness of the low-rank NFK embeddings as data representations in unsupervised learning setting, we consider GANs and VAEs as representative generative models and compute the low-rank NFK embeddings. Then we adopt the linear probing protocol by training a linear classifier on top of the obtained embeddings and report the classification performance to quantify the quality of NFK data representation. For GANs, we use the same pretrained GAN model from (Zhai et al., 2019) and reimplemented the AFV baseline. For VAEs, we follow the same model architecture proposed in (Child, 2020). We then apply the proposed truncated SVD algorithm with 10 power iterations to obtain the 256 dimensional embedding via projection. We present our results on CIFAR-10 (Krizhevsky et al., 2009a) in Table. 1. We use `GAN-NFK-128d` (`GAN-NFK-256d`) to denote the NFK embedding obtained from using top-128 (top-256) eigenvectors in our GAN model. Our VAE models (`VAE-NFK-128d` and `VAE-NFK-256d`) follow the same notations. For VAE baselines, the method proposed in (Mu et al., 2020) combines both gradients features and activations-based features into one linear model, denoted as `VAE` in the table. For GAN baselines, we first consider using intermediate layer activations only as data representation, referred to as the `GAN-Activations` model. We then consider using full Fisher vector as representation, namely using the normalized gradients w.r.t all model parameters as features, denoted as the `GAN-AFV` model as proposed in (Zhai et al., 2019). Moreover, we also compare our results against training whole neural network using data labels in a supervised learning way, denoted as `GAN-Supervised` model.

As shown in Table. 1, by contrasting against the baseline `GAN-AFV` from `GAN-Activations`, as well as validation in recent works (Zhai et al., 2019; Mu et al., 2020), gradients provide additional useful information beyond layer activations based features. However, it would be impractical to use all gradients or full Fisher vector as representation when scaling up to large-scale neural network models. For example, VAE (Child, 2020) has $\sim 40M$ parameters, it would not be possible to apply the baseline methods directly. Our proposed low-rank NFK embedding approach addressed this challenge by building low-dim vector representation from efficient kernel approximation algorithm, making it possible to utilize all model parameters' gradients information by embedding it into a low-dim vector, e.g. 256-dimensional embedding in `VAE-NFK-256d` from $\sim 40M$ parameters. As our low-rank NFK embedding is obtained by linear projections of full Fisher vectors, it naturally provides answers for **Q2** that the NFK embedding can be viewed as a compact yet informative representation containing information from all gradients. We see from Table. 1 that by using top-128 eigenvectors, the low-rank NFK embedding is able to recover the performance of full $\sim 5.9M$-dimension Fisher vector, which provides positive evidence for **Q3** that we can preserve most of the useful information in Fisher vector by taking the advantage of the low-rank structure of NFK spectrum.

Table 2: Error rates of few shot classification on CIFAR10 and SVHN, varying labels from 500 to 4000. NFK-128d yields extremely competitive performance, compared to other more sophisticated baselines, Mixup (Zhang et al., 2018), VAT (Miyato et al., 2019), MeanTeacher(Tarvainen and Valpola, 2017), MixMatch (Berthelot et al., 2019), Improved GAN(Salimans et al., 2016), all are jointly learns with labels, . Also note that the architecture used by MixMatch yields a 4.13% supervised learning error rate, which is a much stronger than our supervised baseline (7.3%).

Model	Category	CIFAR-10				SVHN			
		500	1000	2000	4000	500	1000	2000	4000
Mixup	Joint	36.17	25.72	18.14	13.15	29.62	16.79	10.47	7.96
VAT	Joint	26.11	18.68	14.40	11.05	7.44	5.98	4.85	4.20
MeanTeacher	Joint	47.32	42.01	17.32	12.17	6.45	3.82	3.75	3.51
MixMatch	Joint	9.65	7.75	7.03	6.24	3.64	3.27	3.04	2.89
Improved GAN	Joint	-	19.22	17.25	15.59	18.44	8.11	6.16	-
NFK-128d (ours)	Pretrained	20.68	14.77	13.82	12.95	8.74	4.47	3.82	3.19

Table 3: Supervised knowledge distillation results on CIFAR10 against baseline methods KD (Hinton et al., 2015), FitNet (Romero et al., 2014), AT (Zagoruyko and Komodakis, 2017), NST (Huang and Wang, 2017), VID-I (Ahn et al., 2019), numbers are from (Ahn et al., 2019).

	Teacher	Student	KD	FitNet	AT	NST	VID-I	NFKD (ours)
ACC	94.26	90.72	91.27	90.64	91.60	91.16	91.85	**92.42**

NFK Representations for Semi-Supervised Learning We then test the low-rank NFK embeddings in the semi-supervised learning setting. Following the standard semi-supervised learning benchmark settings (Berthelot et al., 2019; Miyato et al., 2019; Laine and Aila, 2017; Sajjadi et al., 2016; Tarvainen and Valpola, 2017), we evaluate our method on CIFAR-10 (Krizhevsky et al., 2009a) and SVHN datasets (Krizhevsky et al., 2009b). We treat most of the dataset as unlabeled data and use few examples as labeled data. We use the same GAN model as the unsupervised learning setting above, and compute top-128 eigenvectors using training dataset (labeled and unlabeled) to derive the 128-dimensional NFK embedding. Then we only use the labeled data to train a linear classifier on top of the NFK embedding features, denoted as the `NFK-128d` model. We vary the number of labeled training examples and report the results in Table. 2, in comparison with other baseline methods. We see that `NFK-128d` achieves very competitive performance. On CIFAR-10, `NFK-128d` is only outperformed by the state-of-the-art semi-supervised learning algorithm MixMatch (Berthelot et al., 2019), which also uses a stronger architecture than ours. The results on SVHN are mixed though `NFK-128d` is competitive with the top performing approaches. The results demonstrated the effectiveness of NFK embeddings from unsupervised generative models in semi-supervised learning, showing promising sample efficiency for **Q4**.

NFK Representations for Knowledge Distillation We next test the effectiveness of using low-rank NFK embedding for knowledge distillation in the supervised learning setting. We include more details of the distillation method in the Appendix. Our experiments are conducted on CIFAR10, with a teacher set as the `WRN-40-2` model and student being *WRN-16-1*. After training the teacher, we compute the low-rank approximation of NFK of the teacher model, using top-20 eigenvectors. We include more details about the distillation method setup in the Appendix. Our results are reported in Table. 3. We see that our method achieves superior results compared to other competitive baseline knowledge distillation methods, which mainly use the logits and activations from teacher network as distillation target.

5 CONCLUSIONS

We have proposed to use Neural Fisher Kernel as a way of representation extraction for deep neural networks, in both the unsupervised and supervised learning settings. We impose a low-rank hypothesis on the structure of practical NFKs, and provide empirical verification of it. We further propose an efficient GPU friendly algorithm to identify the low-rank approximation of an NFK in linear time w.r.t. number of examples and the desired rank. Experimentally, we show strong performance on linear classification, semi-supervised learning, and distillation tasks, outperforming competitive baselines.

REFERENCES

Tommi S Jaakkola, David Haussler, et al. Exploiting generative models in discriminative classifiers.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Geoffrey E. Hinton, Oriol Vinyals, and Jeffrey Dean. Distilling the knowledge in a neural network. *CoRR*, abs/1503.02531, 2015. URL http://arxiv.org/abs/1503.02531.

Ian J Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks. *arXiv preprint arXiv:1406.2661*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Mark Chen, Alec Radford, Rewon Child, Jeffrey Wu, Heewoo Jun, David Luan, and Ilya Sutskever. Generative pretraining from pixels. In *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, volume 119 of *Proceedings of Machine Learning Research*, pages 1691–1703. PMLR, 2020a. URL http://proceedings.mlr.press/v119/chen20s.html.

Fangzhou Mu, Yingyu Liang, and Yin Li. Gradients as features for deep representation learning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=BkeoaeHKDS.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *arXiv preprint arXiv:1806.07572*, 2018.

Thomas Hofmann, Bernhard Schölkopf, and Alexander J Smola. Kernel methods in machine learning. *The annals of statistics*, pages 1171–1220, 2008.

Radford M Neal. Priors for infinite networks. In *Bayesian Learning for Neural Networks*, pages 29–53. Springer, 1996.

Christopher K. I. Williams. Computing with infinite networks. In Michael Mozer, Michael I. Jordan, and Thomas Petsche, editors, *Advances in Neural Information Processing Systems 9, NIPS, Denver, CO, USA, December 2-5, 1996*, pages 295–301. MIT Press, 1996. URL http://papers.nips.cc/paper/1197-computing-with-infinite-networks.

Nicolas Le Roux and Yoshua Bengio. Continuous neural networks. In Marina Meila and Xiaotong Shen, editors, *Proceedings of the Eleventh International Conference on Artificial Intelligence and Statistics, AISTATS 2007, San Juan, Puerto Rico, March 21-24, 2007*, volume 2 of *JMLR Proceedings*, pages 404–411. JMLR.org, 2007. URL http://proceedings.mlr.press/v2/leroux07a.html.

Tamir Hazan and Tommi S. Jaakkola. Steps toward deep kernel methods from infinite neural networks. *CoRR*, abs/1508.05133, 2015. URL http://arxiv.org/abs/1508.05133.

Jaehoon Lee, Yasaman Bahri, Roman Novak, Samuel S. Schoenholz, Jeffrey Pennington, and Jascha Sohl-Dickstein. Deep neural networks as gaussian processes. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=B1EA-M-0Z.

Alexander G. de G. Matthews, Jiri Hron, Mark Rowland, Richard E. Turner, and Zoubin Ghahramani. Gaussian process behaviour in wide deep neural networks. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=H1-nGgWC-.

Amit Daniely, Roy Frostig, and Yoram Singer. Toward deeper understanding of neural networks: The power of initialization and a dual view on expressivity. In Daniel D. Lee, Masashi Sugiyama, Ulrike von Luxburg, Isabelle Guyon, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pages 2253–2261, 2016. URL https://proceedings.neurips.cc/paper/2016/hash/abea47ba24142ed16b7d8fbf2c740e0d-Abstract.html.

Florent Perronnin and Christopher R. Dance. Fisher kernels on visual vocabularies for image categorization. In *2007 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR 2007), 18-23 June 2007, Minneapolis, Minnesota, USA*. IEEE Computer Society, 2007. doi: 10.1109/CVPR.2007.383266. URL https://doi.org/10.1109/CVPR.2007.383266.

Alessandro Achille, Michael Lam, Rahul Tewari, Avinash Ravichandran, Subhransu Maji, Charless C. Fowlkes, Stefano Soatto, and Pietro Perona. Task2vec: Task embedding for meta-learning. In *2019 IEEE/CVF International Conference on Computer Vision, ICCV 2019, Seoul, Korea (South), October 27 - November 2, 2019*, pages 6429–6438. IEEE, 2019. doi: 10.1109/ICCV.2019.00653. URL https://doi.org/10.1109/ICCV.2019.00653.

Zihang Dai, Amjad Almahairi, Philip Bachman, Eduard Hovy, and Aaron Courville. Calibrating energy-based generative adversarial networks. *arXiv preprint arXiv:1702.01691*, 2017.

Shuangfei Zhai, Walter Talbott, Carlos Guestrin, and Joshua M. Susskind. Adversarial fisher vectors for unsupervised representation learning. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 11156–11166, 2019. URL https://proceedings.neurips.cc/paper/2019/hash/7e1cacfb27da22fb243ff2debf4443a0-Abstract.html.

Tong Che, Ruixiang Zhang, Jascha Sohl-Dickstein, Hugo Larochelle, Liam Paull, Yuan Cao, and Yoshua Bengio. Your GAN is secretly an energy-based model and you should use discriminator driven latent sampling. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/90525e70b7842930586545c6f1c9310c-Abstract.html.

Yuri Burda, Roger B. Grosse, and Ruslan Salakhutdinov. Importance weighted autoencoders. In Yoshua Bengio and Yann LeCun, editors, *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016. URL http://arxiv.org/abs/1509.00519.

Will Grathwohl, Kuan-Chieh Wang, Jörn-Henrik Jacobsen, David Duvenaud, Mohammad Norouzi, and Kevin Swersky. Your classifier is secretly an energy based model and you should treat it like one. *arXiv preprint arXiv:1912.03263*, 2019.

Sam T Roweis and Lawrence K Saul. Nonlinear dimensionality reduction by locally linear embedding. *science*, 290(5500):2323–2326, 2000.

Salah Rifai, Pascal Vincent, Xavier Muller, Xavier Glorot, and Yoshua Bengio. Contractive auto-encoders: Explicit invariance during feature extraction. In *Icml*, 2011a.

Salah Rifai, Yann N Dauphin, Pascal Vincent, Yoshua Bengio, and Xavier Muller. The manifold tangent classifier. *Advances in neural information processing systems*, 24:2294–2302, 2011b.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. *arXiv preprint arXiv:1511.06434*, 2015.

J Mercer. Functions ofpositive and negativetypeand theircommection with the theory ofintegral equations. *Philos. Trinsdictions Rogyal Soc*, 209:4–415, 1909.

Christopher K. I. Williams and Matthias W. Seeger. Using the nyström method to speed up kernel machines. In Todd K. Leen, Thomas G. Dietterich, and Volker Tresp, editors, *Advances in Neural Information Processing Systems 13, Papers from Neural Information Processing Systems (NIPS) 2000, Denver, CO, USA*, pages 682–688. MIT Press, 2000. URL https://proceedings.neurips.cc/paper/2000/hash/19de10adbaa1b2ee13f77f679fa1483a-Abstract.html.

Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In John C. Platt, Daphne Koller, Yoram Singer, and Sam T. Roweis, editors, *Advances in Neural Information Processing Systems 20, Proceedings of the Twenty-First Annual Conference on Neural Information Processing Systems, Vancouver, British Columbia, Canada, December 3-6, 2007*, pages 1177–1184. Curran Associates, Inc., 2007. URL https://proceedings.neurips.cc/paper/2007/hash/013a006f03dbc5392effeb8f18fda755-Abstract.html.

Nathan Halko, Per-Gunnar Martinsson, and Joel A. Tropp. Finding structure with randomness: Probabilistic algorithms for constructing approximate matrix decompositions. *SIAM Rev.*, 53(2): 217–288, 2011. doi: 10.1137/090771806. URL https://doi.org/10.1137/090771806.

Gene H Golub and Henk A Van der Vorst. Eigenvalue computation in the 20th century. *Journal of Computational and Applied Mathematics*, 123(1-2):35–65, 2000.

Klaus-Jürgen Bathe. *Solution methods for large generalized eigenvalue problems in structural engineering*. National Technical Information Service, US Department of Commerce, 1971.

James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL http://github.com/google/jax.

Roman Novak, Lechao Xiao, Jiri Hron, Jaehoon Lee, Alexander A Alemi, Jascha Sohl-Dickstein, and Samuel S Schoenholz. Neural tangents: Fast and easy infinite neural networks in python. *arXiv preprint arXiv:1912.02803*, 2019.

Per-Gunnar Martinsson and Joel A. Tropp. Randomized numerical linear algebra: Foundations and algorithms. *Acta Numer.*, 29:403–572, 2020. doi: 10.1017/S0962492920000021. URL https://doi.org/10.1017/S0962492920000021.

Alexey Dosovitskiy, Philipp Fischer, Jost Tobias Springenberg, Martin Riedmiller, and Thomas Brox. Discriminative unsupervised feature learning with exemplar convolutional neural networks. *IEEE transactions on pattern analysis and machine intelligence*, 38(9):1734–1747, 2015.

Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations. *arXiv preprint arXiv:1803.07728*, 2018.

Liheng Zhang, Guo-Jun Qi, Liqiang Wang, and Jiebo Luo. Aet vs. aed: Unsupervised representation learning by auto-encoding transformations rather than data. *arXiv preprint arXiv:1901.04596*, 2019.

Rewon Child. Very deep vaes generalize autoregressive models and can outperform them on images. *CoRR*, abs/2011.10650, 2020. URL https://arxiv.org/abs/2011.10650.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009a.

Hongyi Zhang, Moustapha Cissé, Yann N. Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*. OpenReview.net, 2018. URL https://openreview.net/forum?id=r1Ddp1-Rb.

Takeru Miyato, Shin-ichi Maeda, Masanori Koyama, and Shin Ishii. Virtual adversarial training: A regularization method for supervised and semi-supervised learning. *IEEE Trans. Pattern Anal. Mach. Intell.*, 41(8):1979–1993, 2019. doi: 10.1109/TPAMI.2018.2858821. URL `https://doi.org/10.1109/TPAMI.2018.2858821`.

Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 1195–1204, 2017. URL `https://proceedings.neurips.cc/paper/2017/hash/68053af2923e00204c3ca7c6a3150cf7-Abstract.html`.

David Berthelot, Nicholas Carlini, Ian Goodfellow, Nicolas Papernot, Avital Oliver, and Colin Raffel. Mixmatch: A holistic approach to semi-supervised learning. *arXiv preprint arXiv:1905.02249*, 2019.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *arXiv preprint arXiv:1606.03498*, 2016.

Samuli Laine and Timo Aila. Temporal ensembling for semi-supervised learning. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL `https://openreview.net/forum?id=BJ6oOfqge`.

Mehdi Sajjadi, Mehran Javanmardi, and Tolga Tasdizen. Regularization with stochastic transformations and perturbations for deep semi-supervised learning. In Daniel D. Lee, Masashi Sugiyama, Ulrike von Luxburg, Isabelle Guyon, and Roman Garnett, editors, *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pages 1163–1171, 2016. URL `https://proceedings.neurips.cc/paper/2016/hash/30ef30b64204a3088a26bc2e6ecf7602-Abstract.html`.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009b.

Adriana Romero, Nicolas Ballas, Samira Ebrahimi Kahou, Antoine Chassang, Carlo Gatta, and Yoshua Bengio. Fitnets: Hints for thin deep nets. *arXiv preprint arXiv:1412.6550*, 2014.

Sergey Zagoruyko and Nikos Komodakis. Paying more attention to attention: Improving the performance of convolutional neural networks via attention transfer. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL `https://openreview.net/forum?id=Sks9_ajex`.

Zehao Huang and Naiyan Wang. Like what you like: Knowledge distill via neuron selectivity transfer. *CoRR*, abs/1707.01219, 2017. URL `http://arxiv.org/abs/1707.01219`.

Sungsoo Ahn, Shell Xu Hu, Andreas Damianou, Neil D Lawrence, and Zhenwen Dai. Variational information distillation for knowledge transfer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9163–9171, 2019.

A. Baratin, Thomas George, César Laurent, R. Devon Hjelm, G. Lajoie, Pascal Vincent, and S. Lacoste-Julien. Implicit regularization via neural feature alignment. *arXiv: Learning*, 2020.

Vardan Papyan. Traces of class/cross-class structure pervade deep learning spectra. *Journal of Machine Learning Research*, 21(252):1–64, 2020.

Abdulkadir Canatar, Blake Bordelon, and Cengiz Pehlevan. Spectral bias and task-model alignment explain generalization in kernel regression and infinitely wide neural networks, 2020.

Pascal Vincent, Hugo Larochelle, Isabelle Lajoie, Yoshua Bengio, Pierre-Antoine Manzagol, and Léon Bottou. Stacked denoising autoencoders: Learning useful representations in a deep network with a local denoising criterion. *Journal of machine learning research*, 11(12), 2010.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020b.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9729–9738, 2020.

R Devon Hjelm, Alex Fedorov, Samuel Lavoie-Marchildon, Karan Grewal, Phil Bachman, Adam Trischler, and Yoshua Bengio. Learning deep representations by mutual information estimation and maximization. *arXiv preprint arXiv:1808.06670*, 2018.

Longlong Jing and Yingli Tian. Self-supervised visual feature learning with deep neural networks: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.

Lei Jimmy Ba and Rich Caruana. Do deep nets really need to be deep? *arXiv preprint arXiv:1312.6184*, 2013.

Frederick Tung and Greg Mori. Similarity-preserving knowledge distillation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1365–1374, 2019.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive representation distillation. *arXiv preprint arXiv:1910.10699*, 2019.

Shun-Ichi Amari. Natural gradient works efficiently in learning. *Neural computation*, 10(2):251–276, 1998.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

A EXTENDED PRELIMINARIES

We extend Sec. 2 to introduce additional technical background and related work.

Kernel methods in Deep Learning. Popularized by the NTK work Jacot et al. (2018), there has been great interests in the deep learning community around the kernel view of neural networks. In particular, several works have studied the low-rank structure of the NTK, including (Baratin et al., 2020; Papyan, 2020; Canatar et al., 2020), which demonstrate that empirical NTK demonstrates low-rankness and that encourages better generalization theoretically. Our low-rank analysis of NFK shares a similar flavor, but generalizes across supervised and unsupervised learning settings. Besides, we make an explicit effort in proposing an efficient implementation of the low-rank approximation, and demonstrate strong empirical performances.

Unsupervised/self supervised representation learning. Unsupervised representation learning is an old idea in deep learning. A large body of work is dedicated to designing better learning objectives (self supervised learning), including denoising (Vincent et al., 2010), contrastive learning (Oord et al., 2018; Chen et al., 2020b; He et al., 2020), mutual information maximization (Hjelm et al., 2018) and other "pretext tasks" Jing and Tian (2020). Our attempt falls into the same category of unsupervised representation learning, but differs in that we instead focus on effectively extracting information from a standard probabilistic model. This makes our effort orthogonal to many of the related works, and can be easily plugged into different family of models.

Knowledge Distillation. Knowledge distillation (KD) is generally concerned about the problem of supervising a student model with a teacher model (Hinton et al., 2015; Ba and Caruana, 2013). The general form of KD is to directly match the statistics of one or a few layers (default is the logits). Various works have studied the layer selection (Romero et al., 2014) or loss function design aspects (Ahn et al., 2019). More closely related to our work is efforts that consider the second order statistics between examples, including (Tung and Mori, 2019; Tian et al., 2019). NFKD differs in that we represent the teacher's knowledge in the kernel space, which is directly tied to the kernel interpretation of neural networks which introduces different inductive biases than layerwise representations.

Neural Tangent Kernel Recent advancements in the understanding of neural networks have shed light on the connection between neural network training and kernel methods. In (Jacot et al., 2018), it is shown that one can use the Neural Tangent Kernel (NTK) to characterize the full training of a neural network using a kernel. Let $f(\boldsymbol{\theta}; \mathbf{x})$ denote a neural network function with parameters $\boldsymbol{\theta}$. The NTK is defined as follows:

$$\mathcal{K}_{\mathrm{ntk}}(\mathbf{x}, \mathbf{z}) = \mathbb{E}_{\theta \sim \mathcal{P}_{\boldsymbol{\theta}}} \langle \nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta}; \mathbf{x}), \nabla_{\boldsymbol{\theta}} f(\boldsymbol{\theta}; \mathbf{z}) \rangle . \tag{7}$$

where $\mathcal{P}_{\boldsymbol{\theta}}$ is the probability distribution of the initialization of $\boldsymbol{\theta}$. (Jacot et al., 2018) further demonstrates that in the large width regime, a neural network undergoing training under gradient descent essentially evolves as a linear model. Let $\boldsymbol{\theta}_0$ denote the parameter values at initialization. To determine how the function $f_t(\boldsymbol{\theta}_t; \mathbf{x})$ evolves, we may naively taylor expand the output around $\boldsymbol{\theta}_0$: $f_{t+1}(\boldsymbol{\theta}_{t+1}; \mathbf{x}) \approx f_t(\boldsymbol{\theta}_t; \mathbf{x}) - \eta \nabla_{\boldsymbol{\theta}_t} f_t(\boldsymbol{\theta}_t; \mathbf{x})^\top (\boldsymbol{\theta}_{t+1} - \boldsymbol{\theta}_t)$. As the weight updates are given by $\boldsymbol{\theta}_{t-1} - \boldsymbol{\theta}_t = -\frac{1}{N} \eta \sum_{i=1}^m \nabla_{\boldsymbol{\theta}_t} \mathcal{L}_t(x_i)$, hence we have $f_{t+1}(\boldsymbol{\theta}_{t+1}; \mathbf{x}) \approx f_t(\boldsymbol{\theta}_t; \mathbf{x}) - \eta \frac{1}{N} \sum_{i=1}^N \mathcal{K}_{\mathrm{ntk}}(\mathbf{x}, \mathbf{x}_i) \nabla_f \mathcal{L}_t(\mathbf{x}_i)$. The significance of the NTK stems from two observations. 1) When suitably initialized, the NTK converges to a limit kernel when the width tends to infinity $\lim_{\mathrm{width} \to \infty} \mathcal{K}_{\mathrm{ntk}}(\mathbf{x}, \mathbf{z}; \boldsymbol{\theta}_0) = \mathring{\mathcal{K}}_{\mathrm{ntk}}(\mathbf{x}, \mathbf{z})$. 2) In that limit, the NTK remains frozen in its limit state throughout training.

B ON THE CONNECTIONS BETWEEN NFK AND NTK

In Sec 3.1, we showed that our definition of NFK in the supervised learning setting bares great similarity to the NTK. We provide more discussion here on the connections between NFK and NTK.

For the L2 regression loss function, the empirical fisher information reduces to $\mathcal{I} = \frac{1}{N} \sum_{i=1}^N \nabla_{\boldsymbol{\theta}} f_{\boldsymbol{\theta}}(\mathbf{x}) \nabla_{\boldsymbol{\theta}} f_{\boldsymbol{\theta}}(\mathbf{x})^\top$. Note that the fisher information matrix $\mathcal{I}$ is give by a covariance matrix of J, while the NTK matrix is defined as the Gram matrix of J, where J is the Jacobian matrix, implying they share the same spectrum, and that the NTK and the NFK share the same eigenvectors. The addition of $\mathcal{I}^{-1}$ in the definition of $\mathcal{K}_{nfk}$ can be seen as a form of conditioning, facilitating fast convergence in all directions spanned by J.

Equation 4 also has immediate connections to NTK. In NTK, the kernel $\mathbf{K}_{\mathrm{ntk}}(\mathbf{x}, \bar{\mathbf{x}}) \in \mathbb{R}^{N \times N}$ is a matrix which measures the dot product of Jacobian for every pair of logits. The NFK, on the other hand, reduces the Jacobian $\nabla_{\boldsymbol{\theta}} f_{\boldsymbol{\theta}}(\mathbf{x})$ for each example $\mathbf{x}$ to a single vector of dimension n (i.e., size of $\boldsymbol{\theta}$), weighted by the predicted probability of each class $p_{\boldsymbol{\theta}}(\mathbf{y}|\mathbf{x})$. The other notable difference between NFK and NTK is the subtractive and normalize factors, represented by $\mathbb{E}_{\mathbf{x}' \sim p_{\boldsymbol{\theta}}(\mathbf{x}')} \sum_{\mathbf{y}} p_{\boldsymbol{\theta}}(\mathbf{y}|\mathbf{x}) \nabla_{\boldsymbol{\theta}} f_{\boldsymbol{\theta}}^{\mathbf{y}}(\mathbf{x}')$ and $\mathcal{I}$, respectively. This distinction is related to the difference between Natural Gradient Descent (Amari, 1998) and gradient descent. In a nutshell, our definition of NFK in the supervised learning setting can be considered as a reduced version of NTK, with proper normalization. These properties make NFK much more scalable w.r.t. the number of classes, and also less sensitive to the scale of model's parameters.

To better see this, we can define an "unnormalized" version of NFK as $\mathcal{K}_u(\mathbf{x}, \bar{\mathbf{x}}) = [\sum_{\mathbf{y}} p_{\boldsymbol{\theta}}(\mathbf{y} | \mathbf{x}) \nabla_{\boldsymbol{\theta}} f_{\boldsymbol{\theta}}^{\mathbf{y}}(\mathbf{x})]^{\top} \sum_{\mathbf{y}} p_{\boldsymbol{\theta}}(\mathbf{y} | \bar{\mathbf{x}}) \nabla_{\boldsymbol{\theta}} f_{\boldsymbol{\theta}}^{\mathbf{y}}(\bar{\mathbf{x}})$. It is easy to see that $\mathcal{K}_u$ has the same rank as the original NFK $\mathcal{K}$, as $\mathcal{I}^{-1}$ is full rank by definition. We can then further rewrite it as

$$\mathcal{K}_u(\mathbf{x}, \bar{\mathbf{x}}) = \sum_{\mathbf{y}} \sum_{\bar{\mathbf{y}}} p_{\boldsymbol{\theta}}(\mathbf{y} | \mathbf{x}) p_{\boldsymbol{\theta}}(\bar{\mathbf{y}}|\bar{\mathbf{x}}) \nabla_{\boldsymbol{\theta}} f_{\boldsymbol{\theta}}^{\mathbf{y}}(\mathbf{x})^{\top} \nabla_{\boldsymbol{\theta}} f_{\boldsymbol{\theta}}^{\bar{\mathbf{y}}}(\bar{\mathbf{x}}) = \sum_{\mathbf{y}} \sum_{\bar{\mathbf{y}}} p_{\boldsymbol{\theta}}(\mathbf{y} | \mathbf{x}) p_{\boldsymbol{\theta}}(\bar{\mathbf{y}} | \bar{\mathbf{x}}) \mathcal{K}_{\mathrm{ntk}}^{\mathbf{y}, \bar{\mathbf{y}}}(\mathbf{x}, \bar{\mathbf{x}})$$

(8)

In words, the unnormalized version of NFK can be considered as a reduction of NTK, where the weights of each element is weighte by the predicted probability for the respective class. If we further assume that the model of interest is well trained, as is often the case in knowledge distillation, we can approximate the $\mathcal{K}_u$ as $\mathcal{K}_{\mathrm{ntk}}^{\mathbf{y}^*, \bar{\mathbf{y}}^*}(\mathbf{x}, \bar{\mathbf{x}})$, where $\mathbf{y}^* = \arg\max_{\mathbf{y}} p_{\boldsymbol{\theta}}(\mathbf{y} | \mathbf{x})$ and likewise for $\bar{\mathbf{y}}^*$. This suggests that the unnormalized NFK can roughly viewd as a downsampled version of NTK. As a result, we expect the unnormalized NFK (and hence the NFK) to exhibit similar low rank properties as demonstrated in the NTK literature.

On the low-rank structure of NTK Consider the NTK Gram matrix $\mathbf{K}_{\mathrm{ntk}} \in \mathbb{R}^{N \times N}$ of some network Given the dataset $\{\mathbf{x}_i\}_{i=1}^N$ (for simplicity we assume a scalar output) and its eigen decomposition $\mathbf{K}_{ntk} = \sum_{j=1}^m \lambda_j \mathbf{u}_j \mathbf{u}_j^{\top}$. Let $f \in \mathbb{R}^N$ denote the concatenated outputs. Under GD in the linear regime, the outputs f_t evolves according to:

$$\forall_j, \quad \mathbf{u}_j^{\top}(f_{t+1} - f_t) \approx -\eta \lambda_j \mathbf{u}_j^{\top} \nabla_f \mathcal{L}.$$

(9)

The updates $f_{t+1} - f_t$ projected onto the bases of the kernel therefore converge at different speeds, determined by the eigenvalues $\{\lambda_j\}$. Intuitively, a good kernel-data alignment means that the $\nabla_f \mathcal{L}$ is spanned by a few eigenvectors with large corresponding eigenvalues, speeding up convergence and promoting generalization.

C EFFICIENT LOW-RANK NFK/NTK APPROXIMATION VIA TRUNCATED SVD

We provide mode details on experimental observations on the low-rank structure of NFK and the low-rank kernel approximation algorithm here.

Low-Rank Structure of NFK For supervised learning models, we trained a LeNet-5 (LeCun et al., 1998) CNN and a 3-layer MLP network by minimizing binary cross entropy loss, and then compute the eigen-decomposition of the NFK Gram matrix. For unsupervised learning models, we trained a small unconditional DCGAN (Radford et al., 2015) model on MNIST dataset. We deliberately selected a small discriminator, which consists of 17K parameters. Because of the relatively low-dimensionality of $\boldsymbol{\theta}$ in the discriminator, we were able to directly compute the Fisher Vectors for a random subset of the training dataset. We then performed standard SVD on the gathered Fisher Vector matrix, and examined the spectrum statistics. In particular, we plot the explained variance ration quantity, defined as $r_k = \frac{\sum_{i=1}^k \lambda_i^2}{\sum_{i=1} \lambda_i^2}$ where λ_i is the i-th singular value. In addition, we have also visualized the top 5 principle components, by showing example images which have the largest projections on each component in Fig. 5.

Furthermore, we conducted a GAN inversion experiment. We sampled a batch of generated examples, and learned a linear mapping from their low dimensional SVD embeddings (dim=100) to their respective latent codes ($\mathbf{z}$). In doing so, we have constructed an implicit auto encoder from a regular GAN. The reconstructions are shown in Figure 3. Interestingly, the 100d SVD embedding gives

rise to a qualitatively faithful reconstruction on real images. This is a good indication that the 100d embedding captures most of the information about an input example.

Figure 3: Left: test images. Right: inverted images with 100d NFK SVD embeddings derived from a DCGAN.

Figure 4: The low-rankness of the NFK on a DCGAN trained on MNIST. For a trained model, the first 100 principle components of the Fisher Vector matrix explains 99.5% of all variances. An untrained model with the same architecture on the other hand, demonstrates a much lower degree of low-rankness.

Figure 5: Images with the largest projections on the first five principle components. Each row corresponds to a principle component.

Power iteration of NTK as JVP/VJP evaluations Our proposed algorithm is based on the Power method Golub and Van der Vorst (2000); Bathe (1971) for finding the leading top eigenvectors of the real symmetric matrix. Starting from a random vector $\mathbf{v}_0$ drawn from a rotationally invariant

Figure 6: Linear probing accuracy on CIFAR10 with different number of principle components in embedding. We use our proposed low-rank approximation method to compute the embedding from the teacher model on CIFAR10 for knowledge distillation.

Algorithm 3 Our proposed method: compute low-rank NFK feature embedding

---

1: $\mathbf{V} = \boldsymbol{\Phi}\mathrm{diag}(\Sigma)\mathbf{P}^\top, \mathbf{P} \in \mathbb{R}^{|\boldsymbol{\theta}|\times k}$ via `truncated_svd(`$\mathbf{X}$`, ` $f_{\boldsymbol{\theta}}$`, topk=`K`,`
   `kernel_type="NFK")`
2:
3: compute $\mathcal{K}\left(\mathbf{x}, \mathbf{X}\right)^\top \boldsymbol{\Phi}_i \approx V_{\mathbf{x}}\mathrm{diag}(\Sigma_i)\mathbf{P}_i$ via JVP evaluation
4: obtain $\mathbf{e}_{\mathrm{nfk}}(\mathbf{x}^*) \in \mathbb{R}^k$ via Eq. 6 and Eq. 5

---

distribution and normalize it to unit norm $\|\mathbf{v}_0\| = 1$, the power method iteratively constructs the sequence $\mathbf{v}_{t+1} = \frac{\mathbf{K}\mathbf{v}_t}{\|\mathbf{K}\mathbf{v}_t\|}$ up to q power iterations. Given the special structure of $\mathbf{K}$ that it's a Gram matrix of the Jacobian matrix $J_{\boldsymbol{\theta}}(\mathbf{X}) \in \mathbb{R}^{D\times N}$, to evaluate $\mathbf{K}\mathbf{v}_t$ in each power iteration step we need to evaluate $J_{\boldsymbol{\theta}}(\mathbf{X})^\top J_{\boldsymbol{\theta}}(\mathbf{X})\mathbf{v}_t$, which can be decomposed as: (i) evaluating $\mathbf{z}_t = J_{\boldsymbol{\theta}}(\mathbf{X})\mathbf{v}_t$, and then (ii) $\mathbf{K}\mathbf{v}_t = J_{\boldsymbol{\theta}}(\mathbf{X})^\top \mathbf{z}_t$. Note that when $\mathbf{K}$ is in the form of NTK of neural networks, step (i) of evaluating $\mathbf{z}_t$ is a Vector-Jacobian-Product (VJP) and step (ii) is a Jacobian-Vector-Product (JVP). With the help of automatic-differentiation techniques, we can evaluate both JVP and VJP efficiently, which only requires the same order of computational costs of one backward-pass and forward-pass of neural networks respectively. In this way, we can reduce the Kernel matrix vector product operation in each power iteration step to one VJP evaluation and one JVP evaluation, without the need to computing and storing the Jacobian matrix and kernel matrix explicitly.

As introduced in Section. 3.2, we include detailed algorithm description here, from Algorithm. 3 to Algorithm. 6. In Algorithm. 3, we show the algorithm to compute the low-rank NFK embedding, which can be used as data representations. In Algorithm. 4, we present our proposed automatic-differentiation based truncated SVD algorithm for kernel approximation. Note that in Algorithm. 5 and 6, we only need to follow Equation. 4 to pre-compute the model distribution statistics, $\mathbf{Z}_{\boldsymbol{\theta}} = \mathbb{E}_{\mathbf{x}'\sim p_{\boldsymbol{\theta}}(\mathbf{x}')}\sum_{\mathbf{y}} p_{\boldsymbol{\theta}}(\mathbf{y}|\mathbf{x})\nabla_{\boldsymbol{\theta}} f_{\boldsymbol{\theta}}^{\mathbf{y}}(\mathbf{x}')$, and FIM $\mathcal{I} = \mathbb{E}_{\mathbf{x}'\sim p_{\boldsymbol{\theta}}(\mathbf{x}')}[U_{\mathbf{x}'}U_{\mathbf{x}'}^\top]$. We adopt the EBM formulation of classifier $f_\theta(\mathbf{x})$ then replace the Jacobian matrix $J_\theta(\mathbf{X})$ with the Fisher vector matrix $V_\theta(\mathbf{X}) = \mathrm{diag}(\mathcal{I})^{-\frac{1}{2}}(J_\theta(\mathbf{X}) - \mathbf{Z}_{\boldsymbol{\theta}})$.

D EXPERIMENTS SETUP

D.1 QUALITY AND EFFICIENCY OF LOW-RANK NFK APPROXIMATIONS

Experiments on Computational Cost We randomly sample $N \in \left\{2^k : 7 \le k \le 16\right\}$ data examples from CIFAR-10 dataset, and compute top-32 eigenvectors of the NFK Gram matrix ($\mathbb{R}^{N\times N}$) by truncated SVD. We use same number of power iterations (10) in baseline method and our algorithm. We show in Fig. 2 the running time of SVD for both methods in terms of number of data examples N.

Experiments on Approximation Accuracy We randomly sample 10000 examples and compute top-128 eigenvalues using both baseline methods and our proposed algorithm. Specifically, we

---

Algorithm 4 `truncated_svd`, Truncated SVD Algorithm for Low-rank Kernel Approximation. Comments are based on NTK for simplicity.

    Input Dataset $\mathbf{X} \equiv \{\mathbf{x}_i\}_{i=1}^N$
    Input Neural network model $f_{\boldsymbol{\theta}}$
    Input Kernel type `kernel`, NFK or NTK
    Input Low-rank embedding size K
    Input Number of power iterations $L = 10$
    Input Number of over samples $U = 10$
    Output Truncated SVD of Jacobian $J_{\theta}(\mathbf{X}) \approx \mathbf{P}_k \Sigma_k \mathbf{Q}_k^\top$
1: $U = K + U$ $\triangleright$ Size of augmented set of vectors in power iterations
2: Draw random matrix $\boldsymbol{\Omega} \in \mathbb{R}^{N \times U}$
3: $\boldsymbol{\Omega} = $`matrix_jacobian_product`$(f_{\boldsymbol{\theta}}, \mathbf{X}, \boldsymbol{\Omega}, $`kernel`$)$ $\triangleright \boldsymbol{\Omega} = J_{\boldsymbol{\theta}}(\mathbf{X})\boldsymbol{\Omega} \in \mathbb{R}^{M \times U}$
4: **for** step $= 1$ to L **do**
5:     $\boldsymbol{\Omega} = $`jacobian_matrix_product`$(f_{\boldsymbol{\theta}}, \mathbf{X}, \boldsymbol{\Omega}, $`kernel`$)$ $\triangleright \boldsymbol{\Omega} = J_{\boldsymbol{\theta}}^\top(\mathbf{X})\boldsymbol{\Omega} \in \mathbb{R}^{N \times U}$
6:     $\boldsymbol{\Omega} = $`matrix_jacobian_product`$(f_{\boldsymbol{\theta}}, \mathbf{X}, \boldsymbol{\Omega}, $`kernel`$)$ $\triangleright \boldsymbol{\Omega} = J_{\boldsymbol{\theta}}(\mathbf{X})\boldsymbol{\Omega} \in \mathbb{R}^{M \times U}$
7:     $\boldsymbol{\Omega} = $`qr_decomposition`$(\boldsymbol{\Omega})$
8: **end for**
9: $\mathbf{B} = $`jacobian_matrix_product`$(f_{\boldsymbol{\theta}}, \mathbf{X}, \boldsymbol{\Omega}, $`kernel`$)$ $\triangleright \mathbf{B} = J_{\boldsymbol{\theta}}^\top(\mathbf{X})\boldsymbol{\Omega} \in \mathbb{R}^{N \times U}$
10: $\mathbf{P}, \boldsymbol{\Sigma}, \mathbf{Q}^\top = $`svd`$(\mathbf{B}^\top)$
11: $\mathbf{P} = \boldsymbol{\Omega}\mathbf{P}$
12: Keep top rank-K vectors to obtain the truncated results $\mathbf{P}_k, \boldsymbol{\Sigma}_k, \mathbf{Q}_k^\top$
13: Return $\mathbf{P}_k, \boldsymbol{\Sigma}_k, \mathbf{Q}_k^\top$

Algorithm 5 `jacobian_matrix_product`

    Input Neural network model $f_{\boldsymbol{\theta}}$
    Input Input data $\mathbf{X} \in \mathbb{R}^{B \times D}$, where B is batch size
    Input Input matrix $\mathbf{M}$
    Input Kernel type `kernel`, NFK or NTK
    Output $J_{\boldsymbol{\theta}}^\top(\mathbf{X})\mathbf{M}$ for NTK, Fisher-vector-matrix-product $V_{\boldsymbol{\theta}}^\top(\mathbf{X})\mathbf{M}$ for NFK
1: `jmp_fn = jax.vmap(jax.jvp)`
2: $\mathbf{P} = $`jmp_fn`$(f_{\boldsymbol{\theta}}, \mathbf{X}, \mathbf{M})$
3: **if** `kernel` $= $ "NFK" **then**
4:     $\mathbf{P} = \text{diag}(\mathcal{I})^{-\frac{1}{2}}(\mathbf{P} - \mathbf{Z}_{\boldsymbol{\theta}}^\top \mathbf{M})$
5: **end if**
6: Return $\mathbf{P}$

---

compute the full Gram matrix and perform eigen-decomposition to obtain baseline results. For our implementation, we run 10 power iterations in randomized SVD.

D.2   NEURAL FISHER KERNEL DISTILLATION

With the efficient low-rank approximation of NFK, one can immediately obtain a compact representation of the kernel. Namely, each example can be represented as a k dimension vector. Essentially, we have achieved a form of kernel distillation, which is a useful technique on its own.

Furthermore, we can use Q as an generalized form for teacher student styled knowledge distillation (KD), as in (Hinton et al., 2015). In standard KD, one obtain a teacher network (e.g., deep model) and use it to train a student network (e.g., a shallow model) with a distillation loss in the following format:

$$L_{kd}(\mathbf{x}, \mathbf{y}) = \alpha * L_{cls}(f_s(\mathbf{x}), \mathbf{y}) + (1 - \alpha) * L_t(f_s(\mathbf{x}), f_t(\mathbf{x})), \tag{10}$$

Algorithm 6 `matrix_jacobian_product`

Input Neural network model $f_{\boldsymbol{\theta}}$
Input Input data $\mathbf{X} \in \mathbb{R}^{B \times D}$, where B is batch size
Input Input matrix $\mathbf{M}$
Input Kernel type `kernel`, NFK or NTK
Output $J_{\boldsymbol{\theta}}(\mathbf{X})\mathbf{M}$ for NTK, Fisher-vector-matrix-product $V_{\boldsymbol{\theta}}(\mathbf{X})\mathbf{M}$ for NFK

1: `mjp_fn` = `jax.vmap(jax.vjp)`
2: $\mathbf{P}$ =`mjp_fn`$(f_{\boldsymbol{\theta}}, \mathbf{X}, \mathbf{M})$
3: **if** `kernel` = "NFK" **then**
4:     $\mathbf{P} = \operatorname{diag}(\mathcal{I})^{-\frac{1}{2}}(\mathbf{P} - \mathbf{Z}_{\boldsymbol{\theta}}\mathbf{M})$
5: **end if**
6: Return $\mathbf{P}$

---

where L_{cls} is a standard classification loss (e.g., cross entropy) and L_t is a teacher loss which forces the student network's output f_s to match that of the teacher f_t. We propose a straightforward extension of KD with NFK, where we modify the loss function to be:

$$L_{nfkd}(\mathbf{x}, \mathbf{y}) = \alpha * L_{cls}(f_s(\mathbf{x}), \mathbf{y}) + (1 - \alpha) * L_t(h_s(\mathbf{x}), Q_t(\mathbf{x})), \tag{11}$$

where $Q_t(\mathbf{x})$ denotes the k dimensional embedding from the SVD of teacher NFK, for example $\mathbf{x}$. h_s is a prediction head from the student, and L_t is overloaded to denote a suitable loss (e.g., $\ell 2$ distance or cosine distance). Equation 11 essentially uses the low dimension embedding of the teacher's NFK as supervision, inplace of the teacher's logits. There are arguable benefits of using L_{nfkd} over L_{kd}. For example, when the number of classes is small, the logit layer contains very little extra information (measured in number of bits) than the label alone, whereas Q_t can still provide dense supervision to the student.

For the Neural Fisher Kernel Distillation (NFKD) experiments, we adopt the WideResNet-40x2 (Zagoruyko and Komodakis, 2016) neural network as the teacher model. We train another WideResnet with 16 layers as the student model, and keep the width unchanged. We run 10 power iterations to compute the SVD approximation of the NFK of the teacher model, to obtain the top-20 eigenvectors and eigenvalues. Then we train the student model with the additional NFKD distillation loss using mini-batch stochastic gradient descent, with 0.9 momentum, for 250 epochs. The initial learning rate begins at 0.1 and we decay the learning rate by 0.1 at 150-th epoch and decay again by 0.1 at 200-th epoch. We also show the linear probing accuracies on CIFAR10 by using different number of embedding dimensions in Figure. 6.