CaLFADS: latent factor analysis of dynamical systems in calcium imaging data

Abstract

Dynamic latent variable modelling has provided a powerful tool for understanding how populations of neurons compute. For spiking data, such latent variable modelling can treat the data as set of point-processes, due to the fact that spiking dynamics occur on a much faster timescale than the computational dynamics being inferred. In contrast, for other experimental techniques the slow dynamics governing the observed data are similar in timescale to the computational dynamics that researchers want to infer. An example of this is in calcium imaging data, where calcium dynamics can have time timescales on the order of hundreds of milliseconds. As such, the successful application of dynamic latent variable modelling to modalities like calcium imaging data will rest on the ability to disentangle the higher- and lower-order dynamical systems' contributions to the data. To-date, no techniques have been developed to directly achieve this. Here we solve this problem by extending recent advances using sequential variational autoencoders for dynamic latent variable modelling of neural data. We solve the problem of disentangling higher- and lower-order dynamics by incorporating a ladder architecture that can infer a hierarchy of dynamical systems. Using some built-in inductive biases for calcium dynamics, we show that we can disentangle calcium flux from the underlying dynamics of neural computation. First, we demonstrate with synthetic calcium data that we can correctly disentangle an underlying Lorenz attractor from calcium dynamics. Next, we show that we can infer appropriate rotational dynamics in spiking data from macaque motor cortex after it has been converted into calcium fluorescence data via a calcium dynamics model. Finally, we show that our method applied to real calcium imaging data from primary visual cortex in mice allows us to infer latent factors that carry salient sensory information about unexpected stimuli. These results demonstrate that variational ladder autoencoders are a promising approach for inferring hierarchical dynamics in experimental settings where the measured variable has its own slow dynamics, such as calcium imaging data. Our new, open source tool, thereby provides the neuroscience community with the ability to apply dynamic latent variable modelling to a wider array of data modalities.

1 Introduction

Dynamic latent variable modelling has been a hugely successful approach to understanding the function of neural circuits. For example, it has been used to uncover previously unknown mechanisms for computation in the motor cortex (Churchland et al., 2012; Pandarinath et al., 2018), somatosensory cortex (Wei et al., 2019b), and hippocampus (Chaudhuri et al., 2019). However, the success of this approach is largely limited to datasets where the observed variables have dynamics whose timescales are much faster than the dynamics of the underlying computations. This is the case, for example, with spiking data, where the dynamics governing the generation of individual spikes are much faster than the dynamics of computation across the circuit. This makes it possible to characterize the observed data, e.g. the spiking data, as a set of point-processes that can be used directly for inferring latent variables.

However, many datasets in the life sciences are generated by a hierarchy of dynamical systems, wherein the lower-order dynamical systems that directly generate the observed data have temporal dynamics whose timescales overlap with that of the higher-order dynamical system to be inferred. A

clear example of this is *in-vivo* calcium imaging data, which is widely used in neuroscience. Thanks to advances in imaging technology and genetically encoded calcium indicators, calcium imaging enables monitoring of the activity of large populations of genetically targeted neurons in awake behaving animals (Yang & Yuste, 2017; Lin & Schnitzer, 2016). However, calcium imaging introduces an additional layer of a relatively slow dynamical system between the computations occurring in the brain and the measurements that neuroscientists make. This problem is outlined in Figure 1A, in which calcium fluorescence observations, x, depend on the state of calcium flux, z_1, which is governed by a lower-order dynamical system with temporal dynamics on the order of hundreds of milliseconds. These dynamics are driven, in part, by perturbations due to spikes, u_1, which are themselves governed by a computational state, z_2, with a similar timescale in its dynamics to the calcium flux (and which itself can be perturbed independently by unknown inputs, u_2, that may also have slow dynamics). Due to the overlap in timescales, it is impossible to identify immediately which components of the calcium fluorescence data are driven by the dynamics of calcium flux, and which are driven by the higher-order latent dynamics of neural computation. Ideally, neuroscientists would have a method for inferring both the lower-order calcium dynamics and the higher-order computational dynamics in order to uncover the hierarchical dynamical systems that generated their data. Such a tool would be of significant benefit to the systems neuroscience community.

Currently, these problems are treated separately. For situations where the observed data can be treated as a point process, we have good techniques for inferring the higher-order dynamics. For example, recent applications of sequential variational autoencoders have seen great success in inferring underlying computations from extracellular spiking data (Pandarinath et al., 2018). This technique, named Latent Factor Analysis of Dynamical Systems (LFADS), has improved neuroscientists' ability to infer underlying neural computations from spiking data, e.g. it has been used to identify latent rotational reaching dynamics and to decode reaching behaviour of macaques and humans with higher fidelity than other techniques.

Although LFADS was a significant advance in our ability to analyze neural data in the form of spike trains, it does not address the problem highlighted above for calcium imaging, wherein the calcium dynamics introduce an additional lower-order dynamical system whose timescale overlaps with the timescale of neural computation. Theoretically, this problem could be solved independently by first inferring spikes from calcium data, whether by deconvolution (e.g., OASIS) (Friedrich et al., 2017), variational inference (e.g., DeepSpike) (Speiser et al., 2017), dynamic programming (Deneux et al., 2016), or a number of other methods (Berens et al., 2018; Pachitariu et al., 2018; Evans et al., 2019; Wei et al., 2020), and then applying LFADS. However, this approach treats each calcium trace as a completely independent variable when conducting the inference on calcium dynamics, and therefore, it would ignore the population dynamics that could be informative for separating out the calcium dynamics from the higher-order computational dynamics. If this separation is sub-optimal, then inference of the higher-order system will be impaired.

Here, we address this problem by extending LFADS with a variational ladder autoencoder architecture (Zhao et al., 2017) that folds the calcium dynamics inference into the larger inference problem (Fig. 1B). Our system, CaLFADS, incorporates inductive biases for calcium dynamics and, thanks to the ladder architecture, is able to infer the higher-order dynamical system better than an approach that treats inference of calcium dynamics and higher-order dynamics as separate problems.

First, we show using synthetic data that we are able to reconstruct ground-truth latent dynamics from synthetic calcium traces. Next, we apply CaLFADS to spiking data from macaque motor cortex that has been converted into calcium fluorescence traces using a calcium dynamics model. We show that we are able to recover rotational dynamics from this "calcified" data just as LFADS identifies rotational dynamics from spiking data. Finally, we show using real 2-photon calcium imaging data from mouse primary visual cortex that CaLFADS can identify higher-order latent factors that carry information about unexpected visual stimuli. Altogether, our work shows the benefits of incorporating the calcium dynamics inference procedure into the larger inference problem. It also provides neuroscientists with a new, open-source tool for analyzing calcium imaging data in order to identify higher-order dynamics. Given the importance of calcium imaging to modern systems neuroscience, we believe that CaLFADS will be a very useful analysis tool for the neuroscience community. Moreover, we believe that our approach may be applicable to other life sciences domains where the observed variables have relatively slow dynamics, and thus, could serve as a basis for the construction of future analysis tools.

Figure 1: A) Hierarchy of dynamical systems (Top). schema of calcium and Lorenz dynamics (Bottom). B) Schema of our hierarchical model. Latent dynamics model in blue, calcium dynamics model in red.

2 MODEL

CaLFADS extends the variational ladder autoencoder (VLAE) approach (Zhao et al., 2017) with RNNs (Fig 1B), which enables inference of hierarchical latent dynamical systems[1]. The full directed acyclic graph for CaLFADS can be found in Figure S1. The VLAE approach to implementing hierarchical inference separates the lower-order inference and the higher-order inference into parallel pathways for inference and generation (1B, orange arrow), and subsequently, recombines these levels in the generative network (1B, pink arrow). In other words, VLAEs ensure that the higher-order inference is based on a deterministic embedding from the lower-order encoder, and that the higher-order generator informs the lower-order generator in a deterministic, sequential fashion. As such, the stochastic nodes of the network for the lower-order and higher-order inferences operate in parallel to each other. This approach has two major advantages: 1) It solves the problem of latent variable collapse in which all latent features are loaded onto the lowest-order variables in the hierarchy. 2) It retains a very simple formulation for the variational/evidence lower bound (ELBO) that is easily reparameterizable (Sønderby et al., 2016; Zhao et al., 2017).

CaLFADS infers the dynamics and unknown events (e.g. spikes) that determine the calcium fluorescence signal (Fig 1B, red network nodes), and the underlying computational dynamical system

---

[1]Supporting code for this submission can be found at `https://anonymous.4open.science/repository/63e5b8d1-31b7-408a-99dc-a55980c2a1ca`

that controls these events (Fig 1B, blue network nodes), through successive encoding and decoding layers in which latent variable distributions are modelled in separated 'rungs' of the ladder architecture. This VLAE architecture enables CaLFADS to disentangle the lower-order calcium dynamics and the higher-order computational dynamics. Algorithm 1 provides details on the forward pass of CaLFADS. Briefly, layers of Gated Recurrent Units (GRUs) create a deterministic hierarchical embedding of the data in the inference network (Fig 1B, above the dashed line). These embeddings are then concatenated with time-shifted, layer-specific deterministic projections of the latent state. This concatenated set of activities is then linearly transformed into the parameters of a factorized Gaussian posterior distribution for the latent variables in the generative network (Fig 1B, below the dashed line). This process provides the inference network with information about the history of the latent states via feedback connections (Fig 1B, purple feedback arrows).

As in any variational autoencoder (VAE) system, latent states are sampled from the posterior distributions determined by the inference network. For the inference of the computational dynamical system, these latent states represent the initial conditions (g_{2,t_0}) and unknown inputs ($u_{2,t}$) to a learned dynamical system modelled discretely by a GRU in the generative network ($g_{2,t}$). The hidden state of this GRU is then linearly transformed into a set of potentially low-dimensional time-varying latent factors ($z_{2,t}$). Concurrently, the latent states for the calcium dynamics ($g_{1,t}$) are concatenated with the dynamic factors from the layer above ($z_{2,t}$), and undergo a linear transformation followed by a rectified-exponential non-linearity $f(x) = ReLU(\exp(x) - 1)$ to provide an approximation to spike counts ($u_{1,t}$). This non-linearity was chosen as a continuous relaxation to discrete calcium transient amplitudes inspired by the zero-inflated gamma model of post-deconvolved calcium traces (Wei et al., 2019a). In our case, we model approximate spike counts using a log-normal distribution with truncation at 0. The approximate spike counts are then used as inputs to an order 1 autoregressive (AR(1)) process model of calcium dynamics ($z_{1,t}$). Since we found that the loss function was extremely sensitive to changes in the AR(1) model parameters, these parameters were fixed using values empirically derived from the OASIS-deconvolution algorithm (Friedrich et al., 2017). While it is possible to transform calcium dynamics into fluorescence using nonlinear models of fluorescence indicator kinetics (Speiser et al., 2017; Deneux et al., 2016), we found that using the AR(1) process to model the transformation of spike counts to fluorescence was sufficient for accurate reconstruction of the latent space, even in synthetic data with nonlinear calcium transient generation. Model hyperparameters for different datasets are shown in table S1.

2.1 Loss function and Training

One of the advantages of using VLAEs is that because the stochastic nodes operate in parallel, the ELBO formulation is the same as that for standard VAEs despite the hierarchical latent space (Zhao et al., 2017). As such, the CaLFADS cost function remains very similar to that of LFADS. It is described in Algorithm 2. One key addition to the LFADS loss function is that because the data is fluorescence data, which includes normal emissions noise, and the inferred lower-order factors are calcium concentrations, the likelihood function of the data given the estimated calcium concentration, $P(x_t|\hat{x}_t)$, is modelled as a Gaussian distribution $x_t \sim \mathcal{N}(\hat{x}_t, \sigma_x^2)$, where σ_x^2 is determined by OASIS. Another key addition is that although spike counts $u_{1,t}$ are not modelled discretely, their probability distribution given the inferred spike rates, $P(u_{1,t}|\lambda_t)$, is modelled as an approximate Poisson process such that $\log(P(u_{1,t}|\lambda_t)) \approx u_{1,t} \log(\lambda_t) - (\lambda_t + u_{1,t})$. The approximation results from the use of an L1 norm on the spikes, instead of the log-gamma term that would normally be used in a Poisson process, which was necessary because most of the data sits within a range that is poorly handled by the log-gamma function. The use of this approximate Poisson process provides an additional regularization term in the cost function, which acts as an inductive bias to ensure that the inferred spike trains in the lower-order dynamical system are constrained to follow the dynamics of the higher-order dynamical system's spike rates λ_t. Per the VLAE framework, the lower-order and higher-order latent variables are treated as independent, with hierarchy imposed in the deterministic paths, i.e., $Q(g_{1,t}, g_{2,t=0}, u_{2,t}|x) = Q(g_{1,t}|x)Q(g_{2,t=0}|x)Q(u_{2,t}|x)$

Parameters of CaLFADS were optimized with ADAM, with an initial learning rate of 0.01. Learning rates were decreased by a factor of 0.95 when plateaus in training error were detected. As in LFADS training, KL and L2 terms in the cost function were 'warmed up', i.e., had a weight $w_{l \in (1,2)}$ between 0 and 1 applied that gradually increased (Bowman et al., 2016; Sønderby et al., 2016). Warm-up for the deeper parameters ($l = 2$, blue modules in Figure 1) was delayed until warm-up for shallower parameters ($l = 1$, red modules in Figure 1) was completed. We found in preliminary tests that this

delayed warm-up sequence was necessary for good hierarchical inference compared to simultaneous warm-up. As with aggressive inference network training methods (He et al., 2019), this prevents issues with training of the higher-order dynamical system parameters converging more slowly than the lower-order dynamical system parameters in the initial stages of training.

3 RESULTS

3.1 LORENZ ATTRACTOR SYNTHETIC DATA

3.1.1 DATA DESCRIPTION

As an initial test of CaLFADS, we examined its ability to infer the hierarchical dynamical systems of synthetic calcium fluorescence data generated from a simple model of spiking neurons. We examined synthetic data generated from a network with a Lorenz attractor embedded in its dynamics. This tests our ability to recover a ground-truth higher-order dynamical system from the data, and has been used as a benchmark by many others (Zhao & Park, 2017; Pandarinath et al., 2018; Clark et al., 2019; She & Wu, 2019; Koppe et al., 2019).

In this system, network dynamics were used to generate a set of spike rates in simulated neurons. We then used a model of calcium dynamics and emissions noise to transform the spikes into synthetic fluorescence data. We tested CaLFADS on data generated from two models of synthetic calcium dynamics: a simple linear model equivalent to an AR(1) process, and a nonlinear model in which an AR(1) process is transformed by a Hill function nonlinearity. We then added white noise to the resulting traces. This procedure is described in more detail in Appendix E.

3.1.2 MODEL COMPARISON

We measured the performance of CaLFADS by computing R^2 goodness-of-fit with the embedded Lorenz attractor state variables. We also measured the ability of CaLFADS to reconstruct other ground-truth variables in the synthetic data (spike counts, spike rates, and fluorescence traces) using R^2, but these were not as critical for assessing model performance.

CaLFADS performance was compared against two baselines. First, we use LFADS with a Gaussian likelihood observation model to account for fluorescence (Gaussian-LFADS). Second, we consider the situation where spike counts are first estimated separately using the OASIS deconvolution algorithm (Friedrich et al., 2017), a robust, popular, and computationally inexpensive method of spike extraction widely used by systems neuroscientists (Pachitariu et al., 2018; Evans et al., 2019). LFADS is then used to infer the higher-order dynamical system and reconstruct the spike rates from the deconvolved spike trains. We refer to this approach as OASIS+LFADS throughout.

Table 1 compares R^2 goodness-of-fit in reconstructing ground-truth dynamic latent variables in held-out validation data. Table 1 shows CaLFADS is able to reconstruct the Lorenz attractor state for synthetic data with either linear or nonlinear synthetic calcium models (see Table 1 caption for significance test results). Indeed, the inclusion of nonlinearities in calcium dynamics does not affect CaLFADS ability to reconstruct the Lorenz attractor state as much as it does with OASIS+LFADS. CaLFADS is also better able to reconstruct other network state variables compared to OASIS+LFADS as can also be seen in Table 1. However, it is worth noting that high accuracy in reconstructing other network state variables does not appear to be necessary for accurate reconstruction of the underlying Lorenz attractor. This indicates that CaLFADS is better suited to handling uncertainty due to spike-timing and is capable of separating sources of slow dynamics to reconstruct the embedded latent space. Example outputs of CaLFADS and OASIS+LFADS are shown in Appendix F.2.

Note that CaLFADS reconstructs the Lorenz dynamics almost as well as LFADS does when applied to the spiking data. Of course, it is to be expected that LFADS applied to true spiking data performs better than CaLFADS, since there is an additional source of observation noise from the generation of fluorescence transients. But, the fact we can get very close to the same level of performance indicates that CaLFADS is effective at performing the same inference on calcium data that LFADS performs on spiking data. We speculate that the uncertainty over AR1 process parameters is overcome in CaLFADS by constraining the reconstructed spike counts with the latent dynamics

Table 1: Comparison of model performance (R^2 mean+sem) on synthetic Lorenz datasets generated with 20 different seeds. A hyphen indicates that the variable cannot be compared, as the model does not infer it. The top row is italicized as the performance of LFADS on this task is considered the upper limit, having no additional observation noise from fluorescence. Results of paired t-tests for testing significance of differences in performance between OASIS+LFADS and CaLFADS within seeds for a) linear calcium model: Lorenz state - $t_{14} = 2.85$, $p = 0.013$; Spike Counts - $t_{14} = 20.67$, $p < 0.001$; Rates - $t_{14} = 4.81$, $p < 0.001$; Fluorescence - $t_{14} = 16.2$, $p < 0.001$. b) nonlinear calcium model: Lorenz state - $t_{14} = 3.29$, $p = 0.005$; Spike Counts - $t_{14} = 17.16$, $p < 0.001$; Rates - $t_{14} = 6.35$, $p < 0.001$; Fluorescence - $t_{14} = 11.16$, $p < 0.001$.

Calcium	Model	Lorenz state	Spike Counts	Firing Rates	Fluorescence
NA	*LFADS*	*0.975 ± 0.001*	-	*0.956 ± 0.003*	-
Linear	Gaussian-LFADS	0.818 ± 0.005	-	0.701 ± 0.004	-
	OASIS+LFADS	0.960 ± 0.001	0.580 ± 0.006	0.912 ± 0.002	0.807 ± 0.005
	CaLFADS	**0.965 ± 0.001**	**0.817 ± 0.007**	**0.937 ± 0.002**	**0.909 ± 0.003**
Nonlinear	Gaussian-LFADS	0.808 ± 0.005	-	0.650 ± 0.006	-
	OASIS+LFADS	0.877 ± 0.003	0.351 ± 0.004	0.682 ± 0.005	0.843 ± 0.004
	CaLFADS	**0.902 ± 0.006**	**0.561 ± 0.010**	**0.756 ± 0.008**	**0.932 ± 0.005**

to make the inference of the observed dynamics process "population-aware", something which cannot be done when using LFADS applied to spike counts obtained by OASIS deconvolution. This may mitigate errors in spike count reconstruction that occur by deconvolution due to the absence of information about whole-network dynamics. Thus, CaLFADS can use population-level dynamics when conducting the inference of network variables, and this helps it to separate out the lower-order dynamics more accurately.

3.2 ROTATIONAL DYNAMICS IN MONKEY MOTOR CORTEX

Next, we wanted to test CaLFADS on a real neural dataset to which LFADS has previously been applied, and successfully used to uncover meaningful latent dynamics. Specifically, it has been shown previously that rotational dynamics underlie neuronal responses in monkey and human motor cortex during reaching behaviour (Churchland et al., 2012). LFADS has been successful in uncovering these known rotational dynamics for single-trial spikes recorded from primary motor cortex (M1) and dorsal premotor cortex (PMd) in macaques (Pandarinath et al., 2018). To test whether CaLFADS could do the same, we took the original spiking data and converted it into semi-synthetic calcium traces, using the same model of calcium dynamics that was used for synthetic data generation in the previous sections (Fig 2A). We used data from the monkey electrophysiology dataset previously described, along with the reaching task, by Churchland et al. (2012), which was kindly provided to us by the original authors. Briefly, monkeys were trained to reach a target under 108 different reach conditions while multi-electrode recordings were made in M1 and PMd. Reaches started from a specified location on a screen, and monkeys were rewarded for correctly reaching toward a target while avoiding on-screen obstacles (Fig 2B).

First, to replicate the previous LFADS results, we applied jPCA (Churchland et al., 2012) to condition-averaged firing rates (trial averages for each of the 108 reach conditions), as well as single-trial firing rates inferred from spike data using LFADS. jPCA is a dimensionality reduction technique that finds orthogonal projections capturing rotational dynamics that explain variability in firing rates. The original LFADS paper showed that rotational dynamics explained a large amount of the variance in firing rates. As in the original papers, we identified both condition-averaged (Fig 2C – top) and single-trial (Fig 2C – bottom) rotational dynamics from firing rates inferred by LFADS, which explained a large amount of the variance ($R^2 = 0.81$), thereby replicating the original findings. Then, we evaluated our CaLFADS model in uncovering the rotational dynamics of both condition-averaged and single trials from firing rates. As shown in Fig 2, our model also successfully uncovers rotational dynamics from calcium traces, explaining a large amount of variance ($R^2 = 0.78$) for both condition-averaged (Fig 2D – top) and single trials (Fig 2D – bottom). These results demonstrate that CaLFADS is capable of identifying latent dynamics in real neural data, similar to LFADS, even when the spiking data is transformed by calcium dynamics and emissions noise. We also found that

Figure 2: A) Schematic for the process of converting spikes to calcium traces, and B) for the reaching task. C) Rotational dynamics inferred from condition-averaged (Top) and single-trial spikes (Bottom) using LFADS. D) Rotational dynamics inferred from condition-averaged (Top) and single-trial calcium traces (Bottom) using CaLFADS. E) Rotational dynamics inferred from condition-averaged (Top) and single-trial calcium traces (Bottom) using OASIS+LFADS. Traces are coloured based on their initial state values along jPC1 (from green to red for increasingly larger values)

the OASIS+LFADS approach was not as successful as CaLFADS in uncovering rotational dynamics, explaining only half the variance ($R^2 = 0.53$, Fig 2E). This result corroborates the importance of the hierarchical modelling of calcium and neuronal dynamics in CaLFADS.

3.3 UNEXPECTED STIMULUS DETECTION IN MOUSE PRIMARY VISUAL CORTEX

Finally, we wanted to test CaLFADS on an entirely new calcium imaging dataset, to determine whether CaLFADS can infer dynamic computational factors that carry information about relevant features of the outside world. We chose to analyse data from mouse primary visual cortex (VisP), a region widely studied in systems neuroscience research where calcium imaging is a standard tool. There is evidence that the visual cortex of mammals performs a predictive function, anticipating expected stimuli (Dayan et al., 1995; Rao & Ballard, 1999; Fiser et al., 2016; Leinweber et al., 2017). As a result, unexpected stimuli can induce perturbations in network dynamics (Fiser et al., 2016; Leinweber et al., 2017). Thus, we wanted to determine whether CaLFADS could infer dynamic computational factors that carry information distinguishing unexpected from expected visual stimuli.

To this end, we trained CaLFADS on calcium imaging data from the mouse visual cortex collected by the Allen Institute for Brain Science (for a detailed description, see Appendix G.1). While awake behaving mice were presented with visual stimuli on a screen (Fig 3A), calcium fluorescence responses in cortical layer 2/3 of VisP were recorded using 2-photon microscopy (Fig 3B). The mice were familiarized with sequences of stimulus frames that followed simple probabilistic rules. Briefly, each sequence consisted of four randomized Gabor pattern frames followed by a grey screen (A, B, C, D, grey) with orientations drawn for each trial from the same distribution. After familiarization with this sequence, the expected D frame was replaced in 10% of trials by a Gabor pattern (E) with orthogonal orientations (Fig 3C). CaLFADS inferred smooth latent factors that did not show signs of over-fitting to noise (Fig S6). To determine if salient information about these unexpected stimulus features was present in the inferred factors from CaLFADS, we trained a non-linear decoder to classify whether the inferred factors came from a trial with an expected D frame or an unexpected E frame (for details, see Appendix G.2). We also trained the non-linear decoder on factors inferred by OASIS+LFADS, and on fluorescence traces reduced in dimensionality with principal components analysis. To compare the models fairly, despite the imbalance between expected and unexpected trial frequencies, we measured average recall. We find that using the CaLFADS factors leads to the highest performance on stimulus-trial identity decoding, with the average recall being significantly

Figure 3: A) Schematic of 2-photon calcium imaging recording setup. Mice are head-fixed on a running wheel under the imaging objective, and visual stimuli are projected onto a screen to the side, B) 2-photon calcium imaging recording plane, C) Schematic example of visual stimuli for expected (A-B-C-D-grey) and unexpected (A-B-C-E-grey) trials. D) Average recall (mean ± sem) of expected vs. unexpected trials using a non-linear decoder trained on principal components of fluorescence (dF/F) traces (0.803 ± 0.012, green), OASIS+LFADS factors (0.805 ± 0.008, blue), and CaLFADS factors (0.826 ± 0.005, purple). (* p-value < 0.05 in 2-tailed paired t-test with Bonferroni correction for multiple comparisons.)

higher than when OASIS+LFADS factors are used (Fig 3D). This indicates that CaLFADS infers latent dynamics from real visual cortex calcium imaging data that reflect the predictability of visual stimuli, corroborating the ability of CaLFADS to infer meaningful dynamic factors in real data.

4 DISCUSSION

In this paper we presented CaLFADS, a hierarchical recurrent variational autoencoder model capable of reconstructing latent computational dynamics. We confirmed CaLFADS' ability to reconstruct known underlying dynamics using synthetic datasets where ground-truth was known. We also showed that CaLFADS is able to infer sensorimotor dynamics from real neural recordings. This indicates that CaLFADS is a promising method for analyzing calcium imaging data in neuroscience.

There are two key advantages of CaLFADS over the use of deconvolution of calcium traces followed by application of LFADS. The first is that we can obtain measures of the uncertainty in both the latent dynamics, and the latent spike counts. The second is that CaLFADS performs better than OASIS+LFADS when nonlinearities in calcium dynamics are present, as is the case in real experimental data where there are many sources of calcium influx related to spikes.

We designed CaLFADS to fit into a much broader class of artificial neural network models, namely *sequential variational ladder autoencoders*, in which different layers of recurrent neural networks can be used to infer and generate different layers of a hierarchical dynamical system. In this sense, this class of models is modular and composable, meaning it could be readily adapted to other domains. For example, it should be possible to replace LFADS as the higher-order dynamical system model with any other differentiable model. Likewise the same is true for our AR1 based model of calcium dynamics: we could replace the calcium dynamics model with other models as required by the experimental set-up. Furthermore, there is no need to stop at two layers in the hierarchy; the brain is comprised of many interconnected recurrent neural networks sending long range signals to one another, and it should be possible to add in additional modules to capture additional hierarchies and dynamics within the brain.

In summary, CaLFADS is a new, open source tool for inferring hierarchical dynamics from calcium imaging data that also has great potential for being modified and applied to other data modalities. This could be of real benefit to the thousands of neuroscience laboratories around the world conducting calcium imaging experiments.

REFERENCES

A. Anonymous. Identifying the role of top-down feedback connections in cortical learning and inference (aibs openscope grant proposal), 2018.

Philipp Berens, Jeremy Freeman, Thomas Deneux, Nikolay Chenkov, Thomas McColgan, Artur Speiser, Jakob H. Macke, Srinivas C. Turaga, Patrick Mineault, Peter Rupprecht, Stephan Gerhard, Rainer W. Friedrich, Johannes Friedrich, Liam Paninski, Marius Pachitariu, Kenneth D. Harris, Ben Bolte, Timothy A. Machado, Dario Ringach, Jasmine Stone, Luke E. Rogerson, Nicolas J. Sofroniew, Jacob Reimer, Emmanouil Froudarakis, Thomas Euler, Miroslav Román Rosón, Lucas Theis, Andreas S. Tolias, and Matthias Bethge. Community-based benchmarking improves spike rate inference from two-photon calcium imaging data. *PLOS Computational Biology*, 14 (5):1–13, 05 2018. doi: 10.1371/journal.pcbi.1006157.

Samuel R. Bowman, Luke Vilnis, Oriol Vinyals, Andrew Dai, Rafal Jozefowicz, and Samy Bengio. Generating sentences from a continuous space. In *Proceedings of The 20th SIGNLL Conference on Computational Natural Language Learning*, pp. 10–21, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/K16-1002.

Rishidev Chaudhuri, Berk Gerçek, Biraj Pandey, Adrien Peyrache, and Ila Fiete. The intrinsic attractor manifold and population dynamics of a canonical cognitive circuit across waking and sleep. *Nature Neuroscience*, 22(9):1512–1520, September 2019. doi: 10.1038/s41593-019-0460-x. Number: 9 Publisher: Nature Publishing Group.

T. W. Chen, T. J. Wardill, Y. Sun, S. R. Pulver, S. L. Renninger, A. Baohan, E. R. Schreiter, R. A. Kerr, M. B. Orger, V. Jayaraman, L. L. Looger, K. Svoboda, and D. S. Kim. Ultrasensitive fluorescent proteins for imaging neuronal activity. *Nature*, 499(7458):295–300, 2013.

Mark M. Churchland, John P. Cunningham, Matthew T. Kaufman, Justin D. Foster, Paul Nuyujukian, Stephen I. Ryu, and Krishna V. Shenoy. Neural population dynamics during reaching. *Nature*, 487(7405):51–56, July 2012. doi: 10.1038/nature11129. Number: 7405 Publisher: Nature Publishing Group.

David G. Clark, Jesse Livezey, and Kristofer E. Bouchard. Unsupervised discovery of temporal structure in noisy data with dynamical components analysis. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, 8-14 December 2019, Vancouver, BC, Canada*, pp. 14267–14278, 2019.

Peter Dayan, Geoffrey E. Hinton, Radford M. Neal, and Richard S. Zemel. The helmholtz machine. *Neural Comput.*, 7(5):889–904, September 1995. doi: 10.1162/neco.1995.7.5.889.

S. E. J. de Vries, J. Lecoq, M. A. Buice, P. A. Groblewski, G. K. Ocker, M. Oliver, D. Feng, N. Cain, P. Ledochowitsch, D. Millman, K. Roll, M. Garrett, T. Keenan, L. Kuan, S. Mihalas, S. Olsen, C. Thompson, W. Wakeman, J. Waters, D. Williams, C. Barber, N. Berbesque, B. Blanchard, N. Bowles, S. Caldejon, L. Casal, A. Cho, S. Cross, C. Dang, T. Dolbeare, M. Edwards, J. Galbraith, N. Gaudreault, F. Griffin, P. Hargrave, R. Howard, L. Huang, S. Jewell, N. Keller, U. Knoblich, J. Larkin, R. Larsen, C. Lau, E. Lee, F. Lee, A. Leon, L. Li, F. Long, J. Luviano, K. Mace, T. Nguyen, J. Perkins, M. Robertson, S. Seid, E. Shea-Brown, J. Shi, N. Sjoquist, C. Slaughterbeck, D. Sullivan, R. Valenza, C. White, A. Williford, D. Witten, J. Zhuang, H. Zeng, C. Farrell, L. Ng, A. Bernard, J. W. Phillips, R. C. Reid, and C. Koch. A large-scale, standardized physiological survey reveals higher order coding throughout the mouse visual cortex. *bioRxiv*, pp. 34, 2018. doi: 10.1101/359513.

Thomas Deneux, Attila Kaszas, Gergely Szalay, Gergely Katona, Tamás Lakner, Amiram Grinvald, Balázs Rózsa, and Ivo Vanzetta. Accurate spike estimation from noisy calcium signals for ultrafast three-dimensional imaging of large neuronal populations in vivo. *Nature Communications*, 7(1): 12190, July 2016. doi: 10.1038/ncomms12190.

Mathew H. Evans, Rasmus S. Petersen, and Mark D. Humphries. On the use of calcium deconvolution algorithms in practical contexts. *bioRxiv*, 2019. doi: 10.1101/871137.

A. Fiser, D. Mahringer, H. K. Oyibo, A. V. Petersen, M. Leinweber, and G. B. Keller. Experience-dependent spatial expectations in mouse visual cortex. *Nature Neuroscience*, 19(12):1658–1664, 2016.

Johannes Friedrich, Pengcheng Zhou, and Liam Paninski. Fast online deconvolution of calcium imaging data. *PLOS Computational Biology*, 13(3):e1005423, March 2017.

Junxian He, Daniel Spokoyny, Graham Neubig, and Taylor Berg-Kirkpatrick. Lagging inference networks and posterior collapse in variational autoencoders. In *International Conference on Learning Representations*, 2019.

J. Homann, S. A. Koay, A. M. Glidden, D. W. Tank, and M. J. Berry. Predictive coding of novel versus familiar stimuli in the primary visual cortex. *bioRxiv*, pp. 17, 2017. doi: 10.1101/197608.

Georgia Koppe, Hazem Toutounji, Peter Kirsch, Stefanie Lis, and Daniel Durstewitz. Identifying nonlinear dynamical systems via generative recurrent neural networks with applications to fmri. *PLOS Computational Biology*, 15(8):1–35, 08 2019. doi: 10.1371/journal.pcbi.1007263.

Marcus Leinweber, Daniel R. Ward, Jan M. Sobczak, Alexander Attinger, and Georg B. Keller. A Sensorimotor Circuit in Mouse Cortex for Visual Flow Predictions. *Neuron*, 95(6):1420–1432.e5, September 2017. doi: 10.1016/j.neuron.2017.08.036. Publisher: Elsevier.

Michael Z Lin and Mark J Schnitzer. Genetically encoded indicators of neuronal activity. *Nature neuroscience*, 19(9):1142, 2016.

Marius Pachitariu, Carsen Stringer, and Kenneth D. Harris. Robustness of Spike Deconvolution for Neuronal Calcium Imaging. *The Journal of Neuroscience*, 38(37):7976–7985, September 2018.

Chethan Pandarinath, Daniel J. O'Shea, Jasmine Collins, Rafal Jozefowicz, Sergey D. Stavisky, Jonathan C. Kao, Eric M. Trautmann, Matthew T. Kaufman, Stephen I. Ryu, Leigh R. Hochberg, Jaimie M. Henderson, Krishna V. Shenoy, L. F. Abbott, and David Sussillo. Inferring single-trial neural population dynamics using sequential auto-encoders. *Nature methods*, 15(10):805–815, October 2018.

Rajesh P. N. Rao and Dana H. Ballard. Predictive coding in the visual cortex: a functional interpretation of some extra-classical receptive-field effects. *Nature Neuroscience*, 2(1):79–87, January 1999. doi: 10.1038/4580. Number: 1 Publisher: Nature Publishing Group.

Qi She and Anqi Wu. Neural dynamics discovery via gaussian process recurrent neural networks. In Amir Globerson and Ricardo Silva (eds.), *Proceedings of the Thirty-Fifth Conference on Uncertainty in Artificial Intelligence, UAI 2019, Tel Aviv, Israel, July 22-25, 2019*, pp. 159. AUAI Press, 2019.

Casper Kaae Sønderby, Tapani Raiko, Lars Maaløe, Søren Kaae Sønderby, and Ole Winther. Ladder Variational Autoencoders. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 29*, pp. 3738–3746. Curran Associates, Inc., 2016.

Artur Speiser, Jinyao Yan, Evan W Archer, Lars Buesing, Srinivas C Turaga, and Jakob H Macke. Fast amortized inference of neural activity from calcium imaging data with variational autoencoders. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 4024–4034. Curran Associates, Inc., 2017.

Xue-Xin Wei, Ding Zhou, Andres Grosmark, Zaki Ajabi, Fraser Sparks, Pengcheng Zhou, Mark Brandon, Attila Losonczy, and Liam Paninski. A zero-inflated gamma model for post-deconvolved calcium imaging traces. *bioRxiv*, 2019a. doi: 10.1101/637652.

Ziqiang Wei, Hidehiko Inagaki, Nuo Li, Karel Svoboda, and Shaul Druckmann. An orderly single-trial organization of population dynamics in premotor cortex predicts behavioral variability. *Nature Communications*, 10(1):216, January 2019b. doi: 10.1038/s41467-018-08141-6. Number: 1 Publisher: Nature Publishing Group.

Ziqiang Wei, Bei-Jung Lin, Tsai-Wen Chen, Kayvon Daie, Karel Svoboda, and Shaul Druckmann. A comparison of neuronal population dynamics measured with calcium imaging and electrophysiology. *PLOS Computational Biology*, 16(9):1–29, 09 2020. doi: 10.1371/journal.pcbi.1008198.

Weijian Yang and Rafael Yuste. In vivo imaging of neural activity. *Nature methods*, 14(4):349, 2017.

Shengjia Zhao, Jiaming Song, and Stefano Ermon. Learning Hierarchical Features from Deep Generative Models. In *International Conference on Machine Learning*, pp. 4091–4099, July 2017.

Yuan Zhao and Il Memming Park. Variational Latent Gaussian Process for Recovering Single-Trial Dynamics from Population Spike Trains. *Neural Computation*, 29(5):1293–1316, March 2017.

A VARIABLE GLOSSARY

Table S1: Glossary of variables, with descriptions and dimensionality across datasets

Variable	Description	Dimensions			
		Lorenz	RNN	M1/PMd	V1
x_t	Fluorescence signal	30	50	202	96
$E_{1,t}$	Calcium dynamics embedding encoder state	128	64	200	128
$E_{2,t}$	Computational dynamics embedding encoder state	64	128	100	128
$C_{1,t}$	Calcium dynamics embedding controller state	128	64	200	128
$C_{2,t}$	Computational dynamics embedding controller state	0	128	0	64
$g_{1,t}$	Calcium dynamics embedding state	100	64	200	128
$g_{2,t}$	Computational dynamics embedding state	64	200	100	200
$u_{1,t}$	Approximate spike counts	30	50	202	96
$u_{2,t}$	Computational dynamics perturbations	0	1	0	1
$z_{1,t}$	Calcium dynamics	30	50	202	96
$z_{2,t}$	Dynamic factors	3	20	40	32
$\hat{x}_t$	Reconstructed fluorescence signal	30	50	202	96

B CALFADS DIRECTED ACYCLIC GRAPH

Figure S1: Directed acyclic graph for hierarchical model. Solid arrows denote deterministic mappings, open arrows denote sampling steps.

C CALFADS FORWARD METHOD PSEUDOCODE

Algorithm 1: Forward method for CaLFADS

---

1 Forward ;

Input   : Fluorescence (dF/F) traces x with dimensions TxN

Output: Denoised dF/F $\hat{x}$, Inferred spike train $z_{1,t}$, Inferred dynamic factors $z_{2,t}$

2 $[E_{l=0,t=1:T}^{fwd}, E_{l=0,t=1:T}^{bwd}] = x_{t=1:T}$

3 **for** $t \leftarrow 1$ **to** T **do**

4   **for** $l \leftarrow 1$ **to** 2 **do**

5          $E_{l,t}^{fwd} = GRU(E_{2,t-1}^{fwd}, [E_{1,t}^{fwd}, E_{1,t}^{bwd}])$

6          $E_{l,T-t}^{bwd} = GRU(E_{2,T-t+1}^{bwd}, [E_{1,T-t}^{fwd}, E_{1,T-t}^{bwd}])$

7   **end**

8 **end**

9 $\mu_{g_{2,t=0}} = Dense([E_{2,T+1}^{fwd}, E_{2,0}^{bwd}])$

10 $\sigma_{g_{2,t=0}} = \exp(0.5Dense([E_{2,T+1}^{fwd}, E_{2,0}^{bwd}]))$

11 $g_{2,t=0} \sim \mathcal{N}(\mu_{g_{2,t=0}}, \sigma_{g_{2,t=0}}^2)$

12 $z_{2,t=0} = Dense(g_{2,t=0})$

13 **for** $t \leftarrow 1$ **to** T **do**

14   **for** $l \leftarrow 1$ **to** 2 **do**

15          $C_{l,t} = GRU(C_{l,t-1}, [E_{l,t}^{fwd}, E_{l,t}^{bwd}, z_{l,t-1}])$

16   **end**

17      $\mu_{u_{2,t}} = Dense(C_{2,t})$

18      $\sigma_{u_{2,t}}^2 = \exp(Dense(C_{2,t}))$

19      $u_{2,t} \sim \mathcal{N}(\mu_{u_{2,t}}, \sigma_{u_{2,t}}^2)$

20      $g_{2,t} = GRU(g_{2,t-1}, u_{2,t})$

21      $z_{2,t} = Dense(g_{2,t})$

22      $\lambda_t = \exp(0.5Dense(z_{2,t}))$

23      $\mu_{g_{1,t}} = Dense(C_{1,t})$

24      $\sigma_{g_{1,t}}^2 = \exp(0.5Dense(C_{1,t}))$

25      $g_{1,t} \sim \mathcal{N}(\mu_{g_{1,t}}, \sigma_{g_{1,t}}^2)$

26      $u_{1,t} = ReLU(\exp(Dense([g_{1,t}, z_{2,t}]) - 1))$

27      $z_{1,t} = AR1(z_{1,t-1}, u_{1,t})$

28      $\hat{x}_t = DyeKinetics(\hat{x}_{t-1}, z_{1,t})$

29 **end**

D   CALFADS LOSS FUNCTION PSEUDOCODE

Algorithm 2: Loss function for CaLFADS

---

1 CaLFADS Loss Function;

    Input   : Fluorescence (dF/F) traces x, reconstructed dF/F $\hat{x}$, Intensity function λ, Inferred spikes u_1, Posterior distribution $[\mu_{g_2,t=0}, \sigma_{g_2,t=0}, \mu_{u_2,t}, \sigma_{u_2,t}, \mu_{g_1,t}, \sigma_{g_1,t}]$

    Output: Loss $\mathcal{L}$

2 $\mathcal{L}_{recon} = -\mathbb{E}_{g_1 \sim Q(g_1|x)}[\log P(x|\hat{x})]$

3 $\mathcal{L}_{spike} = -\mathbb{E}_{g_1,g_2,u_2 \sim Q(g_1,g_2,u_2|x)}[\log(u_1|\lambda)]$

4 $\mathcal{L}_{KL_1} = w_1 D_{\mathrm{KL}}(Q(g_1|x)|P(g_1))$

5 $\mathcal{L}_{KL_2} = w_2 D_{\mathrm{KL}}(Q(g_2,u_2|x)|P(g_2,u_2))$

6 $\mathcal{L} = \mathcal{L}_{recon} + \mathcal{L}_{spike} + \mathcal{L}_{KL_1} + \mathcal{L}_{KL_2}$

7 return $\mathcal{L}$

E SYNTHETIC DATA GENERATION

As discussed in the main text, synthetic calcium fluorescence data was generated by embedding a Lorenz Attractor in the dynamics of a spiking neural network. Two models of calcium dynamics were then used to transform spikes to calcium transients, with additive emissions noise added to the resulting traces.

The Lorenz Attractor is a nonlinear dynamical system with 3 states x_1, x_2, x_3 commonly used to study chaotic dynamics. The dynamical system is defined by,

$$\frac{dx_1}{dt} = \sigma(x_2 - x_1) \tag{1}$$

$$\frac{dx_2}{dt} = x_1(\rho - x_3) - x_2 \tag{2}$$

$$\frac{dx_3}{dt} = x_1 x_2 - \beta x_3. \tag{3}$$

$$\tag{4}$$

This system was parameterized in its typical chaotic regime with $\sigma = 10, \beta = 8/3, \rho = 28$. These states were then normalized to have a mean of zero and a range of $[-1, 1]$.

The state of this system $\mathbf{x}$ was then randomly projected onto the firing rate of a population of $N = 30$ neurons,

$$\lambda_t = \exp(\mathbf{W}\mathbf{x}_t + \mathbf{b}) \tag{5}$$

with $\mathbf{W} \sim \mathcal{N}(0, \frac{1}{\sqrt{N}}\mathbf{I})$, and $\mathbf{b} = \mathbf{1}$. Spike counts in time-bin t for neuron i s_i were then sampled using a Poisson distribution

$$s_{i,t} \sim Poisson(\lambda_{i,t}\Delta t) \tag{6}$$

where Δt is the width of a time-bin. For our simulations, we used $\Delta t = 0.1s$.

Calcium fluorescence traces were then modelled in one of two ways. The first method modelled calcium concentration in neuron i c_i as an exponentially decaying variable with time constant $\tau = 0.3$ and perturbations by spikes

$$\frac{dc_i}{dt} = \frac{-c_i}{\tau} + s_i. \tag{7}$$

Fluorescence was then modelled by adding white emissions noise with standard deviation $\sigma_F = 0.2$.

$$F_t = c_t + \epsilon_t \qquad \epsilon \sim \mathcal{N}(0, \sigma_F) \tag{8}$$

The second method for generating synthetic calcium traces added an intermediary step between calcium influx and observed fluorescence. As previously, spikes were integrated with a slow-varying exponentially decaying variable c as described in Equation 7. A hill function was used to capture the nonlinear binding kinetics of calcium to the indicator dye,

$$d_t = \frac{c_t^n}{1 + \gamma c_t^n} \tag{9}$$

with hill coefficient $n = 2$, and $gamma = 0.0001$. These parameters were chosen to based on parameter fits in Deneux et al. (2016). Finally white noise was added to these resulting traces to provide synthetic fluorescence traces,

$$F_t = d_t + \epsilon_t \qquad \epsilon \sim \mathcal{N}(0, \sigma_F) \tag{10}$$

F CALFADS EXAMPLE OUTPUTS AND SCATTER PLOTS ON SYNTHETIC BENCHMARK DATASETS

F.1 LORENZ ATTRACTOR: LINEAR CALCIUM MODEL

Figure S2(Top), S3(Bottom): Example traces of A) Observed Fluorescence, B) Spike Rates, C) Spike Counts, D) Dynamic Factors. Red: Ground-truth, Blue: Reconstructed. Scatter plots comparing reconstructed and ground-truth of E) Observed Fluorescence, F), Spike Rates, G) Spike Counts, H) Lorenz State

Figure S2 shows examples of the performance of CaLFADS in reconstructing the fluorescence traces (Fig S2A), spike rates (Fig S2B), spike counts (Fig S2C) and Lorenz attractor states (Fig S2D) when using a linear model of synthetic calcium dynamics. Visually, it can be seen that the model achieves a very close fit to the fluorescence traces, spike rates, and Lorenz dynamics. The model also captures spike-timing, with these spike trains appearing smoothed.

For comparison, Figure S3 show examples of OASIS+LFADS reconstructions. A key difference is that the spike counts are not smooth as spike counts are discretized from the deconvolved transient amplitudes, and there is greater variance in reconstruction quality at high spike rates as shown by

the scatter plot in Figure S3F. Nevertheless, OASIS+LFADS also provides a good fit to fluorescence traces, spike rates, spike counts and lorenz dynamics.

F.2 LORENZ ATTRACTOR: NONLINEAR CALCIUM MODEL

Figure S4(Top), S5(Bottom): Example traces of A) Observed Fluorescence, B) Spike Rates, C) Spike Counts, D) Dynamic Factors. Red: Ground-truth, Blue: Reconstructed. Scatter plots comparing reconstructed and ground-truth of E) Observed Fluorescence, F), Spike Rates, G) Spike Counts, H) Lorenz State

Figure S4 shows examples of the performance of CaLFADS in reconstructing the fluorescence traces (Fig S4A), spike rates (Fig S4B), spike counts (Fig S4C) and Lorenz attractor states (Fig S4D) when using a nonlinear model to generated synthetic calcium traces. As with the linear calcium model, it can be seen that the model achieves a close reconstruction of to the Lorenz dynamics. However, the reconstructions of other network variables have deteriorated to a much geater extent. A similar trend can be seen in Figure S5 for OASIS+LFADS.

G   MOUSE VISP DATASET, DECODING NETWORK AND EXAMPLE FACTORS

G.1   MOUSE VISP DATASET

The 2-photon calcium imaging data used here is part of the OpenScope project dataset (Anonymous, 2018), collected by the Allen Institute for Brain Science (AIBS) in Seattle, WA. All animal proce-dures were approved by the Institutional Animal Care and Use Committee at the AIBS. Neuronal activity was recorded in head-fixed, awake Cux2-Cre mice on a running wheel (de Vries et al., 2018) (Fig 3A) expressing the calcium indicator GCamP6f (Chen et al., 2013) in layer 2/3 pyramidal cells of VisP (Fig 3B). The mice were first habituated to a repeating, expected stimulus over 6 days, after which unexpected trials were introduced. The stimuli were adapted from (Homann et al., 2017). In each expected trial, 4 consecutive sets of 30 Gabor patches appeared in sequence for 300 ms each, followed by 300 ms of grey screen (A, B, C, D, grey). For each set, the locations and sizes of the Gabor patches were held constant within a session. However, within each trial, each Gabor patch's orientation was sampled from a von Mises distribution, with trial mean sampled from $\{0, 45, 90, 135\}°$ and standard deviation $0.25°$. In expected trials, occurring 10% of the time, the D set was replaced with a distinct set E, with its own locations and sizes. In addition, the Gabor patch orien-tations for E sets were sampled from a von Mises distribution with mean shifted positively by $90°$ (Fig 3C). Processed fluorescence (dF/F) traces were extracted from the calcium imaging recordings for the putative neurons identified, as described in (de Vries et al., 2018).

G.2   MOUSE VISP DECODING NETWORK AND EXAMPLE FACTORS

Figure S6: Schema of the non-linear model trained to decode expected vs. unexpected stimulus trials. Example latent factors inferred by CaLFADS are plotted for an expected (blue) and an unex-pected (red) trial. Each stimulus frame (A, B, C, D/E, grey) is labelled, and its onset and offset in the trial are marked with dotted lines. Latent factors are passed through GRU and linear modules (green), followed by a sigmoid decision function.

Figure S6 shows a schematic of the non-linear model used to decode from the latent factors whether a trial contained an expected or unexpected frame (decoding performances reported in Fig 3D). In short, the non-linear decoder comprised of a single-layer GRU, followed by a linear layer and a sigmoid decision function. We show an example set of latent factors (Figure S6 left) inferred in expected (blue) and unexpected (red) trials. From these, one can see that CaLFADS was able to infer smooth latent factors from the calcium imaging data that did not show signs of over-fitting to noise.