ACCURATE LEARNING OF GRAPH REPRESENTATIONS WITH GRAPH MULTISET POOLING

ABSTRACT

Message-passing graph neural networks have been widely used on modeling graph data, achieving impressive results on a number of graph classification and link prediction tasks. Yet, obtaining an accurate representation for a graph further requires a well-defined pooling function that maps the set of node representations into a compact form, without information loss of the individual node features and the global graph structure. A simple sum or average over all node representations considers all node features equally without consideration of their task relevance, and any structural dependencies among them. Recently proposed hierarchical graph pooling methods, on the other hand, may yield representations that do not pass the graph isomorphism test, as they suboptimally preserve information from the node features. To tackle these limitations of existing graph pooling methods, we first formulate the graph pooling problem as a multiset encoding problem with auxiliary information about the graph structure, and propose a *Graph Multiset Transformer* (GMT) which is a multi-head attention based global pooling layer that captures the interaction between nodes according to their structural dependencies. We show that GMT satisfies both injectiveness and permutation invariance, such that it is at most as powerful as the Weisfeiler-Lehman graph isomorphism test. Moreover, our methods can be easily extended to the previous node clustering approaches for hierarchical graph pooling. Our experimental results show that GMT significantly outperforms state-of-the-art graph pooling methods on graph classification benchmarks with high memory efficiency, and obtains even larger performance gain on graph reconstruction and generation tasks, which more directly measure the expressiveness of graph pooling methods.

1 INTRODUCTION

Graph neural networks (GNNs) (Zhou et al., 2018; Wu et al., 2019), which work with graph structured data, have recently attracted considerable attention, as they can learn expressive representations for various graph-related tasks such as node classification, link prediction, and graph classification. While the majority of the existing works on GNNs focus on the message passing strategies for neighborhood aggregation (Kipf & Welling, 2017; Hamilton et al., 2017), which aims to encode the nodes in a graph accurately, graph pooling (Zhang et al., 2018; Ying et al., 2018) that maps the set of nodes into a compact representation is crucial in capturing a meaningful structure of an entire graph.

As a simplest approach for graph pooling, we can average or sum all node features in the given graph (Atwood & Towsley, 2016; Xu et al., 2019) (Figure 1 (B)). However, since such simple aggregation schemes treat all nodes equally without considering their relative importance on the given tasks, they can not generate a meaningful graph representation in a task-specific manner. Their flat architecture designs also restrict their capability toward the hierarchical pooling or graph compression into few nodes. To tackle these limitations, several differentiable pooling operations have been proposed to condense the graph with neural network architectures in an end-to-end manner. There are two dominant approaches to pooling a graph. Node drop methods (Zhang et al., 2018; Lee et al., 2019b) (Figure 1 (C)) obtain a score of each node using information from the graph convolutional layers, and then drop unnecessary nodes with lower scores at each pooling step by sorting them. Node clustering methods (Ying et al., 2018; Bianchi et al., 2019) (Figure 1 (D)), on the other hand, cluster similar nodes into a single node by exploiting their hierarchical similarity structure.

Figure 1: **Concepts (Left):** Conceptual comparison of graph pooling methods. Grey box indicates the readout layer, which is compatible with our method. Also, green check icon indicates the model passes the isomorphism test. **(Right):** An illustration of set, multiset, and graph multiset encoding for graph representation learning.

Both graph pooling approaches have obvious drawbacks. First, node drop methods unnecessarily drop some nodes at every pooling step, leading to information loss on those discarded nodes. On the other hand, node clustering methods compute the *dense* soft cluster assignment matrix with an adjacency matrix. This prevents them from exploiting sparsity in the graph topology, leading to excessively high computational complexity (Lee et al., 2019b). Furthermore, since they need a single graph representation at the end, they generally use Readout (Cangea et al., 2018) or 1D convolution (Zhang et al., 2018) for this purpose. However, it is suboptimal since those operations do not explicitly consider the inter-node relationships. Finally, to accurately represent the graph, the GNNs should obtain a representation that is as powerful as the Weisfeiler-Lehman (WL) graph isomorphism test (Weisfeiler & Leman, 1968), such that it can map two different graphs onto two distinct embeddings. While recent message-passing operations satisfy this constraint (Morris et al., 2019; Xu et al., 2019), most deep graph pooling works (Ying et al., 2018; Lee et al., 2019b; Gao & Ji, 2019; Bianchi et al., 2019) overlook graph isomorphism except for a few (Zhang et al., 2018).

To obtain accurate representations of given graphs that can pass the WL-test, we first focus on that the graph representation learning can be regarded as a multiset encoding problem, which allows for possibly repeating elements, since a graph may have redundant node representations (See Figure 1, right). However, since a graph is more than a multiset due to its structural constraint, we further define the problem as a *graph multiset* encoding, whose goal is to encode two different graphs given as multisets of node features with auxiliary structural dependencies among them (See Figure 1, right), into two unique embeddings. We tackle this problem by utilizing a graph-structured attention unit. By leveraging this unit as a fundamental building block, we propose the *Graph Multiset Transformer* (GMT), a pooling mechanism that condenses the given graph into the set of representative nodes, and then further encodes relationships between them to enhance the representation power of a graph. We theoretically analyze the connection between our pooling operations and WL test, and further show that our graph multiset pooling function can be easily extended to node clustering methods.

We then experimentally validate the **graph classification** performance of GMT on 10 benchmark datasets from biochemical and social domains, on which it significantly outperforms existing methods on most of them. However, since graph classification tasks only require discriminative information, to better quantify the amount of information about the graph in condensed nodes after pooling, we further validate it on **graph reconstruction** of synthetic and molecule graphs, and also on two **graph generation** tasks, namely molecular generation and retrosynthesis. Notably, GMT outperforms baselines with even larger performance gap on graph reconstruction, which demonstrates that it learns meaningful information without forgetting original graph structure. Finally, it improves the graph generation performance on two tasks, which shows that GMT can be well coupled with other GNNs for graph representation learning. In sum, our main contributions are summarized as follows:

- We treat a graph pooling problem as a multiset encoding problem, under which we consider relationships among nodes in a set with several attention units, to make a compact representation of an entire graph only with one global function, without additional message-passing operations.
- We show that existing GNN with our parametric pooling operation can be as powerful as the WL test, and also be easily extended to the node clustering approaches with learnable clusters.
- We extensively validate GST for graph classification, reconstruction, and generation tasks on synthetic and real-world graphs, on which it largely outperforms most graph pooling baselines.

2   RELATED WORK

Graph Neural Network   Existing graph neural network (GNN) models generally encode the nodes by aggregating the features from the neighbors (Kipf & Welling, 2017; Hamilton et al., 2017), and have achieved a large success on node classification and link prediction tasks (Velickovic et al., 2018; You et al., 2019). However, accurately representing the given graph as a whole remains challenging. While using mean or max over the node embeddings allow to represent the entire graph for graph classification (Duvenaud et al., 2015; Dai et al., 2016), they are mostly suboptimal, and may output the same representation for two different graphs. To resolve this problem, recent GNN models (Xu et al., 2019; Morris et al., 2019) aim to make the GNNs to be as powerful as the Weisfeiler-Lehman test (Weisfeiler & Leman, 1968) in distinguishing graph structures. Yet, they also rely on simple operations, and we need a more sophisticated method to represent the entire graph.

Graph Pooling   In the graph representation learning tasks, graph pooling methods play an essential role of representing the entire graph. While averaging all node features is directly used as simplest pooling methods (Atwood & Towsley, 2016; Simonovsky & Komodakis, 2017), they result in a loss of information since they consider all node information equally without considering key features for graphs. To overcome this limitation, there have been recent studies on graph pooling to compress the given graph in a task specific manner. Node drop methods use learnable score functions to drop nodes with lower scores (Zhang et al., 2018; Gao & Ji, 2019; Lee et al., 2019b). Also, node clustering methods cast the graph pooling problem into the node clustering problem to map the nodes into a set of clusters (Ying et al., 2018; Bianchi et al., 2019). In addition, Ahmadi et al. (2020) model the memory layer to aggregate nodes without utilizing message-passing after pooling.

(Multi-)Set Representation Learning   Note that a set of nodes in a graph forms a multiset (Xu et al., 2019); a set that allows possibly repeating elements. Therefore, contrary to the previous set-encoding methods which mainly consider non-graph problems (Qi et al., 2017a; Yi et al., 2019; Snell et al., 2017), we regard the graph representation learning as a multi-set encoding problem. Mathematically, Zaheer et al. (2017); Qi et al. (2017b) provide the theoretical grounds on permutation invariant functions for the set encoding. Further, Lee et al. (2019a) propose Set Transformer, which uses attention mechanism on the set encoding. Building on top of these theoretical grounds on set, we propose the multiset encoding function that explicitly considers the graph structures.

3   GRAPH MULTISET POOLING

We posit the graph representation learning problem as a multiset encoding problem, and then utilize the graph-structured attention to consider the global graph structure when encoding the given graph.

3.1   PRELIMINARIES

We begin with the general descriptions of graph neural network, and graph pooling.

Graph Neural Network   A graph G can be represented by its adjacency matrix $\boldsymbol{A} \in \{0, 1\}^{n \times n}$ and node set $\mathcal{V}$ with $|\mathcal{V}| = n$ nodes, along with the c dimensional node features $\boldsymbol{X} \in \mathbb{R}^{n \times c}$. Graph Neural Networks (GNNs) learn feature representation for different nodes using neighborhood aggregation schemes, which are formalized as the following **Message-Passing** function:

$$\boldsymbol{H}_u^{(l+1)} = \text{UPDATE}^{(l)} \left(\boldsymbol{H}_u^{(l)}, \text{AGGREGATE}^{(l)} \left(\left\{ \boldsymbol{H}_v^{(l)}, \forall v \in \mathcal{N}(u) \right\} \right) \right), \tag{1}$$

where $\boldsymbol{H}^{(l+1)} \in \mathbb{R}^{n \times d}$ is the node features computed after l-steps of the GNN simplified as follows: $\boldsymbol{H}^{(l+1)} = \text{GNN}^{(l)}(\boldsymbol{H}^{(l)}, \boldsymbol{A}^{(l)})$, UPDATE and AGGREGATE are arbitrary differentiable functions, $\mathcal{N}(u)$ denotes a set of neighboring nodes of u, and $\boldsymbol{H}_u^{(1)}$ is initialized as the input node features $\boldsymbol{X}_u$.

Graph Pooling   While message-passing functions can produce a set of node representations, we need additional READOUT function to obtain the entire graph representation $\boldsymbol{h}_G \in \mathbb{R}^d$ as follows:

$$\boldsymbol{h}_G = \text{READOUT} \left(\{ \boldsymbol{H}_v \mid v \in \mathcal{V} \} \right). \tag{2}$$

As a READOUT function, we can simply use the average or sum over all node features $\boldsymbol{H}_v, \forall v \in \mathcal{V}$ from the given graph (Atwood & Towsley, 2016; Xu et al., 2019). However, since such aggregation schemes take all node information equally without considering the graph structures, they lose structural information that is necessary for accurately representing a graph. To tackle this limitation,

Node Drop methods (Gao & Ji, 2019; Lee et al., 2019b) select the high scored nodes $\boldsymbol{i}^{(l+1)} \in \mathbb{R}^{n_{l+1}}$ with learnable score function s at layer l, to drop the unnecessary nodes, denoted as follows:

$$\boldsymbol{y}^{(l)} = s(\boldsymbol{H}^{(l)}, \boldsymbol{A}^{(l)}); \quad \boldsymbol{i}^{(l+1)} = \text{top}_k(\boldsymbol{y}^{(l)}), \tag{3}$$

where function s depends on specific implementation, and top_k function samples the top k nodes by dropping nodes with low scores $\boldsymbol{y}^{(l)} \in \mathbb{R}^{n_l}$. Whereas **Node Clustering** methods (Ying et al., 2018; Bianchi et al., 2019) learn cluster assignment matrix $\boldsymbol{C}^{(l)} \in \mathbb{R}^{n_l \times n_{l+1}}$ with the node features $\boldsymbol{H}^{(l)} \in \mathbb{R}^{n_l \times d}$, to coarsen the nodes and the adjacency matrix $\boldsymbol{A}^{(l)} \in \mathbb{R}^{n_l \times n_l}$ at layer l as follows:

$$\boldsymbol{H}^{(l+1)} = \boldsymbol{C}^{(l)^T} \boldsymbol{H}^{(l)}; \quad \boldsymbol{A}^{(l+1)} = \boldsymbol{C}^{(l)^T} \boldsymbol{A}^{(l)} \boldsymbol{C}^{(l)}, \tag{4}$$

where generating an assignment matrix $\boldsymbol{C}^{(l)}$ depends on specific implementation. While these two approaches obtain decent performance on graph classification tasks, they are suboptimal since node drop methods unnecessarily drop arbitrary nodes, and node clustering methods have limited scalability to large graphs (Cangea et al., 2018; Lee et al., 2019b). Therefore, we need a sophisticated graph pooling layer that coarsens the graph with sparse implementation without discarding nodes.

3.2 Graph Multiset Transformer

We now describe the *Graph Multiset Transformer* (GMT) architecture, which can accurately represent the entire graph, given a multiset of node features. We first introduce a multiset encoding scheme that allows to embed two different graphs into distinct embeddings. Then we further describe the graph multi-head attention that reflects the graph topology in the attention-based multiset encoding, to compress the elements of a multiset while considering their structural dependencies.

Multiset Encoding The input of the graph pooling function READOUT consists of nodes in a graph, and they form a multiset (i.e. a set which allows for repeating elements) since different nodes can have identical feature vectors. To design a graph pooling function that is as powerful as the WL test, it needs to satisfy the permutation invariance and injectiveness over the multiset, since two non-isomorphic graphs should be embedded differently through the injective function. While the simple sum pooling satisfies the injectiveness over a multiset (Xu et al., 2019), it may treat all node embeddings equally without consideration of their relevance to the task. To resolve this issue, we consider attention mechanism on the multiset pooling function to capture structural dependencies among nodes within a graph, in which we can provably enjoy the expressive power of the WL test.

Graph Multi-head Attention To overcome the inability of simple pooling methods (e.g. sum) on distinguishing important nodes, we use the attention mechanism as the main component in our pooling scheme. Assume that we have n node vectors, then the input of the *attention function* (Att) consists of query $\boldsymbol{Q} \in \mathbb{R}^{n_q \times d_k}$, key $\boldsymbol{K} \in \mathbb{R}^{n \times d_k}$ and value $\boldsymbol{V} \in \mathbb{R}^{n \times d_v}$. Then we compute the dot product of the query with all keys, to put more weights on the relevant values, namely nodes, as follows: $\text{Att}(\boldsymbol{Q}, \boldsymbol{K}, \boldsymbol{V}) = w(\boldsymbol{Q}\boldsymbol{K}^T)\boldsymbol{V}$, where w is an activation function. Instead of computing a single attention, we can further use a multi-head attention (Vaswani et al., 2017), by linearly projecting the query $\boldsymbol{Q}$, key $\boldsymbol{K}$, and value $\boldsymbol{V}$ h times respectively to yield h different representation subspaces. The output of the *multi-head attention function* (MH) then can be denoted as follows:

$$\text{MH}(\boldsymbol{Q}, \boldsymbol{K}, \boldsymbol{V}) = (O_1, ..., O_h)\boldsymbol{W}^O; \quad O_i = \text{Att}(\boldsymbol{Q}\boldsymbol{W}_i^Q, \boldsymbol{K}\boldsymbol{W}_i^K, \boldsymbol{V}\boldsymbol{W}_i^V), \tag{5}$$

where the operations for h parallel projections are parameter matrices $\boldsymbol{W}_i^Q \in \mathbb{R}^{d_k \times d_k}$, $\boldsymbol{W}_i^K \in \mathbb{R}^{d_k \times d_k}$ and $\boldsymbol{W}_i^V \in \mathbb{R}^{d_v \times d_v}$. Also, the output projection matrix is $\boldsymbol{W}^O \in \mathbb{R}^{hd_v \times d_{model}}$.

While multi-head attention is superior to trivial pooling methods such as sum or mean, as it considers global dependencies among nodes, it can not reflect the graph structures (See Figure 1, right). Therefore, we newly define a novel *graph multi-head attention block* (GMH) to consider the graph structure into account. Formally, given node features $\boldsymbol{H} \in \mathbb{R}^{n \times d}$ with their adjacency information $\boldsymbol{A}$, we construct the key and value using GNNs, to explicitly leverage the graph structure as follows:

$$\text{GMH}(\boldsymbol{Q}, \boldsymbol{H}, \boldsymbol{A}) = (O_1, ..., O_h)\boldsymbol{W}^O; O_i = \text{Att}(\boldsymbol{Q}\boldsymbol{W}_i^Q, \text{GNN}_i^K(\boldsymbol{H}, \boldsymbol{A}), \text{GNN}_i^V(\boldsymbol{H}, \boldsymbol{A})). \tag{6}$$

Graph Multiset Pooling with Graph Multi-head Attention Using the ingredients above, we now propose a graph pooling function that satisfies the injectiveness and permutation invariance, such that overall architecture can be at most as powerful as the WL test, while taking the graph structure into account. Note that constructing the multiset encoding function with all nodes is problematic in terms of memory efficiency since a graph can have a large number of nodes. Therefore,

Figure 2: **Graph Multiset Transformer.** Given a graph passed through several message passing layers, we use an attention-based pooling block (GMPool) and a self-attention block (SelfAtt) to compress the all nodes into few important nodes and consider the interaction among them respectively, within a multiset framework.

given node features $\boldsymbol{H} \in \mathbb{R}^{n \times d}$ from GNNs, we define a *Graph Multiset Pooling* (GMPool), which is inspired by the Transformer (Vaswani et al., 2017; Lee et al., 2019a), to compress the n nodes into the k typical nodes with learnable seed vectors $\boldsymbol{S} \in \mathbb{R}^{k \times d}$ as follows (Figure 2-GMPool):

$$\text{GMPool}_k(\boldsymbol{H}, \boldsymbol{A}) = \text{LN}(\boldsymbol{Z} + \text{rFF}(\boldsymbol{Z})); \quad \boldsymbol{Z} = \text{LN}(\boldsymbol{S} + \text{GMH}(\boldsymbol{S}, \boldsymbol{H}, \boldsymbol{A})), \quad (7)$$

where rFF is any row-wise feedforward layer that processes each individual row independently and identically, and LN is a layer normalization (Ba et al., 2016). Note that the output of the GMPool is a set of k vectors, such that we can condense the all nodes into the set of k nodes. Also, since we should obtain the one feature vector to represent each graph, we set $k = 1$ in the final layer of our overall pooling architectures. Intuitively, feature aggregation using attention is beneficial in the extreme case $k = 1$ because the influence of each instance on the target task is not necessarily equal.

Self-Attention for Inter-node Relationship While previously described GMPool condenses the set of entire nodes into k representative nodes, a major drawback of this scheme is that it does not consider the relationships between nodes in the given set, which limits its ability to accurately represent the graph structure. To tackle this limitation, one should further consider the interactions among n or condensed k different nodes. To this end, we propose a *Self-Attention function* (SelfAtt), inspired by the Transformer (Vaswani et al., 2017; Lee et al., 2019a), as follows (Figure 2-SelfAtt):

$$\text{SelfAtt}(\boldsymbol{H}) = \text{LN}(\boldsymbol{Z} + \text{rFF}(\boldsymbol{Z})); \quad \boldsymbol{Z} = \text{LN}(\boldsymbol{H} + \text{MH}(\boldsymbol{H}, \boldsymbol{H}, \boldsymbol{H})). \quad (8)$$

Overall Architecture We now describe the full structure of *Graph Multiset Transformer* (GMT) consisting of GNN and pooling layers using ingredients above (See Figure 2). For a graph G with node features $\boldsymbol{X}$ and an adjacency matrix $\boldsymbol{A}$, the Encoder : $G \mapsto \boldsymbol{H} \in \mathbb{R}^{n \times d}$ is denoted as follows:

$$\text{Encoder}(\boldsymbol{X}, \boldsymbol{A}) = \text{GNN}_2(\text{GNN}_1(\boldsymbol{X}, \boldsymbol{A}), \boldsymbol{A}), \quad (9)$$

where we can stack several GNNs to construct the deep structures. After obtaining a set of node features $\boldsymbol{H}$ from an encoder, the pooling layer aggregates the features into a single vector form; Pooling : $\boldsymbol{H}, \boldsymbol{A} \mapsto \boldsymbol{h}_G \in \mathbb{R}^d$. To deal with a large number of nodes, we first condense the entire graph into k representative nodes with *Graph Multiset Pooling* (GMPool) which is also adaptable to the varying size of nodes, and then utilize the interaction among them with *Self-Attention Block* (SelfAtt). Finally, we get the entire graph representation by using GMPool with $k = 1$ as follows:

$$\text{Pooling}(\boldsymbol{H}, \boldsymbol{A}) = \text{GMPool}_1(\text{SelfAtt}(\text{GMPool}_k(\boldsymbol{H}, \boldsymbol{A})), \boldsymbol{A}'), \quad (10)$$

where $\boldsymbol{A}' \in \mathbb{R}^{k \times k}$ is the identity or coarsened adjacency matrix since adjacency information should be adjusted after compressing the nodes from n to k with GMPool$_k$ (See Appendix B for detail).

3.3 Connection with Weisfeiler-Lehman Graph Isomorphism Test

Weisfeiler-Lehman (WL) test (Weisfeiler & Leman, 1968) is known for its ability to efficiently distinguish two different graphs. Recent studies (Morris et al., 2019; Xu et al., 2019) show that GNNs can be made to be as powerful as the WL test, by using an injective function over a multiset to map two different graphs into distinct spaces. Building on previous powerful GNNs, if our graph pooling function is injective, then our overall architecture can be at most as powerful as the WL test. To do so, we first recount the theorem from Xu et al. (2019), as formalized in Theorem 1.

Theorem 1 (Non-isomorphic Graphs to Different Embeddings). *Let $\mathcal{A} : \mathcal{G} \to \mathbb{R}^d$ be a GNN, and Weisfeiler-Lehman test decides two graphs $G_1 \in \mathcal{G}$ and $G_2 \in \mathcal{G}$ as non-isomorphic. Then, $\mathcal{A}$ maps two different graphs G_1 and G_2 to distinct vectors if node aggregation and update function are injective, and graph-level readout, which operates on a multiset of node features $\{\boldsymbol{H}_i\}$, is injective.*

Since we focus on the representation of graphs through pooling, we deal with the injectiveness of the READOUT function. Our next Lemma 2 states that GMPool can represent the injective function.

Lemma 2 (Uniqueness on Graph Multiset Pooling). *Assume the input feature space $\mathcal{H}$ is a countable set. Then the output of the $GMPool_k^i(\boldsymbol{H}, \boldsymbol{A})$ with $GMH(\boldsymbol{S}_i, \boldsymbol{H}, \boldsymbol{A})$ for a seed vector $\boldsymbol{S}_i$ can be unique for each multiset $\boldsymbol{H} \subset \mathcal{H}$ of bounded size. Further, the output of the full $GMPool_k(\boldsymbol{H}, \boldsymbol{A})$ constructs a multiset with k elements, which are also unique on the input multiset $\boldsymbol{H}$.*

All proofs regarding the WL test are provided in Appendix A.1. Moreover, our next Proposition 3 states that the sequence of GMPool and SelfAtt with proper GNN is as powerful as the WL test.

Proposition 3 (Injectiveness on Pooling Function). *The overall Graph Multiset Transformer with multiple GMPool and SelfAtt can map two different graphs G_1 and G_2 to distinct embedding spaces, such that the resulting GNN with proposed pooling functions can be as powerful as the WL test.*

3.4 CONNECTION WITH NODE CLUSTERING APPROACHES

Node clustering is widely used for coarsening a given graph in a hierarchical manner, as described in the equation 4. However, since they require to store and even multiply the adjacency matrix $\boldsymbol{A}$ with the soft assignment matrix $\boldsymbol{C}$: $\boldsymbol{A}^{(l+1)} = \boldsymbol{C}^{(l)^T} \boldsymbol{A}^{(l)} \boldsymbol{C}^{(l)}$, they need a quadratic space $\mathcal{O}(n^2)$ for n nodes, which may be problematic for large graphs (Cangea et al., 2018; Lee et al., 2019b). On the other hand, our Graph Multiset Pooling (GMPool) does not compute a coarsened adjacency matrix $A^{(l+1)}$, such that graph representation learning is possible only with sparse implementation, as formalized in Theorem 4. **All proofs regarding node clustering are provided in Appendix A.2**.

Theorem 4 (Space Complexity of Graph Multiset Pooling). *Graph Multiset Pooling condsense a graph with n nodes to k nodes in $\mathcal{O}(nk)$ space complexity, which can be further optimized to $\mathcal{O}(n)$.*

In spite of this huge strength on space complexity, our GMPool can be further approximated to the node clustering methods by manipulating an adjacency matrix, as formalized in Proposition 5.

Proposition 5 (Approximation to Node Clustering). *Graph Multiset Pooling $GMPool_k$ can perform hierarchical node clustering with learnable k cluster centroids by Seed Vector S in equation 7.*

Note that, contrary to previous node clusterings (Ying et al., 2018; Bianchi et al., 2019), GMPool learns data dependent k cluster centroids that might be more meaningful to capture graph structures.

4 EXPERIMENT

To demonstrate the proposed *Graph Multiset Transformer* (GMT) for accurate graph representation learning, we evaluate it on multiple tasks, including graph classification on 10 benchmark datasets, graph reconstruction of synthetic and molecular graphs, and graph generation of molecular graphs.

4.1 GRAPH CLASSIFICATION

Objective Graph classification task is used to measure the representation power of GNNs, where the goal is to predict the label $\boldsymbol{y}_i \in \mathcal{Y}$ of a given graph $G_i \in \mathcal{G}$, with a mapping function $f : \mathcal{G} \to \mathcal{Y}$. To this end, we use a set of node representations $\{\boldsymbol{H}_v \mid v \in \mathcal{V}\}$ to obtain an entire graph representation $\boldsymbol{h}_G$ that is finally used to classify a graph label $f(G) = \hat{\boldsymbol{y}}$. We then learn it with cross-entropy loss, to minimize the negative log likelihood denoted as follows: $\min \sum_{i=1} -\boldsymbol{y}_i \log \hat{\boldsymbol{y}}_i$.

Datasets Among TU datasets (Morris et al., 2020), we select 6 datasets including 3 datasets (D&D, PROTEINS, and MUTAG) on Biochemical domain, and 3 datasets (IMDB-B, IMDB-M, and COL-LAB) on Social domain with accuracy for evaluation metric. Also, we use 4 molecule datasets (HIV, Tox21, ToxCast, BBBP) from the OGB datasets (Hu et al., 2020) with ROC-AUC for evaluation metric. Statistics are reported in the Table 1, and more details are described in the Appendix C.2.

Models **1) GCN. 2) GIN.** Naive GNN baselines with mean or sum pooling (Kipf & Welling, 2017; Xu et al., 2019). **3) Set2Set.** Set pooling baseline (Vinyals et al., 2016). **4) SortPool. 5) SAGPool. 6) TopKPool.** The methods (Zhang et al., 2018; Lee et al., 2019b; Gao & Ji, 2019) that use the node drop scheme, by dropping nodes with lower scores using learnable scoring functions. **7) DiffPool. 8) MinCutPool.** The methods (Ying et al., 2018; Bianchi et al., 2019) that use the node clustering scheme, by generating a cluster assignment matrix to map a set of nodes into a set of clusters. **9) GMT.** Our proposed Graph Multiset Transformer (See Appendix C.1 for details).

Table 1: **Graph classification results** on validation/test sets. All results are averaged over 10 different runs.

	Biochemical Domain							Social Domain			Win Ratio
	D&D	**PROTEINS**	**MUTAG**	**HIV**	**Tox21**	**ToxCast**	**BBBP**	**IMDB-B**	**IMDB-M**	**COLLAB**	
# graphs	1,178	1,113	188	41,127	7,831	8,576	2,039	1,000	1,500	5,000	-
# classes	2	2	2	2	12	617	2	2	3	3	-
Avg # nodes	284.32	39.06	17.93	25.51	18.57	18.78	24.06	19.77	13.00	74.49	-
GCN	76.17 / 72.05	77.13 / 73.24	76.56 / 69.50	81.27 / 76.81	78.80 / 75.04	65.66 / 60.63	93.35 / 65.47	77.93 / 73.26	54.29 / 50.39	83.08 / 80.59	0% / 0%
GIN	76.85 / 70.79	78.43 / 71.46	**94.44** / 81.39	82.10 / 75.95	78.20 / 73.27	66.29 / 60.83	94.64 / 67.65	78.38 / 72.78	54.04 / 48.13	82.19 / 78.19	10% / 0%
Set2Set	76.32 / 71.94	77.64 / 73.27	79.72 / 69.89	80.07 / 74.70	79.13 / 74.10	66.39 / 59.70	91.89 / 66.79	78.13 / 72.90	54.39 / 50.19	82.34 / 79.55	0% / 0%
SortPool	80.68 / 75.58	77.92 / 73.17	81.33 / 71.94	81.17 / 71.82	75.97 / 69.54	64.26 / 58.69	94.21 / 65.98	77.46 / 72.12	52.95 / 48.18	80.58 / 77.87	0% / 0%
DiffPool	81.33 / 77.56	79.09 / 73.03	87.94 / 79.22	83.16 / 75.64	80.02 / 74.88	69.73 / 62.28	**96.32** / 68.25	77.86 / 73.14	54.77 / **51.31**	81.69 / 78.68	10% / 10%
SAGPool(G)	76.73 / 71.54	77.01 / 72.02	88.11 / 76.78	80.55 / 74.56	77.03 / 71.10	64.05 / 58.91	95.59 / 65.16	78.09 / 72.16	53.73 / 49.47	81.91 / 78.85	0% / 0%
SAGPool(H)	79.56 / 74.72	77.24 / 71.56	86.06 / 73.67	79.21 / 71.44	75.36 / 69.81	64.05 / 58.91	93.05 / 63.94	77.11 / 72.55	53.49 / 50.23	80.55 / 78.03	0% / 0%
TopKPool	78.54 / 73.63	75.47 / 70.48	75.06 / 67.61	79.24 / 72.27	75.06 / 69.39	64.56 / 58.42	93.31 / 65.19	76.12 / 71.58	52.75 / 48.59	79.94 / 77.58	0% / 0%
MinCutPool	81.96 / 78.22	79.23 / 74.72	87.22 / 79.17	83.12 / 75.37	**81.10** / 75.11	69.09 / 62.48	95.99 / 65.97	77.76 / 72.65	54.94 / 51.04	**83.37** / **80.87**	15% / 10%
GMT (Ours)	**82.19** / **78.72**	**80.01** / **75.09**	91.00 / **83.44**	**84.02** / **77.49**	80.91 / **77.30**	**69.77** / **65.44**	95.14 / **68.31**	**78.43** / **73.48**	**55.14** / 50.66	**83.37** / 80.74	**65%** / **80%**

Model	D&D	PROTEINS	BBBP
GMT	**78.72**	**75.09**	**68.31**
w/o message passing	78.06	75.07	65.26
w/o graph attention	78.08	74.50	66.21
w/o self-attention	75.13	74.22	64.53
mean pooling	72.05	73.24	65.47

Table 2: Ablation Study.

Figure 3: Memory efficiency.

(a) Original (b) TopKPool (c) DiffPool (d) MinCutPool (e) GMT

Figure 4: Reconstruction results.

Implementation Details For a fair comparison of baselines (Lee et al., 2019b), we fix the GCN (Kipf & Welling, 2017) as a message passing layer and only change the pooling architecture throughout all models. Also, we evaluate the model performance with a 10-fold cross validation setting following the fair comparison setup (Errica et al., 2020). We set the pooling ratio as 25% in each pooling layer for all models. Detailed experimental settings are described in the Appendix C.2.

Results Table 1 shows that our GMT outperforms most baselines, or achieves comparable performance to the best baseline results. These results demonstrate that our method is simple yet powerful as it only performs a single global operation at the final layer, unlike several baselines that use multiple pooling with a sequence of message passing. To see where the performance improvement comes from, we conduct an **Ablation Study**. Table 2 shows that using graph attention with self-attention helps significantly improve the performances from the mean pooling. Further, the performance of the GMT without GNN layers indicates that our pooling layer well captures the graph multiset structure only with pooling without GNNs. **Efficiency.** While node clustering methods achieve decent performances in Table 1, they are known to suffer from large memory usage since they cannot work with sparse graph implementations. To compare the GPU memory efficiency of GMT with baseline models, we test it on the Erdos-Renyi graphs (Erdős & Rényi, 1960) (See Appendix C.2 for detail setup). Figure 3 shows that our GMT is highly efficient in terms of memory thanks to its compatibility with sparse graphs, making it more practical over memory-heavy pooling baselines.

4.2 GRAPH RECONSTRUCTION

Graph classification, often used as benchmarks for GNNs, does not directly measure the expressiveness of the GNNs since identifying discriminative features may be more important than accurately representing the graph for classification. On the other hand, graph reconstruction more directly quantifies the amount of information about the graph retained by condensed nodes after pooling.

Objective For graph reconstruction, we train an autoencoder to reconstruct the input node features $X \in \mathbb{R}^{n \times c}$ from their pooled representations $X^{pool} \in \mathbb{R}^{k \times c}$. The learning objective to minimize the discrepancy between the original graph X and the reconstructed graph X^{rec} with a cluster assignment matrix $C \in \mathbb{R}^{n \times k}$ is defined as follows: $\min \|X - X^{rec}\|$, where $X^{rec} = CX^{pool}$.

Experimental Setup We first experiment with **Synthetic Graph** that can be represented in a 2-D Euclidean space, such as ring and grid (Bianchi et al., 2019), where the goal is to restore the location of each node from pooled features, with an adjacency matrix. We further experiment with real-world **Molecule Graph** for quantitative evaluation on ZINC datasets (Irwin et al., 2012), which consists of 12K molecular graphs. See Appendix C.3 for the experimental detail including model descriptions.

Results Figure 4 shows the original and the reconstructed graphs for **Synthetic Graph**. The noisy results of baseline models indicate that the condensed node features do not fully capture the original graph structure. Whereas our GMT yields almost perfect reconstruction, which demonstrates that our pooling operation learns meaningful representation without discarding the graph information.

Figure 5: Reconstruction results on ZINC.

Figure 6: Reconstruction examples.

Moreover, Figure 5 shows reconstruction results on **Molecule Graph**, namely ZINC, on which GMT largely outperforms all compared baselines (High score indicates the better, and see Appendix C.3 for the evaluation metrics). With given results, we demonstrate that our GMT can be easily extended to the node clustering schemes, while it is powerful enough to encode meaningful information to reconstruct the graph. For **Qualitative Analysis**, we further visualize the reconstruction examples from ZINC. As shown in Figure 6, GMT yields more calibrated clustering over MinCutPool, capturing the detailed substructure of molecules, which results in the successful reconstruction.

4.3 GRAPH GENERATION

Objective The graph generation task is used to generate a valid graph that satisfies the desired properties, in which graph encoding methods are directly used to improve the graph generation performances. Formally, given a graph G with graph encoding function f, the goal here is to generate a valid graph $\bar{G} \in \mathcal{G}$ of desired property $\boldsymbol{y}$ with graph decoding function g as follows: $\min d(\boldsymbol{y}, \bar{G})$, where $\bar{G} = g(f(G))$. d is a distance metric between the generated graph and desired properties, (e.g. validity for molecule optimization), to guarantee that the graph has them.

Experimental Setup To evaluate the applicability of our model, we experiment on **Molecule Generation** to stably generate the valid molecules with MolGAN (Cao & Kipf, 2018) and **Retrosynthesis** to empower the synthesis performances with Graph Logic Network (GLN) (Dai et al., 2019), by replacing their graph embedding function $f(G)$ to ours. In both experiments, we replace the average pooling to either the MinCutPool or GMT. See Appendix C.4 for more experimental details.

Figure 7: Molecule generation results.

Top-k accuracy		1	3	5	10	20	50
Reaction	GLN	51.41	67.55	74.92	83.48	88.64	92.37
Class	MinCutPool	51.17	67.47	**75.59**	**83.68**	89.31	92.31
Unknown	GMT (Ours)	**51.83**	**68.20**	75.17	83.20	**89.33**	**92.47**
Reaction	GLN	63.53	78.27	84.32	89.51	92.17	93.17
Class	MinCutPool	63.91	79.19	84.76	89.69	92.13	93.23
as Prior	GMT (Ours)	**64.17**	**79.61**	**85.32**	**89.97**	**92.31**	**93.25**

Table 3: Retrosynthesis results.

Results The power of the discriminator distinguishing whether a molecule is real or fake is highly important to create a valid molecule in MolGAN. Figure 7 shows the validity curve on the early stage of MolGAN training for **Molecule Generation**, and the representation power of the GMT significantly leads to the stabilized generation of valid molecules than baselines. Further, Table 3 shows the **Retrosynthesis** results, where we use the GLN as a backbone. Similar to the molecule generation, retrosynthesis with GMT further improves the baseline performances, which suggests that GMT can replace existing pooling methods for improved performance on diverse graph tasks.

5 CONCLUSION

In this work, we pointed out that existing graph pooling approaches either do not consider the task relevance of each node (e.g. sum or mean) or may not satisfy the injectiveness (node drop and clustering methods). To overcome such limitations, we proposed a novel graph pooling method, *Graph Multiset Transformer* (GMT), which not only encodes the given set of node embeddings as a multiset to uniquely embed two different graphs into two distinct embeddings, but also considers both the global structure of the graph and their task relevance in compressing the node features. We theoretically justify that the proposed pooling function is as powerful as the WL test, and can be extended to the node clustering schemes. We validate the proposed GMT on 10 graph classification datasets, and our method outperforms state-of-the-art graph pooling models on most of them. We further show that our method is superior to the existing graph pooling approaches on graph reconstruction and generation tasks, which require more accurate representations of the graph than classification tasks.

REFERENCES

Amir Hosein Khas Ahmadi, Kaveh Hassani, Parsa Moradi, Leo Lee, and Quaid Morris. Memory-based graph networks. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*, 2020.

James Atwood and Don Towsley. Diffusion-convolutional neural networks. In *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 1993–2001, 2016.

Lei Jimmy Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization. *arXiv preprint*, arXiv:1607.06450, 2016.

Filippo Maria Bianchi, Daniele Grattarola, and Cesare Alippi. Spectral clustering with graph neural networks for graph pooling. *arXiv preprint*, arXiv:1907.00481, 2019.

Catalina Cangea, Petar Velickovic, Nikola Jovanovic, Thomas Kipf, and Pietro Liò. Towards sparse hierarchical graph classifiers. *arXiv preprint*, arXiv:1811.01287, 2018.

Nicola De Cao and Thomas Kipf. Molgan: An implicit generative model for small molecular graphs. *arXiv preprint*, arXiv:1805.11973, 2018.

Hanjun Dai, Bo Dai, and Le Song. Discriminative embeddings of latent variable models for structured data. In *Proceedings of the 33nd International Conference on Machine Learning, ICML 2016, New York City, NY, USA, June 19-24, 2016*, volume 48 of *JMLR Workshop and Conference Proceedings*, pp. 2702–2711, 2016.

Hanjun Dai, Chengtao Li, Connor W. Coley, Bo Dai, and Le Song. Retrosynthesis prediction with conditional graph logic network. In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, 8-14 December 2019, Vancouver, BC, Canada*, pp. 8870–8880, 2019.

David Duvenaud, Dougal Maclaurin, Jorge Aguilera-Iparraguirre, Rafael Gómez-Bombarelli, Timothy Hirzel, Alán Aspuru-Guzik, and Ryan P. Adams. Convolutional networks on graphs for learning molecular fingerprints. In *Advances in Neural Information Processing Systems 28: Annual Conference on Neural Information Processing Systems 2015, December 7-12, 2015, Montreal, Quebec, Canada*, pp. 2224–2232, 2015.

Vijay Prakash Dwivedi, Chaitanya K. Joshi, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Benchmarking graph neural networks. *arXiv preprint*, arXiv:2003.00982, 2020.

P. Erdős and A Rényi. On the evolution of random graphs. In *PUBLICATION OF THE MATHEMATICAL INSTITUTE OF THE HUNGARIAN ACADEMY OF SCIENCES*, pp. 17–61, 1960.

Federico Errica, Marco Podda, Davide Bacciu, and Alessio Micheli. A fair comparison of graph neural networks for graph classification. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*, 2020.

Hongyang Gao and Shuiwang Ji. Graph u-nets. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2083–2092. PMLR, 2019.

William L. Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*, pp. 1024–1034, 2017.

Kurt Hornik, Maxwell B. Stinchcombe, and Halbert White. Multilayer feedforward networks are universal approximators. *Neural Networks*, 2(5):359–366, 1989.

Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. *arXiv preprint*, arXiv:2005.00687, 2020.

John J. Irwin, Teague Sterling, Michael M. Mysinger, Erin S. Bolstad, and Ryan G. Coleman. ZINC: A free tool to discover chemistry for biology. *J. Chem. Inf. Model.*, 52(7):1757–1768, 2012.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint*, arXiv:1412.6980, 2014.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*, 2017.

Juho Lee, Yoonho Lee, Jungtaek Kim, Adam R. Kosiorek, Seungjin Choi, and Yee Whye Teh. Set transformer: A framework for attention-based permutation-invariant neural networks. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, pp. 3744–3753, 2019a.

Junhyun Lee, Inyeop Lee, and Jaewoo Kang. Self-attention graph pooling. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 3734–3743. PMLR, 2019b.

Christopher Morris, Martin Ritzert, Matthias Fey, William L. Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*, pp. 4602–4609. AAAI Press, 2019.

Christopher Morris, Nils M. Kriege, Franka Bause, Kristian Kersting, Petra Mutzel, and Marion Neumann. Tudataset: A collection of benchmark datasets for learning with graphs. *arXiv preprint*, arXiv:2007.08663, 2020.

Charles Ruizhongtai Qi, Hao Su, Kaichun Mo, and Leonidas J. Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, pp. 77–85. IEEE Computer Society, 2017a.

Charles Ruizhongtai Qi, Hao Su, Kaichun Mo, and Leonidas J. Guibas. Pointnet: Deep learning on point sets for 3d classification and segmentation. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, pp. 77–85. IEEE Computer Society, 2017b.

R. Ramakrishnan, Pavlo O. Dral, Matthias Rupp, and O. A. von Lilienfeld. Quantum chemistry structures and properties of 134 kilo molecules. *Scientific Data*, 1, 2014.

Martin Simonovsky and Nikos Komodakis. Dynamic edge-conditioned filters in convolutional neural networks on graphs. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, pp. 29–38. IEEE Computer Society, 2017.

Jake Snell, Kevin Swersky, and Richard S. Zemel. Prototypical networks for few-shot learning. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*, pp. 4077–4087, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*, pp. 5998–6008, 2017.

Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*, 2018.

Oriol Vinyals, Samy Bengio, and Manjunath Kudlur. Order matters: Sequence to sequence for sets. In *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016.

Edward Wagstaff, Fabian Fuchs, Martin Engelcke, Ingmar Posner, and Michael A. Osborne. On the limitations of representing functions on sets. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 6487–6494. PMLR, 2019.

B. Yu. Weisfeiler and A. A. Leman. Reduction of a graph to a canonical form and an algebra arising during this reduction. 1968.

Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and Philip S. Yu. A comprehensive survey on graph neural networks. *arXiv preprint*, arXiv:1901.00596, 2019.

Keyulu Xu, Chengtao Li, Yonglong Tian, Tomohiro Sonobe, Ken-ichi Kawarabayashi, and Stefanie Jegelka. Representation learning on graphs with jumping knowledge networks. In *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 5449–5458. PMLR, 2018.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019.

Li Yi, Wang Zhao, He Wang, Minhyuk Sung, and Leonidas J. Guibas. GSPN: generative shape proposal network for 3d instance segmentation in point cloud. In *IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2019, Long Beach, CA, USA, June 16-20, 2019*, pp. 3947–3956. Computer Vision Foundation / IEEE, 2019.

Zhitao Ying, Jiaxuan You, Christopher Morris, Xiang Ren, William L. Hamilton, and Jure Leskovec. Hierarchical graph representation learning with differentiable pooling. In *Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, 3-8 December 2018, Montréal, Canada*, pp. 4805–4815, 2018.

Jiaxuan You, Rex Ying, and Jure Leskovec. Position-aware graph neural networks. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 7134–7143. PMLR, 2019.

Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabás Póczos, Ruslan Salakhutdinov, and Alexander J. Smola. Deep sets. In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, 4-9 December 2017, Long Beach, CA, USA*, pp. 3391–3401, 2017.

Muhan Zhang, Zhicheng Cui, Marion Neumann, and Yixin Chen. An end-to-end deep learning architecture for graph classification. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence, (AAAI-18), the 30th innovative Applications of Artificial Intelligence (IAAI-18), and the 8th AAAI Symposium on Educational Advances in Artificial Intelligence (EAAI-18), New Orleans, Louisiana, USA, February 2-7, 2018*, pp. 4438–4445. AAAI Press, 2018.

Jie Zhou, Ganqu Cui, Zhengyan Zhang, Cheng Yang, Zhiyuan Liu, and Maosong Sun. Graph neural networks: A review of methods and applications. *arXiv preprint*, arXiv:1812.08434, 2018.

A PROOFS

A.1 PROOFS REGARDING WEISFEILER-LEHMAN TEST

We first recount the theorem of (Xu et al., 2019) to define a GNN that is injective over a multiset (Theorem 1). We then prove that the proposed *Graph Multiset Pooling* (GMPool) can map two different graphs to distinct spaces (Lemma 2). Finally, we show that our overall architecture *Graph Multiset Transformer* (GMT) with a sequence of proposed *Graph Multiset Pooling* (GMPool) and *Self-Attention* (SelfAtt) can represent the injective function over the input multiset (Proposition 3).

Theorem 1 (Non-isomorphic Graphs to Different Embeddings). *Let $\mathcal{A} : \mathcal{G} \rightarrow \mathbb{R}^d$ be a GNN, and Weisfeiler-Lehman test decides two graphs $G_1 \in \mathcal{G}$ and $G_2 \in \mathcal{G}$ as non-isomorphic. Then, $\mathcal{A}$ maps two different graphs G_1 and G_2 to distinct vectors if node aggregation and update function are injective, and graph-level readout, which operates on a multiset of node features $\{\boldsymbol{H}_i\}$, is injective.*

Proof. To map the two non-isomorphic graphs to distinct embedding spaces with GNNs, we recount the theorem on Graph Isomorphism Network. See Appendix B of Xu et al. (2019) for detail. $\square$

Lemma 2 (Uniqueness on Graph Multiset Pooling). *Assume the input feature space $\mathcal{H}$ is a countable set. Then the output of the $GMPool_k^i(\boldsymbol{H}, \boldsymbol{A})$ with $GMH(\boldsymbol{S}_i, \boldsymbol{H}, \boldsymbol{A})$ for a seed vector $\boldsymbol{S}_i$ can be unique for each multiset $\boldsymbol{H} \subset \mathcal{H}$ of bounded size. Further, the output of the full $GMPool_k(\boldsymbol{H}, \boldsymbol{A})$ constructs a multiset with k elements, which are also unique on the input multiset $\boldsymbol{H}$.*

Proof. We first state that the GNNs of the Graph Multi-head Attention (GMH) in a GMPool can represent the injective function over the multiset $\boldsymbol{H}$ with an adjacency information $\boldsymbol{A}$, by selecting proper message-passing functions that satisfy the WL test (Xu et al., 2019; Morris et al., 2019), denoted as follows: $\boldsymbol{H}' = \text{GNN}(\boldsymbol{H}, \boldsymbol{A})$, where $\boldsymbol{H}' \subset \mathcal{H}$. Then, given enough elements, a $\text{GMPool}_k^i(\boldsymbol{H}, \boldsymbol{A})$ can express the sum pooling over the multiset $\boldsymbol{H}'$ defined as follows: $\rho(\sum_{\boldsymbol{h} \in \boldsymbol{H}'} f(\boldsymbol{h}))$, where f and ρ are mapping functions (see the proof of PMA in Lee et al. (2019a)).

Since $\mathcal{H}$ is a countable set, there is a mapping from the elements to prime numbers denoted by $p(\boldsymbol{h}) : \mathcal{H} \rightarrow \mathbb{P}$. If we let $f(\boldsymbol{h}) = -\log p(\boldsymbol{h})$, then $\sum_{\boldsymbol{h} \in \boldsymbol{H}'} f(\boldsymbol{h}) = \log \prod_{\boldsymbol{h} \in \boldsymbol{H}'} \frac{1}{p(\boldsymbol{h})}$ which constitutes an unique mapping for every multiset $\boldsymbol{H}' \subset \mathcal{H}$ (see Wagstaff et al. (2019)). In other words, $\sum_{\boldsymbol{h} \in \boldsymbol{H}'} f(\boldsymbol{h})$ is injective. Also, we can easily construct a function ρ, such that $\text{GMPool}_k^i(\boldsymbol{H}, \boldsymbol{A}) = \rho(\sum_{\boldsymbol{h} \in \boldsymbol{H}'} f(\boldsymbol{h})) = \rho(\log \prod_{\boldsymbol{h} \in \boldsymbol{H}'} \frac{1}{p(\boldsymbol{h})})$ is injective function for every multiset $\boldsymbol{H} \subset \mathcal{H}$, where $\boldsymbol{H}'$ is derived from the GNN component in the GMPool; $\boldsymbol{H}' = \text{GNN}(\boldsymbol{H}, \boldsymbol{A})$.

Furthermore, since a GMPool considers multiset elements without any order, it satisfies the permutation invariance condition for the multiset function.

Finally, each GMPool block has k components such that the output of it consists of k elements as follows: $\text{GMPool} = \left\{\text{GMPool}_k^i(\boldsymbol{H}, \boldsymbol{A})\right\}_{i=1}^k$, which allows multiple instances for its elements. Then, since each $\text{GMPool}_k^i(\boldsymbol{H}, \boldsymbol{A})$ is unique on the input multiset $\boldsymbol{H}$, the output of the GMPool that consists of k outputs is also unique on the input multiset $\boldsymbol{H}$. $\square$

Thanks to the universal approximation theorem (Hornik et al., 1989), we can construct such functions p and ρ using multi-layer perceptrons (MLPs).

Proposition 3 (Injectiveness on Pooling Function). *The overall Graph Multiset Transformer with multiple GMPool and SelfAtt can map two different graphs G_1 and G_2 to distinct embedding spaces, such that the resulting GNN with proposed pooling functions can be as powerful as the WL test.*

Proof. By Lemma 2, we know that a *Graph Multiset Pooling* (GMPool) can represent the injective function over the multiset. If we can also show that a *Self-Attention* (SelfAtt) can represent the injective function over the multiset, then the sequence of the GMPool and SelfAtt blocks can satisfy the injectiveness.

Let $\boldsymbol{W}^O$ be a zero matrix in SelfAtt function. $\text{SelfAtt}(\boldsymbol{H})$ then can be approximated to the any instance-wise feed-forward network denoted as follows: $\text{SelfAtt}(\boldsymbol{H}) = \text{rFF}(\boldsymbol{H})$. Therefore, this

rFF is a suitable transformation $\phi : \mathbb{R}^d \to \mathbb{R}^d$ that can be easily constructed over the multiset elements $\boldsymbol{h} \in \boldsymbol{H}$, to satisfy the injectiveness. $\square$

To maximize the discriminative power of the Graph Multiset Transformer (GMT) by satisfying the WL test, we assume that SelfAtt does not consider the interactions among multiset elements, namely nodes. While proper GNN with proposed pooling function can be as powerful as the WL test with this assumption, our experimental results with the ablation study show that the interaction among nodes is significantly important to distinguish the broad class of graphs (See Table 2).

A.2 Proofs regrading Node Clustering

We first prove that the space complexity of the *Graph Multiset Pooling* (GMPool) without GNNs can be approximated to the $\mathcal{O}(n)$ with n nodes (Theorem 4), and then show that GMPool can be easily extended to the Node Clustering approaches with learnable cluster centroids (Proposition 5).

Theorem 4 (Space Complexity of Graph Multiset Pooling). *Graph Multiset Pooling condsense a graph with n nodes to k nodes in $\mathcal{O}(nk)$ space complexity, which can be further optimized to $\mathcal{O}(n)$.*

Proof. Assume that we have key $\boldsymbol{K} \in \mathbb{R}^{n \times d_k}$ and value $\boldsymbol{V} \in \mathbb{R}^{n \times d_v}$ matrices of the Att function in Graph Multi-head Attention (GMH) for the simplicity, which is described in the equation 6. To obtain the weights on the values $\boldsymbol{V}$, we multiply the query $\boldsymbol{Q}$ with key $\boldsymbol{K}$: $\boldsymbol{Q}\boldsymbol{K}^T$, where $\boldsymbol{Q}$ is defined as a seed vector $\boldsymbol{S} \in \mathbb{R}^{k \times d}$ in GMPool function. This matrix multiplication then maps a set of n nodes into a set of k nodes, such that it requires the $\mathcal{O}(nk)$ space complexity. Also, we can further drop the constant term k: $\mathcal{O}(n)$, by properly setting the small k values; $k \ll n$.

The multiplication of the attention weights $\boldsymbol{Q}\boldsymbol{K}^T$ with value $\boldsymbol{V}$ also takes the same complexity, such that the overall space complexity of MGPool is $\mathcal{O}(nk)$, which can be further optimized to $\mathcal{O}(n)$. $\square$

The space complexity of GNNs with sparse implementation tasks the $\mathcal{O}(n + m)$ space complexity, where n is the number of nodes, and m is the number of edges in a graph. Therefore, multiple GNNs followed by our GMPool require the total space complexity of $\mathcal{O}(n + m)$ due to the space complexity of the GNN operations, but it is highly efficient than node clustering methods of $\mathcal{O}(n^2)$ space complexity.

Proposition 5 (Approximation to Node Clustering). *Graph Multiset Pooling $GMPool_k$ can perform hierarchical node clustering with learnable k cluster centroids by Seed Vector S in equation 7.*

Proof. Node clustering approaches are widely used to coarsen a given large graph in a hierarchical manner with several message-passing functions. The core part of the node clustering schemes is to generate a cluster assignment matrix $\boldsymbol{C}$, to coarsen nodes and adjacency matrix as in an equation 4. Therefore, if our Graph Multiset Pooling (GMPool) can generate a cluster assignment matrix $\boldsymbol{C}$, then the proposed GMPool can be approximated to the node clustering approaches.

In the proposed GMPool, query $\boldsymbol{Q}$ is generated from a learnable set of k seed vectors $\boldsymbol{S}$, and key $\boldsymbol{K}$ and value $\boldsymbol{V}$ are generated from node features $\boldsymbol{H}$ with GNNs in the Graph Multi-head Attention (GMH) block, as in an equation 6. In this function, if we decompose the attention function $\text{Att}(\boldsymbol{Q}, \boldsymbol{K}, \boldsymbol{V}) = w(\boldsymbol{Q}\boldsymbol{K}^T)\boldsymbol{V}$ into the dot products of the query with all keys, and the corresponding weighted sum of values, then the first them inherently generates a soft assignment matrix as follows: $\boldsymbol{C} = w(\boldsymbol{Q}\boldsymbol{K}^T)$. Therefore, the proposed GMPool can be easily extended to the node clustering schemes, with the inherently generated cluster assignment matrix; $\boldsymbol{C} = w(\boldsymbol{Q}\boldsymbol{K}^T)$, where one of the proper choices for the activation function w is the softmax function as follows:

$$w(\boldsymbol{Q}\boldsymbol{K}^T)_{i,j} = \frac{\exp(\boldsymbol{Q}_i \boldsymbol{K}_j^T)}{\sum_{n=1}^{k} \exp(\boldsymbol{Q}_n \boldsymbol{K}_j^T)} \tag{11}$$

Furthermore, through the learnable seed vectors $\boldsymbol{S}$, we can learn data dependent k different cluster centroids in an end-to-end fashion. $\square$

Note that, as shown in the section 4.2 of the main paper, the proposed GMPool significantly outperforms the previous node clustering approaches (Ying et al., 2018; Bianchi et al., 2019). This

is because, contrary to them, the proposed GMPool can explicitly learn data dependent k cluster centroids by learnable seed vectors $\boldsymbol{S}$.

B DETAILS FOR GRAPH MULTISET TRANSFORMER COMPONENTS

In this section, we describe the *Graph Multiset Pooling* (GMPool) and *Self-Attention* (SelfAtt), which are the components of the proposed architecture *Graph Multiset Transformer*, in detail.

Graph Multiset Pooling   The core components of the Graph Multiset Pooling (GMPool) is the Graph Multi-head Attention (GMH) that considers the graph structure into account, by constructing the key and value using GNNs, as described in the equation 6. As shown in the Table 2 of the main paper, this graph multi-head attention (GMH; equation 6) significantly outperforms the naive multi-head attention (MH; equation 5). However, after compressing the n nodes into the k nodes with GMPool$_k$, we can not directly perform further GNNs since the original adjacency information is useless after pooling. To tackle this limitation, we can generate the new adjacency matrix $\boldsymbol{A}'$ for the compressed nodes, by performing node clustering as described in Proposition 5 of the main paper as follows:

$$\text{GMPool}_1(\text{GMPool}_k(\boldsymbol{H}, \boldsymbol{A}), \boldsymbol{A}'); \quad \boldsymbol{A}' = \boldsymbol{C}^T \boldsymbol{A} \boldsymbol{C}, \tag{12}$$

where $\boldsymbol{C}$ is the generated cluster assignment matrix, and $\boldsymbol{A}'$ is the coarsened adjacency matrix as described in the equation 4. However, this approach is well known for their scalability issues (Lee et al., 2019b; Cangea et al., 2018), since they require quadratic space $\mathcal{O}(n^2)$ to store and even multiply the adjacency matrix $\boldsymbol{A}$ with the soft assignment matrix $\boldsymbol{C}$. Therefore, we leave doing this as future work, and use the following tricks. By replacing the adjacency matrix $\boldsymbol{A}$ with the identity matrix $\boldsymbol{I}$ in the GMPool except for the first block, we can easily perform multiple GMPools without any constraints, which is approximated to the GMPool with MH (equation 5) rather than GMH (equation 6) as follows:

$$\text{GMPool}_1(\text{GMPool}_k(\boldsymbol{H}, \boldsymbol{A}), \boldsymbol{A}'); \quad \boldsymbol{A}' = \boldsymbol{I}. \tag{13}$$

Self-Attention   The Self-Attention (SelfAtt) function can consider the inter-relationships between nodes in a set, which helps the network to take the global graph structure into account. Because of this advantage, the self-attention function significantly improves the proposed model performance on the graph classification tasks, as shown in the Table 2 of the main paper. From a different perspective, we can treat the Self-Attention function as a graph neural network (GNN) with a complete graph. Specifically, given k nodes from the previous layer, the Multi-head Attention (MH) of the Self-Attention function first constructs the adjacency matrix among all nodes with their similarity, through the matrix multiplication of the query with key: $\boldsymbol{Q}\boldsymbol{K}^T$, then computes the outputs with the sum of the obtained weights on the value. In other words, the self-attention function can be considered as one message passing function with a soft adjacency matrix, which might be further connected to the Graph Attention Network (Velickovic et al., 2018).

C EXPERIMENTAL SETUP

In this section, we first introduce the baselines and our model, and then describe the experimental details about graph classification, reconstruction, and generation tasks respectively.

C.1 BASELINES AND OUR MODEL

1) GCN. This method (Kipf & Welling, 2017) is the mean pooling baseline with Graph Convolutional Network (GCN) as a message passing layer.

2) GIN. This method (Xu et al., 2019) is the sum pooling baseline with Graph Isomorphism Network (GIN) as a message passing layer.

3) Set2Set. This method (Vinyals et al., 2016) is the set pooling baseline that uses recurrent neural network to encode the set of all nodes, with content-based attention over them.

4) SortPool. This method (Zhang et al., 2018) is the node drop baseline that drops unimportant nodes by sorting their representation, which is directly generated from the previous GNN layers.

Figure 8: **Illustration of High-level Model Architectures (Top):** Global Graph Classification; GCN, GIN, Set2Set, SortPool, SAGPool(G), GMT. **(Middle:)** Hierarchical Graph Classification; DiffPool, SAGPool(H), TopKPool, MinCutPool. **(Bottom:)** Graph Reconstruction; DiffPool, TopKPool, MinCutPool, GMT. MP denotes the message passing layer.

5) DiffPool. This method (Ying et al., 2018) is the node clustering baseline that produces the hierarchical representation of the graphs in an end-to-end fashion, by clustering similar nodes into the few nodes through graph convolutional layers.

6) SAGPool. This method (Lee et al., 2019b) is the node drop baseline that selects the important nodes, by dropping unimportant nodes with lower scores that is generated by the another graph convolutional layer. Particularly, this method has two variants. **6.1) SAGPool(G)** is the global node drop method that drops unimportant nodes one time at the end of their architecture. **6.2) SAGPool(H)** is the hierarchical node drop method that drops unimportant nodes sequentially with multiple graph convolutional layers.

7) TopkPool. This method (Gao & Ji, 2019) is the node drop baseline that selects the top-ranked nodes using a learnable pooling function.

8) MinCutPool. This method (Bianchi et al., 2019) is the node clustering baseline that applies the spectral clustering with GNNs, to coarsen the nodes and the adjacency matrix of a graph.

9) GMT. Our proposed Graph Multiset Transformer that first condenses all nodes into the important nodes by GMPool, and then considers interaction between nodes in a set. Since in operates on the global READOUT layer, it can be coupled with any pooling methods by replacing their last layer.

C.2 GRAPH CLASSIFICATION

Dataset Among TU datasets (Morris et al., 2020), we select the 6 datasets including 3 datasets (D&D, PROTEINS, and MUTAG) on Biochemical domain, and 3 datasets (IMDB-B, IMDB-M, and COLLAB) on Social domain. We use the classification accuracy as an evaluation metric. As suggested by Errica et al. (2020) for a fair comparison, we use the one-hot encoding of their atom types as initial node features in the bio-chemical datasets, and the one-hot encoding of node degrees as initial node features in the social datasets. Moreover, we use the recently suggested 4 molecule graphs (HIV, Tox21, ToxCast, BBBP) from the OGB datasets (Hu et al., 2020). We use the ROC-AUC for an evaluation metric, and use the additional node features, as suggested by (Hu et al., 2020). Dataset statistics are reported in the Table 1 of the main paper.

Implementation Details on Classification Experiments In the all experiments, we evaluate the model performance with a 10-fold cross validation setting, where we use the 10 percent of the training data as a validation data following the fair comparison setup (Errica et al., 2020). We use the early stopping criterion, where we stop the training if there is no further improvement on the validation loss during 50 epochs. Further, the maximum number of epochs is set to 500. We then report the average performances on the validation and test sets, by performing overall experiments 10 times with 10 different seeds.

(a) Original	(b) Top-K	(c) DiffPool	(d) MinCutPool	(e) GMT

Figure 9: High resolution image for synthetic graph reconstruction results in Figure 4.

For all experiments except D&D dataset, the learning rate is set to 5×10^{-4}, hidden size is set to 128, batch size is set to 128, weight decay is set to 1×10^{-4}, and dropout rate is set to 0.5. Since D&D dataset has a large number of nodes (See Table 1 in the main paper), node clustering methods can not perform clustering operations on large graphs with large batch size, such that the hidden size is set to 32, and batch size is set to 10 on D&D dataset. Then we optimize the network with Adam optimizer (Kingma & Ba, 2014). For a fair comparison of baselines (Lee et al., 2019b), we use the three GCN layers (Kipf & Welling, 2017) as a message passing function for all models with jumping knowledge strategies (Xu et al., 2018), and only change the pooling architecture throughout all models, as illustrated in Figure 8. Also, we set the pooling ratio as 25% in each pooling layer for both baselines and our models.

Implementation Details on Efficiency Experiments   To compare the GPU memory efficiency of GMT with baseline models including node drop and node clustering methods, we first generate the Erdos-Renyi graphs (Erdős & Rényi, 1960) by varying the number of nodes n, where edge sizes m are twice the number of nodes: $m = 2n$. For all models, we compress the given n nodes into the $k = 4$ nodes at the first pooling function.

C.3   GRAPH RECONSTRUCTION

Dataset   We first experiment with synthetic graphs represented in a 2-D Euclidean space, such as ring and grid structures. The node features of a graph consist of their location in a 2-D coordinate space, and the adjacency matrix indicates the connectivity information of nodes. The goal here is to restore all node locations from compressed features after pooling, with the intact adjacency matrix.

While synthetic graphs are appropriate choices for the qualitative analysis, we further do the quantitative evaluation of models with real-world molecular graphs. Specifically, we use the subset (Dwivedi et al., 2020) of the ZINC dataset (Irwin et al., 2012) that consists of 12K real-world molecular graphs, to further conduct a graph reconstruction on the large number of various graphs. The goal of the molecule reconstruction task is to restore the exact atom types of all nodes in the given graph, from the compressed representations after pooling.

Common Implementation Details   Following (Bianchi et al., 2019), we use the two message passing layers right before the pooling operation and right after the unpooling operation. Also, both pooling and unpooling operations are performed once and sequentially connected, as illustrated in the Figure 8. We compare our methods against both the node drop (TopKPool (Gao & Ji, 2019)) and node clustering (DiffPool (Ying et al., 2018) and MinCutPool (Bianchi et al., 2019)) methods. For the node drop method, we use the unpooling operation proposed in the graph U-net (Gao & Ji, 2019). For the node clustering methods, we use the graph coarsening schemes described in the equation 4 with their specific implementation on generating an assignment matrix. In our proposed Graph Multiset Transformer (GMT), we follow the node clustering approaches as described in the subsection 3.4, by generating the single soft assignment matrix from GMPool with one head $h = 1$ in the multi-head attention function. For experiments of both synthetic and molecule reconstructions,

the learning rate is set to 5×10^{-3}, hidden size is set to 32. We then optimize the network with Adam optimizer (Kingma & Ba, 2014).

Implementation Details on Synthetic Graph   We set the compression ratio (pooling ratio) of all models as 25% on synthetic graph reconstruction. For the design of the loss function, we use the Mean Squared Error (MSE) to train the models. We use the early stopping criterion, where we stop the training if there is no further improvement on the training loss during 1,000 epochs. Further, the maximum number of epochs is set to 10,000. Note that, there is no other available graphs for validation of the synthetic graph, such that we train and test the models only with the given graph in the Figure 9. The baseline results are adopted from (Bianchi et al., 2019).

Implementation Details on Molecule Graph   We set the compression ratio (pooling ratio) of all models as 5%, 10%, 15%, and 25% on molecule graph reconstruction, and plot all results in the Figure 5 of the main paper. Note that, in the case of molecule graph reconstruction, softmax layer is appended at the last layer of the model architecture to classify the original atom types of all nodes. For the design of the loss function, we use the cross entropy loss to train the models. We use the early stopping criterion, where we stop the training if there is no further improvement on the validation loss during 50 epochs. Further, the maximum number of epochs is set to 500 and batch size is set to 128. Note that, in the case of molecule graph reconstruction on ZINC dataset, we strictly separate the training, validation and test sets, as suggested by (Dwivedi et al., 2020).

Evaluation Metrics for Molecule Reconstruction   For quantitative evaluations of the molecule reconstruction, we use the three metrics as follows: *1) validity* indicates the number of reconstructed molecules that are chemically valid, *2) exact match* indicates the number of reconstructed molecules that are exactly same as the original molecules, and *3) accuracy* indicates the classification accuracy of atom types for every nodes.

C.4   GRAPH GENERATION

Common Implementation Details   In the graph generation experiments, we replace the graph embedding function $f(G)$ from existing graph generation models to the proposed Graph Multiset Transformer (GMT), to evaluate the applicability of our model on generation tasks, as described in the subsection 4.3 of the main paper. As baselines, we first use the original models with their implementations. Specifically, we use the MolGAN[1] (Cao & Kipf, 2018) for molecule generation, and Graph Logic Network (GLN)[2] (Dai et al., 2019) for retrosynthesis. For both experiments, we directly follow the experimental details of original papers (Cao & Kipf, 2018; Dai et al., 2019) for a fair comparison. Furthermore, to compare our models with another strong pooling method, we use the MinCutPool (Bianchi et al., 2019) as an additional baseline for generation tasks, since it shows the best performance among baselines in the previous two tasks, namely graph classification and graph reconstruction.

For MinCutPool, since it cannot directly compress the all n nodes into the 1 cluster to represent the entire graph, we use the following tricks to replace the simple pooling operation (e.g. sum or mean) with it. We first condense the graph into the k clusters ($k = 4$) using one MinCutPool layer, and then average the condensed nodes to get a single representation of the given graph. However, our proposed Graph Multiset Transformer (GMT) can directly compress the all n nodes into the 1 node with one learnable seed vector, by using the single $GMPool_1$ block. In other words, we use the one $GMPool_1$ to represent the entire graph by replacing their simple pooling (e.g. sum or mean), in which we use the following softmax activation function:

$$w(\boldsymbol{Q}\boldsymbol{K}^T)_{i,j} = \frac{\exp(\boldsymbol{Q}_i \boldsymbol{K}_j^T)}{\sum_{k=1}^{n} \exp(\boldsymbol{Q}_i \boldsymbol{K}_k^T)} \tag{14}$$

Implementation Details on Molecule Generation   For the molecule generation experiment with the MolGAN, we replace the average pooling in the discriminator with $GMPool_1$. We use the QM9 dataset (Ramakrishnan et al., 2014) following the original MolGAN paper (Cao & Kipf, 2018). To

---

[1] https://github.com/yongqyu/MolGAN-pytorch
[2] https://github.com/Hanjun-Dai/GLN

evaluate the models, we report the validity of 13,319 generated molecules at the early stage of the MolGAN training, over 4 different runs. As depicted in Figure 7 of the main paper, each solid curve indicates the average validity of each model with 4 different random seeds, and the shaded area indicates the half of the standard deviation for 4 different runs.

Implementation Details on Retrosynthesis For the retrosynthesis experiment with the Graph Logic Network (GLN), we replace the average pooling in the template and subgraph encoding functions with $GMPool_1$. We use the USPTO-50k dataset. For an evaluation metric, we use the Top-k accuracy for both reaction class is not given and given cases following the convention of the original paper (Dai et al., 2019), and reproduce the all results in Table 3 with published codes from the original paper.

D ADDITIONAL EXAMPLES FOR MOLECULE RECONSTRUCTION

Figure 10: **Molecule Reconstruction Examples (Left):** Original Molecules with the assigned cluster for each node, which is generated from *Graph Multiset Pooling* (GMPool), and represented as color. **(Right):** Reconstructed Molecules. Red dotted circle indicates the incorrect atom prediction.