GrapNet: A Dynamic-Architecture Graph Neural Network Substrate

Abstract

Graph neural networks made graph-as-data a standard modeling primitive. GrapNet studies the complementary graph-as-network setting: the graph is the neural architecture and executable program. The interface is vector-valued rather than modality-specific: any upstream module that emits a representation vector–a dense layer, CNN encoder, ResNet feature extractor, or transformer token representation–can instantiate one sensory GrapNode per coordinate. Each current-layer compute node then owns its next-layer child references and a trainable allocation vector aligned with those references. Deleting a relation physically removes both the child reference and the corresponding allocation coordinate; adding a relation appends both. Structural rules and execution policies live outside the node core, so the same child-owned graph can be trained through a reference path, grouped into trainable family blocks, routed by attention over active relations, and lowered to dense or compiled views after topology stabilizes. In a matched ten-seed Split Fashion-MNIST study, a plastic GrapNet+ER head reaches 63.16% seen-class accuracy versus 51.08% for a parameter-larger dense MLP+ER under the same seen-class loss and replay memory (paired $\Delta = 12.08$ points, $p = 1.3\times10^{-5}$), while matching task-local accuracy. On Split CIFAR-10 using a frozen ImageNet ResNet-18 encoder, the same head improves seen-class accuracy over a dense MLP-256 replay head by 3.81 points ($p = 0.0026$). On two non-image UCI tabular tasks, covariance-driven structure editing preserves accuracy while deleting 22.9–32.1% of child relations and one third of hidden nodes. A ten-seed structural localization audit shows that cutting task-owned child relations drops the owning task by 48.26 points while leaving non-target tasks unchanged. An attention execution-policy audit matches a dense attention reference exactly in forward and gradient checks before and after relation deletion. The results support dynamic-architecture graph neural networks as editable neural programs with efficient execution views.

1 Introduction

GNNs treat a graph as an input object and learn shared neural functions over its nodes and edges. GrapNet treats a graph as the neural network itself. This dynamic-architecture graph neural network setting needs a different ownership invariant:

topology edits must change the executable program, remain visible to training rules, and still admit efficient tensor backends. Dense tensors are an excellent execution format and a poor ownership model for that setting. A masked weight can be disabled, but the rectangular slot, optimizer state, and global tensor layout still remain. A hand-edited module can add or remove Python objects, but relation semantics then spread across module lists, parameter surgery, optimizer refreshes, and execution special cases.

GrapNet addresses this mismatch by storing the network as a child-owned computation graph. For a transition from layer l to layer $l + 1$, every current-layer GrapNode owns a list of next-layer child references and a trainable allocation vector W_{alloc} aligned with that list:

$$\texttt{node.children}[k] \leftrightarrow \texttt{node.W\_alloc}[0, k].$$

The relation is the paired child reference and allocation coordinate. Removing slot k removes both. Adding a relation appends both. Dense, sparse, family-block, and compiled tensors are execution views reconstructed from this canonical object.

GrapNet composes with conventional neural modules rather than replacing them. It does not require raw pixels or hand-designed scalar inputs. Any vector-producing parent interface can feed the sensory layer: a fully connected layer, a convolutional encoder, a frozen ResNet feature extractor, a pooled transformer representation, or an attention module output. The vector coordinates are read in parallel by sensory GrapNodes, one coordinate per sensory node. The relationship is stronger for MLPs: a dense MLP is recovered exactly by choosing a fully connected child-owned topology. Thus the position-wise FFN inside a Transformer block can be instantiated as a GrapNet block while self-attention remains the token-mixing operator. The contribution is the editable child-owned relation structure exposed at or after these vector interfaces.

The paper makes three claims. First, child ownership gives neural topology a stable edit invariant: relation deletion, node deletion, optimizer refresh, and downstream continuity become explicit operations on the graph. Second, placing structural rules outside the GrapNode core makes growth, freezing, pruning, covariance sifting, and replay controllers composable without changing node semantics. Third, execution can follow topology state: the editable graph trains through

live family-vectorized blocks while stable graphs can be lowered to dense or compiled endpoints.

The contribution is therefore not a new pruning score, a task router, or a new replay buffer. It is a representation boundary: the graph object stores the editable neural program, and policies decide how that program is grown, frozen, simplified, routed, and executed. This boundary is useful only if it survives ordinary learning comparisons. The experiments therefore use matched replay streams, seen-class losses, parameter accounting, and head-only visual-feature comparisons rather than relying on task-ID routing or isolated structural demonstrations.

The empirical section is organized around those claims. The main online continual-learning comparison uses a matched seen-class protocol: dense and GrapNet heads see the same Split Fashion-MNIST stream, the same replay memory, and the same cross-entropy over classes seen so far. Under this protocol, a plastic GrapNet head improves global seen-class calibration over dense replay heads with more parameters, while preserving task-local accuracy. A frozen GrapNet variant locks previous hidden nodes and exposes the expected trade-off: lower structural drift and lower global plasticity. A second study uses a frozen ImageNet ResNet-18 encoder on Split CIFAR-10 and trains only the online head, verifying the general vector-interface claim for conventional visual features. A non-image tabular study keeps one sensory node per scalar feature and uses covariance to prune deep shared subgraphs, delete hidden nodes, and rebuild execution families. A structural localization audit then cuts task-owned child relations and measures the resulting task-specific accuracy drop. Execution experiments show that trainable family blocks are a faithful dynamic backend for the same canonical graph.

2   Related Work

Editable and sparse neural structure. Pruning masks, lottery-ticket subnetworks, dynamic sparse training, and PackNet-style task allocation operate over tensorized models (Mallya and Lazebnik 2018; Frankle and Carbin 2019; Evci et al. 2020; Lasby et al. 2023). GrapNet starts from the opposite side: the editable node-owned relation is canonical, and tensor forms are backend choices. The distinction matters for structural rules because a removed child relation is gone from storage, gradient flow, and subsequent execution views.

Continual learning and dynamic architecture. Continual learning methods use regularization, replay, expansion, masking, distillation, and routing to preserve old competence (Kirkpatrick et al. 2017; Zenke, Poole, and Ganguli 2017; Rusu et al. 2016; Yoon et al. 2018; Serra et al. 2018; Chaudhry et al. 2019; Buzzega et al. 2020; Prabhu et al. 2020; Boschini et al. 2023). Architecture itself is now recognized as an active variable in continual learning (Mirzadeh et al. 2022; Douillard et al. 2022; Wang et al. 2022; Wang, Zhang, Su, and Zhu 2024). GrapNet contributes a representation substrate for those variables: growth and freezing are external structural policies over child-owned nodes, while replay remains an external sample-memory controller.

Graph computation and ML systems. PyG and DGL implement *graphs as data*: the graph is an input object whose nodes and edges carry features, while learned message functions are shared over that input graph (Fey and Lenssen 2019; Wang et al. 2019). GrapNet implements *graphs as network*: the graph is the neural program whose nodes own parameters, activations, child references, and execution-relevant relation slots. The same word "graph" therefore denotes different abstraction levels. GNN libraries are natural backends or modeling tools for data graphs; GrapNet addresses the storage and edit semantics of the model graph itself.

Attention mechanisms use input-dependent routing as a core computational pattern (Vaswani et al. 2017). GrapNet realizes this pattern as an execution policy over active child-owned relations rather than as a replacement for canonical topology. Modern ML systems also separate flexible programs from optimized execution (Paszke et al. 2019; Ansel et al. 2024). GrapNet applies the separation inside the neural topology: child-owned storage is canonical, and execution policies lower it to scatter, attention-gated relations, trainable family blocks, dense snapshots, or compiled relation kernels.

3   Child-Owned Computation

Canonical Relation Ownership

A GrapNode stores local state (b_u, ϕ_u), next-layer child references $C_u = [v_1, \ldots, v_{d_u}]$, and an aligned allocation vector $W_{alloc}^u = [w_1, \ldots, w_{d_u}]$. The invariant is

$$I(u): \quad |C_u| = |W_{alloc}^u|, \qquad C_u[k] \leftrightarrow W_{alloc}^u[k].$$

Relation deletion at local slot k maps

$$(C_u, W_{alloc}^u) \mapsto (C_u \setminus C_u[k], \ W_{alloc}^u \setminus W_{alloc}^u[k]).$$

Node deletion is a separate graph operation. This keeps pointer deletion, real node deletion, and downstream continuity distinguishable. The invariant also fixes the optimizer-facing semantics. When a relation is added, a new allocation coordinate is a new trainable parameter slot and the optimizer can be refreshed explicitly. When a relation is removed, its coordinate disappears from the canonical parameter set rather than remaining as a masked entry whose state must be tracked separately.

MLPs and Transformer FFNs as Special Cases

The fully connected MLP case follows by direct parameter mapping. Consider a dense layer with input $h \in \mathbf{R}^n$, weight matrix $A \in \mathbf{R}^{n \times m}$, bias $c \in \mathbf{R}^m$, and output activation ϕ_j:

$$q_j = \sum_{i=1}^{n} h_i A_{ij} + c_j, \qquad h_j' = \phi_j(q_j).$$

Instantiate current-layer GrapNodes $u_1, \ldots, u_n$ and next-layer GrapNodes $v_1, \ldots, v_m$. Set

$$C_{u_i} = [v_1, \ldots, v_m], \quad W_{alloc}^{u_i}[j] = A_{ij}, \quad b_{v_j} = c_j.$$

The GrapNet transition then gives

$$\tilde{q}_j = \sum_{i: v_j \in C_{u_i}} h_i W_{alloc}^{u_i}[j] + b_{v_j} = \sum_{i=1}^{n} h_i A_{ij} + c_j = q_j.$$

Figure 1: Child-owned deletion versus matrix masking. A masked dense matrix leaves a disabled relation as a fixed coordinate in the rectangular parameter layout. GrapNet removes both the next-layer reference $C_u[k]$ and the aligned allocation coordinate $W_{alloc}^u[k]$ from the canonical node-owned structure. Tensor views are rebuilt from the remaining physical relations.

Applying the same mapping layer by layer proves that every feed-forward MLP is a GrapNet topology with fully connected child lists. The released equivalence audit copies Py-Torch dense-layer weights into W_{alloc} and biases and reports maximum absolute differences up to 1.2×10^{-7} across linear, ReLU, and GELU MLP settings.

This also covers the Transformer FFN sublayer. For token states $H \in \mathbf{R}^{B \times T \times D}$, a position-wise FFN applies the same MLP F to each token: $Y_{bt} = F(H_{bt})$. Flattening H to $\bar{H} \in \mathbf{R}^{(BT) \times D}$, applying the equivalent GrapNet implementation of F, and reshaping back to $B \times T \times D'$ gives the same FFN values. Self-attention, residual connections, and normalization remain token-mixing and stabilization operators; GrapNet supplies an editable child-owned implementation of the MLP/FFN transformation. A supplemental Tiny Transformer audit copies a standard FFN into GrapNet-FFN and reports FFN forward error 1.2×10^{-7}, Transformer-logit error 6.0×10^{-8}, matched FFN gradients below 7.5×10^{-9}, identical 93.36% test accuracy after matched training, and physical FFN relation deletion from 1024 to 992 active relations.

Forward Semantics

For batch activations $X \in \mathbf{R}^{B \times P}$ and a transition with E active child-owned relations, the reference backend computes

$$Z[b, t(e)] \mathrel{+}= X[b, s(e)] \, w_e,$$

where source $s(e)$ and target $t(e)$ are derived from node-owned child lists. Algebraically this is a sparse linear map $Z = XW + b$, but W is an execution view. The canonical object remains the node-owned relation set.

Rules and Execution Policies

The GrapNode core contains structural fields and local computation. Growth, freezing, pruning, replay control, covariance sifting, and backend selection are external policies. Structural rule managers can inject, replace, enable, and disable rules at runtime. Execution policy managers redirect selected transitions to alternative backends while preserving the callable graph.

Algorithm 1 Child-Owned Transition
1: Input activations X, current nodes U, next nodes V
2: Initialize next buffer Z to zero
3: **for** each current-layer node u_i in U **do**
4:    Read child list C_i and allocation vector W_{alloc}^i
5:    Compute local messages $M_i = X[:, i] W_{alloc}^i$
6:    **for** each local child slot k in C_i **do**
7:       Add $M_i[:, k]$ into child $C_i[k]$
8:    **end for**
9: **end for**
10: Apply next-node bias and activation functions

Trainable family execution is the dynamic fast path. Current-layer nodes with identical next-layer child-reference patterns form an execution family. For family f, member activations form $H_f \in \mathbf{R}^{B \times m_f}$ and live allocation parameters form $W_f \in \mathbf{R}^{m_f \times k_f}$. The backend evaluates

$$M_f = H_f W_f$$

and scatters M_f to the corresponding next-layer targets. Because W_f is assembled from live W_{alloc} parameters, gradients flow back to the child-owned canonical graph. Stable topology can then be lowered to dense snapshots or compiled relation kernels.

Attention is another execution policy over the same relation set. For active relation (i, j), an attention backend can compute

$$a_{bij} = \text{softmax}_{i:(i,j) \in E}(h_{bi} k_i q_j)$$

and

$$z_{bj} = \sum_{i:(i,j) \in E} a_{bij} h_{bi} w_{ij},$$

where E is read from current child lists and w_{ij} is the child-owned allocation coordinate. A structural edit changes both the executable relation set and the attention mask.

These policies are intended to be native drivers rather than post-hoc repairs. The reference scatter path is useful for correctness and debugging; family execution is the dynamic

acceleration path for repeated child patterns during online editing; attention execution adds input-dependent weighting over the same relation set; dense snapshots and compiled kernels are throughput endpoints after topology stabilizes. All of them read from the same child-owned graph.

4 Experiments

All reported studies use released scripts and JSON outputs. Online studies use one pass over five binary tasks $(0, 1), (2, 3), (4, 5), (6, 7), (8, 9)$, replay memory 500 unless stated otherwise, and two metrics: task-local pair accuracy and global seen-class accuracy. The global metric takes an argmax over classes seen so far using a task-free evaluation rule. The matched studies train dense and GrapNet heads with the same cross-entropy over seen classes for both current and replay batches.

The main comparisons are designed to remove common class-incremental confounds. First, no task identity is used for seen-class evaluation; all compared heads score the same accumulated class set. Second, dense and GrapNet runs share the same task order, minibatch stream, replay insertion rule, replay samples, optimizer family, and seeds. Third, parameter counts are reported because structural methods can otherwise win by silently expanding capacity. Fourth, frozen variants are treated as policy ablations, not as the primary class-incremental head: freezing tests structural memory, while plastic replay tests global calibration under the same child-owned substrate.

Matched Split Fashion-MNIST

Table 2 reports the main ten-seed Fashion-MNIST study (Xiao, Rasul, and Vollgraf 2017). Images are downsampled to 7×7 so the study isolates online structure and replay rather than image modeling. Dense ER-256 has more trainable parameters than GrapNet-48. GrapNet plastic keeps previous hidden nodes trainable under replay; GrapNet frozen locks previous hidden nodes after each task. All rows use the same one-pass stream and the same seen-class objective, so the table compares head structure and structural policy rather than a different evaluation loss.

The plastic GrapNet head improves the class-incremental metric while matching task-local accuracy: against dense ER-256 reservoir, the paired seen-class gain is 12.08 points and global forgetting drops by 15.90 points ($p = 8.6 \times 10^{-6}$). Against dense ER-256 balanced replay, the gain is 12.52 points ($p = 1.4 \times 10^{-6}$). The result is not explained by parameter count: GrapNet-48 reports 13.45K trainable parameters versus 15.37K for dense ER-256. It is also not explained by a task-local oracle, because the decisive metric is the task-free argmax over all classes seen so far.

The frozen-policy ablation identifies the structural-memory operating point. Freezing previous hidden nodes keeps task-local accuracy high but lowers the global seen-class metric because old hidden subgraphs cannot recalibrate logits as new classes arrive. Keeping them plastic under replay is the effective class-incremental head. GrapNet makes this distinction explicit: freezing is a structural policy over node ownership, while replay and seen-class CE remain ordinary learning policies over the same graph.

CIFAR-10 with a Frozen ResNet Encoder

The second study tests encoder composition on CIFAR-10 (Krizhevsky 2009). A torchvision ResNet-18 with ImageNet weights (He et al. 2016) is frozen and maps each image to a 512-dimensional feature vector. The encoder is shared by all methods and is never updated during the online stream; only the head is trained. Thus the comparison isolates whether a child-owned head can use conventional visual features more effectively than dense heads under the same replay and seen-class loss. Table 3 reports five seeds.

The CIFAR result confirms the vector-valued sensory interface. Each encoder coordinate feeds one GrapNet sensory node, and child-owned growth builds an editable head on top. The plastic GrapNet head improves seen-class accuracy over the parameter-larger MLP-256 head while also slightly improving task-local accuracy. The frozen-policy pattern matches Fashion-MNIST: structural locking is available, while the plastic head is the better global seen-class evaluator under replay. This also clarifies the role of convolutional models in GrapNet: the experiment uses a conventional ResNet as the upstream visual module and applies child ownership after its output vector. Convolutional kernels can be viewed as local shared-weight relation aggregation between feature maps, but rewriting the visual encoder is unnecessary for CNN-backed use; the eye can remain a mature convolutional module while GrapNet supplies the editable downstream structure. Dense MLP heads and Transformer FFNs are still closer: by the mapping above, they are fully connected GrapNet special cases.

Tabular Covariance Structure Editing

The third study moves outside image classification. We use the Breast Cancer and Wine tabular datasets from scikit-learn (Pedregosa et al. 2011). Each standardized scalar feature enters through exactly one sensory GrapNode, so the input layer has 30 sensory nodes for Breast Cancer and 13 for Wine. The graph contains three hidden layers organized as shared-child execution families. During training, a covariance rule computes $|\mathrm{corr}(h_i, h'_j)|$ on training activations, removes the weakest child targets from each family, deletes hidden nodes that become zero-incoming, rebuilds the family backend, and continues training.

Table 4 shows structure editing as a first-class operation rather than a mask. On Breast Cancer, covariance editing removes 352 child relations and 32 hidden nodes per run while slightly increasing mean accuracy. On Wine, it removes 162 child relations and 18 hidden nodes per run while matching no-edit accuracy. The input contract is unchanged throughout: every sensory node consumes one feature dimension. These tabular studies are not meant to establish new UCI state of the art; they test whether the same child-owned substrate, family rebuilding, and physical deletion semantics work beyond image-feature heads.

Structural Localization by Relation Cut

The fourth study tests whether learned structure remains causally addressable after training. On the same Split Fashion-MNIST task order, each task receives 48 newly

Claim tested	Study	Fairness control	Primary readout
Child-owned plastic heads improve task-free calibration	Split Fashion-MNIST, 10 seeds	Same stream, replay, loss, seeds; fewer params than ER-256	Seen-class accuracy, forgetting, paired CI
Vector-producing modules compose with sensory nodes	Split CIFAR-10 ResNet-18, 5 seeds	Frozen shared encoder; one feature coordinate per sensory node; head-only online training	Seen-class accuracy over MLP-256
Structure edits are physical and non-image compatible	UCI tabular covariance editing	One sensory node per scalar feature; rebuild families after edit	Accuracy under relation/node deletion
Owned relations remain causally addressable	Relation-cut localization, 10 seeds	Copy graph after training; cut target-owned output relations	Target vs. non-target accuracy drop
Execution policies preserve the same graph	Family and attention audits	Forward/gradient comparisons to references	Numerical equality and speedup
Transformer FFNs are replaceable MLP sublayers	Tiny Transformer FFN audit	Copy standard FFN weights into GrapNet-FFN; same attention and classifier	Forward/loss/gradient equality; matched training accuracy

Table 1: Experiment map. Each study targets a distinct claim about the child-owned substrate while keeping learning and evaluation controls explicit.

Method	Params	Task-local acc.	Seen-class acc.	Global forgetting	Train time
Dense ER-64, reservoir	3.85K	90.91 ± 3.51	48.48 ± 3.84	47.86 ± 5.23	0.25s
Dense ER-256, reservoir	15.37K	96.45 ± 0.53	51.08 ± 2.51	52.24 ± 2.76	0.26s
Dense ER-256, balanced	15.37K	96.41 ± 0.55	50.19 ± 1.84	53.90 ± 2.10	0.27s
GrapNet-48 frozen, reservoir	13.45K	96.01 ± 0.78	54.47 ± 4.29	48.24 ± 5.13	5.48s
GrapNet-48 plastic, reservoir	13.45K	96.41 ± 0.77	$\mathbf{63.16 \pm 3.20}$	$\mathbf{36.34 \pm 4.18}$	3.57s
GrapNet-48 plastic, balanced	13.45K	$\mathbf{96.47 \pm 0.61}$	62.71 ± 2.50	36.75 ± 3.82	3.37s

Table 2: Matched one-pass Split Fashion-MNIST. Dense and GrapNet rows use the same seen-class loss, replay protocol, stream, and seeds. GrapNet plastic improves seen-class accuracy over dense ER-256 reservoir by 12.08 points (95% CI [8.89, 15.26], paired $p = 1.3 \times 10^{-5}$) with comparable task-local accuracy.

Head	Params	Task-local	Seen-class	Forgetting
Linear ER	5.13K	94.14 ± 0.47	57.28 ± 2.29	39.85 ± 3.85
MLP-256 ER	133.90K	94.74 ± 0.65	67.07 ± 2.36	30.66 ± 2.26
GrapNet frozen	124.57K	94.92 ± 0.72	64.72 ± 3.07	36.02 ± 3.12
GrapNet plastic	124.57K	$\mathbf{95.14 \pm 0.43}$	$\mathbf{70.88 \pm 1.72}$	$\mathbf{28.26 \pm 2.74}$

Table 3: Split CIFAR-10 using a frozen ImageNet ResNet-18 feature encoder. Online heads use matched seen-class CE and reservoir replay. GrapNet plastic improves seen-class accuracy over MLP-256 by 3.81 points (95% CI [2.24, 5.38], paired $p = 0.0026$).

Dataset	Sensory	No edit acc.	Cov-edit acc.	Removed rel./nodes
Breast Cancer	30	96.49 ± 1.52	96.73 ± 1.20	22.9% / 33.3%
Wine	13	98.89 ± 0.91	98.89 ± 0.91	32.1% / 33.3%

Table 4: Non-image tabular covariance editing over five stratified splits. "Sensory" is the number of input GrapNodes and equals the number of scalar features. The last column reports deleted relations / hidden nodes; execution families are rebuilt after the edit.

added hidden nodes. Those nodes own output child relations only to the task's two classes. After training all five tasks, we copy the trained graph and cut the physical output child relations owned by one target task. The cut set is selected only from task ownership metadata; test performance is measured after the cut.

Table 5 shows the expected graph-as-network behavior. Relation cuts are exact storage edits: every target task removes 48×2 child-reference/allocation-slot pairs. The owning task drops from near-perfect pair accuracy to chance-level behavior, while non-target tasks remain unchanged within measurement precision. This gives a direct causal readout

for the child-owned architecture graph. The audit should be read as structural localization, not as a claim that GrapNet automatically discovers a semantic task graph: the ownership metadata is created by the growth policy, and the experiment verifies that those owned relations remain editable and causally meaningful after learning.

Execution and Structural Operations

The trainable family backend matches the reference path with forward maximum absolute difference 2.24×10^{-8} and maximum parameter-gradient difference 1.49×10^{-8}. In a three-seed dynamic training check, it reduces GrapNet+ER runtime by 1.75x and GrapNet+DER++ runtime by 1.85x relative to the reference child-owned path while preserving

Metric	Mean	Std.	Audit
Base pair accuracy	98.26	0.25	10 seeds
Target-pair drop	48.26	0.25	96 cuts/task
Non-target-pair drop	0.00	0.00	4 tasks/cut
Localization margin	48.26	0.25	$p = 6.8 \times 10^{-22}$

Table 5: Structural localization on Split Fashion-MNIST. Cutting the task-owned child relations selectively removes the owning task's computation while preserving non-target task performance. Every run removed exactly the expected child-reference/allocation-slot pairs.

accuracy and forgetting. Timings that omit family execution are no-driver reference diagnostics; the dynamic accelerated path is the family backend. After topology stabilizes, a dense snapshot policy gives a 38.1x forward speedup on a full single-family transition, and a standalone C++ CPU relation backend gives a 2.68x speedup by moving accumulation out of Python.

The relation-attention policy audit gives the same guarantee for input-dependent routing. Before deletion, the policy matches a dense attention reference with zero measured forward, loss, child-weight-gradient, key-gradient, and query-gradient difference. After physically deleting five child relations, the attention mask updates from the graph and the same five differences remain zero. Gradients are nonzero for both child-owned W_{alloc} coordinates and attention key/query parameters. In a teacher-student attention task, the same policy trains from 34.38% to 92.19% test accuracy. This experiment is included to show policy generality: family execution exploits repeated structural patterns, whereas attention execution uses input-dependent relation weights over the same canonical child-owned relation set.

Additional structural studies exercise the same invariant. An MLP-equivalent construction matches a dense PyTorch MLP to 1.2×10^{-7} maximum absolute difference. On full-resolution 28x28 Fashion-MNIST organized as ten one-vs-rest online tasks, a child-owned grow-freeze model obtains 87.19% final average accuracy with 0.00 measured forgetting, compared with 66.69% and 26.18% forgetting for a sequential MLP. A covariance-sifter rule operating over shared-child families physically reduces active relations from 3950 to 3750 on a Fashion-MNIST structural run while accuracy changes from 77.78% to 78.17%.

The supplement contains the released scripts, result JSON files, and command notes for the reported studies, including the Tiny Transformer FFN replacement audit. Dataset archives and ImageNet weights are not bundled; the artifact expects Fashion-MNIST and CIFAR-10 archives or the standard torchvision cache. The ResNet-feature study uses torchvision's ImageNet ResNet-18 weights when available and freezes the encoder before the online stream. This keeps the submission artifact lightweight while preserving the exact head-training scripts and aggregate statistics used in the paper.

5 Discussion

The experiments separate three variables that are often entangled in dynamic neural methods. Structural capacity controls how many editable hidden units enter the head. Replay controls sample memory and calibration. Freezing controls whether previously allocated hidden nodes become locked structural memory or remain plastic calibration resources. GrapNet makes these variables explicit because they are policies over child-owned nodes rather than implicit tensor surgery.

The main empirical pattern is consistent across Fashion-MNIST and CIFAR-10 ResNet features. Frozen structural memory is useful for isolating old computation, but global seen-class accuracy benefits from plastic old nodes trained under replay. This does not weaken the structural claim; it separates two operating modes. A deployment that values locked task modules can freeze them, while a class-incremental evaluator that must calibrate old and new logits can leave them plastic. The substrate exposes the choice instead of embedding it in a fixed tensor mask.

The structural localization audit is the clearest distinction from ordinary tensor masking. The selected object is a task-owned set of child relations in the architecture graph. The intervention physically removes those relations and produces a targeted computational effect. This is the operating model of a dynamic-architecture graph neural network: the graph is editable storage, causal program structure, and the source from which execution views are derived. Because the intervention is performed on child-reference/allocation-slot pairs, the same edit changes storage, gradients, and execution views together.

The runtime profile is also a consequence of the representation. Dense heads are fastest when topology is fixed. GrapNet pays for editable relations during online growth, then recovers structure-aware execution through family blocks, attention policies, and dense or compiled views after edits settle. Family execution is the native acceleration driver for the dynamic phase because it groups repeated child patterns without detaching gradients from live allocation coordinates. Dense snapshots and compiled relation kernels are stable-topology endpoints. These backend switches preserve the same canonical graph and avoid redefining the model when moving from editable training to throughput-oriented inference.

6 Scope

GrapNet is evaluated here as an editable dynamic-architecture substrate behind a vector-producing parent interface. The parent can be raw vector input, a fully connected layer, a CNN encoder, a frozen ResNet feature extractor, an attention block, or a pooled/flattened transformer representation. Once a module emits a vector $z \in \mathbf{R}^D$, coordinate z_i is consumed by sensory GrapNode i, and all coordinates can be processed in parallel. This is why the CIFAR-10 experiment uses a frozen ResNet-18 feature vector, while the tabular experiments use standardized scalar coordinates: both instantiate the same sensory contract. The same mathematics also allows internal substitution where the operator

is an MLP: a dense head or Transformer FFN can be implemented as a fully connected GrapNet block. Operator-level versions of convolution and attention are compatible as well–convolution corresponds to local shared-weight aggregation across feature-map positions, and attention corresponds to input-dependent weighting over active relations–but the present experiments do not require replacing mature visual or token-mixing modules. The current evidence shows that child-owned heads can improve seen-class calibration under matched replay, preserve physical edit semantics across image and tabular inputs, and support multiple execution policies over the same canonical graph.

The reported results should therefore be read as evidence for a dynamic-architecture substrate rather than a claim that every backend is already throughput-optimal. No-driver reference timings measure the cost of preserving full editability in the simplest implementation. Family execution, attention execution, dense snapshots, and compiled relation kernels are the intended acceleration hierarchy. The important systems property is that these backends are derived from one graph object: a structural edit updates the storage invariant first, and the execution policy follows.

7 Conclusion

GrapNet introduces dynamic-architecture graph neural networks in the graph-as-network setting. Any vector-producing parent module can feed sensory GrapNodes coordinate-wise, after which each current-layer node owns next-layer child references and the aligned allocation coordinates that implement outgoing computation. This invariant makes structural edits physical, policy-driven, and executable through multiple backends. Matched online studies on Split Fashion-MNIST and CIFAR-10 ResNet features show that an editable GrapNet replay head improves global seen-class accuracy over dense replay heads with comparable or larger parameter counts. Tabular covariance editing and structural localization show that the same substrate supports physical relation deletion and task-targeted causal interventions. Family and attention execution policies then turn the same child-owned graph into live matrix blocks or input-dependent routing kernels without detaching gradients from the canonical graph.

References

Ansel, J.; Yang, E.; He, H.; Gimelshein, N.; Jain, A.; Voznesensky, M.; Bao, B.; Bell, P.; Berard, D.; Burovski, E.; and others. 2024. PyTorch 2: Faster Machine Learning Through Dynamic Python Bytecode Transformation and Graph Compilation. In *Proceedings of the 29th ACM International Conference on Architectural Support for Programming Language and Operating Systems*.

Boschini, M.; Bonicelli, L.; Buzzega, P.; Porrello, A.; and Calderara, S. 2023. Class-Incremental Continual Learning into the eXtended DER-verse. *IEEE Transactions on Pattern Analysis and Machine Intelligence*.

Buzzega, P.; Boschini, M.; Porrello, A.; Abati, D.; and Calderara, S. 2020. Dark Experience for General Continual Learning: A Strong, Simple Baseline. In *NeurIPS*.

Chaudhry, A.; Rohrbach, M.; Elhoseiny, M.; Ajanthan, T.;

Dokania, P. K.; Torr, P. H. S.; and Ranzato, M. 2019. On Tiny Episodic Memories in Continual Learning. In *ICML Workshop*.

Douillard, A.; Ramé, A.; Couairon, G.; and Cord, M. 2022. DyTox: Transformers for Continual Learning with Dynamic Token Expansion. In *CVPR*.

Evci, U.; Gale, T.; Menick, J.; Castro, P. S.; and Elsen, E. 2020. Rigging the Lottery: Making All Tickets Winners. In *ICML*.

Fey, M.; and Lenssen, J. E. 2019. Fast Graph Representation Learning with PyTorch Geometric. In *ICLR Workshop on Representation Learning on Graphs and Manifolds*.

Frankle, J.; and Carbin, M. 2019. The Lottery Ticket Hypothesis: Finding Sparse, Trainable Neural Networks. In *ICLR*.

He, K.; Zhang, X.; Ren, S.; and Sun, J. 2016. Deep Residual Learning for Image Recognition. In *CVPR*.

Kirkpatrick, J.; Pascanu, R.; Rabinowitz, N.; and others. 2017. Overcoming catastrophic forgetting in neural networks. *PNAS*, 114(13):3521–3526.

Krizhevsky, A. 2009. Learning Multiple Layers of Features from Tiny Images. Technical report, University of Toronto.

Lasby, M.; Golubeva, A.; Evci, U.; Nica, M.; and Ioannou, Y. 2023. Dynamic Sparse Training with Structured Sparsity. arXiv:2305.02299.

Mallya, A.; and Lazebnik, S. 2018. PackNet: Adding Multiple Tasks to a Single Network by Iterative Pruning. In *CVPR*.

Mirzadeh, S. I.; Chaudhry, A.; Yin, D.; Nguyen, T.; Pascanu, R.; Gorur, D.; and Farajtabar, M. 2022. Architecture Matters in Continual Learning. arXiv:2202.00275.

Paszke, A.; Gross, S.; Massa, F.; and others. 2019. PyTorch: An Imperative Style, High-Performance Deep Learning Library. In *NeurIPS*.

Pedregosa, F.; Varoquaux, G.; Gramfort, A.; Michel, V.; Thirion, B.; Grisel, O.; Blondel, M.; Prettenhofer, P.; Weiss, R.; Dubourg, V.; and others. 2011. Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research*, 12:2825–2830.

Prabhu, A.; Torr, P. H. S.; and Dokania, P. K. 2020. GDumb: A Simple Approach that Questions Our Progress in Continual Learning. In *ECCV*.

Rusu, A. A.; Rabinowitz, N. C.; Desjardins, G.; Soyer, H.; Kirkpatrick, J.; Kavukcuoglu, K.; Pascanu, R.; and Hadsell, R. 2016. Progressive Neural Networks. arXiv:1606.04671.

Serra, J.; Suris, D.; Miron, M.; and Karatzoglou, A. 2018. Overcoming Catastrophic Forgetting with Hard Attention to the Task. In *ICML*.

Vaswani, A.; Shazeer, N.; Parmar, N.; Uszkoreit, J.; Jones, L.; Gomez, A. N.; Kaiser, L.; and Polosukhin, I. 2017. Attention Is All You Need. In *NeurIPS*.

Wang, M.; Yu, L.; Zheng, D.; and others. 2019. DGL: A Graph-Centric, Highly-Performant Package for Graph Neural Networks. arXiv:1909.01315.

Wang, Z.; Zhang, Z.; Lee, C.-Y.; Zhang, H.; Sun, R.; Ren, X.; Perot, V.; Dy, J.; and Pfister, T. 2022. Learning to Prompt for Continual Learning. In *CVPR*.

Wang, L.; Zhang, X.; Su, H.; and Zhu, J. 2024. A Comprehensive Survey of Continual Learning: Theory, Method

and Application. *IEEE Transactions on Pattern Analysis and Machine Intelligence*.

Xiao, H.; Rasul, K.; and Vollgraf, R. 2017. Fashion-MNIST: A Novel Image Dataset for Benchmarking Machine Learning Algorithms. arXiv:1708.07747.

Yoon, J.; Yang, E.; Lee, J.; and Hwang, S. J. 2018. Lifelong Learning with Dynamically Expandable Networks. In *ICLR*.

Zenke, F.; Poole, B.; and Ganguli, S. 2017. Continual Learning Through Synaptic Intelligence. In *ICML*.