EARLY STOPPING FOR DEEP IMAGE PRIOR

ABSTRACT

Deep image prior (DIP) and its variants have shown remarkable potential for solving inverse problems in computational imaging (CI), *needing no separate training data*. Practical DIP models are often substantially overparameterized. During the learning process, these models learn the desired visual content first and then pick up the potential modeling and observational noise, i.e., overfitting. Thus, the practicality of DIP hinges on early stopping (ES) that captures the transition period. In this regard, the majority of prior DIP works for CI tasks only demonstrate the potential of the models—reporting the peak performance against the groundtruth but providing no clue about how to operationally obtain near-peak performance *without access to the groundtruth*. In this paper, we set to break this practicality barrier of DIP, and propose an efficient ES strategy that consistently detects near-peak performance across several CI tasks and DIP variants. Simply based on the running variance of DIP intermediate reconstructions, our ES method not only outpaces the existing ones—which only work in very narrow regimes, but also remains effective when combined with methods that try to mitigate overfitting.

1 INTRODUCTION

Inverse problems (IPs) are prevalent in computational imaging (CI), from basic image denoising, super-resolution, and deblurring, to advanced 3D reconstruction and major tasks in scientific and medical imaging (Szeliski, 2021). Despite the disparate settings, all these problems take the form of recovering a visual object $\boldsymbol{x}$ from $\boldsymbol{y} = f(\boldsymbol{x})$, where f models the forward process to obtain the observation $\boldsymbol{y}$. Typically, these visual IPs are underdetermined: $\boldsymbol{x}$ cannot be uniquely determined from $\boldsymbol{y}$. This is exacerbated by potential modeling (e.g., linear f to approximate a nonlinear process) and observational (e.g., Gaussian or shot) noise, i.e., $\boldsymbol{y} \approx f(\boldsymbol{x})$. To overcome the nonuniqueness and improve noise stability, people often encode a variety of problem-specific priors on $\boldsymbol{x}$ when formulating IPs. Traditionally, IPs are phrased as regularized data-fitting problems:

$$\min_{\boldsymbol{x}} \ \ell(\boldsymbol{y}, f(\boldsymbol{x})) + \lambda R(\boldsymbol{x}) \qquad \ell(\boldsymbol{y}, f(\boldsymbol{x})) : \text{data-fitting loss}, \ R(\boldsymbol{x}) : \text{regularizer} \qquad (1)$$

where λ is the regularization parameter. Here, the loss ℓ is chosen according to the noise model, and the regularizer R encodes priors on $\boldsymbol{x}$. The advent of deep learning (DL) has revolutionized how IPs are solved: on the radical side, deep neural networks (DNNs) are trained to directly map any given $\boldsymbol{y}$ to an $\boldsymbol{x}$; on the mild side, pretrained or trainable DL models are taken to replace certain nonlinear mappings in numerical algorithms to solve (1) (e.g., plug-and-play, and algorithm unrolling). Recent surveys Ongie et al. (2020); Janai et al. (2020) on these developments all trust large training sets $\{(\boldsymbol{y}_i, \boldsymbol{x}_i)\}$ to sufficiently represent the underlying priors and/or noise distributions. **However, this paper concerns another family of striking ideas that require no separate training data**.

Deep image prior (DIP)   Ulyanov et al. (2018) proposes parameterizing $\boldsymbol{x}$ as $\boldsymbol{x} = G_{\boldsymbol{\theta}}(\boldsymbol{z})$, where $G_{\boldsymbol{\theta}}$ is a trainable DNN parametrized by $\boldsymbol{\theta}$ and $\boldsymbol{z}$ is a trainable or frozen random seed. **No separate training data other than $\boldsymbol{y}$ are used!** Putting the reparametrization into (1), we obtain

$$\min_{\boldsymbol{\theta}} \ \ell(\boldsymbol{y}, f(G_{\boldsymbol{\theta}}(\boldsymbol{z}))) + \lambda R(G_{\boldsymbol{\theta}}(\boldsymbol{z})). \qquad (2)$$

$G_{\boldsymbol{\theta}}$ is often "overparameterized"—containing substantially more parameters than the size of $\boldsymbol{x}$, and "structured"—e.g., consisting of convolution networks to encode structural prior of natural visual objects. The resulting optimization problem is solved via standard first-order methods for modern

DL (e.g., (adaptive) gradient methods). When x contains multiple components with different physical meanings, one can naturally parametrize x using multiple DNNs. This simple idea has led to surprisingly competitive recovery results on a myriad of visual IPs, from low-level image denoising, super-resolution, inpainting (Ulyanov et al., 2018; Heckel & Hand, 2018; Liu et al., 2018) and blind deconvolution (Ren et al., 2020; Wang et al., 2019; Asim et al., 2019; Tran et al., 2021; Zhuang et al., 2022), to mid-level image decomposition (Gandelsman et al., 2019) and image fusion (Ma et al., 2021), and to advanced CI problems (Darestani & Heckel, 2021; Hand et al., 2018; Williams et al., 2019; Yoo et al., 2021; Baguer et al., 2020; Cascarano et al., 2021; Hashimoto & Ote, 2021; Gong et al., 2021; Veen et al., 2020; Tayal et al., 2021) (see the survey Qayyum et al. (2021)).

Overfitting issue in DIP A critical detail that we have glossed over above is **overfitting**. Since G_θ is substantially overparameterized, $G_\theta(z)$ can represent arbitrary elements in the x domain. Globally optimizing (2) would normally lead to $y = f(G_\theta(z))$, but $G_\theta(z)$ may not reproduce x, e.g., when f is non-injective, or $y \approx f(x)$ so that $G_\theta(z)$ also accounts for modeling and observational noise. Fortunately, DIP models and first-order optimization methods together offer a blessing: in practice, $G_\theta(z)$ has a bias toward the desired visual content and learns it much faster than learning the noise. So the reconstruction quality climbs to a peak before potential degradation due to noise; see Fig. 1. This "early-learning-then-overfitting" (ELTO) phenomenon has been re-

Figure 1: The "early-learning-then-overfitting" (ELTO) phenomenon in DIP for image denoising. The quality of the estimated image climbs to a peak first and then plunges once the noise is picked up by the model $G_\theta(z)$ also.

peatedly reported in prior works and is also backed by theories on simple G_θ and linear f (Heckel & Soltanolkotabi, 2020b;a). The successes of DIP models claimed above are mostly conditioned on that appropriate **early stopping** (ES) around the performance peaks can be made.

Is ES for DIP trivial? Natural ideas trying to perform good ES may fail quickly. **(1) Visual inspection**: This subjective approach is fine for small-scale tasks involving few problem instances, but quickly becomes infeasible for many scenarios, such as (a) large-scale batch processing, (b) recovery of visual contents tricky to be visualized and/or examined by eyes (e.g., 3D or 4D visual objects), and (c) scientific imaging of unfamiliar objects (e.g., MRI imaging of rare tumors, and microscopic imaging of new virus species); **(2) Tracking full-reference/no-reference image quality metrics (FR/NR-IQMs)**: Without the groundtruth x, computing any FR-IQM and hence tracking their trajectories (e.g., the PNSR curve in Fig. 1) is out of the question. We consider tracking NR-IQMs as a family of baseline methods in Section 3.1; the performance is much worse than ours; **(3) Tuning the iteration number**: This ad-hoc solution is taken by most previous works. But since the peak iterations of DIP vary considerably across images and tasks (see, e.g., Figs. 3 and 20 and Appendices A.6.3 and A.6.5), this might entail numerous trial- and-error steps and lead to suboptimal stopping points; **(4) Validation-based ES**: ES easily reminds us of validation-based ES in supervised learning. The DIP approach to IPs as summarized in Eq. (2) **is not** supervised learning, as it only deals with a single instance y, without separate (x, y) pairs as training data.

Prior work addressing the overfitting There are three main approaches to countering overfitting in working with DIP models. **(1) Regularization**: Heckel & Hand (2018) mitigates overfitting by restricting the size of G_θ to the underparameterized regime. Metzler et al. (2018); Shi et al. (2021); Jo et al. (2021); Cheng et al. (2019a) control the network capacity by regularizing the norms of layerwise weights or the network Jacobian. Liu et al. (2018); Mataev et al. (2019); Sun (2021); Cascarano et al. (2021) use additional regularizer(s) $R(G_\theta(z))$, such as total-variation norm or trained denoisers. However, in general, it is difficult to choose the right regularization level to preserve the peak performance while avoiding overfitting, and the optimal λ likely depends on the noisy type and level, as shown in Section 3.1—the default λ's for selected methods in this category still lead to overfitting for high-level noise. **(2) Noise modeling**: You et al. (2020) models sparse additive noise as an explicit term in their optimization objective. Jo et al. (2021) designs regularizers

and ES criteria specific to Gaussian and shot noise. Ding et al. (2021) explores subgradient methods with diminishing step-size schedules for impulse noise with the ℓ_1 loss, with preliminary success. These methods do not work beyond the noise types and levels they target, whereas our knowledge about the noise in a given visual IP is typically limited. **(3) Early stopping (ES)**: Shi et al. (2021) tracks the progress based on a ratio of no-reference blurriness and sharpness, but the criterion only works for their modified DIP models, as acknowledged by the authors. Jo et al. (2021) provides noise-specific regularizer and ES criterion, but it is unclear how to extend the methods to unknown noise types and levels. Li et al. (2021) proposes monitoring the DIP reconstruction quality by training a coupled autoencoder. Although it leads to similar detection performance as ours, the extra autoencoder training slows down the whole process dramatically; see Section 3. Yaman et al. (2021); Ding et al. (2022) emulate validation-based ES in supervised learning by splitting elements of $\boldsymbol{y}$ into training and validation sets, leading to training and validation losses so that validation-based ES can be performed. But in IPs, especially when f is nonlinear (e.g., in blind image deblurring—BID, $\boldsymbol{y} \approx \boldsymbol{k} * \boldsymbol{x}$ where $*$ is linear convolution), elements of $\boldsymbol{y}$ can be far from being iid and so validation may not work well. Moreover, holding-out part of the observation in $\boldsymbol{y}$ can substantially reduce the peak performance; see Section 3.3.

Our contribution We advocate the ES approach—**the iteration process stops once a good ES point is detected**, as (1) the regularization and noise modeling approaches, even if effective, often do not improve the peak performance but push it until the last iterations; there could be $\geq 10\times$ more iterations spent than that of climbing to the peak in the original DIP models; (2) both need deep knowledge about the noise type/level, which is practically unknown for most applications. If their key models and hyperparameters are not set appropriately, overfitting likely remains. Then ES is still needed. **In this paper, we build a novel ES criterion for various DIP models by simply tracking the trend of the running variance of the reconstruction sequence**. Our ES method is **(1) Effective**: The gap between our detected and the peak performance, i.e., detection gap, is typically very small, as measured by standard visual quality metrics (PSNR and SSIM); **(2) Efficient**: Per-iteration overhead is a fraction of—the standard version in Algorithm 1, or negligible—the variant in Algorithm 2, relative to the per-iteration cost of Eq. (2); **(3) General**: Our method works well for DIP and its variants, including deep decoder (Heckel & Hand, 2018, DD) and sinusoidal representation networks (Sitzmann et al., 2020, SIREN), on different noise types/levels and across several visual IPs. Also, our method can be wrapped around several regularization methods, e.g., Gaussian process-DIP (Cheng et al., 2019b, GP-DIP), DIP with total variation regularization (Liu et al., 2018; Cascarano et al., 2021, DIP-TV) to perform reasonable ES when they fail to prevent overfitting; **(4) Robust**: Our method is relatively insensitive to the two hyperparameters, i.e., window size and patience number (see Sections 2, 3 and 3.4 and Appendix A.6.10). By contrast, the hyperparameters of most methods reviewed above are sensitive to the noise type/level.

2 OUR EARLY-STOPPING METHOD

We assume: $\boldsymbol{x}$ is the unknown groundtruth visual object of size N, $\{\boldsymbol{\theta}^t\}_{t\geq 1}$ is the iterate sequence, and $\{\boldsymbol{x}^t\}_{t\geq 1}$ the reconstruction sequence where $\boldsymbol{x}^t \doteq \widehat{G}_{\boldsymbol{\theta}^t}(\boldsymbol{z})$.

Figure 2: Relationship between the PSNR, MSE, and VAR curves. Our method relies on the VAR curve, whose valley is often well aligned with the MSE valley, to detect the MSE valley—that corresponds to the PSNR peak.

Intuition for our method Since we do not know $\boldsymbol{x}$, we cannot access the PNSR or any FR-IQM curve. But we observe that (Fig. 2) generally the MSE (resp. PSNR; recall $\mathrm{PSNR}(\boldsymbol{x}^t) = 10 \log_{10} \|\boldsymbol{x}\|_\infty^2 / \mathrm{MSE}(\boldsymbol{x}^t)$) curve follows a U (resp. bell) shape: $\|\boldsymbol{x}^t - \boldsymbol{x}\|_F^2$ initially drops quickly to a low level, and then climbs back due to the noise effect, i.e., the ELTO phenomenon in Section 1; we hope to detect the valley of this U-shaped MSE curve. Then how to gauge the MSE curve **without knowing** $\boldsymbol{x}$? We consider the running variance (VAR):

$$\mathrm{VAR}(t) \doteq 1/W \cdot \sum_{w=0}^{W-1} \|\boldsymbol{x}^{t+w} - 1/W \cdot \sum_{i=0}^{W-1} \boldsymbol{x}^{t+i}\|_F^2. \tag{3}$$

Initially, the models quickly learn the desired visual content, resulting in monotonic, rapidly diminishing MSE curve (see Fig. 2). So we expect the running variance of $\{x^t\}_{t\geq 1}$ to drop quickly also, as shown in Fig. 2. When the iteration is near the MSE valley, all the x^t's are near but scattered around x. So $\frac{1}{W}\sum_{i=0}^{W-1} x^{t+i} \approx x$ and $\text{VAR}(t) \approx \frac{1}{W}\sum_{w=0}^{W-1} \|x^{t+w} - x\|_F^2$. Afterward, the noise effect kicks in and the MSE curve bounces back, leading to a similar bounce-back in the VAR curve as the x^t sequence gradually moves away from x.

This argument suggests a U-shaped VAR curve, and the curve should follow the trend of the MSE curve, with approximately aligned valleys which in turn is aligned with the PSNR peak. To quickly verify this, we randomly sample 1024 images from the RGB track of NTIRE 2020 Real Image Denoising Challenge (Abdelhamed et al., 2020), and perform DIP-based image denoising (i.e., $\min\ \ell(y, G_\theta(z))$ where y

Table 1: DIP-ES (our method) on real-world image denoising for **1024 images**: mean and (std) over the images. (**D**: detected)

ℓ (loss)	PSNR (**D**)	PSNR Gap	SSIM (**D**)	SSIM Gap
MSE	34.04 (3.68)	0.92 (0.83)	0.92 (0.07)	0.02 (0.04)
ℓ_1	33.92 (4.34)	0.92 (0.59)	0.93 (0.05)	0.02 (0.02)
Huber	33.72 (3.86)	0.95 (0.73)	0.92 (0.06)	0.02 (0.03)

denotes the noisy image). Table 1 reports the detected PSNR/SSIM and detection gaps based on our ES method (see Algorithm 1) that tries to detect the valley of the VAR curve. On average, the detection gaps are ≤ 0.95 in PSNR and ≤ 0.02 in SSIM, barely noticeable by eyes! more details in Fig. 11, and Section 3 and Appendix A.6.3.

Detecting transition by running variance Our lightweight method only involves computing the VAR curve and numerically detecting its valley—**the iteration stops once the valley is detected**. To obtain the curve, we set a window-size parameter W and compute the windowed moving variance (WMV). To robustly detect the valley, we introduce a patience number P to tolerate up to P consecutive steps of variance stagnation. Obviously, the cost is dominated by the variance calculation per step, which is $O(WN)$ (N is the size of the visual object). In comparison, a typical gradient update step for solving Eq. (2) costs at least $\Omega(|\theta|N)$, where $|\theta|$ is the number of parameters in the DNN G_θ. Since $|\theta|$ is typically much larger than W (we set the default value to 100), our running VAR and detection induce very little computational overhead. Our whole algorithmic pipeline is summarized in Algorithm 1. To confirm the effectiveness, we provide sample qualitative results in Figs. 3 and 11, with more quantitative results included in the experiment part (Section 3; see also Table 1). Appendix A.6.3 shows on image denoising with different noise types/levels, our ES method can detect near-peak ES points. Similarly, our method remains effective on several popular DIP variants, as shown in Fig. 3.

Algorithm 1 DIP with ES–WMV

Input: random seed z, randomly-initialized θ^0, window size W, patience P, empty queue $\mathcal{Q}$, iteration counter $k = 0$, $\text{VAR}_{\min} = \infty$
Output: reconstruction x^*
1: **while** not stopped **do**
2:     update θ via Eq. (2) to obtain θ^{k+1} and x^{k+1}
3:     push x^{k+1} to $\mathcal{Q}$, pop queue if $|\mathcal{Q}| > W$
4:     **if** $|\mathcal{Q}| = W$ **then**
5:         compute VAR of elements in $\mathcal{Q}$ via Eq. (3)
6:         **if** $\text{VAR} < \text{VAR}_{\min}$ **then**
7:             $\text{VAR}_{\min} \leftarrow \text{VAR}$, $x^* \leftarrow x^{k+1}$
8:         **end if**
9:         **if** $\text{VAR}_{\min}$ stagnates for P iterations **then**
10:             stop and return x^*
11:         **end if**
12:     **end if**
13:     $k = k + 1$
14: **end while**

Seemingly similar ideas Our running variance and its U-shaped curve are reminiscent of the classical U-shaped bias-variance tradeoff curve and hence validation-based ES (Geman et al., 1992; Yang et al., 2020). But there are crucial differences: (1) our learning setting is not supervised; (2) the variance in supervised learning is with respect to sample distribution, whereas our variance here pertains to the $\{x^t\}_{t\geq 1}$ sequence. As discussed in Section 1, we cannot directly apply validation-based ES, although it is possible to heuristically emulate it by splitting the elements in y (Yaman et al., 2021; Ding et al., 2022)—which might be problematic for nonlinear IPs. Another related idea is variance-based online change-point detection in time series analysis (Aminikhanghahi & Cook, 2016), where running variance is often used to detect mean-shift assuming the means are piecewise constant. Here, the piecewise constancy assumption does not hold for our $\{x^t\}_{t\geq 1}$.

Figure 3: Our ES-WMV method on DD, GP-DIP, DIP-TV, and SIREN for denoising "F16" with different levels of Gaussian noise (top: low-level noise; bottom: high-level noise). Red curves are PSNR curves, and blue curves are VAR curves. The green bars indicate the detected ES points.

Theoretical justification We can make our heuristic argument in Section 2 more rigorous by restricting ourselves to additive denoising, i.e., $\boldsymbol{y} = \boldsymbol{x} + \boldsymbol{n}$, and appealing to the popular linearization strategy (i.e., neural tangent kernel Jacot et al. (2018); Heckel & Soltanolkotabi (2020b)) in understanding DNNs. The idea is based on the assumption that during DNN training $\boldsymbol{\theta}$ does not move much from initialization $\boldsymbol{\theta}^0$, so that the learning dynamic can be approximated by that of a linearized model, i.e., suppose we take the MSE loss

$$\left\| \boldsymbol{y} - G_{\boldsymbol{\theta}}(\boldsymbol{z}) \right\|_2^2 \approx \left\| \boldsymbol{y} - G_{\boldsymbol{\theta}^0}(\boldsymbol{z}) - \boldsymbol{J}_G(\boldsymbol{\theta}^0)(\boldsymbol{\theta} - \boldsymbol{\theta}^0) \right\|_2^2 \doteq \widehat{f}(\boldsymbol{\theta}), \tag{4}$$

where $\boldsymbol{J}_G(\boldsymbol{\theta}^0)$ is the Jacobian of G with respect to $\boldsymbol{\theta}$ at $\boldsymbol{\theta}^0$, and $G_{\boldsymbol{\theta}^0}(\boldsymbol{z}) + \boldsymbol{J}_G(\boldsymbol{\theta}^0)(\boldsymbol{\theta} - \boldsymbol{\theta}^0)$ is the first-order Taylor approximation to $G_{\boldsymbol{\theta}}(\boldsymbol{z})$ around $\boldsymbol{\theta}^0$. $\widehat{f}(\boldsymbol{\theta})$ is simply a least-squares objective. We can directly calculate the running variance based on the linear model, as shown below.

Theorem 2.1. *Let σ_i's and $\boldsymbol{w}_i$'s be the singular values and left singular vectors of $\boldsymbol{J}_G(\boldsymbol{\theta}^0)$, and suppose we run gradient descent with step size η on the linearized objective $\widehat{f}(\boldsymbol{\theta})$ to obtain $\{\boldsymbol{\theta}^t\}$ and $\{\boldsymbol{x}^t\}$ with $\boldsymbol{x}^t \doteq G_{\boldsymbol{\theta}^0}(\boldsymbol{z}) + \boldsymbol{J}_G(\boldsymbol{\theta}^0)(\boldsymbol{\theta}^t - \boldsymbol{\theta}^0)$. Then provided that $\eta \leq 1/\max_i(\sigma_i^2)$,*

$$\mathrm{VAR}(t) = \sum_i C_{m,\eta,\sigma_i} \left\langle \boldsymbol{w}_i, \widehat{\boldsymbol{y}} \right\rangle^2 \left(1 - \eta\sigma_i^2\right)^{2t}, \tag{5}$$

where $\widehat{\boldsymbol{y}} = \boldsymbol{y} - G_{\boldsymbol{\theta}^0}(\boldsymbol{z})$, and $C_{W,\eta,\sigma_i} \geq 0$ only depends on W, η, and σ_i for all i.

The proof can be found in Appendix A.2. Theorem 2.1 shows that if the learning rate (LR) η is sufficiently small, the WMV of $\{\boldsymbol{x}^t\}$ is monotonically decreasing. We can develop a complementary upper bound for the WMV that does have a U shape. To this end, we make use of Theorem 1 of Heckel & Soltanolkotabi (2020b), which can be summarized (some technical details omitted; precise statement reproduced in Appendix A.3) as follows: consider two-layer model $G_{\boldsymbol{C}}(\boldsymbol{B}) = \mathrm{ReLU}(\boldsymbol{U}\boldsymbol{B}\boldsymbol{C})\boldsymbol{v}$, where $\boldsymbol{C} \in \mathbb{R}^{n \times k}$ models 1×1 trainable convolutions, $\boldsymbol{v} \in \mathbb{R}^{k \times 1}$ contains fixed weights, $\boldsymbol{U}$ is an upsampling operation, and $\boldsymbol{B}$ is the fixed random seed. Let $\boldsymbol{J}$ be a reference Jacobian matrix solely determined by the upsampling operation $\boldsymbol{U}$, and σ_i's and $\boldsymbol{w}_i$'s the singular values and left singular vectors of $\boldsymbol{J}$. Assume $\boldsymbol{x} \in \mathrm{span}\{\boldsymbol{w}_1, \ldots, \boldsymbol{w}_p\}$. Then when η is sufficiently small, with high probability,

$$\left\| G_{\boldsymbol{C}^t}(\boldsymbol{B}) - \boldsymbol{x} \right\|_2 \leq \left(1 - \eta\sigma_p^2\right)^t \|\boldsymbol{x}\|_2 + E(\boldsymbol{n}) + \varepsilon\|\boldsymbol{y}\|_2, \tag{6}$$

where $\varepsilon > 0$ is a small scalar related to the structure of the network and $E(\boldsymbol{n})$ is the error introduced by noise: $E^2(\boldsymbol{n}) \doteq \sum_{j=1}^n ((1 - \eta\sigma_j^2)^t - 1)^2 \langle \boldsymbol{w}_j, \boldsymbol{n} \rangle^2$. So if the gap $\sigma_p/\sigma_{p+1} > 1$, $\left\| G_{\boldsymbol{C}^t}(\boldsymbol{B}) - \boldsymbol{x} \right\|_2$ is dominated by $\left(1 - \eta\sigma_p^2\right)^t \|\boldsymbol{x}\|_2$ when t is small, and then by $E(\boldsymbol{n})$ when t is large. But since the former decreases and the latter increases when t grows, the upper bound has a U shape with respect to t. Based on this result, we have:

Theorem 2.2. *Assume the same setting as Theorem 2 of Heckel & Soltanolkotabi (2020b). It is highly probable that our WMV is upper bounded by*

$$\frac{12}{W}\|\boldsymbol{x}\|_2^2 \frac{\left(1 - \eta\sigma_p^2\right)^{2t}}{1 - (1 - \eta\sigma_p^2)^2} + 12\sum_{i=1}^{n}\left(\left(1 - \eta\sigma_i^2\right)^{t+W-1} - 1\right)^2(\boldsymbol{w}_i^\mathsf{T}\boldsymbol{n})^2 + 12\varepsilon^2\|\boldsymbol{y}\|_2^2. \quad (7)$$

The exact statement and proof can be found in Appendix A.3. By similar reasoning as above, we can conclude that the upper bound in Theorem 2.2 also has a U shape. To interpret the results, Fig. 4 shows the curves (as functions of t) predicted by Theorems 2.1 and 2.2. The actual VAR curve should lie between the two curves.

A memory-efficient variant While Algorithm 1 is already lightweight and effective in practice, we can slightly modify it to avoid maintaining the $\mathcal{Q}$ and hence save memory. The trick is to use exponential moving variance (EMV), together with the exponential moving average (EMA), shown in Appendix A.4. The hard window size parameter W is now replaced by the soft forgetting factor α: the larger the α, the smaller the impact of the history and hence a smaller effective window. We compare ES-WMV with ES-EMV in Appendix A.6.9.

Figure 4: The exact and upper bounds predicted by Theorems 2.1 and 2.2.

3 EXPERIMENTS

We test ES-WMV for DIP Ulyanov et al. (2018) on image denoising, MRI reconstruction, and blind image deblurring, spanning both linear and nonlinear IPs. For image denoising, we also systematically evaluate ES-WMV on major variants of DIP that try to mitigate overfitting, including DD (Heckel & Hand, 2018), DIP-TV (Cascarano et al., 2021), GP-DIP (Cheng et al., 2019a), and demonstrate ES-WMV as a reliable helper to detect good ES points, whether these methods succeed or not in removing the overfitting. We also compare ES-WMV with major competing methods, including DF-STE (Jo et al., 2021), SV-ES (Li et al., 2021), DOP (You et al., 2020), SB (Shi et al., 2021), and VAL (Yaman et al., 2021;

Figure 5: Baseline ES vs our ES-WMV on denoising with **low-level noise**. For NIMA, we report both technical quality assessment (NIMA-q) and aesthetic assessment (NIMA-a). Smaller PSNR gaps are better.

Ding et al., 2022). Details of major ES-based methods can be found in Appendix A.5. We use both PSNR and SSIM to access the reconstruction quality, and we report PSNR and SSIM gaps (the difference between our detected and peak numbers) as indicators of our detection performance. **Common acronyms, pointers to external codes, detailed experiment settings, real-world denoising are in Appendices A.1, A.6.1, A.6.2 and A.6.7, respectively.**

3.1 IMAGE DENOISING

Prior works dealing with DIP overfitting mostly focus on image denoising, but typically only evaluate their methods on one or two kinds of noise with low noise levels, e.g., low-level Gaussian noise. To stretch our evaluation, we consider 4 types of noise: Gaussian, shot, impulse, and speckle. We take the classical 9-image dataset (Dabov et al., 2007), and for each noise type, generate two noise levels, low and high, i.e., level 2 and 4 of Hendrycks & Dietterich (2019), respectively. See also the performance of our ES-WMV on real-world denoising in Table 1 and Appendix A.6.7.

Comparison with baseline ES methods   It is natural to expect that NR-IQMs, such as the classical BRISQUE (Mittal et al., 2012a), NIQE (Mittal et al., 2012b), and modern DNN-based NIMA (Talebi & Milanfar, 2018) can possibly make good ES criteria. We thus set up 3 baseline methods using BRISQUE, NIQE, and NIMA, respectively and seek the optimal x^t by these metrics. Fig. 5 presents the comparison (in terms of PSNR gaps) of these 3 methods with our ES-WMV on denoising with low-level noise; results on high-level noise, and measured by SSIM are included in Appendix A.6.4 as they have similar trends as the low-level noise. While our method enjoys favorable detection gaps (≤ 2) for most tested noise types/levels (except for Baboon, Kodak1, Kodak2 for certain noise types/levels; DIP itself is suboptimal in terms of denoising such images with substantial high-frequency components), detection gaps by the baseline methods can get huge (≥ 10).

Competing methods   DF-STE is specific for Gaussian and Poisson denoising, and the noise variance is needed for their tuning parameters. Fig. 6 presents the comparison with DF-STE in terms of PSNR. SSIM results are in Appendix A.6.5. Here, we directly report the final PSNRs obtained by both methods. For low-level noise, there is no clear winner. For high-level noise, ES-WMV outperforms DF-STE by considerable margins.

Figure 6: Comparison of DF-STE and ES-WMV for Gaussian and shot noise in terms of PSNR.

Although the right variance level is provided to DF-STE in order to tune their regularization parameters, DF-STE stops after only very few epochs leading to very low performance and almost zero standard deviations—they return almost the noisy input. However, we do not perform any parameter tuning for ES-WMV.

We report the results of SV-ES in Appendix A.6.5 since ES-WMV performs largely comparably to SV-ES. However, ES-WMV is much faster in wall-clock time, as reported in Table 2: for each epoch, the overhead of our ES-WMV is less than $3/4$ of the DIP update itself, while SV-ES is around $25\times$ of that. There is no surprise: while our method only needs to update the running variance of the $\{x^t\}_{t \geq 1}$ each time, SV-ES needs to train a coupled autoencoder which is expensive.

Table 2: Wall-clock time (secs) of DIP, SV-ES, ES-WMV and ES-EMV per epoch on *NVIDIA Tesla K40 GPU*: mean and (std).

	DIP	SV-ES	ES-WMV	ES-EMV
Time	0.448 (0.030)	**13.027 (3.872)**	0.301 (0.016)	0.003 (0.003)

DOP is designed specifically for impulse noise, so we compare ES-WMV with DOP only on impulse noise (see Appendix A.6.5). The loss is changed to ℓ_1 to account for the sparse noise. In terms of the final PSNRs, DOP outperforms DIP with ES-WMV by a small gap. We note that the peak PSNR of DIP with ℓ_1 lags behind DOP by about 2 points for high noise levels.

Table 3: Comparison between ES-WMV and SB for image denoising on the CBSD68 dataset with varying noise level σ. Higher detected PSNR and earlier detection are better, which are in red: mean and (std).

	$\sigma = 15$		$\sigma = 25$		$\sigma = 50$	
	PSNR	Epoch	PSNR	Epoch	PSNR	Epoch
WMV	28.7(3.2)	3962(2506)	27.4(2.6)	3068(2150)	24.2(2.3)	1548(1939)
SB	29.0(3.1)	4908(1757)	27.3(2.2)	5099(1776)	23.0(1.0)	5765(1346)

The ES method in SB is known to fail for vanilla DIP. Moreover, their modified model still suffers from the overfitting issue beyond the very low noise levels, as shown in Appendix A.6.5. Their ES method fails to stop at appropriate places when the noise level is high. Hence, we test both ES-WMV and SB *on their modified DIP model in (Shi et al., 2021)*, based on two datasets they test: the classic 9-image dataset (Dabov et al., 2007) and CBSD68 dataset (Martin et al., 2001). Qualitative results on the 9 images are shown in Appendix A.6.5; detected PSNR and stopping epochs on the CBSD68 dataset are reported in Table 3. For SB, the detection threshold parameter is fixed at 0.01. It is evident that both methods have similar detection performance for low noise levels but ES-WMV outperforms SB when the noise level is high. Also, ES-WMV tends to stop much earlier than SB, saving computational cost.

We compare VAL with our ES-WMV on the 9-image dataset with low/high-level Gaussian and impulse noise. Since Ding et al. (2022) takes 90% pixels to train DIP and that usually decreases the peak performance, we report the final PSNRs detected by both methods (See Fig. 7). The two ES methods perform very comparably in image denoising, which is probably due

to the mild violation of the iid assumption only, and also relatively low-degree information loss due to data splitting. The more complex nonlinear BID in Section 3.3 reveals their gap.

ES-WMV as a helper for DIP variants DD, DIP+TV, GP-DIP represent different regularization strategies for controlling overfitting. A critical issue, however, is setting the right hyperparameters for them so that overfitting is removed while peak-level performance is preserved. So practically, these methods are not free from overfitting, especially when the noise level is high. Thus, instead of treating them as

Figure 7: Comparison of VAL and ES-WMV for Gaussian and impulse noise in terms of PSNR.

competitors, we test if ES-WMV can reliably detect good ES points for them. We focus on Gaussian denoising, and report the results in Fig. 8 (a)-(c) and Appendix A.6.6. ES-WMV is able to attain ≤ 1 PNSR gap for most of the cases, with few outliers. These regularizations typically change the recovery trajectory. We suspect that finetuning of our method may improve on these corner cases.

ES-WMV as a helper for implicit neural representations (INRs) INRs, such as Tancik et al. (2020) and Sitzmann et al. (2020), use multilayer perceptrons to represent high-frequency functions in low-dimensional problem domains and have achieved superior results on complex 3D visual tasks. We further extend our ES-WMV to help the INR family and take SIREN (Sitzmann et al., 2020) as an example. SIREN parameterizes x as the discretization of a continuous function: this function takes into spatial coordinates and returns the corresponding function values. In this experiment, we test SIREN as a replacement of DIP models for Gaussian denoising, and summarize the results in Fig. 8 (d) and Appendix A.6.6. ES-WMV is again able to detect near-peak performance for most images.

Figure 8: Performance of ES-WMV on DD, GP-DIP, DIP-TV, and SIREN for Gaussian denoising in terms of PSNR gaps. L: low noise level; H: high noise level.

3.2 MRI RECONSTRUCTION

We further test ES-WMV on MRI reconstruction, a classical linear IP with a nontrivial forward mapping: $y \approx \mathcal{F}(x)$, where $\mathcal{F}$ is the subsampled Fourier

Table 4: ConvDecoder on MRI reconstruction for **30 cases**: mean and (std). (**D**: Detected)

PSNR(**D**)	PSNR Gap	SSIM(**D**)	SSIM Gap
32.63 (2.36)	0.23 (0.32)	0.81 (0.09)	0.01 (0.01)

operator, and we use ≈ to indicate the noise encountered in practical MRI imaging may be hybrid (e.g., additive, shot) and uncertain. Here, we take 8-fold undersampling and parametrize x using "Conv-Decoder" (Darestani & Heckel, 2021), a variant of DD. Due to the heavy overparameterization, overfitting occurs and ES is needed. Darestani & Heckel (2021) directly set the stopping point at the 2500-th epoch, and we run our ES-WMV. We pick two random cases (C1: 1001339 and C2: 1000190) from Darestani & Heckel (2021), which are part of the same fastMRI datatset (Zbontar et al., 2018). Fig. 20 reports the detection performance (quality measured in SSIM, to be consistent with Darestani & Heckel (2021)). It is clear that ES-WMV detects near-peak performance for both cases, and it is adaptive enough to yield comparable or better ES points than heuristically fixed ES points. Besides the two examples, we further test our ES-WMV on ConvDecoder for **30 cases** from the fastMRI dataset (see Table 4), which shows the precise and stable detection of ES-WMV.

3.3 BLIND IMAGE DEBLURRING (BID)

In BID, a blurry and noisy image is given, and the goal is to recover a sharp and clean image. The blur is mostly caused by motion and/or optical nonideality in the camera, and the forward process is often modeled as $\boldsymbol{y} = \boldsymbol{k} * \boldsymbol{x} + \boldsymbol{n}$, where $\boldsymbol{k}$ is blur kernel, $\boldsymbol{n}$ models additive sensory noise, and $*$ is linear convolution to model the spatial uniformity of the blur effect (Szeliski, 2021). BID is a very challenging visual IP due to the bilinearity: $(\boldsymbol{k}, \boldsymbol{x}) \mapsto \boldsymbol{k} * \boldsymbol{x}$. Recently, Ren et al. (2020); Wang et al. (2019); Asim et al. (2019); Tran et al. (2021) have tried to use DIP models to solve BID by modeling $\boldsymbol{k}$ and $\boldsymbol{x}$ as two separate DNNs, i.e., $\min_{\boldsymbol{\theta}_k, \boldsymbol{\theta}_x} \|\boldsymbol{y} - G_{\boldsymbol{\theta}_k}(\boldsymbol{z}_k) * G_{\boldsymbol{\theta}_x}(\boldsymbol{z}_x)\|_2^2 + \lambda \|\nabla G_{\boldsymbol{\theta}_x}(\boldsymbol{z}_x)\|_1 / \|\nabla G_{\boldsymbol{\theta}_x}(\boldsymbol{z}_x)\|_2$, where the reg-

Figure 9: Top left: ES-WMV on BID; Top right: visual results of ES-WMV; Bottom: quantitative results of ES-WMV and VAL, respectively

ularizer is to promote sparsity in the gradient domain for the reconstruction of $\boldsymbol{x}$, as is standard in BID. Here, we follow Ren et al. (2020) and choose multi-layer perceptron (MLP) with softmax activation for $G_{\boldsymbol{\theta}_k}$, and the canonical DIP model (CNN-based encoder-decoder architecture) for $G_{\boldsymbol{\theta}_x}(\boldsymbol{z}_x)$. We change their regularizer from the original $\|\nabla G_{\boldsymbol{\theta}_x}(\boldsymbol{z}_x)\|_1$ to the current, as their original formulation is tested only on a very low noise level, $\sigma = 10^{-5}$ and no overfitting is observed. We set to work with higher noise level $\sigma = 10^{-3}$, and we find that their original formulation does not work. The positive effect of the modified regularizer on BID is discussed in Krishnan et al. (2011).

For our experiment, we take 4 images and 3 kernels from the standard Levin dataset (Levin et al., 2011), resulting in 12 image-kernel combinations. The high noise level leads to substantial overfitting, as shown in Fig. 9 (top left). Nonetheless, ES-WMV can reliably detect good ES points and lead to impressive visual reconstructions (see Fig. 9 (top right)). We perform systematic comparison of VAL and our ES-WMV on this difficult nonlinear IP, as we suspect that nonlinearity can break VAL as discussed in Section 1, and subsampling the observation $\boldsymbol{y}$ for training-validation splitting may be unwise. Our results (Fig. 9 (bottom left/right)) confirm these predictions: the peak performance is much worse after a small fraction of elements in $\boldsymbol{y}$ are removed (here we take 10% away for validation). In contrast, our ES-WMV returns quantitatively near-peak performance, far better than leaving the process to overfit.

3.4   ABLATION STUDY

The window size W (default: 100) and patience number P (default: 1000) are the only hyperparameters for ES-WMV. To study their impact on ES detection, we vary them across a range and check how the detection gap changes for Gaussian denoising with medium-level noise,

Figure 10: Effect of W and P

as shown in Fig. 10 for PSNR gaps and Appendix A.6.10 for SSIM gaps. Our method is robust against these changes, and it seems larger W and P can bring in marginal improvement.

4   DISCUSSION

We have proposed a simple yet effective ES detection method (ES-WMV, and the ES-EMV variant) that works robustly across multiple visual IPs and DIP variants. In comparison, competing ES methods are noise- or DIP-model-specific, and only work for limited scenarios; Li et al. (2021) has comparable performance but it slows down the running speed too much; validation-based ES (Ding et al., 2022) works well for the simple denoising task while lags behind our ES method a lot in nonlinear IPs, e.g., BID. As for limitations, our theoretical justification is only partial, sharing the same difficulty of analyzing DNNs in general. Our ES method struggles with images with substantial high-frequency components; DIP needs to run numerous iterative steps for every instance, which is not ideal for time-constrained applications.

REFERENCES

Abdelrahman Abdelhamed, Mahmoud Afifi, Radu Timofte, Michael S. Brown, Yue Cao, Zhilu Zhang, Wangmeng Zuo, Xiaoling Zhang, Jiye Liu, Wendong Chen, Changyuan Wen, Meng Liu, Shuailin Lv, Yunchao Zhang, Zhihong Pan, Baopu Li, Teng Xi, Yanwen Fan, Xiyu Yu, Gang Zhang, Jingtuo Liu, Junyu Han, Errui Ding, Songhyun Yu, Bumjun Park, Jechang Jeong, Shuai Liu, Ziyao Zong, Nan Nan, Chenghua Li, Zengli Yang, Long Bao, Shuangquan Wang, Dongwoon Bai, Jungwon Lee, Youngjung Kim, Kyeongha Rho, Changyeop Shin, Sungho Kim, Pengliang Tang, Yiyun Zhao, Yuqian Zhou, Yuchen Fan, Thomas Huang, Zhihao Li, Nisarg A. Shah, Wei Liu, Qiong Yan, Yuzhi Zhao, Marcin Możejko, Tomasz Latkowski, Lukasz Treszczotko, Michał Szafraniuk, Krzysztof Trojanowski, Yanhong Wu, Pablo Navarrete Michelini, Fengshuo Hu, Yunhua Lu, Sujin Kim, Wonjin Kim, Jaayeon Lee, Jang-Hwan Choi, Magauiya Zhussip, Azamat Khassenov, Jong Hyun Kim, Hwechul Cho, Priya Kansal, Sabari Nathan, Zhangyu Ye, Xiwen Lu, Yaqi Wu, Jiangxin Yang, Yanlong Cao, Siliang Tang, Yanpeng Cao, Matteo Maggioni, Ioannis Marras, Thomas Tanay, Gregory Slabaugh, Youliang Yan, Myungjoo Kang, Han-Soo Choi, Kyungmin Song, Shusong Xu, Xiaomu Lu, Tingniao Wang, Chunxia Lei, Bin Liu, Rajat Gupta, and Vineet Kumar. Ntire 2020 challenge on real image denoising: Dataset, methods and results. *arXiv:2005.04117*, 2020.

Samaneh Aminikhanghahi and Diane J. Cook. A survey of methods for time series change point detection. *Knowledge and Information Systems*, 51(2):339–367, sep 2016. doi: 10.1007/s10115-016-0987-z.

Muhammad Asim, Fahad Shamshad, and Ali Ahmed. Blind image deconvolution using deep generative priors. *arXiv:1802.04073*, 2019.

Daniel Otero Baguer, Johannes Leuschner, and Maximilian Schmidt. Computed tomography reconstruction using deep image prior and learned reconstruction methods. *Inverse Problems*, 36(9):094004, Sep 2020. ISSN 1361-6420. doi: 10.1088/1361-6420/aba415. URL http://dx.doi.org/10.1088/1361-6420/aba415.

Khosro Bahrami and Alex C. Kot. A fast approach for no-reference image sharpness assessment based on maximum local variation. *IEEE Signal Processing Letters*, 21(6):751–755, jun 2014. doi: 10.1109/lsp.2014.2314487.

Pasquale Cascarano, Andrea Sebastiani, Maria Colomba Comes, Giorgia Franchini, and Federica Porta. Combining weighted total variation and deep image prior for natural and medical image restoration via admm. *arXiv:2009.11380*, 2021.

Zezhou Cheng, Matheus Gadelha, Subhransu Maji, and Daniel Sheldon. A bayesian perspective on the deep image prior. In *CVPR*. IEEE, jun 2019a. doi: 10.1109/cvpr.2019.00559.

Zezhou Cheng, Matheus Gadelha, Subhransu Maji, and Daniel Sheldon. A bayesian perspective on the deep image prior. *arXiv:1904.07457*, 2019b.

Frederique Crete, Thierry Dolmiere, Patricia Ladret, and Marina Nicolas. The blur effect: perception and estimation with a new no-reference perceptual blur metric. In Bernice E. Rogowitz, Thrasyvoulos N. Pappas, and Scott J. Daly (eds.), *SPIE Proceedings*. SPIE, feb 2007. doi: 10.1117/12.702790.

Kostadin Dabov, Alessandro Foi, Vladimir Katkovnik, and Karen Egiazarian. Image denoising by sparse 3-d transform-domain collaborative filtering. *IEEE Transactions on Image Processing*, 16 (8):2080–2095, aug 2007. doi: 10.1109/tip.2007.901238.

Mohammad Zalbagi Darestani and Reinhard Heckel. Accelerated mri with un-trained neural networks. *IEEE Transactions on Computational Imaging*, 7:724–733, 2021.

Lijun Ding, Liwei Jiang, Yudong Chen, Qing Qu, and Zhihui Zhu. Rank overspecified robust matrix recovery: Subgradient method and exact recovery. *arXiv:2109.11154*, September 2021.

Lijun Ding, Zhen Qin, Liwei Jiang, Jinxin Zhou, and Zhihui Zhu. A Validation Approach to Overparameterized Matrix and Image Recovery, September 2022. URL http://arxiv.org/abs/2209.10675. arXiv:2209.10675 [cs, eess, math, stat].

Yosef Gandelsman, Assaf Shocher, and Michal Irani. "double-dip": Unsupervised image decomposition via coupled deep-image-priors. In *CVPR*, June 2019.

Stuart Geman, Elie Bienenstock, and René Doursat. Neural Networks and the Bias/Variance Dilemma. *Neural Computation*, 4(1):1–58, January 1992. ISSN 0899-7667, 1530-888X. doi: 10.1162/neco.1992.4.1.1. URL https://direct.mit.edu/neco/article/4/1/1-58/5624.

Kuang Gong, Ciprian Catana, Jinyi Qi, and Quanzheng Li. Direct reconstruction of linear parametric images from dynamic pet using nonlocal deep image prior. *arXiv:2106.10359*, 2021.

Paul Hand, Oscar Leong, and Vladislav Voroninski. Phase retrieval under a generative prior. *arXiv:1807.04261*, 2018.

Fumio Hashimoto and Kibo Ote. Direct pet image reconstruction incorporing deep image prior and a forward projection model. *arXiv:2109.00768*, 2021.

Reinhard Heckel and Paul Hand. Deep decoder: Concise image representations from untrained non-convolutional networks. *arXiv preprint arXiv:1810.03982*, 2018.

Reinhard Heckel and Mahdi Soltanolkotabi. Compressive sensing with un-trained neural networks: Gradient descent finds a smooth approximation. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 4149–4158. PMLR, 13–18 Jul 2020a. URL https://proceedings.mlr.press/v119/heckel20a.html.

Reinhard Heckel and Mahdi Soltanolkotabi. Denoising and regularization via exploiting the structural bias of convolutional generators. In *ICLR*, 2020b.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *Proceedings of the International Conference on Learning Representations*, 2019.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. *In Advances in neural information processing systems (pp. 8571-8580) 2018*, June 2018.

Joel Janai, Fatma Güney, Aseem Behl, and Andreas Geiger. Computer vision for autonomous vehicles: Problems, datasets and state of the art. *Foundations and Trends® in Computer Graphics and Vision*, 12(1–3):1–308, 2020. doi: 10.1561/0600000079.

Yeonsik Jo, Se Young Chun, and Jonghyun Choi. Rethinking deep image prior for denoising. *arXiv:2108.12841*, 2021.

Dilip Krishnan, Terence Tay, and Rob Fergus. Blind deconvolution using a normalized sparsity measure. In *CVPR*, pp. 233–240. IEEE, 2011.

Anat Levin, Yair Weiss, Fredo Durand, and William T Freeman. Understanding blind deconvolution algorithms. *IEEE transactions on pattern analysis and machine intelligence*, 33(12):2354–2367, 2011.

Taihui Li, Zhong Zhuang, Hengyue Liang, Le Peng, Hengkang Wang, and Ju Sun. Self-validation: Early stopping for single-instance deep generative priors. In *The British Machine Vision Conference (BMVC)*, 2021.

Jiaming Liu, Yu Sun, Xiaojian Xu, and Ulugbek S. Kamilov. Image restoration using total variation regularized deep image prior. *arXiv:1810.12864*, 2018.

Xudong Ma, Paul Hill, and Alin Achim. Unsupervised image fusion using deep image priors. *arXiv:2110.09490*, October 2021.

D. Martin, C. Fowlkes, D. Tal, and J. Malik. A database of human segmented natural images and its application to evaluating segmentation algorithms and measuring ecological statistics. In *Proceedings Eighth IEEE International Conference on Computer Vision. ICCV 2001*. IEEE Comput. Soc, 2001. doi: 10.1109/iccv.2001.937655.

Gary Mataev, Peyman Milanfar, and Michael Elad. Deepred: Deep image prior powered by red. In *Proceedings of the IEEE/CVF International Conference on Computer Vision Workshops*, pp. 0–0, 2019.

Christopher A. Metzler, Ali Mousavi, Reinhard Heckel, and Richard G. Baraniuk. Unsupervised learning with stein's unbiased risk estimator. *arXiv:1805.10531*, May 2018.

Anish Mittal, Anush Krishna Moorthy, and Alan Conrad Bovik. No-reference image quality assessment in the spatial domain. *IEEE Transactions on image processing*, 21(12):4695–4708, 2012a.

Anish Mittal, Rajiv Soundararajan, and Alan C Bovik. Making a "completely blind" image quality analyzer. *IEEE Signal processing letters*, 20(3):209–212, 2012b.

Gregory Ongie, Ajil Jalal, Christopher A. Metzler, Richard G. Baraniuk, Alexandros G. Dimakis, and Rebecca Willett. Deep learning techniques for inverse problems in imaging. *IEEE Journal on Selected Areas in Information Theory*, 1(1):39–56, may 2020. doi: 10.1109/jsait.2020.2991563.

Adnan Qayyum, Inaam Ilahi, Fahad Shamshad, Farid Boussaid, Mohammed Bennamoun, and Junaid Qadir. Untrained neural network priors for inverse imaging problems: A survey. *TechRxiv*, mar 2021. doi: 10.36227/techrxiv.14208215.v1.

Dongwei Ren, Kai Zhang, Qilong Wang, Qinghua Hu, and Wangmeng Zuo. Neural blind deconvolution using deep priors. In *CVPR*, June 2020.

Zenglin Shi, Pascal Mettes, Subhransu Maji, and Cees G. M. Snoek. On measuring and controlling the spectral bias of the deep image prior. *arXiv:2107.01125*, 2021.

Vincent Sitzmann, Julien Martel, Alexander Bergman, David Lindell, and Gordon Wetzstein. Implicit neural representations with periodic activation functions. *Advances in Neural Information Processing Systems*, 33, 2020.

Zhaodong Sun. Solving inverse problems with hybrid deep image priors: the challenge of preventing overfitting. *arXiv:2011.01748*, 2021.

Richard Szeliski. *Computer Vision*. Springer London, 2nd edition, 2021. doi: 10.1007/978-1-84882-935-0.

Hossein Talebi and Peyman Milanfar. Nima: Neural image assessment. *IEEE Transactions on Image Processing*, 27(8):3998–4011, 2018.

Matthew Tancik, Pratul P. Srinivasan, Ben Mildenhall, Sara Fridovich-Keil, Nithin Raghavan, Utkarsh Singhal, Ravi Ramamoorthi, Jonathan T. Barron, and Ren Ng. Fourier Features Let Networks Learn High Frequency Functions in Low Dimensional Domains, June 2020. URL http://arxiv.org/abs/2006.10739. arXiv:2006.10739 [cs].

Kshitij Tayal, Raunak Manekar, Zhong Zhuang, David Yang, Vipin Kumar, Felix Hofmann, and Ju Sun. Phase retrieval using single-instance deep generative prior. In *OSA Optical Sensors and Sensing Congress 2021 (AIS, FTS, HISE, SENSORS, ES)*. OSA, 2021. doi: 10.1364/ais.2021. jw2a.37.

Phong Tran, Anh Tuan Tran, Quynh Phung, and Minh Hoai. Explore image deblurring via encoded blur kernel space. In *CVPR*. IEEE, jun 2021. doi: 10.1109/cvpr46437.2021.01178.

Dmitry Ulyanov, Andrea Vedaldi, and Victor Lempitsky. Deep image prior. In *CVPR*, pp. 9446–9454, 2018.

Tomas Vaškevičius, Varun Kanade, and Patrick Rebeschini. Implicit regularization for optimal sparse recovery, 2019.

Dave Van Veen, Ajil Jalal, Mahdi Soltanolkotabi, Eric Price, Sriram Vishwanath, and Alexandros G. Dimakis. Compressed sensing with deep image prior and learned regularization. *arXiv:1806.06438*, 2020.

Zhunxuan Wang, Zipei Wang, Qiqi Li, and Hakan Bilen. Image deconvolution with deep image and kernel priors. *arXiv:1910.08386*, 2019.

Francis Williams, Teseo Schneider, Claudio Silva, Denis Zorin, Joan Bruna, and Daniele Panozzo. Deep geometric prior for surface reconstruction. *arXiv:1811.10943*, 2019.

Jun Xu, Hui Li, Zhetong Liang, David Zhang, and Lei Zhang. Real-world Noisy Image Denoising: A New Benchmark, April 2018. URL `http://arxiv.org/abs/1804.02603`. arXiv:1804.02603 [cs].

Burhaneddin Yaman, Seyed Amir Hossein Hosseini, and Mehmet Akcakaya. Zero-shot physics-guided deep learning for subject-specific MRI reconstruction. In *NeurIPS 2021 Workshop on Deep Learning and Inverse Problems*, 2021. URL `https://openreview.net/forum?id=Nzv2jICkWV7`.

Zitong Yang, Yaodong Yu, Chong You, Jacob Steinhardt, and Yi Ma. Rethinking Bias-Variance Trade-off for Generalization of Neural Networks, December 2020. URL `http://arxiv.org/abs/2002.11328`. arXiv:2002.11328 [cs, stat].

Jaejun Yoo, Kyong Hwan Jin, Harshit Gupta, Jerome Yerly, Matthias Stuber, and Michael Unser. Time-dependent deep image prior for dynamic mri. *arXiv:1910.01684*, 2021.

Chong You, Zhihui Zhu, Qing Qu, and Yi Ma. Robust recovery via implicit bias of discrepant learning rates for double over-parameterization. *arXiv:2006.08857*, 2020.

Jure Zbontar, Florian Knoll, Anuroop Sriram, Tullie Murrell, Zhengnan Huang, Matthew J. Muckley, Aaron Defazio, Ruben Stern, Patricia Johnson, Mary Bruno, Marc Parente, Krzysztof J. Geras, Joe Katsnelson, Hersh Chandarana, Zizhao Zhang, Michal Drozdzal, Adriana Romero, Michael Rabbat, Pascal Vincent, Nafissa Yakubova, James Pinkerton, Duo Wang, Erich Owens, C. Lawrence Zitnick, Michael P. Recht, Daniel K. Sodickson, and Yvonne W. Lui. fastmri: An open dataset and benchmarks for accelerated mri. *arXiv:1811.08839*, November 2018.

Zhong Zhuang, Taihui Li, Hengkang Wang, and Ju Sun. Blind Image Deblurring with Unknown Kernel Size and Substantial Noise, August 2022. URL `http://arxiv.org/abs/2208.09483`. arXiv:2208.09483 [cs, eess].

A APPENDIX

A.1 ACRONYMS

List of Common Acronyms (in alphabetic order)	
CI	computational imaging
CNN	convolutional neural network
DD	deep decoder
DIP	deep image prior
DIP-TV	DIP with total variation regularization
DL	deep learning
DNN	deep neural network
ELTO	early-learning-then-overfitting
ES	early stopping
EMA	exponential moving average
EMV	exponential moving variance
FR-IQM	full-reference image quality metric
GP-DIP	Gaussian process DIP
INR	implicit neural representations
IP	inverse problem
MSE	mean squared error
NR-IQM	no-reference image quality metric
PSNR	peak signal-to-noise ratio
SIREN	sinusoidal representation networks
SOTA	state-of-the-art
VAR	variance
WMV	windowed moving variance

A.2 Proof of 2.1

Proof. To simplify the notation, we write $\widehat{y} \doteq y - G_{\theta^0}(z)$, $J \doteq J_G(\theta^0)$, and $c \doteq \theta - \theta^0$. So the least-squares objective in Eq. (4) is equivalent to

$$\|\widehat{y} - Jc\|_2^2 \tag{8}$$

and the gradient update reads

$$c^t = c^{t-1} - \eta J^{\mathsf{T}}\left(Jc^{k-1} - \widehat{y}\right), \tag{9}$$

where $c^0 = 0$ and $x^t = Jc^t + G_{\theta^0}(z)$. The residual at time t can be computed as

$$r^t \doteq \widehat{y} - Jc^t \tag{10}$$

$$= \widehat{y} - J\left(c^{t-1} - \eta J^{\mathsf{T}}\left(J\theta^{t-1} - \widehat{y}\right)\right) \tag{11}$$

$$= \left(I - \eta JJ^{\mathsf{T}}\right)\left(\widehat{y} - Jc^{t-1}\right) \tag{12}$$

$$= \left(I - \eta JJ^{\mathsf{T}}\right)^2\left(\widehat{y} - Jc^{t-2}\right) = \ldots \tag{13}$$

$$= \left(I - \eta JJ^{\mathsf{T}}\right)^t\left(\widehat{y} - Jc^0\right) \quad (\text{using } c^0 = 0) \tag{14}$$

$$= \left(I - \eta JJ^{\mathsf{T}}\right)^t \widehat{y}. \tag{15}$$

Assume the SVD of J as $J = W\Sigma V^{\mathsf{T}}$. Then

$$r^t = \left(I - \eta W\Sigma^2 W^{\mathsf{T}}\right)^t \widehat{y} = \sum_i \left(1 - \eta\sigma_i^2\right)^t w_i^{\mathsf{T}}\widehat{y}w_i \tag{16}$$

and so

$$Jc^t = \widehat{y} - r^t = \sum_i \left(1 - \left(1 - \eta\sigma_i^2\right)^t\right) w_i^{\mathsf{T}}\widehat{y}w_i. \tag{17}$$

Consider a set of W vectors $\mathcal{V} = \{v_1, \ldots, v_W\}$. We have that the empirical variance

$$\text{VAR}(\mathcal{V}) = \frac{1}{W}\sum_{w=1}^{W}\left\|v_w - \frac{1}{W}\sum_{j=1}^{W}v_j\right\|_2^2 = \frac{1}{W}\sum_{w=1}^{W}\|v_w\|_2^2 - \left\|\frac{1}{W}\sum_{w=1}^{W}v_w\right\|_2^2. \tag{18}$$

So the variance of the set $\{x^t, x^{t+1}, \ldots, x^{t+W-1}\}$, same as the variance of the set $\{Jc^t, Jc^{t+1}, \ldots, Jc^{t+W-1}\}$, can be calculated as

$$\frac{1}{W}\sum_{w=0}^{W-1}\sum_i \left(w_i^{\mathsf{T}}\widehat{y}\right)^2\left(1 - \left(1 - \eta\sigma_i^2\right)^{t+w}\right)^2 - \frac{1}{W^2}\sum_i \left(w_i^{\mathsf{T}}\widehat{y}\right)^2\left(\sum_{w=0}^{W-1} 1 - \left(1 - \eta\sigma_i^2\right)^{t+w}\right)^2 \tag{19}$$

$$= \frac{1}{W^2}\sum_i \left(w_i^{\mathsf{T}}\widehat{y}\right)^2\left[W\sum_{w=0}^{W-1}\left(1 - \left(1 - \eta\sigma_i^2\right)^{t+w}\right)^2 - \left(\sum_{w=0}^{W-1} 1 - \left(1 - \eta\sigma_i^2\right)^{t+w}\right)^2\right] \tag{20}$$

$$= \frac{1}{W^2}\sum_i \left(w_i^{\mathsf{T}}\widehat{y}\right)^2\left[\left(W^2 + W\frac{(1 - \eta\sigma_i^2)^{2t}(1 - (1 - \eta\sigma_i^2)^{2W})}{1 - (1 - \eta\sigma_i^2)^2} - 2W\frac{(1 - \eta\sigma_i^2)^t(1 - (1 - \eta\sigma_i^2)^W)}{\eta\sigma_i^2}\right)\right.$$
$$\left. - \left(W^2 - 2W\frac{(1 - \eta\sigma_i^2)^t(1 - (1 - \eta\sigma_i^2)^W)}{\eta\sigma_i^2} + \frac{(1 - \eta\sigma_i^2)^{2t}\left(1 - (1 - \eta\sigma_i^2)^W\right)^2}{\eta^2\sigma_i^4}\right)\right] \tag{21}$$

$$= \frac{1}{W^2}\sum_i \langle w_i, \widehat{y}\rangle^2 \frac{(1 - \eta\sigma_i^2)^{2t}}{\eta\sigma_i^2}\left[W\frac{1 - (1 - \eta\sigma_i^2)^{2W}}{2 - \eta\sigma_i^2} - \frac{(1 - (1 - \eta\sigma_i^2)^W)^2}{\eta\sigma_i^2}\right]. \tag{22}$$

So the constants C_{W,η,σ_i}'s are defined as

$$C_{W,\eta,\sigma_i} \doteq \frac{1}{W^2\eta\sigma_i^2}\left[W\frac{1-(1-\eta\sigma_i^2)^{2W}}{2-\eta\sigma_i^2} - \frac{(1-(1-\eta\sigma_i^2)^W)^2}{\eta\sigma_i^2}\right]. \tag{23}$$

To see they are nonnegative, it is sufficient to show that

$$W\frac{1-(1-\eta\sigma_i^2)^{2W}}{2-\eta\sigma_i^2} - \frac{(1-(1-\eta\sigma_i^2)^W)^2}{\eta\sigma_i^2} \geq 0$$

$$\iff \eta\sigma_i^2 W\left(1-(1-\eta\sigma_i^2)^{2W}\right) - \left(2-\eta\sigma_i^2\right)(1-(1-\eta\sigma_i^2)^W)^2 \geq 0. \tag{24}$$

Now consider the function

$$h(\xi, W) = \xi W\left(1-(1-\xi)^{2W}\right) - (2-\xi)(1-(1-\xi)^W)^2 \quad \xi \in [0,1], W \geq 1. \tag{25}$$

First, one can easily check that $\partial_W h(\xi, W) \geq 0$ for all $W \geq 1$ and all $\xi \in [0,1]$, i.e., $h(\xi, W)$ is monotonically increasing with respect to W. Thus, in order to prove $C_{W,\eta,\sigma_i} \geq 0$, it suffices to show that $h(\xi, 1) \geq 0$. Now

$$h(\xi, 1) = \xi\left(1-(1-\xi)^2\right) - (2-\xi)\xi^2 = 0, \tag{26}$$

completing the proof. $\qquad\square$

A.3 Proof of 2.2

We first restate Theorem 2 in Heckel & Soltanolkotabi (2020b).

Theorem A.1 (Heckel & Soltanolkotabi (2020b))**.** *Let $x \in \mathbb{R}^n$ be a signal in the span of the first p trigonometric basis functions, and consider a noisy observation $y = x + n$, where the noise $n \sim \mathcal{N}\left(0, \xi^2/n \cdot I\right)$. To denoise this signal, we fit a two-layer generator network $G_C(B) = \mathrm{ReLU}(UBC)v$, where $v = [1,\ldots,1,-1,\ldots,-1]/\sqrt{k}$, and $B \sim_{iid} \mathcal{N}(0,1)$, and U is an upsampling operator that implements circular convolution with a given kernel u. Denote $\sigma \doteq \|u\|_2|Fg(u \circledast u/\|u\|_2^2)|^{1/2}$ where $g(t) = (1 - \cos^{-1}(t)/\pi)t$ and $\circledast$ denotes the circular convolution. Fix any $\varepsilon \in (0, \sigma_p/\sigma_1]$, and suppose $k \geq C_u n/\varepsilon^8$, where $C_u > 0$ is a constant only depending on u. Consider gradient descent with step size $\eta \leq \|Fu\|_\infty^{-2}$($Fu$ is the Fourier transform of u) starting from $C_0 \sim_{iid} \mathcal{N}\left(0, \omega^2\right)$, entries, $\omega \propto \frac{\|y\|_2}{\sqrt{n}}$. Then, for all iterates t obeying $t \leq \frac{100}{\eta\sigma_p^2}$, the reconstruction error obeys*

$$\|G_{C^t}(B) - x\|_2 \leq \left(1-\eta\sigma_p^2\right)^t\|x\|_2 + \sqrt{\sum_{i=1}^n\left((1-\eta\sigma_i^2)^t - 1\right)^2\left(w_i^\intercal n\right)^2} + \varepsilon\|y\|_2$$

with probability at least $1 - \exp\left(-k^2\right) - n^{-2}$.

Note that since $B \sim_{iid} \mathcal{N}(0,1)$ and hence is full-rank with probability one, the original Theorem 1 & 2 of Heckel & Soltanolkotabi (2020b) rename BC into C' and state the result directly on C', i.e., assume the model is $\mathrm{ReLU}(UC')v$. It is easy to see the original theorems imply the version stated here.

With this, we can obtain our Theorem 2.2, stated in full technical form here:

Theorem A.2. *Let $x \in \mathbb{R}^n$ be a signal in the span of the first p trigonometric basis functions, and consider a noisy observation $y = x + n$, where the noise $n \sim \mathcal{N}\left(0, \xi^2/n \cdot I\right)$. To denoise this signal, we fit a two-layer generator network $G_C(B) = \mathrm{ReLU}(UBC)v$, where $v = [1,\ldots,1,-1,\ldots,-1]/\sqrt{k}$, and $B \sim_{iid} \mathcal{N}(0,1)$, and U is an upsampling operator that implements circular convolution with a given kernel u. Denote $\sigma \doteq \|u\|_2|Fg(u \circledast u/\|u\|_2^2)|^{1/2}$ where $g(t) = (1 - \cos^{-1}(t)/\pi)t$ and $\circledast$ denotes the circular convolution. Fix any $\varepsilon \in (0, \sigma_p/\sigma_1]$, and suppose $k \geq C_u n/\varepsilon^8$, where $C_u > 0$ is a constant only depending on u. Consider gradient descent with step size $\eta \leq \|Fu\|_\infty^{-2}$($Fu$ is the Fourier transform of u) starting from $C_0 \sim_{iid} \mathcal{N}\left(0, \omega^2\right)$, entries, $\omega \propto \frac{\|y\|_2}{\sqrt{n}}$. Then, for all iterates t obeying $t \leq \frac{100}{\eta\sigma_p^2}$, our WMV obeys*

$$\mathrm{WMV} \leq \frac{12}{W}\|x\|_2^2\frac{\left(1-\eta\sigma_p^2\right)^{2t}}{1-(1-\eta\sigma_p^2)^2} + 12\sum_{i=1}^n\left(\left(1-\eta\sigma_i^2\right)^{t+W-1} - 1\right)^2\left(w_i^\intercal n\right)^2 + 12\varepsilon^2\|y\|_2^2 \tag{27}$$

with probability at least $1 - \exp\left(-k^2\right) - n^{-2}$.

Proof. We make use of the basic inequality: $\|\boldsymbol{a} - \boldsymbol{b}\|_2^2 \leq 2\|\boldsymbol{a}\|_2^2 + 2\|\boldsymbol{b}\|_2^2$ for any two vectors $\boldsymbol{a}, \boldsymbol{b}$ of compatible dimension. We have

$$\frac{1}{W} \sum_{w=0}^{W-1} \|G_{\boldsymbol{C}^{t+w}}(\boldsymbol{B}) - \frac{1}{W} \sum_{j=0}^{W-1} G_{\boldsymbol{C}^{t+j}}(\boldsymbol{B})\|_2^2 \tag{28}$$

$$= \frac{1}{W} \sum_{w=0}^{W-1} \|G_{\boldsymbol{C}^{t+w}}(\boldsymbol{B}) - \boldsymbol{x} + \boldsymbol{x} - \frac{1}{W} \sum_{j=0}^{W-1} G_{\boldsymbol{C}^{t+j}}(\boldsymbol{B})\|_2^2 \tag{29}$$

$$\leq \left(\frac{2}{W} \sum_{w=0}^{W-1} \|G_{\boldsymbol{C}^{t+w}}(\boldsymbol{B}) - \boldsymbol{x}\|_2^2\right) + 2\|\boldsymbol{x} - \frac{1}{W} \sum_{j=0}^{W-1} G_{\boldsymbol{C}^{t+j}}(\boldsymbol{B})\|_2^2 \tag{30}$$

$$\leq \frac{2}{W} \sum_{w=0}^{W-1} \|G_{\boldsymbol{C}^{t+w}}(\boldsymbol{B}) - \boldsymbol{x}\|_2^2 + \frac{2}{W} \sum_{j=0}^{W-1} \|G_{\boldsymbol{C}^{t+j}}(\boldsymbol{B}) - \boldsymbol{x}\|_2^2 \tag{31}$$

$$(\boldsymbol{z} \mapsto \|\boldsymbol{z} - \boldsymbol{x}\|_2^2 \text{ convex and Jensen's inequality})$$

$$= \frac{4}{W} \sum_{w=0}^{W-1} \|G_{\boldsymbol{C}^{t+w}}(\boldsymbol{B}) - \boldsymbol{x}\|_2^2. \tag{32}$$

In view of Theorem A.1,

$$\|G_{\boldsymbol{C}^{t+w}}(\boldsymbol{B}) - \boldsymbol{x}\|_2^2 \leq 3\left(1 - \eta\sigma_p^2\right)^{2t+2w} \|\boldsymbol{x}\|_2^2 + 3\sum_{i=1}^{n} \left(\left(1 - \eta\sigma_j^2\right)^{t+w} - 1\right)^2 (\boldsymbol{w}_i^\mathsf{T}\boldsymbol{n})^2 + 3\varepsilon^2\|\boldsymbol{y}\|_2^2. \tag{33}$$

Thus,

$$\sum_{w=0}^{W-1} \|G_{\boldsymbol{C}^{t+w}}(\boldsymbol{B}) - \boldsymbol{x}\|_2^2$$

$$\leq 3\|\boldsymbol{x}\|_2^2 \sum_{w=0}^{W-1} \left(1 - \eta\sigma_p^2\right)^{2t+2w} + 3\sum_{w=0}^{W-1}\sum_{i=1}^{n} \left(\left(1 - \eta\sigma_i^2\right)^{t+w} - 1\right)^2 (\boldsymbol{w}_i^\mathsf{T}\boldsymbol{n})^2 + 3W\varepsilon^2\|\boldsymbol{y}\|_2^2 \tag{34}$$

$$\leq 3\|\boldsymbol{x}\|_2^2 \frac{\left(1 - \eta\sigma_p^2\right)^{2t}\left(1 - (1 - \eta\sigma_p^2)^{2W}\right)}{1 - (1 - \eta\sigma_p^2)^2} + 3W\sum_{i=1}^{n} \left(\left(1 - \eta\sigma_i^2\right)^{t+W-1} - 1\right)^2 (\boldsymbol{w}_i^\mathsf{T}\boldsymbol{n})^2 + 3W\varepsilon^2\|\boldsymbol{y}\|_2^2 \tag{35}$$

$$\leq 3\|\boldsymbol{x}\|_2^2 \frac{\left(1 - \eta\sigma_p^2\right)^{2t}}{1 - (1 - \eta\sigma_p^2)^2} + 3W\sum_{i=1}^{n} \left(\left(1 - \eta\sigma_i^2\right)^{t+W-1} - 1\right)^2 (\boldsymbol{w}_i^\mathsf{T}\boldsymbol{n})^2 + 3W\varepsilon^2\|\boldsymbol{y}\|_2^2, \tag{36}$$

completing the proof. $\qquad \square$

A.4 ES-EMV ALGORITHM

The exponential moving variance version of our method is summarized in Algorithm 2.

A.5 MORE DETAILS ON MAJOR ES METHODS

Here, we provide more details on major competing methods, all of them ES-based except for You et al. (2020).

Shi et al. (2021) operates on DD models, and proposes two modifications to change the spectral bias: (1) controlling the operator norm of the weight $\boldsymbol{w}$ for each convolutional layer by the normalization

$$\boldsymbol{w}' = \frac{\boldsymbol{w}}{\max\left(1, \|\boldsymbol{w}\|_{\text{op}}/\lambda\right)}, \tag{37}$$

Algorithm 2 DIP with ES–EMV

Input: random seed $\boldsymbol{z}$, randomly-initialized $G_{\boldsymbol{\theta}}$, forgetting factor $\alpha \in (0, 1)$, patience number P,
    iteration counter $k = 0$, $\mathrm{EMA}^0 = 0$, $\mathrm{EMV}^0 = 0$, $\mathrm{VAR}_{\min} = \infty$
Output: reconstruction $\boldsymbol{x}^*$
 1: **while** not stopped **do**
 2:    update $\boldsymbol{\theta}$ via Eq. (2) to obtain $\boldsymbol{\theta}^{k+1}$ and $\boldsymbol{x}^{k+1}$
 3:    $\mathrm{EMA}^{k+1} = (1 - \alpha)\mathrm{EMA}^k + \alpha \boldsymbol{x}^{k+1}$
 4:    $\mathrm{EMV}^{k+1} = (1 - \alpha)\mathrm{EMV}^k + \alpha(1 - \alpha)\|\boldsymbol{x}^{k+1} - \mathrm{EMA}^k\|_2^2$
 5:    **if** $\mathrm{VAR} < \mathrm{VAR}_{\min}$ **then**
 6:        $\mathrm{VAR}_{\min} \leftarrow \mathrm{VAR}$, $\boldsymbol{x}^* \leftarrow \boldsymbol{x}^{k+1}$
 7:    **end if**
 8:    **if** $\mathrm{VAR}_{\min}$ stagnates for P iterations **then**
 9:        stop and return $\boldsymbol{x}^*$
10:    **end if**
11:    $k = k + 1$
12: **end while**

---

ensuring that $\|\boldsymbol{w}'\|_{\mathrm{op}} \leq \lambda$, which in turn controls the Fourier spectrum of the underlying function represented by the layer; (2) performing Gaussian upsampling instead of the typical bilinear upsampling to suppress the smoothness effect of the latter. These two modifications with appropriate parameter setting (λ, and σ in Gaussian filtering) can improve the learning of the high-frequency components by DD, and allow the blurriness-over-sharpness stopping criterion

$$\Delta r\big(\boldsymbol{x}^t\big) = \frac{1}{W}\left|\sum_{w=1}^{W} r\big(\boldsymbol{x}^{t-w}\big) - \sum_{w=1}^{W} r\big(\boldsymbol{x}^{t-W-w}\big)\right|, \tag{38}$$

where $r(\boldsymbol{x}') = B(\boldsymbol{x}')/S(\boldsymbol{x}')$, and $B(\cdot)$ and $S(\cdot)$ are the blurriness and sharpness metrics in Crete et al. (2007) and Bahrami & Kot (2014), respectively. In other words, the criterion in Eq. (38) measures the change of average blurriness-over-sharpness ratios over consecutive windows of size W, and small changes indicate good ES points. But, as said, this criterion only works for the modified DD models and not other DIP variants, as acknowledged by the authors in Shi et al. (2021) and confirmed in our experiment (see Section 3.1).

Jo et al. (2021) targets Gaussian denoising with known noise levels (i.e., $\boldsymbol{y} = \boldsymbol{x} + \boldsymbol{n}$, where n is iid Gaussian noise), and considers the objective

$$\min_{\boldsymbol{\theta}} \frac{1}{n^2}\|\boldsymbol{y} - G_{\boldsymbol{\theta}}(\boldsymbol{y})\|_F^2 + \frac{\sigma^2}{n^2} \operatorname{tr} \boldsymbol{J}_{G_{\boldsymbol{\theta}}}(\boldsymbol{y}), \tag{39}$$

where $\operatorname{tr} \boldsymbol{J}_{G_{\boldsymbol{\theta}}}(\boldsymbol{y})$ is the trace of the network Jacobian with respect to the input, i.e., the divergence term in Jo et al. (2021). The divergence term is a proxy for controlling the capacity of the network. The paper then proposes a heuristic zero-crossing stopping criterion that stops the iteration when the loss starts to cross zero into negative values. Although the idea works reasonably well on Gaussian denoising with low and known noise level (the variance level σ^2 is explicitly needed in the regularization parameter ahead of the divergence term), it starts to break down when the noise level increases even if the right noise level is provided; see Section 3.1. Also, although the paper has extended the formulation to handle Poisson noise, it is unclear how to generalize the idea for handling other types of noise, as well as how to move beyond simple additive denoising problems.

Our previous work Li et al. (2021) proposes training an autoencoder online using the reconstruction sequence $\{\boldsymbol{x}^t\}_{t \geq 1}$:

$$\min_{\boldsymbol{w}, \boldsymbol{v}} \sum_{t \geq 1} \ell_{\mathrm{AE}}\big(\boldsymbol{x}^t, D_{\boldsymbol{w}} \circ E_{\boldsymbol{v}}\big(\boldsymbol{x}^t\big)\big). \tag{40}$$

Any new $\boldsymbol{x}^t$ is passed through the current autoencoder, and the reconstruction error ℓ_{AE} is recorded. We observe that the error curve typically follows a U-shape, and the valley of the curve is approximately aligned with the peak of the PNSR curve. We hence design an ES method by detecting the valley of the error curve. This method works reasonably well across different IPs and different

DIP variants. A major drawback is the efficiency: the overhead caused by online training of the autoencoder is order-of-magnitude larger than the cost of DIP update itself, as shown in **??**.

You et al. (2020) considers additive sparse (e.g., salt-and-pepper noise) noise only and proposes modeling the clean image and noise explicitly in the objective:

$$\min_{\boldsymbol{\theta}, \boldsymbol{g}, \boldsymbol{h}} \|\boldsymbol{y} - G_{\boldsymbol{\theta}}(\boldsymbol{z}) - (\boldsymbol{g} \circ \boldsymbol{g} - \boldsymbol{h} \circ \boldsymbol{h})\|_F^2, \tag{41}$$

where the overparametrized term $\boldsymbol{g} \circ \boldsymbol{g} - \boldsymbol{h} \circ \boldsymbol{h}$ ($\circ$ denotes the Hadamard product) is meant to capture the sparse noise, where a similar idea has proved effective for sparse recovery in Vaškevičius et al. (2019). Different properly-tuned learning rates for the clean image and sparse noise terms are necessary for success. The downside includes the prolonged running time as it pushes the peak reconstruction to the very last iteration, and the difficulty to extend the idea to other types of noise.

A.6 Additional experimental details & results

A.6.1 External codes

- DIP: https://github.com/DmitryUlyanov/deep-image-prior
- DD: https://github.com/reinhardh/supplement_deep_decoder
- DIP-TV: https://github.com/sedaboni/ADMM-DIPTV
- GP-DIP: https://people.cs.umass.edu/~zezhoucheng/gp-dip/
- DF-STE: https://github.com/gistvision/dip-denosing
- SV-ES: https://github.com/sun-umn/Self-Validation
- DOP: https://github.com/ChongYou/robust-image-recovery
- SB: https://github.com/shizenglin/Measure-and-Control-Spectral-Bias

A.6.2 Experiment Settings

Our default setup for all experiments is as follows. Our DIP model is the original one from Ulyanov et al. (2018); the optimizer is ADAM with a learning rate 0.01. For all other models, we use their default architectures, optimizers, and hyperparameters. For ES-WMV, the default window size $W = 100$, and patience number $P = 1000$. We use both PSNR and SSIM to access the reconstruction quality, and we report PSNR and SSIM gaps (the difference between our detected and peak numbers) as an indicator of our detection performance. For most experiments, we repeat the experiments 3 times to report the mean and standard deviation; when not, we explain why.

Noise generation Following the noise generation rules of Hendrycks & Dietterich (2019)[1], we simulate four kinds of noise and three intensity levels for each noise type. The detailed information is as follows.

- **Gaussian noise:** 0 mean additive Gaussian noise with variance 0.12, 0.18, and 0.26 for low, medium, and high noise levels, respectively;
- **Impulse noise:** also known as salt-and-pepper noise, replacing each pixel with probability $p \in [0, 1]$ into white or black pixel with half chance each. Low, medium, and high noise levels correspond to $p = 0.3, 0.5, 0.7$, respectively;
- **Speckle noise:** for each pixel $x \in [0, 1]$, the noisy pixel is $x(1 + \varepsilon)$, where ε is 0-mean Gaussian with a variance level 0.20, 0.35, 0.45 for low, medium, and high noise levels, respectively;
- **Shot noise:** also known as Poisson noise. For each pixel, $x \in [0, 1]$, the noisy pixel is Poisson distributed with rate λx, where λ is $25, 12, 5$ for low, medium, and high noise levels, respectively.

A.6.3 Denoising examples

On image denoising with different types and levels of noise, our ES method can help DIP to detect near-peak ES points, as shown in Fig. 11.

---

[1]https://github.com/hendrycks/robustness

Figure 11: Our ES-WMV method on DIP for denoising "F16" with different noise types and levels (top: low-level noise; bottom: high-level noise). Red curves are PSNR curves, and blue curves are VAR curves. The green bars indicate the detected ES point.

Figure 12: **High-level noise** detection performance in terms of PSNR gaps. For NIMA, we report both technical quality assessment (NIMA-q) and aesthetic assessment (NIMA-a). Smaller PSNR gaps are better.

A.6.4 COMPARISON WITH BASELINE METHODS

To further compare with baseline methods, we report the PSNR gaps of high-level noise cases and SSIM gaps of low- and high-level noise cases in Fig. 12,Fig. 13 and Fig. 14, respectively, which show a similar trend to the results of PSNR gaps. The detection gaps of our method are very marginal (< 0.02) for most noise types and levels (except for Baboon and Kodak1 for certain noise types/levels), while the baseline methods can well exceed 0.1 for most cases.

A.6.5 COMPARISON WITH COMPETING METHODS

Comparison between ES-WMV with DF-STE for Gaussian and shot noise in terms of SSIM is reported in Fig. 15. We compare our ES-WMV and SV-ES in Fig. 16. The DIP results with ES-WMV vs. DOP on impulse noise are shown in Table 5. For SB, part of the qualitative detection results on the 9 images[2] is reported in Fig. 17.

---

[2]http://www.cs.tut.fi/~foi/GCF-BM3D/index.html#ref_results

Figure 13: **Low-level noise** detection performance in terms of SSIM gaps. For NIMA, we report both technical quality assessment (NIMA-q) and aesthetic assessment (NIMA-a). Smaller SSIM gaps are better.

Figure 14: **High-level noise** detection performance in terms of SSIM gaps. For NIMA, we report both technical quality assessment (NIMA-q) and aesthetic assessment (NIMA-a). Smaller SSIM gaps are better.

Figure 15: Comparison of DF-STE and ES-WMV for Gaussian and shot noise in terms of SSIM.

Figure 16: **Low- and high-level noise** detection performance of SV-ES and ours in terms of PSNR gaps.

Table 5: DIP with ES-WMV vs. DOP on impulse noise: mean and (std).

	Low Level		High Level	
	PSNR	SSIM	PSNR	SSIM
DIP-ES	31.64 (5.69)	0.85 (0.18)	24.74 (3.23)	0.67 (0.19)
DOP	32.12 (4.52)	0.92 (0.07)	27.34 (3.78)	0.86 (0.10)

A.6.6 ES-WMV AS A HELPER

Performance of ES-WMV on DD, GP-DIP, DIP-TV, and SIREN for Gaussian denoising in terms of SSIM gaps (see Fig. 18).

A.6.7 PERFORMANCE ON REAL-WORLD DENOISING

Table 6: DIP with ES-WMV on real image denoising in PolyU Dataset: mean and (std). (**D**: Detected)

	PSNR(**D**)	PSNR Gap	SSIM(**D**)	SSIM Gap
DIP (MSE)	36.83 (3.07)	1.26 (1.22)	0.98 (0.02)	0.01 (0.01)
DIP (ℓ_1)	36.20 (2.81)	1.64 (1.58)	0.97 (0.02)	0.01 (0.01)
DIP (Huber)	36.76 (2.96)	1.28 (1.09)	0.98 (0.02)	0.01 (0.01)

As stated from the beginning, ES-WMV is designed with real-world IPs, targeting unknown noise types and levels. Given the encouraging performance above, we test it on a common real-world denoising dataset—PolyU Dataset Xu et al. (2018), which contains 100 cropped regions of 512×512 from 40 scenes. The results are reported in Table 6. We do not repeat the experiments here; the means and standard deviations are obtained over the 100 images of the PolyU dataset. On average, our detection gaps are ≤ 1.64 in PSNR and ≤ 0.01 in SSIM for this dataset across various losses. The absolute PNSR and SSIM detected are surprisingly high.

A.6.8 VISUAL RESULTS FOR MRI RECONSTRUCTION

A.6.9 ES-WMV VS. ES-EMV

We now consider our memory-efficient version (ES-EMV) as described in Algorithm 2, and compare it with ES-WMV, as shown in Fig. 21. Besides the memory benefit, ES-EMV runs around 100 times faster than ES-WMV, as reported in Table 2 and does seem to provide a consistent improvement on

Figure 17: Comparison between ES-WMV and SB for image denoising (top: $\sigma = 15$; middle: $\sigma = 25$; bottom: $\sigma = 50$). The red and blue curves are the PNSR and the ratio metric curves. The orange and green bars indicate the ES points detected by our ES-WMV and SB, respectively.

Figure 18: Performance of ES-WMV on DD, GP-DIP, DIP-TV, and SIREN for Gaussian denoising in terms of SSIM gaps. L: low noise level; H: high noise level

Figure 19: Comparison of VAL and ES-WMV for Gaussian and impulse noise in terms of SSIM.

Figure 20: Detection on MRI reconstruction

the detected PSNRs, due to the strong smoothing effect (we set $\alpha = 0.1$). For this paper, we prefer to stay simple and leave systematic evaluations of these variants as future work.

Figure 21: Detected PSNR comparison between ES-WMV and ES-EMV

A.6.10 ABLATION STUDY

We vary the window size W (default 100) and patience number P (default: 1000) across a range and check how the detection gap changes for Gaussian denoising with medium-level noise (see:Fig. 22).

Figure 22: Effect of patience number and window size on detection in terms of SSIM gaps