Learning Enhanced Representations for Tabular Data via Neighborhood Propagation

Abstract

Prediction over tabular data is an essential and fundamental problem in many important downstream tasks. However, existing methods either take a data instance of the table independently as input or do not fully utilize the multi-rows features and labels to directly change and enhance the target data representations. In this paper, we propose to 1) construct a hypergraph from relevant data instance retrieval to model the cross-row and cross-column patterns of those instances, and 2) perform message **P**ropagation to **E**nhance the target data instance representation for **T**abular prediction tasks. Specifically, our specially-designed message propagation step benefits from 1) fusion of label and features during propagation, and 2) locality-aware high-order feature interactions. Experiments on two important tabular data prediction tasks validate the superiority of the proposed PET model against other baselines. Additionally, we demonstrate the effectiveness of the model components and the feature enhancement ability of PET via various ablation studies and visualizations.

1 Introduction

Prediction over tabular data is a fundamental and essential problem in many data science applications including recommender systems (Bobadilla et al., 2013; Ying et al., 2018), online advertising (Richardson et al., 2007; Zhou et al., 2018), fraud detection (Bolton and Hand, 2002), question answering (Chen et al., 2020), etc. Most existing methods seek to capture the patterns of feature interactions within an instance independently using tree models (Chen and Guestrin, 2016) or deep networks (Guo et al., 2017).

Recently, as shown by Papernot and McDaniel (2018), feeding in neighbors of the target as input can improve the robustness of data representations and help the model generalize better to out-of-distribution samples. Some retrieval based methods (Pi et al., 2020; Qin et al., 2020, 2021) then seek to utilize multiple neighboring data instances of the target for label prediction. These methods take the auxiliary instances as extra inputs but do not consider that such auxiliary information could enhance the target representation. Other existing graph-based methods on tabular data (You et al., 2020; Wu et al., 2021a; Guo et al., 2021b) aim to learn robust representations with locality structure, as Verma and Zhang (2019) proved the stabilization and generalization ability of graph neural networks. However, they either omit the high-order product feature interactions, or else serve as a plugin while resorting to other architectures like factorization machines (Rendle, 2010) to explore feature interactions. Moreover, they ignore the mutual enhancement of the representations between labels and features. In this paper, with the aim of learning enhanced data representations of tabular data, we propose to construct a hypergraph among relevant data instances to model the set relationships (Srinivasan et al., 2021). Additionally, we design an end-to-end graph neural network prediction

Figure 1: Difference between PET and other models. (a) The popular tree models and interaction-based models utilize a single data instance for prediction. (b) The retrieval-based methods take multiple data instances as input without sufficiently mining the interaction patterns among them. (c) The proposed PET models the multiple data instances set as a hypergraph and capture their correlations with the assistance of labels.

model that generates high-order feature interactions with the assistance of the locality structure and label adjustment.

Specifically, we design PET, a novel architecture that **P**ropagates and **E**nhances the **T**abular data representations based on the hypergraph for target label prediction. We first retrieve from the observed data instances pool to get the neighboring data instances for each target. The resulting instance set can be seen as a hypergraph, where sets of feature columns of data instances form hyperedges and each distinct feature value of these data instances form a node. This hypergraph models the cross-row and cross-column relations of the resulting instance set. Then we conduct message propagation on the graph. The propagation serves three purposes. First, auxiliary label information from the retrieved data instances propagates through the common feature value nodes to help the target prediction. Second, feature representations get enhanced through the locality structure. Our interactive message generation, attention-based aggregation, and update generate locality-aware high-order feature interactions. Third, the labels are incorporated into the propagating messages to directly adjust the feature spaces and generate label-enhanced feature representations.

The main contributions are summarized as follows:

- We propose a retrieval-based hypergraph to capture the feature and label correlations among tabular data instances.

- We design an end-to-end graph neural network prediction model that unifies the product feature interaction, locality mining, and label enhancement.

- We utilize the observed labels in the resulting set to guide the feature learning process and use the propagated labels to enhance predictions.

We evaluate the proposed PET model on two prediction tasks, i.e., binary classification and top-n ranking, over five tabular datasets, where substantial performance improvement against other strong baselines validates the superiority of PET.

2 Preliminaries and Related Work

Tabular data prediction. Tabular data prediction treats every row of the table as a data instance and every column/field as a feature attribute.[1] We consider tabular data prediction under a single table scenario in this paper, and prediction over multiple tables can be seen as the prediction over a joined table. We also focus on tabular *discrete* data in this paper, while the continuous feature values can be discretized in various ways (Guo et al., 2021a). Currently some of the most widely used models for tabular data prediction include Gradient Boosting Decision Trees (GBDTs) (Friedman, 2001) and Factorization Machines (FM) (Rendle, 2010). Variants of FM such as DeepFM (Guo et al., 2017) and Wide & Deep (Cheng et al., 2016) are especially popular in industrial applications. For a given row, such models simply take in the row and make predictions, i.e., these models assume that the rows are IID. Such an assumption, however, is reasonable only if the embedding representations of the

---

[1]We use *row* and *data instance*, as well as *column* and *field* interchangeably.

Figure 2: The workflow of PET. For each row to predict (top-left), PET retrieves a fixed number of relevant data instances (bottom-left) and constructs a hypergraph (bottom-right) from the resulting data instances set. After a star expansion (top-right), we get a data-feature bipartite graph with data instance nodes at the bottom and feature value nodes at the top.

tabular data can sufficiently host the high-order interaction patterns within the data instance, which is practically impossible.

Graph neural networks on tabular data. As Graph Neural Networks (GNNs) become popular, multiple attempts to apply GNNs on tabular data prediction have emerged. Since the model takes in a graph that connects the rows and columns together, the prediction on a single row no longer depends only on itself, but also other rows, and is therefore suitable for exploiting non-IID properties in tabular data. Examples of using GNNs on tabular data include Wu et al. (2021a) that constructs a mini-batch data-feature bipartite graph, You et al. (2020) that treats the (incomplete) table as an adjacency matrix of a bipartite graph, and Guo et al. (2021b) that treats rows as nodes and build edges according to predefined rules. These methods omit the product feature interactions or else resort to other architecture like factorization machines to explore them. Moreover, they ignore the mutual enhancement between labels and features.

Hypergraphs and hyperedge classification/regression. If we treat each individual value in a table as a single node, then a row describes an n-ary relationship among the nodes. Normal graphs have trouble describing this relation since edges can only connect two nodes at a time. A *hypergraph* generalizes graphs such that an edge can connect more than two nodes. It is defined as a pair $G = (V, E)$ with its node set V and its *hyperedge* set $E \subseteq \mathcal{P}(V)$, where $\mathcal{P}(V)$ is the power set of V, meaning that each "edge" becomes simply a subset of V, regardless of the number of nodes in the "edge". We can construct a hypergraph from a set of rows, where each hyperedge correspond to a row and each node correspond to the distinct feature values among all the rows. Tabular data prediction problem can be cast into a hyperedge classification/regression problem, where every row now corresponds to a hyperedge.

Hypergraph neural networks. Hypergraph neural networks are an adaptation of GNNs with a message passing paradigm whereby node representations are used to update hyperedge representations, which in turn update the node representations again (Srinivasan et al., 2021; Bai et al., 2021; Feng et al., 2019). Using a hypergraph neural network on tabular data allows us to obtain a representation for each row from its corresponding hyperedge, as well as a representation for each individual value of each column from its corresponding node.

3 Methodology

When making prediction for a sample, feeding in similar or relevant samples together as input is known to contribute to robustness and generalization abilities for out-of-distribution samples (Papernot and McDaniel, 2018). In light of this, for a given data instance, our model retrieves a set of relevant data instances according to a relevance metric, aiming to take auxiliary information from relevant data instances.

The resulting instances set can be seen as a hypergraph, where each distinct feature value forms a node and a collection of them, i.e., a data instance, forms a hyperedge. After the star expansion (Agarwal et al., 2006; Srinivasan et al., 2021), we get a bipartite graph with feature value nodes on one side and data instance nodes on the other, on which we propagate and enhance representations. An advantage of message passing is that it allows us to capture higher-order interactions among nodes and hyperedges (Srinivasan et al., 2021), i.e. the interactions among the individual column values as well as the rows. We argue that these high-order interactions play an essential role in the real-world scenarios. Assume that there are F fields in the given tabular, then there exists $\mathtt{C}_F^2$ second order interactions and $\mathtt{C}_{\cdot}^{\cdot}$ denotes the combination operation (i.e., $\mathtt{C}_F^N$ N-th order interactions). Notice that (2-way) factorization machine (Rendle, 2010) solely modelling the second-order feature interactions is widely employed in real-world scenarios and inspires a series of tabular predictors (Wu et al., 2021b; Qin et al., 2021). Our method leverages the hypergraph structure of the given tabular data to capture high-order interactions beyond the second-order ones, and uses GNNs to represent these high-order features. The other advantage of message passing is that we can utilize the labels of retrieved data instances to interact with features and take advantage of label propagation at the same time. The enhanced data instance representations are then used for prediction.

Figure 2 illustrates the framework of PET. Detailed descriptions of each individual component are provided in the following subsections.

3.1 Graph Construction

For each target data instance, we retrieve K relevant data instances from the observed data instances set using ElasticSearch[2] and construct a hypergraph from the resulting instance set.

Let $X^t = \{x_f^t | f = 1, \ldots, F\}$ be the feature of a target data instance t, where F is the number of feature fields and x_f^t is the feature value of the f-th field of data instance t. We first conduct a boolean query to obtain instances that have at least one common feature value with the target data instance. Then we retrieve the top-K relevant instances $r_1, \cdots, r_K$ from the filtered instances set according to the relevance value (Qin et al., 2021) defined as:

$$R(X^t, X^j) = \sum_{f=1}^{F} \mathrm{IDF}(x_f^t) \cdot 1_{(x_f^t = x_f^j)}, \tag{1}$$

$$\mathrm{IDF}(x_f^t) = \log \frac{N - N(x_f^t) + 0.5}{N(x_f^t) + 0.5}, \tag{2}$$

where $1_{(\cdot)}$ is the indicator function, N is the number of data instances in the table, and $N(x_f^t)$ is the number of data instances that have feature value x_f^t in the f-th field. This metric is equivalent to the BM25 (Robertson et al., 1995) metric if we treat each data instance as a document and their feature values as the terms.

After the retrieval, the resulting instances set $\{X^t, X^{r_1}, \cdots, X^{r_K}\}$ can be seen as a hypergraph, where each distinct feature value in each individual field forms a node and each data instance constructs a hyperedge. We then perform a star expansion (Agarwal et al., 2006) on the hypergraph, i.e. construct a bipartite graph $G = (V_D, V_F, E)$ where $V_D = \{t, r_1, \ldots, r_K\}$, $V_F = \{x_f^j | f = 1, \cdots, F; j = t, r_1, \ldots, r_K\}$, and an edge exists between two nodes $i \in V_F$ and $j \in V_D$ if $i \in X^j$.

3.2 Message Passing and Interaction

After the graph is constructed, we propagate and enhance the representations on it. The propagation serves three purposes. First, the label information propagates through common feature value nodes to help the label prediction of the target data instance node. Second, the features get enhanced through taking in high-order information. Locality-aware high-order product feature interactions are generated through the interactive message generation and attention based aggregation. Third, the label embeddings directly interact with the features to adjust the feature spaces and generate label-enhanced features and high-order interactions. Then we detail the components as follows.

---

[2]https://www.elastic.co/elasticsearch/

Initialization. Before message passing, we initialize the node representations and edge representations with trainable embedding vectors. Let Φ_x and Φ_y be different trainable embedding layers for feature value nodes and data instances nodes, respectively. And let Φ_{in} and Φ_{out} be the embedding layers for the edges. We first initialize the feature value node representations as

$$h_i^{(0)} = \Phi_x(i), i \in V_F. \tag{3}$$

We also initialize the data instance node representations of the retrieved rows with a trainable embedding vector associated with their labels. As for the target data node, we initialize its representations with a constant zero vector.

$$h_j^{(0)} = \begin{cases} \mathbf{0}, & j = t, \\ \Phi_y(y^j), & j \in V_D \backslash \{t\}, \end{cases} \tag{4}$$

where y^j denotes the label of the data instance j.

In addition, we initialize each edge representation with the embedding of its incident data instance node label to guide the feature learning process and generate high-order interactions.

$$e_{ij}^{(0)} = \begin{cases} \Phi_{in}(y^i), & i \in V_D, j \in V_F, \\ \Phi_{out}(y^j), & i \in V_F, j \in V_D. \end{cases} \tag{5}$$

Message Generation. Then we use the interactions between edge and node representations along with the original node representations to generate the messages:

$$m_{ij}^{(l)} = (e_{ij}^{(l-1)} \odot h_i^{(l-1)}) \| h_i^{(l-1)}, \tag{6}$$

where $\odot$ denotes the Hadamard product, superscript l means the l-th layer, and $\|$ denotes the concatenation operation.

As edge representations carry the label information initially, the Hadamard product term generates label-enhanced features. In addition, the edges will contain node features after updating edge representations with incident node representations, then the Hadamard product term produces high-order product feature interactions. The high-order product feature interactions prove to be important in many interaction-based tabular data prediction methods (Qu et al., 2018), which are often missed in other graph-based tabular networks or captured by an extra factorization machine (Wu et al., 2021a).

Message Aggregation. The incoming neighboring messages are then aggregated based on an attention mechanism:

$$\begin{aligned} Q_j^{(l)} &= W_Q^{(l)} h_j^{(l-1)}, \\ K_{ij}^{(l)} &= W_K^{(l)} m_{ij}^{(l)}, \\ V_{ij}^{(l)} &= W_V^{(l)} m_{ij}^{(l)}, \\ a_{ij}^{(l)} &= \text{softmax}_{i \in N(j)}(Q_j^{(l)} K_{ij}^{(l)}), \\ n_j^{(l)} &= \sum_{i \in N(j)} a_{ij}^{(l)} V_{ij}^{(l)}. \end{aligned} \tag{7}$$

Node Embedding Update. After receiving the aggregated neighboring messgages, the node embeddings are updated based on the aggregated messages and their own node embeddings.

$$h_j^{(l)} = \sigma(W_N^{(l)}((h_j^{(l-1)} \| n_j^{(l)}))), \tag{8}$$

where $\sigma(\cdot)$ denotes the ReLU activation function.

Edge Embedding Update. Then we update edge embeddings using their incident node embeddings as Equation (9). As edge embeddings are updated using the node embeddings, the features and labels on nodes are propagated to the edges as well. After rounds of propagation, the messages generated contain high-order feature interactions and high-order feature-label interactions.

$$e_{ij}^{(l)} = \sigma(W_E^{(l)}(h_i^{(l)} \| h_j^{(l)} \| e_{ij}^{(l-1)})). \tag{9}$$

Figure 3: The representation of the target node after propagation. We use the red color to represent the retrieved instance node and use the grey color to represent the target data instance node to predict. Other feature value nodes are in different colors. The information flow is marked with the corresponding color. The dots-on-edges represent the feature and label information stored in edges. (best viewed in colors)

3.3 Label Prediction

Then we use the target data node embedding of the last layer for prediction:

$$\hat{y}_t = \text{MLP}(h_t^{(L)}), \tag{10}$$

For binary classification, the training objective is set as cross entropy:

$$\mathcal{L}(Y, \hat{Y}) = -\sum_t \left(y_t \log \hat{y}_t + (1 - y_t)\log(1 - \hat{y}_t)\right), \tag{11}$$

where y_t is the label of the target data instance t.

3.4 Analysis

We illustrate the representation of the target node after propagation in Figure 3. Following the proposed propagation method, the target node will receive the first order features, second-order features, label-enhanced features, and the propagated labels after two rounds of propagation. Propagating more than two layers will further produce higher-order feature interactions, cross-rows feature interactions, and feature-label interactions. Furthermore, the feature messages are adjusted by corresponding labels and attentively aggregated based on the locality structure.

4 Experiments

In this section, we show the experimental results and the corresponding settings. Generally, we experiment on two kinds of tabular data prediction tasks: click-through rate (CTR) prediction and top-n recommendation. The results showcase the value of our model on tabular data prediction tasks. Additionally, we conduct several ablation studies to validate the components of our model.

4.1 Setup

We evaluate the performance of PET on five datasets. For the CTR prediction task, we conduct experiments on three large-scale datasets, i.e., Tmall[3], Taobao[4], and Alipay[5]. For the top-n recommendation task, we experiment on two widely-used public recommendation datasets, i.e., Movielens-1M[6] and LastFM[7]. The statistics of the used datasets are summarized in Table 1.

Table 1: Dataset statistics.

Datasets	Samples	Fields
Tmall	54,925,331	9
Taobao	100,150,807	4
Alipay	35,179,371	6
Movielens-1M	1,000,209	7
LastFM	18,993,371	5

---

[3]https://tianchi.aliyun.com/dataset/dataDetail?dataId=42

[4]https://tianchi.aliyun.com/dataset/dataDetail?dataId=649

[5]https://tianchi.aliyun.com/dataset/dataDetail?dataId=53

[6]https://grouplens.org/datasets/movielens/1m/

[7]http://ocelma.net/MusicRecommendationDataset/lastfm-1K.html

Table 2: Result comparisons with baselines on CTR prediction task. ($K = 10$)

Models	Tmall			Taobao			Alipay		
	AUC	LogLoss	Rel.Impr.	AUC	LogLoss	Rel.Impr.	AUC	LogLoss	Rel.Impr.
GBDT	0.8319	0.5103	12.08%	0.6134	0.6797	44.08%	0.6747	0.9062	32.36%
DeepFM	0.8581	0.4695	8.66%	0.6710	0.6497	31.71%	0.6971	0.6271	28.1%
FATE	0.8553	0.4737	9.01%	0.6762	0.6497	30.70%	0.7356	0.6199	21.40%
DIN	0.8796	0.4292	6.00%	0.7433	0.6086	18.90%	0.7647	0.6044	16.78%
DIEN	0.8838	0.4445	5.50%	0.7506	0.6084	17.74%	0.7502	0.6151	19.03%
SIM	0.8857	0.4520	5.27%	0.7825	0.5795	12.95%	0.7600	0.6089	17.50%
UBR	0.8975	0.4368	3.89%	0.8169	0.5432	8.19%	0.7952	0.5747	12.30%
RIM	0.9138	0.3804	2.04%	0.8563	0.4644	3.21%	0.8006	0.5615	11.54%
PET	**0.9324**	**0.3321**	–	**0.8838**	**0.4162**	–	**0.8930**	**0.4132**	–

Table 3: Result comparisons with baselines on top-n recommendation task. ($K = 10$)

Datasets	Metric	FPMC	TransRec	NARM	GRU4Rec	SASRec	RIM	PET
ML-1M	HR@1	0.0261	0.0275	0.0337	0.0369	0.0392	0.0645	**0.0904**
	HR@5	0.1334	0.1375	0.1418	0.1395	0.1588	0.2515	**0.2889**
	HR@10	0.2577	0.2659	0.2631	0.2624	0.2709	0.4014	**0.4404**
	NDCG@5	0.0788	0.0808	0.0866	0.0872	0.0981	0.1577	**0.1903**
	NDCG@10	0.1184	0.1217	0.1254	0.1265	0.1341	0.2059	**0.2390**
	MRR	0.1041	0.1078	0.1113	0.1135	0.1193	0.1704	**0.2006**
LastFM	HR@1	0.0148	0.0563	0.0423	0.0658	0.0584	0.0915	**0.1149**
	HR@5	0.0733	0.1725	0.1394	0.1785	0.1729	0.3468	**0.3621**
	HR@10	0.1531	0.2628	0.2227	0.2581	0.2499	0.5780	**0.6033**
	NDCG@5	0.0432	0.1148	0.0916	0.1229	0.1163	0.2165	**0.2381**
	NDCG@10	0.0685	0.1441	0.1185	0.1486	0.1409	0.2911	**0.3156**
	MRR	0.0694	0.1303	0.1083	0.1362	0.1289	0.2210	**0.2492**

The evaluation metrics include area under ROC curve (AUC) and negative log-likelihood (LogLoss) for CTR prediction tasks and hit rate (HR), normalized discounted cumulative gain (NDCG) and mean reciprocal rank (MRR) for top-n recommendation tasks.

Following Qin et al. (2021), we spilt the datasets according to the global timestamps. The earliest data instances are grouped into the retrieval pool. The latest data instances form the test pool. Then the remaining data instances are grouped into the train pool. To avoid unfair comparisons, the non-retrieval model takes the retrieval pool as additional train pool.

On CTR prediction tasks, we compare our model against eight widely-used and strong baselines. GBDT (Chen and Guestrin, 2016) is the widely-used tree model. DeepFM (Guo et al., 2017) is the inner-product interaction-based model. DIN (Zhou et al., 2018) and DIEN (Zhou et al., 2019) are the attention-based sequential models. SIM (Pi et al., 2020), UBR (Qin et al., 2020), and RIM (Qin et al., 2021) are the retrieval-based models. On top-n recommendation tasks, we compare PET with six strong recommendation models, including factorization-based FPMC (Rendle et al., 2010) and TransRec (He et al., 2017), and recently proposed DNN models NARM (Li et al., 2017), GRU4Rec (Hidasi et al., 2016), SASRec (Kang and McAuley, 2018), and RIM (Qin et al., 2021).

As for the hyperparameters, we test the number of GNN layers in $\{2, 3\}$. The embedding sizes of all the models are consistent to ensure the fair comparison. More detailed hyperparameters are provided in the Appendix.

4.2 Overall performance comparison

We first validate the effectiveness of the proposed PET model. The main results are summarized in Tables 2 and 3, where we can see the proposed PET performs consistently better on all datasets.

The results demonstrate the superiority of PET against the baselines on both tasks. On the CTR prediction task, PET achieves relatively $2.04\%, 3.21\%, 11.54\%$ higher AUC over the best performed baseline on Tmall, Taobao, Alipay, respectively. The results show that PET can learn effective tabular data representation for better prediction performance. Furthermore, compared with RIM that takes exactly the same inputs with PET, the improvements of PET are statistically significant under 95% confidence level. Given that RIM also utilizes the labels of relevant rows, this empirically justifies

228 the capability of our propagation method. On the top-n recommendation task, PET shows significant
229 improvements on the recommendation task against other baselines, too. The results show that PET
230 performs substantially better than the strong baselines in all comparisons.

4.3 Ablation study

4.3.1 Impact of the label usages

233 We further study the usage of labels of PET. The results are summarized in Table 4. For fast
234 exploration, we randomly sample 10% data from training pool and test pool on the three largest CTR
235 datasets, respectively. The best performed baseline RIM is tested on the sampled data for comparison.
236 Both RIM and PET utilize the same set of retrieved data instances and their label information. We
237 then examine the impact of different label usages on the sampled data. In the PET model, we initialize
238 the embeddings of data instances nodes and edges with the corresponding label embeddings. We then
239 inspect the impact of such initialization and the operations on edges.

Table 4: Impact of label embeddings. (On randomly sampled data, $K = 10$)

Models	Tmall		Taobao		Alipay	
	AUC	LogLoss	AUC	LogLoss	AUC	LogLoss
RIM	0.9120	0.3769	0.8587	0.4586	0.7845	0.5742
PET	0.9279	0.3387	0.8762	0.4279	0.8720	0.4201
PET (w/o edge labels)	0.9291	0.3367	0.8665	0.4465	0.8558	0.4776
PET (w/o node labels)	0.9233	0.3494	0.8431	0.4847	0.8518	0.4799

240 We first remove edge embedding initialization with labels and eliminate all the operations involved
241 with edges, thus the message becomes

$$m_{ij}^{(l)} = h_i^{(l-1)}. \tag{12}$$

242 In addition, the edge embedding update step in Equation (9) is also omitted. As such, the labels
243 only serve from propagation among nodes. The high-order product interaction between features
244 and label-feature interaction are omitted. As shown in Table 4, PET without edge labels performs
245 weaker than the original PET model, which demonstrates the power of high-order product interactions
246 and label-enhanced features. Moreover, PET without edge labels still performs better than RIM,
247 which validates the superiority of label propagation through common feature nodes against simple
248 attention-based aggregation.

249 By removing the node labels, the embeddings of all the data instance nodes are initialized as constant
250 vectors. In this way, no pure first-order label embeddings are used for prediction. Since any
251 information related with labels will be propagated to nodes after a product interaction with features.
252 One can see that PET without node labels performs better than RIM, which further justifies the
253 effectiveness of high-order product interactions and label-enhanced features. Additionally, PET
254 without node labels performs weaker than the original PET, which implies the power of initializing
255 node embeddings with pure label embeddings for propagation.

4.3.2 Visualization of the feature distribution

257 In order to further explore the representation enhancement of PET, we visualize the features of
258 PET and RIM. Figure 4 illustrates the distributions of data instance embeddings and the feature
259 embeddings of PET and RIM with t-SNE (Van der Maaten and Hinton, 2008). For both models, we
260 randomly choose 10,000 samples from the train data and 10,000 samples from the test data. For PET,
261 the data instance embeddings are taken from the data instance nodes (inputs of the MLP predictor)
262 and the feature embeddings are the concatenated feature node embeddings for each data instance.
263 For RIM, the data instance embeddings are the inputs of the final MLP predictor and the feature
264 embeddings are the concatenated feature embeddings of each data instance.

265 From Figure 4, we can see that the distributions of train positive data points and train negative data
266 points are more dissimilar than those of RIM. The same phenomenon happens in the distributions of
267 test positive data points and test negative data points. This illustrates that PET gives more informative
268 representations.

Figure 4: The distribution of data node (output) and feature node embeddings visualized with t-SNE.

Table 5: Impacts of the retrieval schemes.

Models	Tmall		Taobao		Alipay	
	AUC	LogLoss	AUC	LogLoss	AUC	LogLoss
Random retrieval	0.8433	0.4922	0.6544	0.6572	0.7271	0.6120
Relevance retrieval	0.9324	0.3321	0.8838	0.4162	0.8930	0.4132

4.3.3 Impacts of different retrieval schemes

In this section, we compare the performance of PET w.r.t. different retrieval sizes and retrieval schemes. First, we evaluate the effectiveness of current retrieval by comparing the current retrieval scheme with the random retrieval scheme. The results are summarized in Table 5. One can see that the relevance-based retrieval performs much better the random retrieval. Since the relevance-based retrieval helps the resulting graph to achieve the homophily assumption, which is important in GNNs.

We also study the impact of using different retrieval sizes K. The results are put in the Appendix due to the page limit. Generally, too few retrieval samples may fail to carry enough information to enhance the representation, while too many retrieved samples will introduce more noise.

5   Conclusion

In this paper, we focus on improving the prediction of tabular data, which is essential in many important downstream tasks. Existing methods either take each data instance independently or directly take multiple data instances as input without enhancing the target data instance representation. We propose to construct a retrieval-based hypergraph to model the cross-row and cross-column relations of tabular data, utilizing the propagation on the resulting graph to directly change and enhance the target data instance representations. Concretely, we utilize a relevance retrieval to construct the hyperedges set of the hypergraph, aiming to resort to relevant patterns and reach the homophily assumption of GNNs. Then we design PET, a novel architecture that propagates and enhances the tabular data representations based on the hypergraph for target label prediction. The propagation serves from three aspects: 1) label propagates through common feature values; 2) features get enhanced through locality and high-order product feature interactions are generated through the interactive message passing framework; and 3) labels are used to generate the label-enhanced features. Experiments on two important tabular data prediction tasks validate the superiority of the proposed PET model over strong baselines.

References

Sameer Agarwal, Kristin Branson, and Serge Belongie. 2006. Higher order learning with graphs. In *Proceedings of the 23rd international conference on Machine learning*. 17–24.

Song Bai, Feihu Zhang, and Philip HS Torr. 2021. Hypergraph convolution and hypergraph attention. *Pattern Recognition* 110 (2021), 107637.

J. Bobadilla, F. Ortega, A. Hernando, and A. Gutiérrez. 2013. Recommender systems survey. *Knowledge-Based Systems* 46 (2013), 109–132.

Richard J. Bolton and David J. Hand. 2002. Statistical Fraud Detection: A Review. *Statist. Sci.* 17, 3 (2002), 235–249.

Tianqi Chen and Carlos Guestrin. 2016. Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd acm sigkdd international conference on knowledge discovery and data mining*. 785–794.

Wenhu Chen, Hanwen Zha, Zhiyu Chen, Wenhan Xiong, Hong Wang, and William Wang. 2020. HybridQA: A Dataset of Multi-Hop Question Answering over Tabular and Textual Data.

Heng-Tze Cheng, Levent Koc, Jeremiah Harmsen, Tal Shaked, Tushar Chandra, Hrishi Aradhye, Glen Anderson, Greg Corrado, Wei Chai, Mustafa Ispir, et al. 2016. Wide & deep learning for recommender systems. In *DLRS@RecSys*.

Yifan Feng, Haoxuan You, Zizhao Zhang, Rongrong Ji, and Yue Gao. 2019. Hypergraph neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 33. 3558–3565.

Jerome H Friedman. 2001. Greedy function approximation: a gradient boosting machine. *Annals of statistics* (2001), 1189–1232.

Huifeng Guo, Bo Chen, Ruiming Tang, Weinan Zhang, Zhenguo Li, and Xiuqiang He. 2021a. An embedding learning framework for numerical features in ctr prediction. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*. 2910–2918.

Huifeng Guo, Ruiming Tang, Yunming Ye, Zhenguo Li, and Xiuqiang He. 2017. DeepFM: a factorization-machine based neural network for CTR prediction. In *IJCAI*.

Xiawei Guo, Yuhan Quan, Huan Zhao, Quanming Yao, Yong Li, and Weiwei Tu. 2021b. TabGNN: Multiplex Graph Neural Network for Tabular Data Prediction. *arXiv preprint arXiv:2108.09127* (2021).

Ruining He, Wang-Cheng Kang, and Julian J. McAuley. 2017. Translation-based Recommendation. In *Proceedings of the Eleventh ACM Conference on Recommender Systems, RecSys 2017, Como, Italy, August 27-31, 2017*. 161–169.

Balázs Hidasi, Alexandros Karatzoglou, Linas Baltrunas, and Domonkos Tikk. 2016. Session-based Recommendations with Recurrent Neural Networks. In *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*.

Wang-Cheng Kang and Julian J. McAuley. 2018. Self-Attentive Sequential Recommendation. In *IEEE International Conference on Data Mining, ICDM 2018, Singapore, November 17-20, 2018*. 197–206.

Jing Li, Pengjie Ren, Zhumin Chen, Zhaochun Ren, Tao Lian, and Jun Ma. 2017. Neural Attentive Session-based Recommendation. In *Proceedings of the 2017 ACM on Conference on Information and Knowledge Management, CIKM 2017, Singapore, November 06 - 10, 2017*. 1419–1428.

Nicolas Papernot and Patrick McDaniel. 2018. Deep k-nearest neighbors: Towards confident, interpretable and robust deep learning. *arXiv preprint arXiv:1803.04765* (2018).

Qi Pi, Guorui Zhou, Yujing Zhang, Zhe Wang, Lejian Ren, Ying Fan, Xiaoqiang Zhu, and Kun Gai. 2020. Search-based User Interest Modeling with Lifelong Sequential Behavior Data for Click-Through Rate Prediction. In *CIKM '20: The 29th ACM International Conference on Information and Knowledge Management, Virtual Event, Ireland, October 19-23, 2020*. ACM, 2685–2692.

Jiarui Qin, Weinan Zhang, Rong Su, Zhirong Liu, Weiwen Liu, Ruiming Tang, Xiuqiang He, and Yong Yu. 2021. Retrieval & Interaction Machine for Tabular Data Prediction. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining*. 1379–1389.

Jiarui Qin, Weinan Zhang, Xin Wu, Jiarui Jin, Yuchen Fang, and Yong Yu. 2020. User Behavior Retrieval for Click-Through Rate Prediction. In *Proceedings of the 43rd International ACM SIGIR conference on research and development in Information Retrieval, SIGIR 2020, Virtual Event, China, July 25-30, 2020*. ACM, 2347–2356.

Yanru Qu, Bohui Fang, Weinan Zhang, Ruiming Tang, Minzhe Niu, Huifeng Guo, Yong Yu, and Xiuqiang He. 2018. Product-based Neural Networks for User Response Prediction over Multi-field Categorical Data. *ACM Transactions on Information Systems* (2018).

Steffen Rendle. 2010. Factorization machines. In *ICDM*.

Steffen Rendle, Christoph Freudenthaler, and Lars Schmidt-Thieme. 2010. Factorizing personalized Markov chains for next-basket recommendation. In *Proceedings of the 19th International Conference on World Wide Web, WWW 2010, Raleigh, North Carolina, USA, April 26-30, 2010*. 811–820.

Matthew Richardson, Ewa Dominowska, and Robert Ragno. 2007. Predicting Clicks: Estimating the Click-Through Rate for New Ads. In *Proceedings of the 16th International World Wide Web Conference(WWW-2007)*.

Stephen Robertson, S. Walker, S. Jones, M. M. Hancock-Beaulieu, and M. Gatford. 1995. Okapi at TREC-3. In *Overview of the Third Text REtrieval Conference (TREC-3)*. 109–126.

Balasubramaniam Srinivasan, Da Zheng, and George Karypis. 2021. Learning over Families of Sets-Hypergraph Representation Learning for Higher Order Tasks. In *Proceedings of the 2021 SIAM International Conference on Data Mining (SDM)*. SIAM, 756–764.

Laurens Van der Maaten and Geoffrey Hinton. 2008. Visualizing data using t-SNE. *Journal of machine learning research* 9, 11 (2008).

Saurabh Verma and Zhi-Li Zhang. 2019. Stability and Generalization of Graph Convolutional Neural Networks. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, KDD 2019, Anchorage, AK, USA, August 4-8, 2019*. ACM, 1539–1548.

Qitian Wu, Chenxiao Yang, and Junchi Yan. 2021a. Towards Open-World Feature Extrapolation: An Inductive Graph Learning Approach. In *Advances in Neural Information Processing Systems: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021*.

Qitian Wu, Chenxiao Yang, and Junchi Yan. 2021b. Towards Open-World Feature Extrapolation: An Inductive Graph Learning Approach. *Advances in Neural Information Processing Systems* 34 (2021).

Rex Ying, Ruining He, Kaifeng Chen, Pong Eksombatchai, William L. Hamilton, and Jure Leskovec. 2018. Graph Convolutional Neural Networks for Web-Scale Recommender Systems. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery &amp Data Mining*.

Jiaxuan You, Xiaobai Ma, Daisy Yi Ding, Mykel J. Kochenderfer, and Jure Leskovec. 2020. Handling Missing Data with Graph Representation Learning. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020*.

Guorui Zhou, Na Mou, Ying Fan, Qi Pi, Weijie Bian, Chang Zhou, Xiaoqiang Zhu, and Kun Gai. 2019. Deep Interest Evolution Network for Click-Through Rate Prediction. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*. 5941–5948.

Guorui Zhou, Xiaoqiang Zhu, Chengru Song, Ying Fan, Han Zhu, Xiao Ma, Yanghui Yan, Junqi Jin, Han Li, and Kun Gai. 2018. Deep Interest Network for Click-Through Rate Prediction. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, KDD 2018, London, UK, August 19-23, 2018*. 1059–1068.