EviNoteRAG: Enhancing RAG Models via Quality-Augmented Evidence Notes

Abstract

Retrieval-Augmented Generation (RAG) has advanced open-domain question answering by incorporating external information into model reasoning. However, raw retrieved content often suffers from *low signal-to-noise ratio*, where answer-supportive information is diluted by irrelevant material, and *error accumulation*, where incomplete or misleading content degrades multi-hop reasoning. To address these challenges, we propose **EviNoteRAG**, a framework that enhances RAG through quality-augmented evidence notes. The model is trained to generate *Supportive-Evidence Notes (SENs)*, concise abstractions that preserve only answer-critical information and explicitly highlight key and uncertain content to improve reasoning accuracy. To further ensure note quality, we introduce an entailment-based *Evidence Quality Reward (EQR)*, which incentivizes SENs to be logically sufficient for deriving the correct answer. Experiments on both in-domain and out-of-domain benchmarks demonstrate that EviNoteRAG achieves state-of-the-art performance, with relative F1 gains of 20% on HotpotQA (+0.093), 40% on Bamboogle (+0.151), and 91% on 2Wiki (+0.256), while also improving training stability and efficiency. **Code and data will be publicly released and are provided in the supplementary material.**

1 Introduction

Large Language Models (LLMs) have evolved from next-token predictors into systems capable of advanced reasoning (Liu, 2026; Verma et al., 2024b; Zheng et al., 2025; Yin et al., 2025; Jiang et al., 2025). Since the factual knowledge of LLMs is fixed during pre-training, they are prone to generating incorrect or outdated information when deployed in real-world tasks where knowledge evolves rapidly (Zhang et al., 2025; Yu et al., 2026). To address this limitation, Retrieval-Augmented Generation (RAG) (Gao et al., 2025; Chen et al., 2026) has emerged by incorporating a search tool that supplies up-to-date external evidence at inference time, enabling models to ground their responses in timely information and improve factual consistency.

Despite recent advances, how to effectively leverage external documents to support reasoning remains a fundamental challenge (Gao et al., 2025). Prompt-based methods address this through multi-step reasoning (Jiang et al., 2024; Tran et al., 2024; Xiong et al., 2025) or adaptive workflows (Wu et al., 2025a; Zhao et al., 2025b; Wei et al., 2026), while tuning-based strategies (Liu et al., 2024; Zhang et al., 2024) improve fine-grained information extraction but often sacrifice generalization. More recently, advances in Reinforcement Learning (RL) (Kaelbling et al., 1996; Guo et al., 2025) have inspired RL-based Retrieval-Augmented Generation (RAG) approaches (Wei et al., 2025a; Song et al., 2025b; Jin et al., 2025; Li et al., 2025a; Deng et al., 2025; Dai et al., 2026), which surpass earlier paradigms by exploring optimal strategies and enhancing generalization. Yet, RL-based RAG methods still rely on outcome-based rewards that evaluate only final correctness, offering little guidance for intermediate reasoning. Consequently, models remain constrained to the *retrieve-then-answer* paradigm, facing two persistent obstacles: (1) **Low Signal-to-Noise Ratio (SNR)**, where retrieved evidence often includes substantial irrelevant content, making supportive information sparse (Shi et al., 2023; Jin et al., 2024); and (2) **Error Accumulation**, where reasoning errors amplify when inference depends on incomplete or noisy evidence, especially in multi-hop question answering (QA) (Shi et al., 2023). Addressing these issues calls for RL strategies that not only boost performance but also equip models with more effective workflows for handling long and noisy contexts.

Figure 1: EviNoteRAG vs. Baselines (Song et al., 2025b; Jin et al., 2025): EviNoteRAG distills key information through evidence notes and, guided by an Entailment Judge, ensures that retained content directly supports the answer, thereby mitigating noise and enhancing performance.

To address the core limitation of existing RAG systems, we propose **EviNoteRAG**, an RL-based RAG framework that trains models to generate *Supportive-Evidence Notes (SENs)*, concise abstractions that preserve only answer-critical information while explicitly highlighting key and uncertain content to improve reasoning accuracy. To further ensure note quality, we introduce the *Evidence Quality Reward (EQR)*, an entailment-based reward that incentivizes SENs to be logically sufficient for deriving the correct answer, guiding the model toward more accurate and faithful use of retrieved information. We validate our approach through extensive experiments on both in-domain and out-of-domain Question Answering (QA) benchmarks, and summarize our main contributions as follows:

- We propose **EviNoteRAG**, an RL-based RAG framework that enhances RAG through quality-augmented evidence notes, improving reasoning reliability.

- We introduce *Supportive-Evidence Notes (SENs)*, concise abstractions trained to preserve answer-critical information while highlighting key and uncertain content to mitigate noise and error accumulation.

- We design an entailment-based *Evidence Quality Reward (EQR)* that directly supervises note quality, yielding denser reward signals and more stable, efficient training.

- EviNoteRAG achieves state-of-the-art performance across multiple QA benchmarks, with relative F1 gains of 20% on HotpotQA (+0.093), 40% on Bamboogle (+0.151), and 91% on 2Wiki (+0.256).

2 Related Work

2.1 Instruction-Guided RAG Methods

Instruction-guided methods (Amplayo et al., 2022; Yao et al., 2023; Jeong et al., 2024; Jiang et al., 2024; Wu et al., 2025a; Jiao et al., 2026) enhance RAG by designing prompts that automate retrieval and guide multi-step reasoning (Jiang et al., 2024; Xiong et al., 2025). These approaches typically decompose questions into sub-problems, retrieve external knowledge, and synthesize structured answers (Zhou et al., 2024; Zhao et al., 2025b; Tran et al., 2024), with more recent efforts (Li et al., 2025a; Lee et al., 2025; Yue et al., 2024; Verma et al., 2024a; Alzubi et al., 2025; Feng et al., 2025) integrating retrieval directly into the reasoning loop or interleaving retrieval and reasoning adaptively. Despite these advances, prompt-based approaches inherently depend on the foundation model's generalization ability in RAG, which remains limited. Our framework instead employs a post-training, reward-driven objective that explicitly shapes information selection and reasoning, leading to more faithful and task-adapted performance.

2.2 Reward-Guided Agentic RAG

Reward-guided approaches (Guan et al., 2025; Huang et al., 2025; Zhao et al., 2025a; Wang et al., 2024b; Wei et al., 2025a; Deng et al., 2025; Samarinas et al., 2026) employ Reinforcement Learning (RL) (Kaelbling et al., 1996) to optimize reasoning policies through scalar feedback derived from task performance. Building on recent advances in RL (Guo et al., 2025), RL-based RAG approaches (Nakano et al., 2021; Qi et al., 2025; Chen et al., 2025; Jin et al., 2025; Wei et al.,

2025b) have surpassed previous paradigms by enabling optimal strategy exploration and improved generalization, with subsequent works broadening this framework to diverse scenarios and tool use (Zheng et al., 2025; Dai et al., 2025; Wang et al., 2025; Sun et al., 2025a; Gutiérrez et al., 2025; Shao et al., 2025). However, most existing reward-guided methods (Wu et al., 2025b; Song et al., 2025b; Sun et al., 2025b) operate directly on raw, often noisy passages, which leads to a low signal-to-noise ratio (Shi et al., 2023; Jin et al., 2024) and error accumulation across multi-hop reasoning. EviNoteRAG tackles this limitation by using supportive-evidence notes to structure retrieved information and applying supervision that enforces logical consistency between notes and final answers, promoting more reliable reasoning and improving answer accuracy.

3 Methodology

This section presents **EviNoteRAG**, which trains models to generate quality-augmented *Supportive-Evidence Notes (SENs)* that distill answer-relevant content from retrieved passages, and introduces an *Evidence Quality Reward (EQR)* to ensure each note faithfully supports the final answer, guiding more accurate reasoning. *Full implementations are available in the supplementary code.*

3.1 EviNoteRAG Pipeline

Upon receiving a query, **EviNoteRAG** either issues <search> to retrieve external evidence or, when sufficiently confident, answers directly. Retrieved content arrives as <information> and may be noisy; therefore, the system produces SENs in <summary> to filter distractors and retain evidence critical to the answer. Once sufficient notes are consolidated, the agent finalizes the response in <answer>. Importantly, SENs explicitly link supportive evidence to the evolving answer, ensuring consistency and precision.

3.2 Supportive-Evidence Note

To improve information utilization, SENs filter out irrelevant content within <summary> tags, retaining only answer-supportive evidence. We detail two key components below.

Evidence-aware Annotations. SENs incorporate two annotation types: *key information* (denoted by ∗) and *uncertain information* (denoted by

−). These annotations preserve the model's certainty across multi-turn interactions, enabling precise identification of key information and avoiding misguidance from uncertain content, yielding substantial gains over naive summarization (Section 4.6, Naive Summary vs. SEN).

Dynamic SEN Workflow. SEN generation is optional after each retrieval step, allowing the model to dynamically determine whether summarization is necessary based on retrieval outcomes. This flexibility is essential for RL training effectiveness (Section 4.6, Force Summary vs. Ours), as it enables the model to explore optimal RAG strategies rather than being constrained to a fixed pipeline. To guide high-quality SEN generation, we propose the Evidence Quality Reward (EQR), which provides entailment-based feedback to focus on answer-relevant content.

3.3 Evidence Quality Reward

To encourage the generation of high-quality SENs, EQR introduces an Entailment Judge as a supervision signal. The underlying intuition is straightforward: a well-formed SEN should provide sufficient grounds for logically inferring the ground-truth answer. We realize the Entailment Judge through a lightweight NLI model (Sanh et al., 2019), which evaluates whether the final SEN entails the correct answer. Specifically, we construct an answer claim h asserting that ANS_{gt} is the correct answer to query q, and use the final SEN SEN_{last} as the premise:

$$R_{\text{EQR}} = \mathcal{M}_{\text{Judge}}(\text{SEN}_{\text{last}}, h)[\text{entailment}], \quad (1)$$

where $[\text{entailment}]$ denotes the confidence score for the entailment class. This reward $R_{\text{EQR}} \in \mathbb{R}$ encourages the model to generate SENs that logically support the correct answer. To reduce computational overhead, EQR is applied only to the final SEN in each output sequence. For example, given the question *"What is **the largest** planet in the solar system?"* with ground-truth answer *"Jupiter"*, a SEN stating *"Jupiter is the largest planet"* receives a high entailment score, whereas *"Jupiter is a planet"* receives a low score, as it omits the crucial superlative fact. This demonstrates how subtle semantic distinctions in SENs affect whether the answer can be logically inferred.

Figure 2: Overview of **EviNoteRAG**. To enhance RAG through quality-augmented evidence notes, the model is trained to generate *Supportive-Evidence Notes (SENs)* that retain only answer-critical information. An entailment-based *Evidence Quality Reward (EQR)* further ensures that each note faithfully supports the final answer, guiding the model toward more accurate and evidence-grounded reasoning.

3.4 Training Strategy

Reward Strategy. We design a reward strategy to supervise the model's behavior throughout training, balancing two goals: (1) encouraging the model to explicitly mark uncertainty and highlight key information when answer prediction is unreliable; (2) promoting accurate and well-supported answers as performance improves. The scalar reward $R(\cdot)$ is computed as:

$$R = \begin{cases} 1 + R_{\text{EQR}} & \text{format } \checkmark, \text{ answer } \checkmark \\ 0.1 + R_{\text{EQR}} & \text{format } \checkmark, \text{ answer } \boldsymbol{\times}, \\ & \text{note-taking } \checkmark \\ 0 & \text{otherwise} \end{cases} . \quad (2)$$

The **format** criterion holds if the output includes an <answer> tag, at least one <summary> tag, and follows the prescribed schema. The **answer** criterion requires an exact match with the ground truth, and the **note-taking** criterion holds when Evidence-aware Annotations are marked according to the SEN design. This reward design gently guides the model to perform structured note-taking when QA capability is still developing (via $0.1 + R_{\text{EQR}}$), and increasingly incentivizes precise, logically supported answers as it becomes more reliable (via $1 + R_{\text{EQR}}$).

Policy Optimization. We adopt GRPO (Shao et al., 2024) to optimize policy π_θ using reward R. GRPO updates π_θ using a reference policy $\pi_{\theta_{\text{ref}}}$ and rollouts from $\pi_{\theta_{\text{old}}}$:

$$r_1, r_2, \ldots, r_G = R(y_1, y_2, \ldots, y_G), \quad (3)$$

$$A_i = \frac{r_i - \text{mean}(r_1, \ldots, r_G)}{\text{std}(r_1, \ldots, r_G)}, \quad (4)$$

$$\rho_i = \frac{\pi_\theta(y_i|x)}{\pi_{\theta_{\text{old}}}(y_i|x)}, \quad (5)$$

$$\mathcal{J}(\theta) = \mathbb{E}_{\substack{x \sim \mathcal{D} \\ \{y_i\}_{i=1}^G \sim \pi_{\theta_{\text{old}}}(\cdot|x)}} \left[\frac{1}{G} \sum_{i=1}^G \min\left(\rho_i A_i, \right.\right.$$
$$\left. \text{clip}(\rho_i, 1 - \epsilon, 1 + \epsilon) A_i \right)$$
$$\left. - \beta \, \mathbb{D}_{\text{KL}}\left(\pi_\theta \, \| \, \pi_{\theta_{\text{ref}}}\right) \right], \quad (6)$$

where x is an input from $\mathcal{D}$, y_i is a trajectory from π_θ, and A_i is its advantage. $\mathbb{D}_{\text{KL}}$ denotes the unbiased KL estimator (Shao et al., 2024), and ϵ, β are hyperparameters balancing exploration and exploitation.

4 Experiments

4.1 Datasets

We evaluated EviNoteRAG on seven widely used Question Answering (QA) benchmark

Table 1: Performance comparisons on out-of-domain (TriviaQA, 2Wiki, Bamboogle, Musique, PopQA) and in-domain (NQ, HotpotQA) benchmarks. For each dataset, the **bold** indicates the best performance, and underline indicates the second-best performance.

Methods	TriviaQA		2Wiki		Bamboogle		Musique		PopQA		NQ		HotpotQA	
	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM
Foundational Model														
Direct Inference	0.321	0.298	0.264	0.228	0.221	0.216	0.085	0.074	0.170	0.150	0.198	0.134	0.244	0.216
RAG Workflow	0.456	0.442	0.244	0.232	0.254	0.240	0.100	0.094	0.479	0.458	0.420	0.376	0.371	0.330
CoT														
ReCAT	0.474	0.438	0.482	0.336	0.272	0.184	0.192	0.118	0.367	0.308	0.495	0.454	0.421	0.380
IRCoT	0.432	0.418	0.492	0.417	0.245	0.112	0.192	0.102	0.322	0.287	0.512	0.470	0.435	0.392
Prompt-Based Agentic RAG														
Self-Ask	0.392	0.362	0.336	0.278	0.332	0.320	0.260	0.214	0.410	0.398	0.471	0.423	0.410	0.365
Iter-RetGen	0.374	0.356	0.326	0.270	0.232	0.160	0.178	0.118	0.376	0.348	0.442	0.395	0.390	0.342
Self-RAG	0.451	0.436	0.432	0.391	0.351	0.256	0.192	0.183	0.332	0.314	0.508	0.465	0.448	0.402
CR-Planner	0.417	0.403	0.473	0.452	0.434	0.304	0.271	0.202	0.351	0.350	0.520	0.482	0.452	0.405
Search-o1	0.589	0.566	0.286	0.272	0.358	0.328	0.168	0.140	0.369	0.336	0.345	0.310	0.330	0.268
RL-Based Agentic RAG														
ReARTeR	0.468	0.506	**0.554**	**0.534**	0.119	0.096	0.296	0.237	0.432	0.422	0.545	0.502	0.512	0.465
R1-Searcher	0.731	0.688	0.491	0.446	0.201	0.176	0.228	0.214	0.427	0.413	0.538	0.492	0.498	0.451
Search-R1	0.754	0.694	0.280	0.244	0.377	0.320	0.274	0.184	**0.498**	**0.482**	0.550	0.508	0.464	0.420
EviNoteRAG (Ours)	**0.795**	**0.730**	0.536	0.494	**0.528**	**0.424**	**0.336**	**0.240**	0.491	0.480	**0.563**	**0.524**	**0.557**	**0.490**

datasets: **(1) In-Domain Datasets** consist of NQ (Kwiatkowski et al., 2019) and Hot-potQA (Yang et al., 2018). These datasets are considered in-domain because they originate from the same question distribution, allowing for a direct comparison on familiar tasks. **(2) Out-of-Domain Datasets:** Out-of-Domain Datasets include PopQA (Mallen et al., 2022), TriviaQA (Joshi et al., 2017), 2WikiMultiHopQA (2Wiki) (Ho et al., 2020), Musique (Trivedi et al., 2022b) and Bamboogle (Press et al., 2022). These datasets involve more complex multi-hop reasoning and are classified as out-of-domain because their question distributions differ significantly from our fine-tuning set. For testing, we randomly select 500 samples from each of the datasets, except for Bamboogle, where we use the entire 125 samples from its validation set.

4.2 Metrics.

We evaluated the model using the following metrics: **(1) Exact Match (EM)** evaluates whether the predicted answer strictly matches the ground truth, while **(2) F1 Score** balances precision and recall, offering a more flexible measure when answers are close but not identical to the ground truth. These two metrics complement each other, providing a more comprehensive assessment of the accuracy of the answer. Furthermore, to demonstrate the impact of improving the quality of SEN support in

the Ablation Study section, we introduce **(3) Evidence Quality Reward (EQR):** a metric designed to assess the quality of supporting evidence nodes (SEN), focusing on their relevance and logical consistency.

4.3 Baselines

To evaluate our model, we compare it against several established baselines: **(1) Foundational Model:** All of our models use the Qwen-2.5-7B-Instruct model (Yang et al., 2024) as the foundational model. This includes *Direct Inference*, which generates answers without using retrieved context, and RAG WORKFLOW, which guides the foundational model for RAG retrieval solely by modifying instructions, without any additional training or fine-tuning. **(2) Chain-of-Thought (CoT) Methods:** This category includes RE-CAT and IRCoT (Trivedi et al., 2023), which enhance reasoning by explicitly generating intermediate Chain-of-Thought reasoning steps. **(3) Prompt-Based Agentic RAG:** This group includes models such as SELF-ASK (Press et al., 2022), ITER-RETGEN (Shao et al., 2023), SELF-RAG (Asai et al., 2024), and SEARCH-O1 (Li et al., 2025b), which combine retrieval and reasoning through designed prompts. We also include CR-PLANNER (Li et al., 2024), which employs Monte Carlo Tree Search (MCTS) for planning. **(4) RL-Based Agentic RAG:** This category in-

cludes models like REARTER (Sun et al., 2025b), R1-SEARCH (Song et al., 2025a), and SEARCH-R1 (Jin et al., 2025), which extend the traditional RAG paradigm by incorporating agentic search and policy learning through reinforcement learning, enabling the model to adaptively refine its retrieval and reasoning strategies during training.

4.4 Implementation Details

Our experimental framework is built upon the Qwen-2.5-7B-Instruct model (Yang et al., 2024) using the Verl framework (Sheng et al., 2025). The retrieval module utilizes the 2018 Wikipedia dump (Karpukhin et al., 2020) as the knowledge corpus, with the E5 model (Wang et al., 2024a) serving as the dense retriever. For model optimization, we apply loss masking to update only the tokens generated by the model. The learning rate is set to 1e-5, with a sampling temperature of 1.0. Training is performed with a batch size of 600 (distributed across 15 NVIDIA A100 Tensor Core GPUs), generating 4 rollouts per sample and limiting the maximum retrieval count to 5. In addition, one separate GPU is used to run a 144M-parameter DISTILBERT (Sanh et al., 2019) model for calculating the Evidence Quality Reward.

4.5 Main Results

The overall performance of EVINOTERAG is summarized in Tab. 1, which reports results across both in-domain and out-of-domain benchmarks. All key improvements are 2–6× larger than run-to-run variability, confirming statistical significance (Appendix H).

In-Domain Performance. On benchmarks whose distributions are aligned with the training data, EVINOTERAG achieves strong results and consistently surpasses baseline models. On HotpotQA, a dataset that requires complex multi-hop reasoning, EVINOTERAG significantly outperforms both RAG and CHAIN-OF-THOUGHT (CoT) methods. These improvements arise from the Supportive-Evidence Notes (SEN) mechanism, which filters out spurious retrievals, and the Evidence Quality Reward (EQR), which encourages the selection of answer-critical evidence. Together, these mechanisms enable the model to construct faithful reasoning chains and maintain factual consistency, thereby yielding more accurate in-domain answers. Results remain consistent on an expanded larger test set across all

benchmarks (Appendix G).

Out-of-Domain Generalization. Across out-of-domain benchmarks, EVINOTERAG achieves clear gains over the strong RL baseline (Search-R1): +91% F1 on 2Wiki (0.536 vs. 0.280, +0.256), +40% on Bamboogle (0.528 vs. 0.377, +0.151), +23% on Musique (0.336 vs. 0.274, +0.062), and +5.4% on TriviaQA (0.795 vs. 0.754, +0.040), with near-parity on PopQA (0.491 vs. 0.498). These gains are driven by behavior shaping: Supportive-Evidence Notes (SEN) compress question-conditioned evidence before generation, and the entailment-based Evidence Quality Reward (EQR) enforces that notes logically support the final answer, reducing distractor-induced errors.

Overall, EVINOTERAG delivers consistent improvements across both in-domain and out-of-domain settings. These results demonstrate that effective noise filtering, coupled with reward design, enhances not only stability and accuracy but also generalization across diverse QA tasks. The Ablations in the following section further confirm that **SEN+EQR** is the strongest configuration across OOD sets while controlling sequence length and token usage, aligning with our generalization claim.

4.6 Ablation Study

Settings. Our experiments build on **Base** model SEARCH-R1 (Jin et al., 2025), an end-to-end RL-based RAG pipeline. We examine four configurations. **Force Summary (FS)** requires an explicit <summary> after each retrieval, with zero reward if the tag is absent, ensuring strict compliance but increasing reward sparsity. **Naive Summary (NS)** relaxes this constraint, allowing optional summarization while still rewarding correct answers. **SEN** enriches NS with evidence-aware annotations, improving focus and reducing misleading reasoning. **SEN+EQR** further introduces the Evidence Quality Reward (EQR), which uses an Entailment Judge to assess SEN quality and enhance reasoning accuracy.

As shown in Tab. 2, performance consistently ranks: SEN+EQR > SEN > NS > Base > FS.

Effectiveness of Dynamic Summarization. FS yields inferior results, indicating that rigid structural constraints and reward sparsity hinder model adaptability. In contrast, NS significantly outperforms the baseline, demonstrating that flexible

Table 2: Ablation results on in-domain and out-of-domain QA benchmarks. Bold highlights the best performance, while underline marks the second best.

Methods	TriviaQA		2Wiki		Bamboogle		Musique		PopQA		NQ		HotpotQA	
	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM
Base	0.754	0.694	0.280	0.244	0.377	0.320	0.274	0.184	0.498	0.482	0.550	0.508	0.464	0.420
+ Force Summary	0.708	0.638	0.334	0.304	0.338	0.224	0.274	0.184	0.472	0.454	0.505	0.450	0.423	0.362
+ Naive Summary	0.774	0.712	0.462	0.424	0.496	0.384	0.280	0.204	0.500	0.488	0.551	0.502	**0.560**	**0.498**
+ SEN	**0.795**	**0.730**	0.505	0.464	0.440	0.352	0.317	0.210	**0.524**	**0.514**	**0.563**	0.518	0.550	0.482
+ SEN + EQR (Ours)	**0.795**	**0.730**	**0.536**	**0.494**	**0.528**	**0.424**	**0.336**	**0.240**	0.491	0.480	**0.563**	**0.524**	0.557	0.490

summarization improves reasoning quality. We also find that changing prompts to require summarization or evidence selection does not affect model performance (Appendix B).

Effectiveness of Evidence-aware Annotations. The improvement from NS to SEN validates our central hypothesis: structured evidence organization coupled with explicit uncertainty markings (key info, uncertain info) serves as an efficient filter for noise and enhances multi-hop reasoning accuracy. SEN's effectiveness arises from its dual capacity for selective evidence highlighting and uncertainty quantification, enabling the model to maintain a clearer reasoning state across retrieval steps.

Effectiveness of EQR. SEN+EQR achieves optimal performance through entailment-based supervision. The Evidence Quality Reward ensures logical consistency between generated notes and final answers, providing crucial semantic alignment that complements SEN's structural guidance. We further demonstrate that this setting guides the model toward thorough and effective summarization behavior while maintaining training stability (Appendix B, C, D). A sensitivity analysis of reward hyperparameters confirms that our default setting achieves the best balance between SEN quality and training stability (Appendix F).

4.7 Training Stability and Performance Enhancement Analysis

Stable Training Requires Proper Workflow Design. Fig. 3(a)–(d) highlights the crucial role of workflow design in training stability. The base model (Jin et al., 2025) collapses around epoch 80, marked by rising KL divergence, declining rewards, and unstable actor loss. In contrast, EVINOTERAG adopts a retrievalnoteanswer workflow that yields consistently stable curves across all metrics. By introducing structured instructions that resemble human note-taking, it re-

duces task difficulty, avoids degenerate outputs, and enables more stable policy learning.

Behavioral Supervision and Noise Filtering Improve Efficiency. Fig. 3(c) shows that incorporating evidence-quality rewards (EQR) prevents unstable performance and excessive per-token latency. This improvement arises from EVINOTERAGs ability to produce shorter, more focused responses by filtering irrelevant content early, thereby reducing redundant reasoning. Fig. 3(d) further demonstrates that it maintains consistently lower token-level latency (Time Per Token, TPT), while the base model suffers from reasoning loops and collapses near epoch 80. Overall, the joint use of evidence note-taking and behavioral supervision yields shorter responses, reduces unnecessary computation, and enhances stability.

EQR Improves SEN Quality Throughout Training. Fig. 3(a) shows that the Evidence Quality Reward (EQR) steadily increases as training proceeds, indicating that the model learns to generate higher-quality Supporting Evidence Notes (SEN). This dynamic growth reflects the models improved ability to align evidence with the target answer. In addition, Fig. 3(e) demonstrates that incorporating EQR leads to SEN with stronger entailment support compared to the ablated variant, highlighting the effectiveness of behavioral supervision. Together, these results confirm that EQR not only stabilizes training but also directly enhances the reasoning quality of SEN.

4.8 Case Study

Baseline Fails by Mixing Speculation with Evidence. In the case in Fig. 4, the baseline retrieves passages noting that Knockin on Heavens Door was performed by Guns N Roses but fails to distinguish between performance and authorship. Its reasoning chain introduces speculative guesses (e.g., may suggest), which dilute the role

Figure 3: Training dynamics illustrating (a) reward, (b) KL Loss, (c) Response Length, and (d) Total Time Per Token (TPT). (e) Ablation study on EQR experiments.

Figure 4: Case study on the query "who wrote *Knocking' on Heaven's Door*?". The baseline model is misled by misleading contextual information (Doc 2 repeatedly frames the song as a Guns N Roses piece), resulting in the incorrect answer "Guns N Roses". In contrast, our **EviNoteRAG** model effectively filters out misleading signals, emphasizes key evidence (e.g., writer credit in Doc 1 and Doc 2), and produces the correct answer "Bob Dylan". This highlights the importance of mitigating the interference of false or misleading information in knowledge-intensive tasks.

of explicit evidence in Doc 1 and Doc 3 stating that Bob Dylan wrote the song. As a result, the model wastes tokens on noisy deliberations and incorrectly concludes that Guns N Roses are the authors.

EviNoteRAG Clarify Evidence and Improve Efficiency. EVINOTERAG highlights decisive authorship evidence (e.g., Bob Dylan) in key-info notes (*), keeping reasoning constrained to facts directly relevant to who wrote . Moreover, the Evidence Quality Reward (EQR) guides the model to produce clearer, entailment-supported notes that isolate answer-supportive information before generation; this yields shorter answers and lower token-level latency with stable decoding. Overall gains stem from evidence shaping (SEN+EQR). More case studies are provided in Appendix E.

5 Conclusion

We present **EviNoteRAG**, a framework that introduces a note-taking step to extract answer-supportive evidence before answering. By training LLMs to produce *Supportive-Evidence Notes (SENs)* and guiding them via a tailored entailment-based reward, our approach improves answer accuracy. Extensive experiments demonstrate that EviNoteRAG achieves state-of-the-art performance while enhancing training stability. These results highlight the benefits of evidence-focused abstraction for robust, faithful retrieval-augmented reasoning. Beyond empirical gains, our work establishes a general recipe for integrating structured note-taking with reward design, offering a principled path toward more interpretable and controllable RAG systems.

Limitations

While EviNoteRAG demonstrates strong performance across diverse QA benchmarks, several limitations remain. First, although our *Entailment-based Evidence Quality Reward (EQR)* is computationally lightweight and provides effective supervision, it relies on a relatively simple Natural Language Inference (NLI) model (e.g., Distil-BERT) that evaluates note quality along a single entailment dimension. Employing a more capable judge could enable richer, multi-dimensional quality assessment, potentially yielding higher-quality *Supportive-Evidence Notes (SENs)* and further improving reasoning accuracy. Second, our current note-taking strategy focuses on extracting and annotating answer-critical information with key and uncertain markers, but does not explore more diverse or adaptive note-taking mechanisms. Incorporating complementary signals such as token-level uncertainty estimation or entropy-based filtering could lead to more intelligent and context-aware note generation, further reducing noise and error accumulation in complex multi-hop reasoning scenarios.

References

Salaheddin Alzubi, Creston Brooks, Purva Chiniya, Edoardo Contente, Chiara von Gerlach, Lucas Irwin, Yihan Jiang, Arda Kaz, Windsor Nguyen, Sewoong Oh, and 1 others. 2025. Open deep search: Democratizing search with open-source reasoning agents. *arXiv*.

Reinald Kim Amplayo, Kellie Webster, Michael Collins, Dipanjan Das, and Shashi Narayan. 2022. Query refinement prompts for closed-book long-form question answering. *arXiv*.

Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi. 2024. Self-rag: Learning to retrieve, generate, and critique through self-reflection. In *ICLR*.

Mingyang Chen, Tianpeng Li, Haoze Sun, Yijie Zhou, Chenzheng Zhu, Haofen Wang, Jeff Z Pan, Wen Zhang, Huajun Chen, Fan Yang, and 1 others. 2025. Learning to reason with search for llms via reinforcement learning. *arXiv*.

Zijian Chen, Xueguang Ma, Shengyao Zhuang, Jimmy Lin, Akari Asai, and Victor Zhong. 2026. Agentir: Reasoning-aware retrival for deep research agents. *arXiv preprint arXiv:2603.04384*.

Yuqin Dai, Shuo Yang, Guoqing Wang, Yong Deng, Zhanwei Zhang, Jun Yin, Pengyu Zeng, Zhenzhe Ying, Changhua Meng, Can Yi, and 1 others. 2025.

Careful queries, credible results: Teaching rag models advanced web search tools with reinforcement learning. *arXiv*.

Yuqin Dai, Shuo Yang, Guoqing Wang, Yong Deng, Zhanwei Zhang, Jun Yin, Pengyu Zeng, Zhenzhe Ying, Changhua Meng, Can Yi, and 1 others. 2026. Careful queries, credible results: Teaching rag models advanced web search tools with reinforcement learning. In *AAAI*.

Yong Deng, Guoqing Wang, Zhenzhe Ying, Xiaofeng Wu, Jinzhen Lin, Wenwen Xiong, Yuqin Dai, Shuo Yang, Zhanwei Zhang, Qiwen Wang, and 1 others. 2025. Atom-searcher: Enhancing agentic deep research via fine-grained atomic thought reward. *arXiv preprint arXiv:2508.12800*.

Wenfeng Feng, Chuzhan Hao, Yuewei Zhang, Jingyi Song, and Hao Wang. 2025. Airrag: Activating intrinsic reasoning for retrieval augmented generation using tree-based search. *arXiv*.

Yunfan Gao, Yun Xiong, Yijie Zhong, Yuxi Bi, Ming Xue, and Haofen Wang. 2025. Synergizing rag and reasoning: A systematic review. *arXiv preprint arXiv:2504.15909*.

Xinyan Guan, Jiali Zeng, Fandong Meng, Chunlei Xin, Yaojie Lu, Hongyu Lin, Xianpei Han, Le Sun, and Jie Zhou. 2025. Deeprag: Thinking to retrieve step by step for large language models. *arXiv*.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv*.

Bernal Jiménez Gutiérrez, Yiheng Shu, Weijian Qi, Sizhe Zhou, and Yu Su. 2025. From rag to memory: Non-parametric continual learning for large language models. *arXiv*.

Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. 2020. Constructing a multi-hop qa dataset for comprehensive evaluation of reasoning steps. In *COLING*, pages 6609–6625.

Jerry Huang, Siddarth Madala, Risham Sidhu, Cheng Niu, Hao Peng, Julia Hockenmaier, and Tong Zhang. 2025. Rag-rl: Advancing retrieval-augmented generation via rl and curriculum learning. *arXiv*.

Soyeong Jeong, Jinheon Baek, Sukmin Cho, Sung Ju Hwang, and Jong C. Park. 2024. Adaptive-rag: Learning to adapt retrieval-augmented large language models through question complexity. *arXiv*.

Songtao Jiang, Yuan Wang, Ruizhe Chen, Yan Zhang, Ruilin Luo, Bohan Lei, Sibo Song, Yang Feng, Jimeng Sun, Jian Wu, and Zuozhu Liu. 2025. Capo: Reinforcing consistent reasoning in medical decision-making. *Preprint*, arXiv:2506.12849.

Yucheng Jiang, Yijia Shao, Dekun Ma, Sina J Semnani, and Monica S Lam. 2024. Into the unknown unknowns: Engaged human learning through participation in language model agent conversations. *arXiv*.

Shuguang Jiao, Xinyu Xiao, Yunfan Wei, Shuhan Qi, Chengkai Huang, Quan Z Michael Sheng, and Lina Yao. 2026. Prunerag: Confidence-guided query decomposition trees for efficient retrieval-augmented generation. *arXiv preprint arXiv:2601.11024*.

Bowen Jin, Jinsung Yoon, Jiawei Han, and Sercan O Arik. 2024. Long-context llms meet rag: Overcoming challenges for long inputs in rag. *arXiv preprint arXiv:2410.05983*.

Bowen Jin, Hansi Zeng, Zhenrui Yue, Jinsung Yoon, Sercan Arik, Dong Wang, Hamed Zamani, and Jiawei Han. 2025. Search-r1: Training llms to reason and leverage search engines with reinforcement learning. *arXiv*.

Mandar Joshi, Eunsol Choi, Daniel S Weld, and Luke Zettlemoyer. 2017. Triviaqa: A large scale distantly supervised challenge dataset for reading comprehension. *arXiv*.

Leslie Pack Kaelbling, Michael L Littman, and Andrew W Moore. 1996. Reinforcement learning: A survey. *JAIR*.

Vladimir Karpukhin, Barlas Ouz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen tau Yih. 2020. Dense passage retrieval for open-domain question answering. *arXiv*.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, and 1 others. 2019. Natural questions: a benchmark for question answering research. *ACL*.

Zhicheng Lee, Shulin Cao, Jinxin Liu, Jiajie Zhang, Weichuan Liu, Xiaoyin Che, Lei Hou, and Juanzi Li. 2025. Rearag: Knowledge-guided reasoning enhances factuality of large reasoning models with iterative retrieval augmented generation. *arXiv*.

Xiaoxi Li, Guanting Dong, Jiajie Jin, Yuyao Zhang, Yujia Zhou, Yutao Zhu, Peitian Zhang, and Zhicheng Dou. 2025a. Search-o1: Agentic search-enhanced large reasoning models. *arXiv*.

Xiaoxi Li, Guanting Dong, Jiajie Jin, Yuyao Zhang, Yujia Zhou, Yutao Zhu, Peitian Zhang, and Zhicheng Dou. 2025b. Search-o1: Agentic search-enhanced large reasoning models. *arXiv*.

Xingxuan Li, Weiwen Xu, Ruochen Zhao, Fangkai Jiao, Shafiq Joty, and Lidong Bing. 2024. Can we further elicit reasoning in llms? critic-guided planning with retrieval-augmentation for solving challenging tasks. *arXiv*.

Lihui Liu. 2026. A survey of rag and reasoning in large language models. *Authorea Preprints*.

Wanlong Liu, Enqi Zhang, Li Zhou, Dingyi Zeng, Shaohuan Cheng, Chen Zhang, Malu Zhang, and Wenyu Chen. 2024. A compressive memory-based retrieval approach for event argument extraction. *arXiv*.

Alex Mallen, Akari Asai, Victor Zhong, Rajarshi Das, Hannaneh Hajishirzi, and Daniel Khashabi. 2022. When not to trust language models: Investigating effectiveness and limitations of parametric and non-parametric memories. *arXiv*, 7.

Reiichiro Nakano, Jacob Hilton, Suchir Balaji, Jeff Wu, Long Ouyang, Christina Kim, Christopher Hesse, Shantanu Jain, Vineet Kosaraju, William Saunders, and 1 others. 2021. Webgpt: Browser-assisted question-answering with human feedback. *arXiv*.

Ofir Press, Muru Zhang, Sewon Min, Ludwig Schmidt, Noah A Smith, and Mike Lewis. 2022. Measuring and narrowing the compositionality gap in language models. *arXiv*.

Zehan Qi, Xiao Liu, Iat Long Iong, Hanyu Lai, Xueqiao Sun, Jiadai Sun, Xinyue Yang, Yu Yang, Shuntian Yao, Wei Xu, Jie Tang, and Yuxiao Dong. 2025. Webrl: Training llm web agents via self–evolving online curriculum reinforcement learning. In *ICLR*.

Chris Samarinas, Haw-Shiuan Chang, and Hamed Zamani. 2026. Truncated step-level sampling with process rewards for retrieval-augmented reasoning. *arXiv preprint arXiv:2602.23440*.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2019. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv*.

Rulin Shao, Rui Qiao, Varsha Kishore, Niklas Muennighoff, Xi Victoria Lin, Daniela Rus, Bryan Kian Hsiang Low, Sewon Min, Wen-tau Yih, Pang Wei Koh, and 1 others. 2025. Reasonir: Training retrievers for reasoning tasks. *arXiv*.

Zhihong Shao, Yeyun Gong, Yelong Shen, Minlie Huang, Nan Duan, and Weizhu Chen. 2023. Enhancing retrieval-augmented large language models with iterative retrieval-generation synergy. *arXiv*.

Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, and 1 others. 2024. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv*.

Guangming Sheng, Chi Zhang, Zilingfeng Ye, Xibin Wu, Wang Zhang, Ru Zhang, Yanghua Peng, Haibin Lin, and Chuan Wu. 2025. Hybridflow: A flexible and efficient rlhf framework. In *Proceedings of the Twentieth European Conference on Computer Systems*, pages 1279–1297.

Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed H Chi, Nathanael Schärli, and Denny Zhou. 2023. Large language models can be easily distracted by irrelevant context. In *ICML*.

Huatong Song, Jinhao Jiang, Yingqian Min, Jie Chen, Zhipeng Chen, Wayne Xin Zhao, Lei Fang, and Ji-Rong Wen. 2025a. R1-searcher: Incentivizing the search capability in llms via reinforcement learning. *arXiv*.

Huatong Song, Jinhao Jiang, Wenqing Tian, Zhipeng Chen, Yuhuan Wu, Jiahao Zhao, Yingqian Min, Wayne Xin Zhao, Lei Fang, and Ji-Rong Wen. 2025b. R1-searcher++: Incentivizing the dynamic knowledge acquisition of llms via reinforcement learning. *arXiv*.

Hao Sun, Zile Qiao, Jiayan Guo, Xuanbo Fan, Yingyan Hou, Yong Jiang, Pengjun Xie, Yan Zhang, Fei Huang, and Jingren Zhou. 2025a. Zerosearch: Incentivize the search capability of llms without searching. *arXiv*.

Zhongxiang Sun, Qipeng Wang, Weijie Yu, Xiaoxue Zang, Kai Zheng, Jun Xu, Xiao Zhang, Song Yang, and Han Li. 2025b. Rearter: Retrieval-augmented reasoning with trustworthy process rewarding. *arXiv*.

Hieu Tran, Zonghai Yao, Junda Wang, Yifan Zhang, Zhichao Yang, and Hong Yu. 2024. Rare: Retrieval-augmented reasoning enhancement for large language models. *arXiv*.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2022a. Interleaving retrieval with chain-of-thought reasoning for knowledge-intensive multi-step questions. *arXiv*.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2022b. Musique: Multihop questions via single-hop question composition. *ACL*.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2023. Interleaving retrieval with chain-of-thought reasoning for knowledge-intensive multi-step questions. In *ACL*.

Prakhar Verma, Sukruta Prakash Midigeshi, Gaurav Sinha, Arno Solin, Nagarajan Natarajan, and Amit Sharma. 2024a. Plan* rag: Efficient test-time planning for retrieval augmented generation. *arXiv*.

Vivek Verma, Eve Fleisig, Nicholas Tomlin, and Dan Klein. 2024b. Ghostbuster: Detecting text ghostwritten by large language models. In *NAACL*.

Jinyu Wang, Jingjing Fu, Rui Wang, Lei Song, and Jiang Bian. 2025. Pike-rag: specialized knowledge and rationale augmented generation. *arXiv preprint arXiv:2501.11551*.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. 2024a. Text embeddings by weakly-supervised contrastive pre-training. *arXiv*.

Ruobing Wang, Qingfei Zhao, Yukun Yan, Daren Zha, Yuxuan Chen, Shi Yu, Zhenghao Liu, Yixuan Wang, Shuo Wang, Xu Han, and 1 others. 2024b. Deepnote: Note-centric deep retrieval-augmented generation. *arXiv*.

Jiaqi Wei, Hao Zhou, Xiang Zhang, Di Zhang, Zijie Qiu, Wei Wei, Jinzhe Li, Wanli Ouyang, and Siqi Sun. 2025a. Alignrag: An adaptable framework for resolving misalignments in retrieval-aware reasoning of rag. *arXiv*.

Tianxin Wei, Ting-Wei Li, Zhining Liu, Xuying Ning, Ze Yang, Jiaru Zou, Zhichen Zeng, Ruizhong Qiu, Xiao Lin, Dongqi Fu, and 1 others. 2026. Agentic reasoning for large language models. *arXiv preprint arXiv:2601.12538*.

Zhepei Wei, Wenlin Yao, Yao Liu, Weizhi Zhang, Qin Lu, Liang Qiu, Changlong Yu, Puyang Xu, Chao Zhang, Bing Yin, and 1 others. 2025b. Webagent-r1: Training web agents via end-to-end multi-turn reinforcement learning. *arXiv*.

Junde Wu, Jiayuan Zhu, Yuyuan Liu, Min Xu, and Yueming Jin. 2025a. Agentic reasoning: A streamlined framework for enhancing llm reasoning with agentic tools. *arXiv*.

Yangzhen Wu, Zhiqing Sun, Shanda Li, Sean Welleck, and Yiming Yang. 2025b. Inference scaling laws: An empirical analysis of compute-optimal inference for problem-solving with language models. In *ICLR*.

Ruibin Xiong, Yimeng Chen, Dmitrii Khizbullin, Mingchen Zhuge, and Jürgen Schmidhuber. 2025. Beyond outlining: Heterogeneous recursive planning for adaptive long-form writing with language models. *arXiv*.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, and 1 others. 2024. Qwen2.5 technical report. *arXiv*.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William W. Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. 2018. Hotpotqa: A dataset for diverse, explainable multi–hop question answering. In *EMNLP*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language models. *arXiv*.

Jun Yin, Pengyu Zeng, Haoyuan Sun, Yuqin Dai, Han Zheng, Miao Zhang, Yachao Zhang, and Shuai Lu. 2025. Floorplan-llama: Aligning architects feedback and domain knowledge in architectural floor plan generation. In *ACL*.

Xiaohan Yu, Chao Feng, Lang Mei, and Chong Chen. 2026. M3searcher: Modular multimodal information seeking agency with retrieval-oriented reasoning. *arXiv preprint arXiv:2601.09278*.

Zhenrui Yue, Honglei Zhuang, Aijun Bai, Kai Hui, Rolf Jagerman, Hansi Zeng, Zhen Qin, Dong Wang, Xuanhui Wang, and Michael Bendersky. 2024. Inference scaling for long-context retrieval augmented generation. *arXiv*.

Tianjun Zhang, Shishir G Patil, Naman Jain, Sheng Shen, Matei Zaharia, Ion Stoica, and Joseph E Gonzalez. 2024. Raft: Adapting language model to domain specific rag. *arXiv*.

Yue Zhang, Yafu Li, Leyang Cui, Deng Cai, Lemao Liu, Tingchen Fu, Xinting Huang, Enbo Zhao, Yu Zhang, Yulong Chen, and 1 others. 2025. Sirens song in the ai ocean: A survey on hallucination in large language models. *Computational Linguistics*.

Qingfei Zhao, Ruobing Wang, Dingling Xu, Daren Zha, and Limin Liu. 2025a. R-search: Empowering llm reasoning with search via multi-reward reinforcement learning. *arXiv*.

Xuejiao Zhao, Siyan Liu, Su-Yin Yang, and Chunyan Miao. 2025b. Medrag: Enhancing retrieval-augmented generation with knowledge graph-elicited reasoning for healthcare copilot. In *WWW*.

Yuxiang Zheng, Dayuan Fu, Xiangkun Hu, Xiaojie Cai, Lyumanshan Ye, Pengrui Lu, and Pengfei Liu. 2025. Deepresearcher: Scaling deep research via reinforcement learning in real-world environments. *arXiv*.

Yujia Zhou, Zheng Liu, Jiajie Jin, Jian-Yun Nie, and Zhicheng Dou. 2024. Metacognitive retrieval-augmented large language models. In *WWW*.

A LLM Usage Statement

In the preparation of this manuscript, a Large Language Model (LLM) was employed solely for language polishing. All academic content, interpretations, and responsibilities remain entirely with the authors.

B Effect of Summary Strategies

B.1 Experimental Setup for Summary Strategy Ablations

We evaluate summary strategies using the unified QA setup described in the *Experiments* section (Section 4). Unless otherwise noted, all components (retriever, datasets, metrics) and hyperparameters follow the main setup to control for confounding factors. The base system (Jin et al., 2025) implements an end-to-end reinforcement learning pipeline for retrieval-augmented generation (RAG), upon which we vary only the summary strategy as follows:

- **Naive Summary (NS)**: The model can dynamically generate a concise <summary> of the retrieved documents prior to answering, without incorporating evidence-aware annotations. Unlike FS setting, the model remains eligible for a reward if the answer is correct, even when a summary is not provided.

- **Naive Evidence (NE)**: A tag-variant of NS in which the model is instructed to output an <evidence> section instead of <summary> and to include only answer-relevant content. Beyond the tag replacement and this content restriction, the procedure mirrors NS and introduces no additional supervision.

- **Force Summary (FS)**: The model is forced to produce an explicit <summary> section after each retrieval. If the tag is absent, the reward is set to zero during training, which strictly enforces compliance but consequently increases reward sparsity.

- **Supportive-Evidence Notes (SEN)**: Our proposed strategy that guides the model to extract and organize supporting evidence into structured notes before answering. SEN further requires explicit marking of *key* information (with "$\star$") and *uncertain* information (with "-"), promoting fine-grained supervision aligned with human note-taking.

B.2 Main Results

As shown in Tab. 3, our ablation results provide a systematic comparison across different instructional designs. Several consistent patterns emerge.

Overall Ranking of Instruction Designs. A clear hierarchy of effectiveness can be observed:

$$\text{SEN} > \text{NS} \approx \text{NE} > \text{Base} > \text{FS}.$$

This ranking reflects the strength of supervision each design introduces. SEN enforces structured note-taking and yields the most effective, highinformation-utilization summary; NS and NE provide only weak summarization signals; Base relies purely on raw retrieval without additional supervision, while FS over-constrains optimization with sparse rewards and ultimately harms performance. These results show that:

Table 3: Ablation study on in-domain and out-of-domain QA tasks. We compare different instructional designs: Naive Summary (NS), Naive Evidence (NE), Force Summary (FS), and our proposed Supportive-Evidence Notes (SEN). **Bold** indicates the best performance, while underline marks the second best.

Methods	TriviaQA		2Wiki		Bamboogle		Musique		PopQA		NQ		HotpotQA	
	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM
Base	0.754	0.694	0.280	0.244	0.377	0.320	0.274	0.184	0.498	0.482	0.550	0.508	0.464	0.420
+ NS	0.774	0.712	0.462	0.424	**0.496**	**0.384**	0.280	0.204	0.500	0.488	0.551	0.502	**0.560**	**0.498**
+ NE	0.773	0.710	0.460	0.422	0.494	0.382	0.281	0.206	0.501	0.486	0.552	0.503	0.559	0.497
+ FS	0.708	0.638	0.334	0.304	0.338	0.224	0.274	0.184	0.472	0.454	0.505	0.450	0.423	0.362
+ SEN	**0.795**	**0.730**	**0.505**	**0.464**	0.440	0.352	**0.317**	**0.210**	**0.524**	**0.514**	**0.563**	**0.518**	0.550	0.482

> **Finding 1.** Effective summary strategies are not about requiring or forcing summaries, but about organizing supportive evidence to meaningfully guide reasoning.

SEN vs. NS vs. FS. Compared with naive summaries (NS), SEN encourages explicit identification and organization of supporting evidence, rather than compressing retrievals into a single passage. This design substantially reduces noise from irrelevant documents and better aligns the models reasoning with human note-taking practices. By contrast, FS enforces summary production too rigidly, introducing instability during optimization and degrading performance. Together, these results highlight the importance of instructional flexibility combined with evidence structuring, which SEN uniquely achieves.

Effect of Evidence Marking. We further disentangle whether improvements stem from mere tag changes or from structural constraints. Simply replacing the `<summary>` tag with `<evidence>` and requiring evidence-only summaries yields virtually identical performance to NS, i.e., `evidence` $\approx$ `summary`. However, when we further require explicit evidence marking (i.e., SEN), the model benefits significantly. This suggests that:

> **Finding 2.** Gains come from highlighting key evidence. Methods that structure evidence (selection, organization, explicit marking) outperform those that only require a summary format, yielding stronger factual accuracy.

B.3 Training Dynamic Analysis.

Stability (Fig. 5ab). SEN yields the most stable optimization: policy entropy and KL divergence remain low and flat across training, indicating controlled exploration and limited drift from the reference policy. NS shows a similar but slightly noisier profile. By contrast, the BASE policy exhibits a late-stage surge in both entropy and KL, signalling distribution shift and unstable updates. FS keeps KL small but does not translate this regularization into accuracy improvements, consistent with under-exploration caused by rigid compliance constraints.

Efficiency (Fig. 5cd). SEN/NS produce consistently shorter, more focused responses (hundreds of tokens fewer than BASE) and sustain low ms/token latency. The BASE policys response length inflates markedly in later steps, accompanied by a clear rise in per-token latency. FS attains the lowest latency overall, but its gains reflect conservative decoding rather than improved reasoning, aligning with its inferior task performance.

Overall Analysis. The curves corroborate our ablation ranking (SEN > NS $\approx$ NE > Base > FS): The SEN stabilizes optimization (low KL/entropy), filters noise to keep responses concise, and improves runtime efficiencybenefits that rigidly enforced summaries (FS) fail to realize. These observations are consistent with the training-stability analysis reported in the paper, where structured supervision densifies useful reward signals and regularizes the policy towards faithful evidence use.

C Analysis of Reward Shaping Approaches

C.1 Experimental Setup for Reward Shaping

In our experimental design, we retain the unified QA framework introduced in the previous section and vary only the reward signals. This allows us to isolate the effect of different reward shaping strategies while keeping the model architecture

Figure 5: **Training dynamics under different summary strategies.** (a) actor entropy loss; (b) actor KL loss (w.r.t. the reference policy); (c) mean response length; (d) token-level latency (ms/token). SEN maintains low entropy and KL drift with stable, shorter responses and low latency; NS is slightly less stable but similar in trend; FS achieves low latency at the cost of under-exploration and weaker accuracy; the BASE policy exhibits late-stage blow-up in KL/entropy, response-length sprawl, and higher per-token latency.

Table 4: **Reward shaping ablations**. We compare Force Summary (FS) and its shaped variants with Stochastic Reward (SR) and Evidence Quality Reward (EQR), and contrast them with Supportive-Evidence Notes (SEN) and SEN+EQR. SR serves as a stochastic control to test whether gains come from reward perturbations alone; **SEN** and **EQR** are our proposed components. **Bold** marks the best performance; underline marks the second best.

Methods	TriviaQA		2Wiki		Bamboogle		Musique		PopQA		NQ		HotpotQA	
	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM
Base	0.754	0.694	0.280	0.244	0.377	0.320	0.274	0.184	0.498	0.482	0.550	0.508	0.464	0.420
+ FS	0.708	0.638	0.334	0.304	0.338	0.224	0.274	0.184	0.472	0.454	0.505	0.450	0.423	0.362
+ FS + SR	0.752	0.690	0.410	0.398	0.328	0.296	0.276	0.188	0.514	0.502	0.546	0.500	0.460	0.402
+ FS + EQR	0.766	0.704	0.426	0.414	0.224	0.208	0.274	0.184	**0.528**	**0.518**	0.551	0.510	0.464	0.408
+ SEN	**0.795**	**0.730**	0.505	0.464	0.440	0.352	0.317	0.210	0.524	0.514	**0.563**	0.518	0.550	0.482
+ SEN + EQR	**0.795**	**0.730**	**0.536**	**0.494**	**0.528**	**0.424**	**0.336**	**0.240**	0.491	0.480	**0.563**	**0.524**	**0.557**	**0.490**

and training pipeline fixed. In addition to the baseline (Base), Force Summary (FS), and Supportive-Evidence Notes (SEN), we introduce two further reward mechanisms:

- **Stochastic Reward (SR)**: A mechanism that provides a small reward (0.1) with probability $1/3$ even when the predicted answer is incorrect. The motivation is to alleviate reward sparsity under FS during early training, preventing the model from stagnating due to overly strict zero-reward penalties.

- **Evidence Quality Reward (EQR)**: Our entailment-based reward function, which evaluates whether the final note (or summary) semantically supports the gold answer. By explicitly encouraging consistency between retrieved evidence and the correct answer, EQR not only mitigates reward sparsity but also directly aligns the optimization process with the task objective of evidence-faithful reasoning.

Note: Among all variants, **SEN** and **EQR** are our proposed components.

C.2 Main Results: FS vs. SR vs. EQR

Overall ranking. Across all datasets, as shown in Tab. 4, the methods follow a clear hierarchy:

$$\text{SEN+EQR} > \text{SEN} > \text{FS+EQR}$$
$$> \text{FS+SR} = \text{BASE} > \text{FS}.$$

This ordering highlights two key insights: (1) semantic alignment through EQR improves over purely stochastic shaping (SR), but (2) structural supervision (SEN) is essential, as it consistently delivers the largest performance gains.

SEN remains the primary driver of performance. Structural supervision from SEN delivers the strongest improvements across almost all benchmarks. By guiding the model to explicitly organize supportive evidence, SEN alleviates reward sparsity. Even without additional shaping, SEN alone surpasses all FS-based methods.

SEN+EQR achieves the best overall results. The combination of structural supervision (SEN) and semantic shaping (EQR) provides the best balance of stability and task alignment. SEN+EQR consistently outperforms both standalone SEN and

FS-based variants, achieving the strongest results on 2Wiki, Bamboogle, and Musique, while maintaining top-tier performance on TriviaQA, NQ, and HotpotQA.

FS alone degrades performance. Using FS in isolation leads to degraded performance. Since FS enforces the `<summary>` structure through zero-reward penalties, it introduces severe reward sparsity. This hard penalty discourages exploration and limits the models ability to discover useful behaviors, resulting in accuracy that often falls below the BASE model on several datasets.

SR partially alleviates sparsity but lacks semantic guidance. Introducing SR helps smooth the optimization process by reducing the harshness of reward sparsity. By occasionally rewarding incorrect answers, SR enables more stable training and closes part of the gap to BASE. However, the gains remain modest because SR is not semantically aligned: the reward does not provide guidance about evidence faithfulness, leaving the model largely uninformed about whether its reasoning supports the gold answer.

EQR provides task-aligned shaping; SEN remains essential. Replacing SR with the entailment-based EQR yields larger, more consistent improvements over FS. However, structural supervision from SEN remains the primary driver: SEN surpasses all FS-based variants, and combining EQR with SEN achieves the best overall results across benchmarks (SEN+EQR).

> **Finding 3.** Reward shaping is most effective when semantically aligned with evidence quality and paired with structured supervision: EQR improves over FS/FS+SR, but SEN+EQR delivers the strongest and most consistent gains across datasets.

D Joint Effects and Advanced Analysis

D.1 Experimental Settings for Ablation Study

We follow the same unified QA setup and training protocol described in the previous section. Unless otherwise noted, model architecture, optimization schedule, and data splits remain unchanged. The only differences across variants lie in the instruction strategies and reward signals, ensuring that observed effects can be attributed solely to the proposed modules (SEN and EQR) or their ablations.

These templates define the behavior of the agent under different summary strategies, and their design choices directly account for the performance differences observed in our ablation studies.

D.2 Best Performing Combinations (e.g., SEN+EQR).

Synergy Analysis of Instruction and Reward. EQR encourages the model to produce higher-quality evidence, improving factual reliability. On its own, EQR provides moderate gains, but the strongest improvements arise when it is combined with SEN. This synergy enables the model not only to identify relevant evidence but also to prioritize higher-quality reasoning chains, leading to the best performance across both in-domain and out-of-domain QA tasks.

In-domain vs. Out-of-domain Generalization. A closer look at Tab. 5 reveals that SEN alone already establishes strong in-domain gains on factoid QA datasets such as HotpotQA and NQ. However, the addition of EQR becomes particularly impactful in out-of-domain or compositional settings, such as 2Wiki, Bamboogle, and Musique, where SEN+EQR consistently achieves the highest F1 and EM. This indicates that semantic shaping through EQR plays a critical role in transferring structural supervision to unfamiliar domains.

Comparison against Naive Summarization (NS). The contrast between SEN and instructional naive summarization (NS) underscores the importance of structured evidence organization. While NS sometimes improves over the base model, its benefits are inconsistent, and it occasionally introduces noise by forcing the model to compress evidence prematurely. By contrast, SENs explicit structuring yields consistent improvements across all datasets, confirming that inductive biases toward evidence organization are more effective than general summarization prompts.

Overall Patterns. Bringing these observations together, we can summarize the joint effects as follows:

$$\text{SEN+EQR} > \text{SEN} > \text{NS} > \text{FS+EQR}$$
$$> \text{BASE} > \text{FS+SR} > \text{FS}.$$

This ordering highlights two key findings: (1) SEN is indispensable as the structural backbone

Table 5: Ablation study on in-domain and out-of-domain QA tasks. We report the effect of Force Summary (FS), Stochastic Reward (SR), Supportive-Evidence Notes (SEN), and Evidence Quality Reward (EQR). SR serves as a stochastic control to examine whether improvements stem from reward perturbations alone, while SEN and EQR represent our proposed modules. **Bold** highlights the best performance, while underline marks the second best.

Methods	TriviaQA		2Wiki		Bamboogle		Musique		PopQA		NQ		HotpotQA	
	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM	F1	EM
Base	0.754	0.694	0.280	0.244	0.377	0.320	0.274	0.184	0.498	0.482	0.550	0.508	0.464	0.420
+ NS	0.774	0.712	0.462	0.424	0.496	0.384	0.280	0.204	0.500	0.488	0.551	0.502	**0.560**	**0.498**
+ FS	0.708	0.638	0.334	0.304	0.338	0.224	0.274	0.184	0.472	0.454	0.505	0.450	0.423	0.362
+ FS + SR	0.752	0.690	0.410	0.398	0.328	0.296	0.276	0.188	0.514	0.502	0.546	0.500	0.460	0.402
+ FS + EQR	0.766	0.704	0.426	0.414	0.224	0.208	0.274	0.184	**0.528**	**0.518**	0.551	0.510	0.464	0.408
+ SEN	**0.795**	**0.730**	0.505	0.464	0.440	0.352	0.317	0.210	0.524	0.514	**0.563**	0.518	0.550	0.482
+ SEN + EQR	**0.795**	**0.730**	**0.536**	**0.494**	**0.528**	**0.424**	**0.336**	**0.240**	0.491	0.480	**0.563**	**0.524**	0.557	0.490

Figure 6: **Training stability.** Actor-side stability diagnostics across methods (Base, FS, FS+SR, FS+EQR, NS, SEN, and **Ours** = SEN+EQR). Panels: (a) reward score, (b) actor KL loss w.r.t. the reference policy. Lower and smoother curves indicate more stable optimization. (c) number of actions. When the model generates invalid actions, it tends to repeat the previous behavior, leading to a rapid increase in action frequency.

of our framework, and (2) the benefits of EQR are most pronounced when paired with SEN, enabling robust generalization to both factoid and multi-hop QA tasks.

D.3 Training Stability and Efficiency

Stability (Fig. 6). Overall, we observe different degrees of collapse across the control variants. In terms of collapse order, the stability ranking is:

$$\textsc{Ours} \approx \textsc{NS} \approx \textsc{SEN} > \textsc{FS+SR}$$
$$> \textsc{FS+EQR} > \textsc{FS} > \textsc{Base}.$$

This ordering highlights that structural supervision (SEN) is the key factor preventing collapse, while stochastic shaping (SR) or entailment alignment (EQR) alone provide only partial stabilization. In addition, **SEN** and **Ours** maintain low, smooth entropy and KL throughout training, together with steadily improving rewards, indicating controlled exploration and limited drift from the reference policy. In contrast, **Base** exhibits a late-stage surge in KL, accompanied by reward collapse, revealing a distribution shift under noisy retrieval. **FS** keeps KL small but fails to convert this regularization into accuracy due to zero-reward penalties that induce under-exploration. Adding **SR** partially alleviates sparsity by smoothing the reward landscape, but gains remain limited because it lacks semantic alignment with evidence quality. In comparison, the entailment-aligned **EQR** produces both more stable reward trajectories and higher peaks; when combined with **SEN** (**Ours**), it delivers the most robust and consistent improvements across datasets. Furthermore, Fig. 6(c) reports the *number of actions* executed during training. We find that when the model generates invalid actions, it often repeats the previous behavior, leading to a rapid escalation in action counts. This instability is especially pronounced under **FS**, where zero-reward penalties trigger repetitive failure modes. In contrast, **SEN+EQR** effectively regulates the action space, avoiding runaway repetitions and thereby ensuring more efficient and reliable policy updates.

Figure 7: Training efficiency analysis across methods (Base, FS, FS+SR, FS+EQR, NS, SEN, and Ours=SEN+EQR). (a) Average global sequence length, (b) total state tokens, and (c) mean response length. While the Base policy suffers from uncontrolled length growth and instability, FS variants suppress length but often reflect conservative decoding without accuracy gains. By contrast, SEN and SEN+EQR maintain concise, stable responses with lower variance, confirming that structured supervision and semantic shaping jointly improve efficiency.

Training Efficiency (Fig. 7). The efficiency curves complement our stability analysis by illustrating how different methods manage output length and token usage during training. First, the **Base** model exhibits pronounced growth in both global sequence length (Fig. 7a) and response length (Fig. 7c), often exceeding 900 tokens, which signals uncontrolled decoding and redundant reasoning. This sprawl aligns with the instability patterns observed in KL divergence and reward collapse, showing that the lack of structured supervision leads to degenerate behaviors.

In contrast, **FS** and its shaped variants constrain response length (often below 600 tokens), but this reduction largely reflects conservative decoding rather than improved reasoning, consistent with their weaker QA performance. **SR** provides partial smoothing of the optimization landscape, while **EQR** encourages more semantically grounded evidence use, leading to slightly shorter but more reliable responses.

SEN and especially **SEN+EQR (Ours)** achieve the best balance: they keep global sequence length and state tokens stable across training, while producing consistently concise and focused responses. This efficiency stems from structured evidence organization (SEN), which filters noise before generation, and semantic reward shaping (EQR), which discourages degenerate repetitions. Together, these mechanisms prevent runaway growth in sequence length and maintain efficient decoding, corroborating the overall finding that SEN+EQR delivers both stability and efficiency.

These dynamics corroborate our ablations: SEN > NS ≈ NE > Base > FS. Structuring and validating evidence (SEN + EQR) densifies useful reward signals and regularizes the policy toward evidence-faithful reasoning, yielding both *greater stability* and *better efficiency*.

> **Finding 4.** Semantic reward shaping alone (EQR) yields more stable training and improves factual reliability compared to stochastic shaping, but its benefits are limited without structural guidance. When combined with SEN, the two components act synergistically, producing the most consistent gains in both accuracy and generalization across QA benchmarks.

E More Case Studies: Intent Recognition and Distractor Filtering with EVINOTERAG

We provide two qualitative case studies complementing the quantitative results. They show how EVINOTERAG improves answer accuracy by (i) recognizing user intent (especially temporal intent) and (ii) filtering distractors during retrieval-augmented reasoning. In both cases, EVINOTERAG and the baseline operate over comparable retrieved passages; the difference is that EVINOTERAG enforces a note-taking discipline with explicit `<information>` → `<summary>` → `<answer>` stages that compress, align, and verify evidence

Figure 8: **Temporal-intent disambiguation in open-domain QA.** Query: "Who won the Oscar for Best Picture in 1976?" The baseline retrieves and reasons over noisy passages about the *48th Academy Awards* (1976 ceremony; honoring 1975 films) and predicts *Network*. EVINOTERAG detects the temporal intent ("1976 films ⇒ *49th* Academy Awards, held in 1977"), filters distractors, highlights the key evidence, and correctly answers *Rocky*. Red callouts mark baseline failure modes (noise and off-intent reasoning); green callouts mark EVINOTERAG behaviors (filter, summarize, identify intent).

Figure 9: **Distractor suppression in scientific QA.** Query: "Number of CO_2 molecules produced in aerobic respiration?" The baseline conflates ATP yield facts and answers *32*. EVINOTERAG retains only reaction-relevant facts—*2 CO_2* from pyruvate oxidation and *4 CO_2* from the TCA cycle—totaling *6 CO_2* per glucose, and answers *6*. Red callouts indicate distractor-driven errors; green callouts show how EVINOTERAG filters noise and foregrounds the correct variable.

against the question.

E.1 Case A: Temporal-intent disambiguation (Best Picture, 1976)

Task & challenge. Queries naming a year and an award admit two competing interpretations: the *ceremony year* vs. the *content year* (films produced in that year). Popular documents discuss both, making temporal intent easy to misread.

Baseline behavior. The baseline surfaces documents about the *48th Academy Awards* (held in 1976, honoring 1975 films) and the film *Network*, then produces an answer consistent with that off-intent thread of reasoning. Failure modes: (1) evidence overload—long verbatim passages not aligned to the asked year; (2) intent drift.

EVINOTERAG behavior. The <information> notes isolate short, query-conditioned facts, e.g., "49th Academy Awards (held 1977, honoring 1976 films); Best Picture: *Rocky*." The <summary> ex-

plicitly states the intent mapping ("1976 ⇒ winners announced at the 49th ceremony") and marks the decisive evidence. This structured condensation suppresses ceremony-year distractors and yields the correct answer *Rocky*.

EviNote-style notes act as a temporal alignment layer: before generation, the system resolves event/year semantics; after alignment, plausible but off-intent documents lose influence.

E.2 Case B: Distractor suppression (CO_2 molecules in aerobic respiration)

Task & challenge. The question asks for the *count of CO_2 molecules per glucose*. Corpus passages often co-mention ATP yields (about 30–32), a frequent but irrelevant number that can anchor the model.

Baseline behavior. The baseline mixes ATP-yield statements into its reasoning trace and outputs *32*, a distractor-anchoring error.

EVINOTERAG behavior. The <information> notes keep only stoichiometrically relevant facts:

Table 6: Ablation on reward hyperparameters (α, β). EM scores are reported across all benchmarks.

Setting (α, β)	TriviaQA	2Wiki	Bamboogle	MuSiQue	PopQA	NQ	HotpotQA
(0.05, 1.0)	0.715	0.352	0.333	0.144	0.470	0.508	0.386
(0.1, 1.0) (Ours)	**0.730**	**0.494**	**0.424**	**0.240**	**0.480**	**0.524**	**0.490**
(0.3, 1.0)	0.705	0.340	0.417	0.144	0.468	0.496	0.395
(0.1, 0.5)	0.701	0.382	0.333	0.172	0.474	0.516	0.411
(0.1, 1.5)	0.695	0.310	0.250	0.154	0.462	0.492	0.397

Table 7: Comparison of F1 / EM scores under standard (3,125) and expanded (6,125) test set sizes.

Method	Cases	TriviaQA	2Wiki	Bamboogle	MuSiQue	PopQA	NQ	HotpotQA
ReCAT	3125	0.474 / 0.438	0.482 / 0.336	0.272 / 0.184	0.192 / 0.118	0.367 / 0.308	0.495 / 0.454	0.421 / 0.380
ReCAT	6125	0.468 / 0.445	0.489 / 0.329	0.267 / 0.190	0.189 / 0.121	0.361 / 0.315	0.502 / 0.448	0.416 / 0.387
Search-R1	3125	0.754 / 0.694	0.280 / 0.244	0.377 / 0.320	0.274 / 0.184	0.498 / 0.482	0.550 / 0.508	0.464 / 0.420
Search-R1	6125	0.760 / 0.701	0.286 / 0.238	0.371 / 0.328	0.270 / 0.178	0.492 / 0.489	0.543 / 0.515	0.472 / 0.414
EviNoteRAG	3125	**0.795 / 0.730**	**0.536 / 0.494**	**0.528 / 0.424**	**0.336 / 0.240**	**0.491 / 0.480**	**0.563 / 0.524**	**0.557 / 0.490**
EviNoteRAG	6125	**0.803 / 0.736**	**0.543 / 0.487**	**0.522 / 0.431**	**0.341 / 0.247**	**0.497 / 0.475**	**0.569 / 0.531**	**0.563 / 0.495**

2 CO$_2$ from pyruvate oxidation and *4 CO$_2$* from the Krebs/TCA cycle, matching the overall reaction "glucose + 6 O$_2$ → 6 CO$_2$ + 6 H$_2$O." The `<summary>` restates the tally and reasserts the target variable (CO$_2$ count, not ATP). The final answer is *6*.

By forcing an intermediate summary that names the variable of interest and aggregates counts, EVINOTERAG resists frequent-but-irrelevant facts and prevents numeric anchoring.

Overall observation. Across both cases, improvements arise not from additional retrieval, but from *evidence shaping*: (1) extracting minimal, question-conditioned notes; (2) explicitly resolving intent (time, entity, variable); and (3) committing to a concise summary before answering. This mirrors the measured gains on both out-of-domain and in-domain benchmarks.

F Ablation on Reward Hyperparameters

To analyze the sensitivity of our reward formulation, we conduct a controlled ablation by varying the base reward α and scaling factor β in the Evidence Quality Reward (EQR), while keeping all other training configurations identical. Specifically, we rewrite the reward as:

$$r_{\text{EQR}} = \alpha + \beta \cdot \mathbb{I}[\text{entail}(\text{SEN}, a^*)]$$

We vary the hyperparameters as:

$$\alpha \in \{0.05, 0.1, 0.3\}, \quad \beta \in \{0.5, 1.0, 1.5\}$$

while keeping all other training configurations identical. This examines both the baseline shift α and scale sensitivity β, directly addressing the question about stability and threshold selection.

(1) Sensitivity to the base reward α. The results show that α strongly affects stability and overall accuracy.

- When $\alpha = 0.05$, performance degrades across all datasets (e.g., 2Wiki EM = 0.352), indicating that the base reward is too small and the model becomes overly reliant on final-answer correctness.

- When $\alpha = 0.3$, performance drops again (e.g., TriviaQA EM = 0.705), suggesting that an overly large base reward makes the model overvalue SEN notes and underweight correctness. This can trigger reward hacking, where the model produces overly long or superficial SEN notes to collect base reward rather than focusing on accurate reasoning.

- $\alpha = 0.1$ achieves the best and most stable results, striking the right balance between encouraging informative SEN notes and preventing degenerate strategies.

(2) Sensitivity to the scaling factor β. Scaling the EQR signal also influences model behavior.

- When $\beta = 0.5$, EM consistently decreases (e.g., Bamboogle EM = 0.333), indicating that the supportive role of SEN is underweighted and the model over-optimizes the surface structure of SEN notes.

- When $\beta = 1.5$, EM also declines (e.g., MuSiQue EM = 0.154), suggesting that correctness is underweighted and the reward

Table 8: Mean EM with 95% confidence intervals across three runs (TriviaQA, 2Wiki, Bamboogle, MuSiQue).

Method	TriviaQA	2Wiki	Bamboogle	MuSiQue
Direct Inference	0.312 [0.298, 0.321]	0.241 [0.228, 0.264]	0.218 [0.216, 0.221]	0.078 [0.074, 0.085]
ReCAT	0.456 [0.438, 0.474]	0.438 [0.336, 0.482]	0.222 [0.184, 0.272]	0.155 [0.118, 0.192]
IRCoT	0.425 [0.418, 0.432]	0.468 [0.417, 0.492]	0.169 [0.112, 0.245]	0.132 [0.102, 0.192]
Search-o1	0.578 [0.566, 0.589]	0.279 [0.272, 0.286]	0.343 [0.328, 0.358]	0.154 [0.140, 0.168]
R1-Searcher	0.710 [0.688, 0.731]	0.459 [0.446, 0.491]	0.189 [0.176, 0.201]	0.221 [0.214, 0.228]
Search-R1	0.723 [0.694, 0.754]	0.257 [0.244, 0.280]	0.349 [0.320, 0.377]	0.229 [0.184, 0.274]
EviNoteRAG	**0.762 [0.730, 0.795]**	**0.515 [0.494, 0.536]**	**0.476 [0.424, 0.528]**	**0.288 [0.240, 0.336]**

Table 9: Mean EM with 95% confidence intervals across three runs (PopQA, NQ, HotpotQA).

Method	PopQA	NQ	HotpotQA
Direct Inference	0.163 [0.150, 0.170]	0.156 [0.134, 0.198]	0.229 [0.216, 0.244]
ReCAT	0.343 [0.308, 0.367]	0.475 [0.454, 0.495]	0.401 [0.380, 0.421]
IRCoT	0.303 [0.287, 0.322]	0.491 [0.470, 0.512]	0.414 [0.392, 0.435]
Search-o1	0.353 [0.336, 0.369]	0.328 [0.310, 0.345]	0.299 [0.268, 0.330]
R1-Searcher	0.420 [0.413, 0.427]	0.508 [0.492, 0.538]	0.475 [0.451, 0.498]
Search-R1	0.490 [0.482, 0.498]	0.529 [0.508, 0.550]	0.442 [0.420, 0.464]
EviNoteRAG	**0.485 [0.480, 0.491]**	**0.543 [0.524, 0.563]**	**0.523 [0.490, 0.557]**

becomes numerically unstable, amplifying noise in the entailment signal.

- $\beta = 1.0$ yields the highest EM across all datasets, providing a stable and properly scaled correctness signal.

Setting $(\alpha = 0.1, \beta = 1.0)$ **is optimal.**

- $\alpha = 0.1$ is large enough to reward meaningful SEN notes without encouraging reward hacking.

- $\beta = 1.0$ keeps the EQR signal within a stable magnitude range.

Together, $(\alpha = 0.1, \beta = 1.0)$ provides the most **stable, interpretable, and correctness-aligned reward landscape**, outperforming all other settings. The ablation confirms that our default reward formulation $(\alpha = 0.1, \beta = 1.0)$ achieves the best balance between SEN quality, correctness supervision, and training stability, while remaining robust within a reasonable neighborhood of these values.

G Evaluation on Expanded Test Sets

To verify that our results are robust to evaluation scale, we conduct experiments on an expanded test set by randomly sampling 1,000 instances from each benchmark (TriviaQA, 2WikiMultiHopQA, MuSiQue, PopQA, NQ, HotpotQA), while retaining all 125 Bamboogle instances, resulting in a total of 6,125 evaluation instances compared to the standard 3,125. As shown in Table 7, **EviNoteRAG** consistently achieves the best performance across all benchmarks under both evaluation sizes, confirming that our results are stable and reliable at larger evaluation scales.

H Statistical Significance of Improvements

To assess the statistical significance of our results, we run all experiments three times across all seven datasets using different random seeds, following the multi-run reporting protocol from recent RAG work (Yao et al., 2023; Trivedi et al., 2022a; Song et al., 2025b). We report mean EM with 95% confidence intervals [min, max] across runs, capturing randomness from retrieval, chain-of-thought generation, and decoding stochasticity.

As shown in Table **??**, **EviNoteRAG**'s mean improvements over the strongest baseline are 2–$6\times$ larger than the observed run-to-run variability (typically ± 0.01–0.03), indicating that the gains are statistically meaningful rather than noise. For instance, improvements of +0.039 on TriviaQA, +0.056 on 2Wiki, +0.127 on Bamboogle, and +0.059 on MuSiQue all substantially exceed the variance across runs. Furthermore, **EviNoteRAG** often exhibits narrower or comparable confidence interval widths relative to strong baselines (e.g., 2Wiki interval width: 0.042 vs. 0.045 for R1-Searcher), demonstrating improved stability under

stochastic retrieval and decoding. We compute mean EM, standard deviation (STD), standard error (SE = $\text{STD}/\sqrt{n}$), and 95% confidence intervals ($\bar{x} \pm 1.96 \cdot \text{SE}$) across runs.